Unified Rule Engine

Inference Control Meta-Learning

Nil Geisweiller SNETAthon Fall 2018

SingularityNET Foundation

Unified Rule Engine: reminder

The URE evolves Inference Trees

```
A A->B
-----(MP)
B

A->B B->C
-----(DED)
A A->C
-----(MP)
C

ForAll X P(X) U(P(X), A) A->B B->C
-----(DED)
A A->C
-----(MP)
C
```

- Leaves are premises
- Roots are conclusions


Inference Trees are constructed by composing Rules

forward: expand conclusion




Inference Trees are constructed by composing Rules

forward: expand conclusion



backward: expand premises



Inference Trees are Atomese Programs



```
(BindLink
 (VariableList
     (VariableNode "SA")
       (TypeNode "LambdaLink")
       (TypeNode "PredicateNode")
     (VariableNode "SB")
       (TypeNode "LambdaLink")
       (TypeNode "PredicateNode")
 (AndLink
   (ImplicationLink
     (VariableNode "SA")
     (VariableNode "SB")
   (EvaluationLink
     (ImplicationLink
       (VariableNode "$B")
   (EvaluationLink
     (GroundedPredicateNode "scm: true-enough")
 (ExecutionOutputLink
   (GroundedSchemaNode "scm: modus-ponens-formula")
     (VariableNode "SB")
     (VariableNode "SA")
     (ImplicationLink
       (VariableNode "$B")
```

Inference Trees are Atomese Programs

```
A A->B
----(MP)
```

```
(ExecutionOutputLink
  (GroundedSchemaNode "scm: modus-ponens-formula")
  (ListLink
        (VariableNode "$B")
        (VariableNode "$A")
        (ImplicationLink
            (VariableNode "$A")
            (VariableNode "$B")
        )
      )
    )
}
```

Inference Trees are Atomese Programs

```
A->C C->B
-----(DED)

A A->B
-----(MP)
```

```
(ExecutionOutputLink
  (GroundedSchemaNode "scm: modus-ponens-formula")
  (ListLink
    (VariableNode "$B")
    (VariableNode "$A")
    (ExecutionOutputLink
      (GroundedSchemaNode "scm: deduction-formula")
      (ListLink
        (ImplicationLink
          (VariableNode "$A")
          (VariableNode "$B")
        (ImplicationLink
          (VariableNode "$A")
          (VariableNode "$C")
        (ImplicationLink
          (VariableNode "$C")
          (VariableNode "$B")
```

Algorithm

- 1. Select an inference tree to expand
- 2. Select a node from that tree to expand
- 3. Select a rule to expand with
- 4. Expand the inference tree and place it back to the pool of inference trees. Repeat till termination.

Combinatorial Explosion

Inference Control

Delegate the hard decisions to a cognitive process

Cognitive Schematics:

Context & Action ⇒ Goal

Atomese:

Inference Control



Which rule to choose?

- 1. Modus Ponens
- 2. Universal Instantiation

Look for:

Inference Control

Examples of actual URE Cognitive Schematics

```
(ImplicationScopeLink (stv 0.45945946 0.04625)
     (VariableNode "ST")
     (VariableNode "SL")
     (TypedVariableLink
         (VariableNode "SB")
         (TypeNode "DontExecLink")
     (EvaluationLink
        (PredicateNode "URE:BC:preproof-of")
           (VariableNode "SA")
           (VariableNode *ST*)
     (ExecutionLink
        (SchemaNode "URE:BC:expand-and-BIT")
           (VariableNode *SA*)
           (VariableNode "SL")
         (VariableNode "$B")
```

```
(ImplicationScopeLink (sty 1 0.00625)
   (VariableList
      (VariableNode "ST")
      (TypedVariableLink
         (TypeNode "DontExecLink")
         (VariableNode "SB")
         (TypeNode "DontExecLink")
      (EvaluationLink
         (PredicateNode "URE:BC:preproof-of")
            (VariableNode "SA")
            (VariableNode "ST")
      (ExecutionLink
         (SchemaNode *URE:BC:expand-and-BIT*)
            (VariableNode "$A")
               (ConceptNode "a")
               (VariableNode "SX")
         (VariableNode "$B")
```

Inference Control Algorithm

Given:


- inference rules: $R_1, ..., R_n$
- control rules:
 - $R_1 \rightarrow \{ C_{1,1}, ..., C_{1,m_1} \}$
 - ..
 - $\bullet \ R_n \rightarrow \{\ C_{n,1},\,...,\,C_{n,m_n}\ \}$

Combine $C_{i,j}$ to select best R_i ?

Inference Control Algorithm

Selecting inference rule R_i :

- 1. Mixture model: $M_i = C_{i,1} \oplus \cdots \oplus C_{i,m_i}$ (Bayesian Model Averaging, Solomonoff Operator Induction).
- 2. Thomspon Sampling: $R_i = TS(M_1, ..., M_n)$



Inference Control Meta-Learning

How to get Control Rules?

Answer: Learning

Record all decisions the URE takes and learn from it


Currently: Pattern Mining

Inference Control Learning: URE Trace



Atomese:

Inference Control Learning: URE Trace



Inference Control Learning: URE

Call the URE with a Control Rule Template as target

```
(cog-bc icr-rb (QuoteLink
                 (ImplicationScopeLink
                        (VariableNode "$impl-vardecl")
                     (AndLink
                        (EvaluationLink
                           (PredicateNode "URE:BC:preproof-of")
                              (VariableNode "Spreproof-A-args")
                        (ExecutionLink
                           (SchemaNode "URE:BC:expand-and-BIT")
                              (VariableNode "Sexpand-inputs")
                           (UnquoteLink
                              (VariableNode "Sexpand-output")
                     (EvaluationLink
                        (PredicateNode "URE:BC:preproof-of")
                           (VariableNode "$preproof-B-args")
```

Inference Control Learning: URE

Call the URE with a Control Rule Template as target

```
(ImplicationScopeLink
      (VariableNode "$impl-vardecl")
   (AndLink
      (EvaluationLink
         (PredicateNode "URE:BC:preproof-of")
            (VariableNode "Spreproof-A-args")
      (ExecutionLink
         (SchemaNode "URE:BC:expand-and-BIT")
            (VariableNode "Sexpand-inputs")
         (UnquoteLink
            (VariableNode "Sexpand-output")
   (EvaluationLink
      (PredicateNode "URE:BC:preproof-of")
         (VariableNode "$preproof-B-args")
```

```
(ImplicationScopeLink (stv 0.45945946 0.04625)
      (VariableNode "ST")
      (TypedVariableLink
         (VariableNode "SA")
         (TypeNode "DontExecLink")
        (VariableNode "SB")
         (TypeNode "DontExecLink")
      (EvaluationLink
         (PredicateNode "URE:BC:preproof-of")
         (ListLink
            (VariableNode "$A")
            (VariableNode "ST")
         (SchemaNode *URE:BC:expand-and-BIT*)
            (VariableNode "SA")
            (VariableNode "SL")
         (VariableNode "SB")
```

Inference Control Learning: URE + Pattern Miner

Call the URE with a Control Rule Template as target + Pattern Miner

```
(ImplicationScopeLink
      (VariableNode "$impl-vardecl")
      (EvaluationLink
         (PredicateNode "URE:BC:preproof-of")
            (VariableNode "Spreproof-A-args")
      (ExecutionLink
         (SchemaNode "URE:BC:expand-and-BIT")
            (VariableNode "Sexpand-inputs")
         (UnquoteLink
            (VariableNode "Sexpand-output")
   (EvaluationLink
      (PredicateNode "URE:BC:preproof-of")
         (VariableNode "$preproof-B-args")
```

```
(ImplicationScopeLink (stv 1 0.00625)
         (VariableNode "SA")
         (TypeNode "DontExecLink")
         (TypeNode "DontExecLink")
         (PredicateNode "URE:BC:preproof-of")
            (VariableNode "$A")
            (VariableNode "ST")
      (ExecutionLink
         (SchemaNode *URE:BC:expand-and-BIT*)
            (VariableNode "SA")
            (InheritanceLink
               (ConceptNode "a")
               (VariableNode "SX")
         (VariableNode "SB")
```

Issues, forthcoming work

- Issues:
 - Pattern Miner (WIP), looking for challenges!
 - Too many control rules?
- Forthcoming:
 - Experimentations, looking for challenges!
 - Other learning methods, MOSES, etc
 - Integrate ECAN

Issues, forthcoming work

- Issues:
 - Pattern Miner (WIP), looking for challenges!
 - Too many control rules?
- Forthcoming:
 - Experimentations, looking for challenges!
 - Other learning methods, MOSES, etc
 - Integrate ECAN

Demo time...