



VAN DINH NGHIA

FPGA DESIGN INTERN

Phone: 035 924 1096
Email: dinhnghia22062005@gmail.com
Portfolio: fpga-portfolio
Address: Ho Chi Minh City, Vietnam

ABOUT ME

Electronics and Telecommunications Engineering student focused on FPGA design and AI hardware acceleration. Experienced in Verilog HDL, Xilinx Vivado, RTL verification, synthesis, timing analysis, INT8 quantization, AXI4-Lite integration, and board-level AI inference. Interested in building efficient, verifiable FPGA accelerators for edge AI systems.

EDUCATION

Ho Chi Minh City University of Technology and Education **Expected Graduation: 2027**

B.Eng. in Electronics and Telecommunications Engineering — GPA: 8.43/10 (3.50/4.00)

Specialization: Telecommunications and Integrated Circuit Design. Relevant coursework: Digital Logic Design, Verilog HDL, FPGA Design, Computer Architecture, Digital Signal Processing, and Embedded Systems.

TECHNICAL SKILLS

HDL	Verilog HDL, RTL Design, FSM, Pipelining, INT8 Quantization, Fixed-Point Requantization
FPGA Tools	Xilinx Vivado, Simulation, Synthesis, Implementation, Timing and Resource Analysis
Interfaces	UART, AXI4-Lite, Memory-Mapped I/O, PS-PL Integration
Programming	Embedded C, C/C++, Python, MATLAB, Linux/ARM64, Git
Platforms	Xilinx KV260, ZedBoard, Tang Nano

RESEARCH EXPERIENCE

INT8 1D-CNN AI Inference Accelerator on Xilinx KV260 **01/2026 – 08/2026**

FPGA/SoC AI Hardware Accelerator

- Deployed an end-to-end 5-class 1D-CNN inference pipeline, mapping convolution, ReLU, and max-pooling to integer-only INT8 FPGA logic while executing GAP/Dense classification on the ARM processor.
- Converted floating-point inference using per-layer scale/zero-point parameters and fixed-point requantization for efficient INT8 hardware execution.
- Designed the accelerator with 20 MAC lanes, 5 requantization units, 42 execution contexts, AXI4-Lite control, and configurable on-chip memories.
- Achieved bit-exact RTL validation: 10,240/10,240 outputs matched golden results across 8 samples; all predictions matched the TFLite model.
- Met 100 MHz timing with +0.701 ns WNS and 21,437-cycle inference latency; placed design used 17,530 LUTs (14.97%), 6,898 FFs (2.94%), and 0 DSP/BRAM.
- Integrated the accelerator with the KV260 PS through AXI4-Lite; developed a Linux ARM64 C application and achieved 98.31% board-level accuracy (14,756/15,009 samples correct).

FPGA Multiplier Architecture Optimization **10/2025 – 03/2026**

Student Scientific Research Project — Verilog RTL

- Designed, simulated, synthesized, and implemented nine signed 16-bit multipliers: DSP, array, shift-add, 2/8-stage pipeline, Booth radix-2/radix-4, and 2/8-core architectures.
- Achieved 100% pass rate across 114 functional test cases; deployed and verified selected designs on Xilinx KV260, ZedBoard, and Tang Nano boards through a 115200-baud UART link with automated C-based PASS/FAIL checking.
- Reached 725.16 MHz with the 8-stage pipeline versus 108.57 MHz for the array baseline (nearly 7× higher Fmax); Booth radix-4 reduced latency from 16 to 8 cycles.
- Demonstrated linear multi-core throughput scaling, with the 8-core architecture producing eight results per eight cycles (one result/cycle).

HONORS & ACTIVITIES

Teaching Assistant — Digital Design and Programming Laboratories

- Guided students in combinational/sequential logic, simulation, source-code debugging, and practical laboratory assignments.
- Assisted lecturers in preparing laboratory materials and supporting hands-on engineering sessions.

Principal Investigator — Student Scientific Research Project

- Led the project “Analysis and Experimental Evaluation of Algorithm Optimization Techniques on FPGA” from RTL development through multi-board validation and final technical reporting.

LANGUAGES

Vietnamese: Native **English:** Technical documentation, reading, and communication