

# Graph Mining

## SD212

### 4. PageRank

Thomas Bonald

2018 – 2019



# Motivation


How to identify the most “important” nodes in a graph, either globally or relatively to some other nodes?

Useful for:


- ▶ information retrieval
- ▶ content recommendation
- ▶ local clustering

We focus on PageRank metrics, originally proposed by Google's founders in 1999 to rank Web pages: popular pages are typically visited more frequently by a random Web surfer.


## Example




# PageRank




## Local ranking




# Personalized PageRank



## Directed graphs



# PageRank






# Outline

1. Random walk
2. PageRank
3. Personalized PageRank
4. Forward-Backward PageRank

# Notation

Consider a directed graph  $G = (V, E)$ :


- ▶  $V = \{1, \dots, n\}$
- ▶  $A$ , weighted adjacency matrix
- ▶  $w^+, w^-$ , vectors of out-weights and in-weights



# Random walk

In the **absence** of sinks:

- ▶  $P_{ij} = A_{ij}/w_i^+$ , probability of moving from  $i$  to  $j$
- ▶  $P = D_+^{-1}A$  with  $D_+ = \text{diag}(w^+)$
- ▶ A Markov chain  $X_0, X_1, X_2, \dots$  with transition matrix  $P$
- ▶ Probability distributions  $\pi_0, \pi_1, \pi_2, \dots$  with  $\pi_{t+1} = \pi_t P$



## Stationary distribution

If the graph is **strongly connected**, the unique solution to

$$\pi = \pi P$$

# Computation

Stationary distribution

**Input:**

$P$ , transition matrix

$N$ , number of iterations

**Do:**

$\pi \leftarrow \frac{1}{n}(1, \dots, 1)$

For  $t = 1, \dots, N$ ,  $\pi \leftarrow \pi P$

**Output:**


$\pi$ , (approximate) stationary distribution

Complexity:  $O(Nm)$  in time,  $O(n)$  in memory

# The case of undirected graphs

We have:

- ▶  $w = w^+ = w^-$
- ▶  $P_{ij} = A_{ij}/w_i$ , probability of moving from  $i$  to  $j$
- ▶  $P = D^{-1}A$  with  $D = \text{diag}(w)$



## Stationary distribution

If the graph is **connected**,

$$\pi \propto w$$

# Accounting for sinks

Several options:

1. (recursive) pruning
2. (forced) restart, e.g.,

$$P_{ij} = \begin{cases} \frac{A_{ij}}{w_i^+} & \text{if } w_i^+ > 0 \\ \frac{1}{n} & \text{otherwise} \end{cases}$$

3. wait, i.e.,

$$P_{ij} = \begin{cases} \frac{A_{ij}}{w_i^+} & \text{if } w_i^+ > 0 \\ \delta_{ij} & \text{otherwise} \end{cases}$$

# Traps

# Enforcing irreducibility

Random walks with restarts:

- ▶ Fix  $\alpha \in (0, 1)$
- ▶ Walk with probability  $\alpha$ , restart (e.g., to a random node) with probability  $1 - \alpha$
- ▶ An **irreducible** Markov chain with transition matrix:

$$P^{(\alpha)} = \alpha P + (1 - \alpha) \frac{\mathbf{1}\mathbf{1}^T}{n}$$

- ▶ The stationary distribution  $\pi^{(\alpha)}$  satisfies:

$$\pi^{(\alpha)} = \alpha \pi^{(\alpha)} P + (1 - \alpha) \frac{\mathbf{1}^T}{n}$$

This is the **PageRank** vector!



# Computation

## PageRank

### **Input:**

$P$ , transition matrix (with forced restarts)

$\alpha$ , damping factor

$N$ , number of iterations

### **Do:**


$$\pi \leftarrow \frac{1}{n}(1, \dots, 1)$$

$$\text{For } t = 1, \dots, N, \pi \leftarrow \alpha \pi P + (1 - \alpha) \frac{1}{n}(1, \dots, 1)$$

### **Output:**

$\pi$ , (approximate) PageRank vector

Example ( $\alpha = 0.85$ )



## Setting the damping factor

- ▶ The path length before restart (in the absence of sinks) has a **geometric distribution** with parameter  $1 - \alpha$
- ▶ Average path length:

$$\frac{\alpha}{1 - \alpha}$$

- ▶ For  $\alpha = 0.85$ , we get about 5.7, a typical distance between two nodes in real graphs (cf. the **small-world** property).

# Expression of the PageRank vector


## Proposition

$$\pi^{(\alpha)} = (1 - \alpha) \sum_{t=0}^{+\infty} \alpha^t \pi_t$$


# Outline

1. Random walk
2. PageRank
3. **Personalized PageRank**
4. Forward-Backward PageRank

# Personalization



# Personalization




# Personalized PageRank

- ▶ Restart distribution  $\mu$  on  $S \subset V$
- ▶ Restart from sinks:

$$P_{ij} = \begin{cases} \frac{A_{ij}}{w_i^+} & \text{if } w_i^+ > 0 \\ \mu_j & \text{otherwise} \end{cases}$$

- ▶ Damping:

$$P^{(\alpha)} = \alpha P + (1 - \alpha)1\mu$$





# Computation

## Personalized PageRank

### **Input:**

$P$ , transition matrix (with forced restarts)

$\mu$ , personalization row vector

$\alpha$ , damping factor

$N$ , number of iterations

### **Do:**

$\pi \leftarrow \mu$

For  $t = 1, \dots, N$ ,  $\pi \leftarrow \alpha \pi P + (1 - \alpha) \mu$

### **Output:**

$\pi$ , (approximate) PageRank vector

# Expression of the Personalized PageRank vector

## Proposition

In the absence of sinks,

$$\pi^{(\alpha)} = \sum_{s \in S} \mu_s \pi_s^{(\alpha)}$$


where  $\pi_s^{(\alpha)}$  is the Personalized PageRank vector associated with  $s$

# Outline

1. Random walk
2. PageRank
3. Personalized PageRank
4. **Forward-Backward PageRank**

# Motivation

- ▶ In many practical cases, two nodes having a large number of common **successors** (or **predecessors**) are closely related
- ▶ For instance, the articles “France” and “Germany” of Wikipedia for Schools have 38 common links:  
United States, United Kingdom, World War II, Latin, Japan, Italy, Spain, Russia, Time zone, Currency, ...




# Forward-backward random walk

In the **absence** of sources and sinks:

- ▶  $P_{ik}^+ = A_{ik}/w_i^+$ , probability of moving from  $i$  to  $k$  (original graph)
- ▶  $P_{kj}^- = A_{jk}/w_k^-$ , probability of moving from  $k$  to  $j$  (reverse graph)
- ▶ A Markov chain  $X_0, X_1, X_2, \dots$  with transition matrix  $P = P^+ P^-$ ,

$$P_{ij} = \sum_k \frac{A_{ik}}{w_i^+} \frac{A_{jk}}{w_k^-}$$



## Stationary distribution

If the Markov chain is irreducible,

$$\pi \propto w^+$$

# Computation

Assuming neither sinks nor sources:

Personalized Forward-Backward PageRank

**Input:**

$P^+$  and  $P^-$ , forward and backward transition matrices

$\mu$ , personalization row vector

$\alpha$ , damping factor

$N$ , number of iterations

**Do:**



$\pi \leftarrow \mu$

For  $t = 1, \dots, N$ ,  $\pi \leftarrow \pi P^+$ ,  $\pi \leftarrow \alpha \pi P^- + (1 - \alpha) \mu$

**Output:**

$\pi$ , (approximate) Forward-Backward PageRank vector

## Directed graphs as bipartite graphs



## Co-citation graph

- ▶ **Weighted, undirected** graph  $G^{\text{co}}$  associated with the directed graph  $G$
- ▶ Weighted adjacency matrix:

$$A_{ij}^{\text{co}} = \sum_{k \in V} \frac{A_{ik} A_{jk}}{w_k^-}$$

- ▶ Weight of node  $i$ :

$$w_i^{\text{co}} = \sum_{j \in V} A_{ij}^{\text{co}} = w_i^+$$

## Random walks

The **forward-backward** random walk in  $G$  corresponds to the **regular** random walk in  $G^{\text{co}}$ :

$$P = P^+ P^- = P^{\text{co}}$$



## Size of the co-citation graph

- ▶ Each node  $k$  of  $G$  forms a clique of  $d_k^-$  nodes in  $G^{\text{co}}$
- ▶ Number of edges in  $G^{\text{co}}$  possibly as large as:


$$\sum_{k \in V} (d_k^-)^2$$

May be **huge** for a power-law in-degree distribution!


- ▶ In comparison, the size of  $G$  is:

$$m = \sum_{k \in V} d_k^-$$

## Back to undirected graphs



## The case of bipartite graphs



# Summary

PageRank metrics:

- ▶ Useful to quantify the “importance” of nodes, relatively to other nodes (through **personalization**)
- ▶ **Fast** computation through matrix-vector multiplications using sparse matrices
- ▶ The **Forward-Backward** version for directed graphs, related to the corresponding co-citation graph

A **fundamental tool** for graph analysis!