

Decoding Reed-Muller and Polar Codes by Successive Factor Graph Permutations


Seyyed Ali Hashemi^a, Nghia Doan^a, Marco Mondelli^b,
Warren J. Gross^a

^aMcGill University, Canada

^bStanford University, USA

ISTC 2018
Hong Kong
December 4, 2018.

Motivation



- ▶ **Polar Codes:** adopted in **5G** eMBB control channel
 - ▶ Requires low-complexity decoders with good performance
- ▶ **Reed-Muller (RM) Codes:** very similar to polar codes

In this talk:

We propose a new low-complexity decoder for RM and polar codes with good performance!

RM and Polar Codes: Encoding

$$\mathcal{RM}(8, 4), \mathcal{P}(8, 4)$$

$$\mathbf{u}\mathbf{G}^{\otimes 3} = \mathbf{x}$$

RM and Polar Codes: Encoding

$$\mathcal{RM}(8, 4), \mathcal{P}(8, 4)$$

$$\mathbf{u}\mathbf{G}^{\otimes 3} = \mathbf{x}$$

$$\begin{bmatrix} u_0 \\ u_1 \\ u_2 \\ u_3 \\ u_4 \\ u_5 \\ u_6 \\ u_7 \end{bmatrix}^T \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \end{bmatrix}^T$$

RM and Polar Codes: Encoding

$$\mathcal{RM}(8, 4), \mathcal{P}(8, 4)$$

$$\mathbf{u}\mathbf{G}^{\otimes 3} = \mathbf{x}$$

$$\begin{bmatrix} 0 \\ 0 \\ 0 \\ u_3 \\ 0 \\ u_5 \\ u_6 \\ u_7 \end{bmatrix}^T \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \end{bmatrix}^T$$

RM and Polar Codes: Encoding

$$\mathcal{RM}(8, 4), \mathcal{P}(8, 4)$$

$$\mathbf{u}\mathbf{G}^{\otimes 3} = \mathbf{x}$$

$$\begin{bmatrix} 0 \\ 0 \\ 0 \\ u_3 \\ 0 \\ u_5 \\ u_6 \\ u_7 \end{bmatrix}^T \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \end{bmatrix}^T$$

RM rule:

Remove rows with lowest Hamming weights

RM and Polar Codes: Encoding

$$\mathcal{RM}(8, 4), \mathcal{P}(8, 4)$$


$$\mathbf{u}\mathbf{G}^{\otimes 3} = \mathbf{x}$$

$$\begin{bmatrix} 0 \\ 0 \\ 0 \\ u_3 \\ 0 \\ u_5 \\ u_6 \\ u_7 \end{bmatrix}^T \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix} = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \end{bmatrix}^T$$


Polar rule:

Remove rows with lowest reliabilities


RM and Polar Codes: Recursive Construction



RM and Polar Codes: Recursive Construction




RM and Polar Codes: Recursive Construction



RM and Polar Codes: Decoding

Successive-Cancellation (SC)



$$\alpha_{i,l} = f(\alpha_{i,l+1}, \alpha_{i+2^l,l+1})$$

$$\alpha_{i+2^l,l} = g(\alpha_{i,l+1}, \alpha_{i+2^l,l+1}, \beta_{i,l})$$

$$\beta_{i,l+1} = \beta_{i,l} \oplus \beta_{i+2^l,l}$$

$$\beta_{i+2^l,l+1} = \beta_{i+2^l,l}$$

RM vs Polar

- ▶ RM:
 - ▶ Minimizes error probability under MAP decoding
 - ▶ High complexity
 - ▶ Channel-independent
 - ▶ Low complexity
- ▶ Polar:
 - ▶ Minimizes error probability under SC decoding
 - ▶ Low complexity
 - ▶ Channel-dependent
 - ▶ High complexity


SC List (SCL) Decoding: Something in Between

- ▶ SCL instantiates multiple SC decoders
 - ▶ L codeword candidates survive to limit complexity
 - ▶ A CRC can help SCL find the correct candidate

$$\text{SC} \longleftrightarrow \text{SCL} \longleftrightarrow \text{MAP}$$




- ▶ Requires a large L to get close to MAP

Factor Graph Permutations




- ▶ $n = \log_2 N$ layers $\rightarrow n!$ factor graph permutations
- ▶ Decode over multiple factor graphs \rightarrow Pick the best one
 - ▶ High decoding complexity


Bit Index Permutations



Architecture



Permutations on Sub-Graphs



Total Number of Permutations

- ▶ By cyclic shift permutations at each layer:


$$\prod_{l=0}^{n-1} (n-l)^{(2^l)}$$

- ▶ Much larger than $n!$
- ▶ Quickly grows with n
 - ▶ 1658880 permutations for length 32
 - ▶ More than 1.9×10^{27} for length 128


Issue:

Decoding over all permutations is impossible!


Successive Permutations for SC




Successive Permutations for SC




Successive Permutations for SC




Successive Permutations for SC




Successive Permutations for SC




Successive Permutations for SC



Successive Permutations for SC



Successive Permutations for SC



Selection Criterion

- Reliability of a vector of LLR values α of length N :

$$\mathcal{R}(\alpha) = \sum_{i=0}^{N-1} |\alpha_i|$$

- A larger $\mathcal{R}(\alpha)$ indicates a more reliable LLR vector

Criterion:

Permutation with which the f function results in the most reliable LLR vector

$$P_{l+1} = \arg \max_{p_{l+1} \in \pi_{l+1}} \sum_{i=0}^{2^l-1} \left| f\left(\alpha_{p_{l+1}(i), l+1}, \alpha_{p_{l+1}(i+2^l), l+1}\right) \right|$$


Complexity Analysis

- ▶ Memory: Same as SC
- ▶ Parallel implementation:
 - ▶ Computational complexity: Roughly n times SC
 - ▶ Latency: Same as SC
- ▶ Serial implementation:
 - ▶ Computational complexity: Same as SC
 - ▶ Latency: Roughly n times SC


Performance Analysis

- ▶ RM Codes:
 - ▶ Permutations do not change the info/frozen bit pattern
 - ▶ Code is unchanged but better bits are decoded earlier
 - ▶ Significant improvement is expected
- ▶ Polar Codes:
 - ▶ Permutations may result in a different info/frozen bit pattern not optimized for the channel
 - ▶ We only apply SP on RM sub-codes of polar codes
 - ▶ The info/frozen bit pattern remains unchanged

Results: $\mathcal{RM}(128, 64)$



Results: $\mathcal{P}(128, 64)$



Conclusion

- ▶ We derived total number of permutations for RM and polar codes
- ▶ We proposed successive factor graph permutations for RM and polar codes to find the suitable permutations on the fly
- ▶ At $\text{FER} = 10^{-4}$:
 - ▶ SP gains up to 0.5 dB over SC and SCL of $\mathcal{RM}(128, 64)$
 - ▶ SP gains up to 0.1 dB over SC and SCL of $\mathcal{P}(128, 64)$
- ▶ SCL(16) with SP is within 0.05 dB of the MAP lower bound of $\mathcal{RM}(128, 64)$

Thank you!