Provable Cross-Modal Transfer of Hierarchical Concept Structure in CLIP

Nghia Nguyen **Tianjiao Ding** **Lachlan Ewen MacDonald** **René Vidal**
University of Pennsylvania
nghianhh@seas.upenn.edu

Abstract

Contrastive vision-language models such as CLIP are trained to align images and text, not to represent taxonomies. Yet empirical studies show that CLIP embeddings exhibit hierarchical structure aligned with the hierarchy of semantic concepts. A theoretical characterization of why such hierarchy emerges from a non-hierarchical objective remains open. In this paper, we formalize this phenomenon as *Hierarchical Angular Separation* ($\mathcal{HAS}$), a geometric property whereby each non-leaf concept embedding is more similar to its descendants than to off-branch concepts. Empirically, we show that $\mathcal{HAS}$ holds approximately in raw images and randomly initialized CLIP image embeddings, while in text embeddings it holds approximately only after contrastive learning. To theoretically explain this asymmetry, we analyze an *unconstrained features model* in which the image embeddings are fixed and only the text embeddings are trained. At the global minimizer, the text-side $\mathcal{HAS}$ violation percentage at each anchor is at most the image-side percentage of off-branch nodes that violate or nearly violate $\mathcal{HAS}$. The key mechanism is the hierarchical co-occurrence structure of image-text pairs, which biases text embeddings toward root-centered image prototypes. For a linear contrastive loss, we derive a closed-form solution that makes this mechanism explicit. We extend the analysis to the InfoNCE loss and establish analogous guarantees under sufficient regularization. Synthetic experiments validate the theory and show that $\mathcal{HAS}$ is transferred even beyond the regimes covered by our analysis.

1 Introduction

Given a collection of image-text pairs, Contrastive Language-Image Pretraining (CLIP) learns text and image encoders by aligning paired embeddings and separating unpaired ones. The learned representations enable strong transfer across tasks such as image classification, visual question answering, and multimodal retrieval [1, 2, 3].

One possible explanation for this empirical success is that CLIP embeddings implicitly encode rich semantic and geometric structure. In particular, embeddings of semantic concepts have been shown to organize into linear subspaces [4, 5] and to reflect hierarchical relationships aligned with noun hierarchies in WordNet [6, 7, 8, 9]. For example, a `cat` and a `dog` are both `mammals`, and a `mammal` and a `bird` are both `animals`. Recent work has attempted to characterize such hierarchical structure through geometric conditions, for example via orthogonality relations between embeddings of semantic concepts [10, 11]. However, these conditions fail to capture a fundamental property of semantic hierarchies: a concept should be more similar to its descendants than to concepts from unrelated branches [12, 13, 14, 7]. Empirical studies further suggest that CLIP image embeddings encode hierarchy through separated subtrees [9], but this evidence does not quantify the extent of such structure across models and scales, nor does it provide a principled explanation of its origin.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).




Figure 1: How contrastive learning transfers hierarchy from image to text embeddings. *Top-left:* the image prototypes are arranged so that each concept is closer to its descendants than to concepts in other subtrees. The blue and red dotted lines indicate the boundary of the `dog` and `cat` subtrees, respectively. *Top-right:* each image of a labrador is a noisy copy of the labrador prototype, and its caption may pair with any concept on the path from the root to that leaf, so an image can be captioned `labrador`, `dog` or `animal`. *Bottom-left:* the pairing also means that the caption `dog` pairs with images of `dog` or any of its descendants, so the average of these images approaches the mean of the `dog` subtree. *Bottom-right:* contrastive learning pulls each text embedding toward the corresponding subtree mean, so the text embeddings inherit the arrangement of the image prototypes.

A natural hypothesis is that hierarchical structure is learned through contrastive learning: if one modality encodes semantic relationships, alignment should transfer them to the other. Our experiments show that the two modalities differ. Approximate hierarchical structure is already present in raw-pixel image data and remains after passing through a randomly initialized encoder, so randomly initialized CLIP image embeddings exhibit it before any training has occurred. In contrast, raw text consists of discrete symbols whose semantic relationships are not reflected in their randomly initialized embeddings; any geometric structure must therefore be learned through training.

These observations raise a central question: *how does contrastive learning transform and propagate hierarchical structure across modalities?* In particular, why does alignment amplify and transfer structure from image to text embeddings, rather than suppress it? While the origin of hierarchical structure in image data remains unclear, our focus in this paper is on understanding how contrastive learning transfers such structure to other modalities once it is present in one modality.

To study this phenomenon, we formalize hierarchical structure as a geometric property called *Hierarchical Angular Separation* ($\mathcal{HAS}$): given a taxonomy of concepts, an ancestor has higher cosine similarity to each of its descendants than to any off-branch concept. We quantify violations from this ordering using the $\mathcal{HAS}$ violation percentage ($\mathcal{HAS}$-Viol): the percentage of off-branch concepts that violate the $\mathcal{HAS}$ condition. Here, off-branch concepts exclude both the concept's subtree and its ancestors. Across CLIP models of varying scales and variants, image embeddings already have low $\mathcal{HAS}$-Viol at random initialization, whereas text embeddings have high $\mathcal{HAS}$-Viol that becomes low only after contrastive learning.

These empirical observations motivate the need for a theoretical analysis. However, analyzing contrastive learning with deep networks is challenging due to the non-convexity of the optimization problem. To address this, we adopt the *Unconstrained Features Model* (UFM) [15, 16, 17], which abstracts away the deep network by optimizing directly over last-layer features. Within this framework, we show that hierarchical structure in image embeddings transfers to text embeddings under

contrastive learning. The key mechanism, illustrated in Figure 1, is the hierarchical co-occurrence structure of image-text pairs: although each image corresponds to a specific concept (e.g., `dog`), its paired text may correspond to that concept or to one of its hypernyms (e.g., `mammal`, `animal`). This structure induces a bias that propagates hierarchical relationships from image to text embeddings.

Paper Contributions. In this paper, we empirically characterize hierarchical structure in CLIP embeddings and theoretically explain how contrastive learning transfers this structure from image to text embeddings:

1. **Empirical characterization of hierarchical structure.** Using WordNet, we show that text embeddings have high $\mathcal{HAS}$-Viol at random initialization and low $\mathcal{HAS}$-Viol after pretraining, while image embeddings already have low $\mathcal{HAS}$-Viol at initialization. This reveals a systematic asymmetry: hierarchy is learned in text but partly present in image embeddings prior to training.

2. **Hierarchical co-occurrence transfers image geometry to text at the linear-loss optimum.** Under the UFM with hierarchical co-occurrence, we derive a closed-form minimizer of a linear contrastive loss [18], showing that optimal text embeddings align with root-centered image prototypes. The text-side $\mathcal{HAS}$-Viol at each anchor is at most the image-side percentage of off-branch nodes that violate or nearly violate $\mathcal{HAS}$.

3. **Extension to InfoNCE and robustness beyond theory.** We establish an analogous bound on text $\mathcal{HAS}$-Viol for the InfoNCE loss used in CLIP under sufficient regularization. Furthermore, we empirically show that transfer occurs even when the regularization condition does not hold.

2 Related Work

Unconstrained Features Model. The UFM was originally used to explain Neural Collapse [19]. Subsequent work showed that the Simplex Equiangular Tight Frame is the unique optimal geometry for cross-entropy with weight decay [15, 16, 17] and for supervised contrastive losses [20, 21]. However, these analyses focus on classification with mutually exclusive classes. We extend the UFM to *contrastive learning with hierarchically structured* image-text pairings and characterize the geometry that emerges at global minimizers.

Geometry of Representations in Foundation Models. Recent work has documented geometric structure in pretrained embedding spaces. One line of work shows that semantic concepts form linear or compositional subspaces [22, 23], exhibit hierarchical organization [10, 9, 7], or give rise to phenomena such as the modality gap [24, 25]. Relatedly, Zhao and Thrampoulidis [26] infer a semantic hierarchy from sign patterns in a learned concept basis for next-token prediction. We instead study a given concept tree and explain how $\mathcal{HAS}$ transfers from image to text embeddings during contrastive pretraining.

Learning Theory with Hierarchy Models. Another line of work studies how hierarchical latent structure shapes learning and generation, including hierarchical concept learning in language models [27, 28], emergent properties under hierarchical contrastive learning [29], and phase transitions in diffusion models signaling an underlying latent hierarchy [30, 31]. Closest to our work, several papers [30, 32] analyze the Random Hierarchy Model, a *supervised* setting in which the sample for a class is generated by a hierarchical composition of latent features. However, these works study compositional hierarchies of features, while we instead study hierarchies over object categories.

Hierarchical Representation Learning. Traditionally, hierarchical information is explicitly encoded into models through specialized architectures or objectives. A popular approach is to embed hierarchies in hyperbolic space, exploiting its exponential volume growth [33, 12, 13, 14, 34]. In contrast, we analyze when implicit hierarchical structure transfers in self-supervised learning.

Contrastive Learning Theory. Theoretical analyses have connected contrastive objectives to spectral decompositions of augmentation graphs [35, 36], and have shown that contrastive objectives can invert the data-generating process [37]. A separate line of work provides theoretical and empirical evidence that self-supervised representations cluster at multiple hierarchical levels [38, 39]. By contrast, we analyze how the contrastive loss interacts with hierarchical co-occurrence structures.

3 Hierarchical Angular Separation and Its Modality Asymmetry in CLIP

Pretraining creates a modality asymmetry in CLIP's hierarchical structure: text embeddings acquire the property that each concept is closer to its descendants than to concepts in other branches after training, whereas image embeddings exhibit it approximately at initialization and it strengthens after training. We formalize this ordering as hierarchical angular separation ($\mathcal{HAS}$) in Section 3.1 and measure it across CLIP variants in Section 3.2.

3.1 Definition of Hierarchical Angular Separation

Datasets of natural images and language often contain semantic concepts that can be organized into hierarchies. For example, a `cat` and a `dog` are both `mammals`, and a `mammal` and a `bird` are both `animals`. Below, we introduce the notation used to describe such hierarchies.

Hierarchy. Let $\mathcal{T} = (V, E)$ be a rooted tree with $|V| = M$ nodes, leaf set $V_{\text{leaf}} \subseteq V$, and root node $\text{root} \in V$. Each $u \in V$ corresponds to a *synset* (e.g., `mammal`). For $u \in V$, let $\text{Anc}(u)$ denote its ancestors, $\text{Desc}(u)$ its descendants, and $\text{Sub}(u) := \{u\} \cup \text{Desc}(u)$ the subtree rooted at u.

Concept Embeddings. For each node $k \in V$, we associate a concept embedding $\boldsymbol{c}_k \in \mathbb{R}^d$, and write the embedding of the hierarchy $\mathcal{T}$ as the collection $\{\boldsymbol{c}_k : k \in V\}$. In practice, concept embeddings are obtained using text and image encoders in two common ways: (1) *instance aggregation* [22, 40, 41], which averages all image embeddings $\boldsymbol{z}_j \in \mathbb{R}^d$ corresponding to a node $u \in V$ (e.g., averaging over all `dog` images to estimate the concept embedding for `dog`); (2) *direct concept encoding* [1, 23], which encodes the concept string (e.g., `image of a dog`) to obtain a text embedding.

Hierarchical Angular Separation. We define $\mathcal{HAS}$ as a Euclidean notion of hierarchy based on angular separation, applicable to either image or text embeddings. To make this precise, for non-zero $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^d$, we define $\cos(\boldsymbol{x}, \boldsymbol{y}) := \boldsymbol{x}^\top \boldsymbol{y}/(\|\boldsymbol{x}\|\|\boldsymbol{y}\|)$.

Definition 3.1 (Hierarchical Angular Separation ($\mathcal{HAS}$))**.** The concept embeddings $\{\boldsymbol{c}_k\}_{k \in V}$ of hierarchy $\mathcal{T}$ (obtained by either instance aggregation or direct concept encoding) satisfy $\mathcal{HAS}$ if for every non-leaf node $u \in V$, every descendant $v \in \text{Desc}(u)$, and every node outside the subtree and not an ancestor, $w \notin \text{Sub}(u) \cup \text{Anc}(u)$, we have

$$\cos(\boldsymbol{c}_u, \boldsymbol{c}_v) > \cos(\boldsymbol{c}_u, \boldsymbol{c}_w). \tag{1}$$

Nguyen et al. [9] use instance aggregation to estimate concept embeddings, and claim to have observed subtree separation in pretrained CLIP image embeddings without specifying how.

$\mathcal{HAS}$ differs from prior hierarchy-learning objectives that prescribe hierarchical structure during training. Hyperbolic entailment cones [12, 13, 14] and Poincaré embeddings [33] optimize non-Euclidean embeddings with losses designed to enforce hierarchical relations. In contrast, and as we compare in detail in Appendix A, we define $\mathcal{HAS}$ descriptively rather than prescriptively: Eq. (1) is a Euclidean cosine inequality measured in the learned CLIP space, where the observed angles determine the descendant cone around $\boldsymbol{c}_u$ rather than the training objective imposing it. To quantify how far a set of embeddings is from satisfying Definition 3.1, we use the following per-node metric.


Definition 3.2 ($\mathcal{HAS}$ Violation Percentage)**.** For a non-root non-leaf node u, we first define the *descendant threshold*, the minimum cosine similarity between u and its least similar descendant, as $c_u := \min_{v \in \text{Desc}(u)} \cos(\boldsymbol{c}_u, \boldsymbol{c}_v)$. The *$\mathcal{HAS}$ violation percentage* at u is then the percentage of the set of off-branch (not in the subtree and not an ancestor) nodes $\{w\}$ that has a larger cosine similarity with u than c_u

$$\mathcal{HAS}\text{-Viol}(u) := \frac{|\{w \notin \text{Sub}(u) \cup \text{Anc}(u) : \cos(\boldsymbol{c}_u, \boldsymbol{c}_w) \geq c_u\}|}{|\{w \notin \text{Sub}(u) \cup \text{Anc}(u)\}|} \times 100\%. \tag{2}$$

$\mathcal{HAS}\text{-Viol}(u) = 0$ for every non-root non-leaf $u \in V$ if and only if $\mathcal{HAS}$ (Definition 3.1) holds. We are now ready to measure $\mathcal{HAS}$ in CLIP embeddings.

3.2 Hierarchical Angular Separation in CLIP embeddings

We measure $\mathcal{HAS}$-Viol on the ImageNet-1K training split [42] and the WordNet noun hierarchy [6]. We evaluate both the *text* and *image* embeddings of two pretrained CLIP ViT-L/14



(a) Randomly initialized. (b) OpenAI CLIP. (c) OpenCLIP.

(d) Randomly initialized. (e) OpenAI CLIP. (f) OpenCLIP.

Figure 2: Distribution of $\mathcal{HAS}$-Viol(u) over the non-root, non-leaf nodes, grouped by depth on ViT-L/14 CLIP embeddings. *Top: text* embeddings show that $\mathcal{HAS}$ is acquired through pretraining. *Bottom: image* embeddings show approximate $\mathcal{HAS}$ at random initialization and stronger $\mathcal{HAS}$ after pretraining.

checkpoints (OpenAI CLIP [1] and OpenCLIP [43] trained on DataComp-1B [44]) and a randomly initialized ViT-L/14. To reduce the effect of outliers, we replace the descendant threshold $c_u = \min_{v \in \mathrm{Desc}(u)} \cos(\boldsymbol{c}_u, \boldsymbol{c}_v)$ by its 95th percentile over $\mathrm{Desc}(u)$. Corresponding results on ViT-B/32, ViT-B/16, ViT-L/14@336px, SigLIP2 [45], MetaCLIP2 [46], and on the CUB-200 taxonomy [47], are deferred to Appendix J.1.

Text embeddings: $\mathcal{HAS}$ is acquired through pretraining. In Figure 2 (top), both pretrained text models have low violation percentages across depths, whereas the randomly initialized text model has substantially larger violations across the tree. Hence, for text concept embeddings, $\mathcal{HAS}$ is a *learned* property of contrastive pretraining. Additional results estimating concept embeddings by instance aggregation reach the same conclusion (Appendix J.1).

Image embeddings: $\mathcal{HAS}$ is present in raw pixels and strengthened by pretraining. In Figure 2 (bottom), pretrained image embeddings have violation percentages concentrated near zero across depths. The randomly initialized ViT-L/14 has substantially lower violations than randomly initialized text embeddings, although its violations remain non-negligible.

Instance aggregation can spuriously lower $\mathcal{HAS}$-Viol because an ancestor mean reuses the instances in its descendant means. We remove this overlap by estimating each node from two disjoint image splits, then compare each representation with a hierarchy-shuffled null that preserves its geometry and aggregation procedure. We also include i.i.d. Gaussian vectors as a structure-free baseline, and give the full protocol in Appendix J.1.1.

Table 1: Mean image-side $\mathcal{HAS}$-Viol. Each representation is paired with its own hierarchy-shuffled null. Null values report mean $\pm$ standard deviation over five hierarchy shuffles.

Representation	$\mathcal{HAS}$ violation (%) $\downarrow$	$\mathcal{HAS}$ violation shuffled (%) $\downarrow$
Raw pixels	26.51	50.95 ± 0.29
Randomly initialized ViT-L/14	27.88 ± 0.24	56.80 ± 0.42
Pretrained OpenAI CLIP ViT-L/14	2.95	32.93 ± 0.48
i.i.d. Gaussian vectors ($d = 768$)	76.02 ± 0.97	76.33 ± 0.93




Figure 3: Overview of the $\mathcal{HAS}$ transfer results. Under assumptions on the data model, both losses decompose the text embeddings into prototypes plus perturbations. Bounding the perturbations relative to the prototype norms gives a bound on text-side violations in terms of image-side margins.

In Table 1, raw pixels and randomly initialized image embeddings separate from their own hierarchy-shuffled nulls, whereas Gaussian vectors do not. Approximate image-side $\mathcal{HAS}$ therefore comes from the image data, remains after a randomly initialized encoder, and strengthens with contrastive pretraining, while text-side $\mathcal{HAS}$ is acquired only through pretraining.

4 Provable Transfer of Hierarchical Angular Separation from Image to Text Embeddings

Motivated by the observed empirical asymmetry, we study how contrastive learning transfers pre-existing image geometry to text. We use an Unconstrained Features Model (UFM) in which the image embeddings are fixed and only the text embeddings are learned. Under hierarchical co-occurrence, each text concept aggregates images from its descendant leaves, and contrastive learning therefore aligns the text embedding with the corresponding root-centered image prototype. We first derive this mechanism in closed form for a linear contrastive loss (Section 4.2), then show that regularized symmetric InfoNCE inherits it under common assumptions (Section 4.3). We summarize the overall flow of these theoretical results in Figure 3. We also show that the transfer is robust to weaker regularization than required by theory (Section 4.4).

4.1 Setup and Notation

Hierarchical Image Prototypes and Samples. Continuing the notation of Section 3.1, we consider a tree $\mathcal{T} = (V, E)$ together with an embedding $\{\boldsymbol{\mu}_k\}_{k \in V}$ of its nodes, as illustrated in Figure 1 (top-left). Each vector $\boldsymbol{\mu}_k \in \mathbb{R}^d$, for $k \in V$, is called an *image prototype*.

Our transfer analysis compares the image-side margin of each prototype triplet with the perturbations introduced by sampling and optimization. Because image embedding instances deviate from their prototypes, we model the resulting finite-sample error as follows. We sample exactly c images per leaf, for a total of $N = c|V_{\text{leaf}}|$ images.

Assumption 4.1 (Prototype variation model)**.** The image embeddings $\{\boldsymbol{z}_j\}_{j=1}^N$ are sampled as $\boldsymbol{z}_j = \boldsymbol{\mu}_{y_j} + \boldsymbol{\varepsilon}_j$, where $y_j \in V_{\text{leaf}}$ is the leaf node associated with image j and $\{\boldsymbol{\varepsilon}_j\}_{j=1}^N$ are independent, zero-mean, σ-sub-Gaussian random vectors in $\mathbb{R}^d$.

Hierarchical captions determine each concept's positive images. For each node $u \in V$, let $\text{Path}(u)$ denote the root-to-u path. Each image $j \in [N]$ is paired with a fixed observed caption node $t_j \in \text{Path}(y_j)$ (Figure 1, top-right). For example, an image from the leaf `labrador` may be captioned as `labrador`, `dog`, `mammal`, or `animal`.

For each node $k \in V$, define its empirical positive set and caption count by

$$\mathcal{P}_k := \{j \in [N] : t_j = k\}, \qquad N_k := |\mathcal{P}_k|. \tag{3}$$

As shown in Figure 1 (bottom-left), the positive set of a non-leaf concept such as `dog` can pool images across descendant leaves such as `labrador` and `corgi`.

Hierarchical co-occurrence distinguishes our UFM from non-hierarchical UFM analyses. Prior UFM work for cross-entropy or supervised contrastive learning assumes mutually exclusive class labels and analyzes the resulting Simplex ETF geometry [15, 16, 20, 21]. Here, each image still has one caption, but that caption may be any concept along $\mathrm{Path}(y_j)$ rather than only the mutually exclusive leaf y_j. The resulting dependencies across nodes allow each optimum to depend on subtree prototype averages, making $\mathcal{HAS}$, rather than a flat simplex, the relevant geometry.

The UFM optimizes only the text embeddings. Following the Unconstrained Features Model (UFM) approach [16], we fix the observed image embeddings $\boldsymbol{Z} \in \mathbb{R}^{d\times N}$ and caption labels $\{t_j\}_{j=1}^N$, and optimize the text concept embeddings $\boldsymbol{A} \in \mathbb{R}^{d\times M}$. For a regularization coefficient $\lambda > 0$, the objective is

$$\min_{\boldsymbol{A}} \ \mathcal{L}_{\mathrm{contr}}(\boldsymbol{A}; \boldsymbol{Z}) \ + \ \frac{\lambda}{2}\|\boldsymbol{A}\|_F^2. \tag{4}$$

Remark 4.2 (Relation to CLIP's normalized formulation). In practice, CLIP normalizes embeddings to the unit sphere, which bounds logits and guarantees finite minimizers. We instead use unnormalized embeddings with L_2 regularization, following the standard UFM approach [16, 20, 21]. This substitution is motivated by tractability: normalization introduces non-convexity, which makes analysis more complex. The regularization coefficient λ prevents unbounded growth of embedding norms as a normalization operator does.

Next, we study the geometry of $\boldsymbol{A}^*$ at the global minimizers of the contrastive objective (4). In Section 4.2, we first analyze when the contrastive loss is a linear contrastive loss, which admits an exact minimizer in closed form. We use the closed-form minimizer to identify which image-side triplet orderings are transferred and thereby bound the text-side $\mathcal{HAS}$ violation percentage.

4.2 Linear Contrastive Loss Analysis

To get a closed-form analysis of $\mathcal{HAS}$ transfer in a contrastive learning setting, we first consider the linear contrastive loss of Ji et al. [18]. The symmetric linear contrastive loss $\mathcal{L}^{\mathrm{lin}}(\boldsymbol{A})$ is

$$-\frac{1}{2}\sum_{j=1}^{N}\left[\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j - \frac{1}{M-1}\sum_{\substack{k\in[M]\\k\neq t_j}} \boldsymbol{a}_k^\top \boldsymbol{z}_j + \boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j - \frac{1}{N-1}\sum_{\substack{j'\in[N]\\j'\neq j}} \boldsymbol{a}_{t_j}^\top \boldsymbol{z}_{j'}\right] + \frac{\lambda}{2}\|\boldsymbol{A}\|_F^2. \tag{5}$$


Solving the first-order condition for Eq. (5) gives a unique minimizer. For each node $k \in V$ with $N_k > 0$, define the empirical mean of the images captioned k as $\bar{\boldsymbol{z}}_k := \frac{1}{N_k}\sum_{j\in\mathcal{P}_k} \boldsymbol{z}_j$, and define the global empirical image mean $\bar{\boldsymbol{z}} := \frac{1}{N}\sum_{j=1}^N \boldsymbol{z}_j$. The optimal text embedding for k is a *weighted combination* of these two means (Proposition D.1 and Corollary D.2 in Appendix D). The transfer proof therefore reduces to identifying the prototype component of each $\bar{\boldsymbol{z}}_k$. We first make this identification exact with two simplifying assumptions: leaf-uniform coverage makes each mean uniform over descendant leaves, and prototype consistency identifies that average with the corresponding node prototype.

Assumption 4.3 (Leaf-uniform caption coverage)**.** Every non-root node $k \in V\backslash\{\mathrm{root}\}$ has $N_k > 0$, and its positive set $\mathcal{P}_k$ contains the same number of images from each leaf in $\mathrm{Sub}(k) \cap V_{\mathrm{leaf}}$.

Assumption 4.4 (Prototype consistency)**.** For every node $k \in V$, the average of the prototypes over leaves in $\mathrm{Sub}(k) \cap V_{\mathrm{leaf}}$ is exactly $\boldsymbol{\mu}_k$.

Using Assumptions 4.1, 4.3, and 4.4, we can write $\bar{\boldsymbol{z}}_k = \boldsymbol{\mu}_k + \bar{\boldsymbol{\varepsilon}}_k$ and $\bar{\boldsymbol{z}} = \boldsymbol{\mu}_{\mathrm{root}} + \bar{\boldsymbol{\varepsilon}}$, where $\bar{\boldsymbol{\varepsilon}}_k := \frac{1}{N_k}\sum_{j\in\mathcal{P}_k} \boldsymbol{\varepsilon}_j$ and the global noise average is $\bar{\boldsymbol{\varepsilon}} := \frac{1}{N}\sum_{j=1}^N \boldsymbol{\varepsilon}_j$, yielding the following prototype decomposition for the minimizer. The proof is deferred to Appendix D.

Corollary 4.5 (Prototype Decomposition for the Linear Contrastive Loss)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold. For each non-root k, define* $\xi_k^{\mathrm{lin}} := \frac{N\left(\frac{1}{2(M-1)}+\frac{N_k}{2(N-1)}\right)}{N_k\left(1+\frac{1}{2(M-1)}+\frac{1}{2(N-1)}\right)}$. *Then*



(a) Fixed image prototypes.

(b) Optimal text geometry.

Figure 4: Optimal text geometry for a stylized hierarchy. Each colored triangle is a regular simplex of child concepts, with its parent (diamond) at the centroid. The optimal text directions in (b) satisfy $\boldsymbol{a}_k^* \propto \boldsymbol{\mu}_k - \xi_k \boldsymbol{\mu}_{\text{root}}$, where ξ_k is the root-centering coefficient. Each child simplex remains centered at its parent, and $\mathcal{HAS}$ is preserved.

every such k satisfies

$$\boldsymbol{a}_k^{\text{lin},*} = \frac{N_k}{\lambda}\left(1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)}\right)\left(\boldsymbol{\mu}_k + \bar{\varepsilon}_k - \xi_k^{\text{lin}}\left(\boldsymbol{\mu}_{\text{root}} + \bar{\varepsilon}\right)\right). \tag{6}$$

In Corollary 4.5, $\boldsymbol{a}_k^{\text{lin},*}$ is a positive rescaling of $\boldsymbol{\mu}_k$ plus a perturbation (Figure 1, bottom-right). The perturbation consists of the deterministic root-centering term $-\xi_k^{\text{lin}}\boldsymbol{\mu}_{\text{root}}$, which shifts each prototype along the root direction (Figure 4), and the stochastic variation term $\bar{\varepsilon}_k - \xi_k^{\text{lin}}\bar{\varepsilon}$, which is bounded with high probability by Assumption 4.1. Positive rescaling preserves cosine similarity, so transfer depends on how much the perturbation changes each prototype triplet margin. We therefore bound the perturbation relative to the prototype norms and identify which triplet orderings remain intact. Let $\rho_{\min} := \min_{k \in V \setminus \{\text{root}\}} \|\boldsymbol{\mu}_k\|$ denote the minimum non-root prototype norm. With ξ_k^{lin} from Corollary 4.5, define $\xi_{\max}^{\text{lin}} := \max_{k \in V \setminus \{\text{root}\}} |\xi_k^{\text{lin}}|$ and $\delta_{\text{root}} := \xi_{\max}^{\text{lin}} \|\boldsymbol{\mu}_{\text{root}}\|$, the largest root-centering perturbation norm.

To compare violations across modalities, for a non-root non-leaf anchor $u \in V$, let $\mathcal{HAS}\text{-Viol}^{\text{txt}}(u)$ denote $\mathcal{HAS}$-Viol evaluated on the optimal text embeddings. For non-zero non-root image prototypes and $\tau \geq 0$, let $\mathcal{HAS}\text{-Viol}_\tau^{\text{img}}(u)$ denote the same metric evaluated on the prototypes with their threshold c_u lowered to $c_u - \tau$. Equivalently, $\mathcal{HAS}\text{-Viol}_\tau^{\text{img}}(u)$ is the percentage of off-branch nodes at u whose worst-case triplet margin on the image prototypes is at most τ.

Theorem 4.6 ($\mathcal{HAS}$ Transfer for the Linear Contrastive Loss)**.** *Suppose Assumption 4.1 (sub-Gaussian prototype variation), Assumption 4.3 (leaf-uniform caption coverage), and Assumption 4.4 (prototype consistency) hold, and suppose $\rho_{\min} > 0$. Let $N_{\min} := \min_{k \in V \setminus \{\text{root}\}} N_k$ be the minimum non-root caption count. There exists a universal constant $C > 0$ such that the following holds for every $\epsilon \in (0,1)$. Define the combined error term*

$$D_\epsilon := \delta_{\text{root}} + C\sigma\left(\sqrt{\frac{d + \log(M-1) + \log(4/\epsilon)}{N_{\min}}} + \xi_{\max}^{\text{lin}}\sqrt{\frac{d + \log(4/\epsilon)}{N}}\right). \tag{7}$$

If $D_\epsilon < \rho_{\min}/4$, then, with probability at least $1-\epsilon$, every non-root non-leaf anchor node u satisfies

$$\mathcal{HAS}\text{-Viol}^{\text{txt}}(u) \leq \mathcal{HAS}\text{-Viol}_{\tau_\epsilon}^{\text{img}}(u), \qquad \tau_\epsilon := \frac{8D_\epsilon}{\rho_{\min}}. \tag{8}$$

We defer the proof to Appendix G. Under the assumptions, every image-side triplet with margin greater than τ_ϵ remains correctly ordered on the text side. Only triplets with image-side margin at most τ_ϵ can violate text-side $\mathcal{HAS}$. We now turn to the InfoNCE loss [48].

4.3 InfoNCE Loss Analysis

In the same fixed-image setup, we test whether the transfer mechanism exposed by the linear loss persists under regularized symmetric InfoNCE:

$$\mathcal{L}(\boldsymbol{A}) := \sum_{j=1}^{N} \frac{1}{2} \left(-\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j + \log \sum_{k=1}^{M} e^{\boldsymbol{a}_k^\top \boldsymbol{z}_j} - \boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j + \log \sum_{j'=1}^{N} e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_{j'}} \right) + \frac{\lambda}{2} \|\boldsymbol{A}\|_F^2. \tag{9}$$

The objective is λ-strongly convex, so its unique minimizer $\boldsymbol{A}^*$ satisfies the softmax fixed-point equation (Proposition E.2). Because this equation has no closed form, we analyze $\boldsymbol{A}^*$ as $\lambda \to \infty$.

Proposition 4.7 (Large-Regularization Expansion)**.** *As $\lambda \to \infty$, for any k with $N_k > 0$,*

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda} \bar{\boldsymbol{z}}_k - \frac{1}{\lambda} \left(\frac{N}{2M} + \frac{N_k}{2} \right) \bar{\boldsymbol{z}} + O(\lambda^{-2}). \tag{10}$$

As λ grows, $\boldsymbol{A}^*$ shrinks and the softmax weights approach uniform. The fixed-point equation then yields Eq. (10). We defer the proof to Appendix E. Substituting $\bar{\boldsymbol{z}}_k = \boldsymbol{\mu}_k + \bar{\boldsymbol{\varepsilon}}_k$ and $\bar{\boldsymbol{z}} = \boldsymbol{\mu}_{\mathrm{root}} + \bar{\boldsymbol{\varepsilon}}$ into Eq. (10) gives the same prototype decomposition as the linear-loss minimizer.

Corollary 4.8 (Prototype Decomposition for the Large-Regularization Expansion)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold. For each non-root k, define $\xi_k^{\mathrm{nce}} := \left(\frac{N}{2M} + \frac{N_k}{2}\right)/N_k$. Then every such k satisfies*

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda} \left(\boldsymbol{\mu}_k + \bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\mathrm{nce}} \left(\boldsymbol{\mu}_{\mathrm{root}} + \bar{\boldsymbol{\varepsilon}} \right) \right) + O(\lambda^{-2}). \tag{11}$$

We defer the proof to Appendix E.4. The leading term has the same form as Corollary 4.5 with ξ_k^{nce} in place of ξ_k^{lin}, so the same margin argument gives the following $\mathcal{HAS}$ transfer guarantee for InfoNCE. For $\epsilon \in (0,1)$, define $D_\epsilon^{\mathrm{nce}}$ by recomputing the error term in Eq. (7) with ξ_k^{nce} in place of ξ_k^{lin} throughout, including in $\xi_{\max}^{\mathrm{lin}}$ and δ_{root}, and with $\log(8/\epsilon)$ in place of $\log(4/\epsilon)$.


Theorem 4.9 ($\mathcal{HAS}$ Transfer for InfoNCE)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold and $\rho_{\min} > 0$, and fix $\epsilon \in (0,1)$. If $0 < D_\epsilon^{\mathrm{nce}} < \rho_{\min}/8$, then there is a deterministic threshold $\lambda_0(\epsilon) > 0$ such that, for every $\lambda \geq \lambda_0(\epsilon)$, with probability at least $1-\epsilon$, every non-root non-leaf anchor node u satisfies Eq.* (8) *with τ_ϵ replaced by $\tau_\epsilon^{\mathrm{nce}} := 16 D_\epsilon^{\mathrm{nce}}/\rho_{\min}$.*

Thus, regularized InfoNCE inherits the linear-loss transfer mechanism, and we defer the proof to Appendix H. The large-λ condition is required for the analysis but not for the phenomenon: in Section 4.4 we show that $\mathcal{HAS}$ transfer persists under substantially weaker regularization.

Remark 4.10 (Connection to the modality gap). CLIP embeds images and text in separated regions of the shared space, which is known as the *modality gap* [25]. Our analysis offers an explanation to this phenomenon. In Eqs. (6) and (11), each optimal text embedding subtracts a multiple of the global image mean $\boldsymbol{\mu}_{\mathrm{root}}$. Instead of aligning with the global image mean, the text embeddings subtract it, so the two modalities remain separated at the text optimum.

Extensions beyond the basic transfer model. In Appendix L, we quantify how caption imbalance, inexact prototype consistency, and ancestor omission affect the linear-loss transfer guarantee. Caption imbalance and prototype inconsistency add deterministic error terms, while independent ancestor omissions reduce the effective sample size and introduce random imbalance. In Appendix K, we analyze one exact image-side update after the text-side update under the linear loss, and show that averaging within caption groups reduces stochastic variation for image embeddings.

Limitations. Our analysis explains how pre-existing image geometry transfers to text under a simplified model of contrastive learning. For tractability, we fix the image embeddings and replace CLIP's unit-norm constraints with quadratic regularization (Remark 4.2). The transfer guarantees require perturbations small relative to the prototype norms; for InfoNCE, we additionally require sufficiently large λ. In Section 4.4, we observe transfer under weaker regularization, but a theoretical guarantee in that regime remains open. Beyond these fixed-image guarantees, our analysis of one image-side update does not explain the full joint training dynamics or how approximate $\mathcal{HAS}$ becomes exact. Explaining why hierarchical geometry is already present in image data also remains outside the scope of our transfer analysis. We discuss further limitations in Appendix B.



(a) Convergence at $\lambda = 10^{-3}$.

(b) Regularization sweep over $\lambda \in [10^{-5}, 10^{2}]$.

Figure 5: Synthetic validation of $\mathcal{HAS}$ transfer at small regularization with the InfoNCE loss. *(a)* L-BFGS convergence at $\lambda = 10^{-3}$: the InfoNCE loss without the regularization term (left axis) and the text-side $\mathcal{HAS}$-Viol (right axis) against the training step. *(b)* The text-side $\mathcal{HAS}$-Viol (left axis) converges much earlier than the prototype alignment (right axis) does.

4.4 Synthetic Validation at Small Regularization

Theorem 4.9 certifies transfer only for $\lambda \geq \lambda_0(\epsilon)$, so we test the predictions of Section 4.3 outside that regime. On a synthetic image-prototype hierarchy, we minimize the InfoNCE objective (9) with L-BFGS over a sweep of $\lambda \in [10^{-5}, 10^{2}]$, and we report $\mathcal{HAS}$-Viol at the minimizer found by L-BFGS together with *prototype alignment*, the minimum over non-root k of $\cos(\boldsymbol{a}_k^*, \boldsymbol{\mu}_k)$. We present the full setup in Appendix J.3. Transfer occurs at values of λ for which Theorem 4.9 gives no guarantee: violations vanish at the minimizer found by L-BFGS before prototype alignment saturates (Figure 5). The sufficient perturbation bound for $\mathcal{HAS}$ transfer from Theorem 4.9 is also conservative: the root norm does not satisfy this bound, yet $\mathcal{HAS}$-Viol still converges to zero. Violations also remain small across different values of the root norm and variation strength (Appendix J.3). By contrast, permuting hypernym–image pairings while preserving caption frequencies substantially increases text violations under both the linear and InfoNCE loss (Appendix J.5).

5 Conclusion

In this paper, we studied how concept embeddings learned without explicit hierarchical supervision encode the underlying concept hierarchy. We measured this property with *Hierarchical Angular Separation* ($\mathcal{HAS}$): for each non-leaf concept, a node has a higher cosine similarity to its descendant concepts than to concepts outside its subtree. We first showed empirically that $\mathcal{HAS}$ holds approximately in CLIP text embeddings only after pretraining, while it is already approximately present in image embeddings at random initialization. To explain this phenomenon, we analyzed an Unconstrained Features Model in which we freeze the image embeddings and train the text embeddings using either a linear contrastive loss or the InfoNCE loss with sufficient regularization. Under hierarchical co-occurrence, we proved that the text-side $\mathcal{HAS}$ violation percentage at each anchor is bounded by the image-side percentage of off-branch nodes whose worst-case triplet margin is at most a perturbation threshold. Numerical experiments on synthetic concept hierarchies confirm these predictions and indicate that $\mathcal{HAS}$ is induced even at weaker regularization levels than theoretically required. Our results suggest that multimodal contrastive learning transfers structure already present in image geometry to text embeddings. Whether this mechanism extends beyond hierarchy to sparse, low-rank, or compositional structure, and why image data exhibit hierarchy in the first place, remain open questions.

Acknowledgments and Disclosure of Funding

The authors thank Ryan Chan, Ryan Pilgrim, Uday Kiran Tadipatri, Buyun Liang, Kyle Poe, Leandro Palma, Yi Ma, and anonymous reviewers for their helpful comments and suggestions. This work was funded by Simons Foundation grant 814201, NSF grant 2031985, and University of Pennsylvania startup funds.

References

[1] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

[2] Aditya Chattopadhyay, Kwan Ho Ryan Chan, and René Vidal. Bootstrapping variational information pursuit with large language and vision models for interpretable image classification. In *ICLR*, 2024.

[3] Weizhe Lin, Jinghong Chen, Jingbiao Mei, Alexandru Coca, and Bill Byrne. Fine-grained late-interaction multi-modal retrieval for retrieval augmented visual question answering. In *NeurIPS*, 2023.

[4] Usha Bhalla, Alex Oesterling, Suraj Srinivas, Flavio P. Calmon, and Himabindu Lakkaraju. Interpreting CLIP with Sparse Linear Concept Embeddings (SpLiCE). In *NeurIPS*, 2024.

[5] Yossi Gandelsman, Alexei A. Efros, and Jacob Steinhardt. Interpreting CLIP's Image Representation via Text-Based Decomposition. In *ICLR*, 2024.

[6] George A. Miller. WordNet: A Lexical Database for English. *Communications of the ACM*, 1995.

[7] Morris Alper and Hadar Averbuch-Elor. Emergent Visual-Semantic Hierarchies in Image-Text Representations. In *ECCV*, 2024.

[8] Vladimir Zaigrajew, Hubert Baniecki, and Przemyslaw Biecek. Interpreting CLIP with Hierarchical Sparse Autoencoders. In *ICML*, 2025.

[9] Nghia Nguyen, Tianjiao Ding, and René Vidal. Hierarchical Concept Embedding & Pursuit for Interpretable Image Classification. In *CVPR*, 2026.

[10] Kiho Park, Yo Joong Choe, Yibo Jiang, and Victor Veitch. The Geometry of Categorical and Hierarchical Concepts in Large Language Models. In *ICLR*, 2025.

[11] Yibo Jiang, Bryon Aragam, and Victor Veitch. Uncovering Meanings of Embeddings via Partial Orthogonality. In *NeurIPS*, 2023.

[12] Octavian-Eugen Ganea, Gary Bécigneul, and Thomas Hofmann. Hyperbolic Entailment Cones for Learning Hierarchical Embeddings. In *ICML*, 2018.

[13] Karan Desai, Maximilian Nickel, Tanmay Rajpurohit, Justin Johnson, and Shanmukha Ramakrishna Vedantam. Hyperbolic Image-text Representations. In *ICML*, 2023.

[14] Avik Pal, Max van Spengler, Guido Maria D'Amely di Melendugno, Alessandro Flaborea, Fabio Galasso, and Pascal Mettes. Compositional Entailment Learning for Hyperbolic Vision-Language Models. In *ICLR*, 2025.

[15] Zhihui Zhu, Tianyu Ding, Jinxin Zhou, Xiao Li, Chong You, Jeremias Sulam, and Qing Qu. A Geometric Analysis of Neural Collapse with Unconstrained Features. In *NeurIPS*, 2021.

[16] Dustin G. Mixon, Hans Parshall, and Jianzong Pi. Neural Collapse with Unconstrained Features. *Sampling Theory, Signal Processing, and Data Analysis*, 2022.

[17] Wenlong Ji, Yiping Lu, Yiliang Zhang, Zhun Deng, and Weijie J Su. An Unconstrained Layer-Peeled Perspective on Neural Collapse. In *ICLR*, 2022.

[18] Wenlong Ji, Zhun Deng, Ryumei Nakada, James Zou, and Linjun Zhang. The Power of Contrast for Feature Learning: A Theoretical Analysis. *Journal of Machine Learning Research*, 2023.

[19] Vardan Papyan, X. Y. Han, and David L. Donoho. Prevalence of Neural Collapse during the terminal phase of Deep Learning training. *Proceedings of the National Academy of Sciences*, 2020.

[20] Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Dissecting Supervised Contrastive Learning. In *ICML*, 2021.

[21] Tina Behnia and Christos Thrampoulidis. Supervised Contrastive Representation Learning: Landscape Analysis with Unconstrained Features. In *ISIT*, 2024.

[22] Kiho Park, Yo Joong Choe, and Victor Veitch. The Linear Representation Hypothesis and the Geometry of Large Language Models. In *ICML*, 2024.

[23] Matthew Trager, Pramuditha Perera, Luca Zancato, Alessandro Achille, Parminder Bhatia, and Stefano Soatto. Linear Spaces of Meanings: Compositional Structures in Vision-Language Models. In *ICCV*, 2023.

[24] Meir Yossef Levi and Guy Gilboa. The Double-Ellipsoid Geometry of CLIP. In *ICML*, 2025.

[25] Victor Weixin Liang, Yuhui Zhang, Yongchan Kwon, Serena Yeung, and James Y Zou. Mind the Gap: Understanding the Modality Gap in Multi-modal Contrastive Representation Learning. In *NeurIPS*, 2022.

[26] Yize Zhao and Christos Thrampoulidis. Geometry of Semantics in Next-Token Prediction: How Optimization Implicitly Organizes Linguistic Representations. In *arXiv preprint arXiv:2505.08348*, 2025.

[27] Zeyuan Allen-Zhu and Yuanzhi Li. Physics of Language Models: Part 1, Learning Hierarchical Language Structures. *TMLR*, 2025.

[28] Lingjing Kong, Guangyi Chen, Biwei Huang, Eric P. Xing, Yuejie Chi, and Kun Zhang. Learning Discrete Concepts in Latent Hierarchical Models. In *NeurIPS*, 2024.

[29] Jianyang Gu, Samuel Stevens, Elizabeth G. Campolongo, Matthew J. Thompson, Net Zhang, Jiaman Wu, Andrei Kopanev, Zheda Mai, Alexander E. White, James Balhoff, Wasila Dahdul, Daniel Rubenstein, Hilmar Lapp, Tanya Berger-Wolf, Wei-Lun Chao, and Yu Su. BioCLIP 2: Emergent Properties from Scaling Hierarchical Contrastive Learning. In *NeurIPS*, 2025.

[30] Antonio Sclocchi, Alessandro Favero, and Matthieu Wyart. A phase transition in diffusion models reveals the hierarchical nature of data. *PNAS*, 2025.

[31] Antonio Sclocchi, Alessandro Favero, Noam Itzhak Levi, and Matthieu Wyart. Probing the latent hierarchical structure of data via diffusion models. *Journal of Statistical Mechanics: Theory and Experiment*, 2025.

[32] Francesco Cagnetta, Leonardo Petrini, Umberto M. Tomasini, Alessandro Favero, and Matthieu Wyart. How Deep Neural Networks Learn Compositional Data: The Random Hierarchy Model. *Physical Review X*, 2024.

[33] Maximilian Nickel and Douwe Kiela. Poincaré Embeddings for Learning Hierarchical Representations. In *NeurIPS*, 2017.

[34] Ziwei Wang, Sameera Ramasinghe, Chenchen Xu, Julien Monteil, Loris Bazzani, and Thalaiyasingam Ajanthan. Learning Visual Hierarchies in Hyperbolic Space for Image Retrieval. In *ICCV*, 2025.

[35] Jeff Z. HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable Guarantees for Self-Supervised Deep Learning with Spectral Contrastive Loss. In *NeurIPS*, 2021.

[36] Ryumei Nakada, Halil Ibrahim Gulluk, Zhun Deng, Wenlong Ji, James Zou, and Linjun Zhang. Understanding Multimodal Contrastive Learning and Incorporating Unpaired Data. In *AISTATS*, 2023.

[37] Roland S. Zimmermann, Yash Sharma, Steffen Schneider, Matthias Bethge, and Wieland Brendel. Contrastive Learning Inverts the Data Generating Process. In *ICML*, 2021.

[38] Yuandong Tian, Lantao Yu, Xinlei Chen, and Surya Ganguli. Understanding Self-Supervised Learning with Dual Deep Networks. In *arXiv preprint arXiv:2010.00578*, 2020.

[39] Ido Ben-Shaul, Ravid Shwartz-Ziv, Tomer Galanti, Shai Dekel, and Yann LeCun. Reverse Engineering Self-Supervised Learning. In *NeurIPS*, 2023.

[40] Tom Wollschläger, Jannes Elstner, Simon Geisler, Vincent Cohen-Addad, Stephan Günnemann, and Johannes Gasteiger. The Geometry of Refusal in Large Language Models: Concept Cones and Representational Independence. In *ICML*, 2025.

[41] Jinqi Luo, Tianjiao Ding, Kwan Ho Ryan Chan, Darshan Thaker, Aditya Chattopadhyay, Chris Callison-Burch, and René Vidal. PaCE: Parsimonious Concept Engineering for Large Language Models. In *NeurIPS*, 2024.

[42] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[43] Mehdi Cherti, Romain Beaumont, Ross Wightman, Mitchell Wortsman, Gabriel Ilharco, Cade Gordon, Christoph Schuhmann, Ludwig Schmidt, and Jenia Jitsev. Reproducible scaling laws for contrastive language-image learning. In *CVPR*, 2023.

[44] Samir Yitzhak Gadre, Gabriel Ilharco, Alex Fang, Jonathan Hayase, Georgios Smyrnis, Thao Nguyen, Ryan Marten, Mitchell Wortsman, Dhruba Ghosh, Jieyu Zhang, Eyal Orgad, Rahim Entezari, Giannis Daras, Sarah Pratt, Vivek Ramanujan, Yonatan Bitton, Kalyani Marathe, Stephen Mussmann, Richard Vencu, Mehdi Cherti, Ranjay Krishna, Pang Wei W Koh, Olga Saukh, Alexander J Ratner, Shuran Song, Hannaneh Hajishirzi, Ali Farhadi, Romain Beaumont, Sewoong Oh, Alex Dimakis, Jenia Jitsev, Yair Carmon, Vaishaal Shankar, and Ludwig Schmidt. DataComp: In search of the next generation of multimodal datasets. In *NeurIPS*, 2023.

[45] Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. SigLIP 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features. In *arXiv preprint arXiv:2502.14786*, 2025.

[46] Yung-Sung Chuang, Yang Li, Dong Wang, Ching-Feng Yeh, Kehan Lyu, Ramya Raghavendra, James Glass, Lifei Huang, Jason Weston, Luke Zettlemoyer, Xinlei Chen, Zhuang Liu, Saining Xie, Wen-tau Yih, Shang-Wen Li, and Hu Xu. Meta CLIP 2: A worldwide scaling recipe. In *NeurIPS*, 2025.

[47] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The Caltech-UCSD Birds-200-2011 dataset. Technical Report CNS-TR-2011-001, California Institute of Technology, 2011.

[48] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation Learning with Contrastive Predictive Coding. In *arXiv preprint arXiv:1807.03748*, 2018.

[49] Frederic Sala, Chris De Sa, Albert Gu, and Christopher Ré. Representation Tradeoffs for Hyperbolic Embeddings. In *ICML*, 2018.

[50] Aaron B. Adcock, Blair D. Sullivan, and Michael W. Mahoney. Tree-like structure in large social and information networks. In *ICDM*, 2013.

[51] Alex Fang, Albin Madappally Jose, Amit Jain, Ludwig Schmidt, Alexander T. Toshev, and Vaishaal Shankar. Data filtering networks. In *ICLR*, 2024.

[52] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *ICLR*, 2021.

Contents

1 Introduction **1**

2 Related Work **3**

3 Hierarchical Angular Separation and Its Modality Asymmetry in CLIP **4**

3.1 Definition of Hierarchical Angular Separation 4

3.2 Hierarchical Angular Separation in CLIP embeddings 4

4 Provable Transfer of Hierarchical Angular Separation from Image to Text Embeddings **6**

4.1 Setup and Notation 6

4.2 Linear Contrastive Loss Analysis 7

4.3 InfoNCE Loss Analysis 9

4.4 Synthetic Validation at Small Regularization 10

5 Conclusion **10**

A Formalizations of Hierarchy in Embedding Spaces **15**

A.1 Hyperbolic Entailment Cones 15

A.2 Other Formalizations 16

B Limitations of our analysis **16**

C Supporting Lemmas **16**

C.1 Softmax expansions 16

C.2 Prototype geometry and margin transfer 18

C.3 Caption bias and sampling 21

C.4 Concentration 21

D Proofs for Intermediate Results in Linear Contrastive Loss Analysis **22**

D.1 Closed-Form Minimizers for the Linear Contrastive Loss 22

D.2 Proof of Corollary D.2 (Empirical-Mean Expression) 24

D.3 Proof of Corollary 4.5 25

E Proofs of Intermediate Results in InfoNCE Loss Analysis **25**

E.1 Proof of Lemma E.1 (Strong Convexity) 25

E.2 Proof of Proposition E.2 (Stationarity Condition) 25

E.3 Proof of Proposition 4.7 (Large-Regularization Expansion) 26

E.4 Proof of Corollary 4.8 (Prototype Decomposition) 27

E.5 Quantitative Remainder for the InfoNCE Expansion 27

F Shared Transfer Argument **28**

G Proof of Hierarchical Angular Separation Transfer for the Linear Contrastive Loss **30**

H Proof of Hierarchical Angular Separation Transfer for the InfoNCE Loss **31**

I Step-by-step construction of a Hierarchical Concept Embedding **31**

I.1 Geometric requirements 31

I.2 Feasible subspace and depth–dimension condition 32

I.3 Construction 32

I.4 Properties 32

J Additional Experiments **35**

J.1 Hierarchical Angular Separation on CLIP embeddings 35

J.1.1 Controls and robustness checks for approximate image-side $\mathcal{HAS}$ 35

J.1.2 Robustness to the prototype construction and the taxonomy 35

J.2 Disjoint-Split Control against Instance Overlap for $\mathcal{HAS}$ in Image Embeddings . . 37

J.3 Numerical Validation of $\mathcal{HAS}$ Transfer at Small Regularization 44

J.4 Predicted and Realized Slack on Real ViT-L/14 Prototypes 46

J.5 Caption Permutation Disrupts Approximate $\mathcal{HAS}$ Transfer 48

J.6 Text-side $\mathcal{HAS}$ is strongest with path-consistent captions under joint CLIP training 48

K Alternating Optimization: The Image-Side Update **49**

L Relaxing the Caption-Symmetry Assumptions **53**

L.1 Caption Imbalance and Inexact Prototype Consistency 54

L.2 Partial Ancestor Omission 55

L.3 Total Caption Omission: Collapse of Uncaptioned Concepts 56

A Formalizations of Hierarchy in Embedding Spaces

Several prior works have formalized how an embedding of a rooted tree *encodes* the hierarchy. We group these formalizations into two categories:

- *Prescriptive* formalizations, which incorporate an explicit geometric constraint (e.g., a cone with a chosen angle) into the training objective to enforce it.
- *Descriptive* formalizations, which characterize a property of the learned embeddings without building it into the loss.

Our Definition 3.1 is descriptive: We state a pairwise cosine-similarity inequality to be verified for trained embeddings. We compare with the closest prior work in Appendix A.1 and note other formalizations in Appendix A.2.

A.1 Hyperbolic Entailment Cones

The most comparable prior formalization is the hyperbolic entailment cone line of work [12, 13, 14]. Each non-root embedding $\boldsymbol{x}$ is assigned a convex cone $\mathcal{C}_{\boldsymbol{x}}$ with a half-angle $\psi(\boldsymbol{x})$ specified as a function of $\boldsymbol{x}$, [1] and the loss penalizes violations of cone inclusion: descendants of u must lie inside

[1] Ganea et al. [12] use $\psi(\boldsymbol{x}) = \arcsin(K(1 - \|\boldsymbol{x}\|^2)/\|\boldsymbol{x}\|)$ in the Poincaré ball. Desai et al. [13] (MERU) adapt this to the Lorentz model with learnable curvature c via $\arcsin(2K/(\sqrt{c}\,\|\boldsymbol{x}_{\text{space}}\|))$. Pal et al. [14] (HyCoCLIP) use the MERU angle with a multiplicative slack η.

$\mathcal{C}_{\boldsymbol{a}_u}$, while non-descendants must lie outside. The angle is thus *determined in advance* and enforced as a training margin.

$\mathcal{HAS}$ can be viewed as a Euclidean version of this condition, but *descriptive* rather than prescriptive: the pairwise inequality $\cos(\boldsymbol{a}_u, \boldsymbol{a}_v) > \cos(\boldsymbol{a}_u, \boldsymbol{a}_w)$ is equivalent to strict cone containment with the angle determined by the nearest off-branch embedding, so the angle is *determined by the data* rather than imposed by the loss.

A.2 Other Formalizations

Poincaré embeddings. Nickel and Kiela [33] learn embeddings in the Poincaré ball via a soft-ranking loss, yielding a hierarchical ordering of concepts (general concepts near the origin, specific ones near the boundary) without an explicit descendant-vs-non-descendant inequality. In Definition 3.1, we make the inequality explicit.

Hyperbolic tree distortion and δ-hyperbolicity. A separate line of work formalizes hierarchy at the metric level: Sala et al. [49] bound the distortion of the tree metric under a hyperbolic embedding, and Adcock et al. [50] characterize tree-likeness via Gromov's δ-hyperbolicity. These are *metric* (distance-based) formalizations. In contrast, $\mathcal{HAS}$ is a *directional* (angle-based) one and makes no claim about metric distortion.

B Limitations of our analysis

Our analysis isolates how hierarchical image-caption co-occurrence transfers existing image geometry to text. We discuss the scope of this mechanism and the assumptions that limit its application to CLIP training.

Fixed image embeddings. The fixed-image UFM captures the direction of transfer suggested by the observed modality asymmetry: hierarchical geometry is already approximately present in image embeddings, and text embeddings acquire it through contrastive learning. By optimizing text concept embeddings directly, we can identify hierarchical image-caption co-occurrence as the mechanism that aligns text embeddings with root-centered image prototypes. The model therefore explains how an alignment objective can transfer hierarchical structure without explicit supervision. The limitation is that assuming fixed image embeddings does not capture joint training dynamics. We also replace CLIP's unit-norm embeddings with unnormalized embeddings and quadratic regularization for tractability (Remark 4.2).

Image embedding optimization analysis. The image-side extension in Appendix K identifies noise reduction within caption groups after an exact text update followed by an exact image update under the linear loss. How that mechanism affects subtree-aggregated image prototypes during joint gradient descent, and how the initial image-side hierarchy arises, remain open.

Approximate $\mathcal{HAS}$ guarantees and empirical measurements. The main theorems bound text-side violations using the image-side percentage of off-branch nodes whose worst-case triplet margin is at most the transfer threshold. The guarantees require small perturbations relative to the prototype norms. This sufficient condition fails for the real image prototypes examined in Appendix J.4, so the main theorems give no guarantee for the observed transfer there. Deriving tighter guarantees, therefore, remains an open problem.

Sufficient regularization for InfoNCE. The InfoNCE guarantee requires sufficiently large regularization to control the remainder in the expansion around uniform softmax weights. Experiments in Appendix J.3 show HAS transfer at weaker regularization, but do not extend the theorem to that regime. A guarantee for weaker regularization, or for CLIP's normalized objective, remains open.

C Supporting Lemmas

C.1 Softmax expansions

Lemma C.1 (Softmax partial derivatives)**.** *For $K \geq 1$, define* $\mathrm{softmax} : \mathbb{R}^K \to \mathbb{R}^K$ *by*

$$\big(\mathrm{softmax}(\mathbf{s})\big)_j := \frac{e^{s_j}}{\sum_{r=1}^{K} e^{s_r}}, \qquad j \in [K]. \tag{12}$$

Then, for every $j, \ell \in [K]$,

$$\frac{\partial}{\partial s_\ell}\big(\mathrm{softmax}(\mathbf{s})\big)_j = \big(\mathrm{softmax}(\mathbf{s})\big)_j\big(\delta_{j\ell} - \big(\mathrm{softmax}(\mathbf{s})\big)_\ell\big), \tag{13}$$

where $\delta_{j\ell}$ is the Kronecker delta, equal to 1 when $j = \ell$ and 0 otherwise.

Proof. Write

$$p_j(\mathbf{s}) := \big(\mathrm{softmax}(\mathbf{s})\big)_j = \frac{e^{s_j}}{Z(\mathbf{s})}, \qquad Z(\mathbf{s}) := \sum_{r=1}^{K} e^{s_r}. \tag{14}$$

Differentiating with respect to s_ℓ and using the quotient rule gives

$$\begin{aligned}
\frac{\partial p_j}{\partial s_\ell} &= \frac{\big(\partial_{s_\ell} e^{s_j}\big) Z(\mathbf{s}) - e^{s_j}\, \partial_{s_\ell} Z(\mathbf{s})}{Z(\mathbf{s})^2} \\
&= \frac{\delta_{j\ell} e^{s_j} Z(\mathbf{s}) - e^{s_j} e^{s_\ell}}{Z(\mathbf{s})^2} \\
&= \frac{e^{s_j}}{Z(\mathbf{s})}\left(\delta_{j\ell} - \frac{e^{s_\ell}}{Z(\mathbf{s})}\right) \\
&= \mathrm{softmax}(\mathbf{s})_j\left(\delta_{j\ell} - \mathrm{softmax}(\mathbf{s})_\ell\right).
\end{aligned} \tag{15}$$

□

Lemma C.2 (Quantitative softmax deviation from uniform)**.** *For $K \geq 1$, define $\mathrm{softmax} : \mathbb{R}^K \to \mathbb{R}^K$ as in Lemma C.1. Then, for every $\mathbf{s} \in \mathbb{R}^K$ and every $j \in [K]$,*

$$\left|\mathrm{softmax}(\mathbf{s})_j - \frac{1}{K}\right| \leq 2\|\mathbf{s}\|. \tag{16}$$

Proof. Let $f_j(\mathbf{s}) := \mathrm{softmax}(\mathbf{s})_j$. By Lemma C.1,

$$\nabla f_j(\mathbf{s}) = f_j(\mathbf{s})\big(e_j - \mathrm{softmax}(\mathbf{s})\big), \tag{17}$$

where e_j is the jth standard basis vector in $\mathbb{R}^K$. Since $0 \leq f_j(\mathbf{s}) \leq 1$ and $\|\mathrm{softmax}(\mathbf{s})\| \leq 1$, we have $\|\nabla f_j(\mathbf{s})\| \leq 2$ for every $\mathbf{s} \in \mathbb{R}^K$. By the fundamental theorem of calculus along the segment $\{\tau\mathbf{s} : \tau \in [0,1]\}$,

$$f_j(\mathbf{s}) - f_j(\mathbf{0}) = \int_0^1 \nabla f_j(\tau\mathbf{s})^\top \mathbf{s}\, d\tau. \tag{18}$$

Therefore

$$|f_j(\mathbf{s}) - f_j(\mathbf{0})| \leq \int_0^1 \|\nabla f_j(\tau\mathbf{s})\|\, \|\mathbf{s}\|\, d\tau \leq 2\|\mathbf{s}\|. \tag{19}$$

Since $f_j(\mathbf{0}) = 1/K$, this proves Eq. (16). □

Lemma C.3 (Softmax near the zero vector)**.** *For $K \geq 1$, define $\mathrm{softmax} : \mathbb{R}^K \to \mathbb{R}^K$ by*

$$\big(\mathrm{softmax}(\mathbf{s})\big)_j := \frac{e^{s_j}}{\sum_{\ell=1}^K e^{s_\ell}}, \qquad j \in [K]. \tag{20}$$

Let $\|\cdot\|$ denote the Euclidean norm on $\mathbb{R}^K$. Then $\big(\mathrm{softmax}(\mathbf{0})\big)_j = \frac{1}{K}$ for every $j \in [K]$. Moreover, if $\mathbf{s} \to \mathbf{0}$, then

$$\big(\mathrm{softmax}(\mathbf{s})\big)_j = \frac{1}{K} + \frac{1}{K}\left(s_j - \frac{1}{K}\sum_{\ell=1}^K s_\ell\right) + O(\|\mathbf{s}\|^2), \tag{21}$$

uniformly over $j \in [K]$. In particular, if $\|\mathbf{s}\| = O(\varepsilon)$, then

$$\big(\mathrm{softmax}(\mathbf{s})\big)_j = \frac{1}{K} + O(\varepsilon), \tag{22}$$

uniformly over $j \in [K]$.

Proof. At $\mathbf{s} = \mathbf{0}$, all exponentials equal 1, so

$$\big(\mathrm{softmax}(\mathbf{0})\big)_j = \frac{1}{\sum_{\ell=1}^{K} 1} = \frac{1}{K}. \tag{23}$$

Since $\mathrm{softmax}$ is smooth on $\mathbb{R}^K$, Taylor's theorem around $\mathbf{0}$ with $f_j(\mathbf{s}) := \big(\mathrm{softmax}(\mathbf{s})\big)_j$ gives

$$f_j(\mathbf{s}) = f_j(\mathbf{0}) + \nabla f_j(\mathbf{0})^\top \mathbf{s} + O(\|\mathbf{s}\|^2). \tag{24}$$

Equivalently,

$$\big(\mathrm{softmax}(\mathbf{s})\big)_j = \big(\mathrm{softmax}(\mathbf{0})\big)_j + \sum_{\ell=1}^{K} \frac{\partial f_j}{\partial s_\ell}(\mathbf{0})\, s_\ell + O(\|\mathbf{s}\|^2). \tag{25}$$

By Lemma C.1,

$$\frac{\partial}{\partial s_\ell}\big(\mathrm{softmax}(\mathbf{s})\big)_j = \big(\mathrm{softmax}(\mathbf{s})\big)_j\big(\delta_{j\ell} - \big(\mathrm{softmax}(\mathbf{s})\big)_\ell\big), \tag{26}$$

so at $\mathbf{s} = \mathbf{0}$ we obtain

$$\frac{\partial f_j}{\partial s_\ell}(\mathbf{0}) = \frac{1}{K}\left(\delta_{j\ell} - \frac{1}{K}\right). \tag{27}$$

Therefore the linear term in the Taylor expansion is

$$\begin{aligned} \nabla f_j(\mathbf{0})^\top \mathbf{s} &= \sum_{\ell=1}^{K} \frac{1}{K}\left(\delta_{j\ell} - \frac{1}{K}\right) s_\ell \\ &= \frac{1}{K}\left(s_j - \frac{1}{K}\sum_{\ell=1}^{K} s_\ell\right). \end{aligned} \tag{28}$$

Moreover,

$$\begin{aligned} \left|\nabla f_j(\mathbf{0})^\top \mathbf{s}\right| &\le \frac{1}{K}\left(|s_j| + \frac{1}{K}\left|\sum_{\ell=1}^{K} s_\ell\right|\right) \\ &\le \frac{1}{K}\left(\|\mathbf{s}\| + \frac{1}{K}\|\mathbf{1}\|\,\|\mathbf{s}\|\right) = \frac{1}{K}\left(1 + \frac{1}{\sqrt{K}}\right)\|\mathbf{s}\|, \end{aligned} \tag{29}$$

where $\mathbf{1} \in \mathbb{R}^K$ is the all-ones vector. Thus the linear term is $O(\|\mathbf{s}\|)$. Substituting $f_j(\mathbf{0}) = \frac{1}{K}$ and this expression for $\nabla f_j(\mathbf{0})^\top \mathbf{s}$ into the Taylor expansion yields Eq. (21). If $\|\mathbf{s}\| = O(\varepsilon)$, then the linear term is $O(\varepsilon)$ and the remainder is $O(\varepsilon^2)$, which gives the final claim. □

C.2 Prototype geometry and margin transfer

Lemma C.4 (Balanced Descendant Prototype Averaging)**.** *Assume the tree is balanced with branching factor b, and the prototypes $\{\boldsymbol{\mu}_k\}$ are constructed as in Appendix I. Then for every node k, the average of the leaf prototypes in the subtree rooted at k is exactly $\boldsymbol{\mu}_k$.*

Proof. The claim is immediate for leaves. Now let k be an internal node with children $c_1, \dots, c_b$. By construction,

$$\boldsymbol{\mu}_{c_j} = \boldsymbol{\mu}_k + \boldsymbol{U}\boldsymbol{d}_j, \qquad j = 1, \dots, b, \tag{30}$$

where the embedded simplex offsets satisfy $\sum_{j=1}^{b} \boldsymbol{d}_j = \mathbf{0}$. Hence the child average is

$$\frac{1}{b}\sum_{j=1}^{b} \boldsymbol{\mu}_{c_j} = \boldsymbol{\mu}_k + \boldsymbol{U}\left(\frac{1}{b}\sum_{j=1}^{b} \boldsymbol{d}_j\right) = \boldsymbol{\mu}_k. \tag{31}$$

Because the tree is balanced, each child subtree contains the same number of leaves. Applying the induction hypothesis within each child subtree therefore shows that the leaf-descendant average of k is the same average of the child averages, hence equal to $\boldsymbol{\mu}_k$. □

Lemma C.5 (Cosine stability under small perturbations)**.** *Let $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^d$ be nonzero, let $\boldsymbol{e}_x, \boldsymbol{e}_y \in \mathbb{R}^d$, and set*

$$\rho := \min\{\|\boldsymbol{x}\|, \|\boldsymbol{y}\|\}. \tag{32}$$

If

$$\max\{\|\boldsymbol{e}_x\|, \|\boldsymbol{e}_y\|\} \le \delta < \rho, \tag{33}$$

then

$$|\cos(\boldsymbol{x}+\boldsymbol{e}_x, \boldsymbol{y}+\boldsymbol{e}_y) - \cos(\boldsymbol{x}, \boldsymbol{y})| \le \frac{4\delta}{\rho}. \tag{34}$$

Proof. For any nonzero $\boldsymbol{z} \in \mathbb{R}^d$ and perturbation $\boldsymbol{e}$ with $\|\boldsymbol{e}\| < \|\boldsymbol{z}\|$, define $\nu(\boldsymbol{z}) := \boldsymbol{z}/\|\boldsymbol{z}\|$. Then

$$\begin{aligned}
\|\nu(\boldsymbol{z}+\boldsymbol{e}) - \nu(\boldsymbol{z})\| &= \left\| \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}+\boldsymbol{e}\|} - \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}\|} + \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}\|} - \frac{\boldsymbol{z}}{\|\boldsymbol{z}\|} \right\| \\
&\le \left\| \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}+\boldsymbol{e}\|} - \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}\|} \right\| + \left\| \frac{\boldsymbol{z}+\boldsymbol{e}}{\|\boldsymbol{z}\|} - \frac{\boldsymbol{z}}{\|\boldsymbol{z}\|} \right\| \\
&= \left| \frac{\|\boldsymbol{z}\| - \|\boldsymbol{z}+\boldsymbol{e}\|}{\|\boldsymbol{z}\|} \right| + \frac{\|\boldsymbol{e}\|}{\|\boldsymbol{z}\|} \\
&\le \frac{\|\boldsymbol{e}\|}{\|\boldsymbol{z}\|} + \frac{\|\boldsymbol{e}\|}{\|\boldsymbol{z}\|} \\
&= \frac{2\|\boldsymbol{e}\|}{\|\boldsymbol{z}\|},
\end{aligned} \tag{35}$$

where the first inequality is the triangle inequality after adding and subtracting $(\boldsymbol{z}+\boldsymbol{e})/\|\boldsymbol{z}\|$, and the second inequality is the reverse triangle inequality

$$|\|\boldsymbol{z}\| - \|\boldsymbol{z}+\boldsymbol{e}\|| \le \|\boldsymbol{e}\|. \tag{36}$$

Applying this bound with $(\boldsymbol{z}, \boldsymbol{e}) = (\boldsymbol{x}, \boldsymbol{e}_x)$ and $(\boldsymbol{z}, \boldsymbol{e}) = (\boldsymbol{y}, \boldsymbol{e}_y)$ gives

$$\|\nu(\boldsymbol{x}+\boldsymbol{e}_x) - \nu(\boldsymbol{x})\| \le \frac{2\delta}{\rho}, \qquad \|\nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{y})\| \le \frac{2\delta}{\rho}. \tag{37}$$

Therefore

$$\begin{aligned}
&|\cos(\boldsymbol{x}+\boldsymbol{e}_x, \boldsymbol{y}+\boldsymbol{e}_y) - \cos(\boldsymbol{x}, \boldsymbol{y})| = \left|\nu(\boldsymbol{x}+\boldsymbol{e}_x)^\top \nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{x})^\top \nu(\boldsymbol{y})\right| \\
&= \left|\nu(\boldsymbol{x}+\boldsymbol{e}_x)^\top \nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{x})^\top \nu(\boldsymbol{y}+\boldsymbol{e}_y) + \nu(\boldsymbol{x})^\top \nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{x})^\top \nu(\boldsymbol{y})\right| \\
&\le \left|\left(\nu(\boldsymbol{x}+\boldsymbol{e}_x) - \nu(\boldsymbol{x})\right)^\top \nu(\boldsymbol{y}+\boldsymbol{e}_y)\right| + \left|\nu(\boldsymbol{x})^\top \left(\nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{y})\right)\right| \\
&\le \|\nu(\boldsymbol{x}+\boldsymbol{e}_x) - \nu(\boldsymbol{x})\| \, \|\nu(\boldsymbol{y}+\boldsymbol{e}_y)\| + \|\nu(\boldsymbol{x})\| \, \|\nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{y})\| \\
&= \|\nu(\boldsymbol{x}+\boldsymbol{e}_x) - \nu(\boldsymbol{x})\| + \|\nu(\boldsymbol{y}+\boldsymbol{e}_y) - \nu(\boldsymbol{y})\| \\
&\le \frac{4\delta}{\rho}.
\end{aligned} \tag{38}$$

where the first inequality is the triangle inequality and the second inequality is Cauchy–Schwarz. □

In Theorems 4.6 and 4.9, we compare two embedding families at a common anchor, so each quantity defined below is written with a superscript for the family $\boldsymbol{c} = \{\boldsymbol{c}_k\}_{k \in V \setminus \{\mathrm{root}\}}$ of nonzero vectors it is evaluated on. The first of the two is the quantity that must be positive in Definition 3.1.

Definition C.6 (Admissible triplet and triplet margin)**.** Write $\mathcal{O}_u := V \setminus \big(\mathrm{Sub}(u) \cup \mathrm{Anc}(u)\big)$ for the off-branch set at u, which forms the denominator of Eq. (2), and call (u, v, w) an *admissible triplet* if $u \in V \setminus \{\mathrm{root}\}$ is non-leaf, $v \in \mathrm{Desc}(u)$, and $w \in \mathcal{O}_u$. The *triplet margin* of an admissible triplet under $\boldsymbol{c}$ is

$$\gamma^{\boldsymbol{c}}_{uvw} := \cos(\boldsymbol{c}_u, \boldsymbol{c}_v) - \cos(\boldsymbol{c}_u, \boldsymbol{c}_w). \tag{39}$$

When admissible triplets exist for a family of nonzero image prototypes, define their global margin by

$$\gamma_{\mathcal{HAS}} := \min_{(u,v,w)\ \text{admissible}} \gamma^{\boldsymbol{\mu}}_{uvw}. \tag{40}$$

The second definition is Definition 3.2 with its descendant threshold lowered by a slack.

Definition C.7 (Slack violation percentage)**.** Let $c^{\boldsymbol{c}}_u := \min_{v\in\mathrm{Desc}(u)} \cos(\boldsymbol{c}_u, \boldsymbol{c}_v)$ be the descendant threshold c_u of Definition 3.2 evaluated on $\boldsymbol{c}$. For a non-root non-leaf node u and a slack $\tau \geq 0$, the *slack-τ violation percentage* is

$$\mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}_\tau(u) := \frac{|\{w \in \mathcal{O}_u : \cos(\boldsymbol{c}_u, \boldsymbol{c}_w) \geq c^{\boldsymbol{c}}_u - \tau\}|}{|\mathcal{O}_u|} \times 100\%, \tag{41}$$

and we drop the subscript at $\tau = 0$, writing $\mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}(u) := \mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}_0(u)$.

At $\tau = 0$ the threshold is unchanged, so $\mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}(u)$ is exactly the violation percentage $\mathcal{HAS}\text{-Viol}(u)$ of Definition 3.2 for the family $\boldsymbol{c}$. In the main text the superscript is a mnemonic rather than a symbol: $\mathcal{HAS}\text{-Viol}^{\mathrm{img}}_\tau(u)$ is $\mathcal{HAS}\text{-Viol}^{\boldsymbol{\mu}}_\tau(u)$ on the image prototypes, and $\mathcal{HAS}\text{-Viol}^{\mathrm{txt}}(u)$ is $\mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}(u)$ with $\boldsymbol{c}$ the optimal text embeddings under consideration.

The two definitions are connected through the identity $\min_{v\in\mathrm{Desc}(u)} \gamma^{\boldsymbol{c}}_{uvw} = c^{\boldsymbol{c}}_u - \cos(\boldsymbol{c}_u, \boldsymbol{c}_w)$, which holds for each fixed off-branch node w. The percentage $\mathcal{HAS}\text{-Viol}^{\boldsymbol{c}}_\tau(u)$ is therefore the percentage of off-branch nodes w whose worst-case triplet margin at anchor u is at most τ.

Lemma C.8 is the deterministic core shared by Theorems 4.6 and 4.9. It assumes nothing about the prototype variation model, the observed captions, or the global margin $\gamma_{\mathcal{HAS}}$, and all randomness in either theorem enters only through the bound η on the perturbations.

Lemma C.8 (Per-triplet $\mathcal{HAS}$ margin preservation)**.** *Let $\boldsymbol{\nu} = \{\boldsymbol{\nu}_k\}_{k\in V\setminus\{\mathrm{root}\}}$ be reference vectors with minimum norm $\rho^{\nu}_{\min} := \min_{k\neq\mathrm{root}} \|\boldsymbol{\nu}_k\| > 0$ and, for each non-root node k, let $\widetilde{\boldsymbol{a}}_k = c_k(\boldsymbol{\nu}_k + \boldsymbol{e}_k)$ for some scaling $c_k > 0$ and perturbation $\boldsymbol{e}_k \in \mathbb{R}^d$. Let $\eta \geq 0$ satisfy*

$$\max_{k\neq\mathrm{root}} \|\boldsymbol{e}_k\| \leq \eta < \rho^{\nu}_{\min}, \tag{42}$$

and set $\tau := 8\eta/\rho^{\nu}_{\min}$. Then:

- *(i) the family $\widetilde{\boldsymbol{a}} := \{\widetilde{\boldsymbol{a}}_k\}_{k\neq\mathrm{root}}$ satisfies $\widetilde{\boldsymbol{a}}_k \neq \mathbf{0}$ for every non-root node k, so the cosines in part (ii) and the violation percentage in part (iii) are well defined;*
- *(ii) every admissible triplet (u, v, w) with $\gamma^{\boldsymbol{\nu}}_{uvw} > \tau$ satisfies $\cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_v) > \cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_w)$;*
- *(iii) $\mathcal{HAS}\text{-Viol}^{\widetilde{\boldsymbol{a}}}(u) \leq \mathcal{HAS}\text{-Viol}^{\boldsymbol{\nu}}_\tau(u)$ for every non-root non-leaf node u.*

Proof. (i) By Eq. (42) and the reverse triangle inequality, $\|\boldsymbol{\nu}_k + \boldsymbol{e}_k\| \geq \rho^{\nu}_{\min} - \eta > 0$ for every non-root node k; since $c_k > 0$, this gives $\widetilde{\boldsymbol{a}}_k \neq \mathbf{0}$. The $\boldsymbol{\nu}_k$ are nonzero by hypothesis, so every cosine in parts (ii) and (iii) is taken between nonzero vectors.

(ii) Fix an admissible triplet (u, v, w) with $\gamma^{\boldsymbol{\nu}}_{uvw} > \tau$. Positive rescaling leaves cosines unchanged, so

$$\cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_v) = \cos(\boldsymbol{\nu}_u + \boldsymbol{e}_u, \boldsymbol{\nu}_v + \boldsymbol{e}_v), \tag{43}$$

and similarly with v replaced by w. By Eq. (42), we can apply Lemma C.5 to the pairs (u, v) and (u, w) with $\delta = \eta$ and pairwise minimum norm at least $\rho^{\nu}_{\min}$, so each of the two cosines differs from its reference counterpart by at most $4\eta/\rho^{\nu}_{\min}$. Therefore

$$\cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_v) - \cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_w) \geq \cos(\boldsymbol{\nu}_u, \boldsymbol{\nu}_v) - \cos(\boldsymbol{\nu}_u, \boldsymbol{\nu}_w) - \frac{8\eta}{\rho^{\nu}_{\min}} = \gamma^{\boldsymbol{\nu}}_{uvw} - \tau > 0. \tag{44}$$

(iii) Fix a non-root non-leaf node u and suppose w is counted in $\mathcal{HAS}\text{-Viol}^{\widetilde{\boldsymbol{a}}}(u)$, i.e., $\cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_w) \geq c^{\widetilde{\boldsymbol{a}}}_u$. Let $v^\star \in \mathrm{Desc}(u)$ attain the minimum defining $c^{\widetilde{\boldsymbol{a}}}_u$. Then the $\mathcal{HAS}$ inequality fails for the admissible triplet $(u, v^\star, w)$, so the contrapositive of part (ii) gives $\gamma^{\boldsymbol{\nu}}_{uv^\star w} \leq \tau$. Therefore

$$c^{\boldsymbol{\nu}}_u - \cos(\boldsymbol{\nu}_u, \boldsymbol{\nu}_w) = \min_{v\in\mathrm{Desc}(u)} \gamma^{\boldsymbol{\nu}}_{uvw} \leq \gamma^{\boldsymbol{\nu}}_{uv^\star w} \leq \tau \implies \cos(\boldsymbol{\nu}_u, \boldsymbol{\nu}_w) \geq c^{\boldsymbol{\nu}}_u - \tau. \tag{45}$$

Thus, the same w is counted in $\mathcal{HAS}\text{-Viol}^{\boldsymbol{\nu}}_\tau(u)$. Both percentages share the denominator $|\mathcal{O}_u|$, so the inclusion of the counted sets yields the claim. □

Applied with $\boldsymbol{\nu} = \boldsymbol{\mu}$, part (iii) is the transfer inequality of Eq. (8). In Appendix F, we derive the perturbation bound η for each loss.

C.3 Caption bias and sampling

The optimizer forms for both losses involve the same difference of empirical means. In Lemma C.10, we separate that difference into prototype, caption-bias, and variation components, and in Corollary C.11, we give the conditions under which the caption-bias component vanishes.

Definition C.9 (Empirical caption prototype and caption bias)**.** Fix prototypes $\{\boldsymbol{\mu}_k\}_{k\in V} \subset \mathbb{R}^d$, leaf labels $y_j \in V_{\mathrm{leaf}}$, and caption labels $t_j \in V$ for every $j \in [N]$, with $N_k > 0$ for every non-root node k. The captions need not be path-consistent. Recall from Section 4.1 that $\mathcal{P}_k := \{j \in [N] : t_j = k\}$ is the positive set of node k and $N_k := |\mathcal{P}_k|$. The *empirical caption prototype* of node k and the *global prototype mean* are

$$\bar{\boldsymbol{\mu}}_k := \frac{1}{N_k} \sum_{j\in\mathcal{P}_k} \boldsymbol{\mu}_{y_j}, \qquad \bar{\boldsymbol{\mu}} := \frac{1}{N} \sum_{j=1}^{N} \boldsymbol{\mu}_{y_j}, \tag{46}$$

with associated *caption biases* $\boldsymbol{b}_k := \bar{\boldsymbol{\mu}}_k - \boldsymbol{\mu}_k$ and $\boldsymbol{b} := \bar{\boldsymbol{\mu}} - \boldsymbol{\mu}_{\mathrm{root}}$.

Lemma C.10 (Empirical-mean decomposition)**.** *Fix prototypes, leaf labels, and caption labels as in Definition C.9, and let $\xi_k \in \mathbb{R}$ for every non-root node k. Let $\boldsymbol{z}_j = \boldsymbol{\mu}_{y_j} + \boldsymbol{\varepsilon}_j$ with arbitrary $\boldsymbol{\varepsilon}_j \in \mathbb{R}^d$ for every $j \in [N]$, and define $\bar{\boldsymbol{\varepsilon}}_k := N_k^{-1} \sum_{j\in\mathcal{P}_k} \boldsymbol{\varepsilon}_j$ for every non-root node k and $\bar{\boldsymbol{\varepsilon}} := N^{-1} \sum_{j=1}^{N} \boldsymbol{\varepsilon}_j$. Then, for every non-root node k,*

$$\bar{\boldsymbol{z}}_k = \boldsymbol{\mu}_k + \boldsymbol{b}_k + \bar{\boldsymbol{\varepsilon}}_k, \qquad \bar{\boldsymbol{z}} = \boldsymbol{\mu}_{\mathrm{root}} + \boldsymbol{b} + \bar{\boldsymbol{\varepsilon}}, \tag{47}$$

and, for every non-root node k,

$$\begin{aligned} \bar{\boldsymbol{z}}_k - \xi_k \bar{\boldsymbol{z}} = \boldsymbol{\mu}_k - \xi_k \boldsymbol{\mu}_{\mathrm{root}} + \boldsymbol{b}_k - \xi_k \boldsymbol{b} \\ + \bar{\boldsymbol{\varepsilon}}_k - \xi_k \bar{\boldsymbol{\varepsilon}}. \end{aligned} \tag{48}$$

Proof. Averaging $\boldsymbol{z}_j = \boldsymbol{\mu}_{y_j} + \boldsymbol{\varepsilon}_j$ over $\mathcal{P}_k$ and over $[N]$ gives Eq. (47) by Definition C.9. Subtracting $\xi_k \bar{\boldsymbol{z}}$ gives Eq. (48). □

Lemma C.10 is an identity, so it holds for any observed captions; Appendix F uses it in that generality and adds the caption bias to the error term. The main theorems instead work in the symmetric setting of Section 4.1, where the bias vanishes.

Corollary C.11 (Zero caption bias under symmetric captions)**.** *Fix prototypes, leaf labels, and caption labels as in Definition C.9, suppose the captions are path-consistent, and suppose Assumption 4.3 (leaf-uniform caption coverage) and Assumption 4.4 (prototype consistency) hold. Then $\bar{\boldsymbol{\mu}}_k = \boldsymbol{\mu}_k$, and hence $\boldsymbol{b}_k = \mathbf{0}$, for every non-root node k. If exactly $c \in \mathbb{N}_{>0}$ images are sampled from each leaf, then also $\bar{\boldsymbol{\mu}} = \boldsymbol{\mu}_{\mathrm{root}}$ and $\boldsymbol{b} = \mathbf{0}$.*

Proof. Path-consistency gives $y_j \in \mathrm{Sub}(k)$ for every $j \in \mathcal{P}_k$, and by Assumption 4.3 each such leaf contributes equally many images. Hence $\bar{\boldsymbol{\mu}}_k$ is the uniform average of the leaf prototypes in $\mathrm{Sub}(k)$, which equals $\boldsymbol{\mu}_k$ by Assumption 4.4, so $\boldsymbol{b}_k = \mathbf{0}$. With exactly c images per leaf, $\bar{\boldsymbol{\mu}}$ is the uniform average of all leaf prototypes, which equals $\boldsymbol{\mu}_{\mathrm{root}}$ by the same assumption at the root, so $\boldsymbol{b} = \mathbf{0}$. □

C.4 Concentration

Lemma C.12 (Concentration of finitely many empirical variation means)**.** *Let $\mathcal{K}$ be a finite index set. Let $\{\boldsymbol{\varepsilon}_j\}_{j=1}^N$ be independent centered random vectors in $\mathbb{R}^d$. Assume there exists $\sigma > 0$ such that, for every $j \in [N]$ and every unit vector $\boldsymbol{u} \in \mathbb{S}^{d-1}$, the scalar $\boldsymbol{u}^\top \boldsymbol{\varepsilon}_j$ is sub-Gaussian with Orlicz norm at most σ. For each $k \in \mathcal{K}$, let $I_k \subseteq [N]$ with $s_k := |I_k| > 0$, and define*

$$\bar{\boldsymbol{\varepsilon}}_k := \frac{1}{s_k} \sum_{j\in I_k} \boldsymbol{\varepsilon}_j, \qquad \bar{\boldsymbol{\varepsilon}} := \frac{1}{N} \sum_{j=1}^{N} \boldsymbol{\varepsilon}_j. \tag{49}$$

For each $k \in \mathcal{K}$, let $\xi_k \in \mathbb{R}$, and define

$$\xi_{\max} := \max_{k\in\mathcal{K}} |\xi_k|, \qquad s_{\min} := \min_{k\in\mathcal{K}} s_k. \tag{50}$$

Then there exists a universal constant $C > 0$ such that, for every $u \geq 0$, with probability at least $1 - 4e^{-u}$,

$$\max_{k\in\mathcal{K}} \|\bar{\boldsymbol{\varepsilon}}_k - \xi_k \bar{\boldsymbol{\varepsilon}}\| \leq C\sigma \left(\sqrt{\frac{d + \log|\mathcal{K}| + u}{s_{\min}}} + \xi_{\max} \sqrt{\frac{d+u}{N}} \right). \tag{51}$$

Proof. For each fixed $k \in \mathcal{K}$, apply the scalar Hoeffding-type tail bound for averages of independent centered sub-Gaussian random variables to $\boldsymbol{u}^\top \bar{\boldsymbol{\varepsilon}}_k$ for $\boldsymbol{u} \in \mathbb{S}^{d-1}$. A standard $1/2$-net argument on $\mathbb{S}^{d-1}$ then gives a universal constant $C > 0$ such that, for every $t \geq 0$,

$$\Pr\left(\|\bar{\boldsymbol{\varepsilon}}_k\| > C\sigma \sqrt{\frac{d+t}{s_k}} \right) \leq 2e^{-t} \tag{52}$$

The same argument with $I_k = [N]$ and $s_k = N$ gives

$$\Pr\left(\|\bar{\boldsymbol{\varepsilon}}\| > C\sigma \sqrt{\frac{d+t}{N}} \right) \leq 2e^{-t}. \tag{53}$$

Apply the first bound with $t = u + \log|\mathcal{K}|$ and take a union bound over $k \in \mathcal{K}$. Then, with probability at least $1 - 2e^{-u}$,

$$\max_{k\in\mathcal{K}} \|\bar{\boldsymbol{\varepsilon}}_k\| \leq C\sigma \sqrt{\frac{d + \log|\mathcal{K}| + u}{s_{\min}}}. \tag{54}$$

The second bound with $t = u$ gives, with probability at least $1 - 2e^{-u}$,

$$\|\bar{\boldsymbol{\varepsilon}}\| \leq C\sigma \sqrt{\frac{d+u}{N}}. \tag{55}$$

Another union bound shows that both displayed bounds hold simultaneously with probability at least $1 - 4e^{-u}$. On that event,

$$\max_{k\in\mathcal{K}} \|\bar{\boldsymbol{\varepsilon}}_k - \xi_k \bar{\boldsymbol{\varepsilon}}\| \leq \max_{k\in\mathcal{K}} \|\bar{\boldsymbol{\varepsilon}}_k\| + \xi_{\max} \|\bar{\boldsymbol{\varepsilon}}\|, \tag{56}$$

where we used the triangle inequality and the bound $|\xi_k| \leq \xi_{\max}$ for every $k \in \mathcal{K}$. Substituting Eqs. (54) and (55) into this estimate gives Eq. (51). □

Lemma C.13 (Maximum feature norm under sub-Gaussian variation)**.** *Suppose Assumption 4.1 holds, and define $\mu_{\text{leaf,max}} := \max_{\ell\in V_{\text{leaf}}} \|\boldsymbol{\mu}_\ell\|$. Then there exists a universal constant $C > 0$ such that, for every $\epsilon \in (0,1)$, with probability at least $1 - \epsilon$,*

$$\max_{j\in[N]} \|\boldsymbol{z}_j\| \leq \mu_{\text{leaf,max}} + C\sigma\sqrt{d + \log(2N/\epsilon)}. \tag{57}$$

Proof. For each fixed $j \in [N]$, the same Hoeffding bound used in the proof of Lemma C.12 gives $\Pr(\|\boldsymbol{\varepsilon}_j\| > C\sigma\sqrt{d+u}) \leq 2e^{-u}$ for a universal constant $C > 0$. Taking $u = \log(2N/\epsilon)$ and union bounding over $j \in [N]$ gives $\max_{j\in[N]} \|\boldsymbol{\varepsilon}_j\| \leq C\sigma\sqrt{d + \log(2N/\epsilon)}$ with probability at least $1 - \epsilon$. Absorbing the factor 2 into the universal constant and using $\|\boldsymbol{z}_j\| \leq \|\boldsymbol{\mu}_{y_j}\| + \|\boldsymbol{\varepsilon}_j\| \leq \mu_{\text{leaf,max}} + \|\boldsymbol{\varepsilon}_j\|$ proves the claim. □

D Proofs for Intermediate Results in Linear Contrastive Loss Analysis

D.1 Closed-Form Minimizers for the Linear Contrastive Loss

The same label encoding governs the image-side update in Appendix K, so we state both minimizers together.

Proposition D.1 (Closed-Form Minimizers for the Linear Contrastive Loss with One Side Fixed)**.** *Define the assignment matrix* $\mathbf{Y} \in \{0,1\}^{M\times N}$ *via* $Y_{kj} := \mathbf{1}[t_j = k]$*. Then define the label encoding matrix* $\mathbf{B} \in \mathbb{R}^{M\times N}$ *by*

$$B_{kj} := \frac{1}{2}\left(Y_{kj} - \frac{1-Y_{kj}}{M-1}\right) + \frac{1}{2}\left(Y_{kj} - \frac{N_k - Y_{kj}}{N-1}\right). \tag{58}$$

Then the unique minimizer of Eq. (5) *is*

$$\boldsymbol{A}^{\mathrm{lin},*} = \frac{1}{\lambda}\boldsymbol{Z}\mathbf{B}^\top. \tag{59}$$

For any fixed $\boldsymbol{A} \in \mathbb{R}^{d\times M}$ *and* $\lambda_Z > 0$*, the image-side quadratic* $-\mathrm{tr}(\boldsymbol{A}^\top \boldsymbol{Z}\mathbf{B}^\top) + \frac{\lambda_Z}{2}\|\boldsymbol{Z}\|_F^2$ *has unique minimizer* $\lambda_Z^{-1}\boldsymbol{A}\mathbf{B}$ *over* $\boldsymbol{Z} \in \mathbb{R}^{d\times N}$*.*

We first rewrite Eq. (5) as

$$\mathcal{L}^{\mathrm{lin}}(\boldsymbol{A}) = -\mathrm{tr}\big(\boldsymbol{A}^\top \boldsymbol{Z}\mathbf{B}^\top\big) + \frac{\lambda}{2}\|\boldsymbol{A}\|_F^2, \tag{60}$$

with $\mathbf{B}$ as in Eq. (58).

Proof. Write the two terms in Eq. (5) as $\mathcal{L}^{\mathrm{lin}}_{\mathrm{i2t}}(\boldsymbol{A})$ and $\mathcal{L}^{\mathrm{lin}}_{\mathrm{t2i}}(\boldsymbol{A})$. Since $Y_{kj} = \mathbf{1}[t_j = k]$, the image-to-text term satisfies

$$\begin{aligned}\mathcal{L}^{\mathrm{lin}}_{\mathrm{i2t}}(\boldsymbol{A}) &= -\frac{1}{2}\sum_{j=1}^{N} \boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j + \frac{1}{2(M-1)}\sum_{j=1}^{N}\sum_{\substack{k\in[M]\\ k\neq t_j}} \boldsymbol{a}_k^\top \boldsymbol{z}_j \\ &= -\sum_{k=1}^{M}\sum_{j=1}^{N}\frac{1}{2}\left(Y_{kj} - \frac{1-Y_{kj}}{M-1}\right)\boldsymbol{a}_k^\top \boldsymbol{z}_j. \end{aligned}\tag{61}$$

For the text-to-image term, fix $k \in [M]$ and $j \in [N]$. The logit $\boldsymbol{a}_k^\top \boldsymbol{z}_j$ appears once in the positive part when $t_j = k$, and it appears in the negative pool once for each $j' \in [N] \setminus \{j\}$ with $t_{j'} = k$. Therefore the coefficient of $\boldsymbol{a}_k^\top \boldsymbol{z}_j$ in $\mathcal{L}^{\mathrm{lin}}_{\mathrm{t2i}}(\boldsymbol{A})$ is

$$-\frac{1}{2}Y_{kj} + \frac{1}{2(N-1)}\sum_{\substack{j'\in[N]\\ j'\neq j}} Y_{kj'} = -\frac{1}{2}\left(Y_{kj} - \frac{N_k - Y_{kj}}{N-1}\right), \tag{62}$$

because $\sum_{\substack{j'\in[N]\\ j'\neq j}} Y_{kj'} = N_k - Y_{kj}$ by the definition of N_k. Hence

$$\mathcal{L}^{\mathrm{lin}}_{\mathrm{t2i}}(\boldsymbol{A}) = -\sum_{k=1}^{M}\sum_{j=1}^{N}\frac{1}{2}\left(Y_{kj} - \frac{N_k - Y_{kj}}{N-1}\right)\boldsymbol{a}_k^\top \boldsymbol{z}_j. \tag{63}$$

Adding the two terms and using Eq. (58) gives

$$\mathcal{L}^{\mathrm{lin}}(\boldsymbol{A}) = -\sum_{k=1}^{M}\sum_{j=1}^{N} B_{kj}\boldsymbol{a}_k^\top \boldsymbol{z}_j + \frac{\lambda}{2}\|\boldsymbol{A}\|_F^2. \tag{64}$$

Finally,

$$\mathrm{tr}\big(\boldsymbol{A}^\top \boldsymbol{Z}\mathbf{B}^\top\big) = \sum_{k=1}^{M}\boldsymbol{a}_k^\top\left(\sum_{j=1}^{N} B_{kj}\boldsymbol{z}_j\right) = \sum_{k=1}^{M}\sum_{j=1}^{N} B_{kj}\boldsymbol{a}_k^\top \boldsymbol{z}_j, \tag{65}$$

so the previous display is exactly Eq. (60). Differentiating with respect to $\boldsymbol{A}$ yields

$$\nabla_{\boldsymbol{A}}\mathcal{L}^{\mathrm{lin}}(\boldsymbol{A}) = \lambda\boldsymbol{A} - \boldsymbol{Z}\mathbf{B}^\top. \tag{66}$$

Setting the gradient to zero gives Eq. (59), and the quadratic regularizer makes the minimizer unique. For the image-side quadratic, $\nabla_{\boldsymbol{Z}} = \lambda_Z \boldsymbol{Z} - \boldsymbol{A}\mathbf{B}$; setting this gradient to zero gives the stated image-side minimizer, unique because $\lambda_Z > 0$. □

D.2 Proof of Corollary D.2 (Empirical-Mean Expression)

Corollary D.2 (Empirical-Mean Expression for the Linear Minimizer)**.** *Every node $k \in [M]$ with $N_k > 0$ satisfies*

$$\boldsymbol{a}_k^{\mathrm{lin},*} = \frac{N_k}{\lambda}\left(1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)}\right)\bar{\boldsymbol{z}}_k - \frac{N}{\lambda}\left(\frac{1}{2(M-1)} + \frac{N_k}{2(N-1)}\right)\bar{\boldsymbol{z}}. \tag{67}$$

Proof. Fix a node $k \in [M]$ with $N_k > 0$, and write

$$\mathcal{P}_k := \{j \in [N] : t_j = k\}. \tag{68}$$

By Eq. (58),

$$B_{kj} = \begin{cases} \gamma_k^+, & j \in \mathcal{P}_k, \\ -\gamma_k^-, & j \notin \mathcal{P}_k, \end{cases} \tag{69}$$

where

$$\gamma_k^+ := 1 - \frac{N_k - 1}{2(N-1)}, \qquad \gamma_k^- := \frac{1}{2(M-1)} + \frac{N_k}{2(N-1)}. \tag{70}$$

Applying Proposition D.1,

$$\begin{aligned} \boldsymbol{a}_k^{\mathrm{lin},*} &= \frac{1}{\lambda}\sum_{j=1}^{N} B_{kj}\boldsymbol{z}_j \\ &= \frac{\gamma_k^+}{\lambda}\sum_{j\in\mathcal{P}_k}\boldsymbol{z}_j - \frac{\gamma_k^-}{\lambda}\sum_{j\notin\mathcal{P}_k}\boldsymbol{z}_j. \end{aligned} \tag{71}$$

By definition,

$$\sum_{j\notin\mathcal{P}_k}\boldsymbol{z}_j = \sum_{j=1}^{N}\boldsymbol{z}_j - \sum_{j\in\mathcal{P}_k}\boldsymbol{z}_j, \tag{72}$$

so

$$\boldsymbol{a}_k^{\mathrm{lin},*} = \frac{\gamma_k^+ + \gamma_k^-}{\lambda}\sum_{j\in\mathcal{P}_k}\boldsymbol{z}_j - \frac{\gamma_k^-}{\lambda}\sum_{j=1}^{N}\boldsymbol{z}_j. \tag{73}$$

By definition of $\bar{\boldsymbol{z}}_k$,

$$\sum_{j\in\mathcal{P}_k}\boldsymbol{z}_j = N_k\bar{\boldsymbol{z}}_k. \tag{74}$$

$$\sum_{j=1}^{N}\boldsymbol{z}_j = N\bar{\boldsymbol{z}}. \tag{75}$$

Substituting these identities and using

$$\gamma_k^+ + \gamma_k^- = 1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)} \tag{76}$$

yields

$$\boldsymbol{a}_k^{\mathrm{lin},*} = \frac{N_k}{\lambda}\left(1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)}\right)\bar{\boldsymbol{z}}_k - \frac{N}{\lambda}\left(\frac{1}{2(M-1)} + \frac{N_k}{2(N-1)}\right)\bar{\boldsymbol{z}}, \tag{77}$$

which is Eq. (67). □

D.3 Proof of Corollary 4.5

Corollary 4.5 (Prototype Decomposition for the Linear Contrastive Loss)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold. For each non-root k, define $\xi_k^{\text{lin}} := \frac{N\left(\frac{1}{2(M-1)}+\frac{N_k}{2(N-1)}\right)}{N_k\left(1+\frac{1}{2(M-1)}+\frac{1}{2(N-1)}\right)}$. Then every such k satisfies*

$$\boldsymbol{a}_k^{\text{lin},*} = \frac{N_k}{\lambda}\left(1+\frac{1}{2(M-1)}+\frac{1}{2(N-1)}\right)\left(\boldsymbol{\mu}_k + \bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\text{lin}}\left(\boldsymbol{\mu}_{\text{root}} + \bar{\boldsymbol{\varepsilon}}\right)\right). \tag{6}$$

Proof. The observed captions are path-consistent by the setup in Section 4.1, and the same setup has exactly c images per leaf. Under these hypotheses, Assumptions 4.3 and 4.4, and the decomposition in Assumption 4.1, we can apply Lemma C.10 and Corollary C.11. By Assumption 4.3, we also have $N_k > 0$ for every non-root node k, so we can apply Corollary D.2. Factor its empirical-mean expression using ξ_k^{lin} from Corollary 4.5, and substitute Eq. (48) with $\boldsymbol{b}_k = \boldsymbol{b} = \mathbf{0}$ to obtain Eq. (6). □

E Proofs of Intermediate Results in InfoNCE Loss Analysis

E.1 Proof of Lemma E.1 (Strong Convexity)

Lemma E.1 (Strong Convexity)**.** *The objective $\mathcal{L}(\boldsymbol{A})$ in Eq. (9) is λ-strongly convex in $\boldsymbol{A}$. Therefore, it has a unique global minimizer $\boldsymbol{A}^*$.*

Proof. First, each logit $\boldsymbol{a}_k^\top \boldsymbol{z}_j$ is linear in $\boldsymbol{A}$. Then, the term $-(\text{linear in } \boldsymbol{A}) + \log\sum\exp(\text{linear in } \boldsymbol{A})$ is convex as the composition of log-sum-exp with linear maps. Finally, composition with the sum over $j \in [N]$ and the regularizer $\frac{\lambda}{2}\|\boldsymbol{A}\|_F^2$ yield λ-strong convexity. □

E.2 Proof of Proposition E.2 (Stationarity Condition)

Proposition E.2 (Stationarity Condition)**.** *Define the softmax weights $q_k^{(j)}(\boldsymbol{A}) := e^{\boldsymbol{a}_k^\top \boldsymbol{z}_j} / \sum_{k'=1}^M e^{\boldsymbol{a}_{k'}^\top \boldsymbol{z}_j}$ and $r_{j'}^{(j)}(\boldsymbol{A}) := e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_{j'}} / \sum_{m=1}^N e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_m}$. The unique minimizer $\boldsymbol{A}^*$ of Eq. (9) satisfies, for each $k \in [M]$,*

$$\boldsymbol{a}_k^* = \frac{1}{\lambda}\left(\sum_{j:\, t_j = k} \boldsymbol{z}_j - \frac{1}{2}\sum_{j=1}^N q_k^{(j)}(\boldsymbol{A}^*)\boldsymbol{z}_j - \frac{1}{2}\sum_{j:\, t_j = k}\sum_{j'=1}^N r_{j'}^{(j)}(\boldsymbol{A}^*)\boldsymbol{z}_{j'}.\right) \tag{78}$$

Proof. First, we compute the image-to-text gradients. The total i2t loss is

$$\mathcal{L}^{\text{i2t}} = \sum_{j=1}^N \mathcal{L}_j^{\text{i2t}}, \tag{79}$$

where

$$\mathcal{L}_j^{\text{i2t}} = -\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j + \log\sum_{k'} e^{\boldsymbol{a}_{k'}^\top \boldsymbol{z}_j}. \tag{80}$$

Each term depends on $\boldsymbol{a}_k$ both through the numerator (when $t_j = k$) and the log-sum-exp denominator:

$$\begin{aligned}\nabla_{\boldsymbol{a}_k}\mathcal{L}_j^{\text{i2t}} &= -\mathbf{1}[t_j = k]\,\boldsymbol{z}_j + \frac{e^{\boldsymbol{a}_k^\top \boldsymbol{z}_j}}{\sum_{k'} e^{\boldsymbol{a}_{k'}^\top \boldsymbol{z}_j}}\,\boldsymbol{z}_j \\ &= \left(-\mathbf{1}[t_j = k] + q_k^{(j)}\right)\boldsymbol{z}_j.\end{aligned} \tag{81}$$

Summing over $j \in [N]$ gives

$$\nabla_{\boldsymbol{a}_k}\mathcal{L}^{\text{i2t}} = \sum_{j=1}^N\left(-\mathbf{1}[t_j = k] + q_k^{(j)}\right)\boldsymbol{z}_j = -\sum_{j:\, t_j = k}\boldsymbol{z}_j + \sum_{j=1}^N q_k^{(j)}\,\boldsymbol{z}_j. \tag{82}$$

Next, we compute the text-to-image gradients. The total t2i loss is

$$\mathcal{L}^{\text{t2i}} = \sum_{j=1}^{N} \mathcal{L}_j^{\text{t2i}}, \tag{83}$$

where

$$\mathcal{L}_j^{\text{t2i}} = -\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_j + \log \sum_{j'=1}^{N} e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_{j'}}. \tag{84}$$

Since $\boldsymbol{a}_k$ appears in $\mathcal{L}_j^{\text{t2i}}$ only when $t_j = k$:

$$\begin{aligned}\nabla_{\boldsymbol{a}_k} \mathcal{L}_j^{\text{t2i}} &= \mathbf{1}[t_j = k] \left(-\boldsymbol{z}_j + \frac{\sum_{j'=1}^{N} e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_{j'}} \boldsymbol{z}_{j'}}{\sum_{m=1}^{N} e^{\boldsymbol{a}_{t_j}^\top \boldsymbol{z}_m}} \right) \\ &= \mathbf{1}[t_j = k] \left(-\boldsymbol{z}_j + \sum_{j'=1}^{N} r_{j'}^{(j)} \boldsymbol{z}_{j'} \right). \end{aligned} \tag{85}$$

Summing over $j \in [N]$ gives

$$\nabla_{\boldsymbol{a}_k} \mathcal{L}^{\text{t2i}} = \sum_{j:\, t_j = k} \left(-\boldsymbol{z}_j + \sum_{j'=1}^{N} r_{j'}^{(j)} \boldsymbol{z}_{j'} \right). \tag{86}$$

Finally, we combine Eqs. (82) and (86) and add the regularization gradient $\lambda \boldsymbol{a}_k$. Since $\boldsymbol{A}^*$ is the unique minimizer, it satisfies

$$\nabla_{\boldsymbol{a}_k} \mathcal{L} = \frac{1}{2} \left(\nabla_{\boldsymbol{a}_k} \mathcal{L}^{\text{i2t}} + \nabla_{\boldsymbol{a}_k} \mathcal{L}^{\text{t2i}} \right) + \lambda \boldsymbol{a}_k^* = \mathbf{0}. \tag{87}$$

Substituting Eqs. (82) and (86) and rearranging yields Eq. (78). □

E.3 Proof of Proposition 4.7 (Large-Regularization Expansion)

Proposition 4.7 (Large-Regularization Expansion)**.** *As $\lambda \to \infty$, for any k with $N_k > 0$,*

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda} \bar{\boldsymbol{z}}_k - \frac{1}{\lambda} \left(\frac{N}{2M} + \frac{N_k}{2} \right) \bar{\boldsymbol{z}} + O(\lambda^{-2}). \tag{10}$$

Proof. Let $Z_{\max} := \max_{j \in [N]} \|\boldsymbol{z}_j\|$. Since $\sum_{k=1}^{M} q_k^{(j)}(\boldsymbol{A}^*) = 1$ and $\sum_{j'=1}^{N} r_{j'}^{(j)}(\boldsymbol{A}^*) = 1$, we obtain from Eq. (78)

$$\begin{aligned}\|\boldsymbol{a}_k^*\| &\le \frac{1}{\lambda} \left(N_k Z_{\max} + \frac{1}{2} \sum_{j=1}^{N} q_k^{(j)}(\boldsymbol{A}^*) Z_{\max} + \frac{1}{2} \sum_{j \in \mathcal{P}_k} \sum_{j'=1}^{N} r_{j'}^{(j)}(\boldsymbol{A}^*) Z_{\max} \right) \\ &\le \frac{1}{\lambda} \left(N_k + \frac{N}{2} + \frac{N_k}{2} \right) Z_{\max} = O(\lambda^{-1}). \end{aligned} \tag{88}$$

Therefore every logit $(\boldsymbol{a}_\ell^*)^\top \boldsymbol{z}_j$ is $O(\lambda^{-1})$, uniformly over $(\ell, j) \in [M] \times [N]$. Hence the i2t logit vectors

$$\mathbf{s}^{(j)} := \left((\boldsymbol{a}_1^*)^\top \boldsymbol{z}_j, \ldots, (\boldsymbol{a}_M^*)^\top \boldsymbol{z}_j \right) \in \mathbb{R}^M$$

and the t2i logit vectors

$$\mathbf{u}^{(j)} := \left((\boldsymbol{a}_{t_j}^*)^\top \boldsymbol{z}_{j'} \right)_{j' \in [N]} \in \mathbb{R}^N$$

have all entries' magnitudes of order $O(\lambda^{-1})$, and therefore satisfy $\|\mathbf{s}^{(j)}\|, \|\mathbf{u}^{(j)}\| = O(\lambda^{-1})$, uniformly over the relevant indices. In particular, these norms converge to 0 as $\lambda \to \infty$, so for all sufficiently large λ they lie in a fixed neighborhood of $\mathbf{0}$ where we can apply Lemma C.3. Applying that lemma with $K = M$ and $K = N$, respectively, gives

$$q_k^{(j)}(\boldsymbol{A}^*) = \frac{1}{M} + O(\lambda^{-1}), \qquad r_{j'}^{(j)}(\boldsymbol{A}^*) = \frac{1}{N} + O(\lambda^{-1}), \tag{89}$$

uniformly over the relevant indices. Substituting these expansions into Eq. (78) gives

$$\begin{aligned}\boldsymbol{a}_k^* &= \frac{1}{\lambda}\left(\sum_{j\in\mathcal{P}_k}\boldsymbol{z}_j - \frac{1}{2M}\sum_{j=1}^{N}\boldsymbol{z}_j - \frac{N_k}{2N}\sum_{j=1}^{N}\boldsymbol{z}_j\right) + O(\lambda^{-2}) \\ &= \frac{N_k}{\lambda}\bar{\boldsymbol{z}}_k - \frac{1}{\lambda}\left(\frac{N}{2M}+\frac{N_k}{2}\right)\bar{\boldsymbol{z}} + O(\lambda^{-2}),\end{aligned} \tag{90}$$

which is Eq. (10). □

E.4 Proof of Corollary 4.8 (Prototype Decomposition)

Proof. Recall the per-node global-mean coefficient

$$\xi_k^{\mathrm{nce}} := \frac{\frac{N}{2M}+\frac{N_k}{2}}{N_k}, \qquad k \in V\setminus\{\mathrm{root}\}. \tag{91}$$

The observed captions are path-consistent by the setup in Section 4.1, and the same setup has exactly c images per leaf. Under these hypotheses, Assumptions 4.3 and 4.4, and the decomposition in Assumption 4.1, we can apply Lemma C.10 and Corollary C.11. By Assumption 4.3, $N_k > 0$ for every non-root node k, so we can apply Proposition 4.7. Factor Eq. (10) using Eq. (91), and substitute Eq. (48) with $\boldsymbol{b}_k = \boldsymbol{b} = \mathbf{0}$ to obtain Eq. (11). □

E.5 Quantitative Remainder for the InfoNCE Expansion

The asymptotic expansion identifies the leading empirical means; transfer at a specified regularization level also requires a quantitative remainder bound.

Lemma E.3 (Quantitative remainder for the large-λ expansion)**.** *Let $Z_{\max} := \max_{j\in[N]}\|\boldsymbol{z}_j\|$, assume $N_k > 0$ for every non-root node k, and let $N_{\min} := \min_{k\in V\setminus\{\mathrm{root}\}} N_k$. For each non-root node $k \in V\setminus\{\mathrm{root}\}$, with ξ_k^{nce} as in Eq.* (91)*, define the* prototype-decomposition residual $\boldsymbol{r}_{k,\lambda} \in \mathbb{R}^d$ *by*

$$\boldsymbol{r}_{k,\lambda} := \frac{\lambda}{N_k}\,\boldsymbol{a}_k^* - \big(\bar{\boldsymbol{z}}_k - \xi_k^{\mathrm{nce}}\bar{\boldsymbol{z}}\big). \tag{92}$$

Under the hypotheses of Corollary 4.8, $\bar{\boldsymbol{z}}_k - \xi_k^{\mathrm{nce}}\bar{\boldsymbol{z}} = \widetilde{\boldsymbol{\mu}}_k + \bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\mathrm{nce}}\bar{\boldsymbol{\varepsilon}}$ with $\widetilde{\boldsymbol{\mu}}_k := \boldsymbol{\mu}_k - \xi_k^{\mathrm{nce}}\boldsymbol{\mu}_{\mathrm{root}}$, so that, equivalently,

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda}\Big(\widetilde{\boldsymbol{\mu}}_k + \bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\mathrm{nce}}\,\bar{\boldsymbol{\varepsilon}} + \boldsymbol{r}_{k,\lambda}\Big). \tag{93}$$

Then there exists a deterministic constant $C_{\mathrm{rem}} = C_{\mathrm{rem}}(M, N, N_{\min})$, depending only on M, N, and $N_{\min}$, such that for every $\lambda > 0$,

$$\max_{k\in V\setminus\{\mathrm{root}\}}\|\boldsymbol{r}_{k,\lambda}\| \le \frac{C_{\mathrm{rem}}\,Z_{\max}^3}{\lambda}. \tag{94}$$

Proof. We first bound the difference between the KKT identity and its uniform-softmax approximation. For every non-root node $k \in V\setminus\{\mathrm{root}\}$, define

$$\boldsymbol{\rho}_{k,\lambda} := -\frac{1}{2\lambda}\sum_{j=1}^{N}\left(q_k^{(j)}(\boldsymbol{A}^*) - \frac{1}{M}\right)\boldsymbol{z}_j - \frac{1}{2\lambda}\sum_{j\in\mathcal{P}_k}\sum_{j'=1}^{N}\left(r_{j'}^{(j)}(\boldsymbol{A}^*) - \frac{1}{N}\right)\boldsymbol{z}_{j'}. \tag{95}$$

Substituting Eq. (95) into the stationarity condition in Eq. (78) gives

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda}\bar{\boldsymbol{z}}_k - \frac{1}{\lambda}\left(\frac{N}{2M}+\frac{N_k}{2}\right)\bar{\boldsymbol{z}} + \boldsymbol{\rho}_{k,\lambda}. \tag{96}$$

From Eq. (78) and the identities $\sum_k q_k^{(j)}(\boldsymbol{A}^*) = 1$, $\sum_{j'} r_{j'}^{(j)}(\boldsymbol{A}^*) = 1$, we have

$$\max_{\ell\in[M]}\|\boldsymbol{a}_\ell^*\| \le \frac{1}{\lambda}\left(N + \tfrac{N}{2} + \tfrac{N}{2}\right)Z_{\max} = \frac{2N\,Z_{\max}}{\lambda}. \tag{97}$$

For each image index $j \in [N]$, each entry of the i2t logit vector $\mathbf{s}^{(j)}$ has magnitude at most $\|\boldsymbol{a}_\ell^*\| \, \|\boldsymbol{z}_j\| \le 2NZ_{\max}^2/\lambda$. For each $j \in [N]$, each entry of the t2i logit vector $\mathbf{u}^{(j)}$ has the same upper bound. Hence

$$\|\mathbf{s}^{(j)}\| \le \sqrt{M} \cdot \frac{2N\, Z_{\max}^2}{\lambda}, \qquad \|\mathbf{u}^{(j)}\| \le \sqrt{N} \cdot \frac{2N\, Z_{\max}^2}{\lambda}. \tag{98}$$

Applying Lemma C.2 with $K = M$ and $K = N$, respectively, gives

$$\left| q_k^{(j)}(\boldsymbol{A}^*) - \tfrac{1}{M} \right| \le 2\, \|\mathbf{s}^{(j)}\| \le c_1(M,N)\, \frac{Z_{\max}^2}{\lambda}, \tag{99}$$

$$\left| r_{j'}^{(j)}(\boldsymbol{A}^*) - \tfrac{1}{N} \right| \le 2\, \|\mathbf{u}^{(j)}\| \le c_1(M,N)\, \frac{Z_{\max}^2}{\lambda}, \tag{100}$$

uniformly over the relevant indices, where $c_1(M,N) := 4N\sqrt{M+N}$. Using the fact that $\|\boldsymbol{z}_j\| \le Z_{\max}$ and Eqs. (99)–(100),

$$\|\boldsymbol{\rho}_{k,\lambda}\| \le \frac{1}{2\lambda}\Big(N + N_k\, N\Big) \cdot c_1(M,N) \frac{Z_{\max}^2}{\lambda} \cdot Z_{\max} \le \frac{c_2(M,N)\, Z_{\max}^3}{\lambda^2}, \tag{101}$$

with $c_2(M,N) := N(1+N)\, c_1(M,N)/2$.

By Eq. (91), the coefficient of $\bar{\boldsymbol{z}}$ in Eq. (96) equals $N_k \xi_k^{\mathrm{nce}}/\lambda$, and therefore we can rewrite Eq. (96) as

$$\boldsymbol{a}_k^* = \frac{N_k}{\lambda}\, (\bar{\boldsymbol{z}}_k - \xi_k^{\mathrm{nce}} \bar{\boldsymbol{z}}) + \boldsymbol{\rho}_{k,\lambda}. \tag{102}$$

Comparing this identity with the definition of $\boldsymbol{r}_{k,\lambda}$ in Eq. (92) gives

$$\frac{N_k}{\lambda} \boldsymbol{r}_{k,\lambda} = \boldsymbol{\rho}_{k,\lambda}, \tag{103}$$

and therefore $\|\boldsymbol{r}_{k,\lambda}\| \le c_2(M,N) Z_{\max}^3/(N_k\lambda)$. Since $N_k \ge N_{\min}$ for every non-root node $k \in V \setminus \{\mathrm{root}\}$,

$$\max_{k \in V \setminus \{\mathrm{root}\}} \|\boldsymbol{r}_{k,\lambda}\| \le \frac{C_{\mathrm{rem}}\, Z_{\max}^3}{\lambda}, \tag{104}$$

where $C_{\mathrm{rem}}(M,N,N_{\min}) := \frac{c_2(M,N)}{N_{\min}}$. □

F Shared Transfer Argument

For $\lambda > 0$, write $\{\boldsymbol{a}_k\}$ for the minimizer under consideration, $\boldsymbol{A}^{\mathrm{lin},*}$ of Eq. (5) for the linear loss and $\boldsymbol{A}^*$ of Eq. (9) for InfoNCE. For both losses $\boldsymbol{a}_k$ is a positive multiple of the empirical-mean difference $\bar{\boldsymbol{z}}_k - \xi_k \bar{\boldsymbol{z}}$: exactly so for the linear loss, and up to a remainder bounded by Lemma E.3 for InfoNCE. The two transfer proofs therefore share the same steps, which we present next. We allow a caption bias throughout, so that the main theorems are the special case of zero bias and the relaxations of Appendix L need only a bound on it.

In Lemma F.1 below, we need only a bound on the perturbation in a representation $\boldsymbol{a}_k = c_k\,(\boldsymbol{\mu}_k + \text{perturbation})$ with $c_k > 0$. It has three components, the caption bias, the sampling noise, and the finite regularization, which we define in turn below.

Recall from Definition C.9 that $\boldsymbol{b}_k = \bar{\boldsymbol{\mu}}_k - \boldsymbol{\mu}_k$ and $\boldsymbol{b} = \bar{\boldsymbol{\mu}} - \boldsymbol{\mu}_{\mathrm{root}}$, the gaps between the caption-averaged prototypes and the true ones; by Eq. (48) the bias contributes $\boldsymbol{b}_k - \xi_k \boldsymbol{b}$ to the empirical-mean difference. The transfer bound uses that contribution only through an upper bound on its largest norm, so for fixed observed captions with non-root coverage and a fixed family of coefficients $\{\xi_k \in \mathbb{R}\}_{k \in V \setminus \{\mathrm{root}\}}$, we call $\delta_{\mathrm{bias}} \ge 0$ a *caption bias bound* if

$$\max_{k \ne \mathrm{root}} \|\boldsymbol{b}_k - \xi_k\, \boldsymbol{b}\| \le \delta_{\mathrm{bias}}. \tag{105}$$

The smallest caption bias bound is the left-hand side itself. We allow larger values so that we can apply Lemma F.1 directly with an upper bound on this maximum in Appendix L.

The error terms D_ϵ and $D_\epsilon^{\mathrm{nce}}$ of the main theorems carry over unchanged. Throughout, ξ_k are the coefficients of the loss under consideration, from Corollary 4.5 for the linear loss and Eq. (91) for

InfoNCE, and $\xi_{\max}$, $N_{\min}$, and δ_{root} are evaluated at the observed captions and those coefficients, and δ_{bias} is a caption bias bound for them. Write D_ϵ for the expression in Eq. (7) and $D_\epsilon^{\mathrm{nce}}$ for its InfoNCE counterpart defined before Theorem 4.9, using the universal constant from Lemma C.12. Both expressions are defined for any observed captions with non-root coverage, regardless of caption symmetry, so we use the same D_ϵ and $D_\epsilon^{\mathrm{nce}}$ in the biased setting here and in the symmetric setting of the main theorems.

For InfoNCE we also choose a regularization threshold that makes the large-λ remainder no larger than $D_\epsilon^{\mathrm{nce}}$. For $\epsilon \in (0,1)$ and $D_\epsilon^{\mathrm{nce}} > 0$, define

$$R_\epsilon := \max_{\ell \in V_{\mathrm{leaf}}} \|\boldsymbol{\mu}_\ell\| + C_{\max}\sigma\sqrt{d + \log(4N/\epsilon)}, \qquad \lambda_0(\epsilon) := \frac{C_{\mathrm{rem}} R_\epsilon^3}{D_\epsilon^{\mathrm{nce}}}, \tag{106}$$

where $C_{\max} > 0$ is the universal constant from Lemma C.13 and $C_{\mathrm{rem}} = C_{\mathrm{rem}}(M, N, N_{\min})$ is the deterministic constant from Lemma E.3. In particular, R_ϵ is independent of the captions, whereas $\lambda_0(\epsilon)$ depends on the observed captions through C_{rem} and $D_\epsilon^{\mathrm{nce}}$.

Recall the minimum non-root prototype norm $\rho_{\min} := \min_{k \neq \mathrm{root}} \|\boldsymbol{\mu}_k\|$, which sets the scale of the threshold below. For $\epsilon \in (0,1)$, the *total error term* $D_\epsilon^{\mathrm{bias}}$ and the *margin threshold* $\tau_\epsilon^{\mathrm{bias}}$ it induces are

$$D_\epsilon^{\mathrm{bias}} := \begin{cases} D_\epsilon + \delta_{\mathrm{bias}}, & \text{linear contrastive loss,} \\ 2D_\epsilon^{\mathrm{nce}} + \delta_{\mathrm{bias}}, & \text{InfoNCE loss,} \end{cases} \qquad \tau_\epsilon^{\mathrm{bias}} := \frac{8D_\epsilon^{\mathrm{bias}}}{\rho_{\min}}. \tag{107}$$

The caption bias enters additively in both cases, and the factor 2 in the InfoNCE case appears because $D_\epsilon^{\mathrm{nce}}$ bounds each of two terms, the perturbation from the empirical means and the large-λ remainder.

In Lemma F.1, we assume neither Assumption 4.3 nor Assumption 4.4, and nothing about the global margin $\gamma_{\mathcal{HAS}}$; the captions enter only through δ_{bias}.

Lemma F.1 ($\mathcal{HAS}$ transfer under biased captions)**.** *Suppose Assumption 4.1 (sub-Gaussian prototype variation) holds, $\rho_{\min} > 0$, and the observed captions are deterministic with $N_k > 0$ for every non-root node k. Fix $\epsilon \in (0,1)$, $\lambda > 0$, and a caption bias bound δ_{bias}, and suppose $D_\epsilon^{\mathrm{bias}} < \rho_{\min}/4$; in the InfoNCE case suppose also $D_\epsilon^{\mathrm{nce}} > 0$ and $\lambda \geq \lambda_0(\epsilon)$. Then, with probability at least $1-\epsilon$, all of the following hold simultaneously:*

(i) $\boldsymbol{a}_k \neq \mathbf{0}$ *for every non-root node k;*

(ii) every admissible triplet (u, v, w) with $\gamma_{uvw} > \tau_\epsilon^{\mathrm{bias}}$ satisfies $\cos(\boldsymbol{a}_u, \boldsymbol{a}_v) > \cos(\boldsymbol{a}_u, \boldsymbol{a}_w)$;

(iii) $\mathcal{HAS}$-$\mathrm{Viol}^{\mathrm{txt}}(u) \leq \mathcal{HAS}$-$\mathrm{Viol}^{\mathrm{img}}_{\tau_\epsilon^{\mathrm{bias}}}(u)$ for every non-root non-leaf node u, with $\mathcal{HAS}$-$\mathrm{Viol}^{\mathrm{txt}}(u)$ computed on $\{\boldsymbol{a}_k\}_{k \neq \mathrm{root}}$.

Proof. **Step 1: Decompose the optimal embeddings.** Fix the observed captions and the coefficients for the loss under consideration. For every non-root node k, set

$$\boldsymbol{e}_k := -\xi_k \boldsymbol{\mu}_{\mathrm{root}} + \bar{\boldsymbol{\varepsilon}}_k - \xi_k \bar{\boldsymbol{\varepsilon}}, \qquad \widetilde{\boldsymbol{b}}_k := \boldsymbol{b}_k - \xi_k \boldsymbol{b}. \tag{108}$$

Under coverage, we apply Corollary D.2 for the linear loss and Lemma E.3 for InfoNCE to write $\boldsymbol{a}_k$ as a positive multiple of $\bar{\boldsymbol{z}}_k - \xi_k \bar{\boldsymbol{z}}$ plus the remainder. Under Assumption 4.1, every sample satisfies $\boldsymbol{z}_j = \boldsymbol{\mu}_{y_j} + \boldsymbol{\varepsilon}_j$, which is the form required by Lemma C.10. Substituting Eq. (48) into those empirical-mean expressions gives

$$\boldsymbol{a}_k = c_k \left(\boldsymbol{\mu}_k + \boldsymbol{e}_k + \widetilde{\boldsymbol{b}}_k + \boldsymbol{r}_{k,\lambda} \right), \tag{109}$$

where $c_k = \frac{N_k}{\lambda}\left(1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)}\right)$ and $\boldsymbol{r}_{k,\lambda} = \mathbf{0}$ for the linear loss, whereas $c_k = N_k/\lambda$ and $\boldsymbol{r}_{k,\lambda}$ is defined by Eq. (92) for InfoNCE. In both cases, coverage and $\lambda > 0$ give $c_k > 0$, and by Eq. (105), $\max_{k \neq \mathrm{root}} \|\widetilde{\boldsymbol{b}}_k\| \leq \delta_{\mathrm{bias}}$.

Step 2: Bound the stochastic deviation. For a failure probability $p \in (0,1)$, define

$$\eta_p := C\sigma \left(\sqrt{\frac{d + \log(M-1) + \log(4/p)}{N_{\min}}} + \xi_{\max} \sqrt{\frac{d + \log(4/p)}{N}} \right), \tag{110}$$

and let $\mathcal{E}_p := \{\max_{k\neq\text{root}} \|\bar{\boldsymbol{\varepsilon}}_k - \xi_k \bar{\boldsymbol{\varepsilon}}\| \le \eta_p\}$. The observed captions are deterministic and have coverage, so the index sets $\mathcal{P}_k$ are fixed and nonempty, and the variations $\boldsymbol{\varepsilon}_j$ are independent, centered, and sub-Gaussian by Assumption 4.1. Apply Lemma C.12 with $\mathcal{K} = V \setminus \{\text{root}\}$, $I_k = \mathcal{P}_k$ for every $k \in \mathcal{K}$, the fixed coefficients ξ_k, and $u = \log(4/p)$. Since $|\mathcal{K}| = M - 1$ and $\min_{k\in\mathcal{K}} |I_k| = N_{\min}$, we obtain $\Pr(\mathcal{E}_p) \ge 1 - p$ from Eq. (51). On $\mathcal{E}_p$, Eq. (108) and the triangle inequality give

$$\max_{k\neq\text{root}} \|\boldsymbol{e}_k\| \le \delta_{\text{root}} + \eta_p. \tag{111}$$

For the linear loss, choose $p = \epsilon$. Then $\delta_{\text{root}} + \eta_\epsilon = D_\epsilon$ and the remainder is zero, so the total perturbation in Eq. (109) is at most $D_\epsilon + \delta_{\text{bias}} = D_\epsilon^{\text{bias}}$ with probability at least $1 - \epsilon$.

Step 3: Control the InfoNCE remainder. For InfoNCE, choose $p = \epsilon/2$ in Step 2, so $\delta_{\text{root}} + \eta_{\epsilon/2} = D_\epsilon^{\text{nce}}$. Under Assumption 4.1, we can also apply Lemma C.13 with failure probability $p = \epsilon/2$. Thus $\mathcal{F}_\epsilon := \{\max_{j\in[N]} \|\boldsymbol{z}_j\| \le R_\epsilon\}$ has probability at least $1 - \epsilon/2$. On $\mathcal{F}_\epsilon$, by Lemma E.3 and Eq. (106), for every $\lambda \ge \lambda_0(\epsilon)$,

$$\max_{k\neq\text{root}} \|\boldsymbol{r}_{k,\lambda}\| \le \frac{C_{\text{rem}} R_\epsilon^3}{\lambda} \le D_\epsilon^{\text{nce}}. \tag{112}$$

The union bound gives $\Pr(\mathcal{E}_{\epsilon/2} \cap \mathcal{F}_\epsilon) \ge 1 - \epsilon$; independence of these events is not needed. On their intersection, the total perturbation is at most $2D_\epsilon^{\text{nce}} + \delta_{\text{bias}} = D_\epsilon^{\text{bias}}$.

Step 4: Apply the per-triplet transfer bound. For either loss, we have established an event of probability at least $1 - \epsilon$ on which

$$\max_{k\neq\text{root}} \|\boldsymbol{e}_k + \widetilde{\boldsymbol{b}}_k + \boldsymbol{r}_{k,\lambda}\| \le D_\epsilon^{\text{bias}} < \rho_{\min}/4 < \rho_{\min}. \tag{113}$$

Apply Lemma C.8 with reference vectors $\boldsymbol{\nu}_k = \boldsymbol{\mu}_k$, the positive scalings c_k in Eq. (109), and the total perturbations $\boldsymbol{e}_k + \widetilde{\boldsymbol{b}}_k + \boldsymbol{r}_{k,\lambda}$. With $\eta = D_\epsilon^{\text{bias}}$ its threshold is $\tau = 8D_\epsilon^{\text{bias}}/\rho_{\min} = \tau_\epsilon^{\text{bias}}$, so parts (i), (ii), and (iii) of that lemma are claims (i), (ii), and (iii). □

G Proof of Hierarchical Angular Separation Transfer for the Linear Contrastive Loss

Theorem 4.6 (*$\mathcal{HAS}$* Transfer for the Linear Contrastive Loss)**.** *Suppose Assumption 4.1 (sub-Gaussian prototype variation), Assumption 4.3 (leaf-uniform caption coverage), and Assumption 4.4 (prototype consistency) hold, and suppose $\rho_{\min} > 0$. Let $N_{\min} := \min_{k\in V\setminus\{\text{root}\}} N_k$ be the minimum non-root caption count. There exists a universal constant $C > 0$ such that the following holds for every $\epsilon \in (0, 1)$. Define the combined error term*

$$D_\epsilon := \delta_{\text{root}} + C\sigma\left(\sqrt{\tfrac{d+\log(M-1)+\log(4/\epsilon)}{N_{\min}}} + \xi_{\max}^{\text{lin}}\sqrt{\tfrac{d+\log(4/\epsilon)}{N}}\right). \tag{7}$$

If $D_\epsilon < \rho_{\min}/4$, then, with probability at least $1-\epsilon$, every non-root non-leaf anchor node u satisfies

$$\mathcal{HAS}\text{-Viol}^{\text{txt}}(u) \le \mathcal{HAS}\text{-Viol}^{\text{img}}_{\tau_\epsilon}(u), \qquad \tau_\epsilon := \frac{8D_\epsilon}{\rho_{\min}}. \tag{8}$$

Proof. **Step 1: Establish zero caption bias.** The observed captions are path-consistent by the setup in Section 4.1, and the same setup has exactly c images per leaf. By Corollary C.11 together with Assumptions 4.3 and 4.4, $\boldsymbol{b}_k = \boldsymbol{0}$ for every non-root node k and $\boldsymbol{b} = \boldsymbol{0}$. Therefore, by Eq. (105), $\delta_{\text{bias}} = 0$ is a caption bias bound for the linear-loss coefficients.

Step 2: Bound the error term. We obtain non-root coverage from Assumption 4.3 and the required variation model from Assumption 4.1, and we assume $\rho_{\min} > 0$ and $D_\epsilon < \rho_{\min}/4$ in the theorem. With $\delta_{\text{bias}} = 0$, we have $D_\epsilon^{\text{bias}} = D_\epsilon < \rho_{\min}/4$ by Eq. (107).

Step 3: Apply the shared transfer lemma. We can apply Lemma F.1 with $\tau_\epsilon^{\text{bias}} = 8D_\epsilon/\rho_{\min} = \tau_\epsilon$. Its part (iii) gives Eq. (8) with probability at least $1-\epsilon$; parts (i) and (ii) also establish nonzero optimal embeddings and preservation of every admissible triplet with margin greater than τ_ϵ. □

H Proof of Hierarchical Angular Separation Transfer for the InfoNCE Loss

Theorem 4.9 (*$\mathcal{HAS}$* Transfer for InfoNCE)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold and $\rho_{\min} > 0$, and fix $\epsilon \in (0,1)$. If $0 < D_\epsilon^{\mathrm{nce}} < \rho_{\min}/8$, then there is a deterministic threshold $\lambda_0(\epsilon) > 0$ such that, for every $\lambda \geq \lambda_0(\epsilon)$, with probability at least $1-\epsilon$, every non-root non-leaf anchor node u satisfies Eq.* (8) *with τ_ϵ replaced by $\tau_\epsilon^{\mathrm{nce}} := 16 D_\epsilon^{\mathrm{nce}}/\rho_{\min}$.*

Proof. **Step 1: Establish zero caption bias.** The observed captions are path-consistent by the setup in Section 4.1, and the same setup has exactly c images per leaf. By Corollary C.11 together with Assumptions 4.3 and 4.4, $\boldsymbol{b}_k = \mathbf{0}$ for every non-root node k and $\boldsymbol{b} = \mathbf{0}$. Therefore, by Eq. (105), $\delta_{\mathrm{bias}} = 0$ is a caption bias bound for the InfoNCE coefficients.

Step 2: Bound the error term. We obtain non-root coverage from Assumption 4.3 and the required variation model from Assumption 4.1. The theorem hypothesis $0 < D_\epsilon^{\mathrm{nce}} < \rho_{\min}/8$ gives $D_\epsilon^{\mathrm{bias}} = 2D_\epsilon^{\mathrm{nce}} < \rho_{\min}/4$ and makes the deterministic threshold in Eq. (106) positive and finite.

Step 3: Apply the shared transfer lemma. For every $\lambda \geq \lambda_0(\epsilon)$, we can therefore apply Lemma F.1 with $\tau_\epsilon^{\mathrm{bias}} = 16 D_\epsilon^{\mathrm{nce}}/\rho_{\min} = \tau_\epsilon^{\mathrm{nce}}$. Its part (iii) gives Eq. (8) at $\tau_\epsilon^{\mathrm{nce}}$ with probability at least $1-\epsilon$; parts (i) and (ii) also establish nonzero optimal embeddings and preservation of every admissible triplet with margin greater than $\tau_\epsilon^{\mathrm{nce}}$. □

I Step-by-step construction of a Hierarchical Concept Embedding

In this section, we provide an explicit construction for the hierarchical prototypes $\{\boldsymbol{\mu}_k\}_{k\in V}$ used in our theoretical analysis, introduced by Nguyen et al. [9]. Throughout this section the tree $\mathcal{T}$ of Section 3.1 is balanced with depth $L \geq 2$ and branching factor $b \geq 2$, so every non-leaf node has b children and there are $m = b^L$ leaves. The construction has the following properties: (i) the displacement $\boldsymbol{\mu}_k - \boldsymbol{\mu}_p$ from each strict ancestor p to a non-root node k is orthogonal to $\boldsymbol{\mu}_p$, (ii) sibling prototypes $\{\boldsymbol{\mu}_{u^{(j)}}\}_{j=1}^b$ form a regular simplex around their parent $\boldsymbol{\mu}_u$, and (iii) every child $\boldsymbol{\mu}_{u^{(j)}}$ is located in a fixed half-angle cone around its parent $\boldsymbol{\mu}_u$. The prototypes satisfy the averaging property in Lemma C.4, while the angle schedule in Proposition I.1 also ensures a positive $\mathcal{HAS}$ margin.

Fix an internal node $u \in V$ at depth $l := d(u) \geq 0$ with children $u^{(1)}, \ldots, u^{(b)}$, and write $\pi_0(u), \pi_1(u), \ldots, \pi_l(u)$ for the ancestors of u along the root-to-u path, with $\pi_l(u) = u$. Assume the ancestor prototypes $\boldsymbol{\mu}_{\pi_0(u)}, \ldots, \boldsymbol{\mu}_{\pi_l(u)}$ have already been constructed and stack them into the matrix

$$\boldsymbol{A}_u := \begin{bmatrix} \boldsymbol{\mu}_{\pi_0(u)} & \boldsymbol{\mu}_{\pi_1(u)} & \cdots & \boldsymbol{\mu}_{\pi_l(u)} \end{bmatrix} \in \mathbb{R}^{d\times(l+1)}. \tag{114}$$

The construction below produces the b child prototypes $\{\boldsymbol{\mu}_{u^{(j)}}\}_{j=1}^b$ and proceeds inductively starting from any nonzero root prototype $\boldsymbol{\mu}_{\mathrm{root}} \in \mathbb{R}^d$.

I.1 Geometric requirements

The child prototypes are required to satisfy the following three conditions, where $\theta_l \in (0, \pi/2)$ is a fixed cone half-angle for depth-l children.

(R1) Hierarchical orthogonality. For every ancestor $\pi_k(u)$, $k = 0, \ldots, l$, and every child $j = 1, \ldots, b$,

$$\big(\boldsymbol{\mu}_{u^{(j)}} - \boldsymbol{\mu}_{\pi_k(u)}\big)^\top \boldsymbol{\mu}_{\pi_k(u)} = 0. \tag{115}$$

(R2) Regular $(b-1)$-simplex on siblings. With the parent $\boldsymbol{\mu}_u$ as the simplex centroid,

$$\big(\boldsymbol{\mu}_{u^{(j)}} - \boldsymbol{\mu}_u\big)^\top \big(\boldsymbol{\mu}_{u^{(k)}} - \boldsymbol{\mu}_u\big) = \begin{cases} \lambda_l^2, & j = k, \\ -\lambda_l^2/(b-1), & j \neq k, \end{cases} \tag{116}$$

for a scale $\lambda_l > 0$ chosen below.

(R3) Cone half-angle around the parent. For every $j = 1, \ldots, b$,

$$\angle\big(\boldsymbol{\mu}_{u^{(j)}}, \boldsymbol{\mu}_u\big) = \theta_l. \tag{117}$$

I.2 Feasible subspace and depth–dimension condition

The ancestor orthogonality conditions in (R1) intersect in the affine subspace

$$\mathcal{V}_u := \{\boldsymbol{x} \in \mathbb{R}^d \,:\, \boldsymbol{A}_u^\top \boldsymbol{x} = \boldsymbol{z}_u\}, \qquad \boldsymbol{z}_u := \left[\|\boldsymbol{\mu}_{\pi_0(u)}\|^2, \ldots, \|\boldsymbol{\mu}_{\pi_l(u)}\|^2\right]^\top. \tag{118}$$

When the ancestor prototypes are linearly independent, $\dim \mathcal{V}_u = d - (l+1)$. Embedding a regular $(b-1)$-simplex inside $\mathcal{V}_u$ for every internal node up to depth $L-1$ therefore requires the depth–dimension condition

$$d \;\geq\; L + b - 1, \tag{119}$$

which makes the trade-off explicit: L dimensions are absorbed by the ancestor-orthogonality constraints down to depth $L-1$, while the regular $(b-1)$-simplex of siblings requires $b-1$ additional dimensions [9].

Limits on hierarchy depth. Eq. (119) is necessary but not sufficient. Because each child is separated from its parent by a fixed angle θ_l (see (R3)), the children's cones must be nested inside their parent's cone. This, in turn, forces the half-angles $\{\theta_l\}_{l=0}^{L-1}$ to shrink monotonically with depth and to satisfy a recursive feasibility constraint coupling θ_l, θ_{l-1}, and the branching factor b. As L increases, the admissible cone angles collapse and the inter-prototype margin $\gamma_{\mathcal{HAS}}$ degrades, establishing an effective upper bound on the depth L for a fixed embedding dimension d while preserving $\mathcal{HAS}$. For the full analysis on the precise depth-angle-dimension trade-off and the resulting bound on L, we refer the reader to Nguyen et al. [9]. The dimension condition in Eq. (119) makes the orthogonal simplex construction feasible, but a positive $\mathcal{HAS}$ margin also requires control of the angles across depths. In Proposition I.1, we give a sufficient decay schedule for this construction.

I.3 Construction

We construct $\{\boldsymbol{\mu}_{u^{(j)}}\}_{j=1}^b$ in five steps.

1. **Origin in $\mathcal{V}_u$ [for (R1)].** Take the parent itself, $\boldsymbol{g}_u := \boldsymbol{\mu}_u$. Hierarchical orthogonality of $\boldsymbol{\mu}_u$ to all its ancestors (inductively) gives $\boldsymbol{\mu}_u^\top \boldsymbol{\mu}_{\pi_k(u)} = \|\boldsymbol{\mu}_{\pi_k(u)}\|^2$ for every $k \leq l$, so $\boldsymbol{g}_u \in \mathcal{V}_u$.
2. **Orthonormal basis of the offset directions [for (R1)].** Because $d - l - 1 \geq b - 1$ for every internal node at depth $l \leq L-1$ by Eq. (119), choose $\boldsymbol{U}_u \in \mathbb{R}^{d\times(b-1)}$ with $\boldsymbol{A}_u^\top \boldsymbol{U}_u = \boldsymbol{0}$ and $\boldsymbol{U}_u^\top \boldsymbol{U}_u = I_{b-1}$, e.g. by taking any $b-1$ left singular vectors spanning $\ker(\boldsymbol{A}_u^\top)$. Any vector in $\boldsymbol{g}_u + \mathrm{range}(\boldsymbol{U}_u)$ lies in $\mathcal{V}_u$ and therefore satisfies (R1).
3. **Canonical regular simplex in $\mathbb{R}^{b-1}$ [for (R2)].** Choose vectors $\tilde{\boldsymbol{d}}_1, \ldots, \tilde{\boldsymbol{d}}_b \in \mathbb{R}^{b-1}$ forming a centered regular simplex:

$$\sum_{j=1}^b \tilde{\boldsymbol{d}}_j = \boldsymbol{0}, \qquad \tilde{\boldsymbol{d}}_j^\top \tilde{\boldsymbol{d}}_k = \mathbf{1}[j=k] - \frac{1}{b}, \qquad j,k \in [b]. \tag{120}$$

4. **Scale to enforce the cone condition [for (R3)].** Set

$$\lambda_l \;:=\; \|\boldsymbol{\mu}_u\| \tan\theta_l, \qquad \boldsymbol{d}_j \;:=\; \tfrac{\lambda_l}{\sqrt{(b-1)/b}}\, \tilde{\boldsymbol{d}}_j, \qquad j \in [b], \tag{121}$$

   so that $\|\boldsymbol{d}_j\| = \lambda_l$ and $\boldsymbol{d}_j^\top \boldsymbol{d}_k = -\lambda_l^2/(b-1)$ for $j \neq k$, satisfying (R2).
5. **Embed and translate.**

$$\boldsymbol{\mu}_{u^{(j)}} \;:=\; \boldsymbol{\mu}_u + \boldsymbol{U}_u\, \boldsymbol{d}_j, \qquad j = 1, \ldots, b. \tag{122}$$

I.4 Properties

Compatibility with the assumptions. Iterating the construction from the root to all leaves gives a set of prototypes $\{\boldsymbol{\mu}_k\}_{k\in V}$ where (i) for every non-root node k and strict ancestor p, the displacement $\boldsymbol{\mu}_k - \boldsymbol{\mu}_p$ is orthogonal to $\boldsymbol{\mu}_p$, and (ii) the children of any internal node form a centered regular simplex around their parent. Property (i) yields $\|\boldsymbol{\mu}_k\| > 0$ for every non-root k provided the depth-wise scales $\|\boldsymbol{\mu}_u\| \tan\theta_l$ are positive, so $\rho_{\min} > 0$. Under the angle schedule in Proposition I.1, the prototypes also have $\gamma_{\mathcal{HAS}} > 0$. Property (ii) is exactly the centered-simplex hypothesis used

in Lemma C.4, so the descendant average of leaf prototypes equals the ancestor prototype. As this holds for every internal node, the resulting set of prototypes is consistent with Assumption 4.4.

The centroid property holds for any choice of the angles, whereas a positive $\mathcal{HAS}$ margin needs separation between descendants and off-branch nodes.

Proposition I.1 (Positive $\mathcal{HAS}$ margin under geometric angle decay)**.** *Suppose the prototypes are constructed as in Appendix I.3 with* $0 < \theta_0 < \pi/2$ *and some* q *such that*

$$0 < q \leq 1/4, \tag{123}$$

$$\theta_{r+1} \leq q\theta_r \quad (r \in \{0, \ldots, L-2\}). \tag{124}$$

Then the global margin $\gamma_{\mathcal{HAS}}$ *of Eq.* (40) *is positive, so the prototype family satisfies* $\mathcal{HAS}$*.*

Proof. Fix an admissible triplet (u, v, w), let p be the lowest common ancestor of u and w, and write $l := d(p)$. The nodes u and w lie below distinct children a and a' of p. By Eqs. (116) and (117), their sibling angle $\alpha_l := \angle(\boldsymbol{\mu}_a, \boldsymbol{\mu}_{a'})$ satisfies

$$\begin{aligned}
\cos\alpha_l &= \frac{\boldsymbol{\mu}_a^\top \boldsymbol{\mu}_{a'}}{\|\boldsymbol{\mu}_a\|\|\boldsymbol{\mu}_{a'}\|} && \text{(definition of } \alpha_l\text{)} \\
&= \frac{\|\boldsymbol{\mu}_p\|^2 + (\boldsymbol{\mu}_a - \boldsymbol{\mu}_p)^\top(\boldsymbol{\mu}_{a'} - \boldsymbol{\mu}_p)}{\|\boldsymbol{\mu}_p\|^2 + \lambda_l^2} && \text{(by Eqs. (115) and (116))} \\
&= \frac{\|\boldsymbol{\mu}_p\|^2 - \lambda_l^2/(b-1)}{\|\boldsymbol{\mu}_p\|^2 + \lambda_l^2} && \text{(by Eq. (116))} \\
&= \frac{1 - \lambda_l^2/((b-1)\|\boldsymbol{\mu}_p\|^2)}{1 + \lambda_l^2/\|\boldsymbol{\mu}_p\|^2} && \text{(dividing by } \|\boldsymbol{\mu}_p\|^2\text{)} \\
&= \frac{1 - \tan^2\theta_l/(b-1)}{1 + \tan^2\theta_l} && \text{(by Eq. (121))} \\
&= \cos^2\theta_l - \frac{\sin^2\theta_l}{b-1} && \text{(multiplying by } \cos^2\theta_l\text{)} \\
&< \cos\theta_l && \text{(since } 0 < \cos\theta_l < 1 \text{ and } b \geq 2\text{)} \\
\iff \alpha_l &> \theta_l && \text{(since cosine decreases on } [0,\pi]\text{).} \qquad (125)
\end{aligned}$$

Set $T_l := \sum_{j=l+1}^{L-1} \theta_j$. Applying the angle triangle inequality first through u and then through w gives

$$\begin{aligned}
\alpha_l &\leq \angle(\boldsymbol{\mu}_a, \boldsymbol{\mu}_u) + \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_{a'}) \\
&\leq \angle(\boldsymbol{\mu}_a, \boldsymbol{\mu}_u) + \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_w) + \angle(\boldsymbol{\mu}_w, \boldsymbol{\mu}_{a'}).
\end{aligned}$$

By Eq. (117) and repeated angle triangle inequalities along the three ancestor–descendant paths,

$$\begin{aligned}
\angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_a) &\leq \textstyle\sum_{j=l+1}^{d(u)-1} \theta_j \leq T_l, \\
\angle(\boldsymbol{\mu}_w, \boldsymbol{\mu}_{a'}) &\leq \textstyle\sum_{j=l+1}^{d(w)-1} \theta_j \leq T_l, \\
\angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_v) &\leq \textstyle\sum_{j=d(u)}^{d(v)-1} \theta_j \leq T_l.
\end{aligned}$$

Rearranging the sibling-angle bound and applying these path bounds gives

$$\begin{aligned}
\angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_w) &\geq \alpha_l - \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_a) - \angle(\boldsymbol{\mu}_w, \boldsymbol{\mu}_{a'}) \\
&\geq \alpha_l - T_l - \angle(\boldsymbol{\mu}_w, \boldsymbol{\mu}_{a'}) && \text{(since } \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_a) \leq T_l\text{)} \\
&\geq \alpha_l - 2T_l && \text{(since } \angle(\boldsymbol{\mu}_w, \boldsymbol{\mu}_{a'}) \leq T_l\text{)} \\
\angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_w) - \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_v) &\geq \alpha_l - 2T_l - \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_v) \\
&\geq \alpha_l - 3T_l && \text{(since } \angle(\boldsymbol{\mu}_u, \boldsymbol{\mu}_v) \leq T_l\text{).} \qquad (126)
\end{aligned}$$

It remains to show that $3T_l < \alpha_l$. Since $q > 0$ by Eq. (123), iterating Eq. (124) gives $\theta_{l+m} \leq q^m \theta_l$ for every $m \in \{1, \ldots, L-l-1\}$. Thus

$$\begin{aligned}
3T_l &= 3 \sum_{j=l+1}^{L-1} \theta_j && \text{(definition of } T_l\text{)} \\
&\leq 3\theta_l \sum_{m=1}^{L-l-1} q^m && \text{(by Eq. (124))} \\
&\leq 3\theta_l \sum_{m=1}^{\infty} q^m && \text{(since } q > 0 \text{ by Eq. (123))} \\
&= \frac{3q}{1-q}\theta_l && \text{(geometric series)} \\
&\leq \theta_l && \text{(since } q \leq 1/4 \text{ by Eq. (123))} \\
&< \alpha_l && \text{(by Eq. (125)).} \qquad (127)
\end{aligned}$$

Thus the angle margin is positive. Cosine decreases with angle on $[0, \pi]$, so the triplet margin is positive. Since $L \geq 2$ and $b \geq 2$, admissible triplets exist, and their margin is positive. □

J Additional Experiments

All experiments are run on a server equipped with NVIDIA RTX A5000 GPUs (24 GB memory each). The CLIP empirical evaluations of Section 3.2 use publicly released CLIP checkpoints over the ImageNet-1K training set and the WordNet hierarchy. The synthetic experiments of Appendix J.3 run on a single A5000.

J.1 Hierarchical Angular Separation on CLIP embeddings

J.1.1 Controls and robustness checks for approximate image-side $\mathcal{HAS}$

Table 1 measures every representation under the disjoint-split protocol of Appendix J.2: we partition the images in each ImageNet-1K leaf into even and odd halves, estimate every node embedding from each half separately by descendant-leaf-weighted instance aggregation, and average $\mathcal{HAS}$-Viol over the two directions. For raw pixels, we apply CLIP's resize, center-crop, and channel-normalization preprocessing without an encoder and flatten each image into a $150{,}528$-dimensional vector. The Gaussian control instead draws independent isotropic vectors in $\mathbb{R}^{768}$ with the same per-leaf sample counts. Every condition uses the WordNet hierarchy, anchor set, and 95th-percentile descendant threshold of Section 3.2, and its hierarchy-shuffled null reassigns leaf groups within that hierarchy while preserving the representation and the aggregation procedure.

The randomly initialized row of Table 1 averages three ViT-L/14 random initializations, so it leaves open whether approximate $\mathcal{HAS}$ at random initialization depends on the architecture. We therefore repeat the measurement across visual backbones, with at least three independent random initializations each.


Table 2: Approximate image-side $\mathcal{HAS}$ at random initialization across visual backbones, measured with the disjoint-split protocol. Each backbone is evaluated with n independent random initializations, and both columns report the mean $\pm$ sample standard deviation across those samplings; each sampling's null is itself a mean over five hierarchy shuffles. The ViT-L/14 row is the randomly initialized row of Table 1.

Backbone	n	$\mathcal{HAS}$ violation (%) $\downarrow$	$\mathcal{HAS}$ violation shuffled (%) $\downarrow$
ViT-B/16	6	28.55 ± 0.34	57.20 ± 0.07
ViT-B/32	3	29.58 ± 0.13	57.39 ± 0.15
ViT-L/14	3	27.88 ± 0.24	56.80 ± 0.12
ViT-H/14	3	27.63 ± 0.56	56.62 ± 0.03
RN50	3	28.53 ± 1.66	59.45 ± 1.44
ViT-L/14@336	1	27.83	56.83 ± 0.33

Across architectures and random seeds, the violation percentage of every backbone is far below its own shuffled null.

J.1.2 Robustness to the prototype construction and the taxonomy

Image-side $\mathcal{HAS}$ could depend on two choices in the setup of Section 3.2: the descendant-leaf weighting used to build prototypes, and the WordNet taxonomy itself. We repeat the disjoint-split measurement with each choice replaced in turn. First, we replace the descendant-leaf mean by a uniform mean over child prototypes, so that every child contributes equally regardless of how many images it has. Second, we replace ImageNet-1K and WordNet by CUB-200 [47] with its own bird taxonomy, an independent hierarchy of different depth and branching. Chance level depends on both choices, so we compare each condition against its own hierarchy-shuffled null rather than against a common baseline.



(a) Randomly initialized. (b) OpenAI. (c) OpenCLIP (DataComp-1B).

Figure 6: $\mathcal{HAS}$ violation percentage by depth on ViT-L-14 CLIP *text* embeddings (instance aggregation): $\mathcal{HAS}$ appears with pretraining.

Table 3: Image-side $\mathcal{HAS}$ is robust to the prototype construction and to the taxonomy. Each condition is paired with its own hierarchy-shuffled null (mean $\pm$ standard deviation over five shuffles). The first row restates the ViT-L/14 measurements of Table 1 at the precision used there; its randomly initialized entries are the seed-0 initialization rather than the mean over three initializations reported there.

	Pretrained OpenAI CLIP		Randomly initialized	
Setting	$\mathcal{HAS}$-Viol (%)	own null (%)	$\mathcal{HAS}$-Viol (%)	own null (%)
ImageNet / WordNet, descendant-leaf mean	2.95	32.93 ± 0.48	28.15	56.70 ± 0.42
ImageNet / WordNet, uniform child mean	3.9	34.5 ± 0.3	29.1	56.8 ± 0.5
CUB-200 / bird taxonomy	3.8	41.2 ± 0.8	33.6	66.3 ± 1.4

In all three conditions, the violation percentage of the pretrained encoder is roughly an order of magnitude below its own null, while that of the randomly initialized encoder is roughly half of its null. Neither the prototype construction nor the choice of taxonomy therefore changes the conclusion: pretraining accounts for roughly the same share of the achievable separation in every setting, and approximate separation at random initialization appears in every setting.


Instance aggregation on the text side (ViT-L/14). Figure 6 repeats the text experiment of Section 3.2 estimating concept embeddings by instance aggregation instead of direct concept encoding, again on ViT-L-14, and reaches the same conclusion: the median violation percentages are concentrated near zero for both pretrained models and substantially larger for the randomly initialized model.

ViT-H/14 results. We further repeat the experiment on ViT-H/14, comparing OpenCLIP trained on DFN-5B [51] against a randomly initialized ViT-H/14. Figure 7 groups text embeddings (top; instance aggregation) and image embeddings (bottom; instance aggregation) and reproduces the same qualitative pattern.

ViT-B/16 results. We additionally repeat the main-text experiment on a smaller backbone, ViT-B/16, comparing OpenAI CLIP [1] and OpenCLIP [43] trained on DataComp-1B [44] against a randomly initialized ViT-B/16. Figure 8 (text via direct concept encoding on top, image via instance aggregation on bottom) and Figure 9 (text, instance aggregation) reproduce the same qualitative pattern as on ViT-L/14: text $\mathcal{HAS}$ appears with pretraining, while image embeddings show approximate $\mathcal{HAS}$ at random initialization.

ViT-B/32 results. We further repeat the experiment on ViT-B/32, comparing OpenAI CLIP and OpenCLIP (DataComp-1B) against a randomly initialized ViT-B/32. Figure 10 groups text embeddings (top; direct concept encoding) and image embeddings (bottom; instance aggregation) and reproduces the same qualitative pattern.

ViT-L/14@336px results. We also evaluate the higher-resolution ViT-L/14@336px backbone, for which only the OpenAI checkpoint ships at 336px in OpenCLIP; we compare it against a randomly initialized ViT-L/14@336px. Figure 11 groups text embeddings (top; direct concept encoding) and image embeddings (bottom; instance aggregation) and reproduces the same qualitative pattern.



(a) Randomly initialized.

(b) OpenCLIP (DFN-5B).

(c) Randomly initialized.

(d) OpenCLIP (DFN-5B).


Figure 7: $\mathcal{HAS}$ violation percentage by depth on ViT-H/14 CLIP embeddings. *Top: text* embeddings (instance aggregation) – $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.

SigLIP2 results. We evaluate SigLIP2 (ViT-B/16 at 256px), comparing the pretrained SigLIP2 checkpoint against a randomly initialized ViT-B/16 at 256px. Figure 12 (text via direct concept encoding on top, image via instance aggregation on bottom) reproduces the same qualitative pattern: text $\mathcal{HAS}$ appears with pretraining, while image embeddings show approximate $\mathcal{HAS}$ at random initialization.

MetaCLIP2 results. We evaluate MetaCLIP2 (ViT-H/14 at 224px), comparing the pretrained MetaCLIP2 worldwide checkpoint against a randomly initialized ViT-H/14. Figure 13 (text via direct concept encoding on top, image via instance aggregation on bottom) reproduces the same qualitative pattern: text $\mathcal{HAS}$ appears with pretraining, while image embeddings show approximate $\mathcal{HAS}$ at random initialization.

J.2 Disjoint-Split Control against Instance Overlap for $\mathcal{HAS}$ in Image Embeddings


To test whether $\mathcal{HAS}$ in image embeddings is explained by exact instance overlap between parent and descendant prototypes, we repeat the ViT-L/14 image experiment with disjoint image splits. For each ImageNet training leaf, we split images into two disjoint sets, rebuild all internal prototypes separately in each split using instance aggregation, and calculate $\mathcal{HAS}$-Viol across splits. For example, to calculate the similarity between a parent node and its descendant nodes, we use the parent embedding calculated from one set of images, while calculating the descendant and off-branch embeddings from the other set. Thus, parent prototypes and descendant & off-branch prototypes never share image instances. We average across two split directions (parent in the first set and descendants & off-branch in the second set, and vice versa) so the result does not depend on which split holds the



(a) Randomly initialized. (b) OpenAI. (c) OpenCLIP (DataComp-1B).

(d) Randomly initialized. (e) OpenAI. (f) OpenCLIP (DataComp-1B).


Figure 8: $\mathcal{HAS}$ violation percentage by depth on ViT-B/16 CLIP embeddings. *Top: text* embeddings (direct concept encoding): $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.



(a) Randomly initialized. (b) OpenAI. (c) OpenCLIP (DataComp-1B).

Figure 9: $\mathcal{HAS}$ violation percentage by depth on ViT-B/16 CLIP *text* embeddings (instance aggregation): $\mathcal{HAS}$ appears with pretraining.


parent. Figure 14 compares this disjoint-split control with the original image instance-aggregation evaluation, yielding results consistent with the unsplit evaluation.



(a) Randomly initialized. (b) OpenAI. (c) OpenCLIP (DataComp-1B).

(d) Randomly initialized. (e) OpenAI. (f) OpenCLIP (DataComp-1B).

Figure 10: $\mathcal{HAS}$ violation percentage by depth on ViT-B/32 CLIP embeddings. *Top: text* embeddings (direct concept encoding): $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.




(a) Randomly initialized.

(b) OpenAI.

(c) Randomly initialized.


(d) OpenAI.

Figure 11: $\mathcal{HAS}$ violation percentage by depth on ViT-L/14@336px CLIP embeddings. *Top: text* embeddings (direct concept encoding): $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.




(a) Randomly initialized.

(b) SigLIP2 pretrained.




(c) Randomly initialized.




(d) SigLIP2 pretrained.

Figure 12: $\mathcal{HAS}$ violation percentage by depth on SigLIP2 embeddings. *Top: text* embeddings (direct concept encoding): $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.




(a) Randomly initialized.

(b) MetaCLIP2 pretrained.




(c) Randomly initialized.



(d) MetaCLIP2 pretrained.

Figure 13: $\mathcal{HAS}$ violation percentage by depth on MetaCLIP2 embeddings. *Top: text* embeddings (direct concept encoding): $\mathcal{HAS}$ appears with pretraining. *Bottom: image* embeddings (instance aggregation): approximate $\mathcal{HAS}$ appears at random initialization and strengthens after pretraining.



(a) Randomly initialized. (b) OpenAI. (c) OpenCLIP (DataComp-1B).

(d) Randomly initialized. (e) OpenAI. (f) OpenCLIP (DataComp-1B).

Figure 14: $\mathcal{HAS}$ violation percentages by depth on ViT-L/14 CLIP *image* embeddings remain similar under the disjoint-split control. *Top:* disjoint-split control, where parent prototypes and comparison prototypes are estimated from disjoint image instances. *Bottom:* original instance-aggregation evaluation.

J.3 Numerical Validation of $\mathcal{HAS}$ Transfer at Small Regularization

In Theorem 4.9, we guarantee approximate $\mathcal{HAS}$ transfer only for sufficiently large λ, but leave open whether transfer persists outside the asymptotic regime used in its proof. We test this possibility on a synthetic image-prototype hierarchy by minimizing Eq. (9) across a sweep of λ. We verify whether transfer happens outside the large-λ regime, whether the optimal text embeddings approach the root-centered prototype decomposition of Corollary 4.8 as λ increases, and whether the sufficient transfer condition is conservative. We report $\mathcal{HAS}$-Viol at the minimizer found by L-BFGS and define prototype alignment as the minimum, over non-root nodes k, of the cosine between $\boldsymbol{a}_k^*$ and $\boldsymbol{\mu}_k$.

Experimental setup. For convenience, we restate the data generating process from Assumption 4.1 as

$$\boldsymbol{z}_j = \boldsymbol{\mu}_{y_j} + \boldsymbol{\varepsilon}_j, \qquad \mathbf{E}[\boldsymbol{\varepsilon}_j] = \mathbf{0}, \;\; j \in [N]. \tag{128}$$

We instantiate Eq. (128) with isotropic Gaussian variation $\boldsymbol{\varepsilon}_j \sim \mathcal{N}(\mathbf{0}, \sigma^2 \boldsymbol{I}_d)$ at depth $L = 5$, branching factor 3, variation parameter $\sigma = 10^{-5}$, feature-dimension-to-number-of-nodes ratio $d/|V| = 1$, and 150 images per leaf, using prototypes generated by geometric-decay sibling angles ($\theta_0 = 85°$). We optimize the symmetric InfoNCE objective (temperature 1, no learnable temperature) with L-BFGS to find the global minimizer. We assign captions deterministically, cycling each leaf's images through its root-to-leaf path; we call this the balanced-caption setup.

Transfer precedes the asymptotic regime. Sweeping $\lambda \in [10^{-5}, 10^{2}]$ separates the onset of transfer from the accuracy of the large-λ expansion. $\mathcal{HAS}$-Viol reaches zero before prototype alignment saturates (Figure 5b). The convergence trace confirms that zero $\mathcal{HAS}$-Viol holds at the minimizer found by L-BFGS rather than only at an early iterate (Figure 5a).

The large-λ expansion predicts the limiting geometry. Prototype alignment increases with λ and approaches one in the large-λ regime (Figure 5b). The trend is consistent with the directional prediction of Corollary 4.8, while the earlier disappearance of violations shows that transfer does not require near-perfect prototype alignment.

The sufficient transfer condition is conservative. Under Theorem 4.9, transfer is certified when $D_\epsilon^{\mathrm{nce}} < \rho_{\min}\gamma_{\mathcal{HAS}}/16$. Both tested root norms, $\|\boldsymbol{\mu}_{\mathrm{root}}\| \in \{10^{-4}, 10^{-2}\}$, violate this condition yet produce nearly the same transition (Figures 5b and 15). At fixed $\lambda = 10^{-3}$, violations remain small across the root-norm sweep and increase only under substantially larger shifts (Figure 16). Across the noise sweep at $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1}\}$, degradation appears first under the weakest regularization and later under all three regularization values (Figure 17). We therefore find that the theorem's transfer condition is sufficient but not necessary in this synthetic setting.




Figure 15: λ sweep at root norm $\|\boldsymbol{\mu}_{\text{root}}\| = 10^{-2}$ in the same balanced-caption setup as Figure 5b. The x-axis is λ; the left y-axis is the final $\mathcal{HAS}$-Viol averaged over non-leaf nodes, and the right y-axis is the final minimum prototype alignment over non-root nodes. Although this root norm violates the sufficient transfer condition $D_{\epsilon}^{\text{nce}} < \rho_{\min}\gamma_{\mathcal{HAS}}/16$ by a factor of 161 on this set of prototypes, because $D_{\epsilon}^{\text{nce}} \geq \xi_{\max}\|\boldsymbol{\mu}_{\text{root}}\|$ and $\xi_{\max} = 2.50$, the drop in violation percentage is nearly unchanged: it again reaches zero by $\lambda = 10^{-3}$, while prototype alignment saturates just below 1, reflecting the remaining root prototype $\boldsymbol{\mu}_{\text{root}}$.




Figure 16: Root-norm sweep at $\lambda = 10^{-3}$ in the same balanced-caption setup as Appendix J.3. The x-axis is the root norm $\|\boldsymbol{\mu}_{\text{root}}\|$, and the y-axis is the final $\mathcal{HAS}$-Viol averaged over non-leaf nodes. The violation percentage remains nearly flat at small root norm, then departs strongly from near-zero once the root norm is large, with non-monotone behavior in the extreme large-root-norm regime.




Figure 17: σ-robustness sweep in the same balanced-caption setup as Appendix J.3, with root norm $\|\boldsymbol{\mu}_{\text{root}}\| = 10^{-4}$ and $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1}\}$. *Left:* $\mathcal{HAS}$-Viol. *Middle:* global minimum branch margin. *Right:* minimum non-root prototype alignment. All three regularization levels remain stable through $\sigma = 3\times10^{-3}$. At $\sigma = 10^{-2}$, only $\lambda = 10^{-3}$ has a nonzero violation percentage (0.014%) and a negative global minimum margin; the other two settings retain zero violations and positive margins. At $\sigma = 3\times10^{-2}$, every λ has a negative global minimum margin and a violation percentage between 0.37% and 0.38%.

J.4 Predicted and Realized Slack on Real ViT-L/14 Prototypes

We use these experiments to compare the guarantee of Theorem 4.6 with the behavior of its exact linear-loss minimizer on real prototypes. We first evaluate the theorem's threshold $\tau_\epsilon = 8D_\epsilon/\rho_{\min}$, then measure the realized transfer and explain the gap between them. Although the theorem's bound gives no information in this setting, approximate $\mathcal{HAS}$ still transfers.

We use the ImageNet-1K / WordNet image prototypes of Section 3.2 (1375 nodes and $N = 1{,}281{,}167$ training images) from three ViT-L/14 backbones: randomly initialized, OpenAI CLIP, and OpenCLIP trained on DataComp-1B. Holding the image prototypes fixed at $\boldsymbol{Z}$, we compute the closed-form text-side minimizer $\boldsymbol{A}^{\text{lin},*}$ of Proposition D.1. Each leaf prototype is its exact empirical image mean: we neither inject nor fit noise. The calculation in this subsection is therefore deterministic given the prototypes and caption counts.

The inequality required by the theorem does not hold. For this calculation, the reference vector is the empirical prototype itself, $\boldsymbol{\mu}_k = \bar{\boldsymbol{z}}_k$, taken as the descendant-leaf-weighted instance aggregation of Section 3.2. The stochastic part of the perturbation therefore vanishes, leaving $\boldsymbol{e}_k = -\xi_k^{\text{lin}}\bar{\boldsymbol{z}}$. The theorem's error term consequently reduces to the root-centering contribution alone, $D = \xi_{\max}^{\text{lin}}\|\bar{\boldsymbol{z}}\|$, where $\xi_k^{\text{lin}} \in [0.50, 8.54]$ is fixed by the ImageNet caption counts and shared across encoders.

Using expected counts has a negligible effect on the prototypes or violation percentages. We use $N_k = \sum_\ell n_\ell/|\text{path}(\ell)|$ under Assumption 4.3 rather than a sampled caption assignment, which makes the calculation deterministic. Under that assumption the empirical mean $\bar{\boldsymbol{z}}_k$ of the images captioned k weights each descendant leaf ℓ by $n_\ell/|\text{path}(\ell)|$ instead of n_ℓ. When we rebuild every internal prototype under that weighting, the prototypes and the text-side violation percentages of Table 5 remain essentially unchanged.

For every backbone, the inequality $D < \rho_{\min}/4$ required by Theorem 4.6 does not hold, so we obtain no guarantee from the theorem for these prototypes. Moreover, the resulting threshold exceeds the largest possible cosine-margin difference, which is 2, so the bound does not certify any triplet. The mismatch is structural: the stochastic term is zero here, and the universal constant C multiplies only that term.

The sufficient bound is loose, but approximate $\mathcal{HAS}$ still transfers. We therefore measure transfer descriptively rather than certify it. For each anchor, we find the smallest slack that satisfies Eq. (8), then report the largest of these anchor-specific values. This worst-anchor slack is the single post hoc slack needed for the inequality to hold at every anchor.

The quantity $\mathcal{HAS}\text{-Viol}_\tau^{\text{img}}(u)$ is Definition 3.2 evaluated on the image prototypes with the descendant radius $c_u^{\boldsymbol{\mu}}$ relaxed by τ. The theoretical bound and the empirical metric of Section 3.2 therefore have the same units: a percentage of off-branch nodes per anchor. The same bound holds for the percentile-based descendant radius used there for outlier robustness, provided both sides replace the minimum by the same order statistic, the r-th smallest descendant cosine for a fixed r. If w is counted on the text side, then at least r descendants v satisfy $\cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_v) \le \cos(\widetilde{\boldsymbol{a}}_u, \widetilde{\boldsymbol{a}}_w)$.

Table 4: The inequality required by Theorem 4.6 and measured approximate $\mathcal{HAS}$ transfer on the same real prototypes. The inequality $D < \rho_{\min}/4$ does not hold for any of the three backbones, so we obtain no guarantee from the theorem here. We evaluate the image-side rows on the fixed prototypes and the text-side rows on the closed-form linear-loss optimum $\boldsymbol{A}^{\mathrm{lin},*}$. For the worst-anchor slack, one value of τ must satisfy Eq. (8) at every anchor, so we report the largest anchor-specific slack. This slack is post hoc. For the last three rows, we pool the $505{,}938$ (anchor, off-branch node) pairs over the 375 anchors. For the two $\mathcal{HAS}$-Viol rows, we report per-anchor percentages measured from all training images per node in one pass, not with the disjoint even/odd split of Table 1.

Quantity	Randomly initialized ViT-L/14	OpenAI CLIP ViT-L/14	OpenCLIP ViT-L/14 (DataComp-1B)
Inequality required by Theorem 4.6 $D < \rho_{\min}/4$ holds?	No	No	No
Realized transfer			
Mean $\mathcal{HAS}$-Viol$^{\mathrm{img}}(u)$ across anchors (%)	25.55	2.95	2.42
Mean $\mathcal{HAS}$-Viol$^{\mathrm{txt}}(u)$ across anchors (%)	27.11	9.58	8.35
Worst-anchor slack (must hold at every anchor)	0.123	0.184	0.259
Median image margin	0.03	0.19	0.28
Pr[text triplet violates] (%)	26.6	9.2	7.9
Pr[text triplet violates | image triplet violates] (%)	62	79	86
Pr[text violates | image violates]/ Pr[text violates]	2.3×	8.6×	10.9×

By part (ii) of Lemma C.8, $\gamma_{uvw} \leq \tau$ for each of them, so at least r descendants satisfy $\cos(\boldsymbol{\mu}_u, \boldsymbol{\mu}_v) \leq \cos(\boldsymbol{\mu}_u, \boldsymbol{\mu}_w) + \tau$, and w is counted on the image side.

As in Section 3.2, we compute the 95th percentile of the descendant angles with linear interpolation rather than as an exact order statistic. Both sides have the same rank, but neither radius is one of the measured cosines, so the order-statistic argument applies only approximately. When we recompute both sides with the order statistic, every conclusion in this appendix remains intact.

To assess whether individual image-side violations persist after transfer, we pool the $505{,}938$ (anchor, off-branch node) pairs scored by Definition 3.2 over the 375 anchors. We compare the probability that such a pair violates $\mathcal{HAS}$ in the learned text embeddings with the conditional probability that it violates $\mathcal{HAS}$ on the text side given that it violates $\mathcal{HAS}$ on the image side.

Table 4 shows that the theorem's bound is loose for these prototypes. Although $D < \rho_{\min}/4$ does not hold for any backbone, Eq. (8) holds at every anchor with a post hoc slack well below the largest possible cosine-margin difference of 2. The worst-anchor slack is comparable to the median image margin for the two pretrained backbones and exceeds it for the randomly initialized encoder.

For the randomly initialized encoder, the image and text geometries are most similar because their mean violation percentages nearly match. The worst-anchor slack shows that this agreement is not uniform across anchors.

The slack bound is loose because the perturbation is structured. The realized perturbation $\boldsymbol{e}_k = -\xi_k^{\mathrm{lin}} \bar{\boldsymbol{z}}$ is rank one: every text embedding moves along the single direction $-\bar{\boldsymbol{z}}$, differing only in magnitude. By contrast, in Lemma C.5 we bound perturbations in arbitrary directions by $4\eta/\rho_{\min}$ per cosine and $8\eta/\rho_{\min}$ for the cosine difference in Definition 3.1. In the worst case, the perturbations at u, v, and w point in directions that maximize the change in the cosine difference. Here the parallel shifts largely cancel in the cosine difference. The gap between the theorem's bound and the observed transfer is therefore due to the worst-case bound, which allows perturbations in any direction, not a failure of the transfer mechanism.

To obtain a useful a priori threshold for these real embeddings, we may need an analysis that accounts for the perturbations sharing one direction, which we leave open.

Image-side violations persist, but new text-side violations also arise. If image- and text-side violations were independent, the conditional and marginal text-side violation probabilities would be equal. Instead, their ratio exceeds one for every backbone in Table 4. Thus an image-side violation is more likely to remain after transfer than an arbitrary triplet is to violate on the text side.

A high conditional violation probability does not mean that text-side violations occur only where image-side ones do. On the trained backbones, the per-anchor text violation percentage substantially exceeds the image percentage, so many text-side violations have no image-side counterpart. We

Table 5: Caption-permutation ablations for (a) the closed-form linear-loss text optimum on fixed real image prototypes and (b) the synthetic InfoNCE setting of Appendix J.3. Permuted entries are mean $\pm$ standard deviation over five permutation seeds.

(a) Real prototypes with the linear contrastive loss

		$\mathcal{HAS}$-Viol^{txt} (%)	
Fixed image embeddings	$\mathcal{HAS}$-Viol^{img} (%)	path-consistent	permuted
Randomly initialized ViT-L/14	25.55	27.11	61.63 ± 0.24
OpenAI CLIP ViT-L/14	2.95	9.58	54.06 ± 0.21
OpenCLIP ViT-L/14 (DataComp-1B)	2.42	8.35	54.17 ± 0.16

(b) Synthetic prototypes with the InfoNCE loss

	$\mathcal{HAS}$-Viol^{txt} (%)	
λ	path-consistent	permuted
10^{-5}	1.76	64.3 ± 4.6
10^{-4}	0.06	59.7 ± 4.9
10^{-3}	0.00	59.3 ± 4.5

conclude only that, where Theorem 4.6 gives no guarantee, substantial approximate $\mathcal{HAS}$ structure remains after transfer while new violations also arise.

J.5 Caption Permutation Disrupts Approximate $\mathcal{HAS}$ Transfer

We test whether approximate $\mathcal{HAS}$ transfer depends on caption–image pairings or only on the marginal caption distribution. Under the path-consistent setup of Section 4.1, each caption co-occurs only with images from its descendant leaves.

Using the ImageNet-1K / WordNet prototypes from three ViT-L/14 backbones in Appendix J.4, we compute the closed-form linear-loss text minimizer $\boldsymbol{A}^{\mathrm{lin},*}$ from Proposition D.1 with path-consistent captions and with hypernyms randomly permuted across images. The permutation preserves the image prototypes and marginal caption distribution but disrupts path consistency. We repeat the ablation in the synthetic InfoNCE setting of Appendix J.3, varying λ to test whether stronger regularization compensates for the permutation.

In Table 5(a), permutation more than doubles the text-side violation percentage for every backbone, raising it above half. In Table 5 (b), increasing λ reduces the path-consistent violation percentage to zero, but not the permuted percentage. Thus, in both settings, preserving the marginal caption distribution alone does not preserve approximate $\mathcal{HAS}$ transfer.

J.6 Text-side $\mathcal{HAS}$ is strongest with path-consistent captions under joint CLIP training

In Appendix J.5, we fix the image embeddings and permute hypernym captions to test whether text-side $\mathcal{HAS}$ depends on their image pairings. Here we train both CLIP encoders on ImageNet and compare caption pairings.

Training procedure. We train CLIP ViT-B/32 [1, 52] from scratch with OpenCLIP [43] on the 1,281,167 ImageNet-1K training images for 32 epochs. We use AdamW ($\beta_1 = 0.9$, $\beta_2 = 0.98$, $\epsilon = 10^{-6}$), learning rate 10^{-3}, and weight decay 0.1. We use batch size 1024, 2000 warmup steps, and a learned temperature. For each image, we fix one caption across epochs by placing a hierarchy node's name in one of the 80 ImageNet prompt templates of Radford et al. [1].

Caption pairings. We compare the following caption pairings:

- *path-consistent*: draw uniformly from the image's leaf and its ancestors in the WordNet hierarchy of Section 3.2, following Section 4.1;
- *leaf-only*: choose the image's leaf;




Figure 18: Text-side $\mathcal{HAS}$-Viol is lowest with path-consistent captions during joint CLIP training. We plot text (left) and image (right, log scale) $\mathcal{HAS}$ violation percentages (lower is better). Path-consistent captions pair an image with a leaf or ancestor; leaf-only captions only pair with the leaf; in the permuted pairing, we shuffle hypernyms among images at the same depth.

- *permuted*: start with the path-consistent draw, then shuffle non-leaf caption labels across images within each depth, preserving each caption count.

After every epoch, we measure $\mathcal{HAS}$-Viol using the 375 anchors and 95th-percentile descendant threshold of Section 3.2. We average the 80 prompt templates for each text concept and aggregate 50 fixed training images per leaf with descendant-leaf weighting for each image concept. In the left panel of Figure 18, the path-consistent pairing has the lowest $\mathcal{HAS}$-Viol from the first epoch onward. Text-side violations fall less under leaf-only captions and remain high under permutation.

K Alternating Optimization: The Image-Side Update

The fixed-image results explain how image-side approximate $\mathcal{HAS}$ transfers to text, but not how an image-side update changes variation among images. We therefore analyze an exact image update after the text-side update. Images sharing a caption then receive the same embedding; their input variation enters through caption-group averages, the global image mean, and a common shift weighted by caption counts. In Proposition K.3, we bound the stochastic deviation of these updated embeddings.

We analyze one exact text-side step followed by one exact image-side step under the linear contrastive loss, with ridge regularization on both sides. We use the linear loss because the InfoNCE image-side step has no closed form.

$$\mathcal{L}^{\text{alt}}(\boldsymbol{A}, \boldsymbol{Z}) := -\operatorname{tr}\big(\boldsymbol{A}^\top \boldsymbol{Z}\mathbf{B}^\top\big) + \frac{\lambda}{2}\|\boldsymbol{A}\|_F^2 + \frac{\lambda_Z}{2}\|\boldsymbol{Z}\|_F^2, \tag{129}$$

Here $\lambda, \lambda_Z > 0$ and $\mathbf{B}$ is the label-encoding matrix of Eq. (58); by Eq. (60), the first two terms are exactly the regularized linear contrastive loss of Eq. (5). The cross-modal term is bilinear in $(\boldsymbol{A}, \boldsymbol{Z})$, and the objective is strongly convex in either argument when the other is fixed. We obtain the exact minimizer of each step from Proposition D.1.

To obtain the image-side update, we first analyze the same label-encoding matrix $\mathbf{B}$ used in the $\boldsymbol{A}$-step by columns, splitting each entry into a matched-caption contribution and an off-caption coefficient shared across image columns. Set $\kappa := 1 + \frac{1}{2(M-1)} + \frac{1}{2(N-1)}$ and, for $k \in [M]$, $\gamma_k^- := \frac{1}{2(M-1)} + \frac{N_k}{2(N-1)}$. Expanding Eq. (58) and collecting terms in Y_{kj} gives

$$\begin{aligned} B_{kj} &= Y_{kj} + \frac{Y_{kj} - 1}{2(M-1)} + \frac{Y_{kj} - N_k}{2(N-1)} \\ &= \kappa Y_{kj} - \gamma_k^-, \qquad (k, j) \in [M] \times [N]. \end{aligned} \tag{130}$$

The indicator Y_{kj} selects the paired text embedding, while summing $-\gamma_k^-$ against the text embeddings gives the uniform and caption-frequency-weighted means in the common shift below.

Fix $\boldsymbol{A} \in \mathbb{R}^{d\times M}$. Applying Proposition D.1 to Eq. (129) gives the image-side minimizer

$$\boldsymbol{Z}^{\mathrm{lin},*}(\boldsymbol{A}) = \frac{1}{\lambda_Z}\,\boldsymbol{A}\,\mathbf{B}. \tag{131}$$

To express its columns, define the uniform and caption-frequency-weighted text means

$$\bar{\boldsymbol{a}} := \frac{1}{M}\sum_{k=1}^{M}\boldsymbol{a}_k, \qquad \bar{\boldsymbol{a}}_{\mathrm{capt}} := \frac{1}{N}\sum_{k=1}^{M}N_k\,\boldsymbol{a}_k = \frac{1}{N}\sum_{j=1}^{N}\boldsymbol{a}_{t_j}. \tag{132}$$

Using Eq. (130) and the means in Eq. (132), the j-th column of Eq. (131) is

$$\begin{aligned}\boldsymbol{z}_j^{\mathrm{lin},*}(\boldsymbol{A}) &= \frac{1}{\lambda_Z}\sum_{k=1}^{M}B_{kj}\boldsymbol{a}_k \\ &= \frac{1}{\lambda_Z}\left(\kappa\boldsymbol{a}_{t_j} - \sum_{k=1}^{M}\gamma_k^{-}\,\boldsymbol{a}_k\right) \\ &= \frac{1}{\lambda_Z}\left[\kappa\boldsymbol{a}_{t_j} - \frac{M}{2(M-1)}\,\bar{\boldsymbol{a}} - \frac{N}{2(N-1)}\,\bar{\boldsymbol{a}}_{\mathrm{capt}}\right] \qquad \text{for every } j\in[N]. \end{aligned}\tag{133}$$

Thus images with the same caption receive the same embedding, even before imposing the text-side optimum.

In Eq. (133), the positive term favors the text embedding paired with image j, while the two subtracted means play the role of the global image mean $\bar{\boldsymbol{z}}$ in Corollary D.2. To simplify this image-side update after the text step, we first show that its uniform text mean vanishes.

Lemma K.1 (Global centering at the $\boldsymbol{A}$-step optimum)**.** *Every column of* $\mathbf{B}$ *sums to zero:* $\sum_{k=1}^{M}B_{kj} = 0$ *for every* $j\in[N]$. *Consequently, for every* $\boldsymbol{Z}$*, the* $\boldsymbol{A}$*-step optimum of Proposition D.1 satisfies*

$$\sum_{k=1}^{M}\boldsymbol{a}_k^{\mathrm{lin},*} = \mathbf{0}. \tag{134}$$

Proof. Fix $j\in[N]$. Each image has exactly one caption, so $\sum_{k=1}^{M}Y_{kj} = 1$; also $\sum_{k=1}^{M}N_k = N$. Therefore, by Eq. (130),

$$\sum_{k=1}^{M}B_{kj} = \kappa - \frac{M}{2(M-1)} - \frac{N}{2(N-1)} = 0, \tag{135}$$

Thus $\mathbf{B}^\top\mathbf{1} = \mathbf{0}$ with $\mathbf{1}\in\mathbb{R}^M$ the all-ones vector. Since $\sum_{k=1}^{M}\boldsymbol{a}_k^{\mathrm{lin},*} = \boldsymbol{A}^{\mathrm{lin},*}\mathbf{1}$, we obtain Eq. (134) from Proposition D.1. □

At the $\boldsymbol{A}$-step optimum, we remove the uniform mean from Eq. (133) using Lemma K.1. The remaining terms give an affine copy of the text embeddings.

Corollary K.2 (Image-side update as a scaled, shifted text embedding)**.** *Let* $\boldsymbol{A} = \boldsymbol{A}^{\mathrm{lin},*}$ *for arbitrary fixed* $\boldsymbol{Z}$*. With* κ *from Eq.* (130)*, define the* caption-mean shift

$$\boldsymbol{e}_{\mathrm{capt}} := -\frac{N}{2(N-1)\,\kappa}\,\bar{\boldsymbol{a}}_{\mathrm{capt}}. \tag{136}$$

Then the $\boldsymbol{Z}$*-step optimum is a scaled, shifted copy of the caption's text embedding:*

$$\boldsymbol{z}_j^{\mathrm{lin},*} = \frac{\kappa}{\lambda_Z}\left(\boldsymbol{a}_{t_j}^{\mathrm{lin},*} + \boldsymbol{e}_{\mathrm{capt}}\right) \qquad \textit{for every } j\in[N]. \tag{137}$$

Proof. By Lemma K.1, $\bar{\boldsymbol{a}} = \mathbf{0}$ at $\boldsymbol{A} = \boldsymbol{A}^{\mathrm{lin},*}$. Substituting this and Eq. (136) into Eq. (133) gives Eq. (137). □

This update makes images with the same caption identical. The remaining stochastic deviation comes from caption-group averages and a common caption-count-weighted shift; in Proposition K.3, we bound it after removing the update's positive scale.

Proposition K.3 (Caption-group averaging in the image update)**.** *Suppose Assumptions 4.1, 4.3, and 4.4 hold. Starting from $\boldsymbol{Z}$, compute the exact text-side minimizer $\boldsymbol{A}^{\mathrm{lin},*}$ and then the exact image-side minimizer $\boldsymbol{Z}^{\mathrm{lin},*}$. Fix the observed leaf and caption labels, and let $\mathbb{E}_{\boldsymbol{\varepsilon}}$ average over the independent variation vectors of Assumption 4.1. For each non-root k and any $j \in \mathcal{P}_k$, define the normalized stochastic deviation*

$$\boldsymbol{s}_k := \frac{\lambda\lambda_Z}{\kappa^2 N_k}\left(\boldsymbol{z}_j^{\mathrm{lin},*} - \mathbb{E}_{\boldsymbol{\varepsilon}}\boldsymbol{z}_j^{\mathrm{lin},*}\right), \tag{138}$$

where κ is from Eq. (130) *and the choice of $j \in \mathcal{P}_k$ does not matter by Eq.* (137)*. The effect of the common caption-count-weighted shift is measured by*

$$\omega := \frac{\sqrt{\sum_{k=1}^M N_k^3}}{(N-1)\sqrt{N_{\min}}}. \tag{139}$$

With $\xi_{\max}^{\mathrm{lin}}$ defined before Theorem 4.6, there exists a universal constant $C > 0$ such that, for every $\epsilon \in (0,1)$, with probability at least $1-\epsilon$,

$$\max_{k \neq \mathrm{root}} \|\boldsymbol{s}_k\| \le C\sigma\left((1+\omega)\sqrt{\frac{d + \log(M-1) + \log(8/\epsilon)}{N_{\min}}} + \xi_{\max}^{\mathrm{lin}}\sqrt{\frac{d+\log(8/\epsilon)}{N}}\right). \tag{140}$$

Proof. **Step 1: Identify the centered image update.** We first write the common shift $\boldsymbol{e}_{\mathrm{capt}}$ in terms of the input images. For each image $j \in [N]$, define its caption-count weight by

$$\begin{aligned} h_j &:= N_{t_j} - \frac{1}{\kappa}\sum_{k=1}^M N_k\gamma_k^- \\ &= N_{t_j} - \frac{1}{\kappa}\left(\frac{N}{2(M-1)} + \frac{\sum_{k=1}^M N_k^2}{2(N-1)}\right). \end{aligned} \tag{141}$$

The common shift in Eq. (136) uses the N_k/N-weighted text mean of Eq. (132). The text-side minimizer of Proposition D.1 and the label encoding in Eq. (130) apply to every $k \in [M]$, including nodes with $N_k = 0$. Substituting them into the weighted mean gives

$$\begin{aligned} \lambda\bar{\boldsymbol{a}}_{\mathrm{capt}} &= \frac{1}{N}\sum_{k=1}^M N_k\lambda\boldsymbol{a}_k^{\mathrm{lin},*} && \text{(by Eq. (132))} \\ &= \frac{\kappa}{N}\sum_{k=1}^M N_k \sum_{i\in\mathcal{P}_k}\boldsymbol{z}_i - \left(\sum_{k=1}^M N_k\gamma_k^-\right)\bar{\boldsymbol{z}} && \text{(by Eqs. (59) and (130))} \\ &= \frac{\kappa}{N}\sum_{j=1}^N N_{t_j}\boldsymbol{z}_j - \frac{1}{N}\sum_{j=1}^N\left(\sum_{k=1}^M N_k\gamma_k^-\right)\boldsymbol{z}_j && \text{(since } j\in\mathcal{P}_{t_j} \text{ and } \bar{\boldsymbol{z}} = \tfrac{1}{N}\textstyle\sum_j \boldsymbol{z}_j\text{)} \\ &= \frac{\kappa}{N}\sum_{j=1}^N\left(N_{t_j} - \frac{1}{\kappa}\sum_{k=1}^M N_k\gamma_k^-\right)\boldsymbol{z}_j && \text{(collecting terms in } \boldsymbol{z}_j\text{)} \\ &= \frac{\kappa}{N}\sum_{j=1}^N h_j\boldsymbol{z}_j && \text{(by Eq. (141)).} \end{aligned} \tag{142}$$

Substituting this expression into Eq. (136) gives

$$\begin{aligned} \boldsymbol{e}_{\mathrm{capt}} &= -\frac{N}{2(N-1)\kappa}\bar{\boldsymbol{a}}_{\mathrm{capt}} \\ &= -\frac{1}{2(N-1)\lambda}\sum_{j=1}^N h_j\boldsymbol{z}_j. \end{aligned} \tag{143}$$

Fix a non-root k and $j \in \mathcal{P}_k$, so $t_j = k$. Substituting this shift and the text-side empirical-mean expression of Corollary D.2 into Eq. (137) gives

$$\begin{aligned}
\boldsymbol{z}_j^{\mathrm{lin},*} &= \frac{\kappa}{\lambda_Z}\left(\boldsymbol{a}_k^{\mathrm{lin},*} + \boldsymbol{e}_{\mathrm{capt}}\right) && \text{(by Eq. (137) with } t_j = k) \\
&= \frac{\kappa}{\lambda_Z}\left[\frac{\kappa N_k}{\lambda}\left(\bar{\boldsymbol{z}}_k - \xi_k^{\mathrm{lin}}\bar{\boldsymbol{z}}\right) - \frac{1}{2(N-1)\lambda}\sum_{i=1}^{N} h_i \boldsymbol{z}_i\right] && \text{(by Eqs. (67) and (143))} \\
&= \frac{\kappa^2 N_k}{\lambda\lambda_Z}\left(\bar{\boldsymbol{z}}_k - \xi_k^{\mathrm{lin}}\bar{\boldsymbol{z}} - \frac{1}{2\kappa(N-1)N_k}\sum_{i=1}^{N} h_i \boldsymbol{z}_i\right) && \text{(factoring out } \kappa^2 N_k/(\lambda\lambda_Z)). \quad (144)
\end{aligned}$$

The path-consistent captions and equal image counts across leaves from Section 4.1, together with Assumptions 4.1, 4.3, and 4.4, allow us to apply Lemma C.10 and Corollary C.11. With ξ_k^{lin} from Corollary 4.5, substituting Eq. (47) with $\boldsymbol{b}_k = \boldsymbol{b} = \boldsymbol{0}$ and $\boldsymbol{z}_i = \boldsymbol{\mu}_{y_i} + \boldsymbol{\varepsilon}_i$ for every $i \in [N]$ gives

$$\begin{aligned}
\frac{\lambda\lambda_Z}{\kappa^2 N_k}\boldsymbol{z}_j^{\mathrm{lin},*} &= (\boldsymbol{\mu}_k + \bar{\boldsymbol{\varepsilon}}_k) - \xi_k^{\mathrm{lin}}\left(\boldsymbol{\mu}_{\mathrm{root}} + \bar{\boldsymbol{\varepsilon}}\right) && \text{(by Eqs. (47) and (144))} \quad (145) \\
&\quad - \frac{1}{2\kappa(N-1)N_k}\sum_{i=1}^{N} h_i\left(\boldsymbol{\mu}_{y_i} + \boldsymbol{\varepsilon}_i\right) && (146) \\
&= \boldsymbol{\mu}_k - \xi_k^{\mathrm{lin}}\boldsymbol{\mu}_{\mathrm{root}} - \frac{1}{2\kappa(N-1)N_k}\sum_{i=1}^{N} h_i \boldsymbol{\mu}_{y_i} && \text{(grouping prototype and noise terms)} \\
& && (147) \\
&\quad + \left(\bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\mathrm{lin}}\bar{\boldsymbol{\varepsilon}} - \frac{1}{2\kappa(N-1)N_k}\sum_{i=1}^{N} h_i \boldsymbol{\varepsilon}_i\right). && (148)
\end{aligned}$$

The parenthesized noise term has zero mean by Assumption 4.1, so it equals $\boldsymbol{s}_k$ in Eq. (138). Thus the exact prototype decomposition is

$$\boldsymbol{z}_j^{\mathrm{lin},*} = \frac{\kappa^2 N_k}{\lambda\lambda_Z}\left(\boldsymbol{\mu}_k - \xi_k^{\mathrm{lin}}\boldsymbol{\mu}_{\mathrm{root}} - \frac{1}{2\kappa(N-1)N_k}\sum_{i=1}^{N} h_i \boldsymbol{\mu}_{y_i} + \boldsymbol{s}_k\right). \quad (149)$$

Step 2: Bound the caption-group and global means. By Assumption 4.3, $N_k \geq N_{\min} > 0$ for every non-root k, and by Assumption 4.1, the variations are independent, centered, and sub-Gaussian. Apply Lemma C.12 with $\mathcal{K} = V \setminus \{\mathrm{root}\}$, $I_k = \mathcal{P}_k$ for $k \in \mathcal{K}$, coefficients $\{\xi_k^{\mathrm{lin}}\}_{k\in\mathcal{K}}$, and $u = \log(8/\epsilon)$. Since $|\mathcal{K}| = M - 1$ and $\min_{k\in\mathcal{K}} |I_k| = N_{\min}$, with probability at least $1 - \epsilon/2$,

$$\max_{k\neq\mathrm{root}} \|\bar{\boldsymbol{\varepsilon}}_k - \xi_k^{\mathrm{lin}}\bar{\boldsymbol{\varepsilon}}\| \leq C\sigma\left(\sqrt{\frac{d + \log(M-1) + \log(8/\epsilon)}{N_{\min}}} + \xi_{\max}^{\mathrm{lin}}\sqrt{\frac{d + \log(8/\epsilon)}{N}}\right). \quad (150)$$

Step 3: Bound the common weighted shift and combine the events. We first control the caption-count weights. By Eq. (141), $N_{t_j} - h_j$ is nonnegative and takes the same value for every $j \in [N]$. Since $\sum_{k=1}^{M} N_k = N$, Cauchy–Schwarz gives $N^2 \leq M\sum_{k=1}^{M} N_k^2$. Hence

$$\begin{aligned}
&\sum_{j=1}^{N}\left(N_{t_j} + h_j\right) \\
&\quad = \sum_{j=1}^{N}\left[2N_{t_j} - \frac{1}{\kappa}\left(\frac{N}{2(M-1)} + \frac{\sum_{k=1}^{M} N_k^2}{2(N-1)}\right)\right] && \text{(by Eq. (141))} \\
&\quad = 2\sum_{k=1}^{M} N_k^2 - \frac{1}{\kappa}\left(\frac{N^2}{2(M-1)} + \frac{N\sum_{k=1}^{M} N_k^2}{2(N-1)}\right) && \text{(since } N_k \text{ images have } t_j = k) \\
&\quad \geq \left(2 - \frac{M}{2(M-1)} - \frac{N}{2(N-1)}\right)\sum_{k=1}^{M} N_k^2 && \text{(since } \kappa \geq 1 \text{ and } N^2 \leq M\textstyle\sum_k N_k^2) \\
&\quad \geq 0 && \text{(since } M \geq 2 \text{ and } N \geq 2). \quad (151)
\end{aligned}$$

Therefore, with $\boldsymbol{h} := (h_1, \ldots, h_N)$,

$$\begin{aligned}
\|\boldsymbol{h}\|^2 &= \sum_{j=1}^{N} N_{t_j}^2 - \sum_{j=1}^{N} \big(N_{t_j} - h_j\big)\big(N_{t_j} + h_j\big) && \text{(difference of squares)} \\
&\le \sum_{j=1}^{N} N_{t_j}^2 && \text{(by Eq. (151), since } N_{t_j} - h_j \ge 0 \text{ is constant)} \\
&= \sum_{k=1}^{M} N_k^3 && \text{(since } N_k \text{ images have } t_j = k\text{).} \qquad (152)
\end{aligned}$$

The Hoeffding and net argument in the proof of Lemma C.12 applies to the fixed weights $\boldsymbol{h}$ and gives $\Pr\big(\|\sum_{j=1}^{N} h_j \boldsymbol{\varepsilon}_j\| > C\sigma\|\boldsymbol{h}\|\sqrt{d+t}\big) \le 2e^{-t}$ for every $t > 0$. Taking $t = \log(4/\epsilon)$ makes the probability of exceeding this bound at most $\epsilon/2$. On the complementary event,

$$\begin{aligned}
&\max_{k \ne \text{root}} \left\| \frac{1}{2\kappa(N-1)N_k} \sum_{j=1}^{N} h_j \boldsymbol{\varepsilon}_j \right\| \\
&\le \frac{1}{2(N-1)N_{\min}} \left\| \sum_{j=1}^{N} h_j \boldsymbol{\varepsilon}_j \right\| && \text{(since } \kappa \ge 1 \text{ and } N_k \ge N_{\min}\text{)} \\
&\le \frac{C\sigma\|\boldsymbol{h}\|\sqrt{d + \log(4/\epsilon)}}{2(N-1)N_{\min}} && \text{(by the Hoeffding bound with } t = \log(4/\epsilon)\text{)} \\
&\le \frac{C\sigma\sqrt{\sum_{k=1}^{M} N_k^3}\sqrt{d + \log(4/\epsilon)}}{2(N-1)N_{\min}} && \text{(by Eq. (152))} \\
&= \frac{C}{2}\,\sigma\,\omega\sqrt{\frac{d + \log(4/\epsilon)}{N_{\min}}} && \text{(by Eq. (139)).} \qquad (153)
\end{aligned}$$

Since $\log(4/\epsilon) \le \log(M-1) + \log(8/\epsilon)$, a union bound over the two failure events gives Eq. (140) with probability at least $1 - \epsilon$. □

In Lemma C.13, we bound per-instance input noise at scale $C\sigma\sqrt{d + \log(2N/\epsilon)}$. The caption-group term in Eq. (140) is smaller by order $\sqrt{N_{\min}}/(1+\omega)$, up to logarithmic factors. The separate $N^{-1/2}$ term comes from the global image mean.

The result concerns one exact alternating step under the linear loss, so it is an analytic surrogate for joint gradient descent rather than a model of CLIP training. The bound controls stochastic deviation around the caption-grouped prototype decomposition, not the deterministic prototype margin: reduced variation can protect a small positive margin, but the bound alone does not certify reversal of a negative margin. Whether the same contraction holds for the subtree-aggregated prototypes of Section 3.2, which mix caption groups along root-to-node paths, remains open.

L Relaxing the Caption-Symmetry Assumptions

In Lemma F.1, $\mathcal{HAS}$ transfer under observed captions depends on a bound on caption bias. In Appendix L.1, we bound two sources of that bias, caption imbalance and inexact prototype consistency, and give transfer conditions for both losses. We then examine partial ancestor omission, which creates random caption imbalance, in Appendix L.2. Finally, in Appendix L.3, we analyze total omission, for which a caption mean is undefined. Throughout this section, we sample exactly c images per leaf as in Section 4.1. In Appendix J.5, we support these bounds with empirical results: permuting which images match each caption increases the caption bias well outside the small-bias regime of Corollary L.2, and approximate $\mathcal{HAS}$ transfer fails.

L.1 Caption Imbalance and Inexact Prototype Consistency

Caption imbalance changes how leaf prototypes contribute to a concept's caption mean. For example, `dog` captions drawn mostly from dalmatians overrepresent one descendant leaf; off-path captions add images from outside the dog's subtree. Inexact prototype consistency adds bias even when captions are leaf-uniform. To bound these effects, for every non-root node k, split its positive set into

$$\mathcal{P}_k^{\mathrm{on}} := \{j \in \mathcal{P}_k : y_j \in \mathrm{Sub}(k)\}, \qquad \mathcal{P}_k^{\mathrm{off}} := \mathcal{P}_k \setminus \mathcal{P}_k^{\mathrm{on}}, \tag{154}$$

where $L_k := \mathrm{Sub}(k) \cap V_{\mathrm{leaf}}$ denotes the leaf descendants of each node $k \in V$, and $n_{k\ell}^{\mathrm{on}} := |\{j \in \mathcal{P}_k^{\mathrm{on}} : y_j = \ell\}|$ for $\ell \in L_k$ counts its on-path captions from leaf ℓ. A nonempty, leaf-uniform on-path set has prototype mean $\frac{1}{|L_k|}\sum_{\ell \in L_k} \boldsymbol{\mu}_\ell$, which equals $\boldsymbol{\mu}_k$ under Assumption 4.4. When every non-root node has $N_k > 0$, define the caption imbalance by

$$\delta_{\mathrm{cap}} := \max_{k \neq \mathrm{root}} \Bigg[\underbrace{\frac{1}{N_k} \underbrace{\sum_{\ell \in L_k}}_{\text{leaves of } k} \overbrace{\left| n_{k\ell}^{\mathrm{on}} - \frac{|\mathcal{P}_k^{\mathrm{on}}|}{|L_k|} \right|}^{\text{extra or missing captions of leaf } \ell} \overbrace{\|\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\|}^{\text{prototype distance of leaf } \ell}}_{\text{uneven leaf coverage}} + \underbrace{\frac{1}{N_k} \underbrace{\sum_{j \in \mathcal{P}_k^{\mathrm{off}}}}_{\substack{\text{images captioned } k \\ \text{with leaf outside } \mathrm{Sub}(k)}} \overbrace{\|\boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k\|}^{\text{prototype distance of image } j}}_{\text{off-path captions}} \Bigg], \tag{155}$$

and the prototype mismatch by

$$\delta_{\mathrm{cons}} := \max_{k \in V} \left\| \frac{1}{|L_k|} \sum_{\ell \in L_k} \boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k \right\|. \tag{156}$$

The maximum in δ_{cons} includes the root because its prototype mismatch contributes to the global caption bias.

Lemma L.1 (Caption bias under imbalanced captions and inexact prototypes)**.** *Suppose exactly c images are sampled per leaf and the observed captions satisfy $N_k > 0$ for every non-root node k. Write $\boldsymbol{b}_k := \bar{\boldsymbol{\mu}}_k - \boldsymbol{\mu}_k$ for the caption bias of each non-root node k and $\boldsymbol{b} := \bar{\boldsymbol{\mu}} - \boldsymbol{\mu}_{\mathrm{root}}$ for the global caption bias, as in Definition C.9. Then*

$$\|\boldsymbol{b}\| \le \delta_{\mathrm{cons}}, \qquad \max_{k \neq \mathrm{root}} \|\boldsymbol{b}_k\| \le \delta_{\mathrm{cap}} + \delta_{\mathrm{cons}}. \tag{157}$$

In particular, $\delta_{\mathrm{cap}} + (1 + \xi_{\max})\delta_{\mathrm{cons}}$ is a caption bias bound for any coefficients $\{\xi_k \in \mathbb{R}\}_{k \in V \setminus \{\mathrm{root}\}}$, where $\xi_{\max} := \max_{k \neq \mathrm{root}} |\xi_k|$. Under Assumption 4.4, $\boldsymbol{b} = \mathbf{0}$ and δ_{cap} is a caption bias bound for any such coefficients.

Proof. Balanced image sampling gives

$$\begin{aligned} \boldsymbol{b} &= \bar{\boldsymbol{\mu}} - \boldsymbol{\mu}_{\mathrm{root}} && \text{(by Definition C.9)} \\ &= \frac{1}{|V_{\mathrm{leaf}}|} \sum_{\ell \in V_{\mathrm{leaf}}} \boldsymbol{\mu}_\ell - \boldsymbol{\mu}_{\mathrm{root}} && \text{(since each leaf contributes } c \text{ images).} \end{aligned}$$

Since $L_{\mathrm{root}} = V_{\mathrm{leaf}}$, this is the root term in Eq. (156), so $\|\boldsymbol{b}\| \le \delta_{\mathrm{cons}}$. For a non-root node k with $\mathcal{P}_k^{\mathrm{on}} \neq \varnothing$, grouping images by their leaf and adding and subtracting the centroid of the descendant leaf prototypes give

$$\begin{aligned} \frac{1}{|\mathcal{P}_k^{\mathrm{on}}|} \sum_{j \in \mathcal{P}_k^{\mathrm{on}}} \left(\boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k\right) &= \sum_{\ell \in L_k} \frac{n_{k\ell}^{\mathrm{on}}}{|\mathcal{P}_k^{\mathrm{on}}|} \left(\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\right) \\ &= \sum_{\ell \in L_k} \left(\frac{n_{k\ell}^{\mathrm{on}}}{|\mathcal{P}_k^{\mathrm{on}}|} - \frac{1}{|L_k|} \right) \left(\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\right) + \left(\frac{1}{|L_k|} \sum_{\ell \in L_k} \boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k \right). \end{aligned} \tag{158}$$

By Definition C.9 and the split in Eq. (154),

$$\boldsymbol{b}_k = \frac{1}{N_k} \sum_{j \in \mathcal{P}_k^{\mathrm{on}}} \left(\boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k\right) + \frac{1}{N_k} \sum_{j \in \mathcal{P}_k^{\mathrm{off}}} \left(\boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k\right). \tag{159}$$

For $\mathcal{P}_k^{\mathrm{on}} = \varnothing$, the first sum in Eq. (159) is zero. Otherwise, substituting Eq. (158) into that sum and applying the triangle inequality give

$$\begin{aligned}\|\boldsymbol{b}_k\| &\le \frac{1}{N_k}\sum_{\ell\in L_k}\left|n_{k\ell}^{\mathrm{on}} - \frac{|\mathcal{P}_k^{\mathrm{on}}|}{|L_k|}\right|\|\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\| + \frac{1}{N_k}\sum_{j\in\mathcal{P}_k^{\mathrm{off}}}\|\boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k\| \\ &\quad + \frac{|\mathcal{P}_k^{\mathrm{on}}|}{N_k}\left\|\frac{1}{|L_k|}\sum_{\ell\in L_k}\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\right\| \\ &\le \delta_{\mathrm{cap}} + \delta_{\mathrm{cons}},\end{aligned}$$

since the first two terms are the bracket in Eq. (155) at node k and $|\mathcal{P}_k^{\mathrm{on}}| \le N_k$. The same bound holds when $\mathcal{P}_k^{\mathrm{on}} = \varnothing$, because only the off-path sum then remains. Taking the maximum over non-root k gives the second bound in Eq. (157). Since $|\xi_k| \le \xi_{\max}$ for every non-root k, the triangle inequality gives

$$\max_{k\neq\mathrm{root}}\|\boldsymbol{b}_k - \xi_k\boldsymbol{b}\| \le \max_{k\neq\mathrm{root}}\|\boldsymbol{b}_k\| + \xi_{\max}\|\boldsymbol{b}\| \le \delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}},$$

so $\delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}}$ is a caption bias bound by Eq. (105). Under Assumption 4.4, $\delta_{\mathrm{cons}} = 0$, so $\boldsymbol{b} = \mathbf{0}$ and this value reduces to δ_{cap} for any coefficients. □

By Lemma L.1, we can use $\delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}}$ as the additive bias value in Lemma F.1. The next corollary gives the resulting transfer conditions. Within this bound, the uneven-coverage term vanishes for leaf-uniform on-path captions, the off-path term vanishes for path-consistent captions, and δ_{cons} vanishes under Assumption 4.4.

Corollary L.2 ($\mathcal{HAS}$ transfer under imbalanced captions and inexact prototypes)**.** *Suppose Assumption 4.1 holds, exactly c images are sampled per leaf, $\rho_{\min} > 0$, and the observed captions are deterministic with $N_k > 0$ for every non-root node k. Assumption 4.4 need not hold. Fix $\epsilon \in (0,1)$ and $\lambda > 0$. For the loss under consideration, compute $\xi_{\max}$ from its coefficients, assume the corresponding case below, and let τ denote its threshold.*

Linear loss. *Assume $D_\epsilon + \delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}} < \rho_{\min}/4$ and set*

$$\tau := \frac{8\left(D_\epsilon + \delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}}\right)}{\rho_{\min}}. \tag{160}$$

InfoNCE. *Assume $D_\epsilon^{\mathrm{nce}} > 0$, $\lambda \ge \lambda_0(\epsilon)$, and $2D_\epsilon^{\mathrm{nce}} + \delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}} < \rho_{\min}/4$, and set*

$$\tau := \frac{8\left(2D_\epsilon^{\mathrm{nce}} + \delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}}\right)}{\rho_{\min}}. \tag{161}$$

Then, with probability at least $1-\epsilon$, all of the following hold simultaneously:

- *(i) $\boldsymbol{a}_k \neq \mathbf{0}$ for every non-root node k;*
- *(ii) every admissible triplet (u,v,w) with $\gamma_{uvw} > \tau$ satisfies $\cos(\boldsymbol{a}_u, \boldsymbol{a}_v) > \cos(\boldsymbol{a}_u, \boldsymbol{a}_w)$;*
- *(iii) $\mathcal{HAS}\text{-Viol}^{\mathrm{txt}}(u) \le \mathcal{HAS}\text{-Viol}_\tau^{\mathrm{img}}(u)$ for every non-root non-leaf node u, with $\mathcal{HAS}\text{-Viol}^{\mathrm{txt}}(u)$ computed on $\{\boldsymbol{a}_k\}_{k\neq\mathrm{root}}$.*

Proof. By Lemma L.1, $\delta_{\mathrm{cap}} + (1+\xi_{\max})\delta_{\mathrm{cons}}$ is a caption bias bound, so we can take δ_{bias} equal to it. By Eq. (107), $D_\epsilon^{\mathrm{bias}}$ then equals $D_\epsilon + \delta_{\mathrm{bias}}$ for the linear loss and $2D_\epsilon^{\mathrm{nce}} + \delta_{\mathrm{bias}}$ for InfoNCE. In both cases, it is less than $\rho_{\min}/4$ by assumption, and $\tau_\epsilon^{\mathrm{bias}}$ equals the threshold τ in Eq. (160) or (161). The remaining InfoNCE hypotheses, $D_\epsilon^{\mathrm{nce}} > 0$ and $\lambda \ge \lambda_0(\epsilon)$, also hold by assumption. Applying Lemma F.1 with this δ_{bias} therefore gives parts (i)–(iii) at τ with probability at least $1-\epsilon$. □

L.2 Partial Ancestor Omission

The deterministic bound above applies to each realized caption assignment. To study the random imbalance caused by ancestor omission, we fix the image sample and independently retain each occurrence of a concept caption with the same probability across leaves. Conditional on the retained count, the positive set is a uniform sample of the original leaf-uniform captions. We can therefore bound its expected bias separately from the effect of a smaller N_k on the stochastic transfer term.

Lemma L.3 (Caption bias under partial ancestor omission)**.** *Suppose Assumption 4.4 holds, and fix a non-root node k with subtree radius $R_k := \max_{\ell \in L_k} \|\boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k\|$. Suppose that, before omission, the positive set of k contains equally many images from each leaf in L_k, and that each of these images independently keeps caption k with the same probability. Then, for every $n \geq 1$ with $\Pr(N_k = n) > 0$, the caption bias of the retained positive set satisfies*

$$\boldsymbol{E}\left[\boldsymbol{b}_k \mid N_k = n\right] = \mathbf{0}, \qquad \boldsymbol{E}\left[\|\boldsymbol{b}_k\| \mid N_k = n\right] \leq \frac{R_k}{\sqrt{n}}. \tag{162}$$

Proof. Condition on $N_k = n$, and let $\mathcal{P}_k^{\mathrm{full}}$ be the positive set of k before omission. Since every image keeps caption k independently with the same probability, the retained positive set $\mathcal{P}_k$ is a uniformly random n-subset of $\mathcal{P}_k^{\mathrm{full}}$. Write $\boldsymbol{x}_j := \boldsymbol{\mu}_{y_j} - \boldsymbol{\mu}_k$ for $j \in \mathcal{P}_k^{\mathrm{full}}$, so that $\|\boldsymbol{x}_j\| \leq R_k$ and

$$\begin{aligned}
\frac{1}{|\mathcal{P}_k^{\mathrm{full}}|} \sum_{j \in \mathcal{P}_k^{\mathrm{full}}} \boldsymbol{x}_j &= \frac{1}{|L_k|} \sum_{\ell \in L_k} \boldsymbol{\mu}_\ell - \boldsymbol{\mu}_k && \text{(equal image counts across } L_k\text{)} \\
&= \mathbf{0} && \text{(by Assumption 4.4).}
\end{aligned}$$

Hence

$$\begin{aligned}
\mathbf{E}[\boldsymbol{b}_k \mid N_k = n] &= \mathbf{E}\left[\frac{1}{n} \sum_{j \in \mathcal{P}_k} \boldsymbol{x}_j \,\middle|\, N_k = n\right] && \text{(by Definition C.9)} \\
&= \frac{1}{|\mathcal{P}_k^{\mathrm{full}}|} \sum_{j \in \mathcal{P}_k^{\mathrm{full}}} \boldsymbol{x}_j && \text{(each image is retained with probability } n/|\mathcal{P}_k^{\mathrm{full}}|\text{)} \\
&= \mathbf{0} && \text{(by the zero average above).}
\end{aligned}$$

Sampling without replacement has variance at most that of sampling with replacement, so

$$\begin{aligned}
\mathbf{E}[\|\boldsymbol{b}_k\| \mid N_k = n] &\leq \sqrt{\mathbf{E}[\|\boldsymbol{b}_k\|^2 \mid N_k = n]} && \text{(by Jensen's inequality)} \\
&\leq \sqrt{\frac{1}{n} \cdot \frac{1}{|\mathcal{P}_k^{\mathrm{full}}|} \sum_{j \in \mathcal{P}_k^{\mathrm{full}}} \|\boldsymbol{x}_j\|^2} && \text{(variance with replacement, zero average)} \\
&\leq \frac{R_k}{\sqrt{n}} && \text{(since } \|\boldsymbol{x}_j\| \leq R_k\text{).}
\end{aligned}$$

□

Omission can also lower N_k, which affects the stochastic transfer term through the realized $N_{\min}$ and $\xi_{\max}$. If the resulting labels remain path-consistent, are independent of the image variations, and keep $N_k > 0$ for every non-root node k, we can condition on them and apply Corollary L.2. The off-path term in δ_{cap} is then zero, as is δ_{cons} under Assumption 4.4.

With leaf-dependent retention, $\mathbf{E}[\boldsymbol{b}_k \mid N_k = n]$ need not vanish. For each realized path-consistent assignment, we can still use Lemma L.1 to bound the caption bias by the δ_{cap} of that assignment, whose off-path term is zero.

L.3 Total Caption Omission: Collapse of Uncaptioned Concepts

When $N_k = 0$, the caption mean is undefined, so the transfer corollary does not apply. We analyze the optimizer directly to determine how uncaptioned concepts affect $\mathcal{HAS}$.

Proposition L.4 (Collapse of uncaptioned concepts)**.** *Fix the image features and observed captions, let $\lambda > 0$, and define the uncaptioned non-root concepts by*

$$U := \{k \in V \setminus \{\mathrm{root}\} : N_k = 0\}. \tag{163}$$

Under either the linear contrastive loss of Eq. (5) *or the InfoNCE loss of Eq.* (9)*, every pair of distinct concepts in U has equal optimal text embeddings. For every non-root non-leaf node u, write*

$\mathcal{O}_u := V \setminus \big(\mathrm{Sub}(u) \cup \mathrm{Anc}(u)\big)$ *for its off-branch set. If the optimal text embeddings are nonzero at every non-root node, then every such* u *with* $U \cap \mathrm{Desc}(u) \neq \varnothing$ *satisfies*

$$\mathcal{HAS}\text{-Viol}^{\mathrm{txt}}(u) \geq \frac{|U \cap \mathcal{O}_u|}{|\mathcal{O}_u|} \times 100\%. \tag{164}$$

In particular, $\mathcal{HAS}$ *cannot hold if some non-root non-leaf node* u *has both* $U \cap \mathrm{Desc}(u) \neq \varnothing$ *and* $U \cap \mathcal{O}_u \neq \varnothing$*. Under the linear contrastive loss, every uncaptioned concept* k *also has the exact embedding*

$$\boldsymbol{a}_k^{\mathrm{lin},*} = -\frac{N}{2(M-1)\lambda}\,\bar{\boldsymbol{z}}. \tag{165}$$

Proof. Fix either loss and write $\{\boldsymbol{a}_m\}_{m\in[M]}$ for its optimal text embeddings. Let $k \neq k'$ belong to U. Exchanging $\boldsymbol{a}_k$ and $\boldsymbol{a}_{k'}$ leaves the objective unchanged. Neither index occurs in a positive term or a text-to-image term, the image-to-text terms sum symmetrically over concept indices, and the ridge penalty assigns the same coefficient to both embeddings. The linear loss has a unique minimizer by Proposition D.1, and the InfoNCE loss has a unique minimizer by Lemma E.1. The swapped optimizer must therefore equal the original optimizer, so $\boldsymbol{a}_k = \boldsymbol{a}_{k'}$.

Suppose every non-root $\boldsymbol{a}_m$ is nonzero, and fix a non-root non-leaf node u with $U \cap \mathrm{Desc}(u) \neq \varnothing$. Choose $v \in U \cap \mathrm{Desc}(u)$. For every $w \in U \cap \mathcal{O}_u$, the equality above gives $\boldsymbol{a}_w = \boldsymbol{a}_v$, and therefore

$$c_u^{\mathrm{txt}} \leq \cos(\boldsymbol{a}_u, \boldsymbol{a}_v) = \cos(\boldsymbol{a}_u, \boldsymbol{a}_w),$$

where c_u^{txt} is the descendant threshold in Definition C.7 at zero slack. Thus every $w \in U \cap \mathcal{O}_u$ is counted in $\mathcal{HAS}\text{-Viol}^{\mathrm{txt}}(u)$, which proves Eq. (164). If $U \cap \mathrm{Desc}(u)$ and $U \cap \mathcal{O}_u$ are both nonempty, the right-hand side of Eq. (164) is positive, so $\mathcal{HAS}$ cannot hold. If any non-root optimal text embedding is zero, the required cosine is undefined, so $\mathcal{HAS}$ cannot hold in that case either.

For the additional linear characterization, fix an uncaptioned concept k. Then $Y_{kj} = N_k = 0$ for every $j \in [N]$, so Eq. (58) gives

$$\begin{aligned} B_{kj} &= \frac{1}{2}\left(0 - \frac{1}{M-1}\right) + \frac{1}{2}\left(0 - \frac{0}{N-1}\right) \\ &= -\frac{1}{2(M-1)}. \end{aligned}$$

By Proposition D.1, the optimal embedding is therefore

$$\begin{aligned} \boldsymbol{a}_k^{\mathrm{lin},*} &= \frac{1}{\lambda}\sum_{j=1}^{N} B_{kj}\boldsymbol{z}_j && \text{(by Eq. (59))} \\ &= -\frac{1}{2(M-1)\lambda}\sum_{j=1}^{N}\boldsymbol{z}_j && \text{(substituting } B_{kj}\text{)} \\ &= -\frac{N}{2(M-1)\lambda}\bar{\boldsymbol{z}} && \text{(by the definition of } \bar{\boldsymbol{z}}\text{),} \end{aligned}$$

which is Eq. (165). □

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The theoretical and empirical results are consistent with the claims made in the abstract and introduction.

   Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Limitations of our assumptions are mentioned at the end of Section 4.3.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [Yes]

   Justification: All assumptions are provided before the results are stated, and proofs are provided in the appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.

- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Hyperparameters and evaluation protocols are detailed either in the main text or in the appendix where relevant.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code will be released upon acceptance. Used datasets/models are public.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.

- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: The experimental setting and hyperparameters are detailed either in the main text or in the appendix where relevant.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Error bars are reported in relevant plots.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
   - The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
   - The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
   - The assumptions made should be given (e.g., Normally distributed errors).
   - It should be clear whether the error bar is the standard deviation or the standard error of the mean.
   - It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
   - For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
   - If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: The GPUs we use are several NVIDIA RTX A5000 GPUs (24 GB each). More details are in Appendix J.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The research conducted in the paper follows the NeurIPS Code of Ethics.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [N/A]

    Justification: This is a theoretical paper analyzing the geometry of pretrained CLIP embeddings, and we do not identify direct positive or negative societal consequences that warrant specific discussion.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The paper poses no such risks.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: All existing assets used in the paper are publicly released and credited at the point of use:

- WordNet 3.0 [6]: BSD-style Princeton WordNet License, free for research and commercial use with attribution.
- ImageNet-1K [42]: ImageNet terms of access, non-commercial research use.
- OpenAI CLIP checkpoints [1]: MIT License, via the official `openai/CLIP` release.
- OpenCLIP code and checkpoints [43]: MIT License, via `mlfoundations/open_clip`.
- DataComp / DataComp-1B [44]: MIT License, via `mlfoundations/datacomp`.

We use these assets within their stated terms.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [N/A]

Justification: The paper does not release new assets.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.

- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: This paper does not involve crowdsourcing nor research with human subjects. The experiments were conducted on existing datasets and pre-trained models.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: This paper does not involve crowdsourcing nor research with human subjects. The experiments were conducted on existing datasets and pre-trained models.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [N/A]

    Justification: LLMs were used only for editing purposes, not for the core methods.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.