Table of Contents

End-User Guide – translator_docs_book_v5.exe

Document version: 1.0
Audience: Windows end users
Purpose: run batch document translation with the translator_docs_book_v5.exe command-line executable

---

1. Overview

translator_docs_book_v5.exe is a batch-oriented document translation tool. It can accept **a single file** or **an input folder**, extract content, perform OCR when needed, translate into a target language, and export a structured output package with translated text, bilingual output, logs, indexes, and reports.

Common file groups

- PDF
- Word (.docx)
- PowerPoint (.pptx)
- Excel (.xlsx)
- EPUB / ebook
- HTML / Markdown / TXT / CSV / JSON / XML / YAML

Typical use cases

- Batch translation of technical or regulatory document sets
- Pharmacopoeia, submission dossiers, SMPC/PIL packages
- Internal review packages with traceable output
- QA-oriented runs with logs and segment-level reports

---

2. Requirements

Operating system

- Windows 10 or Windows 11

How to run in PowerShell

If you are already in the folder that contains the EXE, use:

.\translator_docs_book_v5.exe

In PowerShell, do not rely on translator_docs_book_v5.exe alone when the file is in the current directory.

Supporting components

- **Tesseract OCR**: required for scanned or image-based PDFs
- **LibreOffice**: useful for some legacy Office formats
- **Calibre**: useful for some extended ebook formats

If your software package already bundles these components, no extra setup is needed. Otherwise, ask your deployment or support team to install them.

---

3. Basic syntax

```
.\translator_docs_book_v5.exe "INPUT_PATH" --out "OUTPUT_PATH"
```

Where: - INPUT_PATH: path to **a file** or **a folder** - --out: root folder for all generated output

Minimal example

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output"
```

---

4. Quick-start scenarios

4.1. Translate a mixed PDF/Office folder into Vietnamese

```
.\translator_docs_book_v5.exe "D:\Regulatory\Input" --out "D:\Regulatory\Output_VI" --ocr auto --source-lang auto --target-lang vi
```

4.2. Translate scanned Chinese PDFs into Vietnamese

```
.\translator_docs_book_v5.exe "D:\ChineseDocs" --out "D:\ChineseDocs_VI" --ocr all --ocr-lang chi_sim+eng --source-lang zh-CN --target-lang vi
```

4.3. Translate scanned Japanese PDFs into English

```
.\translator_docs_book_v5.exe "D:\JP_PDF" --out "D:\JP_PDF_EN" --ocr all --ocr-lang jpn+eng --source-lang ja --target-lang en
```

4.4. Test only the first three files

```
.\translator_docs_book_v5.exe "D:\LargeInput" --out "D:\TestOutput" --max-files 3 --ocr auto --source-lang auto --target-lang vi
```

4.5. Extract only, no translation

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\ExtractOnly" --translator none
```

---

5. Most important options

5.1. Input and output

Option	Meaning	When to use it
input_path	Source file or folder	Required for real processing
--out	Output root folder	Required for real processing
--flat	Do not scan subfolders recursively	Use when you want the current level only
--max-files N	Process only the first N files	Use for quick testing
--no-copy-original	Do not copy the original file into the output structure	Use to save disk space

5.2. OCR

Option	Meaning	Recommendation
--ocr off	Disable OCR	Use only for text-based PDFs
--ocr auto	OCR only when needed	Safest choice for most runs
--ocr all	OCR every page	Use for scanned PDFs
--ocr-lang ...	OCR language pack	Example: chi_sim+eng, chi_tra+eng, jpn+eng
--ocr-min-native-chars N	Threshold for low native text detection	Advanced usage
--tesseract-exe	Path to tesseract.exe	Use when you must point to a specific install
--tessdata-dir	Path to tessdata	Use when you must point to a specific install

5.3. Translation

Option	Meaning	Recommendation
--translator deep_translator	Use the default translator backend	Standard choice
--translator none	Skip translation and keep only extraction/output flow	Useful for extraction tests
--source-lang	Source language	auto, zh-CN, zh-TW, ja, en, vi, etc.
--target-lang	Target language	Example: vi, en
--sleep-seconds	Delay between translation chunks	Default is usually sufficient
--retries	Number of retry attempts	Increase if the service is unstable
--retry-delay	Delay between retries	Use together with --retries

Option	Meaning	Recommendation
--max-chunk-chars	Maximum chunk length	Change only for advanced tuning
--keep-source-on-error	Keep source text when translation fails	Helpful for QA review

5.4. Reuse, skip, or force reprocessing

Option	Meaning
--overwrite-translation	Ignore old translations and translate everything again
--no-skip-existing	Process documents even if a previous run marked them complete
--retranslate-errors-only	Retry only failed segments
--no-reuse-extraction	Re-extract content instead of using cached extraction

5.5. Inspection and environment checks

Option	Meaning
--show-config	Print the parsed runtime configuration and exit
--list-supported-formats	Print supported extensions and exit
--show-tesseract-info	Print Tesseract runtime information and exit

6. Output structure

Each input document typically gets its own document folder inside OUTPUT_PATH. Common generated artifacts include:

- 01_source – original file copy
- 02_extracted/extracted_document.json – structured extracted data
- 02_extracted/full_source.txt – full extracted source text
- 03_translation/translation_bundle.json – segment-level translation bundle
- 03_translation/full_target.txt – full translated output
- 03_translation/bilingual.md – bilingual output
- 03_translation/target_only.md – target-only output
- 04_indexes/segment_index.csv – segment index
- 04_indexes/translation_memory.csv – translation memory
- 08_logs/translation_log.csv – detailed translation log
- 09_reports/translation_report.json – per-document report
- manifest.json – document metadata

- batch_summary.json – batch-level summary

Which files to check first

1. batch_summary.json – overall processed / skipped / failed counts
2. 09_reports/translation_report.json – document-level details
3. 08_logs/translation_log.csv – segment-level problems
4. 03_translation/bilingual.md – quick human-readable review output

---

7. Recommended end-user workflow

Step 1 – Prepare the input folder

- Place source documents in a clean folder
- Split by project or language if needed
- Avoid extremely long paths or unusual special characters

Step 2 – Run a small pilot first

Use --max-files 3 or a small subfolder before a full batch.

Step 3 – Pick the right OCR mode

- Text PDF: --ocr off or --ocr auto
- Scanned PDF: --ocr all
- Mixed / unsure: --ocr auto

Step 4 – Run the full batch

Once the pilot looks good, remove --max-files and run the full folder.

Step 5 – Review the report and bilingual output

Open batch_summary.json, translation_report.json, bilingual.md, and translation_log.csv.

---

8. Suggested scenario presets

Scenario A – Chinese pharmacopoeia, scanned PDF

Recommended: - --ocr all - --ocr-lang chi_sim+eng - --source-lang zh-CN - --target-lang vi

Scenario B – Japanese SMPC/PIL package

Recommended: - --ocr auto or --ocr all - --ocr-lang jpn+eng - --source-lang ja - --target-lang en

Scenario C – Internal Word/PowerPoint/Excel package

Recommended: - --ocr off or --ocr auto - --source-lang auto - --target-lang vi

Scenario D – QA / error follow-up

Recommended: - --keep-source-on-error - --retranslate-errors-only

---

9. Troubleshooting

9.1. PowerShell says the EXE is not recognized

Most common cause: you did not prefix the file with .\.

Correct:

```
.\translator_docs_book_v5.exe
```

9.2. OCR output is poor or empty

- Check whether you are using --ocr off
- Check whether Tesseract is available
- Run --show-tesseract-info
- Try --ocr all

9.3. Some files are skipped

A previous run may have already marked those documents as complete. Try:

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output" --overwrite-translation --no-skip-existing
```

9.4. Retry only failed parts

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output" --retranslate-errors-only
```

9.5. Inspect the resolved runtime config before processing

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output" --ocr auto --source-lang auto --target-lang vi --show-config
```

---

10. Recommended command templates

Template 1 – Translate a folder into Vietnamese

```
.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output_VI" --ocr auto --source-lang auto --target-lang vi
```

Template 2 – Translate scanned Chinese PDFs into Vietnamese

.\translator_docs_book_v5.exe "D:\ChinesePDF" --out "D:\ChinesePDF_VI" --ocr all --ocr-lang chi_sim+eng --source-lang zh-CN --target-lang vi

Template 3 – Translate scanned Japanese PDFs into English

.\translator_docs_book_v5.exe "D:\JapanesePDF" --out "D:\JapanesePDF_EN" --ocr all --ocr-lang jpn+eng --source-lang ja --target-lang en

Template 4 – Pilot run on the first five files

.\translator_docs_book_v5.exe "D:\LargeBatch" --out "D:\LargeBatch_Test" --max-files 5 --ocr auto --source-lang auto --target-lang vi

Template 5 – List supported formats

.\translator_docs_book_v5.exe --list-supported-formats

Template 6 – Check Tesseract runtime info

.\translator_docs_book_v5.exe --show-tesseract-info

---

11. Operational recommendations

- Always start with a small pilot run
- For scanned PDFs, prefer --ocr all when the extracted text quality is poor
- For very large folders, split by project or language
- Always review batch_summary.json after each batch
- Use bilingual.md for quick quality checks
- Keep indexes and logs enabled unless you have a specific reason to disable them

---

12. Internal support handoff checklist

When opening a support ticket or escalation, include: - the exact command you ran - batch_summary.json - translation_report.json - translation_log.csv - one or two representative source files - a screenshot of the error if available

---

Appendix A – Full option list

input_path
--out
--flat
--max-files
--no-copy-original
--ocr {auto,off,all}
--ocr-lang
--ocr-min-native-chars

--translator {deep_translator,none}
--source-lang
--target-lang
--overwrite-translation
--no-skip-existing
--retranslate-errors-only
--keep-source-on-error
--sleep-seconds
--retries
--retry-delay
--max-chunk-chars
--folder-style {auto,hash12,plain}
--tesseract-exe
--tessdata-dir
--show-tesseract-info
--list-supported-formats
--show-config
--no-reuse-extraction
--no-write-indexes
--no-write-translation-memory

Appendix B – Best first-run command

.\translator_docs_book_v5.exe "D:\Input" --out "D:\Output" --ocr auto --source-lang auto --target-lang vi