Faculty of Computer Science & Engineering

Operating Systems

Contact:
Trần Ngọc Anh Tú
51304672@hcmut.edu.vn

Ho Chi Minh City
University of Technology

Lab 4 - Process

Objective

- Know how data are layout inside a process
- Understand dynamic memory allocation mechanism

Inside a process

- Each process has its own address space which is a set of memory addresses that a process can access.
- Address space is a large array of bytes starting at 0 and going up to some large number $2^{32} - 1$ or $2^{64} - 1$
- The address space is split into multiple parts, each part holds different parts of the process
  - Text
  - Data
  - Heap
  - Stack

Inside a process

- Exercise: Given following program, identify the memory segments which variables (or function) belongs to.

- global_f
- local_f
- func
- dynamic_f

```
#include <stdio.h>
#include <stdlib.h>
int global_f = 10;
int func() {
  return 0;
}
int main() {
  int local_f = 100;
  int *dynamic_f = (int*)malloc(sizeof(int));
  printf("global_f:  %p\n", &global_f);
  printf("local_f:   %p\n", &local_f);
  printf("func:      %p\n", &func);
  printf("dynamic_f: %p\n", dynamic_f);
}
```

Inside a process

- Exercise: Given following program, identify the memory segments which variables (or function) belongs to.

  - `global_f`
  - `local_f`
  - `func`
  - `dynamic_f`



Inside a process

- Exercise: Given following program, identify the memory segments which variables (or function) belongs to.

  - `global_f`
  - `local_f`
  - `func`
  - `dynamic_f`



Process address space in Linux



Heap region

- The heap is placed right after data region in address space.
- break (program break) separates used regions and unused regions.
- Heap increases upward but the break cannot go through rlimit



Heap region

- We could increase or decrease the size of heap region by using two system calls:
  - brk ->changes the value of break pointer.
  - sbrk -> increases the value of break by a given number of bytes.
- We could use those system calls to implement malloc and free.

Heap region

- A simple implementation of malloc

```
int *ptr = (int *) malloc(10 * sizeof (int));
if (ptr == NULL) {
} else {
    /* Allocation succeeded.  Do something.  */
    free(ptr);
    ptr = NULL;
}
```

Dynamic allocation

- Actually, malloc does not allocate a new memory region whose size exactly equals to the size given by user. It allocates a few extra bytes to hold needed information (including the size of allocated region) so that free function could easily clean this region.

Dynamic allocation

- How to allocate and clean memory region on heap?

```
void *p;
p = malloc(100);

// do something



free(p);
```

Dynamic allocation

- How to allocate and clean memory region on heap?

```
void *p;
p = malloc(100);

// do something



free(p);
```



Dynamic allocation

- How to allocate and clean memory region on heap?

```
void *p;
p = malloc(100);

// do something



free(p);
```

Dynamic allocation

- Exercise: Implement your version of malloc and free using the technique described above.

End

Thanks!