LiveRecall Technical Report

Members: David Goh, Ng Kheng Yang, Wang Yanxiang, Qin Haichen

1. Architecture and protocol

LiveRecall distributes a changing caption stream from one source to many browsers over WebSockets. The server validates revisions and manages each receiver's delivery independently.



Figure 1. Source ingestion, shared caption state and independent per-receiver delivery inside one asyncio server.

`CaptionStore` is the shared authority for revision acceptance and recent finals. Each `Client` owns an `OutboundBuffer`, one sender, a final-log cursor, and a probe task. Accepting and enqueueing an update never waits for a receiver's socket, so a blocked sender does not directly block delivery to other clients. Broadcast still requires work proportional to the number of clients.

`SOURCE_HELLO` and `CLIENT_HELLO` establish the connection role. Sources send `CAPTION_UPDATE` messages; receivers get `HISTORY` on initial connection or reconnect, followed by live `CAPTION_UPDATE` messages. Malformed source updates are ignored before state changes or broadcast, and `SOURCE_DONE` is not forwarded. Only one source is active at a time. The implementation assumes the supplied source's increasing segment and finalization order. State survives source disconnection in one shared namespace; starting a new lecture requires a server restart and browser reload.

2. Revision and recovery semantics

Revision replacement. A segment is one caption whose text may change through several provisional revisions. While unfinished, it accepts only a higher revision; equal or lower revisions are duplicates or stale state. Once final, it rejects every further update, including higher revisions.

Revision numbers may skip values. The browser applies this same gate to live and recovered captions, rewriting one row per segment and distinguishing drafts from finals visually. Repeated messages therefore cannot overwrite newer held state or append duplicate final rows.

Incremental recovery. `CLIENT_HELLO` reports the latest finalized `(last_segment, last_revision)` already held by the browser. A provisional revision does not advance this marker: its final may still be missing. The server returns only finals beyond the marker and within the requested recent window, capped at 60 seconds. A late join uses `(0, 0)`. Ordering these finals by acceptance gives oldest-first recovery under the sequential source. This marker assumes ordered completion; it cannot represent holes below a later final.

Registration and snapshot capture happen without yielding, recording both the requested history and the current end of the final log. `HISTORY` message is broken down into batches to avoid exceeding the websocket message size limit, all `HISTORY` batches are sent before live delivery starts at that boundary. Finals accepted during history transmission lie after the boundary and remain owed. Batches target 64 captions and 256 KiB; an oversized caption travels alone and must fit the peer's message limit. Existing unfinished captions are absent from the snapshot and appear only on their next update.

Appendix A shows history before live delivery and the reconnect sequence.

Recovery limits and local recall. Finals enter a shared log once, with internal sequence numbers marking

delivery progress for each client using an internal cursor recording the last delivered final message. They are retained for 90 seconds after server acceptance and pruned during store operations. Connected clients under replay mode can use that full window for consuming final messages in the shared log based on their cursor position, whereas reconnect creates a fresh cursor after its requested context: older excluded finals are not replayed later. Retired segment IDs are rejected to prevent stale state returning after pruning. Server unfinished state is capped at 4,000 segments by retiring the lowest IDs.

During an automatic reconnect, the browser keeps its in-memory caption state and sends its latest finalized position with a request for up to 60 seconds of recent history. The server returns finalized captions in that window that are newer than the position; reloading instead becomes a late join. Its local 15/30/60-second recall, defaulting to 30, filters already-held finals without a server request. On accepted updates it prunes finals older than 150 seconds and caps unfinished state at 400 segments. The 80-row live display limit does not limit recall storage.

3. Backpressure and overload policy

Normal delivery preserves every accepted revision. Each receiver has a FIFO, so a healthy browser sees drafts develop into their final text. Keeping every revision indefinitely when a receiver falls behind would instead accumulate obsolete text, memory use, and delivery delay. That slow receiver switches to replay mode on the same connection, while healthy receivers keep their own delivery policy.

```
NORMAL -- queue pressure / late probe --> REPLAY
   ^                                        |
   +--------- caught up; lease expired -----+
capacity / retention / stall failure --> close affected receiver (1013)
```

Replay preserves useful state. Reaching 256 pending updates or exceeding 4 MiB triggers compaction and replay. Queued finals leave the local buffer and are read in order from the shared log after the receiver's cursor. Each unfinished segment keeps only its newest queued revision, preserving its original queue age; a final removes its queued draft. Thus pending drafts r1, r2, and r3 for one segment collapse to r3, and none remains queued once the final arrives. Intermediate drafts are sacrificed, while outstanding finals remain available within retention. Replay sends individual `CAPTION_UPDATE` messages; `HISTORY` is reserved for hello recovery.

Finals normally take priority. After at least four consecutive finals, a draft queued for one second gets a turn; eligible drafts can also be sent when no final remains. This grace period allows rapidly superseded drafts to disappear while giving longer-lived unfinished captions an opportunity to progress. The final cursor advances only after a successful send.

Lag controls pacing and return to normal. Each client has one ping probe. Its measured time runs from ping initiation to pong receipt, so a blocked write can make the probe late. If the delay exceeds max(0.5 s, 6 × smoothed round-trip time), the client enters replay mode and starts a three-second catch-up lease. While the pong is overdue, the lease is repeatedly extended. This keeps the client in replay even if its backlog briefly drains.

During lag-driven replay, the sender sends bursts of up to 64 updates or 256 KiB, then waits for a probe completed after that burst before sending another. A single caption may take a burst past the byte target. Queue pressure can also trigger replay, but pressure alone does not enable probe pacing. A pong or successful socket write shows transport progress; it does not show that the browser accepted or rendered the caption.

After the pong arrives, replay continues until the lease has expired and no replay final or eligible provisional update remains. The client then stops coalescing and resumes FIFO delivery, including any queued drafts that were not yet eligible during replay. If lag returns before the normal-mode probation period ends, the next lease doubles, up to 30 seconds. If the client remains in normal mode through probation, the next lease resets to three seconds.

Finite capacity has an explicit failure policy. Normal admission failure first attempts replay. Remaining unfinished work must fit within 4,000 entries and 4 MiB of pending JSON. Exceeding that capacity, losing an

outstanding final to 90-second retention (`ReplayExpired`), or stalling an individual send or complete probe for 75 seconds initiates a 1013 close for that receiver. Closing gets two seconds before transport abort. Queue bounds exclude in-flight work, recovery snapshots, and transport buffers; shared-log memory depends on caption rate and size within retention. Sustained overload can therefore prevent final completeness, and reconnect restores only the requested recent context.

4. Public experiments and results

4.1 Reproducible setup

T1-T5 use the complete Ubuntu run added in commit `e0f7fd9`, archived in `results/prob_ab_david/probe_ab/`. The recorded environment on 4 November 2026 was Ubuntu 26.04.1 LTS, Linux 7.0.0-42-generic x86_64, one vCPU, approximately 3.32 GiB RAM, Python 3.14.4 and websockets 16.1.1. All recorded source hashes match the current application, public harness and experiment scripts. This replaces the earlier ARM64 VM evidence; differences between the evidence sets do not measure an implementation change.

The source uses nominal 200-ms revision delays and 350-ms segment gaps; other settings are seed 3103, a one-second source start delay, 30-second history, 500-ms freshness threshold and port 8811. No extra drain interval was added. The supplied measurement logic was unchanged. Each test used three independent runs per configuration, restarting the server each time and reporting the median of per-run metrics. **Section 4 uses with-probe results only; Section 5 compares with and without probes.** Server, source and simulated clients ran in the same Ubuntu VM. Loopback was initially `noqueue`; T5 applied 120 ms delay, 30 ms normal-distribution jitter and 3% loss, with a verified reset afterwards.

Test	Required scenario	Configuration / evidence path
T1	20 clients, 20 s; 22 expected segments	`results/prob_ab_david/probe_ab/`
T2	100 clients, 40 s; 49 expected segments	Same directory
T3	100 clients, 60 s, 10% slow; 500 ms sleep/message; 76 expected segments	Same directory
T4	100 clients, 60 s, 20% disconnect at 15 s for 5 s; 76 expected segments	Same directory
T5	100 clients, 40 s; 49 expected segments; loopback netem	Same directory

4.2 Measured results

Caption Age is client receive time minus `source_ts`, excluding browser rendering; the public analyser computes its percentiles over accepted live updates. Final completeness counts correctly received unique finals, including recovered history, against expected finals across clients. The following table gives **with-probe three-run medians**. T3 group metrics are derived from the CSV role flags; all 30 raw CSV files reproduce their saved JSON summaries exactly.

Test / client group	P50 age (ms)	P95 age (ms)	P99 age (ms)	Final completeness (%)
T1	3.28	6.67	8.11	100.00
T2	15.82	27.85	36.93	100.00
T3 overall	11.99	2,248.88	7,786.01	99.38
T3 normal readers	11.45	23.88	30.44	100.00
T3 slow readers	6,250.78	8,490.87	8,811.84	93.82
T4	5.29	8.80	12.55	100.00
T5	258.43	660.66	801.68	100.00

Fresh Caption Ratio is the fraction of accepted live updates within threshold T (public default: 500 ms). Fresh Final Caption Ratio counts unique finals received within T against expected finals, including finals recovered through history. The analyser's Normal Update Coverage includes all client roles; the table labels this live revision coverage and separately shows the T3 reader groups.

Test / client group	Fresh Caption Ratio (%)	Fresh Final Caption Ratio (%)	Live revision coverage (%)
T1	100.00	100.00	100.00
T2	100.00	100.00	100.00
T3 overall	94.65	90.00	95.18
T3 normal readers	100.00	100.00	100.00
T3 slow readers	1.69	0.00	51.75
T4	100.00	98.42	98.33
T5	91.28	87.39	98.86

All 15 with-probe runs recorded zero duplicate/stale captions, invalid non-final HISTORY items and connection errors. T4's 20 forced-disconnect clients reconnected and received HISTORY in every run. Median HISTORY-response P95 was 3.31 ms; this is not a separate measurement of complete-state recovery time. No RSS/CPU or queue-high-water trace was collected.

4.3 Interpretation

Deadline and source timing. Clients stop at a fixed deadline, and absent deliveries do not enter live-age percentiles. Unlike the earlier ARM64 runs, all T3 normal readers received every expected final in both configurations. The CSV `source_ts` for final segment 76 was 57.84-58.12 s after the first recorded connection across the six T3 runs, within the 60-s window. The remaining T3 completeness deficit is confined to slow readers; source generation beyond the deadline does not explain it in this evidence set.

T1-T2: normal delivery and scale. Every expected final and revision arrived in all runs. T1 P99 age was 8.11 ms; at 100 clients, T2 P95/P99 was 27.85/36.93 ms. Both tests had 100% fresh captions and fresh finals at 500 ms.

T3: normal readers stay responsive, but slow readers lag. Normal-reader P95/P99 was 23.88/30.44 ms, compared with T2's 27.85/36.93 ms, and final completeness was 100%. Slow readers received 720, 710 and 713 of 760 expected final/client pairs, giving 93.82% median completeness and P95 age 8.49 s. Overall completeness was 99.38%. Normal readers retained every revision while slow-reader live revision coverage was 51.75%, consistent with coalescing and backlog under the imposed 500-ms processing delay.

T4: reconnect restores all expected finals by the deadline. Every forced-disconnect client reconnected and received HISTORY in each run; all 7,600 expected final/client pairs arrived. Median HISTORY-response P95 was 3.31 ms and live-update P99 was 12.55 ms. Live revision coverage was 98.33% because recovery supplies finals rather than every missed draft. Fresh-final ratio was 98.42%; HISTORY-response timing does not measure complete recovery time.

T5: impairment increases age while all expected finals arrive. Each run received 4,900/4,900 final/client pairs. P50 was 258.43 ms and P95/P99 660.66/801.68 ms; fresh-final ratio was 87.39% at 500 ms. This is consistent with delay/jitter and TCP retransmission/ordered-delivery effects, without isolating their contributions. Loopback netem affects both source and receiver traffic. Live revision coverage was 98.86%.

5. Before/after optimization comparison

The final with-probe design is compared with a copied client whose probe task is not started. Queue-pressure coalescing and the send timeout remain. Disabling the probe removes lag detection, probe-driven wakeups/

pacing and probe stall detection together. Both configurations use the same public parameters and three independent runs from the same evidence set; changes below are with-probe minus no-probe, using unrounded medians.

Metric (include unit)	Baseline / probe disabled	Final / probe enabled	Change
T3 final completeness (%)	95.13	99.38	+4.25 pp
T3 P99 age (ms)	24,035.07	7,786.01	-16,249.06
T3 slow-reader P95 age (ms)	28,093.65	8,490.87	-19,602.78
T3 normal-reader P95 age (ms)	17.26	23.88	+6.62
T3 live revision coverage (%)	95.18	95.18	+0.00 pp
T5 final completeness (%)	99.98	100.00	+0.02 pp
T5 live revision coverage (%)	99.97	98.86	-1.12 pp
T5 P95 age (ms)	905.82	660.66	-245.16
T5 P99 age (ms)	1,270.90	801.68	-469.22

With probes, T3 median slow-reader P95 was 69.8% lower and overall P99 67.6% lower, while normal-reader P95 was 6.62 ms higher. Normal readers received every final in both configurations; median slow-reader completeness increased from 51.32% to 93.82%. Earlier lag detection and coalescing are consistent with reduced backlog. Both configurations had identical 95.18% overall live revision coverage, so coverage alone does not capture the improvement in final delivery. All with-probe runs preceded no-probe runs; these three-run differences remain descriptive rather than an isolated causal estimate.

T5 received 4,900 finals per with-probe run versus 4,899, 4,899 and 4,900 without probes. The trade-off was 1.12 pp lower live revision coverage. Median P95/P99 was lower by 245.16/469.22 ms, but network loss sequences differed and fixed arm order limits attribution to probing. Eventual delivery beyond the observation deadline was not measured.

6. Discussion, limitations and future work

Failures and trade-offs. T3 normal-reader P95 was 23.88 ms with 100% final completeness, while slow readers had 93.82% median completeness and 8.49-s P95 age. Normal readers stayed responsive, but slow readers still missed finals generated within the measurement window. T5 received all expected finals but exceeded the 500-ms freshness threshold at P95. Coalescing reduces obsolete draft traffic at the cost of intermediate revision coverage. Longer catch-up leases discourage repeated overload but can postpone the return to full revisions after a receiver improves. Delivery traces are needed to locate where slow-reader finals remain pending at the measurement deadline.

Limitations. Lag detection measures transport responsiveness without measuring the receiver's caption-processing rate. Healthy pongs can therefore coexist with an application backlog, and fixed bursts may supply updates faster than the receiver consumes them. Coalescing affects only the server's pending buffer: obsolete drafts already handed to socket or receiver buffers cannot be withdrawn and can delay newer finals. Recovery after a bottleneck consequently depends on how much data was sent before replay began. Memory use also remains workload-dependent: the shared final log has an age limit but no byte cap, so caption bursts or large texts can increase memory consumption despite the per-client queue limits.

Future work. Our objective is 100% final completeness in T3 and a faster return to full revision delivery after a temporary slowdown, within the existing queue bounds. We will first trace unreceived finals, then compare burst limits and catch-up lease policies in repeated, matched T3 and slowdown/recovery tests. Completeness and caption age will be compared at the same observation deadline. After restoring normal reading speed, we will measure the time until all newly generated revisions are received consistently. Normal-client latency, peak queue usage, and process memory will be monitored to check that improved slow-client delivery preserves isolation and bounded resource use.

References

- CS3103 Assignment 4 specification, Sections 8-12 (experiments, metrics, environment, report requirements).
- Latest Ubuntu T1-T5 comparison and recorded configuration, including source hashes, environment and both arms' CSV/JSON files.
- TODO: Cite external technical sources actually used.

Appendices

Appendix A. Communication sequence



Figure A1. Connection setup, live revisions, local recall and reconnect recovery. Shared state access is grouped under Server; the [detailed component sequence] expands sender, buffer and probe interactions.

Appendix B. Experiment evidence and reproduction

Per-run CSV/JSON files and logs are stored alongside the latest full comparison, under `with_probe/output/` and `no_probe/output/`. The configuration records the environment, source hashes, test arguments and successful runner exits for all ten test/configuration combinations. T5's `qdisc_*.json` files and `t5_network_status.json` record impairment application, traffic counters and reset. All 30 summaries were recomputed from their CSVs with the public analyser; T3 reader-group metrics use the same definitions restricted by the CSV `slow` flag.

To reproduce from the repository root inside Ubuntu with the recorded dependencies and sudo/netem available, use a fresh output directory:

```
venv/bin/python -u experiments/probe_ab.py --tests t1,t2,t3,t4,t5 --runs 3 \
  --port 8811 --venv "$PWD/venv" --require-t5 --out output/probe_ab_fresh
```

Earlier ARM64 results and run caveats remain available for comparison; their values are not used in Sections 4-5.

Draft completion checklist (remove before export)

The assignment specifies **4-5 main pages, excluding references/appendices**; it does not prescribe font size or margins. Use a readable export (for example, A4, 11 pt text, 20 mm margins) and verify the rendered PDF after completing all TODOs. Do not add a separate cover page. The following budgets are drafting targets, not assignment rules; they include space for headings and tables.

Main section	Page allowance	Prose target
1. Architecture and protocol	0.90	350 words
2. Revision and recovery	0.65	300 words
3. Backpressure and overload	0.65	300 words
4. Experiments and results	1.50	550 words plus the compact results tables
5. Optimization comparison	0.55	225 words plus one comparison table
6. Discussion and future work	0.50	175 words
Total	4.75	About 1,900 words plus tables

Replace TODO instructions with final prose and measurements within these budgets. Keep architecture concise; a method-by-method walkthrough belongs in an appendix. Leave the remaining 0.25 page for the title, team line, and layout variation. An A4/11 pt/20 mm-margin layout projection expanded to these prose targets, with the existing tables, rendered to five main pages. This is a planning check; verify again after replacing placeholders and adding any figures. Replace a table with a figure where useful instead of continually adding material.

- [ ] All required sections are supported by the submitted implementation and evidence; no TODOs remain.
- [ ] Sections 2-3 explain actual rules, numeric bounds, and failure/recovery limits.
- [ ] Results cover all required metrics, recovery time, isolation, and bounded resource usage.
- [ ] The separate deterministic browser demo covers revision replacement, local recall, reconnect, and late join.
- [ ] T1–T5 each have at least three independent runs; medians and units are clear.
- [ ] At least one stress-test before/after comparison is quantified and reproducible.
- [ ] The main report is 4–5 pages after PDF export, excluding references/appendices.
- [ ] The reviewed PDF is saved as `submission_root/report.pdf`.
- [ ] README, AI usage, contributions and the separate 5–7-minute demo video are completed.