

# PyCVI: A Python package for internal Cluster Validity Indices, compatible with time-series data

Natacha Galmiche <sup>1</sup>

<sup>1</sup> University of Bergen, Norway

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright  
and release the work under a  
Creative Commons Attribution 4.0  
International License ([CC BY 4.0](#)).

## Summary

PyCVI is a Python package specialized in internal Clustering Validity Indices (CVIs) compatible with both time-series and non time-series data.

Clustering is a task that aims at finding groups within a given dataset. CVIs are used to select the best clustering among a pre-computed set of clusterings. In other words, CVIs select the division of the dataset into groups that best ensures that similar datapoints belong to the same group and non-related datapoints are in different groups.

PyCVI implements 12 state-of-the-art *internal* CVIs to improve clustering pipelines as well as the Variation of Information ([Meilă, 2003](#)), a measure between clusterings that can be used as an *external* CVI. The *internal* qualifier here refers to the general case in practice where no *external* information is available about the dataset such as the true association of the datapoints with groups, as opposed to *classification* tasks.

## Statement of need

There exist many mature libraries in python for machine learning and in particular clustering [scikit-learn](#) ([Pedregosa et al., 2011](#)), [TensorFlow](#) ([Abadi et al., 2015](#)), [PyTorch](#) ([Paszke et al., 2019](#)), [scikit-learn-extra](#) ([Scikit-learn Extra, n.d.](#)), and even several specifically for time series data: [aeon](#) ([Aeon, n.d.](#)), [sktime](#) ([Löning et al., 2019](#)), [tslearn](#) ([Tavenard et al., 2020](#)).

However, although being fundamental to clustering tasks and being an active research topic, very few internal CVIs are implemented in standard python libraries (only 3 in [scikit-learn](#), more were available in R but few were maintained and kept in CRAN ([Charrad et al., 2014](#))). This is despite the well-known limitations of all existing CVIs ([Arbelaitz et al., 2013](#)), ([Gagolewski et al., 2021](#)), ([Gurrutxaga et al., 2011](#)), ([Theodoridis & Koutroumbas, 2009](#)) and the need to use the right one(s) according to the specific dataset at hand, similarly to matching the right clustering method with the given problem. A crucial step towards developing better CVIs would be an easy access to an implementation of existing CVIs in order to facilitate larger comparative studies.

In addition, all CVIs rely on the definition of a distance between datapoints and most of them on the notion of cluster center.

For non-time-series data, the distance between datapoints is usually the euclidean distance and the cluster center is defined as the usual average. Libraries such as [scipy](#), [numpy](#), [scikit-learn](#), etc. offer a large selection of distance measures that are compatible with their main functions.

For time-series data however, the common distance used is Dynamic Time Warping (DTW) ([Berndt & Clifford, 1994](#)) and the barycenter of a group of time series is then not defined as the usual mean, but as the DTW Barycentric Average (DBA) ([Petitjean et al., 2011](#)). Unfortunately, DTW and DBA are not compatible with the libraries mentioned above.

PyCVI then tries to fill that gap by implementing 12 state-of-the-art internal CVIs: Hartigan (Strauss & Hartigan, 1975), Calinski-Harabasz (Calinski & Harabasz, 1974), GapStatistic (Tibshirani et al., 2001), Silhouette (Rousseeuw, 1987), ScoreFunction (Saitta et al., 2007), Maulik-Bandyopadhyay (Maulik & Bandyopadhyay, 2002), SD (Halkidi et al., 2000), SDbw (Halkidi & Vazirgiannis, 2001), Dunn (Dunn, 1974), Xie-Beni (Xie & Beni, 1991), XB\* (Kim & Ramakrishna, 2005) and Davies-Bouldin (Davies & Bouldin, 1979). Then, in PyCVI their definition is extended in order to make them compatible with DTW and DBA in addition to non time-series data. PyCVI is entirely compatible with `scikit-learn`, `scikit-learn-extra`, `aeon` and `sktime`, in order to be easily integrated into any clustering pipeline in python. To ensure a fast a reliable computation of DTW and DBA, PyCVI relies on the `aeon` library.

## Example




Figure 1: KMeans clustering on non time-series data, all implemented CVIs.







Figure 2: KMeans clustering on non time-series data, selected number of clusters according to all implemented CVIs.



**Figure 3:** Agglomerative clustering on non time-series data, all implemented CVIs.




**Figure 4:** Agglomerative clustering on non time-series data, selected number of clusters according to all implemented CVIs.




**Figure 5:** KMeans clustering on time-series data, with DTW, all implemented CVIs.

Number of CVIs that selected a given number of clusters




**Figure 6:** KMeans clustering on time-series data, with DTW, selected number of clusters according to all implemented CVIs.



**Figure 7:** KMedoids clustering on time-series data, without DTW, all implemented CVIs.

Number of CVIs that selected a given number of clusters



**Figure 8:** KMedoids clustering on time-series data, with DTW, selected number of clusters according to all implemented CVIs.

51 We experimented on 3 different cases: non time-series data (Barton, 2015), time-series data  
 52 (Dau et al., 2018) with euclidean distance and time-series data with DTW and DBA as distance  
 53 measure and center of clusters.

For each case, we used a different clustering method from a different library: KMeans (Lloyd, 1982) and AgglomerativeClustering (Ward, 1963) from [scikit-learn](#), TimeSeriesKMeans from [aeon](#) and KMedoids ("Partitioning Around Medoids (Program PAM)," 1990) from [scikit-learn-extra](#) in order to give examples of integration with other clustering libraries. Then, for each case, we ran all the CVIs implemented in PyCVI, selected the best clustering according to each CVI and plotted the selected clustering.

Finally, we computed the variation of information (VI) between each selected clustering and the true clustering (second plot of all figures). A large variation of information there indicates a poor clustering quality due to the clustering method. In [Figure 1](#) and [Figure 3](#), we can see the difference of quality when assuming the correct number of clusters between the AgglomerativeClustering and the KMeans clustering method on the non time-series data. Therefore, when the quality of the clustering selected by the CVI is poor it can then either be due to the clustering method or the CVI, hence the necessity of robust evaluation pipeline for both clustering methods and CVIs.

The code of this example is available on the [GitHub repository](#) of the package, as well as on its [documentation](#).

## Acknowledgements

We thank the climate and energy transition strategy of the University of Bergen in Norway (UiB) for funding this work.

## References

- Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., ... Zheng, X. (2015). *TensorFlow: Large-scale machine learning on heterogeneous systems*. <https://www.tensorflow.org/>
- Aeon. (n.d.). "<https://github.com/aeon-toolkit/aeon>"; Github.
- Arbelaitz, O., Gurrutxaga, I., Muguerza, J., Pérez, J. M., & Perona, I. (2013). An extensive comparative study of cluster validity indices. *Pattern Recognition*, 46(1), 243–256. <https://doi.org/10.1016/j.patcog.2012.07.021>
- Barton, T. (2015). *Clustering benchmarks*. "<https://github.com/deric/clusteringbenchmark>"; Github.
- Berndt, D. J., & Clifford, J. (1994). Using dynamic time warping to find patterns in time series. *Proceedings of the 3rd International Conference on Knowledge Discovery and Data Mining*, 359–370.
- Calinski, T., & Harabasz, J. (1974). A dendrite method for cluster analysis. *Communications in Statistics - Theory and Methods*, 3(1), 1–27. <https://doi.org/10.1080/03610927408827101>
- Charrad, M., Ghazzali, N., Boiteau, V., & Niknafs, A. (2014). NbClust: An r package for determining the relevant number of clusters in a data set. *Journal of Statistical Software*, 61(6). <https://doi.org/10.18637/jss.v061.i06>
- Dau, H. A., Keogh, E., Kamgar, K., Yeh, C.-C. M., Zhu, Y., Gharghabi, S., Ratanamahatana, C. A., Yanping, Hu, B., Begum, N., Bagnall, A., Mueen, A., Batista, Gustavo, & Hexagon-ML. (2018). *The UCR time series classification archive*.
- Davies, D. L., & Bouldin, D. W. (1979). A cluster separation measure. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-1(2), 224–227. <https://doi.org/10.1109/tpami.1979.4766909>

- 98 Dunn, J. C. (1974). Well-separated clusters and optimal fuzzy partitions. *Journal of Cybernetics*,  
99 4(1), 95–104. <https://doi.org/10.1080/01969727408546059>
- 100 Gagolewski, M., Bartoszek, M., & Cena, A. (2021). Are cluster validity measures (in) valid?  
101 *Information Sciences*, 581, 620–636. <https://doi.org/10.1016/j.ins.2021.10.004>
- 102 Gurrutxaga, I., Muguerza, J., Arbelaiz, O., Pérez, J. M., & Martín, J. I. (2011). Towards  
103 a standard methodology to evaluate internal cluster validity indices. *Pattern Recognition*  
104 *Letters*, 32(3), 505–515. <https://doi.org/10.1016/j.patrec.2010.11.006>
- 105 Halkidi, M., & Vazirgiannis, M. (2001). Clustering validity assessment: Finding the optimal  
106 partitioning of a data set. *Proceedings 2001 IEEE International Conference on Data Mining*,  
107 187–194. <https://doi.org/10.1109/icdm.2001.989517>
- 108 Halkidi, M., Vazirgiannis, M., & Batistakis, Y. (2000). Quality scheme assessment in the  
109 clustering process. In *Principles of data mining and knowledge discovery* (pp. 265–276).  
110 Springer Berlin Heidelberg. [https://doi.org/10.1007/3-540-45372-5\\_26](https://doi.org/10.1007/3-540-45372-5_26)
- 111 Kim, M., & Ramakrishna, R. S. (2005). New indices for cluster validity assessment. *Pattern*  
112 *Recognition Letters*, 26(15), 2353–2363. <https://doi.org/10.1016/j.patrec.2005.04.007>
- 113 Lloyd, S. (1982). Least squares quantization in PCM. *IEEE Transactions on Information*  
114 *Theory*, 28(2), 129–137.
- 115 Löning, M., Bagnall, A., Ganesh, S., Kazakov, V., Lines, J., & Király, F. J. (2019). *Sktime: A*  
116 *unified interface for machine learning with time series*. arXiv. [https://doi.org/10.48550/](https://doi.org/10.48550/ARXIV.1909.07872)  
117 [ARXIV.1909.07872](https://doi.org/10.48550/ARXIV.1909.07872)
- 118 Maulik, U., & Bandyopadhyay, S. (2002). Performance evaluation of some clustering algorithms  
119 and validity indices. *IEEE Transactions on Pattern Analysis and Machine Intelligence*,  
120 24(12), 1650–1654. <https://doi.org/10.1109/tpami.2002.1114856>
- 121 Meilă, M. (2003). Comparing clusterings by the variation of information. In *Lecture notes in*  
122 *computer science* (pp. 173–187). Springer Berlin Heidelberg. [https://doi.org/10.1007/](https://doi.org/10.1007/978-3-540-45167-9_14)  
123 [978-3-540-45167-9\\_14](https://doi.org/10.1007/978-3-540-45167-9_14)
- 124 Partitioning around medoids (program PAM). (1990). In *Finding groups in data* (pp. 68–125).  
125 John Wiley & Sons, Ltd. <https://doi.org/10.1002/9780470316801.ch2>
- 126 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,  
127 Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M.,  
128 Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An  
129 imperative style, high-performance deep learning library. In *Advances in neural information*  
130 *processing systems* 32 (pp. 8024–8035). Curran Associates, Inc. [https://doi.org/10.](https://doi.org/10.48550/ARXIV.1912.01703)  
131 [48550/ARXIV.1912.01703](https://doi.org/10.48550/ARXIV.1912.01703)
- 132 Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,  
133 Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D.,  
134 Brucher, M., Perrot, M., & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python.  
135 *Journal of Machine Learning Research*, 12, 2825–2830.
- 136 Petitjean, F., Ketterlin, A., & Gançarski, P. (2011). A global averaging method for dynamic  
137 time warping, with applications to clustering. *Pattern Recognition*, 44(3), 678–693.  
138 <https://doi.org/10.1016/j.patcog.2010.09.013>
- 139 Rousseeuw, P. J. (1987). Silhouettes: A graphical aid to the interpretation and validation  
140 of cluster analysis. *Journal of Computational and Applied Mathematics*, 20, 53–65.  
141 [https://doi.org/10.1016/0377-0427\(87\)90125-7](https://doi.org/10.1016/0377-0427(87)90125-7)
- 142 Saitta, S., Raphael, B., & Smith, I. F. C. (2007). A bounded index for cluster validity. In  
143 *Machine learning and data mining in pattern recognition* (pp. 174–187). Springer Berlin  
144 Heidelberg. [https://doi.org/10.1007/978-3-540-73499-4\\_14](https://doi.org/10.1007/978-3-540-73499-4_14)

- 145 *Scikit-learn Extra*. (n.d.). <https://scikit-learn-extra.readthedocs.io/en/stable/>.
- 146 Strauss, D. J., & Hartigan, J. A. (1975). Clustering algorithms. *Biometrics*, 31(3), 793.  
147 <https://doi.org/10.2307/2529577>
- 148 Tavenard, R., Faouzi, J., Vandewiele, G., Divo, F., Androz, G., Holtz, C., Payne, M., Yurchak,  
149 R., Rußwurm, M., Kolar, K., & Woods, E. (2020). Tslern, a machine learning toolkit for  
150 time series data. *Journal of Machine Learning Research*, 21(118), 1–6. [http://jmlr.org/](http://jmlr.org/papers/v21/20-091.html)  
151 [papers/v21/20-091.html](http://jmlr.org/papers/v21/20-091.html)
- 152 Theodoridis, S., & Koutroumbas, K. (2009). Chapter 16 - cluster validity. In S. Theodoridis &  
153 K. Koutroumbas (Eds.), *Pattern recognition (fourth edition)* (Fourth Edition, pp. 863–913).  
154 Academic Press. <https://doi.org/https://doi.org/10.1016/B978-1-59749-272-0.50018-9>
- 155 Tibshirani, R., Walther, G., & Hastie, T. (2001). Estimating the number of clusters in a  
156 data set via the gap statistic. *Journal of the Royal Statistical Society Series B: Statistical*  
157 *Methodology*, 63(2), 411–423. <https://doi.org/10.1111/1467-9868.00293>
- 158 Ward, J. H. (1963). Hierarchical grouping to optimize an objective function. *Journal of the*  
159 *American Statistical Association*, 58(301), 236–244. [https://doi.org/10.1080/01621459.](https://doi.org/10.1080/01621459.1963.10500845)  
160 [1963.10500845](https://doi.org/10.1080/01621459.1963.10500845)
- 161 Xie, X. L., & Beni, G. (1991). A validity measure for fuzzy clustering. *IEEE Transactions on*  
162 *Pattern Analysis and Machine Intelligence*, 13(8), 841–847. [https://doi.org/10.1109/34.](https://doi.org/10.1109/34.85677)  
163 [85677](https://doi.org/10.1109/34.85677)