

Competitive Programming Reference

ngmh

Last Updated: 07/01/2026

Contents

1	Data Structures	3
1.1	Prefix Sums	3
1.1.1	1D	3
1.1.2	2D	3
1.2	Fenwick Trees	3
1.2.1	Point Update Range Query	3
1.2.2	Range Update Point Query	4
1.2.3	Range Update Range Query	4
1.2.4	2D PURQ / RUPQ	4
1.2.5	2D RURQ	5
1.3	Segment Trees	6
1.3.1	Standard	6
1.3.2	Lazy Propagation	6
1.3.3	Maxsum	7
1.3.4	Merge Sort Tree / Order Statistics	7
1.3.5	2D	8
2	Graph Theory	9
2.1	Depth First Search	9
2.2	Breadth First Search	9
2.3	0-1 BFS	10
2.4	Floyd-Warshall	10
2.5	Bellman-Ford	10
2.6	Dijkstra's Algorithm	11
2.7	Shortest Path Faster Algorithm	11
2.8	Prim's Algorithm	11
2.9	Union Find Disjoint Subset	12
2.10	Kruskal's Algorithm	12
2.11	Topological Sort	12
2.12	Floyd's Cycle Finding Algorithm	13
2.13	Maximum Cardinality Bipartite Matching	13
2.13.1	Kun's Algorithm	13
2.13.2	Hopcroft-Karp	14
2.14	Articulation Points and Bridges	15
2.15	Strongly Connected Components	16
2.16	Trees	16
2.16.1	Pre/Postorder Traversal	16
2.16.2	Subtree to Range	17
2.16.3	Weighted Maximum Independent Set	17
2.16.4	Diameter	18
2.16.5	2^K Decomposition	18
2.16.6	Lowest Common Ancestor	18
2.16.7	Shortest Path	19

3	Dynamic Programming	19
3.1	Maxsum	19
3.1.1	1D	19
3.2	Longest Increasing Subsequence	19
3.2.1	N^2 DP	19
3.2.2	Data Structure Speedup	19
3.2.3	$N \log N$ DP	20
3.3	Coin Combinations	20
3.4	Coin Change	20
3.5	Knapsack	20
3.5.1	0-1	20
3.6	Digit DP	21
3.7	Convex Hull Trick	22
3.8	Li Chao Tree	23
3.9	Divide and Conquer	24
4	Math	24
4.1	Fast Exponentiation	24
4.2	Prime Factorisation	25
4.3	Sieve of Eratosthenes	25
4.4	Greatest Common Divisor	25
4.5	Lowest Common Multiple	26
4.6	Modular Inverse	26
4.7	$\binom{n}{k}$	26
4.8	Fibonacci	26
5	Algorithms	27
5.1	Binary Search	27
5.2	Binary Search using Lifting	27
5.3	Sliding Set	27
5.4	Set Merging	28
5.5	Discretisation	28
6	Miscellaneous	28
6.1	Fast I/O	28
6.2	Superfast I/O	28

1 Data Structures

Data Structure	Precomputation / Update	Query	Memory	Notes
Prefix Sum	$O(N) / X$	$O(1)$	$O(N)$	Associative Functions (+, XOR)
Sparse Table	$O(N \log N) / X$	$O(1)$	$O(N \log N)$	Non-Associative Functions (max, gcd)
Fenwick Tree	$X / O(\log N)$	$O(\log N)$	$O(N)$	Prefix Sum with Updates
Segment Tree	$X / O(\log N)$	$O(\log N)$	$O(4N)$	Allows more Information

Table 1: Quick Summary of Data Structures

1.1 Prefix Sums

1.1.1 1D

$O(N)$ precomputation, $O(1)$ query.

```
//Query - 1-Indexed
int query(int s, int e){
    return ps[e]-ps[s-1];
}

//Precomputation
ps[0] = 0;
for(int i = 1; i <= n; i++) ps[i] = ps[i-1]+a[i];
```

1.1.2 2D

$O(R \cdot C)$ precomputation, $O(1)$ query.

```
//Query - 1-Indexed
int query(int x1, int y1, int x2, int y2){
    return ps[x2][y2]-ps[x1-1][y2]-ps[x2][y1-1]+ps[x1-1][y1-1];
}

//Precomputation
for (int i = 0; i <= r; i++) ps[i][0] = 0;
for (int j = 0; j <= c; j++) ps[0][j] = 0;
for (int i = 1; i <= r; i++) {
    for (int j = 1; j <= c; j++) {
        ps[i][j] = ps[i-1][j]+ps[i][j-1]-ps[i-1][j-1]+a[i][j];
    }
}
```

1.2 Fenwick Trees

1.2.1 Point Update Range Query

$O(\log N)$ update and query.

```
inline int ls(int x){ return (x)&(-x); }

int fw[MAXN]; // 1-Indexed

void pu(int i, int v) {
    for(; i <= n; i += ls(i)) fw[i] += v;
}

int pq(int i) {
    int t = 0;
```

```

        for(; i; i -= ls(i)) t += fw[i];
        return t;
    }

    int rq(int s, int e) {
        return pq(e) - pq(s - 1);
    }

```

1.2.2 Range Update Point Query

$O(\log N)$ update and query.

```
// Requires PURQ Code (PU, PQ)
```

```

void ru(int s, int e, int v) {
    pu(s, v);
    pu(e+1, -v);
}

```

1.2.3 Range Update Range Query

$O(\log N)$ update and query.

```
// Requires PURQ Code (PU, PQ)
// Functions need to be modified to take in array parameter
// e.g. int pu(*tree, int i, int v)
```

```

void ru(int s, int e, int v) {
    pu(fw1, s, v);
    pu(fw1, e+1, -v);
    pu(fw2, s, -v*(s-1));
    pu(fw2, e+1, v*e);
}

int ps(int i) {
    return pq(fw1, i)*i + pq(fw2, i);
}

int rq(int s, int e) {
    return ps(e) - ps(s - 1);
}

```

1.2.4 2D PURQ / RUPQ

$O(\log N \cdot \log M)$ update and query.

```

inline int ls(int x) { return x & -x; }

int fw[MAXN][MAXN]; // 1-indexed

void pu(int x, int y, int v) {
    for (int i = x; i < MAXN; i += ls(i)) {
        for (int j = y; j < MAXN; j += ls(j)) {
            fw[i][j] += v;
        }
    }
}

```

```

int pq(int x, int y) {
    int ans = 0;
    for (int i = x; i > 0; i -= ls(i)) {
        for (int j = y; j > 0; j -= ls(j)) {
            ans += fw[i][j];
        }
    }
    return ans;
}

// Range Query
int rq(int x1, int y1, int x2, int y2) {
    return pq(x2, y2) - pq(x1 - 1, y2) - pq(x2, y1 - 1) + pq(x1 - 1, y1 - 1);
}

// Range Update, Point Query
void ru(int x1, int y1, int x2, int y2, int v) {
    pu(x1, y1, v);
    pu(x1, y2 + 1, -v);
    pu(x2 + 1, y1, -v);
    pu(x2 + 1, y2 + 1, v);
}

```

1.2.5 2D RURQ

$O(\log N \cdot \log M)$ update and query.

// Requires 2D PURQ Code

```

void ru(int x1, int y1, int x2, int y2, long long v) {
    pu(fw1, x1, y1, v);
    pu(fw1, x1, y2+1, -v);
    pu(fw1, x2+1, y1, -v);
    pu(fw1, x2+1, y2+1, v);

    pu(fw2, x1, y1, v*(x1-1));
    pu(fw2, x1, y2+1, -v*(x1-1));
    pu(fw2, x2+1, y1, -v*x2);
    pu(fw2, x2+1, y2+1, v*x2);

    pu(fw3, x1, y1, v*(y1-1));
    pu(fw3, x1, y2+1, -v*y2);
    pu(fw3, x2+1, y1, -v*(y1-1));
    pu(fw3, x2+1, y2+1, v*y2);

    pu(fw4, x1, y1, v*(x1-1)*(y1-1));
    pu(fw4, x1, y2+1, -v*(x1-1)*y2);
    pu(fw4, x2+1, y1, -v*x2*(y1-1));
    pu(fw4, x2+1, y2+1, v*x2*y2);
}

long long ps(int x, int y) {
    return pq(fw1, x, y)*x*y - pq(fw2, x, y)*y - pq(fw3, x, y)*x + pq(fw4, x, y);
}

long long rq(int x1, int y1, int x2, int y2) {
    return ps(x2, y2) - ps(x1-1, y2) - ps(x2, y1-1) + ps(x1-1, y1-1);
}

```

1.3 Segment Trees

1.3.1 Standard

$O(\log N)$ point update and range query.

```
struct node {
    int s, e, m, v;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2; v = 0;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(int x, int y) {
        if (s == e) { v = y; return; }
        if (x <= m) l->pu(x, y);
        if (x > m) r->pu(x, y);
        v = min(l->v, r->v);
    }
    int rq(int x, int y) {
        if (s == x && e == y) return v;
        if (y <= m) return l->rq(x, y);
        if (x > m) return r->rq(x, y);
        return min(l->rq(x, m), r->rq(m+1, y));
    }
}
} *root;

root = new node(0, n-1);
```

1.3.2 Lazy Propagation

$O(\log N)$ range update and range query.

```
struct node {
    int s, e, m, v, lazy;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2; v = lazy = 0;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    int pu() {
        if (s == e) { v += lazy; lazy = 0; return v; }
        v += lazy;
        l->lazy += lazy; r->lazy += lazy;
        lazy = 0;
        return v;
    }
    void ru(int x, int y, int z) {
        if (s == x && e == y) { lazy += z; return; }
        if (y <= m) l->ru(x, y, z);
        else if (x > m) r->ru(x, y, z);
        else l->ru(x, m, z), r->ru(m+1, y, z);
    }
}
```

```

        v = max(l->pu(), r->pu());
    }

    int rq(int x, int y) {
        pu();
        if (s == x && e == y) return pu();
        if (y <= m) return l->rq(x, y);
        if (x > m) return r->rq(x, y);
        return max(l->rq(x, m), r->rq(m+1, y));
    }
} *root;

root = new node(0, n-1);

```

1.3.3 Maxsum

$O(\log N)$ point update and range query.

```

struct node {
    ll s, e, m, ps, ss, ms, ts;
    node *l, *r;
    node(ll _s, ll _e) {
        s = _s; e = _e; m = (s+e)/2; ps = ss = ms = ts = 0;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(ll x, ll y) {
        if (s == e) { ps = ss = ms = ts = y; return; }
        if (x <= m) l->pu(x, y);
        if (x > m) r->pu(x, y);
        //New Prefix Max -> Left Prefix, Left + Right Prefix
        ps = max(l->ps, l->ts+r->ps);
        //New Suffix Max -> Right Suffix, Left Suffix + Right
        ss = max(r->ss, r->ts+l->ss);
        //Total Sum -> Left + Right
        ts = l->ts+r->ts;
        //Maxsum - Left Suffix + Right Prefix, Left, Right,
        //          Total, Left Maxsum, Right Maxsum
        ms = max({l->ss+r->ps, ps, ss, ts, l->ms, r->ms});
    }
    ll ans() {
        return ms;
    }
} *root;

root = new node(0, n-1);

```

1.3.4 Merge Sort Tree / Order Statistics

Insertion: $O(\log N)$, Building: $O(N \log^2 N)$, Counting: $O(\log^2 N)$, Finding: $O(\log V \cdot \log^2 N)$, Range Max: $O(\log N)$.

```

struct node {
    int s, e, m;
    vector<int> v;
    node *l, *r;

```

```

node(int _s, int _e) {
    s = _s; e = _e; m = (s+e)/2;
    if (s != e) {
        l = new node(s, m);
        r = new node(m+1, e);
    }
}

void insert(int x, int y) {
    if (s == e) { v.push_back(y); return; }
    if (x > m) r->insert(x, y);
    if (x <= m) l->insert(x, y);
    v.push_back(y);
}

void build(){
    if (s == e) return;
    l->build();
    r->build();
    sort(v.begin(), v.end());
}

int countLessEqual(int x, int y, int k) {
    if (x > y) return 0;
    if (s == x && e == y) {
        return upper_bound(v.begin(), v.end(), k)-v.begin();
    }
    if (x > m) return r->countLessEqual(x, y, k);
    if (y <= m) return l->countLessEqual(x, y, k);
    return l->countLessEqual(x, m, k)+r->countLessEqual(m+1, y, k);
}

int kthSmallest(int x, int y, int k) {
    int mini = 0, maxi = (1 << 30);
    int ans = mini, gap = maxi;
    while (gap > 0) {
        while (ans + gap <= maxi && countLessEqual(x, y, ans + gap) < k) {
            ans += gap;
        }
        gap >>= 1;
    }
    return ans + 1;
}

int rangeMax(int x, int y) {
    if (x > y) return 0;
    if (s == x && e == y) return v.back();
    if (x > m) return r->rangeMax(x, y);
    if (y <= m) return l->rangeMax(x, y);
    return max(l->rangeMax(x, m), r->rangeMax(m+1, y));
}

} *root;

root = new node(0, n-1);

```

1.3.5 2D

$O(N \cdot \log N \cdot \log M)$ point update and range query.

```

struct node2D {
    int s, e, m;
    node1D *maxi;
    node2D *l, *r;
}

```



```

node2D(int a, int b, int c, int d) {
    s = a; e = b; m = (s+e)/2;
    maxi = new node1D(c, d);
    if (s != e) {
        l = new node2D(s, m, c, d);
        r = new node2D(m+1, e, c, d);
    }
}

void pu(int a, int b, int v) {
    if (s == e) { maxi->pu(b, v); return; }
    if (a <= m) l->pu(a, b, v);
    else r->pu(a, b, v);
    maxi->pu(b, max(l->maxi->rq(b, b), r->maxi->rq(b, b)));
}

int rq(int a, int b, int c, int d) {
    if (s == a && e == b) return maxi->rq(c, d);
    if (b <= m) return l->rq(a, b, c, d);
    if (a > m) return r->rq(a, b, c, d);
    return max(l->rq(a, m, c, d), r->rq(m+1, b, c, d));
}
} *root;

root = new node(0, n-1, 0, n-1);

```

2 Graph Theory

2.1 Depth First Search

Runs in $O(V + E)$.

```

// For adjacency lists
void dfs(int x, int p) {
    for (int y : adj[x]) {
        if (y != p) {
            dist[y] = dist[x]+1;
            dfs(y, x);
        }
    }
}

```

2.2 Breadth First Search

Runs in $O(V + E)$.

```

// For adjacency lists
visited[s] = 1;
dist[s] = 0;
q.push(s);
while (!q.empty()) {
    int f = q.front(); q.pop();
    for (int i : adjlist[f]) {
        if (!visited[i]) {
            q.push(i);
            visited[i] = 1;
            dist[i] = dist[f] + 1;
        }
    }
}

```

2.3 0-1 BFS

Runs in $O(V + E)$.

```
// For adjacency lists
deque<int> dq;
dist[s] = 0;
dq.push(s);
while (!dq.empty()) {
    int u = dq.front(); dq.pop();
    for (int e : adjlist[u]) {
        int v = e.first, w = e.second;
        if (dist[v] > dist[u] + w) {
            dist[v] = dist[u] + w;
            if (w == 0) dq.push_front(v);
            else dq.push_back(v);
        }
    }
}
```

2.4 Floyd-Warshall

Runs in $O(N^3)$.

```
// Initialise adjacency matrix
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        if (i == j) adj[i][j] = 0;
        else adj[i][j] = INF;
    }
}

// Floyd-Warshall
for (int k = 0; k < n; k++) {
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            adj[i][j] = min(adj[i][j], adj[i][k] + adj[k][j]);
            if (adj[i][i] < 0) negCycle = true;
        }
    }
}
```

2.5 Bellman-Ford

Runs in $O(VE)$.

```
vector<int> dist(n, INF);
dist[s] = 0;
bool negCycle = false;
for (int i = 1; i <= n; i++) {
    bool update = false;
    for (Edge e : edges) {
        if (dist[e.u] < INF && dist[e.v] > dist[e.u] + e.w) {
            dist[e.v] = dist[e.u] + e.w;
            update = true;
        }
    }
    if (!update) break;
    if (update && i == n) negCycle = true;
}
```

2.6 Dijkstra's Algorithm

Runs in $O(E \log V)$.

```
priority_queue<pi, vector<pi>, greater<pi>> pq;
vector<int> dist(n, INF);
dist[s] = 0;
pq.push({0, s});
while (!pq.empty()) {
    pi f = pq.top(); pq.pop();
    int d = f.first, u = f.second;
    if (d != dist[u]) continue;
    for (pi x : adj[u]) {
        int v = x.first, w = x.second;
        if (dist[v] > d + w) {
            dist[v] = d + w;
            pq.push({ dist[v], v });
        }
    }
}
```

2.7 Shortest Path Faster Algorithm

Runs in $O(VE)$.

```
vector<int> dist(n, INF);
vector<int> inQueue(n, 0);
queue<int> q;
dist[s] = 0;
q.push(s);
inQueue[s]++;
bool negCycle = false;
while (!q.empty()) {
    int u = q.front(); q.pop();
    inQueue[u]--;
    for (Edge e : adj[u]) {
        if (dist[e.v] > dist[u] + e.w) {
            dist[e.v] = dist[u] + e.w;
            if (inQueue[e.v] == 0) {
                q.push(e.v);
                inQueue[e.v]++;
                if (inQueue[e.v] > n) {
                    negCycle = true;
                    break;
                }
            }
        }
    }
}
if (negCycle) break;
}
```

2.8 Prim's Algorithm

Runs in $O(E \log V)$.

```
priority_queue<pi, vector<pi>, greater<pi>> pq;
vector<int> dist(n, INF);
vector<bool> vis(n, false);
dist[s] = 0;
```

```

pq.push({0, s});
while (!pq.empty()) {
    pi f = pq.top(); pq.pop();
    int d = f.first, u = f.second;
    if (vis[u]) continue;
    vis[u] = true;
    for (pi x : adj[u]) {
        int v = x.first, w = x.second;
        if (!vis[v] && dist[v] > w) {
            dist[v] = w;
            pq.push({ dist[v], v });
        }
    }
}
}

```

2.9 Union Find Disjoint Subset

With both path compression and union by rank, runs in $O(\alpha(n))$ (basically constant time).

```

int p[MAXN];
int sz[MAXN];

int root(int x) {
    if (p[x] == -1) return x;
    return p[x] = root(p[x]);
}

void connect(int x, int y) {
    x = root(x); y = root(y);
    if (x == y) return;
    if (sz[x] < sz[y]) swap(x, y);
    p[y] = x;
    sz[x] += sz[y];
}

fill(p, p+MAXN, -1);
fill(sz, sz+MAXN, 1);

```

2.10 Kruskal's Algorithm

Runs in $O(E \log E)$.

```

sort(edges.begin(), edges.end());
for (Edge e : edges) {
    if (root(e.u) != root(e.v)) {
        connect(e.u, e.v);
        cost += e.w;
    }
}

```

2.11 Topological Sort

Runs in $O(V + E)$.

```

void dfs(int x) {
    if (v[x]) return;
    v[x] = 1;
    for (int y : adj[x]) dfs(y);
}

```

```

        topo.push_back(x);
    }
    for (int i = 0; i < n; i++) dfs(i);
    reverse(topo.begin(), topo.end());

```

2.12 Floyd's Cycle Finding Algorithm

For graphs with outdegree 1, runs in $O(V + E)$.

```

// detect cycle
int slow = s, fast = s;
do {
    slow = nxt[slow];
    fast = nxt[nxt[fast]];
} while (slow != fast);
// find start of cycle
slow = start;
while (slow != fast) {
    slow = nxt[slow];
    fast = nxt[fast];
}
// collect all nodes in cycle
vector<int> cycle;
int cur = slow;
do {
    cycle.push_back(cur);
    cur = nxt[cur];
} while (cur != slow);

```

2.13 Maximum Cardinality Bipartite Matching

2.13.1 Kun's Algorithm

Runs in $O(V^3)$.

```

int n, mcbms = 0, miss = 0;
vector<int> match;
vector<bool> vis;
vector<vector<int>> adj;
vector<int> left;

// dfs for augmenting path
bool dfs(int u) {
    for (int v : adj[u]) {
        if (!vis[v]) {
            vis[v] = true;
            if (match[v] == -1 || dfs(match[v])) {
                match[v] = u;
                match[u] = v;
                return true;
            }
        }
    }
    return false;
}

void mcbm() {
    match.assign(n, -1);

```

```

mcbms = 0;
// greedy initial matching
for (int u : left) {
    for (int v : adj[u]) {
        if (match[v] == -1) {
            match[v] = u;
            match[u] = v;
            mcbms++;
            break;
        }
    }
}
// dfs augmenting paths for unmatched
for (int u : left) {
    if (match[u] == -1) {
        vis.assign(n, false);
        if (dfs(u)) mcbms++;
    }
}
miss = n - mcbms;
}

```

2.13.2 Hopcroft-Karp

Runs in $O(E \cdot \sqrt{V})$.

```

int n, m;
vector<vector<int>> adj;
vector<int> pairU, pairV, dist;

bool bfs() {
    queue<int> q;
    for (int u = 0; u < n; u++) {
        if (pairU[u] == -1) {
            dist[u] = 0;
            q.push(u);
        } else {
            dist[u] = INF;
        }
    }
    bool found = false;
    while (!q.empty()) {
        int u = q.front(); q.pop();
        for (int v : adj[u]) {
            if (pairV[v] == -1) {
                found = true;
            } else if (dist[pairV[v]] == INF) {
                dist[pairV[v]] = dist[u] + 1;
                q.push(pairV[v]);
            }
        }
    }
    return found;
}

bool dfs(int u) {
    for (int v : adj[u]) {
        if (pairV[v] == -1 || (dist[pairV[v]] == dist[u] + 1 && dfs(pairV[v]))) {

```

```

        pairU[u] = v;
        pairV[v] = u;
        return true;
    }
}
dist[u] = INF;
return false;
}

int hopcroftKarp() {
    pairU.assign(n, -1);
    pairV.assign(m, -1);
    dist.assign(n, 0);
    int mcbm = 0;
    while (bfs()) {
        for (int u = 0; u < n; u++) {
            if (pairU[u] == -1 && dfs(u)) {
                mcbm++;
            }
        }
    }
    return mcbm;
}

```

2.14 Articulation Points and Bridges

Using Tarjan's Algorithm, runs in $O(V + E)$.

```

vector<int> adj[MAXN];
vector<int> dep(MAXN, 0), low(MAXN, 0), par(MAXN, -1);
vector<int> chi(MAXN, 0), atp(MAXN, 0);
vector<bool> vis(MAXN, false);
vector<pi> bridges;

void tarjan(int u, int d) {
    vis[u] = true;
    dep[u] = low[u] = d;
    chi[u] = 0; atp[u] = 1;
    for (int v : adj[u]) {
        if (!vis[v]) {
            par[v] = u;
            chi[u]++;
            tarjan(v, d+1);
            low[u] = min(low[u], low[v]);
            if (low[v] >= dep[u]) atp[u]++;
            if (low[v] > dep[u]) bridges.push_back({u, v});
        } else if (v != par[u]) {
            low[u] = min(low[u], dep[v]);
        }
    }
}

tarjan(0, 0);
// handle root separately since it has no parents
atp[0] = chi[0];
// atp stores number of components separated upon removal
// bridges stores all bridges in the graph

```

2.15 Strongly Connected Components

Using Tarjan's Algorithm, runs in $O(V + E)$.

```
vector<int> adj[MAXN];
vector<int> comps[MAXN];
set<int> adjscs[MAXN];
vector<int> idxs(MAXN, -1), low(MAXN, 0);
vector<bool> onStack(MAXN, false);
stack<int> st;
int dfsidx = 0, sccidx;
int comp[MAXN];

void scc(int u) {
    idxs[u] = low[u] = dfsidx++;
    st.push(u);
    onStack[u] = true;
    for (int v : adj[u]) {
        if (idxs[v] == -1) {
            scc(v);
            low[u] = min(low[u], low[v]);
        } else if (onStack[v]) {
            low[u] = min(low[u], idxs[v]);
        }
    }
    if (low[u] == idxs[u]) {
        // u is a root of an scc
        comps[sccidx].clear();
        int w;
        do {
            w = st.top(); st.pop();
            onStack[w] = false;
            comps[sccidx].push_back(w);
            comp[w] = sccidx;
        } while (w != u);
        sccidx++;
    }
}

for (int i = 1; i <= n; i++) {
    if (idxs[i] == -1) scc(i);
}

for (int u = 1; u <= n; u++) {
    for (int v : adj[u]) {
        if (comp[u] != comp[v]) adjscs[comp[u]].insert(comp[v]);
    }
}

// dfs idxs now range from 0 to dfsidx-1
// scc idxs now range from 0 to sccidx-1
```

2.16 Trees

2.16.1 Pre/Postorder Traversal

Runs in $O(V)$.

```
int prec = 0, postc = 0;
```



```

void dfs(int x, int p) {
    pre[x] = prec++;
    for(int y : adj[x]) {
        if (y != p) dfs(y, x);
    }
    post[x] = postc++;
}

```

2.16.2 Subtree to Range

Runs in $O(V)$.

```

int dfs(int x, int p) {
    pre[x] = c++;
    rig[pre[x]] = pre[x];
    for (int y : adj[x]) {
        if (y != p) {
            rig[pre[x]] = max(rig[pre[x]], dfs(y, x));
        }
    }
    return rig[pre[x]];
}
// Subtree -> pre[x], rig[pre[x]]
// Node Index -> pre[x]
// Range of Children -> pre[x]+1, rig[pre[x]]

```

2.16.3 Weighted Maximum Independent Set

Runs in $O(V)$.

```

int dp[MAXN][2];

int mis(int v, bool take, int p) {
    if (dp[v][take] != -1) return dp[v][take];
    int ans = take * c[v];
    for (int u : adj[v]) {
        if (u == p) continue;
        int temp = mis(u, 0, v);
        if (!take) temp = max(temp, mis(u, 1, v));
        ans += temp;
    }
    return dp[v][take] = ans;
}

void ans(int v, bool take, int p) {
    for (int u : adj[v]) {
        if (u == p) continue;
        int temp0 = dp[u][0], temp1 = (take ? -1 : dp[u][1]);
        if (temp0 > temp1) ans(u, 0, v);
        else { a.push_back(u); ans(u, 1, v); }
    }
}

memset(dp, -1, sizeof(dp));
mis(0, 0, -1); // don't take root
mis(0, 1, -1); // take root
if(dp[0][1] > dp[0][0]) { a.push_back(0); ans(0, 1, -1); }
else ans(0, 0, -1);

```

2.16.4 Diameter

Runs in $O(V)$.

```
pi dfs(int x, int p, int d) {
    pi b = {x, d};
    for (pi y : adj[x]) {
        if (y.first != p) {
            pi c = dfs(y.first, x, d + y.second);
            if (c.second > b.second) b = c;
        }
    }
    return b;
}
pi s = dfs(0, -1, 0);
pi e = dfs(s.first, -1, 0);
// e.second gives diameter
// For even diameter, centroid is at e.second / 2
// For odd diameter, centroid is at e.second / 2 and e.second / 2 + 1
```

2.16.5 2^K Decomposition

$O(N \log N)$ precomputation and memory, $O(\log N)$ query.

```
int par(int x, int k) {
    for(int i = MAXLOGN; i >= 0; i--) {
        if (k >= (1 << i)) {
            if(x == -1) return x;
            x = p[x][i];
            k -= (1 << i);
        }
    }
    return x;
}

int p[MAXN][MAXLOGN];
memset(p, -1, sizeof(p));
dfs(0); // compute initial parent p[i][0]
for (int k = 1; k <= MAXLOGN; k++) {
    for (int i = 0; i < n; i++) {
        if(p[i][k-1] != -1) p[i][k] = p[p[i][k-1]][k-1];
    }
}
}
```

2.16.6 Lowest Common Ancestor

Runs in $O(\log N)$.

```
int lca(int x, int y) {
    // make both nodes the same depth
    if (dep[x] < dep[y]) swap(x, y);
    for (int k = MAXLOGN; k >= 0; k--) {
        if (p[x][k] != -1 && dep[p[x][k]] >= dep[y]) x = p[x][k];
    }
    if (x == y) return x;
    // perform binary lifting while parents are different
    for (int k = MAXLOGN; k >= 0; k--) {
        if (p[x][k] != p[y][k]) {
            x = p[x][k];
        }
    }
    return p[x][0];
}
```

```

        y = p[y][k];
    }
}
// find the next parent
return p[x][0];
}

```

2.16.7 Shortest Path

Runs in $O(\log N)$.

```

int distance(int x, int y) {
    return dist[x] + dist[y] - 2 * dist[lca(x, y)];
}

```

3 Dynamic Programming

3.1 Maxsum

3.1.1 1D

Kadane's Algorithm. Runs in $O(N)$.

```

int ans = nums[0], cur = nums[0];
for (int i = 1; i < nums.size(); i++) {
    if (cur < 0) cur = 0;
    cur += nums[i];
    ans = max(ans, cur);
}

```

3.2 Longest Increasing Subsequence

3.2.1 N^2 DP

```

int ans = 0, dp[n];
memset(dp, 0, sizeof(dp));
for (int i = 0; i < n; i++) {
    for (int j = 0; j < i; j++) {
        if (a[j] < a[i]) {
            dp[i] = max(dp[i], dp[j]);
        }
    }
    dp[i]++;
    ans = max(ans, dp[i]);
}

```

3.2.2 Data Structure Speedup

```

// Data structure should support point max updates and range max queries
// Discretise values first
for (int i = 0; i < n; i++) {
    t = query(a[i] - 1) + 1;
    update(a[i], t);
    ans = max(ans, t);
}

```

3.2.3 $N \log N$ DP

```
int len = 0, dp[n];
memset(dp, 0, sizeof(dp));
for (int x : a) {
    int pos = lower_bound(dp, dp + len, x) - dp;
    dp[pos] = x;
    if (pos == len) len++;
}
cout << len;
```

3.3 Coin Combinations

Runs in $O(N \cdot V)$.

```
int ways[v+1];
memset(ways, 0, sizeof(ways));
ways[0] = 1;
for (int i = 0; i < n; i++) {
    int c = coins[i];
    for (int sum = c; sum <= v; sum++) {
        ways[sum] = (ways[sum] + ways[sum - c]) % MOD;
    }
}
cout << ways[v];
```

3.4 Coin Change

Runs in $O(N \cdot V)$.

```
const int INF = 1e9;
vector<int> dp(v + 1, INF);
dp[0] = 0;
for (int i = 1; i <= v; i++) {
    for (int j = 0; j < n; j++) {
        if (i >= c[j] && dp[i - c[j]] != INF) {
            dp[i] = min(dp[i], dp[i - c[j]] + 1);
        }
    }
}
cout << dp[v];
```

3.5 Knapsack

3.5.1 0-1

Runs in $O(N \cdot S)$.

```
for (int i = 0; i < n; i++) {
    for (int j = s; j >= w[i]; j--) {
        dp[j] = max(dp[j], dp[j - w[i]] + v[i]);
    }
}
cout << dp[s];
```

3.6 Digit DP

Runs in $O(D)$.

```
// Example - Numbers
// Compute the number of palindrome free numbers in a given range

vector<int> num;
ll dp[20][11][11][2][2]; // idx, last1, last2, tight, hasStarted

ll derp(int pos, int last1, int last2, bool tight, bool hasStarted) {
    if(pos == num.size()) return 1; // successfully populated whole number

    if(dp[pos][last1][last2][tight][hasStarted] != -1) {
        // state already visited
        return dp[pos][last1][last2][tight][hasStarted];
    }

    ll res = 0;
    int limit = tight ? num[pos] : 9; // do we need to keep to the range
    for(int d = 0; d <= limit; d++) { // try all next digits
        bool newHasStarted = hasStarted || (d != 0);
        bool newTight = tight && (d == limit);
        // skip palindromes only if the number has started
        if(newHasStarted) {
            if(d == last1) continue; // palindrome length 2
            if(d == last2) continue; // palindrome length 3
        }
        int newLast1 = newHasStarted ? d : 10;
        int newLast2 = hasStarted ? last1 : 10;
        res += derp(pos+1, newLast1, newLast2, newTight, newHasStarted);
    }
    return dp[pos][last1][last2][tight][hasStarted] = res;
}

// convert number to digits
void dcmp(ll x){
    num.clear();
    if(x == 0) num.push_back(0);
    while(x > 0) {
        num.push_back(x % 10);
        x /= 10;
    }
    reverse(num.begin(), num.end());
}

// Total Valid with value <= x
// Use PIE to get number within [a, b]
ll solve(ll x){
    dcmp(x);
    memset(dp, -1, sizeof(dp));
    return derp(0, 10, 10, true, false);
}

// To compute the kth string satisfying
// Either binary search or build character by character:
int count = 0;
vector<int> ans;
```

```

for (int i = 0; i < n; i++) {
    int x = 0;
    for (int j = 1; j < 10; j++) { // adjust to size of alphabet
        if (count + dp(i, j) > k) {
            break;
        }
        x = j;
    }
    count += dp(i, x); // position i is bounded by x
    ans.push_back(x);
}

```

3.7 Convex Hull Trick

Supports insertion and queries in amortised $O(1)$.

```

// Example: Commando
// Partition into contiguous groups with maximal effectiveness
// Group effectiveness is a quadratic function of their sum
// dp(x) = max(dp(i)+f(p(x)-p(i)))
//         = max(dp(i)+a(p(x)-p(i))^2+b(p(x)-p(i))+c)
//         = max(dp(i)+ap(x)^2-2ap(x)p(i)+ap(i)^2+bp(x)-bp(i))+c
//         = max(dp(i)+ap(i)^2-bp(i)-2ap(x)p(i))+ap(x)^2+bp(x)+c
//         = max([dp(i)+ap(i)^2-bp(i)][-2ap(i)][p(x)])[+ap(x)^2+bp(x)+c]
//         = max(c(i)+m(i)p(x))+v(x)
// c(i) = dp(i)+ap(i)^2-bp(i)
// m(i) = -2ap(i)
// v(x) = ap(x)^2+bp(x)+c
// Lines have increasing gradients, queries have increasing x

deque<pi> hull;

ll func(pi line, ll x){
    return line.first*x+line.second;
}

ld intersection(ll m1, ll c1, ll m2, ll c2) {
    return (ld) (c2-c1) / (m1-m2);
}

ld intersect(pi x, pi y) {
    return intersection(x.first, x.second, y.first, y.second);
}

// query maximum y at x
ll query(ll x) {
    while (hull.size() > 1) {
        if (func(hull[0], x) < func(hull[1], x)) {
            hull.pop_front();
        } else break;
    }
    return func(hull[0], x);
}

// insert new line
void insert(ll m, ll c) {
    pi line = pi(m, c);
    while (hull.size() > 1) {

```

```

        ll s = hull.size();
        if (intersect(hull[s-1], line) <= intersect(hull[s-2], line)) {
            hull.pop_back();
        } else break;
    }
    hull.push_back(line);
}

insert(0, 0); // dp[0]
for(int i = 1; i <= n; i++){
    dp[i] = query(ps[i])+a*ps[i]*ps[i]+b*ps[i]+c; // max(mx + c) + v
    insert(-2*a*ps[i], dp[i]+a*ps[i]*ps[i]-b*ps[i]); // insert new (m, c)
}

```

3.8 Li Chao Tree

Supports insertion and queries in $O(\log X)$ time where X is the domain.

```

struct Node {
    ll m, c;
    Node *lc, *rc;
    Node(ll _m = 0, ll _c = -INF) {
        m = _m; c = _c;
        lc = nullptr; rc = nullptr;
    }
    ll value(ll x) {
        return m * x + c;
    }
    void insert(ll nm, ll nc, ll l, ll r) {
        ll mid = (l+r)/2;
        bool leftCheck = nm * l + nc > value(l);
        bool midCheck = nm * mid + nc > value(mid);
        if (midCheck) {
            swap(m, nm);
            swap(c, nc);
        }
        if (r-l == 1) return;
        if (leftCheck != midCheck) {
            if (!lc) lc = new Node();
            lc->insert(nm, nc, l, mid);
        } else {
            if (!rc) rc = new Node();
            rc->insert(nm, nc, mid, r);
        }
    }
    ll query(ll x, ll l, ll r) {
        ll res = value(x);
        if (r-l == 1) return res;
        ll mid = (l+r)/2;
        if (x < mid && lc) return max(res, lc->query(x, l, mid));
        if (x >= mid && rc) return max(res, rc->query(x, mid, r));
        return res;
    }
};

// Queries are on half open [L, R)
// Example: Commando
Node *root = new Node();

```

```

root->insert(0, 0, MINX, MAXX);
for (int i = 1; i <= n; i++) {
    // query lct
    ll x = p[i];
    ll best = root->query(x, MINX, MAXX);
    dp[i] = best + a*x*x + b*x + c;
    // update lct
    ll m = -2*a*x;
    ll c = dp[i] + a*x*x - b*x;
    root->insert(m, c, MINX, MAXX);
}

```

3.9 Divide and Conquer

Reduces complexity from $O(N^2 \cdot K)$ to $O(N \log N \cdot K)$.

```

// Example: Guards
// Minimise sum of costs where cost of partition is length * sum
// DP has form dp(i, j) = min dp(i-1, k-1) + C(k, j)
// i is the current layer, k to j is the new group
// Cost function satisfies quadrangle inequality:
// C(a, c) + C(b, d) <= C(a, d) + C(b, c) for a <= b <= c <= d

long long cost(int s, int e) {
    return (ps[e]-ps[s-1])*(e-s+1);
}

void dnc(int s, int e, long long x, int y, int k) {
    if(s > e) return;
    int m = (s+e)/2, best = 0;
    dp[m][k] = INF;
    for (int i = x; (i <= y && i <= m); i++) {
        ll val = dp[i][!k]+cost(i+1, m);
        if (dp[m][k] > val) {
            dp[m][k] = val;
            best = i;
        }
    }
    if (s < m) dnc(s, m-1, x, best, k);
    if (m < e) dnc(m+1, e, best, y, k);
}

// Uses DP on the fly to save space
for (int i = 1; i <= n; i++) dp[i][0] = INF;
for (int i = 1; i <= g; i++) {
    for (int j = 1; j <= n; j++) dp[j][i%2] = INF;
    dnc(0, n, 0, n, i%2);
}

```

4 Math

4.1 Fast Exponentiation

Runs in $O(\log b)$.

```

int powmod(int a, int b, int m) {
    int res = 1;

```



```

    while (b > 0) {
        if (b & 1) res = (res * a) % m;
        a = (a * a) % m;
        b >>= 1;
    }
    return res % m;
}

```

4.2 Prime Factorisation

Runs in $O(\sqrt{x})$.

```

map<int, int> cnt;
while (x % 2 == 0) {
    cnt[2]++;
    x /= 2;
}
for (int i = 3; i * i <= x; i++) {
    while (x % i == 0) {
        cnt[i]++;
        x /= i;
    }
}
if (x > 1) {
    cnt[x]++;
}

```

4.3 Sieve of Eratosthenes

Runs in $O(n \log \log n)$ with high constant.

```

bitset<MAXN> prime;
prime.set();
prime[0] = prime[1] = 0;
for (int i = 2; i < MAXN; i++) {
    if (prime[i]) {
        for (int j = i*i; j < MAXN; j += i) {
            prime[j] = 0;
        }
    }
}

```

4.4 Greatest Common Divisor

Runs in $O(\log \min(a, b))$.

```

int gcd(int a, int b) {
    if (a > b) swap(a, b);
    while (a != 0) {
        b %= a;
        swap(a, b);
    }
    return b;
}

```

4.5 Lowest Common Multiple

```
int lcm(int a, int b) {
    return a / gcd(a, b) * b;
}
```

4.6 Modular Inverse

```
ll modinv(ll a){
    return powmod(a, MOD-2, MOD);
}
```

4.7 $\binom{n}{k}$

Precomputation takes $O(MAXN)$ time, queries answered in $O(1)$.

```
ll fac[MAXN+1], modinv[MAXN+1];

ll nck(ll n, ll k) {
    if (n < k) return 0;
    ll res = fac[n];
    res = (res * modinv[k]) % MOD;
    res = (res * modinv[n-k]) % MOD;
    return res;
}

fac[0] = 1;
for(int i = 1; i <= MAXN; i++) {
    fac[i] = fac[i-1] * i % MOD;
}
modinv[MAXN] = powmod(fac[MAXN], MOD-2, MOD);
for(int i = MAXN; i > 0; i--) {
    modinv[i-1] = modinv[i] * i % MOD;
}
```

4.8 Fibonacci

Runs in $O(\log N)$ time.

```
struct Mat {
    ll a, b, c, d; // 2x2 Matrix: [a b; c d]
};

Mat mul(Mat x, Mat y) {
    return {
        x.a*y.a + x.b*y.c,
        x.a*y.b + x.b*y.d,
        x.c*y.a + x.d*y.c,
        x.c*y.b + x.d*y.d
    };
}

Mat mpow(Mat base, long long exp) {
    Mat res = {1, 0, 0, 1}; // Identity Matrix
    while (exp) {
        if (exp & 1) res = mul(res, base);
    }
}
```

```

        base = mul(base, base);
        exp >>= 1;
    }
    return res;
}

11 fib(long long n) {
    if (n == 0) return 0;
    Mat m = {1, 1, 1, 0}; // Fibonacci Seed Matrix
    return mpow(m, n-1).a;
}

```

5 Algorithms

5.1 Binary Search

Find the cuberoot of n . Runs in $O(\log N)$.

```

long long n; cin >> n;
long long mini = 0, maxi = 1e6, medi;
while (mini < maxi) {
    medi = mini+(maxi-mini)/2;
    if (medi * medi * medi >= n) maxi = medi;
    else mini = medi+1;
}
cout << mini << "\n";

```

5.2 Binary Search using Lifting

Find the cuberoot of n . Runs in $O(\log N)$.

```

long long n; cin >> n;
long long cur = 0, gap = 1e6, next;
while (gap > 0) {
    while (next = cur + gap, next * next * next < n) {
        cur = next;
    }
    gap >>= 1;
}
cout << cur+1 << "\n";

```

5.3 Sliding Set

Speeds up DP from $O(N^2)$ to $O(N \log N)$.

```

// Example - Candymountain
// Jump across with minimax candies
// Populate with initial window
for(int i = 0; i < k; i++) {
    dp[i] = candies[i];
    s.insert(candies[i]);
}
// Sliding Set
for(int i = k; i < n; i++){
    dp[i] = max(candies[i], *s.begin());
    s.erase(s.find(dp[i-k]));
    s.insert(dp[i]);
}

```

5.4 Set Merging

Reduces complexity from $O(Q \cdot N \log N)$ to $O(N \log^2 N)$.

```
for (int i = 0; i < q; i++) {
    cin >> a >> b;
    // small to large merging
    if (s[a].size() > s[b].size()) swap(s[a], s[b]);
    for (int x : s[a]) s[b].insert(x);
    s[a].clear();
    cout << s[b].size() << "\n";
}
```

5.5 Discretisation

Runs in $O(N \log N)$.

```
vector<int> a(n);
vector<int> b = a;
sort(b.begin(), b.end());
b.erase(unique(b.begin(), b.end()), b.end());
for (int &i : a) {
    i = lower_bound(b.begin(), b.end(), i) - b.begin() + 1; // 1-indexed
}
// a now holds discretised values
```

6 Miscellaneous

6.1 Fast I/O

Cannot use with `scanf`, `printf`.

```
ios_base::sync_with_stdio(false);
cin.tie(0);
```

6.2 Superfast I/O

Only for non-negative integer input.

```
inline ll ri () {
    ll x = 0;
    char ch = getchar_unlocked();
    while (ch < '0' || ch > '9') ch = getchar_unlocked();
    while (ch >= '0' && ch <= '9') {
        x = (x << 3) + (x << 1) + ch - '0';
        ch = getchar_unlocked();
    }
    return x;
}
```
