

noiref

ngmh

February 2019

Contents

1	Data Structures	3
1.1	Fenwick Trees	3
1.1.1	Point Update, Range Query	3
1.1.2	Range Update, Point Query	3
1.1.3	Range Update, Range Query	3
1.2	Segment Trees	3
1.2.1	1D	3
1.2.2	Lazy Propagation	4
1.2.3	2D	4
1.3	Sparse Table	5
2	Graph Theory	5
2.1	Depth First Search	5
2.2	Breadth First Search	5
2.3	Floyd-Warshall	5
2.4	Dijkstra	6
2.5	Travelling Salesman Problem	6
2.6	Union Find Disjoint Subset	6
2.7	Minimum Spanning Tree	6
2.7.1	Kruskal	6
2.7.2	Prim's	7
2.8	Bipartite Matching	7
2.9	Articulation Points	7
2.10	Bridges	8
2.11	Strongly Connected Components	8
2.12	Trees	9
2.12.1	Diameter	9
2.12.2	2^K Decomposition	9
2.12.3	Lowest Common Ancestor	10
2.12.4	All Pairs Shortest Path	10
2.12.5	Preorder	10
2.12.6	Postorder	10
2.12.7	Subtree to Range	10
2.12.8	Leaf Pruning	11
2.12.9	Weighted Maximum Independent Set	11
2.12.10	Heavy-Light Decomposition	11
2.12.11	Centroid Decomposition	12
3	Dynamic Programming	12
3.1	Coin Change	12
3.2	Coin Combinations	12
3.3	Knapsack	12
3.3.1	0-1	12
3.3.2	0-K	12
3.4	Longest Increasing Subsequence	13

3.4.1	N^2	13
3.4.2	$N \log N$	13
3.4.3	Optimal	13
3.5	Longest Common Subsequence	13
3.5.1	N^2	13
3.5.2	Longest Increasing Subsequence	13
3.6	Digits	14
3.7	Convex Hull Speedup	14
3.8	Divide and Conquer	15
3.9	Prefix Sums	15
3.9.1	1D	15
3.9.2	2D	15
4	Math	16
4.1	Greatest Common Divisor	16
4.2	Lowest Common Multiple	16
4.3	Modular Functions	16
4.3.1	Multiplication	16
4.3.2	Exponentiation	16
4.4	Primes	16
4.4.1	Sieve of Eratosthenes	16
4.4.2	Prime Factorisation	17
4.5	Fibonacci	17
4.6	nC_k	17
5	Algorithms	17
5.1	Discretisation	17
5.2	Binary Search	18
5.3	Mo's Algorithm	18
6	Miscellaneous	18
6.1	Macros + Functions + Variables	18
6.2	Compile Commands	19
6.2.1	Compile	19
6.2.2	Build	19
6.2.3	Command Line	19
6.2.4	Simple Script	19
6.3	Input/Output	19
6.3.1	Fast	19
6.3.2	Faster	19
6.4	Pruning	19
6.5	Optimise	19

1 Data Structures

1.1 Fenwick Trees

1.1.1 Point Update, Range Query

```
void pu(int i, int v){
    for(; i <= n; i += ls(i)) fw[i] += v;
}
int pq(int i){
    int t = 0;
    for(; i; i -= ls(i)) t += fw[i];
    return t;
}
int rq(int s, int e){
    return pq(e)-pq(s-1);
}
```

1.1.2 Rang Update, Point Query

```
void ru(int s, int e, int v){
    pu(s, v);
    pu(e+1, -v);
}
```

1.1.3 Range Update, Range Query

```
void ru(int s, int e, int v){
    pu(fw1, s, v);
    pu(fw1, e+1, -v);
    pu(fw2, s, -v*(s-1));
    pu(fw2, e+1, v*e);
}
int ps(int i){
    return pq(fw1, i)*i+pq(fw2, i);
}
int rq(int s, int e){
    return ps(e)-ps(s-1);
}
```

1.2 Segment Trees

1.2.1 1D

```
struct node {
    int s, e, m, v;
    node *l, *r;
    node(int _s, int _e){
        s = _s; e = _e; m = (s+e)/2; v = 0;
        if(s != e){
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(int x, int y){
        if(s == e){ v = y; return; }
        if(x <= m) l->pu(x, y);
        if(x > m) r->pu(x, y);
        v = min(l->v, r->v);
    }
    int rq(int x, int y){
```

```

        if(s == x && e == y) return v;
        if(y <= m) return l->rq(x, y);
        if(x > m) return r->rq(x, y);
        return min(l->rq(x, m), r->rq(m+1, y));
    }
} *root;

```

1.2.2 Lazy Propagation

```

int pu(){
    if(s == e){ v += lazy; lazy = 0; return v; }
    v += lazy;
    l->lazy += lazy; r->lazy += lazy;
    lazy = 0;
    return v;
}

void ru(int x, int y, int z){
    if(s == x && e == y){ lazy += z; return; }
    if(y <= m) l->ru(x, y, z);
    else if(x > m) r->ru(x, y, z);
    else l->ru(x, m, z), r->ru(m+1, y, z);
    v = max(l->pu(), r->pu());
}

int rq(int x, int y){
    pu();
    if(s == x && e == y) return pu();
    if(y <= m) return l->rq(x, y);
    if(x > m) return r->rq(x, y);
    return max(l->rq(x, m), r->rq(m+1, y));
}

```

1.2.3 2D

```

struct node2D {
    int s, e, m;
    node1D *maxi;
    node2D *l, *r;
    node2D(int a, int b, int c, int d){
        s = a; e = b; m = (s+e)/2;
        maxi = new node1D(c, d);
        if(s != e){
            l = new node2D(s, m, c, d);
            r = new node2D(m+1, e, c, d);
        }
    }
    void pu(int a, int b, int v){
        if(s == e){ maxi->pu(b, v); return; }
        if(a <= m) l->pu(a, b, v);
        else r->pu(a, b, v);
        maxi->pu(b, max(l->maxi->rq(b, b), r->maxi->rq(b, b)));
    }
    int rq(int a, int b, int c, int d){
        if(s == a && e == b) return maxi->rq(c, d);
        if(b <= m) return l->rq(a, b, c, d);
        if(a > m) return r->rq(a, b, c, d);
        return max(l->rq(a, m, c, d), r->rq(m+1, b, c, d));
    }
} *root;

```

1.3 Sparse Table

```
int query(int l, int r){
    r++;
    int p = 31-__builtin_clz(r-l);
    return __gcd(sp[p][l], sp[p][r-(1<<p)]);
}

h = floor(log2(n));
for(int i = 0; i < n; i++) sp[0][i] = a[i];
for(int i = 1; i <= h; i++){
    for(int j = 0; j+(1<<i) <= n; j++){
        sp[i][j] = __gcd(sp[i-1][j], sp[i-1][j+(1<<(i-1))]);
    }
}
```

2 Graph Theory

2.1 Depth First Search

```
void dfs(int x, int p){
    for(auto it : adj[x]){
        if(it != p){
            par[it] = x;
            dep[it] = dep[x]+1;
            dist[it] = dist[x]+1;
            dfs(it, x);
        }
    }
}
```

2.2 Breadth First Search

```
d[nx][ny] = 0;
q.push(pi(sx, sy));
while(!q.empty()){
    pi f = q.front(); q.pop();
    for(int i = 0; i < 4; i++){
        nx = f.first+dx[i];
        ny = f.second+dy[i];
        if(nx < 0 || ny < 0 || nx >= h || ny >= w) continue;
        if(d[nx][ny] != -1) continue;
        d[nx][ny] = d[f.first][f.second]+1;
        q.push(pi(nx, ny));
    }
}
```

2.3 Floyd-Warshall

```
for(int i = 0; i < n; i++){
    for(int j = 0; j < n; j++){
        if(i == j) adj[i][j] = 0;
        else adj[i][j] = INT_MAX;
    }
}

for(int k = 0; k < n; k++){
    for(int i = 0; i < n; i++){
        for(int j = 0; j < n; j++){
            adj[i][j] = min(adj[i][j], adj[i][k]+adj[k][j]);
        }
    }
}
```

```

    }
}

```

2.4 Dijkstra

```

priority_queue<pi, vector<pi>, greater<pi> > pq;
dist[s] = 0;
pq.push(pi(0, s));
while(!pq.empty()){
    pi f = pq.top(); pq.pop();
    for(auto it:adj[f.second]){
        if(dist[it.first] == -1 || dist[it.first] > f.first+it.second){
            dist[it.first] = f.first+it.second;
            pq.push(pi(dist[it.first], it.first));
        }
    }
}

```

2.5 Travelling Salesman Problem

```

long long adj[14][14], dp[8200][14];

//start with 1, 0
//mask is 0 visited, at node 0
long long tsp(long long mask, long long pos){
    if(mask == visited) return adj[pos][0];
    if(dp[mask][pos] != -1) return dp[mask][pos];
    long long ans = LLONG_MAX;
    for(int i = 0; i < m; i++){
        if((mask&(1<<i)) == 0){
            long long newans = adj[pos][i]+tsp(mask|(1<<i), i);
            ans = min(ans, newans);
        }
    }
    return dp[mask][pos] = ans;
}

```

```

visited = (1 << m)-1;
res = tsp(1, 0);
if(res < 0) cout << "-1";
else cout << res;

```

2.6 Union Find Disjoint Subset

```

int root(int x){
    if(p[x] == -1) return x;
    return p[x] = root(p[x]);
}
void connect(int x, int y){
    p[root(x)] = root(y);
}

```

2.7 Minimum Spanning Tree

2.7.1 Kruskal

```

sort(edgs.begin(), edgs.end());
for(auto it:edgs){

```

```

        if(root(it.second.first) != root(it.second.second)){
            connect(it.second.first, it.second.second);
            cost += it.first;
        }
    }
}

```

2.7.2 Prim's

```

priority_queue<pi, vector<pi>, greater<pi> > pq;
dist[s] = 0;
pq.push(pi(0, s));
while(!pq.empty()){
    pi f = pq.top(); pq.pop();
    for(auto it:adj[f.second]){
        if(dist[it.first] == -1 || dist[it.first] > max(f.first, it.second)){
            dist[it.first] = max(f.first, it.second);
            pq.push(pi(dist[it.first], it.first));
        }
    }
}
}

```

2.8 Bipartite Matching

```

bool dfs(int u){
    if(v[u]) return 0;
    v[u] = 1;
    for(auto v:adj[u]){
        if(match[v] == -1 || dfs(match[v])){
            match[v] = u;
            match[u] = v;
            return 1;
        }
    }
    return 0;
}

memset(match, -1, sizeof(match));
for(auto lit:ho){
    for(auto rit:adj[lit]){
        if(match[rit] == -1){
            match[rit] = lit;
            match[lit] = rit;
            mcbm++;
            break;
        }
    }
}

for(auto lit:ho){
    if(match[lit] == -1){
        memset(v, 0, sizeof(v));
        mcbm += dfs(lit);
    }
}

mis = n-mcbm;

```

2.9 Articulation Points

```

void atp(int node, int depth){
    vi[node] = 1;
    dep[node] = depth;
    low[node] = depth;
}

```

```

    for(auto it:adj[node]){
        if(!vi[it]){
            par[it] = node;
            atp(it, depth+1);
            chi[node]++;
            if(low[it] >= dep[node]) atps[node]++;
            low[node] = min(low[node], low[it]);
        } else if(it != par[node]){
            low[node] = min(low[node], dep[it]);
        }
    }
}
}
atp(0, 0);
// root -> chi[i]
// other -> atps[i]+1

```

2.10 Bridges

```

void bridges(int x, int par){
    if(dep[x] != -1) return;
    dep[x] = low[x] = co++;
    int t = 0;
    for(auto it:adj[x]){
        if(it == par && t == 0){ t++; continue; }
        if(dep[it] != -1){
            if(low[it] > dep[x]) bgs.push_back(pi(x, it));
            low[x] = min(low[x], low[it]);
            continue;
        }
        bridges(it, x);
        if(low[it] > dep[x]) bgs.push_back(pi(x, it));
        low[x] = min(low[x], low[it]);
    }
}

for(int i = 1; i <= n; i++) bridges(i, 0);

```

2.11 Strongly Connected Components

```

stack<int> s;
vector<int> cur, adj[100001];
set<int> adjsc[100001];
vector<vector<int>> > comps;
void scc(int v){
    idxs[v] = idx;
    lowlink[v] = idx;
    idx++;
    s.push(v);
    ins[v] = 1;
    for(auto w:adj[v]){
        if(idxs[w] == -1){
            scc(w);
            lowlink[v] = min(lowlink[v], lowlink[w]);
        } else if(ins[w]){
            lowlink[v] = min(lowlink[v], idxs[w]);
        }
    }
    if(lowlink[v] == idxs[v]){
        cur.clear();
        w = 0;
    }
}

```



```

        while(w != v){
            w = s.top(); s.pop();
            ins[w] = 0;
            cur.push_back(w);
        }
        comps.push_back(cur);
    }
}
idx = 1;
memset(idxs, -1, sizeof(idxs));
for(int i = 1; i <= n; i++){
    if(idxs[i] == -1) scc(i);
}
memset(com, -1, sizeof(com));
for(int i = 0; i < comps.size(); i++){
    for(auto it:comps[i]) com[it] = i;
}
for(int i = 1; i <= n; i++){
    for(auto it:adj[i]){
        if(com[i] != com[it]) adjsc[com[i]].insert(com[it]);
    }
}
}

```

2.12 Trees

2.12.1 Diameter

```

pi dfs(int node, int par, int dist){
    pi b = pi(node, dist);
    for(auto it:adj[node]){
        if(it.first != par){
            pi c = dfs(it.first, node, dist+it.second);
            if(c.second > b.second) b = c;
        }
    }
    return b;
}
f = dfs(0, -1, 0);
l = dfs(f.first, -1, 0);
// l.second

```

2.12.2 2^K Decomposition

```

int par(int x, int k){
    for(int i = 19; i >= 0; i--){
        if(k >= (1<<i)){
            if(x == -1) return x;
            x = p[x][i];
            k -= (1<<i);
        }
    }
    return x;
}

memset(p, -1, sizeof(p));
dfs(0);
for(int k = 1; k <= 19; k++){
    for(int i = 0; i < n; i++){
        if(p[i][k-1] != -1) p[i][k] = p[p[i][k-1]][k-1];
    }
}

```

```
}
```

2.12.3 Lowest Common Ancestor

```
int lca(int x, int y){
    if(dep[x] < dep[y]) swap(x, y);
    for(int k = 19; k >= 0; k--){
        if(p[x][k] != -1 && dep[p[x][k]] >= dep[y]) x = p[x][k];
    }
    if(x == y) return x;
    for(int k = 19; k >= 0; k--){
        if(p[x][k] != p[y][k]){
            x = p[x][k];
            y = p[y][k];
        }
    }
    return p[x][0];
}
```

2.12.4 All Pairs Shortest Path

```
int distance(int x, int y){
    return dist[x]+dist[y]-2*dist[lca(x, y)];
}
```

2.12.5 Preorder

```
// UNTESTED
void dfs(int x, int par){
    c++;
    pre[x] = c;
    for(auto it:adj[x]){
        if(it != par) dfs(adj[it], x);
    }
}
```

2.12.6 Postorder

```
// UNTESTED
void dfs(int x, int par){
    c++;
    for(auto it:adj[x]){
        if(it != par) dfs(adj[it], x);
    }
    post[x] = c;
}
```

2.12.7 Subtree to Range

```
int dfs(int x, int par){
    c++;
    pre[x] = c;
    for(auto it:adj[x]){
        if(it != par) rig[pre[x]] = max(rig[pre[x]], dfs(it, x));
    }
    if(rig[pre[x]] == 0) rig[pre[x]] = pre[x];
    return rig[pre[x]];
}
// node -> pre[x]
// children -> pre[x]+1, rig[pre[x]]
```

2.12.8 Leaf Pruning

```
for(int i = 1; i <= n; i++){
    if(adj[i].size() == 1) leafs.push(i);
}
while(!leafs.empty()){
    u = leafs.front(); leafs.pop();
    t = adj[u][0];
    adj[t].erase(find(adj[t].begin(), adj[t].end(), u));
    if(adj[t].size() == 1) leafs.push(t);
    adj[u].erase(find(adj[u].begin(), adj[u].end(), t));
}
```

2.12.9 Weighted Maximum Independent Set

```
int mis(int v, bool take, int p){
    if(dp[v][take] != -1) return dp[v][take];
    int ans = take*c[v];
    for(auto it:adj[v]){
        if(it == p) continue;
        int temp = mis(it, 0, v);
        if(!take) temp = max(temp, mis(it, 1, v));
        ans += temp;
    }
    return dp[v][take] = ans;
}

void ans(int v, bool take, int p){
    for(auto it:adj[v]){
        if(it == p) continue;
        int temp0 = dp[it][0], temp1 = (take ? -1 : dp[it][1]);
        if(temp0 > temp1) ans(it, 0, v);
        else { a.push_back(it); ans(it, 1, v); }
    }
}

mis(0, 0, -1);
mis(0, 1, -1);
if(dp[0][1] > dp[0][0]){ a.push_back(0); ans(0, 1, -1); }
else ans(0, 0, -1);
```

2.12.10 Heavy-Light Decomposition

```
int dfs(int node){
    int size = 1, max_c = 0;
    for(auto it:adj[node]){
        if(it.s != par[node]){
            par[it.s] = node; dep[it.s] = dep[node]+1;
            int c_size = dfs(it.s);
            size += c_size;
            if(c_size > max_c){ max_c = c_size; heav[node] = it.s; }
        }
    }
    return size;
}

void decomp(int node, int hea){
    head[node] = hea; pos[node] = c_pos++;
    if(heav[node] != -1) decomp(heav[node], hea);
    for(auto it:adj[node]){
        if(it.s == par[node]) continue;
        if(it.s != heav[node]) decomp(it.s, it.s);
    }
}
```

```

        root->update(pos[it.s], it.f);
    }
}
int query(int a, int b){
    int res = 0;
    for(; head[a] != head[b]; b = par[head[b]]){
        if(dep[head[a]] > dep[head[b]]) swap(a, b);
        res = max(res, root->query(pos[head[b]], pos[b]));
    }
    if(dep[a] > dep[b]) swap(a, b);
    res = max(res, root->query(pos[a]+1, pos[b]));
    return res;
}
dfs(0);
decomp(0, 0);

```

2.12.11 Centroid Decomposition

Decompose Tree into Centroid Tree
 where the node is central
 Use them to speed queries up

3 Dynamic Programming

3.1 Coin Change

```

dp[0] = 0;
for(int i = 1; i <= v; i++){
    dp[i] = INT_MAX;
    for(int j = 0; j < n; j++){
        if(i >= c[j]) dp[i] = min(dp[i], dp[i-c[j]]+1);
    }
}

```

3.2 Coin Combinations

```

ways[0] = 1;
for(int i = 0; i < c; i++){
    for(int j = 1; j <= v; j++){
        if(j >= coins[i]) ways[j] += ways[j-coins[i]];
    }
}

```

3.3 Knapsack

3.3.1 0-1

```

for(int i = 0; i < n; i++){
    for(int j = s; j >= w[i]; j--){
        dp[j] = max(dp[j], dp[j-w[i]]+v[i]);
    }
}

```

3.3.2 0-K

```

//further speedup:
//take top s/w most valued items
//for every possible item
//not just multiple copies of one item

```

```

for(int i = 0; i < n; i++){
    cin >> v >> w >> k;
    k = min(k, s/w);
    c = 1;
    while(true){
        if(k < c) break;
        items.push_back(pi(v*c, w*c));
        k -= c;
        c *= 2;
    }
    if(k != 0) items.push_back(pi(v*k, w*k));
}
for(auto it : items){
    for(int i = s; i >= it.second; i--){
        dp[i] = max(dp[i], dp[i-it.second]+it.first);
    }
}

```

3.4 Longest Increasing Subsequence

3.4.1 N^2

```

for(int i = 0; i < n; i++){
    for(int j = 0; j < i; j++){
        if(a[j] < a[i]) lis[i] = max(lis[i], lis[j]);
    }
    lis[i]++;
    ans = max(ans, lis[i]);
}

```

3.4.2 $N \log N$

```

for(int i = 0; i < n; i++){
    t = query(a[i]-1)+1;
    update(a[i], t);
    ans = max(ans, t);
}

```

3.4.3 Optimal

```

for(int i = 0; i < n; i++){
    int p = lower_bound(dp, dp+l, a[i])-dp;
    dp[p] = a[i];
    l = max(p+1, l);
}

```

3.5 Longest Common Subsequence

3.5.1 N^2

```

int lcs(int al, int bl){
    if(al == 0 || bl == 0) return 0;
    if(dp[al][bl] != -1) return dp[al][bl];
    dp[al][bl] = max(lcs(al-1, bl), lcs(al, bl-1));
    if(a[al-1] == b[bl-1]) dp[al][bl] = max(dp[al][bl], lcs(al-1, bl-1)+1);
    return dp[al][bl];
}

```

3.5.2 Longest Increasing Subsequence

```

for(int i = 0; i < n; i++){ cin >> a[i].first; a[i].second = i+1; }
for(int i = 0; i < m; i++) cin >> b[i];
sort(a, a+n);
for(int i = 0; i < m; i++){
    p = lower_bound(a, a+n, pi(b[i], 0));
    if(p != a+n) c.push_back(p->second);
}
// Perform LIS on c

```

3.6 Digits

```

long long derp(int idx, int prev, int same, int allzero){
    if(idx == num.size()) return dp[idx][prev][same][allzero] = !allzero;
    if(dp[idx][prev][same][allzero] != -1) return dp[idx][prev][same][allzero];
    long long sum = 0, limit;
    if((!allzero && same) || (allzero && idx == 0)) limit = num[idx];
    else limit = 9;
    for(int i = 0; i <= limit; i++){
        if(i == 4) continue;
        if(allzero){
            if(i == 0) sum += derp(idx+1, 10, 1, 1);
            else sum += derp(idx+1, i, (idx == 0 && i == limit), 0);
        } else if(!(i == 3 && prev == 1)){
            if(same && i == num[idx]) sum += derp(idx+1, i, 1, 0);
            else sum += derp(idx+1, i, 0, 0);
        }
    }
    return dp[idx][prev][same][allzero] = sum;
}

void dcmp(long long x){
    num.clear();
    while(x > 0){ num.push_back(x%10); x /= 10; }
    reverse(num.begin(), num.end());
}

long long solve(long long x){
    if(memo.count(x) != 0) return memo[x];
    memset(dp, -1, sizeof(dp));
    dcmp(x);
    return memo[x] = derp(0, 10, 1, 1);
}

```

3.7 Convex Hull Speedup

```

// dp(x) = max(dp(i)+f(p(x)-p(i)))
//         = max(dp(i)+a(p(x)-p(i))^2+b(p(x)-p(i))+c)
//         = max(dp(i)+ap(x)^2-2ap(x)p(i)+ap(i)^2+bp(x)-bp(i))+c
//         = max(dp(i)+ap(i)^2-bp(i)-2ap(x)p(i))+ap(x)^2+bp(x)+c
//         = max(c(i)+m(i)p(x))+v(x)
// c(i) = dp(i)+ap(i)^2-bp(i)
// m(i) = -2ap(i)
// v(x) = ap(x)^2+bp(x)+c
long long func(pi line, long long x){
    return line.first*x+line.second;
}

long double intersection(long long m1, long long c1, long long m2, long long c2){
    return (long double)(c2-c1)/(m1-m2);
}

long double intersect(pi x, pi y){
    return intersection(x.first, x.second, y.first, y.second);
}

```

```

}
long long query(long long x){
    while(hull.size() > 1){
        if(func(hull[0], x) < func(hull[1], x)){
            hull.pop_front();
        } else break;
    }
    return func(hull[0], x);
}
void insert(long long m, long long c){
    pi line = pi(m, c);
    while(hull.size() > 1){
        long long s = hull.size();
        if(intersect(hull[s-1], line) <= intersect(hull[s-2], line)){
            hull.pop_back();
        } else break;
    }
    hull.push_back(line);
}
insert(0, 0);
for(int i = 1; i <= n; i++){
    dp[i] = query(ps[i])+a*ps[i]*ps[i]+b*ps[i]+c;
    insert(-2*a*ps[i], dp[i]+a*ps[i]*ps[i]-b*ps[i]);
}

```

3.8 Divide and Conquer

```

long long cost(int s, int e){
    return (ps[e]-ps[s-1])*(e-s+1);
}
void dnc(int s, int e, long long x, int y, int k){
    if(s > e) return;
    int m = (s+e)/2, best = 0;
    dp[m][k] = LLONG_MAX/2;
    for(int i = x; (i <= y && i <= m); i++){
        if(dp[m][k] > dp[i][!k]+cost(i+1, m)){
            dp[m][k] = dp[i][!k]+cost(i+1, m);
            best = i;
        }
    }
    if(s < m) dnc(s, m-1, x, best, k);
    if(m < e) dnc(m+1, e, best, y, k);
}
for(int i = 1; i <= n; i++) dp[i][0] = LLONG_MAX/2;
for(int i = 1; i <= g; i++){
    for(int j = 1; j <= n; j++) dp[j][i%2] = LLONG_MAX/2;
    dnc(0, n, 0, n, i%2);
}

```

3.9 Prefix Sums

3.9.1 1D

```

int query(int s, int e){
    return ps[e]-ps[s-1];
}

```

```

for(int i = 1; i <= n; i++) ps[i] = ps[i-1]+a[i];

```

3.9.2 2D

```

int query(int x1, int y1, int x2, int y2){
    return ps[x2][y2]-ps[x1-1][y2]-ps[x2][y1-1]+ps[x1-1][y1-1];
}

for(int i = 1; i <= r; i++){
    for(int j = 1; j <= c; j++){
        ps[i][j] = ps[i-1][j]+ps[i][j-1]-ps[i-1][j-1]+a[i][j];
    }
}

```

4 Math

4.1 Greatest Common Divisor

```

// Alternatively, find highest common powers for each factor
int gcd(int a, int b){
    if(b == 0) return a;
    return gcd(b, a%b);
}

```

4.2 Lowest Common Multiple

```

// Alternatively, find highest powers for each factor
int lcm(int a, int b){
    return (a*b)/gcd(a, b);
}

```

4.3 Modular Functions

4.3.1 Multiplication

```

int mulmod(int a, int b, int m) {
    int res = 0;
    while(b > 0) {
        if(b % 2 == 1) res = (res+a)%m;
        a = (a*2)%m;
        b /= 2;
    }
    return res % m;
}

```

4.3.2 Exponentiation

```

int powmod(int a, int b, int m) {
    int res = 1;
    while(b > 0) {
        if(b % 2 == 1) res = mulmod(res, a, m);
        a = mulmod(a, a, m);
        b /= 2;
    }
    return res % m;
}

```

4.4 Primes

4.4.1 Sieve of Eratosthenes

```

memset(prime, 1, sizeof(prime));
prime[0] = prime[1] = 0;
for(int i = 2; i <= 1000000; i++){
    if(prime[i]){

```



```

        for(int j = 2; i*j <= 1000000; j++){
            prime[i*j] = 0;
        }
    }
}

```

4.4.2 Prime Factorisation

```

while(x % 2 == 0){ cnt[2]++; x /= 2; }
for(int i = 3; i*i <= x+1; i += 2){
    while(x % i == 0){ cnt[i]++; x /= i; }
    if(x == 1) break;
}
if(x > 1) cnt[x]++;

```

4.5 Fibonacci

```

typedef pair<pi, pi> matrix;
matrix multiply(matrix x, matrix y, long long z){
    return matrix(
        pi((x.f.f*y.f.f+x.f.s*y.s.f)%z,
            (x.f.f*y.f.s+x.f.s*y.s.s)%z),
        pi((x.s.f*y.f.f+x.s.s*y.s.f)%z,
            (x.s.f*y.f.s+x.s.s*y.s.s)%z));
}
matrix square(matrix x, long long y){
    return multiply(x, x, y);
}
matrix power(matrix x, long long y, long long z){
    if(y == 1) return x;
    if(y % 2 == 0) return square(power(x, y/2, z), z);
    return multiply(x, square(power(x, y/2, z), z), z);
}
long long fibo(long long n, long long m){
    matrix x = matrix(pi(1, 1), pi(1, 0));
    return power(x, n, m).f.s;
}

```

4.6 nC_k

```

if(k > n-k) k = n-k;
for(int i = 0; i < k; i++){
    ans *= (n-i);
    ans /= (i+1);
}

```

5 Algorithms

5.1 Discretisation

```

for(int i = 0; i < n; i++){
    cin >> a[i];
    b[i] = a[i];
}
sort(b, b+n);
for(int i = 0; i < n; i++){
    d = lower_bound(b, b+n, a[i]) - b;
    a[i] = d+1;
}

```

5.2 Binary Search

```
while(mini < maxi){
    medi = mini+(maxi-mini)/2;
    if(can(medi)) maxi = medi;
    else mini = medi+1;
}
```

5.3 Mo's Algorithm

```
//queries : index, left, right
//answers : index, answer

bool cmp(pii x, pii y){
    if(x.second.first/blk != y.second.first/blk){
        return x.second.first/blk < y.second.first/blk;
    }
    if(x.second.first/blk & 1){
        return x.second.second < y.second.second;
    }
    return x.second.second > y.second.second;
}

blk = sqrt(n);
sort(qs, qs+q, cmp);
for(int i = 0; i < q; i++){
    l = qs[i].second.first; r = qs[i].second.second;
    while(lft > l){
        //remove a[lft-1]
        lft--;
    }
    while(rgt <= r){
        //add a[rgt]
        rgt++;
    }
    while(lft < l){
        //add a[lft]
        lft++;
    }
    while(rgt > r+1){
        //remove a[rgt-1]
        rgt--;
    }
    ans[i] = pi(qs[i].first, cur);
}
sort(ans, ans+q);
```

6 Miscellaneous

6.1 Macros + Functions + Variables

```
#define f first
#define s second
#define pb push_back
#define ins insert
int ls(int x){ return (x)&(-x); }
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
// 4 Directions
int dx[]={0, 0, -1, 1};
```

```

int dy[]={-1, 1, 0, 0};
// 8 Directions
int dx[]={0, 0, -1, 1, -1, 1, -1, 1};
int dy[]={-1, 1, -1, 1, 0, 0, 1, -1};
// Knight Moves
int dx[]={-1, -2, 1, 2, 2, 1, -2, 1};
int dy[]={-2, -1, -2, -1, 1, 2, 1, 2};

```

6.2 Compile Commands

6.2.1 Compile

```
g++ -c "%f" -std=c++11
```

6.2.2 Build

```
g++ -o "%e" "%f" -std=c++11
```

6.2.3 Command Line

```
g++ "file.cpp" -o "file" -std=c++11
```

6.2.4 Simple Script

```

int main(int argc, char **argv){
    system(g++ -o (argv[1]) (argv[1]).cpp -std=c++11);
}

```

6.3 Input/Output

6.3.1 Fast

```

ios_base::sync_with_stdio(false);
cin.tie(0);

```

6.3.2 Faster

```

inline int read_int() {
    int x = 0;
    char ch = getchar_unlocked();
    while (ch < '0' || ch > '9') ch = getchar_unlocked();
    while (ch >= '0' && ch <= '9'){
        x = (x << 3) + (x << 1) + ch - '0';
        ch = getchar_unlocked();
    }
    return x;
}

```

6.4 Pruning

```

auto start = chrono::high_resolution_clock::now();
auto end = chrono::high_resolution_clock::now();
auto elapse = chrono::duration<double>(end-start);
if(elapse.count() > 2.9) break;

```

6.5 Optimise

```
int __attribute__((optimize("Ofast"), target("arch=sandybridge"))) f(){}

```