

noiref

ngmh

December 2019

Contents

1	Data Structures	3
1.1	Fenwick Trees	3
1.1.1	Point Update, Range Query	3
1.1.2	Range Update, Point Query	3
1.1.3	Range Update, Range Query	3
1.2	Segment Trees	4
1.2.1	1D	4
1.2.2	Lazy Propagation	4
1.2.3	2D	5
1.3	Sparse Table	5
2	Graph Theory	6
2.1	Depth First Search	6
2.2	Breadth First Search	6
2.3	Floyd-Warshall	6
2.4	Dijkstra	7
2.5	Travelling Salesman Problem	7
2.6	Union Find Disjoint Subset	7
2.7	Minimum Spanning Tree	8
2.7.1	Kruskal	8
2.7.2	Prim's	8
2.8	Bipartite Matching	8
2.9	Articulation Points	9
2.10	Bridges	9
2.11	Strongly Connected Components	9
2.12	Trees	10
2.12.1	Diameter	10
2.12.2	2^K Decomposition	11
2.12.3	Lowest Common Ancestor	11
2.12.4	All Pairs Shortest Path	11
2.12.5	Preorder	11
2.12.6	Postorder	12
2.12.7	Subtree to Range	12
2.12.8	Leaf Pruning	12
2.12.9	Weighted Maximum Independent Set	12
2.12.10	Heavy-Light Decomposition	13
2.12.11	Centroid Decomposition	13
3	Dynamic Programming	14
3.1	Coin Change	14
3.2	Coin Combinations	14
3.3	Knapsack	14
3.3.1	0-1	14
3.3.2	0-K	14
3.4	Longest Increasing Subsequence	15

3.4.1	N^2	15
3.4.2	$N \log N$	15
3.4.3	Optimal	15
3.5	Longest Common Subsequence	15
3.5.1	N^2	15
3.5.2	Longest Increasing Subsequence	16
3.6	Digits	16
3.7	Convex Hull Speedup	16
3.8	Divide and Conquer	17
3.9	Prefix Sums	18
3.9.1	1D	18
3.9.2	2D	18
4	Math	18
4.1	Greatest Common Divisor	18
4.2	Lowest Common Multiple	18
4.3	Modular Functions	18
4.3.1	Multiplication	18
4.3.2	Exponentiation	19
4.4	Primes	19
4.4.1	Sieve of Eratosthenes	19
4.4.2	Prime Factorisation	19
4.5	Fibonacci	19
4.6	nC_k	20
5	Algorithms	20
5.1	Discretisation	20
5.2	Binary Search	20
5.3	Mo's Algorithm	20
6	Miscellaneous	21
6.1	Macros + Functions + Variables	21
6.2	Compile Commands	21
6.2.1	Compile	21
6.2.2	Build	21
6.2.3	Command Line	21
6.2.4	Simple Script	22
6.3	Input/Output	22
6.3.1	Fast	22
6.3.2	Faster	22
6.4	Pruning	22
6.5	Optimise	22

1 Data Structures

Data Structure	Update	Query	Memory	Notes
Prefix Sum	X	$O(1)$	$O(N)$	Associative Functions (+, XOR)
Fenwick Tree	$O(\log N)$	$O(\log N)$	$O(N)$	Low Memory
Segment Tree	$O(\log N)$	$O(\log N)$	$O(4N)$	Can store more information
Sparse Table	X	$O(1)$	$O(N \log N)$	Non-Associative Functions (max, gcd)

Table 1: Quick Summary of Data Structures

1.1 Fenwick Trees

Fenwick Trees are a very useful data structure for prefix sums. They are able to perform point or range queries and updates. One cool use case is for range maximum, but only when updates are strictly non-decreasing.

Query: $O(\log N)$ Update: $O(\log N)$

1.1.1 Point Update, Range Query

```
1 void pu(int i, int v){
2     for(; i <= n; i += ls(i)) fw[i] += v;
3 }
4 int pq(int i){
5     int t = 0;
6     for(; i; i -= ls(i)) t += fw[i];
7     return t;
8 }
9 int rq(int s, int e){
10    return pq(e)-pq(s-1);
11 }
```

1.1.2 Range Update, Point Query

```
1 void ru(int s, int e, int v){
2     pu(s, v);
3     pu(e+1, -v);
4 }
```

1.1.3 Range Update, Range Query

```
1 void ru(int s, int e, int v){
2     pu(fw1, s, v);
3     pu(fw1, e+1, -v);
4     pu(fw2, s, -v*(s-1));
5     pu(fw2, e+1, v*e);
6 }
7 int ps(int i){
8     return pq(fw1, i)*i+pq(fw2, i);
9 }
10 int rq(int s, int e){
11    return ps(e)-ps(s-1);
12 }
```

1.2 Segment Trees

Segment Trees are a very useful data structure for range queries. These queries can be on anything really, one use case is for finding the Kth largest element.

Query: $O(\log N)$ Update: $O(\log N)$

1.2.1 1D

```
1 struct node {
2     int s, e, m, v;
3     node *l, *r;
4     node(int _s, int _e){
5         s = _s; e = _e; m = (s+e)/2; v = 0;
6         if(s != e){
7             l = new node(s, m);
8             r = new node(m+1, e);
9         }
10    }
11    void pu(int x, int y){
12        if(s == e){ v = y; return; }
13        if(x <= m) l->pu(x, y);
14        if(x > m) r->pu(x, y);
15        v = min(l->v, r->v);
16    }
17    int rq(int x, int y){
18        if(s == x && e == y) return v;
19        if(y <= m) return l->rq(x, y);
20        if(x > m) return r->rq(x, y);
21        return min(l->rq(x, m), r->rq(m+1, y));
22    }
23 } *root;
```

1.2.2 Lazy Propagation

```
1 int pu(){
2     if(s == e){ v += lazy; lazy = 0; return v; }
3     v += lazy;
4     l->lazy += lazy; r->lazy += lazy;
5     lazy = 0;
6     return v;
7 }
8
9 void ru(int x, int y, int z){
10    if(s == x && e == y){ lazy += z; return; }
11    if(y <= m) l->ru(x, y, z);
12    else if(x > m) r->ru(x, y, z);
13    else l->ru(x, m, z), r->ru(m+1, y, z);
14    v = max(l->pu(), r->pu());
15 }
16
17 int rq(int x, int y){
18    pu();
19    if(s == x && e == y) return pu();
20    if(y <= m) return l->rq(x, y);
21    if(x > m) return r->rq(x, y);
22    return max(l->rq(x, m), r->rq(m+1, y));
23 }
```

1.2.3 2D

```
1 struct node2D {
2     int s, e, m;
3     node1D *maxi;
4     node2D *l, *r;
5     node2D(int a, int b, int c, int d){
6         s = a; e = b; m = (s+e)/2;
7         maxi = new node1D(c, d);
8         if(s != e){
9             l = new node2D(s, m, c, d);
10            r = new node2D(m+1, e, c, d);
11        }
12    }
13    void pu(int a, int b, int v){
14        if(s == e){ maxi->pu(b, v); return; }
15        if(a <= m) l->pu(a, b, v);
16        else r->pu(a, b, v);
17        maxi->pu(b, max(l->maxi->rq(b, b), r->maxi->rq(b, b)));
18    }
19    int rq(int a, int b, int c, int d){
20        if(s == a && e == b) return maxi->rq(c, d);
21        if(b <= m) return l->rq(a, b, c, d);
22        if(a > m) return r->rq(a, b, c, d);
23        return max(l->rq(a, m, c, d), r->rq(m+1, b, c, d));
24    }
25 } *root;
```

1.3 Sparse Table

Sparse Tables may not seem so useful at first, but they are just similar to Prefix Sums. The exception is that they can be used on non-Associative functions like max and gcd, which does not work with prefix sums.

Query: $O(1)$ Update: X

```
1 int query(int l, int r){
2     r++;
3     int p = 31-__builtin_clz(r-l);
4     return __gcd(sp[p][l], sp[p][r-(1<<p)]);
5 }
6
7 h = floor(log2(n));
8 for(int i = 0; i < n; i++) sp[0][i] = a[i];
9 for(int i = 1; i <= h; i++){
10     for(int j = 0; j+(1<<i) <= n; j++){
11         sp[i][j] = __gcd(sp[i-1][j], sp[i-1][j+(1<<(i-1))]);
12     }
13 }
```

2 Graph Theory

Graph Algorithm	Complexity	Notes
DFS	$O(N)$	Connectedness
BFS	$O(N)$	Unweighted Shortest Path
Floyd-Warshall	$O(N^3)$	All Pairs Shortest Path
Dijkstra	$O(E \log E)$	Single Source Shortest Path
TSP	$O(2^N)$	Visiting All Nodes
UFDS	$O(1)$	Amortized
MST - Kruskal	$O(E)$	Greedy
MST - Prim's	$O(E \log E)$	Dijkstra
Bipartite Matching	?	2 Sets of Nodes
Articulation Points	?	Node Splits Graph
Bridges	?	Edge Splits Graph
SCC	?	Cycles

Table 2: Quick Summary of General Graph Algorithms

2.1 Depth First Search

```
1 void dfs(int x, int p){
2     for(auto it : adj[x]){
3         if(it != p){
4             par[it] = x;
5             dep[it] = dep[x]+1;
6             dist[it] = dist[x]+1;
7             dfs(it, x);
8         }
9     }
10 }
```

2.2 Breadth First Search

```
1 d[nx][ny] = 0;
2 q.push(pi(sx, sy));
3 while(!q.empty()){
4     pi f = q.front(); q.pop();
5     for(int i = 0; i < 4; i++){
6         nx = f.first+dx[i];
7         ny = f.second+dy[i];
8         if(nx < 0 || ny < 0 || nx >= h || ny >= w) continue;
9         if(d[nx][ny] != -1) continue;
10        d[nx][ny] = d[f.first][f.second]+1;
11        q.push(pi(nx, ny));
12    }
13 }
```

2.3 Floyd-Warshall

```
1 for(int i = 0; i < n; i++){
2     for(int j = 0; j < n; j++){
3         if(i == j) adj[i][j] = 0;
4         else adj[i][j] = INT_MAX;
5     }
6 }
```

```

6 }
7 for(int k = 0; k < n; k++){
8     for(int i = 0; i < n; i++){
9         for(int j = 0; j < n; j++){
10             adj[i][j] = min(adj[i][j], adj[i][k]+adj[k][j]);
11         }
12     }
13 }

```

2.4 Dijkstra

```

1 priority_queue<pi, vector<pi>, greater<pi> > pq;
2 dist[s] = 0;
3 pq.push(pi(0, s));
4 while(!pq.empty()){
5     pi f = pq.top(); pq.pop();
6     for(auto it:adj[f.second]){
7         if(dist[it.first] == -1 || dist[it.first] > f.first+it.second){
8             dist[it.first] = f.first+it.second;
9             pq.push(pi(dist[it.first], it.first));
10        }
11    }
12 }

```

2.5 Travelling Salesman Problem

```

1 long long adj[14][14], dp[8200][14];
2
3 //start with 1, 0
4 //mask is 0 visited, at node 0
5 long long tsp(long long mask, long long pos){
6     if(mask == visited) return adj[pos][0];
7     if(dp[mask][pos] != -1) return dp[mask][pos];
8     long long ans = LLONG_MAX;
9     for(int i = 0; i < m; i++){
10        if((mask&(1<<i)) == 0){
11            long long newans = adj[pos][i]+tsp(mask|(1<<i), i);
12            ans = min(ans, newans);
13        }
14    }
15    return dp[mask][pos] = ans;
16 }
17
18
19 visited = (1 << m)-1;
20 res = tsp(1, 0);
21 if(res < 0) cout << "-1";
22 else cout << res;

```

2.6 Union Find Disjoint Subset

```

1 int root(int x){
2     if(p[x] == -1) return x;
3     return p[x] = root(p[x]);
4 }

```

```

5 void connect(int x, int y){
6     p[root(x)] = root(y);
7 }

```

2.7 Minimum Spanning Tree

2.7.1 Kruskal

```

1 sort(edges.begin(), edges.end());
2 for(auto it:edges){
3     if(root(it.second.first) != root(it.second.second)){
4         connect(it.second.first, it.second.second);
5         cost += it.first;
6     }
7 }

```

2.7.2 Prim's

```

1 priority_queue<pi, vector<pi>, greater<pi> > pq;
2 dist[s] = 0;
3 pq.push(pi(0, s));
4 while(!pq.empty()){
5     pi f = pq.top(); pq.pop();
6     for(auto it:adj[f.second]){
7         if(dist[it.first] == -1 || dist[it.first] > max(f.first, it.second)){
8             dist[it.first] = max(f.first, it.second);
9             pq.push(pi(dist[it.first], it.first));
10        }
11    }
12 }

```

2.8 Bipartite Matching

```

1 bool dfs(int u){
2     if(v[u]) return 0;
3     v[u] = 1;
4     for(auto v:adj[u]){
5         if(match[v] == -1 || dfs(match[v])){
6             match[v] = u;
7             match[u] = v;
8             return 1;
9         }
10    }
11    return 0;
12 }
13 memset(match, -1, sizeof(match));
14 for(auto lit:ho){
15     for(auto rit:adj[lit]){
16         if(match[rit] == -1){
17             match[rit] = lit;
18             match[lit] = rit;
19             mcbm++;
20             break;
21         }
22    }

```



```

23 }
24 for(auto lit:ho){
25     if(match[lit] == -1){
26         memset(v, 0, sizeof(v));
27         mcbm += dfs(lit);
28     }
29 }
30 mis = n-mcbm;

```

2.9 Articulation Points

```

1 void atp(int node, int depth){
2     vi[node] = 1;
3     dep[node] = depth;
4     low[node] = depth;
5     for(auto it:adj[node]){
6         if(!vi[it]){
7             par[it] = node;
8             atp(it, depth+1);
9             chi[node]++;
10            if(low[it] >= dep[node]) atps[node]++;
11            low[node] = min(low[node], low[it]);
12        } else if(it != par[node]){
13            low[node] = min(low[node], dep[it]);
14        }
15    }
16 }
17 atp(0, 0);
18 // root -> chi[i]
19 // other -> atps[i]+1

```

2.10 Bridges

```

1 void bridges(int x, int par){
2     if(dep[x] != -1) return;
3     dep[x] = low[x] = co++;
4     int t = 0;
5     for(auto it:adj[x]){
6         if(it == par && t == 0){ t++; continue; }
7         if(dep[it] != -1){
8             if(low[it] > dep[x]) bgs.push_back(pi(x, it));
9             low[x] = min(low[x], low[it]);
10            continue;
11        }
12        bridges(it, x);
13        if(low[it] > dep[x]) bgs.push_back(pi(x, it));
14        low[x] = min(low[x], low[it]);
15    }
16 }
17 for(int i = 1; i <= n; i++) bridges(i, 0);

```

2.11 Strongly Connected Components

```

1 stack<int> s;
2 vector<int> cur, adj[100001];

```

```

3  set<int> adjsc[100001];
4  vector<vector<int> > comps;
5  void scc(int v){
6      idxs[v] = idx;
7      lowlink[v] = idx;
8      idx++;
9      s.push(v);
10     ins[v] = 1;
11     for(auto w:adj[v]){
12         if(idxs[w] == -1){
13             scc(w);
14             lowlink[v] = min(lowlink[v], lowlink[w]);
15         } else if(ins[w]){
16             lowlink[v] = min(lowlink[v], idxs[w]);
17         }
18     }
19     if(lowlink[v] == idxs[v]){
20         cur.clear();
21         w = 0;
22         while(w != v){
23             w = s.top(); s.pop();
24             ins[w] = 0;
25             cur.push_back(w);
26         }
27         comps.push_back(cur);
28     }
29 }
30 idx = 1;
31 memset(idxs, -1, sizeof(idxs));
32 for(int i = 1; i <= n; i++){
33     if(idxs[i] == -1) scc(i);
34 }
35 memset(com, -1, sizeof(com));
36 for(int i = 0; i < comps.size(); i++){
37     for(auto it:comps[i]) com[it] = i;
38 }
39 for(int i = 1; i <= n; i++){
40     for(auto it:adj[i]){
41         if(com[i] != com[it]) adjsc[com[i]].insert(com[it]);
42     }
43 }

```

2.12 Trees

2.12.1 Diameter

```

1  pi dfs(int node, int par, int dist){
2      pi b = pi(node, dist);
3      for(auto it:adj[node]){
4          if(it.first != par){
5              pi c = dfs(it.first, node, dist+it.second);
6              if(c.second > b.second) b = c;
7          }
8      }
9      return b;
10 }
11 f = dfs(0, -1, 0);
12 l = dfs(f.first, -1, 0);

```

```
13 // 1.second
```

2.12.2 2^K Decomposition

```
1 int par(int x, int k){
2     for(int i = 19; i >= 0; i--){
3         if(k >= (1<<i)){
4             if(x == -1) return x;
5             x = p[x][i];
6             k -= (1<<i);
7         }
8     }
9     return x;
10 }
11
12 memset(p, -1, sizeof(p));
13 dfs(0);
14 for(int k = 1; k <= 19; k++){
15     for(int i = 0; i < n; i++){
16         if(p[i][k-1] != -1) p[i][k] = p[p[i][k-1]][k-1];
17     }
18 }
```

2.12.3 Lowest Common Ancestor

```
1 int lca(int x, int y){
2     if(dep[x] < dep[y]) swap(x, y);
3     for(int k = 19; k >= 0; k--){
4         if(p[x][k] != -1 && dep[p[x][k]] >= dep[y]) x = p[x][k];
5     }
6     if(x == y) return x;
7     for(int k = 19; k >= 0; k--){
8         if(p[x][k] != p[y][k]){
9             x = p[x][k];
10            y = p[y][k];
11        }
12    }
13    return p[x][0];
14 }
```

2.12.4 All Pairs Shortest Path

```
1 int distance(int x, int y){
2     return dist[x]+dist[y]-2*dist[lca(x, y)];
3 }
```

2.12.5 Preorder

```
1 // UNTESTED
2 void dfs(int x, int par){
3     c++;
4     pre[x] = c;
5     for(auto it:adj[x]){
6         if(it != par) dfs(adj[it], x);
7     }
8 }
```

```

7     }
8 }

```

2.12.6 Postorder

```

1 // UNTESTED
2 void dfs(int x, int par){
3     c++;
4     for(auto it:adj[x]){
5         if(it != par) dfs(adj[it], x);
6     }
7     post[x] = c;
8 }

```

2.12.7 Subtree to Range

```

1 int dfs(int x, int par){
2     c++;
3     pre[x] = c;
4     for(auto it:adj[x]){
5         if(it != par) rig[pre[x]] = max(rig[pre[x]], dfs(it, x));
6     }
7     if(rig[pre[x]] == 0) rig[pre[x]] = pre[x];
8     return rig[pre[x]];
9 }
10 // node -> pre[x]
11 // children -> pre[x]+1, rig[pre[x]]

```

2.12.8 Leaf Pruning

```

1 for(int i = 1; i <= n; i++){
2     if(adj[i].size() == 1) leafs.push(i);
3 }
4 while(!leafs.empty()){
5     u = leafs.front(); leafs.pop();
6     t = adj[u][0];
7     adj[t].erase(find(adj[t].begin(), adj[t].end(), u));
8     if(adj[t].size() == 1) leafs.push(t);
9     adj[u].erase(find(adj[u].begin(), adj[u].end(), t));
10 }

```

2.12.9 Weighted Maximum Independent Set

```

1 int mis(int v, bool take, int p){
2     if(dp[v][take] != -1) return dp[v][take];
3     int ans = take*c[v];
4     for(auto it:adj[v]){
5         if(it == p) continue;
6         int temp = mis(it, 0, v);
7         if(!take) temp = max(temp, mis(it, 1, v));
8         ans += temp;
9     }
10     return dp[v][take] = ans;
11 }

```

```

12 void ans(int v, bool take, int p){
13     for(auto it:adj[v]){
14         if(it == p) continue;
15         int temp0 = dp[it][0], temp1 = (take ? -1 : dp[it][1]);
16         if(temp0 > temp1) ans(it, 0, v);
17         else { a.push_back(it); ans(it, 1, v); }
18     }
19 }
20 mis(0, 0, -1);
21 mis(0, 1, -1);
22 if(dp[0][1] > dp[0][0]){ a.push_back(0); ans(0, 1, -1); }
23 else ans(0, 0, -1);

```

2.12.10 Heavy-Light Decomposition

```

1 int dfs(int node){
2     int size = 1, max_c = 0;
3     for(auto it:adj[node]){
4         if(it.s != par[node]){
5             par[it.s] = node; dep[it.s] = dep[node]+1;
6             int c_size = dfs(it.s);
7             size += c_size;
8             if(c_size > max_c){ max_c = c_size; heav[node] = it.s; }
9         }
10    }
11    return size;
12 }
13 void decomp(int node, int hea){
14     head[node] = hea; pos[node] = c_pos++;
15     if(heav[node] != -1) decomp(heav[node], hea);
16     for(auto it:adj[node]){
17         if(it.s == par[node]) continue;
18         if(it.s != heav[node]) decomp(it.s, it.s);
19         root->update(pos[it.s], it.f);
20     }
21 }
22 int query(int a, int b){
23     int res = 0;
24     for(; head[a] != head[b]; b = par[head[b]]){
25         if(dep[head[a]] > dep[head[b]]) swap(a, b);
26         res = max(res, root->query(pos[head[b]], pos[b]));
27     }
28     if(dep[a] > dep[b]) swap(a, b);
29     res = max(res, root->query(pos[a]+1, pos[b]));
30     return res;
31 }
32 dfs(0);
33 decomp(0, 0);

```

2.12.11 Centroid Decomposition

- 1 Decompose Tree into Centroid Tree
- 2 where the node is central
- 3 Use them to speed queries up

3 Dynamic Programming

DP Algorithm	Complexity	Notes
Coin Change	$O(NV)$	
Coin Combinations	$O(NV)$	
Knapsack - 0-1	$O(NS)$	
Knapsack - 0-K	$O(\log_2(K)+NS)$	
LIS - Naive	$O(N^2)$	
LIS - DS / Optimal	$O(N \log N)$	
LCS	$O(N^2)$	
LCS - LIS	$O(N \log N)$	
Digits	$O(10 \cdot N)$	
Convex Hull Speedup	$O(N)$	Amortized
Divide and Conquer	$O(N \log N)$	

Table 3: Quick Summary of General Dynamic Programming Algorithms

3.1 Coin Change

```
1 dp[0] = 0;
2 for(int i = 1; i <= v; i++){
3     dp[i] = INT_MAX;
4     for(int j = 0; j < n; j++){
5         if(i >= c[j]) dp[i] = min(dp[i], dp[i-c[j]]+1);
6     }
7 }
```

3.2 Coin Combinations

```
1 ways[0] = 1;
2 for(int i = 0; i < c; i++){
3     for(int j = 1; j <= v; j++){
4         if(j >= coins[i]) ways[j] += ways[j-coins[i]];
5     }
6 }
```

3.3 Knapsack

3.3.1 0-1

```
1 for(int i = 0; i < n; i++){
2     for(int j = s; j >= w[i]; j--){
3         dp[j] = max(dp[j], dp[j-w[i]]+v[i]);
4     }
5 }
```

3.3.2 0-K

```
1 //further speedup:
2 //take top s/w most valued items
3 //for every possible item
4 //not just multiple copies of one item
5
6 for(int i = 0; i < n; i++){
```

```

7     cin >> v >> w >> k;
8     k = min(k, s/w);
9     c = 1;
10    while(true){
11        if(k < c) break;
12        items.push_back(pi(v*c, w*c));
13        k -= c;
14        c *= 2;
15    }
16    if(k != 0) items.push_back(pi(v*k, w*k));
17 }
18 for(auto it : items){
19     for(int i = s; i >= it.second; i--){
20         dp[i] = max(dp[i], dp[i-it.second]+it.first);
21     }
22 }

```

3.4 Longest Increasing Subsequence

3.4.1 N^2

```

1 for(int i = 0; i < n; i++){
2     for(int j = 0; j < i; j++){
3         if(a[j] < a[i]) lis[i] = max(lis[i], lis[j]);
4     }
5     lis[i]++;
6     ans = max(ans, lis[i]);
7 }

```

3.4.2 $N \log N$

```

1 for(int i = 0; i < n; i++){
2     t = query(a[i]-1)+1;
3     update(a[i], t);
4     ans = max(ans, t);
5 }

```

3.4.3 Optimal

```

1 for(int i = 0; i < n; i++){
2     int p = lower_bound(dp, dp+1, a[i])-dp;
3     dp[p] = a[i];
4     l = max(p+1, l);
5 }

```

3.5 Longest Common Subsequence

3.5.1 N^2

```

1 int lcs(int a1, int b1){
2     if(a1 == 0 || b1 == 0) return 0;
3     if(dp[a1][b1] != -1) return dp[a1][b1];
4     dp[a1][b1] = max(lcs(a1-1, b1), lcs(a1, b1-1));
5     if(a[a1-1] == b[b1-1]) dp[a1][b1] = max(dp[a1][b1], lcs(a1-1, b1-1)+1);
6     return dp[a1][b1];

```

```
7 }
```

3.5.2 Longest Increasing Subsequence

```
1 for(int i = 0; i < n; i++){ cin >> a[i].first; a[i].second = i+1; }
2 for(int i = 0; i < m; i++) cin >> b[i];
3 sort(a, a+n);
4 for(int i = 0; i < m; i++){
5     p = lower_bound(a, a+n, pi(b[i], 0));
6     if(p != a+n) c.push_back(p->second);
7 }
8 // Perform LIS on c
```

3.6 Digits

```
1 long long derp(int idx, int prev, int same, int allzero){
2     if(idx == num.size()) return dp[idx][prev][same][allzero] = !allzero;
3     if(dp[idx][prev][same][allzero] != -1) return dp[idx][prev][same][allzero];
4     long long sum = 0, limit;
5     if((!allzero && same) || (allzero && idx == 0)) limit = num[idx];
6     else limit = 9;
7     for(int i = 0; i <= limit; i++){
8         if(i == 4) continue;
9         if(allzero){
10             if(i == 0) sum += derp(idx+1, 10, 1, 1);
11             else sum += derp(idx+1, i, (idx == 0 && i == limit), 0);
12         } else if(!(i == 3 && prev == 1)){
13             if(same && i == num[idx]) sum += derp(idx+1, i, 1, 0);
14             else sum += derp(idx+1, i, 0, 0);
15         }
16     }
17     return dp[idx][prev][same][allzero] = sum;
18 }
19 void dcmp(long long x){
20     num.clear();
21     while(x > 0){ num.push_back(x%10); x /= 10; }
22     reverse(num.begin(), num.end());
23 }
24 long long solve(long long x){
25     if(memo.count(x) != 0) return memo[x];
26     memset(dp, -1, sizeof(dp));
27     dcmp(x);
28     return memo[x] = derp(0, 10, 1, 1);
29 }
```

3.7 Convex Hull Speedup

This speeds up any DP which is a quadratic function. A similar idea can also be done for linear functions but just using a set.

The important part is knowing how to rearrange the transition to get coefficients.

Query: $O(1)$ Update: $O(1)$

```
1 // dp(x) = max(dp(i)+f(p(x)-p(i)))
2 //         = max(dp(i)+a(p(x)-p(i))^2+b(p(x)-p(i))+c)
3 //         = max(dp(i)+ap(x)^2-2ap(x)p(i)+ap(i)^2+bp(x)-bp(i))+c
```



```

4 //      = max(dp(i)+ap(i)^2-bp(i)-2ap(x)p(i))+ap(x)^2+bp(x)+c
5 //      = max(c(i)+m(i)p(x))+v(x)
6 // c(i) = dp(i)+ap(i)^2-bp(i)
7 // m(i) = -2ap(i)
8 // v(x) = ap(x)^2+bp(x)+c
9 long long func(pi line, long long x){
10     return line.first*x+line.second;
11 }
12 long double intersection(long long m1, long long c1, long long m2, long long c2){
13     return (long double)(c2-c1)/(m1-m2);
14 }
15 long double intersect(pi x, pi y){
16     return intersection(x.first, x.second, y.first, y.second);
17 }
18 long long query(long long x){
19     while(hull.size() > 1){
20         if(func(hull[0], x) < func(hull[1], x)){
21             hull.pop_front();
22         } else break;
23     }
24     return func(hull[0], x);
25 }
26 void insert(long long m, long long c){
27     pi line = pi(m, c);
28     while(hull.size() > 1){
29         long long s = hull.size();
30         if(intersect(hull[s-1], line) <= intersect(hull[s-2], line)){
31             hull.pop_back();
32         } else break;
33     }
34     hull.push_back(line);
35 }
36 insert(0, 0);
37 for(int i = 1; i <= n; i++){
38     dp[i] = query(ps[i])+a*ps[i]*ps[i]+b*ps[i]+c;
39     insert(-2*a*ps[i], dp[i]+a*ps[i]*ps[i]-b*ps[i]);
40 }

```

3.8 Divide and Conquer

```

1 long long cost(int s, int e){
2     return (ps[e]-ps[s-1])*(e-s+1);
3 }
4 void dnc(int s, int e, long long x, int y, int k){
5     if(s > e) return;
6     int m = (s+e)/2, best = 0;
7     dp[m][k] = LLONG_MAX/2;
8     for(int i = x; (i <= y && i <= m); i++){
9         if(dp[m][k] > dp[i][!k]+cost(i+1, m)){
10             dp[m][k] = dp[i][!k]+cost(i+1, m);
11             best = i;
12         }
13     }
14     if(s < m) dnc(s, m-1, x, best, k);
15     if(m < e) dnc(m+1, e, best, y, k);
16 }
17 for(int i = 1; i <= n; i++) dp[i][0] = LLONG_MAX/2;

```

```

18 for(int i = 1; i <= g; i++){
19     for(int j = 1; j <= n; j++) dp[j][i%2] = LLONG_MAX/2;
20     dnc(0, n, 0, n, i%2);
21 }

```

3.9 Prefix Sums

3.9.1 1D

```

1 int query(int s, int e){
2     return ps[e]-ps[s-1];
3 }
4
5 for(int i = 1; i <= n; i++) ps[i] = ps[i-1]+a[i];

```

3.9.2 2D

```

1 int query(int x1, int y1, int x2, int y2){
2     return ps[x2][y2]-ps[x1-1][y2]-ps[x2][y1-1]+ps[x1-1][y1-1];
3 }
4
5 for(int i = 1; i <= r; i++){
6     for(int j = 1; j <= c; j++){
7         ps[i][j] = ps[i-1][j]+ps[i][j-1]-ps[i-1][j-1]+a[i][j];
8     }
9 }

```

4 Math

4.1 Greatest Common Divisor

```

1 // Alternatively, find highest common powers for each factor
2 int gcd(int a, int b){
3     if(b == 0) return a;
4     return gcd(b, a%b);
5 }

```

4.2 Lowest Common Multiple

```

1 // Alternatively, find highest powers for each factor
2 int lcm(int a, int b){
3     return (a*b)/gcd(a, b);
4 }

```

4.3 Modular Functions

4.3.1 Multiplication

```

1 int mulmod(int a, int b, int m) {
2     int res = 0;
3     while(b > 0) {
4         if(b % 2 == 1) res = (res+a)%m;
5         a = (a*2)%m;

```

```

6         b /= 2;
7     }
8     return res % m;
9 }

```

4.3.2 Exponentiation

```

1 int powmod(int a, int b, int m) {
2     int res = 1;
3     while(b > 0) {
4         if(b % 2 == 1) res = mulmod(res, a, m);
5         a = mulmod(a, a, m);
6         b /= 2;
7     }
8     return res % m;
9 }

```

4.4 Primes

4.4.1 Sieve of Eratosthenes

```

1 memset(prime, 1, sizeof(prime));
2 prime[0] = prime[1] = 0;
3 for(int i = 2; i <= 1000000; i++){
4     if(prime[i]){
5         for(int j = 2; i*j <= 1000000; j++){
6             prime[i*j] = 0;
7         }
8     }
9 }

```

4.4.2 Prime Factorisation

```

1 while(x % 2 == 0){ cnt[2]++; x /= 2; }
2 for(int i = 3; i*i <= x+1; i += 2){
3     while(x % i == 0){ cnt[i]++; x /= i; }
4     if(x == 1) break;
5 }
6 if(x > 1) cnt[x]++;

```

4.5 Fibonacci

```

1 typedef pair<pi, pi> matrix;
2 matrix multiply(matrix x, matrix y, long long z){
3     return matrix(
4         pi((x.f.f*y.f.f+x.f.s*y.s.f)%z,
5           (x.f.f*y.f.s+x.f.s*y.s.s)%z),
6         pi((x.s.f*y.f.f+x.s.s*y.s.f)%z,
7           (x.s.f*y.f.s+x.s.s*y.s.s)%z));
8 }
9 matrix square(matrix x, long long y){
10     return multiply(x, x, y);
11 }
12 matrix power(matrix x, long long y, long long z){

```

```

13     if(y == 1) return x;
14     if(y % 2 == 0) return square(power(x, y/2, z), z);
15     return multiply(x, square(power(x, y/2, z), z), z);
16 }
17 long long fibo(long long n, long long m){
18     matrix x = matrix(pi(1, 1), pi(1, 0));
19     return power(x, n, m).f.s;
20 }

```

4.6 nC_k

```

1  if(k > n-k) k = n-k;
2  for(int i = 0; i < k; i++){
3      ans *= (n-i);
4      ans /= (i+1);
5  }

```

5 Algorithms

5.1 Discretisation

```

1  for(int i = 0; i < n; i++){
2      cin >> a[i];
3      b[i] = a[i];
4  }
5  sort(b, b+n);
6  for(int i = 0; i < n; i++){
7      d = lower_bound(b, b+n, a[i]) - b;
8      a[i] = d + 1;
9  }

```

5.2 Binary Search

```

1  while(mini < maxi){
2      medi = mini + (maxi - mini) / 2;
3      if(can(medi)) maxi = medi;
4      else mini = medi + 1;
5  }

```

5.3 Mo's Algorithm

```

1  //queries : index, left, right
2  //answers : index, answer
3
4  bool cmp(pii x, pii y){
5      if(x.second.first/blk != y.second.first/blk){
6          return x.second.first/blk < y.second.first/blk;
7      }
8      if(x.second.first/blk & 1){
9          return x.second.second < y.second.second;
10     }
11     return x.second.second > y.second.second;
12 }

```

```

13
14 blk = sqrt(n);
15 sort(qs, qs+q, cmp);
16 for(int i = 0; i < q; i++){
17     l = qs[i].second.first; r = qs[i].second.second;
18     while(lft > l){
19         //remove a[lft-1]
20         lft--;
21     }
22     while(rgt <= r){
23         //add a[rgt]
24         rgt++;
25     }
26     while(lft < l){
27         //add a[lft]
28         lft++;
29     }
30     while(rgt > r+1){
31         //remove a[rgt-1]
32         rgt--;
33     }
34     ans[i] = pi(qs[i].first, cur);
35 }
36 sort(ans, ans+q);

```

6 Miscellaneous

6.1 Macros + Functions + Variables

```

1 #define f first
2 #define s second
3 #define pb push_back
4 #define ins insert
5 int ls(int x){ return (x)&(-x); }
6 mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
7 // 4 Directions
8 int dx[]={0, 0, -1, 1};
9 int dy[]={-1, 1, 0, 0};
10 // 8 Directions
11 int dx[]={0, 0, -1, 1, -1, 1, -1, 1};
12 int dy[]={-1, 1, -1, 1, 0, 0, 1, -1};
13 // Knight Moves
14 int dx[]={-1, -2, 1, 2, 2, 1, -2, 1};
15 int dy[]={-2, -1, -2, -1, 1, 2, 1, 2};

```

6.2 Compile Commands

6.2.1 Compile

```

1 g++ -c "%f" -std=c++11

```

6.2.2 Build

```

1 g++ -o "%e" "%f" -std=c++11

```

6.2.3 Command Line

```
1 g++ "file.cpp" -o "file" -std=c++11
```

6.2.4 Simple Script

```
1 int main(int argc, char **argv){
2     system(g++ -o (argv[1]) (argv[1]).cpp -std=c++11);
3 }
```

6.3 Input/Output

6.3.1 Fast

```
1 ios_base::sync_with_stdio(false);
2 cin.tie(0);
```

6.3.2 Faster

```
1 inline int read_int() {
2     int x = 0;
3     char ch = getchar_unlocked();
4     while (ch < '0' || ch > '9') ch = getchar_unlocked();
5     while (ch >= '0' && ch <= '9'){
6         x = (x << 3) + (x << 1) + ch - '0';
7         ch = getchar_unlocked();
8     }
9     return x;
10 }
```

6.4 Pruning

```
1 auto start = chrono::high_resolution_clock::now();
2 auto end = chrono::high_resolution_clock::now();
3 auto elapse = chrono::duration<double>(end-start);
4 if(elapse.count() > 2.9) break;
```

6.5 Optimise

```
1 int __attribute__((optimize("Ofast"), target("arch=sandybridge"))) f(){}
```
