

Competitive Programming Reference

ngmh

Last Updated: 11/03/2026

Contents

1	Data Structures	4
1.1	Prefix Sums	4
1.1.1	1D	4
1.1.2	2D	4
1.2	Sparse Table	4
1.2.1	1D	4
1.2.2	2D	5
1.3	Fenwick Trees	6
1.3.1	Point Update Range Query	6
1.3.2	Range Update Point Query	6
1.3.3	Range Update Range Query	6
1.3.4	2D PURQ / RUPQ	7
1.3.5	2D RURQ	7
1.4	Segment Trees	8
1.4.1	Standard	8
1.4.2	Lazy Propagation	8
1.4.3	Lazy Node Creation	9
1.4.4	Maxsum	10
1.4.5	Merge Sort Tree / Order Statistics	10
1.4.6	2D	11
2	Graph Theory	12
2.1	Depth First Search	12
2.2	Breadth First Search	13
2.3	0-1 BFS	13
2.4	Floyd-Warshall	13
2.5	Bellman-Ford	14
2.6	Dijkstra's Algorithm	14
2.7	Shortest Path Faster Algorithm	14
2.8	Prim's Algorithm	15
2.9	Union Find Disjoint Subset	15
2.10	Kruskal's Algorithm	16
2.11	Topological Sort	16
2.12	Floyd's Cycle Finding Algorithm	16
2.13	Maximum Cardinality Bipartite Matching	17
2.13.1	Kuhn's Algorithm	17
2.13.2	Hopcroft-Karp	18
2.13.3	Hungarian	20
2.13.4	Edmond's	21
2.13.5	Weighted Edmond's	24
2.14	Articulation Points and Bridges	28
2.15	Strongly Connected Components	28
2.16	Travelling Salesman Problem	29
2.16.1	Bottom Up	29
2.16.2	Top Down	30

2.17	Max Flow / Min Cut	30
2.18	Trees	33
2.18.1	Pre/Postorder Traversal	33
2.18.2	Subtree to Range	34
2.18.3	Weighted Maximum Independent Set	34
2.18.4	Diameter	34
2.18.5	2^K Decomposition	35
2.18.6	Lowest Common Ancestor	35
2.18.7	Shortest Path	36
2.18.8	Heavy Light Decomposition	36
2.18.9	Centroid Decomposition	37
3	Dynamic Programming	38
3.1	Maxsum	38
3.1.1	1D	38
3.2	Longest Increasing Subsequence	39
3.2.1	N^2 DP	39
3.2.2	Data Structure Speedup	39
3.2.3	$N \log N$ DP	39
3.3	Coin Combinations	39
3.4	Coin Change	40
3.5	Knapsack	40
3.5.1	0-1	40
3.5.2	0-1 No Values	40
3.5.3	0-K Binary Grouping	40
3.5.4	0-K Monotonic Queue	41
3.6	Digit DP	41
3.7	Convex Hull Trick	43
3.8	Li Chao Tree	44
3.9	Divide and Conquer	44
3.10	Longest Common Subsequence	45
3.10.1	N^2 DP	45
3.10.2	LIS Reduction	45
4	Math	46
4.1	Fast Exponentiation	46
4.2	Prime Factorisation	46
4.3	Sieve of Eratosthenes	46
4.4	Greatest Common Divisor	47
4.5	Lowest Common Multiple	47
4.6	Modular Inverse	47
4.7	$\binom{n}{k}$	47
4.8	Fibonacci	47
4.9	Convex Hull	48
4.10	Furthest Pair of Points	49
4.11	Nearest Pair of Points	50
5	Algorithms	52
5.1	Binary Search	52
5.2	Binary Search using Lifting	52
5.3	Sliding Set	52
5.4	Sliding Window	52
5.5	Set Merging	53
5.6	Discretisation	53
5.7	Meet in the Middle	53
5.8	On the Fly	54
5.9	Square Root Decomposition	54
5.10	Mo's Algorithm	54

6	Strings	55
6.1	Manacher's Algorithm	55
6.2	Knuth-Morris-Pratt	56
6.3	Z-Function	56
6.4	Suffix Array	57
7	Miscellaneous	60
7.1	Maximum Time complexity v/s N	60
7.2	Fast I/O	60
7.3	Superfast I/O	61
7.4	Header	61
7.5	Compile Commands	62
7.6	Pruning	62
7.7	STL Data Structures and Functions	63

1 Data Structures

Data Structure	Precomputation	Update	Query	Memory	Notes
Prefix Sum	$O(N)$	X	$O(1)$	$O(N)$	Associative Functions (+, XOR)
Sparse Table	$O(N \log N)$	X	$O(1)$	$O(N \log N)$	Idempotent Functions (max, gcd)
Fenwick Tree	X	$O(\log N)$	$O(\log N)$	$O(N)$	Prefix Operations
Segment Tree	X	$O(\log N)$	$O(\log N)$	$O(4N)$	Very flexible and extendable

1.1 Prefix Sums

1.1.1 1D

$O(N)$ precomputation, $O(1)$ query.

```
//Query - 1-Indexed
int query(int s, int e){
    return ps[e]-ps[s-1];
}

//Precomputation
ps[0] = 0;
for(int i = 1; i <= n; i++) ps[i] = ps[i-1]+a[i];
```

1.1.2 2D

$O(R \cdot C)$ precomputation, $O(1)$ query.

```
//Query - 1-Indexed
int query(int x1, int y1, int x2, int y2){
    return ps[x2][y2]-ps[x1-1][y2]-ps[x2][y1-1]+ps[x1-1][y1-1];
}

//Precomputation
for (int i = 0; i <= r; i++) ps[i][0] = 0;
for (int j = 0; j <= c; j++) ps[0][j] = 0;
for (int i = 1; i <= r; i++) {
    for (int j = 1; j <= c; j++) {
        ps[i][j] = ps[i-1][j]+ps[i][j-1]-ps[i-1][j-1]+a[i][j];
    }
}
```

1.2 Sparse Table

1.2.1 1D

$O(N \log N)$ precomputation, $O(1)$ query.

```
int sp[MAXLOGN][MAXN];

// Query - 0-indexed, inclusive [l, r]
int query(int l, int r){
    r++;
    int p = 31 - __builtin_clz(r - l); // 63 for long long
    return __gcd(sp[p][l], sp[p][r - (1 << p)]);
}

// Precomputation
h = 31 - __builtin_clz(n);
for (int i = 0; i < n; i++) sp[0][i] = a[i];
```

```

for (int i = 1; i <= h; i++) {
    for (int j = 0; j + (1 << i) <= n; j++) {
        sp[i][j] = __gcd(sp[i-1][j], sp[i-1][j + (1 << (i-1))]);
    }
}

```

1.2.2 2D

$O(NM \log N \log M)$ precomputation, $O(1)$ query.

```

int sp[MAXLOGN][MAXLOGM][MAXN][MAXM];

// Query - 0-indexed, inclusive
int query(int x1, int y1, int x2, int y2) {
    x2++; y2++;
    // 63 for long long
    int kx = 31 - __builtin_clz(x2 - x1);
    int ky = 31 - __builtin_clz(y2 - y1);
    int g1 = sp[kx][ky][x1][y1];
    int g2 = sp[kx][ky][x2 - (1 << kx)][y1];
    int g3 = sp[kx][ky][x1][y2 - (1 << ky)];
    int g4 = sp[kx][ky][x2 - (1 << kx)][y2 - (1 << ky)];
    return __gcd(__gcd(g1, g2), __gcd(g3, g4));
}

// Precomputation
// Build single elements
for (int i = 0; i < n; i++) {
    for (int j = 0; j < m; j++) {
        sp[0][0][i][j] = a[i][j];
    }
}

// Build along columns (k2)
for (int k2 = 1; (1 << k2) <= m; k2++) {
    for (int i = 0; i < n; i++) {
        for (int j = 0; j + (1 << k2) <= m; j++) {
            sp[0][k2][i][j] =
                __gcd(sp[0][k2-1][i][j],
                    sp[0][k2-1][i][j + (1 << (k2-1))]);
        }
    }
}

// Build along rows (k1)
for (int k1 = 1; (1 << k1) <= n; k1++) {
    for (int k2 = 0; (1 << k2) <= m; k2++) {
        for (int i = 0; i + (1 << k1) <= n; i++) {
            for (int j = 0; j + (1 << k2) <= m; j++) {
                sp[k1][k2][i][j] =
                    __gcd(sp[k1-1][k2][i][j],
                        sp[k1-1][k2][i + (1 << (k1-1))][j]);
            }
        }
    }
}

```

1.3 Fenwick Trees

1.3.1 Point Update Range Query

$O(\log N)$ update and query.

```
inline int ls(int x){ return (x)&(-x); }

int fw[MAXN]; // 1-Indexed

void pu(int i, int v) {
    for(; i <= n; i += ls(i)) fw[i] += v;
}

int pq(int i) {
    int t = 0;
    for(; i; i -= ls(i)) t += fw[i];
    return t;
}

int rq(int s, int e) {
    return pq(e) - pq(s - 1);
}
```

1.3.2 Range Update Point Query

$O(\log N)$ update and query.

```
// Requires PURQ Code (PU, PQ)

void ru(int s, int e, int v) {
    pu(s, v);
    pu(e+1, -v);
}
```

1.3.3 Range Update Range Query

$O(\log N)$ update and query.

```
// Requires PURQ Code (PU, PQ)
// Functions need to be modified to take in array parameter
// e.g. int pu(*tree, int i, int v)

void ru(int s, int e, int v) {
    pu(fw1, s, v);
    pu(fw1, e+1, -v);
    pu(fw2, s, -v*(s-1));
    pu(fw2, e+1, v*e);
}

int ps(int i) {
    return pq(fw1, i)*i + pq(fw2, i);
}

int rq(int s, int e) {
    return ps(e) - ps(s - 1);
}
```

1.3.4 2D PURQ / RUPQ

$O(\log N \cdot \log M)$ update and query.

```
inline int ls(int x) { return x & -x; }

int fw[MAXN][MAXN]; // 1-indexed

void pu(int x, int y, int v) {
    for (int i = x; i < MAXN; i += ls(i)) {
        for (int j = y; j < MAXN; j += ls(j)) {
            fw[i][j] += v;
        }
    }
}

int pq(int x, int y) {
    int ans = 0;
    for (int i = x; i > 0; i -= ls(i)) {
        for (int j = y; j > 0; j -= ls(j)) {
            ans += fw[i][j];
        }
    }
    return ans;
}

// Range Query
int rq(int x1, int y1, int x2, int y2) {
    return pq(x2, y2) - pq(x1-1, y2) - pq(x2, y1-1) + pq(x1-1, y1-1);
}

// Range Update, Point Query
void ru(int x1, int y1, int x2, int y2, int v) {
    pu(x1, y1, v);
    pu(x1, y2 + 1, -v);
    pu(x2 + 1, y1, -v);
    pu(x2 + 1, y2 + 1, v);
}
```

1.3.5 2D RURQ

$O(\log N \cdot \log M)$ update and query.

```
// Requires 2D PURQ Code

void ru(int x1, int y1, int x2, int y2, long long v) {
    pu(fw1, x1, y1, v);
    pu(fw1, x1, y2+1, -v);
    pu(fw1, x2+1, y1, -v);
    pu(fw1, x2+1, y2+1, v);

    pu(fw2, x1, y1, v*(x1-1));
    pu(fw2, x1, y2+1, -v*(x1-1));
    pu(fw2, x2+1, y1, -v*x2);
    pu(fw2, x2+1, y2+1, v*x2);

    pu(fw3, x1, y1, v*(y1-1));
    pu(fw3, x1, y2+1, -v*y2);
    pu(fw3, x2+1, y1, -v*(y1-1));
}
```

```

    pu-fw3, x2+1, y2+1, v*y2);

    pu-fw4, x1, y1, v*(x1-1)*(y1-1));
    pu-fw4, x1, y2+1, -v*(x1-1)*y2);
    pu-fw4, x2+1, y1, -v*x2*(y1-1));
    pu-fw4, x2+1, y2+1, v*x2*y2);
}

long long ps(int x,int y) {
    return pq-fw1, x, y)*x*y-pq-fw2, x, y)*y-pq-fw3, x, y)*x+pq-fw4, x, y);
}

long long rq(int x1,int y1,int x2,int y2) {
    return ps(x2, y2)-ps(x1-1, y2)-ps(x2, y1-1)+ps(x1-1, y1-1);
}

```

1.4 Segment Trees

1.4.1 Standard

$O(\log N)$ point update and range query.

```

struct node {
    int s, e, m, v;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2; v = 0;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(int x, int y) {
        if (s == e) { v = y; return; }
        if (x <= m) l->pu(x, y);
        if (x > m) r->pu(x, y);
        v = min(l->v, r->v);
    }
    int rq(int x, int y) {
        if (s == x && e == y) return v;
        if (y <= m) return l->rq(x, y);
        if (x > m) return r->rq(x, y);
        return min(l->rq(x, m), r->rq(m+1, y));
    }
} *root;

root = new node(0, n-1);

```

1.4.2 Lazy Propagation

$O(\log N)$ range update and range query.

```

struct node {
    int s, e, m, v, lazy;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2; v = lazy = 0;
        if (s != e) {

```



```

        l = new node(s, m);
        r = new node(m+1, e);
    }
}

int pu() {
    if (s == e) { v += lazy; lazy = 0; return v; }
    v += lazy;
    l->lazy += lazy; r->lazy += lazy;
    lazy = 0;
    return v;
}

void ru(int x, int y, int z) {
    if (s == x && e == y) { lazy += z; return; }
    if (y <= m) l->ru(x, y, z);
    else if (x > m) r->ru(x, y, z);
    else l->ru(x, m, z), r->ru(m+1, y, z);
    v = max(l->pu(), r->pu());
}

int rq(int x, int y) {
    pu();
    if (s == x && e == y) return pu();
    if (y <= m) return l->rq(x, y);
    if (x > m) return r->rq(x, y);
    return max(l->rq(x, m), r->rq(m+1, y));
}
} *root;

root = new node(0, n-1);

```

1.4.3 Lazy Node Creation

```

struct node {
    int s, e, m, v;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2; v = 0;
        l = nullptr, r = nullptr;
    }
    void create() {
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(int x, int y) {
        if (s == e) { v = y; return; }
        create();
        if (x <= m) l->pu(x, y);
        if (x > m) r->pu(x, y);
        v = min(l->v, r->v);
    }
    int rq(int x, int y) {
        if (s == x && e == y) return v;
        create();
    }
}

```

```

        if (y <= m) return l->rq(x, y);
        if (x > m) return r->rq(x, y);
        return min(l->rq(x, m), r->rq(m+1, y));
    }
} *root;

root = new node(0, n-1);

```

1.4.4 Maxsum

$O(\log N)$ point update and range query.

```

struct node {
    ll s, e, m, ps, ss, ms, ts;
    node *l, *r;
    node(ll _s, ll _e) {
        s = _s; e = _e; m = (s+e)/2; ps = ss = ms = ts = 0;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }
    void pu(ll x, ll y) {
        if (s == e) { ps = ss = ms = ts = y; return; }
        if (x <= m) l->pu(x, y);
        if (x > m) r->pu(x, y);
        //New Prefix Max -> Left Prefix, Left + Right Prefix
        ps = max(l->ps, l->ts+r->ps);
        //New Suffix Max -> Right Suffix, Left Suffix + Right
        ss = max(r->ss, r->ts+l->ss);
        //Total Sum -> Left + Right
        ts = l->ts+r->ts;
        //Maxsum - Left Suffix + Right Prefix, Left, Right,
        //          Total, Left Maxsum, Right Maxsum
        ms = max({l->ss+r->ps, ps, ss, ts, l->ms, r->ms});
    }
    ll ans() {
        return ms;
    }
} *root;

root = new node(0, n-1);

```

1.4.5 Merge Sort Tree / Order Statistics

Insertion: $O(\log N)$, Building: $O(N \log^2 N)$, Counting: $O(\log^2 N)$, Finding: $O(\log V \cdot \log^2 N)$, Range Max: $O(\log N)$.

```

struct node {
    int s, e, m;
    vector<int> v;
    node *l, *r;
    node(int _s, int _e) {
        s = _s; e = _e; m = (s+e)/2;
        if (s != e) {
            l = new node(s, m);
            r = new node(m+1, e);
        }
    }

```

```

}
void insert(int x, int y) {
    if (s == e) { v.push_back(y); return; }
    if (x > m) r->insert(x, y);
    if (x <= m) l->insert(x, y);
    v.push_back(y);
}
void build(){
    if (s == e) return;
    l->build();
    r->build();
    sort(v.begin(), v.end());
}
int countLessEqual(int x, int y, int k) {
    if (x > y) return 0;
    if (s == x && e == y) {
        return upper_bound(v.begin(), v.end(), k)-v.begin();
    }
    if (x > m) return r->countLessEqual(x, y, k);
    if (y <= m) return l->countLessEqual(x, y, k);
    return l->countLessEqual(x, m, k)+r->countLessEqual(m+1, y, k);
}
int kthSmallest(int x, int y, int k) {
    int mini = 0, maxi = (1 << 30);
    int ans = mini, gap = maxi;
    while (gap > 0) {
        while (ans + gap <= maxi && countLessEqual(x, y, ans + gap) < k) {
            ans += gap;
        }
        gap >>= 1;
    }
    return ans + 1;
}
int rangeMax(int x, int y) {
    if (x > y) return 0;
    if (s == x && e == y) return v.back();
    if (x > m) return r->rangeMax(x, y);
    if (y <= m) return l->rangeMax(x, y);
    return max(l->rangeMax(x, m), r->rangeMax(m+1, y));
}
} *root;

root = new node(0, n-1);

```

1.4.6 2D

$O(N \cdot \log N \cdot \log M)$ point update and range query.

```

struct node2D {
    int s, e, m;
    node1D *maxi;
    node2D *l, *r;
    node2D(int a, int b, int c, int d) {
        s = a; e = b; m = (s+e)/2;
        maxi = new node1D(c, d);
        if (s != e) {
            l = new node2D(s, m, c, d);
            r = new node2D(m+1, e, c, d);
        }
    }
};

```

```

    }
}
void pu(int a, int b, int v) {
    if (s == e) { maxi->pu(b, v); return; }
    if (a <= m) l->pu(a, b, v);
    else r->pu(a, b, v);
    maxi->pu(b, max(l->maxi->rq(b, b), r->maxi->rq(b, b)));
}
int rq(int a, int b, int c, int d) {
    if (s == a && e == b) return maxi->rq(c, d);
    if (b <= m) return l->rq(a, b, c, d);
    if (a > m) return r->rq(a, b, c, d);
    return max(l->rq(a, m, c, d), r->rq(m+1, b, c, d));
}
} *root;

root = new node(0, n-1, 0, n-1);

```

2 Graph Theory

Graph Algorithm	Complexity	Notes
DFS	$O(V+E)$	Flood Fill, Trees
BFS	$O(V+E)$	Unweighted Shortest Path
0-1 BFS	$O(V+E)$	Unweighted Shortest Path
Floyd-Warshall	$O(N^3)$	All Pairs Shortest Path
Bellman-Ford	$O(VE)$	Negative Single Source Shortest Path
Dijkstra'	$O(E \log V)$	Single Source Shortest Path
SPFA	$O(VE)$	Negative Single Source Shortest Path
Prim's	$O(E \log V)$	Dijkstra's
UFDS	$O(\alpha(n))$	Connectedness
Kruskal's	$O(E \log E)$	Greedy
Toposort	$O(V+E)$	Postorder
Floyd's Cycle Finding	$O(V+E)$	Outdegree 1
Kuhn's	$O(V^3)$	Bipartite Matching
Hopcroft-Karp	$O(E\sqrt{V})$	Bipartite Matching
Hungarian	$O(V^3)$	Weighted Bipartite Matching
Edmond's	$O(V^3)$	General Matching
Weighted Edmond's	$O(V^3)$	Weighted General Matching
Articulation Points	$O(V+E)$	Find Splitting Nodes
Bridges	$O(V+E)$	Find Splitting Edges
SCC	$O(V+E)$	Compress Cycles
TSP	$O(N^2 2^N)$	Tour All Nodes
Max Flow / Min Cut	$O(V^2 E)$	Maximum Flow / Minimum Cut
Pre/Postorder	$O(V)$	Ordering of Nodes
Subtree To Range	$O(V)$	Ordering Nodes
Weighted MIS	$O(V)$	Tree DP
Diameter	$O(V)$	DFS
2^K Decomposition	$O(N \log N)$ precompute, $O(\log N)$ query	Find Parent
Lowest Common Ancestor	$O(\log N)$ query	Find Common Parent
Heavy Light Decomposition	$O(N)$ precompute, $O(\log N)$ query	Decomposition
Centroid Decomposition	$O(N \log N)$ precompute, $O(\log N)$ query	Decomposition

2.1 Depth First Search

Runs in $O(V + E)$.

```
// For adjacency lists
void dfs(int x, int p) {
    for (int y : adj[x]) {
        if (y != p) {
            dist[y] = dist[x]+1;
            dfs(y, x);
        }
    }
}
```

2.2 Breadth First Search

Runs in $O(V + E)$.

```
// For adjacency lists
visited[s] = 1;
dist[s] = 0;
q.push(s);
while (!q.empty()) {
    int f = q.front(); q.pop();
    for (int i : adjlist[f]) {
        if (!visited[i]) {
            q.push(i);
            visited[i] = 1;
            dist[i] = dist[f] + 1;
        }
    }
}
```

2.3 0-1 BFS

Runs in $O(V + E)$.

```
// For adjacency lists
deque<int> dq;
dist[s] = 0;
dq.push(s);
while (!dq.empty()) {
    int u = dq.front(); dq.pop();
    for (int e : adjlist[u]) {
        int v = e.first, w = e.second;
        if (dist[v] > dist[u] + w) {
            dist[v] = dist[u] + w;
            if (w == 0) dq.push_front(v);
            else dq.push_back(v);
        }
    }
}
```

2.4 Floyd-Warshall

Runs in $O(N^3)$.

```
// Initialise adjacency matrix
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        if (i == j) adj[i][j] = 0;
    }
}
```

```

        else adj[i][j] = INF;
    }
}
// Floyd-Warshall
for (int k = 0; k < n; k++) {
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            adj[i][j] = min(adj[i][j], adj[i][k]+adj[k][j]);
            if (adj[i][i] < 0) negCycle = true;
        }
    }
}

```

2.5 Bellman-Ford

Runs in $O(VE)$.

```

vector<int> dist(n, INF);
dist[s] = 0;
bool negCycle = false;
for (int i = 1; i <= n; i++) {
    bool update = false;
    for (Edge e : edges) {
        if (dist[e.u] < INF && dist[e.v] > dist[e.u] + e.w) {
            dist[e.v] = dist[e.u] + e.w;
            update = true;
        }
    }
    if (!update) break;
    if (update && i == n) negCycle = true;
}

```

2.6 Dijkstra's Algorithm

Runs in $O(E \log V)$.

```

priority_queue<pi, vector<pi>, greater<pi>> pq;
vector<int> dist(n, INF);
dist[s] = 0;
pq.push({0, s});
while (!pq.empty()) {
    pi f = pq.top(); pq.pop();
    int d = f.first, u = f.second;
    if (d != dist[u]) continue;
    for (pi x : adj[u]) {
        int v = x.first, w = x.second;
        if (dist[v] > d + w) {
            dist[v] = d + w;
            pq.push({ dist[v], v });
        }
    }
}

```

2.7 Shortest Path Faster Algorithm

Runs in $O(VE)$.

```

vector<int> dist(n, INF);
vector<int> inQueue(n, 0);
queue<int> q;
dist[s] = 0;
q.push(s);
inQueue[s]++;
bool negCycle = false;
while (!q.empty()) {
    int u = q.front(); q.pop();
    inQueue[u]--;
    for (Edge e : adj[u]) {
        if (dist[e.v] > dist[u] + e.w) {
            dist[e.v] = dist[u] + e.w;
            if (inQueue[e.v] == 0) {
                q.push(e.v);
                inQueue[e.v]++;
                if (inQueue[e.v] > n) {
                    negCycle = true;
                    break;
                }
            }
        }
    }
}
if (negCycle) break;
}

```

2.8 Prim's Algorithm

Runs in $O(E \log V)$.

```

priority_queue<pi, vector<pi>, greater<pi>> pq;
vector<int> dist(n, INF);
vector<bool> vis(n, false);
dist[s] = 0;
pq.push({0, s});
while (!pq.empty()) {
    pi f = pq.top(); pq.pop();
    int d = f.first, u = f.second;
    if (vis[u]) continue;
    vis[u] = true;
    for (pi x : adj[u]) {
        int v = x.first, w = x.second;
        if (!vis[v] && dist[v] > w) {
            dist[v] = w;
            pq.push({ dist[v], v });
        }
    }
}
}

```

2.9 Union Find Disjoint Subset

With both path compression and union by rank, runs in $O(\alpha(n))$ (basically constant time).

```

int p[MAXN];
int sz[MAXN];

int root(int x) {

```

```

    if (p[x] == -1) return x;
    return p[x] = root(p[x]);
}

void connect(int x, int y) {
    x = root(x); y = root(y);
    if (x == y) return;
    if (sz[x] < sz[y]) swap(x, y);
    p[y] = x;
    sz[x] += sz[y];
}

fill(p, p+MAXN, -1);
fill(sz, sz+MAXN, 1);

```

2.10 Kruskal's Algorithm

Runs in $O(E \log E)$.

```

sort(edges.begin(), edges.end());
for (Edge e : edges) {
    if (root(e.u) != root(e.v)) {
        connect(e.u, e.v);
        cost += e.w;
    }
}

```

2.11 Topological Sort

Runs in $O(V + E)$.

```

void dfs(int x) {
    if (v[x]) return;
    v[x] = 1;
    for (int y : adj[x]) dfs(y);
    topo.push_back(x);
}

for (int i = 0; i < n; i++) dfs(i);
reverse(topo.begin(), topo.end());

```

2.12 Floyd's Cycle Finding Algorithm

For graphs with outdegree 1, runs in $O(V + E)$.

```

// detect cycle
int slow = s, fast = s;
do {
    slow = nxt[slow];
    fast = nxt[nxt[fast]];
} while (slow != fast);
// find start of cycle
slow = start;
while (slow != fast) {
    slow = nxt[slow];
    fast = nxt[fast];
}
// collect all nodes in cycle
vector<int> cycle;

```



```

int cur = slow;
do {
    cycle.push_back(cur);
    cur = nxt[cur];
} while (cur != slow);

```

2.13 Maximum Cardinality Bipartite Matching

2.13.1 Kuhn's Algorithm

Unweighted MCBM, runs in $O(V^3)$.

```

class Kuhns {
private:
    int nL, nR;
    int mcbm = 0;
    vector<int> matchR;
    vector<int> matchL;
    vector<bool> vis;
    vector<vector<int>> adj;

    bool dfs(int u) {
        for (int v : adj[u]) {
            if (!vis[v]) {
                vis[v] = true;
                if (matchR[v] == -1 || dfs(matchR[v])) {
                    matchR[v] = u;
                    matchL[u] = v;
                    return true;
                }
            }
        }
        return false;
    }

public:
    Kuhns(int L, int R) : nL(L), nR(R), matchR(R, -1), matchL(L, -1),
                        vis(R), adj(L) {}

    void addEdge(int u, int v) {
        adj[u].push_back(v);
    }

    void compute() {
        mcbm = 0;
        matchR.assign(nR, -1);
        matchL.assign(nL, -1);

        // greedy initial matching
        for (int u = 0; u < nL; ++u) {
            for (int v : adj[u]) {
                if (matchR[v] == -1) {
                    matchR[v] = u;
                    matchL[u] = v;
                    mcbm++;
                    break;
                }
            }
        }
    }
}

```

```

        // dfs for augmenting paths
        for (int u = 0; u < nL; ++u) {
            if (matchL[u] == -1) {
                vis.assign(nR, false);
                if (dfs(u)) mcbm++;
            }
        }
    }

    int getMCBM() { return mcbm; }
    int getMIS() { return nL + nR - mcbm; }

    int getMatchedU(int u) { return matchL[u]; }
    int getMatchedV(int v) { return matchR[v]; }
};

Kuhns solver(3, 3); // (N, M)
solver.addEdge(0, 2); // (L, R)
solver.compute(); // DON'T FORGET THIS!
solver.getMCBM();
solver.getMIS();
solver.getMatchedU(0);
solver.getMatchedV(2);

```

2.13.2 Hopcroft-Karp

Unweighted MCBM, runs in $O(E \cdot \sqrt{V})$.

```

class HopcroftKarp {
private:
    int n, m;
    int mcbm = 0;
    const int INF = INT_MAX;
    vector<vector<int>> adj;
    vector<int> pairU, pairV, dist;

    bool bfs() {
        queue<int> q;
        for (int u = 0; u < n; ++u) {
            if (pairU[u] == -1) {
                dist[u] = 0;
                q.push(u);
            } else {
                dist[u] = INF;
            }
        }
        bool found = false;
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (int v : adj[u]) {
                if (pairV[v] == -1) {
                    found = true;
                } else if (dist[pairV[v]] == INF) {
                    dist[pairV[v]] = dist[u] + 1;
                    q.push(pairV[v]);
                }
            }
        }
    }

```

```

    }
    return found;
}

bool dfs(int u) {
    for (int v : adj[u]) {
        if (pairV[v] == -1 ||
            (dist[pairV[v]] == dist[u] + 1 && dfs(pairV[v]))) {
            pairU[u] = v;
            pairV[v] = u;
            return true;
        }
    }
    dist[u] = INF;
    return false;
}

public:
    HopcroftKarp(int n, int m) : n(n), m(m), adj(n),
                                pairU(n, -1), pairV(m, -1), dist(n) {}

    void addEdge(int u, int v) {
        adj[u].push_back(v);
    }

    int compute() {
        pairU.assign(n, -1);
        pairV.assign(m, -1);
        dist.assign(n, 0);

        mcbm = 0;
        while (bfs()) {
            for (int u = 0; u < n; ++u) {
                if (pairU[u] == -1 && dfs(u)) {
                    mcbm++;
                }
            }
        }
        return mcbm;
    }

    int getMCBM() { return mcbm; }
    int getMIS() { return n + m - mcbm; }

    int getMatchedU(int u) { return pairU[u]; }
    int getMatchedV(int v) { return pairV[v]; }
};

HopcroftKarp solver(3, 3); // (N, M)
solver.addEdge(0, 0); // (L, R)
solver.compute(); // DON'T FORGET THIS!
solver.getMCBM();
solver.getMIS();
solver.getMatchedU(0); // Left side
solver.getMatchedV(0); // Right side

```

2.13.3 Hungarian

Min-weighted MCBM, runs in $O(V^3)$.

```
class Hungarian {
private:
    int n, m;
    int minCost = 0;
    const int INF = INT_MAX / 4; // prevent overflow
    vector<vector<int>> cost;
    vector<int> u, v, p, way;

public:
    Hungarian(int n, int m) : n(n), m(m), cost(n + 1, vector<int>(m + 1, 0)),
                               u(n + 1), v(m + 1), p(m + 1), way(m + 1) {}

    void setWeight(int i, int j, int weight) {
        cost[i + 1][j + 1] = weight;
    }

    int compute() {
        fill(u.begin(), u.end(), 0);
        fill(v.begin(), v.end(), 0);
        fill(p.begin(), p.end(), 0);
        fill(way.begin(), way.end(), 0);

        for (int i = 1; i <= n; ++i) {
            p[0] = i;
            int j0 = 0;
            vector<int> minv(m + 1, INF);
            vector<bool> used(m + 1, false);
            do {
                used[j0] = true;
                int i0 = p[j0], delta = INF, j1 = 0;
                for (int j = 1; j <= m; ++j) {
                    if (!used[j]) {
                        int cur = cost[i0][j] - u[i0] - v[j];
                        if (cur < minv[j]) {
                            minv[j] = cur;
                            way[j] = j0;
                        }
                        if (minv[j] < delta) {
                            delta = minv[j];
                            j1 = j;
                        }
                    }
                }
            } while (j1 > 0);
            for (int j = 0; j <= m; ++j) {
                if (used[j]) u[p[j]] += delta, v[j] -= delta;
                else minv[j] -= delta;
            }
            j0 = j1;
        } while (p[j0] != 0);
        do {
            int j1 = way[j0];
            p[j0] = p[j1];
            j0 = j1;
        } while (j0);
    }
}
```

```

        minCost = -v[0];
        return minCost;
    }

    int getMinCost() { return minCost; }

    int getMatchedU(int u) {
        for (int j = 1; j <= m; ++j) if (p[j] == u + 1) return j - 1;
        return -1;
    }
};

// requires N <= M!

// min weight matching
Hungarian minSolver(3, 3);
minSolver.setWeight(0, 0, 10);
minSolver.compute();
minSolver.getMinCost();

// max weight matching - negate edges!
Hungarian maxSolver(3, 3);
maxSolver.setWeight(0, 0, -10);
maxSolver.compute();
-maxSolver.getMinCost();

```

2.13.4 Edmond's

Unweighted MCBM for general graph, runs in $O(V^3)$.

```

class Edmonds {
private:
    int n, m;
    int mcbm = 0;
    vector<int> mate;
    vector<vector<int>> b;
    vector<int> p, d, bl;
    vector<vector<int>> g;

    void match(int u, int v) {
        g[u][v] = g[v][u] = -1;
        mate[u] = v;
        mate[v] = u;
    }

    vector<int> trace(int x) {
        vector<int> vx;
        while (true) {
            while (bl[x] != x) x = bl[x];
            if (!vx.empty() && vx.back() == x) break;
            vx.push_back(x);
            x = p[x];
        }
        return vx;
    }

    void contract(int c, int x, int y, vector<int>& vx, vector<int>& vy) {
        b[c].clear();
    }
}

```

```

    int r = vx.back();
    while (!vx.empty() && !vy.empty() && vx.back() == vy.back()) {
        r = vx.back();
        vx.pop_back();
        vy.pop_back();
    }
    b[c].push_back(r);
    b[c].insert(b[c].end(), vx.rbegin(), vx.rend());
    b[c].insert(b[c].end(), vy.begin(), vy.end());
    for (int i = 0; i <= c; i++) {
        g[c][i] = g[i][c] = -1;
    }
    for (int z : b[c]) {
        bl[z] = c;
        for (int i = 0; i < c; i++) {
            if (g[z][i] != -1) {
                g[c][i] = z;
                g[i][c] = g[i][z];
            }
        }
    }
}

vector<int> lift(vector<int>& vx) {
    vector<int> A;
    while (vx.size() >= 2) {
        int z = vx.back(); vx.pop_back();
        if (z < n) {
            A.push_back(z);
            continue;
        }
        int w = vx.back();
        int i = (A.size() % 2 == 0 ?
            find(b[z].begin(), b[z].end(), g[z][w]) - b[z].begin() : 0);
        int j = (A.size() % 2 == 1 ?
            find(b[z].begin(), b[z].end(), g[z][A.back()]) - b[z].begin() : 0);
        int k = b[z].size();
        int dif = (A.size() % 2 == 0 ? i % 2 == 1 : j % 2 == 0) ? 1 : k - 1;
        while (i != j) {
            vx.push_back(b[z][i]);
            i = (i + dif) % k;
        }
        vx.push_back(b[z][i]);
    }
    return A;
}

public:
    Edmonds(int n) : n(n) {
        m = n + n / 2;
        mate.assign(n, -1);
        b.resize(m);
        p.resize(m);
        d.resize(m);
        bl.resize(m);
        g.assign(m, vector<int>(m, -1));
    }
}

```

```

void addEdge(int u, int v) {
    g[u][v] = u;
    g[v][u] = v;
}

int compute() {
    fill(mate.begin(), mate.end(), -1);

    for (int ans = 0; ; ans++) {
        fill(d.begin(), d.end(), 0);
        queue<int> Q;
        for (int i = 0; i < m; i++) bl[i] = i;
        for (int i = 0; i < n; i++) {
            if (mate[i] == -1) {
                Q.push(i);
                p[i] = i;
                d[i] = 1;
            }
        }
        int c = n;
        bool aug = false;
        while (!Q.empty() && !aug) {
            int x = Q.front(); Q.pop();
            if (bl[x] != x) continue;
            for (int y = 0; y < c; y++) {
                if (bl[y] == y && g[x][y] != -1) {
                    if (d[y] == 0) {
                        p[y] = x;
                        d[y] = 2;
                        p[mate[y]] = y;
                        d[mate[y]] = 1;
                        Q.push(mate[y]);
                    } else if (d[y] == 1) {
                        vector<int> vx = trace(x);
                        vector<int> vy = trace(y);
                        if (vx.back() == vy.back()) {
                            contract(c, x, y, vx, vy);
                            Q.push(c);
                            p[c] = p[b[c][0]];
                            d[c] = 1;
                            c++;
                        } else {
                            aug = true;
                            vx.insert(vx.begin(), y);
                            vy.insert(vy.begin(), x);
                            vector<int> A = lift(vx);
                            vector<int> B = lift(vy);
                            A.insert(A.end(), B.rbegin(), B.rend());
                            for (int i = 0; i < (int)A.size(); i += 2) {
                                match(A[i], A[i + 1]);
                                if (i + 2 < (int)A.size()) {
                                    addEdge(A[i + 1], A[i + 2]);
                                }
                            }
                        }
                    }
                }
            }
            break;
        }
    }
}

```

```

        }
    }
    if (!aug) {
        mcbm = ans;
        return mcbm;
    }
}

int getMCM() { return mcbm; }
int getMatched(int u) { return mate[u]; }
};

Edmonds solver(N);
solver.addEdge(u, v);
solver.compute();
solver.getMCM();
solver.getMatched(i);

```

2.13.5 Weighted Edmond's

Weighted MCBM for general graph, runs in $O(V^3)$.

// jacobtpl on yosupo

```

template<int SZ>
class WeightedMatching {
    struct Edge { int u, v, w; };
    Edge g[SZ * 2][SZ * 2];
    int N, NX, lab[SZ * 2], match[SZ * 2], slack[SZ * 2], st[SZ * 2];
    int par[SZ * 2], floFrom[SZ * 2][SZ], S[SZ * 2], aux[SZ * 2];
    vector<int> flo[SZ * 2];
    queue<int> q;

public:
    void init(int _N) {
        N = _N; NX = N;
        for (int i = 0; i <= 2 * N; ++i) {
            for (int j = 0; j <= 2 * N; ++j) g[i][j] = {i, j, 0};
            flo[i].clear(); match[i] = 0; st[i] = i;
        }
    }

    void addEdge(int u, int v, int w) {
        g[u][v].w = g[v][u].w = w;
    }

    int eDelta(Edge e) { return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2; }

    void updSlack(int u, int x) {
        if (!slack[x] || eDelta(g[u][x]) < eDelta(g[slack[x]][x])) {
            slack[x] = u;
        }
    }

    void setSlack(int x) {
        slack[x] = 0;
        for (int u = 1; u <= N; ++u) {

```



```

        if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0) {
            updSlack(u, x);
        }
    }
}

void qPush(int x) {
    if (x <= N) q.push(x);
    else for (int t : flo[x]) qPush(t);
}

void setSt(int x, int b) {
    st[x] = b; if (x > N) for (int t : flo[x]) setSt(t, b);
}

int getPr(int b, int xr) {
    int pr = find(flo[b].begin(), flo[b].end(), xr) - flo[b].begin();
    if (pr & 1) {
        reverse(flo[b].begin() + 1, flo[b].end());
        return (int)flo[b].size() - pr;
    }
    return pr;
}

void setMatch(int u, int v) {
    Edge e = g[u][v]; match[u] = e.v; if (u <= N) return;
    int xr = floFrom[u][e.u], pr = getPr(u, xr);
    for (int i = 0; i < pr; ++i) setMatch(flo[u][i], flo[u][i ^ 1]);
    setMatch(xr, v);
    rotate(flo[u].begin(), flo[u].begin() + pr, flo[u].end());
}

void augment(int u, int v) {
    while (1) {
        int xnv = st[match[u]]; setMatch(u, v);
        if (!xnv) return;
        setMatch(xnv, st[par[xnv]]);
        u = st[par[xnv]], v = xnv;
    }
}

int lca(int u, int v) {
    static int t = 0;
    for (++t; u || v; swap(u, v)) {
        if (!u) continue;
        if (aux[u] == t) return u;
        aux[u] = t; u = st[match[u]];
        if (u) u = st[par[u]];
    }
    return 0;
}

void addBlossom(int u, int anc, int v) {
    int b = N + 1; while (b <= NX && st[b]) ++b;
    if (b > NX) ++NX;
    lab[b] = S[b] = 0; match[b] = match[anc]; flo[b] = {anc};
    auto blossom = [&](int x) {
        for (int y; x != anc; x = st[par[y]]) {

```

```

        flo[b].push_back(x), flo[b].push_back(y = st[match[x]]), qPush(y);
    }
};
blossom(u);
reverse(flo[b].begin() + 1, flo[b].end());
blossom(v);
setSt(b, b);
for (int x = 1; x <= NX; ++x) g[b][x].w = g[x][b].w = 0;
for (int x = 1; x <= N; ++x) floFrom[b][x] = 0;
for (int xs : flo[b]) {
    for (int x = 1; x <= NX; ++x) {
        if (g[b][x].w == 0 || eDelta(g[xs][x]) < eDelta(g[b][x])) {
            g[b][x] = g[xs][x], g[x][b] = g[x][xs];
        }
    }
    for (int x = 1; x <= N; ++x) {
        if (floFrom[xs][x]) floFrom[b][x] = xs;
    }
}
setSlack(b);
}

void expandBlossom(int b) {
    for (int t : flo[b]) setSt(t, t);
    int xr = floFrom[b][g[b][par[b]].u], pr = getPr(b, xr);
    for (int i = 0; i < pr; i += 2) {
        int xs = flo[b][i], xns = flo[b][i + 1];
        par[xs] = g[xns][xs].u;
        S[xs] = 1;
        S[xns] = slack[xs] = slack[xns] = 0;
        qPush(xns);
    }
    S[xr] = 1; par[xr] = par[b];
    for (int i = pr + 1; i < (int)flo[b].size(); ++i) {
        int xs = flo[b][i]; S[xs] = -1; setSlack(xs);
    }
    st[b] = 0;
}

bool onFoundEdge(Edge e) {
    int u = st[e.u], v = st[e.v];
    if (S[v] == -1) {
        par[v] = e.u; S[v] = 1; slack[v] = 0;
        int nu = st[match[v]]; S[nu] = slack[nu] = 0; qPush(nu);
    } else if (S[v] == 0) {
        int anc = lca(u, v);
        if (!anc) { augment(u, v); augment(v, u); return 1; }
        addBlossom(u, anc, v);
    }
    return 0;
}

bool matching() {
    q = queue<int>();
    for (int x = 1; x <= NX; ++x) {
        S[x] = -1; slack[x] = 0;
        if (st[x] == x && !match[x]) par[x] = S[x] = 0, qPush(x);
    }
}

```

```

    if (q.empty()) return 0;
    while (1) {
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (int v = 1; v <= N; ++v) {
                if (g[u][v].w > 0 && st[u] != st[v]) {
                    if (eDelta(g[u][v]) == 0) {
                        if (onFoundEdge(g[u][v])) return 1;
                    }
                    else updSlack(u, st[v]);
                }
            }
        }
        int d = INT_MAX;
        for (int b = N + 1; b <= NX; ++b) {
            if (st[b] == b && S[b] == 1) d = min(d, lab[b] / 2);
        }
        for (int x = 1; x <= NX; ++x) if (st[x] == x && slack[x]) {
            if (S[x] == -1) d = min(d, eDelta(g[slack[x]][x]));
            else if (S[x] == 0) d = min(d, eDelta(g[slack[x]][x]) / 2);
        }
        for (int u = 1; u <= N; ++u) {
            if (S[st[u]] == 0) { if (lab[u] <= d) return 0; lab[u] -= d; }
            else if (S[st[u]] == 1) lab[u] += d;
        }
        for (int b = N + 1; b <= NX; ++b) {
            if (st[b] == b && S[b] != -1) {
                lab[b] += (S[b] == 0 ? 1 : -1) * d * 2;
            }
        }
        q = queue<int>();
        for (int x = 1; x <= NX; ++x) {
            if (st[x] == x && slack[x] && st[slack[x]] != x
                && eDelta(g[slack[x]][x]) == 0) {
                if (onFoundEdge(g[slack[x]][x])) return 1;
            }
        }
        for (int b = N + 1; b <= NX; ++b) {
            if (st[b] == b && S[b] == 1 && lab[b] == 0) expandBlossom(b);
        }
    }
    return 0;
}

pair<int, long long> compute() {
    int wMax = 0;
    for (int u = 1; u <= N; ++u) for (int v = 1; v <= N; ++v) {
        floFrom[u][v] = (u == v ? u : 0); wMax = max(wMax, g[u][v].w);
    }
    for (int u = 1; u <= N; ++u) lab[u] = wMax;
    int num = 0; long long wei = 0;
    while (matching()) ++num;
    for (int u = 1; u <= N; ++u) {
        if (match[u] && match[u] < u) wei += g[u][match[u]].w;
    }
    return {num, wei};
}

```

```

    int getMatched(int u) { return match[u + 1] - 1; }
};

// can't handle negative weights

// maximum weight matching
WeightedMatching<N> solver;
solver.init(N);
solver.addEdge(u + 1, v + 1, w); // 1-indexed
auto res = solver.compute(); // (num, weight)
solver.getMatched(i); // check that it's not -1

// minimum weight matching
const long long K = 1000000;
WeightedMatching<N> solver;
solver.init(N);
solver.addEdge(u + 1, v + 1, K - w); // 1-indexed
auto res = solver.compute(); // (num, weight)
long long minCost = (N / 2) * K - res.second;
solver.getMatched(i); // check that it's not -1

```

2.14 Articulation Points and Bridges

Using Tarjan's Algorithm, runs in $O(V + E)$.

```

vector<int> adj[MAXN];
vector<int> dep(MAXN, 0), low(MAXN, 0), par(MAXN, -1);
vector<int> chi(MAXN, 0), atp(MAXN, 0);
vector<bool> vis(MAXN, false);
vector<pi> bridges;

void tarjan(int u, int d) {
    vis[u] = true;
    dep[u] = low[u] = d;
    chi[u] = 0; atp[u] = 1;
    for (int v : adj[u]) {
        if (!vis[v]) {
            par[v] = u;
            chi[u]++;
            tarjan(v, d+1);
            low[u] = min(low[u], low[v]);
            if (low[v] >= dep[u]) atp[u]++;
            if (low[v] > dep[u]) bridges.push_back({u, v});
        } else if (v != par[u]) {
            low[u] = min(low[u], dep[v]);
        }
    }
}

tarjan(0, 0);
// handle root separately since it has no parents
atp[0] = chi[0];
// atp stores number of components separated upon removal
// bridges stores all bridges in the graph

```

2.15 Strongly Connected Components

Using Tarjan's Algorithm, runs in $O(V + E)$.

```

vector<int> adj[MAXN];
vector<int> comps[MAXN];
set<int> adjscc[MAXN];
vector<int> idxs(MAXN, -1), low(MAXN, 0);
vector<bool> onStack(MAXN, false);
stack<int> st;
int dfsidx = 0, sccidx;
int comp[MAXN];

void scc(int u) {
    idxs[u] = low[u] = dfsidx++;
    st.push(u);
    onStack[u] = true;
    for (int v : adj[u]) {
        if (idxs[v] == -1) {
            scc(v);
            low[u] = min(low[u], low[v]);
        } else if (onStack[v]) {
            low[u] = min(low[u], idxs[v]);
        }
    }
    if (low[u] == idxs[u]) {
        // u is a root of an scc
        comps[sccidx].clear();
        int w;
        do {
            w = st.top(); st.pop();
            onStack[w] = false;
            comps[sccidx].push_back(w);
            comp[w] = sccidx;
        } while (w != u);
        sccidx++;
    }
}

for (int i = 1; i <= n; i++) {
    if (idxs[i] == -1) scc(i);
}

for (int u = 1; u <= n; u++) {
    for (int v : adj[u]) {
        if (comp[u] != comp[v]) adjscc[comp[u]].insert(comp[v]);
    }
}

// dfs idxs now range from 0 to dfsidx-1
// scc idxs now range from 0 to sccidx-1

```

2.16 Travelling Salesman Problem

Both of these solutions run in $O(N^2 \cdot 2^N)$ time.

2.16.1 Bottom Up

```

int full = (1 << n) - 1;
for (int mask = 0; mask <= full; mask++) {
    for (int i = 0; i < n; i++) {

```

```

        dp[mask][i] = INF;
    }
}
dp[1][0] = 0; // assume source is node 0
for (int mask = 1; mask <= full; mask++) {
    for (int i = 0; i < n; i++) {
        if (!(mask & (1 << i)) || dp[mask][i] >= INF) continue;
        for (int j = 0; j < n; j++) {
            if (mask & (1 << j)) continue;
            if (adj[i][j] >= INF) continue;
            int newMask = mask | (1 << j);
            dp[newMask][j] = min(dp[newMask][j], dp[mask][i] + adj[i][j]);
        }
    }
}
ll ans = INF;
for (int i = 0; i < n; i++) {
    if (adj[i][0] < INF) {
        // close the tour
        ans = min(ans, dp[full][i] + adj[i][0]);
    }
}

```

2.16.2 Top Down

```

ll adj[MAXN][MAXN], dp[1 << MAXN][MAXN];

ll tsp(int mask, int pos) {
    if (mask == (1 << n) - 1) {
        // assume node 0 is the start and end
        return adj[pos][0] < INF ? adj[pos][0] : INF;
    }
    if (dp[mask][pos] != -1) return dp[mask][pos];
    ll ans = INF;
    for (int i = 0; i < n; i++) {
        if ((mask & (1 << i)) == 0 && adj[pos][i] < INF) {
            ans = min(ans, adj[pos][i] + tsp(mask | (1 << i), i));
        }
    }
    return dp[mask][pos] = ans;
}

memset(dp, -1, sizeof(dp));
ll res = tsp(1, 0); // initial mask has source visited

```

2.17 Max Flow / Min Cut

Using Dinic's Algorithm, runs in $O(V^2E)$ for the general case. For graph with unit capacity, $O(E\sqrt{E})$. For unit network (unit capacity and either unique incoming or outgoing edge), $O(E\sqrt{V})$.

```

const long long INF = 1e18;

struct Dinic {
    struct Edge {
        int u, v;
        long long cap, flow;
        int rid;
    };

```

```

        int id;
    };

    struct EdgeRef {
        int u, idx;
    };

    vector<vector<Edge>> adj;
    vector<long long> dist, ptr;
    vector<EdgeRef> edge_lookup;

    Dinic(int n) : adj(n), dist(n), ptr(n) {}

    inline int in(int u) { return 2 * u; }
    inline int out(int u) { return 2 * u + 1; }

    int addNodeCap(int u, long long cap) {
        return addEdge(in(u), out(u), cap);
    }

    int addEdgeBetweenNodes(int u, int v, long long cap) {
        return addEdge(out(u), in(v), cap);
    }

    int addEdge(int u, int v, long long cap) {
        int u_idx = adj[u].size();
        int v_idx = adj[v].size();
        int lookup_id = edge_lookup.size();
        edge_lookup.push_back({u, u_idx});
        adj[u].push_back({u, v, cap, 0, v_idx, lookup_id});
        adj[v].push_back({v, u, 0, 0, u_idx, -1});
        return lookup_id;
    }

    void updateCap(int id, long long new_cap) {
        EdgeRef ref = edge_lookup[id];
        adj[ref.u][ref.idx].cap = new_cap;
    }

    long long getFlow(int id) {
        EdgeRef ref = edge_lookup[id];
        return adj[ref.u][ref.idx].flow;
    }

    bool bfs(int s, int t) {
        fill(dist.begin(), dist.end(), -1);
        queue<int> q;
        dist[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (auto &e : adj[u]) {
                if (e.cap - e.flow > 0 && dist[e.v] == -1) {
                    dist[e.v] = dist[u] + 1;
                    q.push(e.v);
                }
            }
        }
    }
}

```

```

        return dist[t] != -1;
    }

    long long dfs(int u, int t, long long f) {
        if (u == t || f == 0) return f;
        for (; ptr[u] < adj[u].size(); ptr[u]++) {
            Edge &e = adj[u][ptr[u]];
            if (dist[u] + 1 != dist[e.v] || e.cap - e.flow == 0) continue;
            long long pushed = dfs(e.v, t, min(f, e.cap - e.flow));
            if (pushed > 0) {
                e.flow += pushed;
                adj[e.v][e.rid].flow -= pushed;
                return pushed;
            }
        }
        return 0;
    }

    long long flow(int s, int t) {
        long long res = 0;
        while (bfs(s, t)) {
            fill(ptr.begin(), ptr.end(), 0);
            while (long long cflow = dfs(s, t, INF)) res += cflow;
        }
        return res;
    }

    void resetFlow() {
        for (int i = 0; i < adj.size(); i++) {
            for (auto &e : adj[i]) {
                e.flow = 0;
            }
        }
    }

    vector<int> getSComponent() {
        vector<int> s_comp;
        for (int i = 0; i < adj.size(); i++) {
            if (dist[i] != -1) s_comp.push_back(i);
        }
        return s_comp;
    }

    vector<int> getTComponent() {
        vector<int> t_comp;
        for (int i = 0; i < adj.size(); i++) {
            if (dist[i] == -1) t_comp.push_back(i);
        }
        return t_comp;
    }

    vector<Edge> getCutEdges() {
        vector<Edge> cut;
        for (int u = 0; u < adj.size(); u++) {
            if (dist[u] != -1) {
                for (auto &e : adj[u]) {
                    if (e.id != -1 && dist[e.v] == -1) {
                        cut.push_back(e);
                    }
                }
            }
        }
    }

```



```

        }
    }
}
return cut;
}

vector<Edge> getUsedEdges() {
    vector<Edge> used;
    for (int u = 0; u < adj.size(); u++) {
        for (auto &e : adj[u]) {
            if (e.id != -1 && e.flow > 0) {
                used.push_back(e);
            }
        }
    }
    return used;
}

};

Dinic solver(n); // Use n for standard max flow
Dinic solver(2 * n); // Use 2 * n for max flow with node capacities

// Returns edge id
solver.addEdge(u, v, c); // Add edge for standard max flow
// For graph with node capacities
solver.in(u); // Logical input vertex
solver.out(u); // Logical output vertex
solver.addEdgeBetweenNodes(u, v, c); // Add edge between nodes
solver.addNodeCap(u, c); // Add node capacity

solver.updateCap(edge_id, c); // Set new edge capacity

// Returns flow value
solver.resetFlow();
solver.flow(s, t); // Get max flow
solver.getFlow(edge_id); // Access specific flow value on edge

// Accesssing more information
vector<int> s_side = solver.getSComponent(); // Get source component
vector<int> t_side = solver.getTComponent(); // Get sink component
vector<Dinic::Edge> cut = solver.getCutEdges(); // Get edges on min cut
vector<Dinic::Edge> es = solver.getUsedEdges(); // Get edges used in max flow

```

2.18 Trees

2.18.1 Pre/Postorder Traversal

Runs in $O(V)$.

```

int prec = 0, postc = 0;
void dfs(int x, int p) {
    pre[x] = prec++;
    for(int y : adj[x]) {
        if (y != p) dfs(y, x);
    }
    post[x] = postc++;
}

```

2.18.2 Subtree to Range

Runs in $O(V)$.

```
int dfs(int x, int p) {
    pre[x] = c++;
    rig[pre[x]] = pre[x];
    for (int y : adj[x]) {
        if (y != p) {
            rig[pre[x]] = max(rig[pre[x]], dfs(y, x));
        }
    }
    return rig[pre[x]];
}
// Subtree -> pre[x], rig[pre[x]]
// Node Index -> pre[x]
// Range of Children -> pre[x]+1, rig[pre[x]]
```

2.18.3 Weighted Maximum Independent Set

Runs in $O(V)$.

```
int dp[MAXN][2];

int mis(int v, bool take, int p) {
    if (dp[v][take] != -1) return dp[v][take];
    int ans = take * c[v];
    for (int u : adj[v]) {
        if (u == p) continue;
        int temp = mis(u, 0, v);
        if (!take) temp = max(temp, mis(u, 1, v));
        ans += temp;
    }
    return dp[v][take] = ans;
}

void ans(int v, bool take, int p) {
    for (int u : adj[v]) {
        if (u == p) continue;
        int temp0 = dp[u][0], temp1 = (take ? -1 : dp[u][1]);
        if (temp0 > temp1) ans(u, 0, v);
        else { a.push_back(u); ans(u, 1, v); }
    }
}

memset(dp, -1, sizeof(dp));
mis(0, 0, -1); // don't take root
mis(0, 1, -1); // take root
if (dp[0][1] > dp[0][0]) { a.push_back(0); ans(0, 1, -1); }
else ans(0, 0, -1);
```

2.18.4 Diameter

Runs in $O(V)$.

```
pi dfs(int x, int p, int d) {
    pi b = {x, d};
    for (pi y : adj[x]) {
        if (y.first != p) {
            pi c = dfs(y.first, x, d + y.second);
        }
    }
    return b;
}
```

```

        if (c.second > b.second) b = c;
    }
}
return b;
}
pi s = dfs(0, -1, 0);
pi e = dfs(s.first, -1, 0);
// e.second gives diameter
// For even diameter, centroid is at e.second / 2
// For odd diameter, centroid is at e.second / 2 and e.second / 2 + 1

```

2.18.5 2^K Decomposition

$O(N \log N)$ precomputation and memory, $O(\log N)$ query.

```

int par(int x, int k) {
    for(int i = MAXLOGN; i >= 0; i--) {
        if (k >= (1 << i)) {
            if(x == -1) return x;
            x = p[x][i];
            k -= (1 << i);
        }
    }
    return x;
}

int p[MAXN][MAXLOGN];
memset(p, -1, sizeof(p));
dfs(0); // compute initial parent p[i][0]
for (int k = 1; k <= MAXLOGN; k++) {
    for (int i = 0; i < n; i++) {
        if(p[i][k-1] != -1) p[i][k] = p[p[i][k-1]][k-1];
    }
}

```

2.18.6 Lowest Common Ancestor

Runs in $O(\log N)$.

```

int lca(int x, int y) {
    // make both nodes the same depth
    if (dep[x] < dep[y]) swap(x, y);
    for (int k = MAXLOGN; k >= 0; k--) {
        if (p[x][k] != -1 && dep[p[x][k]] >= dep[y]) x = p[x][k];
    }
    if (x == y) return x;
    // perform binary lifting while parents are different
    for (int k = MAXLOGN; k >= 0; k--) {
        if (p[x][k] != p[y][k]) {
            x = p[x][k];
            y = p[y][k];
        }
    }
    // find the next parent
    return p[x][0];
}

```

2.18.7 Shortest Path

Runs in $O(\log N)$.

```
int distance(int x, int y) {
    return dist[x] + dist[y] - 2 * dist[lca(x, y)];
}
```

2.18.8 Heavy Light Decomposition

$O(N)$ precomputation, $O(\log N)$ query (excluding $O(\log N)$ from data structure).

```
// Requires segment tree, supports path maximum queries

vector<pi> adj[MAXN];
int par[MAXN], dep[MAXN], heavy[MAXN], head[MAXN], pos[MAXN], cpos = 0;
// heavy: heavy child, head: start of chain, pos: position in segment tree

int dfs(int x, int p) {
    int sz = 1, maxc = 0;
    par[x] = p;
    for (pi y : adj[x]) {
        if (y.s != p) {
            dep[y.s] = dep[x] + 1;
            int csz = dfs(y.s, x);
            sz += csz;
            if (csz > maxc) {
                maxc = csz;
                heavy[x] = y.s;
            }
        }
    }
    return sz;
}

void decomp(int x, int h) {
    head[x] = h; pos[x] = cpos++;
    if (heavy[x] != -1) decomp(heavy[x], h);
    for (pi y : adj[x]) {
        if (y.s == par[x]) continue;
        if (y.s != heavy[x]) decomp(y.s, y.s);
        root->update(pos[y.s], y.f);
    }
}

int query(int a, int b) {
    int res = 0;
    for (; head[a] != head[b]; b = par[head[b]]) {
        // maintain b as deeper
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
        res = max(res, root->query(pos[head[b]], pos[b]));
    }
    // a and b are now on the same chain
    if (dep[a] > dep[b]) swap(a, b);
    res = max(res, root->query(pos[a]+1, pos[b]));
    return res;
}

memset(heavy, -1, sizeof(heavy));
```

```

dep[0] = 0;
dfs(0, -1);
decomp(0, 0);

```

2.18.9 Centroid Decomposition

$O(N \log N)$ precomputation, $O(\log N)$ updates and queries.

```

// Example: Xenia and Tree
// Update: Mark a node red
// Query: Find distance to closest red node to query node

int sz[MAXN], par[MAXN], lvl[MAXN];
ll dist[MAXN][MAXLOGN], best[MAXN];

// find subtree sizes
int dfsSize(int x, int p) {
    sz[x] = 1;
    for (int y : adj[x]) {
        if (lvl[y] != -1 || y == p) continue;
        sz[x] += dfsSize(y, x);
    }
    return sz[x];
}

// find centroid of each subtree
int dfsCentroid(int x, int p, int n) {
    for (int y : adj[x]) {
        if (lvl[y] != -1 || y == p) continue;
        if (sz[y] > n / 2) return dfsCentroid(y, x, n);
    }
    // current node is centroid
    return x;
}

void dfsDist(int x, int p, int level, ll d) {
    dist[x][level] = d;
    for (int y : adj[x]) {
        if (lvl[y] != -1 || y == p) continue;
        dfsDist(y, x, level, d + 1);
    }
}

void build(int x, int p, int level) {
    // find subtree sizes and centroid
    int size = dfsSize(x, -1);
    int cent = dfsCentroid(x, -1, size);
    if (p == -1) p = cent;
    par[cent] = p; // set parent of centroid to previous centroid
    lvl[cent] = level;
    dfsDist(cent, -1, level, 0);
    // recursively build subtrees
    for (int y : adj[cent]) {
        if (lvl[y] != -1) continue;
        build(y, cent, level + 1);
    }
}

```

```

void update(int x) {
    int y = x;
    int level = lvl[x];
    while (level != -1) {
        // shortest distance from y to any red node
        // update using new node x and its distance to the centroid y
        best[y] = min(best[y], dist[x][level]);
        y = par[y];
        level--;
    }
}

11 query(int x) {
    11 res = INF;
    int y = x;
    int level = lvl[x];
    while (level != -1) {
        // shortest distance to any red node in centroid chain
        res = min(res, best[y] + dist[x][level]);
        y = par[y];
        level--;
    }
    return res;
}

memset(lvl, -1, sizeof(lvl));
fill(best, best+n, INF);
build(0, -1, 0);
update(0); // adding a node to be considered
query(y); // querying with all considered nodes

```

3 Dynamic Programming

DP Algorithm	Complexity	Notes
Maxsum	$O(N)$	
LIS - Naive	$O(N^2)$	
LIS - DS / Fast DP	$O(N \log N)$	
Coin Combinations	$O(NV)$	
Coin Change	$O(NV)$	
Knapsack - 0-1	$O(NS)$	
Knapsack - 0-1 No Values	$O(NX/64)$	
Knapsack - 0-K Binary	$O(S \sum \log K)$	
Knapsack - 0-K Queue	$O(NS)$	
Digit DP	$O(D)$	
Convex Hull Trick	$O(1)$ insertion and query	Amortized
Li Chao Tree	$O(\log X)$ insertion and query	
Divide and Conquer	$O(N \log N)$	From $O(N^2)$
LCS	$O(N^2)$	
LCS - LIS	$O(N \log N)$	

3.1 Maxsum

3.1.1 1D

Kadane's Algorithm. Runs in $O(N)$.

```

int ans = nums[0], cur = nums[0];
for (int i = 1; i < nums.size(); i++) {
    if (cur < 0) cur = 0;
    cur += nums[i];
    ans = max(ans, cur);
}

```

3.2 Longest Increasing Subsequence

3.2.1 N^2 DP

```

int ans = 0, dp[n];
memset(dp, 0, sizeof(dp));
for (int i = 0; i < n; i++) {
    for (int j = 0; j < i; j++) {
        if (a[j] < a[i]) {
            dp[i] = max(dp[i], dp[j]);
        }
    }
    dp[i]++;
    ans = max(ans, dp[i]);
}

```

3.2.2 Data Structure Speedup

```

// Data structure should support point max updates and range max queries
// Discretise values first
for (int i = 0; i < n; i++) {
    t = query(a[i] - 1) + 1;
    update(a[i], t);
    ans = max(ans, t);
}

```

3.2.3 $N \log N$ DP

```

int len = 0, dp[n];
memset(dp, 0, sizeof(dp));
for (int x : a) {
    int pos = lower_bound(dp, dp + len, x) - dp;
    dp[pos] = x;
    if (pos == len) len++;
}
cout << len;

```

3.3 Coin Combinations

Runs in $O(N \cdot V)$.

```

int ways[v+1];
memset(ways, 0, sizeof(ways));
ways[0] = 1;
for (int i = 0; i < n; i++) {
    int c = coins[i];
    for (int sum = c; sum <= v; sum++) {
        ways[sum] = (ways[sum] + ways[sum - c]) % MOD;
    }
}

```

```

    }
}
cout << ways[v];

```

3.4 Coin Change

Runs in $O(N \cdot V)$.

```

const int INF = 1e9;
vector<int> dp(v + 1, INF);
dp[0] = 0;
for (int i = 1; i <= v; i++) {
    for (int j = 0; j < n; j++) {
        if (i >= c[j] && dp[i - c[j]] != INF) {
            dp[i] = min(dp[i], dp[i - c[j]] + 1);
        }
    }
}
cout << dp[v];

```

3.5 Knapsack

3.5.1 0-1

Runs in $O(N \cdot S)$.

```

for (int i = 0; i < n; i++) {
    for (int j = s; j >= w[i]; j--) {
        dp[j] = max(dp[j], dp[j - w[i]] + v[i]);
    }
}
cout << dp[s];

```

3.5.2 0-1 No Values

Runs in $O(N \cdot X/64)$.

```

bitset<MAXX> dp;
dp[0] = 1;
for (int i = 0; i < n; i++) {
    dp |= dp << w[i];
}
cout << dp[x];

```

3.5.3 0-K Binary Grouping

Runs in $O(S \cdot \sum \log K)$.

```

for(int i = 0; i < n; i++){
    cin >> v >> w >> k;
    k = min(k, s/w);
    c = 1;
    while (k) {
        int ck = min(c, k);
        items.push_back({ v*ck, w*ck });
        k -= ck;
        c <+= 1;
    }
}

```

```
}
```

```
// apply normal knapsack
```

3.5.4 0-K Monotonic Queue

Runs in $O(N \cdot S)$.

```
for (int i = 0; i < N; i++) {
    long long v, w, k;
    cin >> v >> w >> k;
    if (w > S || k == 0) continue;
    k = min(k, S / w); // limit k
    ndp = dp;
    // process residue classes mod w by considering multiples
    for (int r = 0; r < w; r++) {
        // j = r + x * w, find range of x
        int X = (S - r) / w;
        deque<int> dq; // stores x indices, in decreasing values of dp[r+x*w] - v*x

        auto val = [&](int x) -> long long {
            return dp[r + x * w] - v * x;
        };

        for (int x = 0; x <= X; x++) {
            // remove out of window indices, need (x - t) <= k => t >= x - k
            while (!dq.empty() && dq.front() < x - k) dq.pop_front();

            // push current x
            while (!dq.empty() && val(dq.back()) <= val(x)) dq.pop_back();
            dq.push_back(x);

            // best is at front of deque
            // ndp[r+x*w] = max_{t in [x-k, x]} dp[r+t*w] + (x-t)*v
            //                = v*x + max_{t} (dp[r+t*w] - v*t)
            long long best = val(dq.front()) + v * x;
            int j = r + x * w;
            if (best > ndp[j]) ndp[j] = best;
        }
    }
    dp.swap(ndp);
}
```

3.6 Digit DP

Runs in $O(D)$.

```
// Example - Numbers
// Compute the number of palindrome free numbers in a given range

vector<int> num;
11 dp[20][11][11][2][2]; // idx, last1, last2, tight, hasStarted

11 derp(int pos, int last1, int last2, bool tight, bool hasStarted) {
    if(pos == num.size()) return 1; // successfully populated whole number

    if(dp[pos][last1][last2][tight][hasStarted] != -1) {
        // state already visited
    }
}
```

```

        return dp[pos][last1][last2][tight][hasStarted];
    }

    ll res = 0;
    int limit = tight ? num[pos] : 9; // do we need to keep to the range
    for(int d = 0; d <= limit; d++) { // try all next digits
        bool newHasStarted = hasStarted || (d != 0);
        bool newTight = tight && (d == limit);
        // skip palindromes only if the number has started
        if(newHasStarted) {
            if(d == last1) continue; // palindrome length 2
            if(d == last2) continue; // palindrome length 3
        }
        int newLast1 = newHasStarted ? d : 10;
        int newLast2 = hasStarted ? last1 : 10;
        res += derp(pos+1, newLast1, newLast2, newTight, newHasStarted);
    }
    return dp[pos][last1][last2][tight][hasStarted] = res;
}

// convert number to digits
void dcmp(ll x){
    num.clear();
    if(x == 0) num.push_back(0);
    while(x > 0) {
        num.push_back(x % 10);
        x /= 10;
    }
    reverse(num.begin(), num.end());
}

// Total Valid with value <= x
// Use PIE to get number within [a, b]
ll solve(ll x){
    dcmp(x);
    memset(dp, -1, sizeof(dp));
    return derp(0, 10, 10, true, false);
}

// To compute the kth string satisfying
// Either binary search or build character by character:
int count = 0;
vector<int> ans;
for (int i = 0; i < n; i++) {
    int x = 0;
    for (int j = 1; j < 10; j++) { // adjust to size of alphabet
        if (count + dp(i, j) > k) {
            break;
        }
        x = j;
    }
    count += dp(i, x); // position i is bounded by x
    ans.push_back(x);
}

```

3.7 Convex Hull Trick

Supports insertion and queries in amortised $O(1)$.

```
// Example: Commando
// Partition into contiguous groups with maximal effectiveness
// Group effectiveness is a quadratic function of their sum
// dp(x) = max(dp(i)+f(p(x)-p(i)))
//         = max(dp(i)+a(p(x)-p(i))^2+b(p(x)-p(i))+c)
//         = max(dp(i)+ap(x)^2-2ap(x)p(i)+ap(i)^2+bp(x)-bp(i))+c
//         = max(dp(i)+ap(i)^2-bp(i)-2ap(x)p(i))+ap(x)^2+bp(x)+c
//         = max([dp(i)+ap(i)^2-bp(i)][-2ap(i)][p(x)])[+ap(x)^2+bp(x)+c]
//         = max(c(i)+m(i)p(x))+v(x)
// c(i) = dp(i)+ap(i)^2-bp(i)
// m(i) = -2ap(i)
// v(x) = ap(x)^2+bp(x)+c
// Lines have increasing gradients, queries have increasing x

deque<pi> hull;

ll func(pi line, ll x){
    return line.first*x+line.second;
}

ld intersection(ll m1, ll c1, ll m2, ll c2) {
    return (ld) (c2-c1) / (m1-m2);
}

ld intersect(pi x, pi y) {
    return intersection(x.first, x.second, y.first, y.second);
}

// query maximum y at x
ll query(ll x) {
    while (hull.size() > 1) {
        if (func(hull[0], x) < func(hull[1], x)) {
            hull.pop_front();
        } else break;
    }
    return func(hull[0], x);
}

// insert new line
void insert(ll m, ll c) {
    pi line = pi(m, c);
    while (hull.size() > 1) {
        ll s = hull.size();
        if (intersect(hull[s-1], line) <= intersect(hull[s-2], line)) {
            hull.pop_back();
        } else break;
    }
    hull.push_back(line);
}

insert(0, 0); // dp[0]
for(int i = 1; i <= n; i++){
    dp[i] = query(ps[i])+a*ps[i]*ps[i]+b*ps[i]+c; // max(mx + c) + v
    insert(-2*a*ps[i], dp[i]+a*ps[i]*ps[i]-b*ps[i]); // insert new (m, c)
}
```

3.8 Li Chao Tree

Supports insertion and queries in $O(\log X)$ time where X is the domain.

```
struct Node {
    ll m, c;
    Node *lc, *rc;
    Node(ll _m = 0, ll _c = -INF) {
        m = _m; c = _c;
        lc = nullptr; rc = nullptr;
    }
    ll value(ll x) {
        return m * x + c;
    }
    void insert(ll nm, ll nc, ll l, ll r) {
        ll mid = (l+r)/2;
        bool leftCheck = nm * l + nc > value(l);
        bool midCheck = nm * mid + nc > value(mid);
        if (midCheck) {
            swap(m, nm);
            swap(c, nc);
        }
        if (r-l == 1) return;
        if (leftCheck != midCheck) {
            if (!lc) lc = new Node();
            lc->insert(nm, nc, l, mid);
        } else {
            if (!rc) rc = new Node();
            rc->insert(nm, nc, mid, r);
        }
    }
    ll query(ll x, ll l, ll r) {
        ll res = value(x);
        if (r-l == 1) return res;
        ll mid = (l+r)/2;
        if (x < mid && lc) return max(res, lc->query(x, l, mid));
        if (x >= mid && rc) return max(res, rc->query(x, mid, r));
        return res;
    }
};

// Queries are on half open [L, R)
// Example: Commando
Node *root = new Node();
root->insert(0, 0, MINX, MAXX);
for (int i = 1; i <= n; i++) {
    // query lct
    ll x = p[i];
    ll best = root->query(x, MINX, MAXX);
    dp[i] = best + a*x*x + b*x + c;
    // update lct
    ll m = -2*a*x;
    ll c = dp[i] + a*x*x - b*x;
    root->insert(m, c, MINX, MAXX);
}
```

3.9 Divide and Conquer

Reduces complexity from $O(N^2 \cdot K)$ to $O(N \log N \cdot K)$.

```

// Example: Guards
// Minimise sum of costs where cost of partition is length * sum
// DP has form  $dp(i, j) = \min dp(i-1, k-1) + C(k, j)$ 
//  $i$  is the current layer,  $k$  to  $j$  is the new group
// Cost function satisfies quadrangle inequality:
//  $C(a, c) + C(b, d) \leq C(a, d) + C(b, c)$  for  $a \leq b \leq c \leq d$ 

long long cost(int s, int e) {
    return (ps[e]-ps[s-1])*(e-s+1);
}

void dnc(int s, int e, long long x, int y, int k) {
    if(s > e) return;
    int m = (s+e)/2, best = 0;
    dp[m][k] = INF;
    for (int i = x; (i <= y && i <= m); i++) {
        ll val = dp[i][!k]+cost(i+1, m);
        if (dp[m][k] > val) {
            dp[m][k] = val;
            best = i;
        }
    }
    if (s < m) dnc(s, m-1, x, best, k);
    if (m < e) dnc(m+1, e, best, y, k);
}

// Uses DP on the fly to save space
for (int i = 1; i <= n; i++) dp[i][0] = INF;
for (int i = 1; i <= g; i++) {
    for (int j = 1; j <= n; j++) dp[j][i%2] = INF;
    dnc(0, n, 0, n, i%2);
}

```

3.10 Longest Common Subsequence

3.10.1 N^2 DP

```

int dp[MAXN][MAXM];
int lcs(int i, int j) {
    if (i == 0 || j == 0) return 0;
    if (dp[i][j] != -1) return dp[i][j];
    dp[i][j] = max(lcs(i-1, j), lcs(i, j-1));
    if (a[i-1] == b[j-1]) dp[i][j] = max(dp[i][j], lcs(i-1, j-1) + 1);
    return dp[i][j];
}

memset(dp, -1, sizeof(dp));

```

3.10.2 LIS Reduction

Array a cannot have duplicates.

```

for (int i = 0; i < n; i++) {
    cin >> a[i].first;
    a[i].second = i+1;
}
for (int i = 0; i < m; i++) {

```

```

        cin >> b[i];
    }
    sort(a, a+n);
    for (int i = 0; i < m; i++) {
        p = lower_bound(a, a+n, pi(b[i], 0));
        if (p != a+n) c.push_back(p->second);
    }
    // Perform LIS on c

```

4 Math

4.1 Fast Exponentiation

Runs in $O(\log b)$.

```

int powmod(int a, int b, int m) {
    int res = 1;
    while (b > 0) {
        if (b & 1) res = (res * a) % m;
        a = (a * a) % m;
        b >>= 1;
    }
    return res % m;
}

```

4.2 Prime Factorisation

Runs in $O(\sqrt{x})$.

```

map<int, int> cnt;
while (x % 2 == 0) {
    cnt[2]++;
    x /= 2;
}
for (int i = 3; i * i <= x; i++) {
    while (x % i == 0) {
        cnt[i]++;
        x /= i;
    }
}
if (x > 1) {
    cnt[x]++;
}

```

4.3 Sieve of Eratosthenes

Runs in $O(n \log \log n)$ with high constant.

```

bitset<MAXN> prime;
prime.set();
prime[0] = prime[1] = 0;
for (int i = 2; i < MAXN; i++) {
    if (prime[i]) {
        for (int j = i*i; j < MAXN; j += i) {
            prime[j] = 0;
        }
    }
}

```

4.4 Greatest Common Divisor

Runs in $O(\log \min(a, b))$.

```
int gcd(int a, int b) {
    if (a > b) swap(a, b);
    while (a != 0) {
        b %= a;
        swap(a, b);
    }
    return b;
}
```

4.5 Lowest Common Multiple

```
int lcm(int a, int b) {
    return a / gcd(a, b) * b;
}
```

4.6 Modular Inverse

For prime modulo.

```
ll modinv(ll a){
    return powmod(a, MOD-2, MOD);
}
```

4.7 $\binom{n}{k}$

Precomputation takes $O(MAXN)$ time, queries answered in $O(1)$.

```
ll fac[MAXN+1], modinv[MAXN+1];

ll nck(ll n, ll k) {
    if (n < k) return 0;
    ll res = fac[n];
    res = (res * modinv[k]) % MOD;
    res = (res * modinv[n-k]) % MOD;
    return res;
}

fac[0] = 1;
for(int i = 1; i <= MAXN; i++) {
    fac[i] = fac[i-1] * i % MOD;
}
modinv[MAXN] = powmod(fac[MAXN], MOD-2, MOD);
for(int i = MAXN; i > 0; i--) {
    modinv[i-1] = modinv[i] * i % MOD;
}
```

4.8 Fibonacci

Runs in $O(\log N)$ time.

```
struct Mat {
    ll a, b, c, d; // 2x2 Matrix: [a b; c d]
};
```

```

Mat mul(Mat x, Mat y) {
    return {
        x.a*y.a + x.b*y.c,
        x.a*y.b + x.b*y.d,
        x.c*y.a + x.d*y.c,
        x.c*y.b + x.d*y.d
    };
}

Mat mpow(Mat base, long long exp) {
    Mat res = {1, 0, 0, 1}; // Identity Matrix
    while (exp) {
        if (exp & 1) res = mul(res, base);
        base = mul(base, base);
        exp >>= 1;
    }
    return res;
}

ll fib(long long n) {
    if (n == 0) return 0;
    Mat m = {1, 1, 1, 0}; // Fibonacci Seed Matrix
    return mpow(m, n-1).a;
}

```

4.9 Convex Hull

Using Monotone Chain Algorithm, runs in $O(N \log N)$ time.

```

struct pt {
    double x, y;
};

int orientation(pt a, pt b, pt c) {
    double v = a.x*(b.y-c.y)+b.x*(c.y-a.y)+c.x*(a.y-b.y);
    if (v < 0) return -1; // clockwise
    if (v > 0) return +1; // counter-clockwise
    return 0;
}

bool cw(pt a, pt b, pt c, bool includeCollinear) {
    int o = orientation(a, b, c);
    return o < 0 || (includeCollinear && o == 0);
}

bool ccw(pt a, pt b, pt c, bool includeCollinear) {
    int o = orientation(a, b, c);
    return o > 0 || (includeCollinear && o == 0);
}

// Monotone Chain Algorithm
void convexHull(vector<pt>& a, bool includeCollinear = false) {
    if (a.size() == 1) return;
    sort(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.x, a.y) < make_pair(b.x, b.y);
    });
    pt p1 = a[0], p2 = a.back();

```



```

vector<pt> up, down;
up.push_back(p1);
down.push_back(p1);
for (int i = 1; i < (int)a.size(); i++) {
    if (i == a.size() - 1 || cw(p1, a[i], p2, includeCollinear)) {
        while (up.size() >= 2 &&
            !cw(up[up.size()-2], up[up.size()-1],
                a[i], includeCollinear)) {
            up.pop_back();
        }
        up.push_back(a[i]);
    }
    if (i == a.size() - 1 || ccw(p1, a[i], p2, includeCollinear)) {
        while (down.size() >= 2 &&
            !ccw(down[down.size()-2], down[down.size()-1],
                a[i], includeCollinear)) {
            down.pop_back();
        }
        down.push_back(a[i]);
    }
}
if (includeCollinear && up.size() == a.size()) {
    reverse(a.begin(), a.end());
    return;
}
a.clear();
for (int i = 0; i < up.size(); i++) {
    a.push_back(up[i]);
}
for (int i = down.size() - 2; i > 0; i--) {
    a.push_back(down[i]);
}
}

```

4.10 Furthest Pair of Points

Using Rotating Calipers, runs in $O(H)$ time.

```

struct pt {
    double x, y;
    int id; // original index
};

// Include Convex Hull code here

// Squared Distance
ll dist2(const pt &a, const pt &b) {
    ll dx = (ll)(a.x - b.x);
    ll dy = (ll)(a.y - b.y);
    return dx * dx + dy * dy;
}

// Rotating Calipers
pair<int, int> farthestPair(const vector<pt> &hull) {
    int n = hull.size();
    if (n == 1) return {hull[0].id, hull[0].id};
    if (n == 2) return {hull[0].id, hull[1].id};
}

```

```

    ll best = 0;
    pair<int, int> ans = {hull[0].id, hull[1].id};

    int j = 1;
    for (int i = 0; i < n; i++) {
        int ni = (i + 1) % n;
        while (true) {
            int nj = (j + 1) % n;
            ll cur = llabs(
                (ll)(hull[ni].x - hull[i].x) * (hull[j].y - hull[i].y)
                - (ll)(hull[ni].y - hull[i].y) * (hull[j].x - hull[i].x)
            );
            ll nxt = llabs(
                (ll)(hull[ni].x - hull[i].x) * (hull[nj].y - hull[i].y)
                - (ll)(hull[ni].y - hull[i].y) * (hull[nj].x - hull[i].x)
            );
            if (nxt > cur) j = nj;
            else break;
        }

        ll d1 = dist2(hull[i], hull[j]);
        if (d1 > best) {
            best = d1;
            ans = {hull[i].id, hull[j].id};
        }

        ll d2 = dist2(hull[ni], hull[j]);
        if (d2 > best) {
            best = d2;
            ans = {hull[ni].id, hull[j].id};
        }
    }
    return ans;
}

convexHull(pts, false);
pair<int, int> ans = farthestPair(pts);

```

4.11 Nearest Pair of Points

Using Shamos-Hoey, runs in $O(N \log N)$ time.

```

struct pt {
    long long x, y;
    int id;
};

struct cmp_x {
    bool operator()(const pt &a, const pt &b) const {
        if (a.x != b.x) return a.x < b.x;
        return a.y < b.y;
    }
};

struct cmp_y {
    bool operator()(const pt &a, const pt &b) const {
        return a.y < b.y;
    }
}

```

```

};

vector<pt> a, t;
long long mindist;
pair<int, int> best_pair;

// Square Distance
inline long long dist2(const pt &a, const pt &b) {
    long long dx = a.x - b.x;
    long long dy = a.y - b.y;
    return dx * dx + dy * dy;
}

// Compare and update
inline void update(const pt &a, const pt &b) {
    long long d = dist2(a, b);
    if (d < mindist) {
        mindist = d;
        best_pair = {a.id, b.id};
    }
}

void rec(int l, int r) {
    /// Handle small case naively
    if (r - l <= 3) {
        for (int i = l; i < r; i++)
            for (int j = i + 1; j < r; j++)
                update(a[i], a[j]);
        sort(a.begin() + l, a.begin() + r, cmp_y());
        return;
    }

    int m = (l + r) >> 1;
    long long midx = a[m].x;
    rec(l, m);
    rec(m, r);

    merge(a.begin() + l, a.begin() + m,
          a.begin() + m, a.begin() + r,
          t.begin(), cmp_y());
    copy(t.begin(), t.begin() + (r - l), a.begin() + l);

    int tsz = 0;
    for (int i = l; i < r; i++) {
        long long dx = a[i].x - midx;
        if (dx * dx < mindist) {
            for (int j = tsz - 1; j >= 0; j--) {
                long long dy = a[i].y - t[j].y;
                if (dy * dy >= mindist) break;
                update(a[i], t[j]);
            }
            t[tsz++] = a[i];
        }
    }
}

// Remember to check for duplicates
sort(a.begin(), a.end(), cmp_x());

```

```
mindist = LLONG_MAX;
best_pair = {0, 1};
rec(0, N);
```

5 Algorithms

5.1 Binary Search

Find the cuberoot of n . Runs in $O(\log N)$.

```
long long n; cin >> n;
long long mini = 0, maxi = 1e6, medi;
while (mini < maxi) {
    medi = mini+(maxi-mini)/2;
    if (medi * medi * medi >= n) maxi = medi;
    else mini = medi+1;
}
cout << mini << "\n";
```

5.2 Binary Search using Lifting

Find the cuberoot of n . Runs in $O(\log N)$.

```
long long n; cin >> n;
long long cur = 0, gap = 1e6, next;
while (gap > 0) {
    while (next = cur + gap, next * next * next < n) {
        cur = next;
    }
    gap >>= 1;
}
cout << cur+1 << "\n";
```

5.3 Sliding Set

Speeds up DP from $O(N^2)$ to $O(N \log N)$.

```
// Example - Candymountain
// Jump across with minimax candies
// Populate with initial window
for(int i = 0; i < k; i++) {
    dp[i] = candies[i];
    s.insert(candies[i]);
}
// Sliding Set
for(int i = k; i < n; i++){
    dp[i] = max(candies[i], *s.begin());
    s.erase(s.find(dp[i-k]));
    s.insert(dp[i]);
}
```

5.4 Sliding Window

Runs in $O(N)$.

```
// Example: Count number of subarrays with sum at least k
// All numbers are non-negative
int s = 0, sum = 0, ans = 0;
for (int i = 0; i < n; i++) {
    sum += a[i];
    while (sum >= k) {
        ans += (n-i);
        sum -= a[s];
        s++;
    }
}
```

5.5 Set Merging

Reduces complexity from $O(Q \cdot N \log N)$ to $O(N \log^2 N)$.

```
for (int i = 0; i < q; i++) {
    cin >> a >> b;
    // small to large merging
    if (s[a].size() > s[b].size()) swap(s[a], s[b]);
    for (int x : s[a]) s[b].insert(x);
    s[a].clear();
    cout << s[b].size() << "\n";
}
```

5.6 Discretisation

Runs in $O(N \log N)$.

```
vector<int> a(n);
vector<int> b = a;
sort(b.begin(), b.end());
b.erase(unique(b.begin(), b.end()), b.end());
for (int &i : a) {
    i = lower_bound(b.begin(), b.end(), i) - b.begin() + 1; // 1-indexed
}
// a now holds discretised values
```

5.7 Meet in the Middle

Reduces time complexity from $O(2^N)$ to $O(N \cdot 2^{N/2})$.

```
// Example: Bobek
// Count number of subsets with sum <= tgt
left = n/2; right = n-left;
vector<int> sums;
for (int i = 0; i < (1 << left); i++) {
    int cur = 0;
    for (int j = 0; j < left; j++) {
        if (i & (1 << j)) cur += a[j];
    }
    sums.push_back(cur);
}
sort(sums.begin(), sums.end());
for (int i = 0; i < (1 << right); i++) {
    int cur = 0;
    for (int j = 0; j < right; j++) {
```

```

        if (i & (1 << j)) cur += a[left + j];
    }
    ans += upper_bound(sums.begin(), sums.end(), tgt-cur) - sums.begin();
}

```

5.8 On the Fly

Reduces memory usage from $O(N \cdot K)$ to $O(N)$.

```

// Stolen from DNC code
// Use i%2 and !(i%2) for indexing
for (int i = 1; i <= g; i++) {
    for (int j = 1; j <= n; j++) dp[j][i%2] = INF;
    dnc(0, n, 0, n, i%2);
}

```

5.9 Square Root Decomposition

$O(N)$ precomputation, $O(1)$ update, $O(\sqrt{n})$ query.

```

// Point Update, Range Sum Query

vector<ll> a(n);
int blockSize = sqrt(n) + 1;
vector<ll> blocks(blockSize, 0);
// precomputation
for (int i = 0; i < n; i++) {
    blocks[i / blockSize] += a[i];
}
// update
blocks[k / blockSize] += u - a[k];
a[k] = u;
// query
ll sum = 0;
int s = l / blockSize;
int e = r / blockSize;
if (s == e) {
    for (int i = l; i <= r; i++) sum += a[i];
} else {
    for (int i = l; i < (s + 1) * blockSize; i++) sum += a[i];
    for (int b = s+1; b < e; b++) sum += blocks[b];
    for (int i = e * blockSize; i <= r; i++) sum += a[i];
}

```

5.10 Mo's Algorithm

Runs in $O((N + Q) \cdot \sqrt{N})$. Does not support online queries or updates.

```

struct Query {
    int l, r, idx;
};

vector<ll> a(n);
int blockSize = sqrt(n) + 1;
ll sum = 0;

bool cmp(const Query &x, const Query &y) {
    int bx = x.l / blockSize;

```

```

    int by = y.l / blockSize;
    if (bx != by) return bx < by;
    return (bx & 1) ? (x.r < y.r) : (x.r > y.r);
}

// modify to insert idx
void plus(int idx) {
    sum += a[idx];
}

// modify to remove idx
void minus(int idx) {
    sum -= a[idx];
}

// make sure indexes are 0-indexed
vector<Query> queries(q);
sort(queries.begin(), queries.end(), cmp);
vector<ll> ans(q);
int curL = 0, curR = -1;
for (Query &cq : queries) {
    while (curL > cq.l) plus(--curL);
    while (curR < cq.r) plus(++curR);
    while (curL < cq.l) minus(curL++);
    while (curR > cq.r) minus(curR--);
    ans[cq.idx] = sum;
}

```

6 Strings

6.1 Manacher's Algorithm

Runs in $O(N)$.

```

// for odd length palindromes, returns radius of palindrome at each index
vector<int> manacher(const string &s) {
    int n = s.size();
    vector<int> p(n);
    int l = 0, r = -1;
    for (int i = 0; i < n; i++) {
        int k = (i > r) ? 1 : min(p[l + r - i], r - i + 1);
        while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) {
            k++;
        }
        p[i] = k;
        if (i + k - 1 > r) {
            l = i - k + 1;
            r = i + k - 1;
        }
    }
    return p;
}

// surround with #s so we only have to run odd case
string s, t;
for (char c : s) {
    t.push_back('#');
    t.push_back(c);
}

```

```

t.push_back('#');
vector<int> p = manacher(t);
// handle # removal accordingly

```

6.2 Knuth-Morris-Pratt

Runs in $O(N)$.

```

// Returns prefix function
// p[i] is longest prefix of s[0..i] which is also a suffix of it

vector<int> kmp(string s) {
    int n = s.size();
    vector<int> p(n);
    for (int i = 1; i < n; i++) {
        int j = p[i - 1];
        while (j > 0 && s[i] != s[j]) {
            j = p[j - 1];
        }
        if (s[i] == s[j]) j++;
        p[i] = j;
    }
    return p;
}

// Example: Count how many times a pattern occurs in a text
string concat = pattern + '#' + text;
vector<int> p = kmp(concat);
int ans = 0;
for (int i = 0; i < pattern.size() + 1; i < p.size(); i++) {
    if (p[i] == pattern.size()) ans++;
}

```

6.3 Z-Function

Runs in $O(N)$.

```

// Z-Function: Longest strings that is a prefix of S and S starting from i
vector<int> zfunction(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i < r) {
            z[i] = min(r - i, z[i - l]);
        }
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            z[i]++;
        }
        if (i + z[i] > r) {
            l = i;
            r = i + z[i];
        }
    }
    z[0] = n;
    return z;
}

```

6.4 Suffix Array

Runs in $O(N \log N)$.

```
class SuffixArray {
private:
    string text;
    int n;

    // Sorting helper
    void sort_by_second_half(vector<int>& sa, const vector<int>& rank,
                           int h, int classes, vector<int>& cnt) {
        vector<int> pn(n);
        for (int i = 0; i < n; i++) {
            pn[i] = (sa[i] - h + n) % n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++) cnt[rank[pn[i]]]++;
        for (int i = 1; i < classes; i++) cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--) sa[--cnt[rank[pn[i]]]] = pn[i];
    }

    // Build suffix array
    void construct_sa() {
        const int alphabet_size = 256;
        vector<int> cnt(max(alphabet_size, n), 0);
        suffix_array.resize(n);
        rank_array.resize(n);

        for (int i = 0; i < n; i++) cnt[(unsigned char)text[i]]++;
        for (int i = 1; i < alphabet_size; i++) cnt[i] += cnt[i-1];
        for (int i = 0; i < n; i++) {
            suffix_array[--cnt[(unsigned char)text[i]]] = i;
        }

        rank_array[suffix_array[0]] = 0;
        int classes = 1;
        for (int i = 1; i < n; i++) {
            if (text[suffix_array[i]] != text[suffix_array[i-1]]) classes++;
            rank_array[suffix_array[i]] = classes - 1;
        }

        vector<int> next_rank(n);
        for (int h = 1; h < n; h <= 1) {
            sort_by_second_half(suffix_array, rank_array, h, classes, cnt);

            next_rank[suffix_array[0]] = 0;
            classes = 1;
            for (int i = 1; i < n; i++) {
                pair<int, int> current = {
                    rank_array[suffix_array[i]],
                    rank_array[(suffix_array[i] + h) % n]
                };
                pair<int, int> previous = {
                    rank_array[suffix_array[i-1]],
                    rank_array[(suffix_array[i-1] + h) % n]
                };
                if (current != previous) classes++;
                next_rank[suffix_array[i]] = classes - 1;
            }
        }
    }
};
```

```

    }
    rank_array = next_rank;
    if (classes == n) break;
}
}

void construct_lcp() {
    vector<int> inverse_sa(n);
    for (int i = 0; i < n; i++) inverse_sa[suffix_array[i]] = i;

    int match_len = 0;
    lcp_array.assign(n, 0);
    for (int i = 0; i < n; i++) {
        if (inverse_sa[i] == n - 1) {
            match_len = 0;
            continue;
        }
        int next_suffix_idx = suffix_array[inverse_sa[i] + 1];
        while (i + match_len < n && next_suffix_idx + match_len < n &&
            text[i + match_len] == text[next_suffix_idx + match_len]) {
            match_len++;
        }
        lcp_array[inverse_sa[i]] = match_len;
        if (match_len > 0) match_len--;
    }
}

public:
    vector<int> suffix_array;
    vector<int> lcp_array;
    vector<int> rank_array;

    SuffixArray(string input_text, bool add_terminal = true) {
        text = input_text;
        if (add_terminal) text += "$";
        n = text.size();
        construct_sa();
        construct_lcp();
    }

    // LCS of 2 strings, build with S + # + T
    // {s start, s end, t start, t end}
    vector<int> find_lcs(int split_point) {
        int max_len = 0;
        vector<int> res = {0, 0, 0, 0};

        for (int i = 0; i < n - 1; i++) {
            int p1 = suffix_array[i];
            int p2 = suffix_array[i+1];

            if ((p1 < split_point) != (p2 < split_point)) {
                if (p1 == split_point || p2 == split_point) continue;

                if (lcp_array[i] > max_len) {
                    max_len = lcp_array[i];
                    int start_s = (p1 < split_point) ? p1 : p2;
                    int start_t = (p1 < split_point) ? p2 : p1;
                }
            }
        }
    }

```

```

        int c_coord = start_t - (split_point + 1);
        res = {start_s, start_s + max_len,
               c_coord, c_coord + max_len};
    }
}
return res;
}

// Binary search for pattern in string
pair<int, int> find_pattern_range(const string& pattern) {
    int m = pattern.size();
    int first = -1, low = 0, high = n - 1;

    while (low <= high) {
        int mid = low + (high - low) / 2;
        if (text.substr(suffix_array[mid], m) >= pattern) {
            first = mid;
            high = mid - 1;
        } else low = mid + 1;
    }
    if (first == -1 || text.substr(suffix_array[first], m) != pattern) {
        return {-1, -1};
    }

    int last = -1;
    low = 0, high = n - 1;
    while (low <= high) {
        int mid = low + (high - low) / 2;
        if (text.substr(suffix_array[mid], m) <= pattern) {
            last = mid;
            low = mid + 1;
        } else high = mid - 1;
    }
    return {first, last};
}

// Count distinct substrings
long long count_distinct_substrings() {
    long long len = n - 1;
    long long total_substrings = len * (len + 1) / 2;
    long long duplicated_substrings = 0;
    for (int lcp_val : lcp_array) {
        duplicated_substrings += lcp_val;
    }
    return total_substrings - duplicated_substrings;
}

};

// Suffix Array
string s = "banana";
SuffixArray sa(s);
sa.suffix_array[i];
sa.lcp_array[i];

// Distinct Substrings
sa.count_distinct_substrings() << endl;

```

```

// Pattern Matching
string pattern = "ana";
pair<int, int> range = sa.find_pattern_range(pattern);
// Occurrences: [range.first, range.second]

// Longest Common Substring
string s1 = "apple pie";
string s2 = "the apple falls";
int split_point = s1.size();
SuffixArray sa_lcs(s1 + "#" + s2);
sa_lcs.find_lcs(split_point);

// Smallest Cyclic Shift
// Build without $
sa.suffix_array[0];

// Glossary
// sa[i] = j
// starting index j in original string of ith lexicographically smallest suffix

// lcp[i] = k, longest common prefix between sa[i] and sa[i-1]
// lcp[0] = 0

// rank[j] = i
// lexicographical rank i of suffix starting at j
// inverse of the sa, sa[i] = j <=> rank[j] = i.

```

7 Miscellaneous

7.1 Maximum Time complexity v/s N

Complexity	Maximum in 1s
$O(1)$	Infinite
$O(\log N)$	2^{10^6}
$O(\sqrt{N})$	10^{14}
$O(N)$	10^7
$O(N \log N)$	10^6
$O(N \sqrt{N})$	10^5
$O(N^2)$	10^4
$O(N^3)$	500
$O(N^4)$	100
$O(2^N)$	22
$O(N \times 2^N)$	20
$O(N!)$	12
$O(N \times N!)$	11

7.2 Fast I/O

Cannot use with `scanf`, `printf`.

```

ios_base::sync_with_stdio(false);
cin.tie(0);

```

7.3 Superfast I/O

Only for non-negative integer input.

```
inline ll ri () {
    ll x = 0;
    char ch = getchar_unlocked();
    while (ch < '0' || ch > '9') ch = getchar_unlocked();
    while (ch >= '0' && ch <= '9') {
        x = (x << 3) + (x << 1) + ch - '0';
        ch = getchar_unlocked();
    }
    return x;
}
```

7.4 Header

Macros, functions, and variables.

```
#pragma GCC optimize("O3")
#pragma GCC optimize("unroll-loops")

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

using namespace __gnu_pbds;
using namespace std;

#define F first
#define S second
#define pf push_front
#define pb push_back
#define pof pop_front
#define pob pop_back
#define ins insert
#define lb lower_bound
#define ub upper_bound
#define sz(a) ((int)(a).size())
#define all(a) begin(a), end(a)
#define FOR(i, a, b) for(int i = a; i <= b; i++)
#define ROF(i, a, b) for(int i = a; i >= b; i--)
#define FOR(i, a) FOR(i, 0, a)
#define ROF(i, a) ROF(i, a, 0)
#define ITER(i, a) for(auto i : a)
#define FAST ios_base::sync_with_stdio(false); cin.tie(0); cout.tie(0);
#define MOD 1000000007
#define MOD2 998244353
#define INF INT_MAX/2
#define EPS 1e-9

typedef long long ll;
typedef pair<ll, ll> pi;
typedef pair<ll, pi> pii;
typedef tree<pi, null_type, less<pi>,
            rb_tree_tag, tree_order_statistics_node_update> ordered_set;

int ls(int x){ return (x)&(-x); }
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
```

```

inline ll rngr(ll x, ll y) { return (rng()%(y-x+1))+x; }

inline ll ri() {
    ll x = 0;
    char ch = getchar_unlocked();
    while (ch < '0' || ch > '9') ch = getchar_unlocked();
    while (ch >= '0' && ch <= '9'){
        x = (x << 3) + (x << 1) + ch - '0';
        ch = getchar_unlocked();
    }
    return x;
}

struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
    size_t operator()(pair<uint64_t,uint64_t> x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x.first + FIXED_RANDOM)
            ^ (splitmix64(x.second + FIXED_RANDOM) >> 1);
    }
};

typedef unordered_map<int, int, custom_hash> safe_map;
typedef gp_hash_table<int, int, custom_hash> safe_hash_table;

// 4 Directions
int dx[]={0, 0, -1, 1};
int dy[]={-1, 1, 0, 0};
// 8 Directions
int dx[]={0, 0, -1, 1, -1, 1, -1, 1};
int dy[]={-1, 1, -1, 1, 0, 0, 1, -1};
// Knight Moves
int dx[]={-1, -2, 1, 2, 2, 1, -2, 1};
int dy[]={-2, -1, -2, -1, 1, 2, 1, 2};

```

7.5 Compile Commands

```

g++ -c "%f" -std=c++20 // Editor Compile
g++ -o "%e" "%f" -std=c++20 // Editor Build
g++ "file.cpp" -o "file" -std=c++20 // Simple for command line

```

7.6 Pruning

Kill execution after a specific time duration.

```
#define LIMIT 2.9
auto start = chrono::high_resolution_clock::now();
auto end = chrono::high_resolution_clock::now();
auto elapse = chrono::duration<double>(end-start);
if(elapse.count() > LIMIT) break;
```

7.7 STL Data Structures and Functions

```
//File I/O
freopen("test.in", "r", stdin);
freopen("test.out", "w", stdout);

// Variable / Array Functions
min(a, b);
max(a, b);
__gcd(a, b);
swap(a, b);

lower_bound(a, a+n, b); // Value >= b
upper_bound(a, a+n, b); // Value > b

fill(a, a+n, 0);
memset(a, 0, sizeof(a));
copy(a, a+n, b);

sort(a, a+n);
stable_sort(a, a+n); // If a = b, indexes will remain same
reverse(a, a+n);
random_shuffle(a, a+n, rng);
max_element(a, a+n);

// Math Functions (Low Accuracy)
pow(1, 2);
sqrt(1);
cbrt(1);
floor(1);
ceil(1);
abs(1);
log(1);
log10(1);

// Limits
INT_MAX
LLONG_MAX
LDBL_MAX

// Others
to_string(0);
stoll("0");

vector<int> v;
v.push_back(0);
v.front();
v.back();
v.pop_back();
```

```

queue<int> q;
q.push(0);
q.front();
q.pop();

priority_queue<int> pq;
pq.push(0);
pq.top();
pq.pop();

deque<int> dq;
dq.push_front(0);
dq.front();
dq.push_back(1);
dq.back();
dq.pop_front();
dq.pop_back();

set<int> s;
unordered_set<int> us;
s.insert(0);
s.find(0); // Pointer to 0's position
s.erase(0);

multiset<int> ms;
ms.insert(0);
ms.insert(0);
ms.count(0);
ms.find(0); // Pointer to a 0's position
ms.erase(ms.find(0)); // Erase a 0
ms.erase(0); // Erase all 0s

map<int, int> m;
unordered_map<int, int> um;
m[0] = 1;
m[1] = 2;

stack<int> st;
st.push(0);
st.top(); //0
st.pop();

// GNU PBDS
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

typedef tree<int, null_type, less<int>,
            rb_tree_tag, tree_order_statistics_node_update> ordered_set;

typedef tree<pi, null_type, less<pi>, //Use a pair to simulate multisets
            rb_tree_tag, tree_order_statistics_node_update> ordered_set;

ordered_set os;
os.insert(1);
os.insert(2);
os.insert(4);
os.insert(8);
os.insert(16);

```



```
//Find by order - Kth largest (starting from 0)
os.find_by_order(1); // 2
os.find_by_order(2); // 4
os.find_by_order(4); // 16
//Order of key - How many elements are < K
os.order_of_key(-5); // 0
os.order_of_key(1); // 0
os.order_of_key(3); // 2
os.order_of_key(4); // 2
os.order_of_key(400); // 5
```
