

QConnectBase

v. 1.1.0

Nguyen Huynh Tri Cuong

05.07.2022

Contents

1	Introduction	1
2	Description	2
2.1	Getting Started	2
2.2	Usage	2
2.2.1	<code>connect</code>	2
2.2.2	<code>disconnect</code>	3
2.2.3	<code>send command</code>	3
2.2.4	<code>verify</code>	4
2.3	Example	4
2.4	Contribution Guidelines	5
2.5	Configure Git and correct EOL handling	5
2.6	Sourcecode Documentation	6
2.7	Feedback	6
2.8	About	6
2.8.1	Maintainers	6
2.8.2	Contributors	6
2.9	License	6
3	<code>__init__.py</code>	7
3.1	Class: <code>ConnectionManager</code>	7
4	<code>connection_base.py</code>	8
4.1	Class: <code>BrokenConnError</code>	8
4.2	Class: <code>ConnectionBase</code>	8
4.2.1	Method: <code>is_supported_platform</code>	8
4.2.2	Method: <code>is_precondition_pass</code>	8
4.2.3	Method: <code>error_instruction</code>	8
4.2.4	Method: <code>quit</code>	9
4.2.5	Method: <code>connect</code>	9
4.2.6	Method: <code>disconnect</code>	9
4.2.7	Method: <code>send_obj</code>	9
4.2.8	Method: <code>read_obj</code>	10
4.2.9	Method: <code>wait_4_trace</code>	10
4.2.10	Method: <code>wait_4_trace_continuously</code>	11
4.2.11	Method: <code>create_and_activate_trace_queue</code>	11
4.2.12	Method: <code>deactivate_and_delete_trace_queue</code>	12
4.2.13	Method: <code>activate_trace_queue</code>	12

4.2.14	Method: deactivate_trace_queue	13
4.2.15	Method: check_timeout	13
4.2.16	Method: pre_msg_check	13
4.2.17	Method: post_msg_check	13
5	connection_manager.py	14
5.1	Class: InputParam	14
5.1.1	Method: get_attr_list	14
5.2	Class: ConnectParam	14
5.3	Class: SendCommandParam	14
5.4	Class: VerifyParam	14
5.5	Class: ConnectionManager	14
5.5.1	Method: quit	15
5.5.2	Method: add_connection	15
5.5.3	Method: remove_connection	15
5.5.4	Method: get_connection_by_name	15
5.5.5	Method: disconnect	16
5.5.6	Method: connect	16
5.5.7	Method: connect_named_args	16
5.5.8	Method: connect_unnamed_args	16
5.5.9	Method: send_command	17
5.5.10	Method: send_command_named_args	17
5.5.11	Method: send_command_unnamed_args	17
5.5.12	Method: verify	18
5.5.13	Method: verify_named_args	18
5.5.14	Method: verify_unnamed_args	18
5.6	Class: TestOption	19
6	constants.py	20
6.1	Class: SocketType	20
6.2	Class: String	20
7	qlogger.py	21
7.1	Class: ColorFormatter	21
7.1.1	Method: format	21
7.2	Class: QFileHandler	21
7.2.1	Method: get_log_path	21
7.2.2	Method: get_config_supported	22
7.3	Class: QDefaultFileHandler	22
7.3.1	Method: get_log_path	22
7.3.2	Method: get_config_supported	22
7.4	Class: QConsoleHandler	22
7.4.1	Method: get_config_supported	23
7.5	Class: QLogger	23
7.5.1	Method: get_logger	23
7.5.2	Method: set_handler	23

8	serial_base.py	24
8.1	Class: SerialConfig	24
8.2	Class: SerialSocket	24
8.2.1	Method: connect	24
8.2.2	Method: disconnect	24
8.2.3	Method: quit	24
8.3	Class: SerialClient	25
8.3.1	Method: connect	25
9	raw_tcp.py	26
9.1	Class: RawTCPBase	26
9.2	Class: RawTCPServer	26
9.3	Class: RawTCPClient	26
10	ssh_client.py	27
10.1	Class: AuthenticationType	27
10.2	Class: SSHConfig	27
10.3	Class: SSHClient	27
10.3.1	Method: close	27
10.3.2	Method: quit	27
11	tcp_base.py	28
11.1	Class: TCPConfig	28
11.2	Class: TCPBase	28
11.2.1	Method: close	28
11.2.2	Method: quit	28
11.2.3	Method: connect	28
11.2.4	Method: disconnect	29
11.3	Class: TCPBaseServer	29
11.3.1	Method: accept_connection	29
11.3.2	Method: connect	29
11.3.3	Method: disconnect	29
11.4	Class: TCPBaseClient	29
11.4.1	Method: connect	29
11.4.2	Method: disconnect	29
12	utils.py	30
12.1	Class: Singleton	30
12.2	Class: DictToClass	30
12.2.1	Method: validate	30
12.3	Class: Utils	30
12.3.1	Method: get_all_descendant_classes	30
12.3.2	Method: get_all_sub_classes	31
12.3.3	Method: is_valid_host	31
12.3.4	Method: execute_command	31
12.3.5	Method: kill_process	31
12.3.6	Method: caller_name	31

12.3.7 Method: <code>load_library</code>	31
12.3.8 Method: <code>is_ascii_or_unicode</code>	32
12.4 Class: <code>Job</code>	32
12.4.1 Method: <code>stop</code>	32
12.4.2 Method: <code>run</code>	32
12.5 Class: <code>ResultType</code>	32
12.6 Class: <code>ResponseMessage</code>	32
12.6.1 Method: <code>get_json</code>	32
12.6.2 Method: <code>get_data</code>	32
12.6.3 Method: <code>create_from_string</code>	32
13 Appendix	33
14 History	34

Chapter 1

Introduction

QConnectBaseLibrary is a connection testing library for [RobotFramework](#). Library will be supported to download from PyPI soon. It provides a mechanism to handle trace log continuously receiving from a connection (such as Raw TCP, SSH, Serial, etc.) besides sending data back to the other side. It's especially efficient for monitoring the overflowed response trace log from an asynchronous trace systems. It is supporting Python 3.7+ and RobotFramework 3.2+.

Chapter 2

Description

QConnectBase

2.1 Getting Started

We have a plan to publish all the sourcecode as OSS in the near future so that you can download from PyPI. For the current period, you can checkout

[QConnectBaseLibrary](#)

After checking out the source completely, you can install by running below command inside **robotframework-qconnect-base** directory.

```
python setup.py install
```

2.2 Usage

QConnectBase Library support following keywords for testing connection in RobotFramework.

2.2.1 connect

Use for establishing a connection.

Syntax:

connect [conn_name] [conn_type] [conn_mode] [conn_conf] (*All parameters are required to be in order*) or

connect conn_name=[conn_name] conn_type=[conn_type] conn_mode=[conn_mode]
conn_conf=[conn_conf] (*All parameters are assigned by name*)

Arguments:

conn_name: Name of the connection.

conn_type: Type of the connection. QConnectBaseLibrary has supported below connection types:

- **TCPIPClient:** Create a Raw TCPIP connection to TCP Server.
- **SSHClient:** Create a client connection to a SSH server.
- **SerialClient:** Create a client connection via Serial Port.

conn_mode: (unused) Mode of a connection type.

conn_conf: Configurations for making a connection. Depend on **conn_type** (Type of Connection), there is a suitable configuration in JSON format as below.

- **TCPIPClient**

```
{
  "address": [server host], # Optional. Default value is ↵
  ↵ "localhost".
  "port": [server port]      # Optional. Default value is 1234.
  "logfile": [Log file path. Possible values: 'nonlog', ↵
  ↵ 'console', [user define path] ]
}
```

• SSHClient

```
{
  "address" : [server host], # Optional. Default value is ↵
  ↵ "localhost".
  "port" : [server host],    # Optional. Default value is 22.
  "username" : [username],   # Optional. Default value is "root".
  "password" : [password],   # Optional. Default value is "".
  "authentication" : "password" | "keyfile" | ↵
  ↵ "passwordkeyfile", # Optional. Default value is "".
  "key_filename" : [filename or list of filenames], # ↵
  ↵ Optional. Default value is null.
  "logfile": [Log file path. Possible values: 'nonlog', ↵
  ↵ 'console', [user define path] ]
}
```

• SerialClient

```
{
  "port" : [comport or null],
  "baudrate" : [Baud rate such as 9600 or 115200 etc.],
  "bytesize" : [Number of data bits. Possible values: 5, 6, 7, 8],
  "stopbits" : [Number of stop bits. Possible values: 1, 1.5, 2],
  "parity" : [Enable parity checking. Possible values: 'N', ↵
  ↵ 'E', 'O', 'M', 'S'],
  "rtscts" : [Enable hardware (RTS/CTS) flow control.],
  "xonxoff" : [Enable software flow control.],
  "logfile": [Log file path. Possible values: 'nonlog', ↵
  ↵ 'console', [user define path] ]
}
```

2.2.2 disconnect

Use for disconnect a connection by name.

Syntax:

```
disconnect conn_name
```

Arguments:

conn_name: Name of the connection.

2.2.3 send command

Use for sending a command to the other side of connection.

Syntax:

```
send command [conn_name] [command] (All parameters are required to be in order) or
send command conn_name=[conn_name] command=[command] (All parameters are
assigned by name)
```

Arguments:

conn_name: Name of the connection.

command: Command to be sent.

2.2.4 verify

Use for verifying a response from the connection if it matched a pattern.

Syntax:

```
verify [conn_name] [search_pattern] [timeout] [fetch_block] [eob_pattern]
[filter_pattern] [send_cmd] (All parameters are required to be in order) or
verify conn_name=[conn_name] search_pattern=[search_pattern] timeout=[timeout]
fetch_block=[fetch_block] eob_pattern=[eob_pattern] filter_pattern=[filter_pattern]
send_cmd=[send_cmd] (All parameters are assigned by name)
```

Arguments:

conn_name: Name of the connection.

search_pattern: Regular expression for matching with the response.

timeout: Timeout for waiting response matching pattern.

fetch_block: If this value is true, every response line will be put into a block until a line match **eob_pattern** pattern.

eob_pattern: Regular expression for matching the endline when using **fetch_block**.

filter_pattern: Regular expression for filtering every line of block when using **fetch_block**.

send_cmd: Command to be sent to the other side of connection and waiting for response.

Return value:

A corresponding match object if it is found.

E.g.

```
${result} = verify conn_name=SSH_Connection
                  search_pattern=(?<=\s).*([0-9]).*(command).$
                  send_cmd=*echo This is the 1st test command.*
```

- `${result}[0]` will be **"This is the 1st test command."** which is the matched string.
- `${result}[1]` will be **"1st"** which is the first captured string.
- `${result}[2]` will be **"command"** which is the second captured string.

2.3 Example

```
*** Settings ***
Documentation      Suite description
Library           QConnectBase.ConnectionManager

*** Test Cases ***
Test SSH Connection
    # Create config for connection.
    ${config_string}=    concatenate
    ...    {
    ...    "address": "127.0.0.1",
    ...    "port": 8022,
    ...    "username": "root",
    ...    "password": "",
    ...    "authentication": "password",
    ...    "key_filename": null
    ...    }
    log to console        \nConnecting with configurations:\n${config_string}
    ${config}=            evaluate    json.loads('"'${config_string}'"')    json

    # Connect to the target with above configurations.
    connect                conn_name=test_ssh
    ...                    conn_type=SSHClient
    ...                    conn_conf=${config}

    # Send command 'cd ..' and 'ls' then wait for the response '.*' pattern.
    send command            conn_name=test_ssh
```

```

...                                command=cd ..

${res}=        verify                conn_name=test_ssh
...                                search_pattern=.*
...                                send_cmd=ls
log to console    ${res}

# Disconnect
disconnect test_ssh

```

Listing 2.1: Robot code example

2.4 Contribution Guidelines

QConnectBaseLibrary is designed for ease of making an extension library. By that way you can take advantage of the QConnectBaseLibrary's infrastructure for handling your own connection protocol. For creating an extension library for QConnectBaseLibrary, please following below steps.

1. Create a library package which have the prefix name is **robotframework-qconnect-***[your specific name]*.
2. Your handling connection class should be derived from **QConnectionLibrary.connection_base.ConnectionBase** class.
3. In your *Connection Class*, override below attributes and methods:
 - **_CONNECTION_TYPE**: name of your connection type. It will be the input of the `conn_type` argument when using **connect** keyword. Depend on the type name, the library will determine the correct connection handling class.
 - **__init__(self, mode, config)**: in this constructor method, you should:
 - Prepare resource for your connection.
 - Initialize receiver thread by calling **self.init_thread_receiver(cls._socket_instance, mode="")** method.
 - Configure and initialize the lowlevel receiver thread (if it's necessary) as below


```

self._llrecv_thrd_obj = None
self._llrecv_thrd_term = threading.Event()
self._init_thrd_llrecv(cls._socket_instance)

```
 - In case you use the lowlevel receiver thread. You should implement the **thrd_llrecv_from_connection_interface** method. This method is a mediate layer which will receive the data from connection at the very beginning, do some process then put them in a queue for the **receiver thread** above getting later.
 - Create the queue for this connection (use `Queue.Queue`).
 - **connect()**: implement the way you use to make your own connection protocol.
 - **_read()**: implement the way to receive data from connection.
 - **_write()**: implement the way to send data via connection.
 - **disconnect()**: implement the way you use to disconnect your own connection protocol.
 - **quit()**: implement the way you use to quit connection and clean resource.

2.5 Configure Git and correct EOL handling

Here you can find the references for [Dealing with line endings](#).

Every time you press return on your keyboard you're actually inserting an invisible character called a line ending. Historically, different operating systems have handled line endings differently. When you view changes in a file, Git handles line endings in its own way. Since you're collaborating on projects with Git and GitHub, Git might produce unexpected results if, for example, you're working on a Windows machine, and your collaborator has made a change in OS X.

To avoid problems in your diffs, you can configure Git to properly handle line endings. If you are storing the `.gitattributes` file directly inside of your repository, then you can assure that all EOL are managed by git correctly as defined.

2.6 Sourcecode Documentation

For investigating sourcecode, please refer to [QConnectBase library documentation](#)

2.7 Feedback

If you have any problem when using the library or think there is a better solution for any part of the library, I'd love to know it, as this will all help me to improve the library. Please don't hesitate to contact me.

Do share your valuable opinion, I appreciate your honest feedback!

2.8 About

2.8.1 Maintainers

[Nguyen Huynh Tri Cuong](#)

2.8.2 Contributors

[Nguyen Huynh Tri Cuong](#)

[Thomas Pollerspöck](#)

2.9 License

Copyright 2020-2022 Robert Bosch GmbH

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Chapter 3

`__init__.py`

3.1 Class: `ConnectionManager`

```
QConnectBase.__init__
```

Class to manage all connections.

Chapter 4

connection_base.py

4.1 Class: BrokenConnError

```
QConnectBase.connection_base
```

4.2 Class: ConnectionBase

```
QConnectBase.connection_base
```

Base class for all connection classes.

4.2.1 Method: is_supported_platform

Check if current platform is supported.

Returns:

/ Type: bool /
True if platform is supported.
False if platform is not supported.

4.2.2 Method: is_precondition_pass

Check for precondition.

Returns:

/ Type: bool /
True if passing the precondition.
False if failing the precondition.

4.2.3 Method: error_instruction

Get the error instruction.

Returns:

/ Type: str /
Error instruction string.

4.2.4 Method: quit

>> This method MUST be overridden in derived class <<
Abstract method for quitting the connection.

Arguments:

- `is_disconnect_all`
/ *Condition*: optional / *Type*: bool /
Determine if it's necessary to disconnect all connections.

Returns:

(no returns)

4.2.5 Method: connect

>> This method MUST be overridden in derived class <<
Abstract method for quitting the connection.

Arguments:

- `device`
/ *Condition*: required / *Type*: str /
Device name.
- `files`
/ *Condition*: optional / *Type*: list /
Trace file list if using dlt connection.
- `test_connection`
/ *Condition*: optional / *Type*: bool /
Determine if it's necessary for testing the connection.

Returns:

(no returns)

4.2.6 Method: disconnect

>> This method MUST be overridden in derived class <<
Abstract method for disconnecting connection.

Arguments:

- `n_thrd_id`
/ *Condition*: required / *Type*: int /
Thread id.

Returns:

(no returns)

4.2.7 Method: send_obj

Wrapper method to send message to a tcp connection.

Arguments:

- `obj`
/ *Condition*: required / *Type*: str /
Data to be sent.
- `cr`
/ *Condition*: optional / *Type*: str /
Determine if it's necessary to add newline character at the end of command.

Returns:

(no returns)

4.2.8 Method: read_obj

Wrapper method to get the response from connection.

Returns:

- `msg`
/ *Type*: str /
Responded message.

4.2.9 Method: wait_4_trace

Suspend the control flow until a Trace message is received which matches to a specified regular expression.

Arguments:

- `search_obj`
/ *Condition*: required / *Type*: str /
Regular expression all received trace messages are compare to. Can be passed either as a string or a regular expression object. Refer to Python documentation for module 're'.
- `use_fetch_block`
/ *Condition*: optional / *Type*: bool / *Default*: False /
Determine if 'fetch block' feature is used.
- `end_of_block_pattern`
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
The end of block pattern.
- `filter_pattern`
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
Pattern to filter message line by line.
- `timeout`
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Timeout parameter specified as a floating point number in the unit 'seconds'.
- `fct_args`
/ *Condition*: optional / *Type*: Tuple / *Default*: None /
List of function arguments passed to be sent.

Returns:

- `match`
/ *Type*: re.Match /
If no trace message matched to the specified regular expression and a timeout occurred, return None.
If a trace message has matched to the specified regular expression, a match object is returned as the result. The complete trace message can be accessed by the 'string' attribute of the match object. For access to groups within the regular expression, use the group() method. For more information, refer to Python documentation for module 're'.

4.2.10 Method: wait_4_trace_continuously

Getting trace log continuously without creating a new trace queue.

Arguments:

- `trace_queue`
/ *Condition*: required / *Type*: Queue /
Queue to store the traces.
- `timeout`
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Timeout for waiting a matched log.
- `fct_args`
/ *Condition*: optional / *Type*: Tuple / *Default*: None /
Arguments to be sent to connection.

Returns:

- `None`
/ *Type*: None /
If no trace message matched to the specified regular expression and a timeout occurred.
- `match`
/ *Type*: re.Match /
If a trace message has matched to the specified regular expression, a match object is returned as the result. The complete trace message can be accessed by the 'string' attribute of the match object. For access to groups within the regular expression, use the group() method. For more information, refer to Python documentation for module 're'.

4.2.11 Method: create_and_activate_trace_queue

Create Queue and assign it to `_trace_queue` object and activate the queue with the search element.

Arguments:

- `search_element`
/ *Condition*: required / *Type*: str /
Regular expression all received trace messages are compare to.
Can be passed either as a string or a regular expression object. Refer to Python documentation for module 're'.#
- `use_fetch_block`
/ *Condition*: optional / *Type*: bool / *Default*: False /
Determine if 'fetch block' feature is used.
- `end_of_block_pattern`
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
The end of block pattern.
- `regex_line_filter_pattern`
/ *Condition*: optional / *Type*: re.Pattern / *Default*: None /
Regular expression object to filter message line by line.

Returns:

- `trq_handle, trace_queue`
/ *Type*: tuple /
The handle and search object

4.2.12 Method: deactivate_and_delete_trace_queue

Deactivate trace queue and delete.

Arguments:

- `trq_handle`
/ *Condition*: required / *Type*: int /
Trace queue handle.
- `trace_queue`
/ *Condition*: required / *Type*: Queue /
Trace queue object.

Returns:

(no returns)

4.2.13 Method: activate_trace_queue

Activates a trace message filter specified as a regular expression. All matching trace messages are put in the specified queue object.

Arguments:

- `search_obj`
/ *Condition*: required / *Type*: str /
Regular expression all received trace messages are compare to. Can be passed either as a string or a regular expression object. Refer to Python documentation for module 're'.
- `trace_queue`
/ *Condition*: required / *Type*: Queue /
A queue object all trace message which matches the regular expression are put in. The using application must assure, that the queue is emptied or deleted.
- `use_fetch_block`
/ *Condition*: optional / *Type*: bool / *Default*: False /
Determine if 'fetch block' feature is used.
- `end_of_block_pattern`
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
The end of block pattern.
- `line_filter_pattern`
/ *Condition*: optional / *Type*: re.Pattern / *Default*: None /
Regular expression object to filter message line by line.

Returns:

- `handle_id`
/ *Type*: int /
Handle to deactivate the message filter.

4.2.14 Method: deactivate_trace_queue

Deactivates a trace message filter previously activated by ActivateTraceQ() method.

Arguments:

- handle
/ Condition: required / Type: int /
Integer object returned by ActivateTraceQ() method.

Returns:

* is_success

/ Type: bool / . False : No trace message filter active with the specified handle (i.e. handle is not in use).
True : Trace message filter successfully deleted.

4.2.15 Method: check_timeout

>> This method will be override in derived class <<

Check if responded message come in cls._RESPOND_TIMEOUT or we will raise a timeout event.

Arguments:

- timeout
/ Condition: required / Type: int /
Timeout in seconds.

Returns:

(no returns)

4.2.16 Method: pre_msg_check

>> This method will be override in derived class <<

Pre-checking message when receiving it from connection.

Arguments:

- msg
/ Condition: required / Type: str /
Received message to be checked.

Returns:

(no returns)

4.2.17 Method: post_msg_check

>> This method will be override in derived class <<

Post-checking message when receiving it from connection.

Arguments:

- msg
/ Condition: required / Type: str /
Received message to be checked.

Returns:

(no returns)

Chapter 5

connection_manager.py

5.1 Class: InputParam

```
QConnectBase.connection_manager
```

5.1.1 Method: get_attr_list

5.2 Class: ConnectParam

```
QConnectBase.connection_manager
```

Class for storing parameters for connect action.

5.3 Class: SendCommandParam

```
QConnectBase.connection_manager
```

Class for storing parameters for send command action.

5.4 Class: VerifyParam

```
QConnectBase.connection_manager
```

Class for storing parameters for verify action.

5.5 Class: ConnectionManager

```
QConnectBase.connection_manager
```

Class to manage all connections.

5.5.1 Method: quit

Quit connection manager.

Returns:

(no returns)

5.5.2 Method: add_connection

Add a connection to managed dictionary.

Arguments:

- name
/ *Condition*: required / *Type*: str /
Connection's name.
- conn
/ *Condition*: required / *Type*: socket.socket /
Connection object.

Returns:

(no returns)

5.5.3 Method: remove_connection

Remove a connection by name.

Arguments:

- connection_name
/ *Condition*: required / *Type*: str /
Connection's name.

Returns:

(no returns)

5.5.4 Method: get_connection_by_name

Get an exist connection by name.

Arguments:

- connection_name
/ *Condition*: required / *Type*: str /
Connection's name.

Returns:

- conn
/ *Type*: socket.socket /
Connection object.

5.5.5 Method: disconnect

Keyword for disconnecting a connection by name.

Arguments:

- `connection_name`
/ *Condition*: required / *Type*: str /
Connection's name.

Returns:

(no returns)

5.5.6 Method: connect

Keyword for making a connection.

Arguments:

- `args`
/ *Condition*: required / *Type*: tuple /
Non-Keyword Arguments.
- `kwargs`
/ *Condition*: required / *Type*: dict /
Keyword Arguments.

Returns:

(no returns)

5.5.7 Method: connect_named_args

Making a connection with name arguments.

Arguments:

- `kwargs`
/ *Condition*: required / *Type*: dict /
Keyword Arguments.

Returns:

(no returns)

5.5.8 Method: connect_unnamed_args

Making a connection.

Arguments:

- `connection_name`
/ *Condition*: required / *Type*: str /
Name of connection.
- `connection_type`
/ *Condition*: required / *Type*: str /
Type of connection.

- `mode`
/ *Condition*: required / *Type*: str /
Connection mode.
- `config`
/ *Condition*: required / *Type*: json /
Configuration for connection.

Returns:

(no returns)

5.5.9 Method: `send_command`

Keyword for sending command to a connection.

Arguments:

- `args`
/ *Condition*: require / *Type*: tuple /
Non-Keyword Arguments.
- `kwargs`
/ *Condition*: require / *Type*: dict /
Keyword Arguments.

Returns:

(no returns)

5.5.10 Method: `send_command_named_args`

Send command to a connection with name arguments.

Arguments:

- `kwargs`
/ *Condition*: required / *Type*: dict /
Keyword Arguments.

Returns:

(no returns)

5.5.11 Method: `send_command_unnamed_args`

Send command to a connection.

Arguments:

- `connection_name`
/ *Condition*: required / *Type*: str /
Name of connection.
- `command`
/ *Condition*: required / *Type*: str /
Command to be sent.

Returns:

(no returns)

5.5.12 Method: verify

Keyword uses to verify a pattern from connection response after sending a command.

Arguments:

- args
/ *Condition*: required / *Type*: tuple /
Non-Keyword Arguments.
- kwargs
/ *Condition*: required / *Type*: dict /
Keyword Arguments.

Returns:

- match_res
/ *Type*: str /
Matched string.

5.5.13 Method: verify_named_args

Verify a pattern from connection response after sending a command with named arguments.

Arguments:

- kwargs
/ *Condition*: required / *Type*: dict /
Keyword Arguments.

Returns:

- match_res
/ *Type*: str /
Matched string.

5.5.14 Method: verify_unnamed_args

Verify a pattern from connection response after sending a command.

Arguments:

- connection_name
/ *Condition*: required / *Type*: str /
Name of connection.
- search_obj
/ *Condition*: required / *Type*: str /
Regular expression all received trace messages are compare to. Can be passed either as a string or a regular expression object. Refer to Python documentation for module 're'.
- fetch_block
/ *Condition*: optional / *Type*: bool / *Default*: False /
Determine if 'fetch block' feature is used.
- eob_pattern
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
The end of block pattern.

- `filter_pattern`
/ *Condition*: optional / *Type*: str / *Default*: '.*' /
Pattern to filter message line by line.
- `timeout`
/ *Condition*: optional / *Type*: float / *Default*: 0 /
Timeout parameter specified as a floating point number in the unit 'seconds'.
- `fct_args`
/ *Condition*: optional / *Type*: Tuple / *Default*: None /
List of function arguments passed to be sent.

Returns:

- `match_res`
/ *Type*: str /
Matched string.

5.6 Class: TestOption

```
QConnectBase.connection_manager
```


Chapter 6

constants.py

6.1 Class: SocketType

```
QConnectBase.constants
```

6.2 Class: String

```
QConnectBase.constants
```

Chapter 7

qlogger.py

7.1 Class: ColorFormatter

```
QConnectBase.qlogger
```

Custom formatter class for setting log color.

7.1.1 Method: format

Set the color format for the log.

Arguments:

- `record`
/ *Condition*: required / *Type*: str /
Log record.

Returns:

/ *Type*: logging.Formatter /
Log with color formatter.

7.2 Class: QFileHandler

```
QConnectBase.qlogger
```

Handler class for user defined file in config.

7.2.1 Method: get_log_path

Get the log file path for this handler.

Arguments:

- `config`
/ *Condition*: required / *Type*: DictToClass /
Connection configurations.

Returns:

/ *Type*: str /
Log file path.

7.2.2 Method: get_config_supported

Check if the connection config is supported by this handler.

Arguments:

- `config`
/ *Condition*: required / *Type*: DictToClass /
Connection configurations.

Returns:

/ *Type*: bool /
True if the config is supported.
False if the config is not supported.

7.3 Class: QDefaultFileHandler

```
QConnectBase.qlogger
```

Handler class for default log file path.

7.3.1 Method: get_log_path

Get the log file path for this handler.

Arguments:

- `logger_name`
/ *Condition*: required / *Type*: str /
Name of the logger.

Returns:

/ *Type*: str /
Log file path.

7.3.2 Method: get_config_supported

Check if the connection config is supported by this handler.

Arguments:

- `config`
/ *Condition*: required / *Type*: DictToClass /
Connection configurations.

Returns:

/ *Type*: bool /
True if the config is supported.
False if the config is not supported.

7.4 Class: QConsoleHandler

```
QConnectBase.qlogger
```

Handler class for console log.

7.4.1 Method: get_config_supported

Check if the connection config is supported by this handler.

Arguments:

- `config`
/ *Condition*: required / *Type*: DictToClass /
Connection configurations.

Returns:

/ *Type*: bool /
True if the config is supported.
False if the config is not supported.

7.5 Class: QLogger

```
QConnectBase.qlogger
```

Logger class for QConnect Libraries.

7.5.1 Method: get_logger

Get the logger object.

Arguments:

- `logger_name`
/ *Condition*: required / *Type*: str /
Name of the logger.

Returns:

- `logger`
/ *Type*: Logger /
Logger object. .

7.5.2 Method: set_handler

Set handler for logger.

Arguments:

- `config`
/ *Condition*: required / *Type*: DictToClass /
Connection configurations.

Returns:

- `handler_ins`
/ *Type*: logging.handler /
None if no handler is set.
Handler object.

Chapter 8

serial_base.py

8.1 Class: SerialConfig

```
QConnectBase.serialclient.serial_base
```

Class to store the configuration for Serial connection.

8.2 Class: SerialSocket

```
QConnectBase.serialclient.serial_base
```

Class for handling serial connection.

8.2.1 Method: connect

Connect to serial port.

Returns:

(no returns)

8.2.2 Method: disconnect

Disconnect serial port.

Arguments:

- `_device`
/ *Condition*: required / *Type*: str /
Unused

Returns:

(no returns)

8.2.3 Method: quit

Quit serial connection.

Returns:

(no returns)

8.3 Class: SerialClient

```
QConnectBase.serialclient.serial_base
```

Serial client class.

8.3.1 Method: connect

Connect to the Serial port.

Returns:

(no returns)

Chapter 9

raw_tcp.py

9.1 Class: RawTCPBase

```
QConnectBase.tcp/raw.raw_tcp
```

Base class for a raw tcp connection.

9.2 Class: RawTCPServer

```
QConnectBase.tcp/raw.raw_tcp
```

Class for a raw tcp connection server.

9.3 Class: RawTCPClient

```
QConnectBase.tcp/raw.raw_tcp
```

Class for a raw tcp connection client.

Chapter 10

ssh_client.py

10.1 Class: AuthenticationType

```
QConnectBase.tcp/ssh.ssh_client
```

10.2 Class: SSHConfig

```
QConnectBase.tcp/ssh.ssh_client
```

Class to store the configuration for SSH connection.

10.3 Class: SSHClient

```
QConnectBase.tcp/ssh.ssh_client
```

SSH client connection class. Method: connect -----

Implementation for creating a SSH connection.

Returns:

(no returns)

10.3.1 Method: close

Close SSH connection.

Returns:

(no returns)

10.3.2 Method: quit

Quit and stop receiver thread.

Returns:

(no returns)

Chapter 11

tcp_base.py

11.1 Class: TCPConfig

```
QConnectBase.tcp.tcp_base
```

Class to store configurations for TCP connection.

11.2 Class: TCPBase

```
QConnectBase.tcp.tcp_base
```

Base class for a tcp connection.

11.2.1 Method: close

Close connection.

Returns:

(no returns)

11.2.2 Method: quit

Quit connection.

Arguments:

- `is_disconnect_all`
/ *Condition*: required / *Type*: bool /
Determine if it's necessary for disconnect all connection.

Returns:

(no returns)

11.2.3 Method: connect

>> Should be override in derived class.

Establish the connection.

Returns:

(no returns)

11.2.4 Method: disconnect

>> Should be override in derived class.

Disconnect the connection.

Returns:

(no returns)

11.3 Class: TCPBaseServer

```
QConnectBase.tcp.tcp_base
```

Base class for TCP server.

11.3.1 Method: accept_connection

Wrapper method for handling accept action of TCP Server.

Returns:

(no returns)

11.3.2 Method: connect

11.3.3 Method: disconnect

11.4 Class: TCPBaseClient

```
QConnectBase.tcp.tcp_base
```

Base class for TCP client.

11.4.1 Method: connect

11.4.2 Method: disconnect

Chapter 12

utils.py

12.1 Class: Singleton

```
QConnectBase.utils
```

Class to implement Singleton Design Pattern. This class is used to derive the TTFisClientReal as only a single instance of this class is allowed.

Disabled pyLint Messages: R0903: Too few public methods (%s/%s) Used when class has too few public methods, so be sure it's really worth it.

This base class implements the Singleton Design Pattern required for the TTFisClientReal. Adding further methods does not make sense.

12.2 Class: DictToClass

```
QConnectBase.utils
```

Class for converting dictionary to class object.

12.2.1 Method: validate

12.3 Class: Utils

```
QConnectBase.utils
```

Class to implement utilities for supporting development.

12.3.1 Method: get_all_descendant_classes

Get all descendant classes of a class

Arguments: cls: Input class for finding descendants.

Returns:

/ *Type*: list /

Array of descendant classes.

12.3.2 Method: get_all_sub_classes

Get all children classes of a class

Arguments:

- `cls`
/ *Condition*: required / *Type*: class /
Input class for finding children.

Returns:

/ *Type*: list /
Array of children classes.

12.3.3 Method: is_valid_host

12.3.4 Method: execute_command

12.3.5 Method: kill_process

12.3.6 Method: caller_name

Get a name of a caller in the format module.class.method

Arguments:

- `skip`
/ *Condition*: required / *Type*: int /

Specifies how many levels of stack to skip while getting caller name. `skip=1` means "who calls me", `skip=2` "who calls my caller" etc.

Returns:

/ *Type*: str /
An empty string is returned if skipped levels exceed stack height

12.3.7 Method: load_library

Load native library depend on the calling convention.

Arguments:

- `path`
/ *Condition*: required / *Type*: str /
Library path.
- `is_stdcall`
/ *Condition*: optional / *Type*: bool / *Default*: True /
Determine if the library's calling convention is stdcall or cdecl.

Returns:

Loaded library object.

12.3.8 Method: is_ascii_or_unicode

Check if the string is ascii or unicode

Arguments: str_check: string for checking codecs: encoding type list

Returns:

/ Type: bool /

True : if checked string is ascii or unicode

False : if checked string is not ascii or unicode

12.4 Class: Job

```
QConnectBase.utils
```

12.4.1 Method: stop

12.4.2 Method: run

12.5 Class: ResultType

```
QConnectBase.utils
```

Result Types.

12.6 Class: ResponseMessage

```
QConnectBase.utils
```

Response message class

12.6.1 Method: get_json

Convert response message to json

Returns:

Response message in json format

12.6.2 Method: get_data

Get string data result

Returns:

String result

12.6.3 Method: create_from_string

Chapter 13

Appendix

About this package:

Table 13.1: Package setup

Setup parameter	Value
Name	QConnectBase
Version	1.1.0
Date	05.07.2022
Description	Robot Framework test library for TCP, SSH, serial connection
Package URL	robotframework-qconnect-base
Author	Nguyen Huynh Tri Cuong
Email	cuong.nguyenhuyhtri@vn.bosch.com
Language	Programming Language :: Python :: 3
License	License :: OSI Approved :: Apache Software License
OS	Operating System :: OS Independent
Python required	>=3.0
Development status	Development Status :: 4 - Beta
Intended audience	Intended Audience :: Developers
Topic	Topic :: Software Development

Chapter 14

History

1.1.0	07/2022
<i>Initial version</i>	

QConnectBase.pdf*Created at 31.08.2022 - 15:53:41**by GenPackageDoc v. 0.28.0*
