

Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>



Convolution



Convolution



Convolution




Convolution






Dense




Output









<https://arxiv.org/abs/1512.00567>



We gratefully acknowledge support from the Simons Foundation and member institutions.

[arXiv.org](#) > [cs](#) > [arXiv:1512.00567](#)

Search or Article ID All fields
([Help](#) | [Advanced search](#))

Computer Science > Computer Vision and Pattern Recognition

Rethinking the Inception Architecture for Computer Vision

[Christian Szegedy](#), [Vincent Vanhoucke](#), [Sergey Ioffe](#), [Jonathon Shlens](#), [Zbigniew Wojna](#)

(Submitted on 2 Dec 2015 (v1), last revised 11 Dec 2015 (this version, v3))

Convolutional networks are at the core of most state-of-the-art computer vision solutions for a wide variety of tasks. Since 2014 very deep convolutional networks started to become mainstream, yielding substantial gains in various benchmarks. Although increased model size and computational cost tend to translate to immediate quality gains for most tasks (as long as enough labeled data is provided for training), computational efficiency and low parameter count are still enabling factors for various use cases such as mobile vision and big-data scenarios. Here we explore ways to scale up networks in ways that aim at utilizing the added computation as efficiently as possible by suitably factorized convolutions and aggressive regularization. We benchmark our methods on the ILSVRC 2012 classification challenge validation set demonstrate substantial gains over the state of the art: 21.2% top-1 and 5.6% top-5 error for single frame evaluation using a network with a computational cost of 5 billion multiply-adds per inference and with using less than 25 million parameters. With an ensemble of 4 models and multi-crop evaluation, we report 3.5% top-5 error on the validation set (3.6% error on the test set) and 17.3% top-1 error on the validation set.

Download:

- [PDF](#)
 - [Other formats](#)
- ([license](#))

Current browse context:

cs.CV

[< prev](#) | [next >](#)
[new](#) | [recent](#) | [1512](#)

Change to browse by:

[cs](#)

References & Citations

- [NASA ADS](#)

http://image-net.org/



14,197,122 images, 21841 synsets indexed

[Explore](#) [Download](#) [Challenges](#) [Publications](#) [CoolStuff](#) [About](#)

Not logged in. [Login](#) | [Signup](#)

ImageNet is an image database organized according to the **WordNet** hierarchy (currently only the nouns), in which each node of the hierarchy is depicted by hundreds and thousands of images. Currently we have an average of over five hundred images per node. We hope ImageNet will become a useful resource for researchers, educators, students and all of you who share our passion for pictures.

[Click here](#) to learn more about ImageNet, [Click here](#) to join the ImageNet mailing list.



What do these images have in common? *Find out!*

[Check out the ImageNet Challenge on Kaggle!](#)

[https://storage.googleapis.com/mledu-datasets/
inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5](https://storage.googleapis.com/mledu-datasets/inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5)

```
local_weights_file = '/tmp/inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5'

pre_trained_model = tf.keras.applications.inception_v3.InceptionV3(
    input_shape=(150, 150, 3),
    include_top=False,
    weights=None)

pre_trained_model.load_weights(local_weights_file)
```



```
for layer in pre_trained_model.layers:  
    layer.trainable = False
```

```
pre_trained_model.summary()
```

Model: "inception_v3"

Layer (type)	Output Shape	Param #	Connected to
input_layer_1 (InputLayer)	(None, 150, 150, 3)	0	-
conv2d_94 (Conv2D)	(None, 74, 74, 32)	864	input_layer_1[0]...
batch_normalizatio... (BatchNormalizatio...)	(None, 74, 74, 32)	96	conv2d_94[0][0]
activation_94 (Activation)	(None, 74, 74, 32)	0	batch_normalizat...
conv2d_95 (Conv2D)	(None, 72, 72, 32)	9,216	activation_94[0]...
batch_normalizatio... (BatchNormalizatio...)	(None, 72, 72, 32)	96	conv2d_95[0][0]

...



```
last_layer = pre_trained_model.get_layer('mixed7')
```

```
last_output = last_layer.output
```

```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['accuracy'])
```



```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['accuracy'])
```




```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)
```

```
model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['accuracy'])
```

```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)
```

```
model = tf.keras.Model(pre_trained_model.input, x)
```

```
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['accuracy'])
```

```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['accuracy'])
```





```
history = model_with_aug.fit(  
    train_dataset_final,  
    validation_data=validation_dataset_final,  
    epochs=20,  
    verbose=2)
```












```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['acc'])
```



```
x = tf.keras.layers.Flatten()(last_output)
x = tf.keras.layers.Dense(1024, activation='relu')(x)
x = tf.keras.layers.Dropout(0.2)(x)
x = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(pre_trained_model.input, x)
model.compile(
    optimizer=RMSprop(learning_rate=0.0001),
    loss='binary_crossentropy',
    metrics=['acc'])
```



