

10

General Issues in Using Variables

CC2E.COM/1085

Contents

- 10.1 Data Literacy
- 10.2 Making Variable Declarations Easy
- 10.3 Guidelines for Initializing Variables
- 10.4 Scope
- 10.5 Persistence
- 10.6 Binding Time
- 10.7 Relationship Between Data Types and Control Structures
- 10.8 Using Each Variable for Exactly One Purpose

Related Topics

- Naming variables: Chapter 11
- Fundamental data types: Chapter 12
- Unusual data types: Chapter 13
- Formatting data declarations: “Laying Out Data Declarations” in Section 31.5
- Documenting variables: “Commenting Data Declarations” in Section 32.5

IT’S NORMAL AND DESIRABLE FOR construction to fill in small gaps in the requirements and architecture. It would be inefficient to draw blueprints to such a microscopic level that every detail was completely specified. This chapter describes a nuts and bolts construction issue—ins and outs of using variables.

The information in this chapter should be particularly valuable to you if you’re an experienced programmer. It’s easy to start using hazardous practices before you’re fully aware of your alternatives and then to continue to use them out of habit even after you’ve learned ways to avoid them. An experienced programmer might find the discussions on binding time in Section 10.6 and on using each variable for one purpose in Section 10.8 particularly interesting. If you’re not

sure whether you qualify as an “experienced programmer,” take the “Data Literacy Test” in the next section, and find out.

Throughout this chapter I use the word “variable” to refer to objects as well as to built-in data types like integers and arrays. The phrase “data type” generally refers to built-in data types, while the word “data” refers to either objects or built-in types.

10.1 Data Literacy

KEY POINT

The first step in creating effective data is knowing which kind of data to create. A good repertoire of data types is a key part of a programmer’s toolkit. A tutorial in data types is beyond the scope of this book, but take the “Data Literacy Test” below to determine how much more you might need to learn about them.

The Data Literacy Test

Put a *1* next to each term that looks familiar. If you think you know what a term means but aren’t sure, give yourself a *0.5*. Add the points when you’re done, and interpret your score according to the scoring table below.

- | | |
|--------------------------|-----------------------------|
| _____ abstract data type | _____ literal |
| _____ array | _____ local variable |
| _____ bitmap | _____ lookup table |
| _____ boolean variable | _____ member data |
| _____ B-tree | _____ pointer |
| _____ character variable | _____ private |
| _____ container class | _____ retroactive synapse |
| _____ double precision | _____ referential integrity |
| _____ elongated stream | _____ stack |
| _____ enumerated type | _____ string |
| _____ floating point | _____ structured variable |
| _____ heap | _____ tree |
| _____ index | _____ typedef |
| _____ integer | _____ union |
| _____ linked list | _____ value chain |

_____ named constant

_____ variant

_____ **Total Score**

Here is how you can interpret the scores (loosely):

0–14	You are a beginning programmer, probably in your first year of computer science in school or teaching yourself your first programming language. You can learn a lot by reading one of the books listed below. Many of the descriptions of techniques in this part of the book are addressed to advanced programmers, and you’ll get more out of them after you’ve read one of these books.
15–19	You are an intermediate programmer or an experienced programmer who has forgotten a lot. Although many of the concepts will be familiar to you, you too can benefit from reading one of the books listed below.
20–24	You are an expert programmer. You probably already have the books listed below on your shelf.
25–29	You know more about data types than I do. Consider writing your own computer book. (Send me a copy!)
30–32	You are a pompous fraud. The terms “elongated stream,” “retroactive synapse,” and “value chain” don’t refer to data types—I made them up. Please read the intellectual-honesty section in Chapter 31!

Additional Resources on Data Types

These books are good sources of information about data types:

Cormen, H. Thomas, Charles E. Leiserson, Ronald L. Rivest. *Introduction to Algorithms*. New York: McGraw Hill. 1990.

Sedgewick, Robert. *Algorithms in C++, Part 5, 3d ed.* Boston, Mass.: Addison-Wesley, 2002.

Sedgewick, Robert. *Algorithms in C++, Parts 1-4, 3d ed.* Boston, Mass.: Addison-Wesley, 1998.

10.2 Making Variable Declarations Easy

This section describes what you can do to streamline the task of declaring variables. To be sure, this is a small task, and you may think it's too small to deserve its own section in this book. Nevertheless, you spend a lot of time creating variables, and developing the right habits can save time and frustration over the life of a project.

Implicit Declarations

Some languages have implicit variable declarations. For example, if you use a variable in Visual Basic without declaring it, the compiler declares it for you automatically (depending on your compiler settings).

Implicit declaration is one of the most hazardous features available in any language.

If you program in Visual Basic, you know how frustrating it is to try to figure out why *acctNo* doesn't have the right value and then notice that *acctNum* is the variable that's reinitialized to 0. This kind of mistake is an easy one to make if your language doesn't require you to declare variables.

If you're programming in a language that requires you to declare variables, you have to make two mistakes before your program will bite you. First you have to put both *acctNum* and *acctNo* into the body of the routine. Then you have to declare both variables in the routine. This is a harder mistake to make and virtually eliminates the synonymous-variables problem. Languages that require you explicitly to declare data force you to use data more carefully, which is one of their primary advantages. What do you do if you program in a language with implicit declarations? Here are some suggestions:

Turn off implicit declarations

Some compilers allow you to disable implicit declarations. For example, in Visual Basic you would use an *Option Explicit* statement, which forces you to declare all variables before you use them.

Declare all variables

As you type in a new variable, declare it, even though the compiler doesn't require you to. This won't catch all the errors, but it will catch some of them.

Use naming conventions

Establish a naming convention for common suffixes such as *Num* and *No* so that you don't use two variables when you mean to use one.

53

54 **CROSS-REFERENCE** For
55 details on layout of variable
56 declarations, see "Laying Out
57 Data Declarations" in Section
58 31.5. For details on
59 documenting them, see
60 "Commenting Data
61 Declarations" in Section
62 32.5.

63

64

65

66

67

68

69 **KEY POINT**

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84 **CROSS-REFERENCE** For
85 details on the standardization
86 of abbreviations, see
"General Abbreviation
Guidelines" in Section 11.6.

Check variable names

Use the cross-reference list generated by your compiler or another utility program. Many compilers list all the variables in a routine, allowing you to spot both *acctNum* and *acctNo*. They also point out variables that you've declared and not used.

10.3 Guidelines for Initializing Variables

KEY POINT

Improper data initialization is one of the most fertile sources of error in computer programming. Developing effective techniques for avoiding initialization problems can save a lot of debugging time.

The problems with improper initialization stem from a variable's containing an initial value that you do not expect it to contain. This can happen for any of the several reasons described on the next page.

CROSS-REFERENCE For a testing approach based on data initialization and use patterns, see "Data-Flow Testing" in Section 22.3.

- The variable has never been assigned a value. Its value is whatever bits happened to be in its area of memory when the program started.
- The value in the variable is outdated. The variable was assigned a value at some point, but the value is no longer valid.
- Part of the variable has been assigned a value and part has not.

This last theme has several variations. You can initialize some of the members of an object but not all of them. You can forget to allocate memory and then initialize the "variable" the uninitialized pointer points to. This means that you are really selecting a random portion of computer memory and assigning it some value. It might be memory that contains data. It might be memory that contains code. It might be the operating system. The symptom of the pointer problem can manifest itself in completely surprising ways that are different each time—that's what makes debugging pointer errors harder than debugging other errors.

Here are guidelines for avoiding initialization problems.

Initialize each variable as it's declared

Initializing variables as they're declared is an inexpensive form of defensive programming. It's a good insurance policy against initialization errors. The example below ensures that *studentName* will be reinitialized each time you call the routine that contains it.

118 **CROSS-REFERENCE** Cod
e samples in this book are
119 formatted using a coding
CROSS-REFERENCE Che
cking input parameters is a
121 form of defensive
122 programming. For details on
defensive programming, see
123 Chapter 8, “Defensive
124 Programming.”

125 **CODING HORROR**
Considerations in Section

126 11.4.

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

C++ Example of Initialization at Declaration Time

```
char  studentName [ NAME_LENGTH + 1 ] = {'\0'};  // full name of student
```

Initialize each variable close to where it’s first used

Some languages, including Visual Basic, don’t support initializing variables as they’re declared. That can lead to coding styles like the one below, in which declarations are grouped together, and then initializations are grouped together—all far from the first actual use of the variables.

Visual Basic Example of Bad Initialization

```
' declare all variables
Dim accountIndex As Integer
Dim total As Double
Dim done As Boolean

' initialize all variables
accountIndex = 0
total = 0.0
done = False
...

' code using accountIndex
...

' code using total
...

' code using done
While Not done
    ...
```

A better practice is to initialize variables as close as possible to where they’re first used:

Visual Basic Example of Good Initialization

```
Dim accountIndex As Integer
accountIndex = 0
' code using accountIndex
...

Dim total As Double
total = 0.0
' code using total
...

Dim done As Boolean
```

155 *total is declared and initialized*
156 *close to where it’s used.*

157

158

159

160 *done is also declared and*
161 *initialized close to where it's*
162 *used.*

163

164 **CROSS-REFERENCE** For
165 more details on keeping
166 related actions together, see
167 Section 14.2, "Statements
168 Whose Order Doesn't
169 Matter."

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189 *total is initialized close to*
190 *where it's used.*

191

192

193 *done is also initialized close to*
194 *where it's used.*

195

196

```
done = False
' code using done
While Not done
    ...
```

The second example is superior to the first for several reasons. By the time execution of the first example gets to the code that uses *done*, *done* could have been modified. If that's not the case when you first write the program, later modifications might make it so. Another problem with the first approach is that throwing all the initializations together creates the impression that all the variables are used throughout the whole routine—when in fact *done* is used only at the end. Finally, as the program is modified (as it will be, if only by debugging), loops might be built around the code that uses *done*, and *done* will need to be reinitialized. The code in the second example will require little modification in such a case. The code in the first example is more prone to producing an annoying initialization error.

This is an example of the Principle of Proximity: Keep related actions together. The same principle applies to keeping comments close to the code they describe, to keeping loop setup code close to the loop, to grouping statements in straight-line code, and to many other areas.

Ideally, declare and define each variable close to where it's used

A declaration establishes a variable's type. A definition assigns the variable a specific value. In languages that support it, such as C++ and Java, variables should be declared and defined close to where they are first used. Ideally, each variable should be defined at the same time it's declared, as shown below.

Java Example of Good Initialization

```
int accountIndex = 0;
// code using accountIndex
...

double total = 0.0;
// code using total
...

boolean done = false;
// code using done
while ( ! done ) {
    ...
```

197 **CROSS-REFERENCE** For
198 more details on keeping
199 related actions together, see
200 Section 14.2, “Statements
201 Whose Order Doesn’t
202 Matter.”

203
204

205
206
207
208
209
210

211
212
213
214
215
216
217
218

219
220
221
222
223
224
225

226
227

228 **CROSS-REFERENCE** For
229 more on checking input
230 parameters, see Section 8.1,
231 “Protecting Your Program
232 From Invalid Inputs” and the
233 rest of Chapter 8, “Defensive
Programming.”

Pay special attention to counters and accumulators

The variables *i*, *j*, *k*, *sum*, and *total* are often counters or accumulators. A common error is forgetting to reset a counter or an accumulator before the next time it’s used.

Initialize a class’s member data in its constructor

Just as a routine’s variables should be initialized within each routine, a class’s data should be initialized within its constructor. If memory is allocated in the constructor, it should be freed in the destructor.

Check the need for reinitialization

Ask yourself whether the variable will ever need to be reinitialized—either because a loop in the routine uses the variable many times or because the variable retains its value between calls to the routine and needs to be reset between calls. If it needs to be reinitialized, make sure that the initialization statement is inside the part of the code that’s repeated.

Initialize named constants once; initialize variables with executable code

If you’re using variables to emulate named constants, it’s OK to write code that initializes them once, at the beginning of the program. To do this, initialize them in a *Startup()* routine. Initialize true variables in executable code close to where they’re used. One of the most common program modifications is to change a routine that was originally called once so that you call it multiple times. Variables that are initialized in a program-level *Startup()* routine aren’t reinitialized the second time through the routine.

Use the compiler setting that automatically initializes all variables

If your compiler supports such an option, having the compiler set to automatically initialize all variables is an easy variation on the theme of relying on your compiler. Relying on specific compiler settings, however, can cause problems when you move the code to another machine and another compiler. Make sure you document your use of the compiler setting; assumptions that rely on specific compiler settings are hard to uncover otherwise.

Take advantage of your compiler’s warning messages

Many compilers warn you that you’re using an uninitialized variable.

Check input parameters for validity

Another valuable form of initialization is checking input parameters for validity. Before you assign input values to anything, make sure the values are reasonable.

Use a memory-access checker to check for bad pointers

In some operating systems, the operating-system code checks for invalid pointer references. In others, you’re on your own. You don’t have to stay on your own,

however, because you can buy memory-access checkers that check your program's pointer operations.

Initialize working memory at the beginning of your program

Initializing working memory to a known value helps to expose initialization problems. You can take any of several approaches:

- You can use a preprogram memory filler to fill the memory with a predictable value. The value 0 is good for some purposes because it ensures that uninitialized pointers point to low memory, making it relatively easy to detect them when they're used. On the Intel processors, 0xCC is a good value to use because it's the machine code for a breakpoint interrupt; if you are running code in a debugger and try to execute your data rather than your code, you'll be awash in breakpoints. Another virtue of the value 0xCC is that it's easy to recognize in memory dumps— and it's rarely used for legitimate reasons. Alternatively, Brian Kernighan and Rob Pike suggest using the constant *0xDEADBEEF* as memory filler that's easy to recognize in a debugger (1999).
- If you're using a memory filler, you can change the value you use to fill the memory once in awhile. Shaking up the program sometimes uncovers problems that stay hidden if the environmental background never changes.
- You can have your program initialize its working memory at startup time. Whereas the purpose of using a preprogram memory filler is to expose defects, the purpose of this technique is to hide them. By filling working memory with the same value every time, you guarantee that your program won't be affected by random variations in the startup memory.

10.4 Scope

"Scope" is a way of thinking about a variable's celebrity status: how famous is it? Scope, or visibility, refers to the extent to which your variables are known and can be referenced throughout a program. A variable with limited or small scope is known in only a small area of a program—a loop index used in only one small loop, for instance. A variable with large scope is known in many places in a program—a table of employee information that's used throughout a program, for instance.

Different languages handle scope in different ways. In some primitive languages, all variables are global. You therefore don't have any control over the scope of a variable, and that can create a lot of problems. In C++ and similar languages, a variable can be visible to a block (a section of code enclosed in curly brackets), a

routine, a class, or the whole program. In Java and C#, a variable can also be visible to a package or namespace (a collection of classes).

The following sections provide guidelines that apply to scope.

Localize References to Variables

The code between references to a variable is a “window of vulnerability.” In the window, new code might be added, inadvertently altering the variable, or someone reading the code might forget the value the variable is supposed to contain. It’s always a good idea to localize references to variables by keeping them close together.

The idea of localizing references to a variable is pretty self-evident, but it’s an idea that lends itself to formal measurement. One method of measuring how close together the references to a variable are is to compute the “span” of a variable. Here’s an example:

Java Example of Variable Span

```
a = 0;
b = 0;
c = 0;
a = b + c;
```

In this case, two lines come between the first reference to *a* and the second, so *a* has a span of two. One line comes between the two references to *b*, so *b* has a span of one, and *c* has a span of zero. Here’s another example:

Java Example of Spans of One and Zero

```
a = 0;
b = 0;
c = 0;
b = a + 1;
b = b / c;
```

In this case, there is one line between the first reference to *b* and the second, for a span of one. There are no lines between the second reference to *b* and the third, for a span of zero.


The average span is computed by averaging the individual spans; in *b*’s case, $(1+0)/2$ equals an average span of 0.5. When you keep references to variables close together, you enable the person reading your code to focus on one section at a time. If the references are far apart, you force the reader to jump around in the program. Thus the main advantage of keeping references to variables together is that it improves program readability.

FURTHER READING For more information on variable span, see *Software Engineering Metrics and Models* (Conte, Dunsmore, and Shen 1986).

Keep Variables Live for As Short a Time As Possible

A concept that’s related to variable span is variable “live time,” the total number of statements over which a variable is live. A variable’s life begins at the first statement in which it’s referenced; its life ends at the last statement in which it’s referenced.

Unlike span, live time isn’t affected by how many times the variable is used between the first and last times it’s referenced. If the variable is first referenced on line 1 and last referenced on line 25, it has a live time of 25 statements. If those are the only two lines in which it’s used, it has an average span of 23 statements. If the variable were used on every line from line 1 through line 25, it would have an average span of 0 statements, but it would still have a live time of 25 statements. Figure 10-1 illustrates both span and live time.



F10xx01

Figure 10-1

“Long live time” means that a variable is alive over the course of many statements. “Short live time” means it’s alive for only a few statements. “Span” refers to how close together the references to a variable are.

325 As with span, the goal with respect to live time is to keep the number low, to
326 keep a variable live for as short a time as possible. And as with span, the basic
327 advantage of maintaining a low number is that it reduces the window of
328 vulnerability. You reduce the chance of incorrectly or inadvertently altering a
329 variable between the places in which you intend to alter it.

330 A second advantage of keeping the live time short is that it gives you an accurate
331 picture of your code. If a variable is assigned a value in line 10 and not used
332 again until line 45, the very space between the two references implies that the
333 variable is used between lines 10 and 45. If the variable is assigned a value in
334 line 44 and used in line 45, no other uses of the variable are implied, and you can
335 concentrate on a smaller section of code when you're thinking about that
336 variable.

337 A short live time also reduces the chance of initialization errors. As you modify
338 a program, straight-line code tends to turn into loops and you tend to forget
339 initializations that were made far away from the loop. By keeping the
340 initialization code and the loop code closer together, you reduce the chance that
341 modifications will introduce initialization errors.

342 Finally, a short live time makes your code more readable. The fewer lines of
343 code a reader has to keep in mind at once, the easier your code is to understand.
344 Likewise, the shorter the live time, the less code you have to keep on your screen
345 when you want to see all the references to a variable during editing and
346 debugging.

347 Measuring the Live Time of a Variable

348 You can formalize the concept of live time by counting the number of lines
349 between the first and last references to a variable (including both the first and
350 last lines). Here's an example with live times that are too long:

351 Java Example of Variables with Excessively Long Live Times

```
352 1 // initialize all variables
353 2 recordIndex = 0;
354 3 total = 0;
355 4 done = false;
356 ...
357 26 while ( recordIndex < recordCount ) {
358 27 ...
359 28 recordIndex = recordIndex + 1;
360 ...
361
362 64 while ( !done ) {
363 ...
```

359 *Last reference to recordIndex*

364 *Last reference to total*
365 *Last reference to done*
366

```
69     if ( total > projectedTotal ) {  
70         done = true;
```

Here are the live times for the variables in this example:

<i>recordIndex</i>	(line 28 – line 2 + 1) = 27
<i>total</i>	(line 69 – line 3 + 1) = 67
<i>done</i>	(line 70 – line 4 + 1) = 67
<hr/>	
Average Live Time	(27 + 67 + 67) / 3 ≈ 54

367 The example has been rewritten below so that the variable references are closer
368 together:

Java Example of Variables with Good, Short Live Times

369
370
371 *Initialization of recordIndex is*
372 *moved down from line 3.*
373
374
375
376 *Initialization of total and done*
377 *are moved down from lines 4*
378 *and 5.*
379
380
381
382

```
...  
25  recordIndex = 0;  
26  while ( recordIndex < recordCount ) {  
27  ...  
28      recordIndex = recordIndex + 1;  
...  
62  total = 0;  
63  done = false;  
64  while ( !done ) {  
...  
69      if ( total > projectedTotal ) {  
70          done = true;
```

Here are the live times for the variables in this example:

<i>recordIndex</i>	(line 28-line 25 + 1) = 4
<i>total</i>	(line 69-line 62 + 1) = 8
<i>done</i>	(line 70-line 63 + 1) = 8
Average Live Time	(4 + 8 + 8) / 3 ≈ 7

383 **FURTHER READING** For
384 more information on “live”
385 variables, see *Software*
386 *Engineering Metrics and*
387 *Models* (Conte, Dunsmore,
and Shen 1986).
Intuitively, the second example seems better than the first because the
initializations for the variables are performed closer to where the variables are
used. The measured difference in average live time between the two examples is
significant: An average of 54 vs. an average of 7 provides good quantitative
support for the intuitive preference for the second piece of code.

388
389
390
Does a hard number separate a good live time from a bad one? A good span from
a bad one? Researchers haven’t yet produced that quantitative data, but it’s safe
to assume that minimizing both span and live time is a good idea.

391
392
393
If you try to apply the ideas of span and live time to global variables, you’ll find
that global variables have enormous spans and live times—one of many good
reasons to avoid global variables.

General Guidelines for Minimizing Scope

Here are some specific guidelines you can use to minimize scope.

Initialize variables used in a loop immediately before the loop rather than back at the beginning of the routine containing the loop

Doing this improves the chance that when you modify the loop, you'll remember to make corresponding modifications to the loop initialization. Later, when you modify the program and put another loop around the initial loop, the initialization will work on each pass through the new loop rather than on only the first pass.

Don't assign a value to a variable until just before the value is used

You might have experienced the frustration of trying to figure out where a variable was assigned its value. The more you can do to clarify where a variable receives its value, the better. Languages like C++ and Java support variable initializations like these:

C++ Example of Good Variable Declarations and Initializations

```
int receiptIndex = 0;
float dailyReceipts = TodaysReceipts();
double totalReceipts = TotalReceipts( dailyReceipts );
```

Group related statements

The following examples show a routine for summarizing daily receipts and illustrate how to put references to variables together so that they're easier to locate. The first example illustrates the violation of this principle:

C++ Example of Using Two Sets of Variables in a Confusing Way

```
void SummarizeData (...) {
    ...
    GetOldData( oldData, &numOldData );
    GetNewData( newData, &numNewData );
    totalOldData = Sum( oldData, numOldData );
    totalNewData = Sum( newData, numNewData );
    PrintOldDataSummary( oldData, totalOldData, numOldData );
    PrintNewDataSummary( newData, totalNewData, numNewData );
    SaveOldDataSummary( totalOldData, numOldData );
    SaveNewDataSummary( totalNewData, numNewData );
    ...
}
```

Note that, in the example above, you have to keep track of *oldData*, *newData*, *numOldData*, *numNewData*, *totalOldData*, and *totalNewData* all at once—six variables for just this short fragment. The example below shows how to reduce that number to only three elements

394

395

396 **CROSS-REFERENCE** For
 397 details on initializing
 398 variables close to where
 399 they're used, see Section
 400 10.3, "Guidelines for
 401 Initializing Variables," earlier
 402 in this chapter.

403 **CROSS-REFERENCE** For
 404 more on this style of variable
 405 declaration and definition,
 406 see "Ideally, declare and
 407 "Initialize each variable close
 408 to where it's first used" in
 409 Section 10.3, earlier in this
 410 chapter.

409

410

411

412

413 **CROSS-REFERENCE** For
 414 more details on keeping
 415 related statements together,
 416 see Section 14.2, "Statements
 Whose Order Doesn't
 Matter."

417

418

419 *Statements using two sets of*
 420 *variables*

421

422

423

424

425

426

427

428

429

430

431

432

433
434
435 *Statements using oldData*
436
437
438
439
440 *Statements using newData*
441
442
443
444
445
446
447
448
449

C++ Example of Using Two Sets of Variables More Understandably

```
void SummarizeDaily( ... ) {
    GetOldData( oldData, &numOldData );
    totalOldData = Sum( oldData, numOldData );
    PrintOldDataSummary( oldData, totalOldData, numOldData );
    SaveOldDataSummary( totalOldData, numOldData );
    ...
    GetNewData( newData, &numNewData );
    totalNewData = Sum( newData, numNewData );
    PrintNewDataSummary( newData, totalNewData, numNewData );
    SaveNewDataSummary( totalNewData, numNewData );
    ...
}
```

When the code is broken up as shown above, the two blocks are each shorter than the original block and individually contain fewer variables. They're easier to understand, and if you need to break this code out into separate routines, the shorter blocks with fewer variables make better-defined routines.

450 **CROSS-REFERENCE** For
451 more on global variables, see
452 Section 13.3, "Global Data."

Begin with most restricted visibility, and expand the variable's scope only if necessary

Part of minimizing the scope of a variable is keeping it as local as possible. It is much more difficult to reduce the scope of a variable that has had a large scope than to expand the scope of a variable that has had a small scope—in other words, it's harder to turn a global variable into a class variable than it is to turn a class variable into a global variable. It's harder to turn a protected data member into a private data member than vice versa. For that reason, when in doubt, favor the smallest possible scope for a variable—local to an individual routine if possible, then private, then protected, then package (if your programming language supports that), and global only as a last resort.

Comments on Minimizing Scope

Many programmers' approach to minimizing variables' scope depends on their views of the issues of "convenience" and "intellectual manageability." Some programmers make many of their variables global because global scope makes variables convenient to access and the programmers don't have to fool around with parameter lists and class scoping rules. In their minds, the convenience of being able to access variables at any time outweighs the risks involved.

468 **CROSS-REFERENCE** The
 469 idea of minimizing scope is
 470 related to the idea of
 471 information hiding. For
 472 details, see “Hide Secrets
 (Information Hiding)” in
 Section 5.3.

473 **KEY POINT**

474

475

476

477

478

479

480

481 **CROSS-REFERENCE** For
 482 details on using access
 483 routines, see “Using Access
 484 Routines Instead of Global
 Data” in Section 13.3.

485

486

487

Other programmers prefer to keep their variables as local as possible because local scope helps intellectual manageability. The more information you can hide, the less you have to keep in mind at any one time. The less you have to keep in mind, the smaller the chance that you’ll make an error because you forgot one of the many details you needed to remember.

The difference between the “convenience” philosophy and the “intellectual manageability” philosophy boils down to a difference in emphasis between writing programs and reading them. Maximizing scope might indeed make programs easy to write, but a program in which any routine can use any variable at any time is harder to understand than a program that uses well-factored routines. In such a program, you can’t understand only one routine; you have to understand all the other routines with which that routine shares global data. Such programs are hard to read, hard to debug, and hard to modify.

Consequently, you should declare each variable to be visible to the smallest segment of code that needs to see it. If you can confine the variable’s scope to a single routine, great. If you can’t confine the scope to one routine, restrict the visibility to the routines in a single class. If you can’t restrict the variable’s scope to the class that’s most responsible for the variable, create access routines to share the variable’s data with other classes. You’ll find that you rarely if ever need to use naked global data.

10.5 Persistence

“Persistence” is another word for the life span of a piece of data. Persistence takes several forms. Some variables persist

- for the life of a particular block of code or routine. Variables declared inside a *for* loop in C++ or Java are examples of this kind of persistence.
- as long as you allow them to. In Java, variables created with *new* persist until they are garbage collected. In C++, variables created with *new* persist until you *delete* them.
- for the life of a program. Global variables in most languages fit this description, as do *static* variables in C++ and Java.
- forever. These variables might include values that you store in a database between executions of a program. For example, if you have an interactive program in which users can customize the color of the screen, you can store their colors in a file and then read them back each time the program is loaded.

The main problem with persistence arises when you assume that a variable has a longer persistence than it really does. The variable is like that jug of milk in your refrigerator. It's supposed to last a week. Sometimes it lasts a month, and sometimes it turns sour after five days. A variable can be just as unpredictable. If you try to use the value of a variable after its normal life span is over, will it have retained its value? Sometimes the value in the variable is sour, and you know that you've got an error. Other times, the computer leaves the old value in the variable, letting you imagine that you have used it correctly.

Here are a few steps you can take to avoid this kind of problem:

- CROSS-REFERENCE** Debug code is easy to include in access routines and is discussed more in “Advantages of Access Routines” in Section 13.3.
- Use debug code or assertions in your program to check critical variables for reasonable values. If the values aren't reasonable, display a warning that tells you to look for improper initialization.
 - Write code that assumes data isn't persistent. For example, if a variable has a certain value when you exit a routine, don't assume it has the same value the next time you enter the routine. This doesn't apply if you're using language-specific features that guarantee the value will remain the same, such as *static* in C++ and Java.
 - Develop the habit of declaring and initializing all data right before it's used. If you see data that's used without a nearby initialization, be suspicious!

10.6 Binding Time

An initialization topic with far-reaching implications for program maintenance and modifiability is “binding time”—the time at which the variable and its value are bound together (Thimbleby 1988). Are they bound together when the code is written? When it is compiled? When it is loaded? When the program is run? Some other time?

It can be to your advantage to use the latest binding time possible. In general, the later you make the binding time, the more flexibility you build into your code. The next example shows binding at the earliest possible time, when the code is written.

Java Example of a Variable That's Bound at Code-Writing Time

```
titleBar.color = 0xFF; // 0xFF is hex value for color blue
```

The value *0xFF* is bound to the variable *titleBar.color* at the time the code is written because *0xFF* is a literal value hard-coded into the program. Hard-coding like this is nearly always a bad idea because if this *0xFF* changes, it can get out of synch with *0xFF*s used elsewhere in the code that must be the same value as this one.

539 Here's an example of binding at a slightly later time, when the code is compiled:

540 **Java Example of a Variable That's Bound at Compile Time**

```
541 private static final int COLOR_BLUE = 0xFF;
542 private static final int TITLE_BAR_COLOR = COLOR_BLUE;
543 ...
544 titleBar.color = TITLE_BAR_COLOR;
```

545 *TITLE_BAR_COLOR* is a named constant, an expression for which the compiler
546 substitutes a value at compile time. This is nearly always better than hard-
547 coding, if your language supports it. It increases readability because
548 *TITLE_BAR_COLOR* tells you more about what is being represented than *0xFF*
549 does. It makes changing the title bar color easier because one change accounts
550 for all occurrences. And it doesn't incur a run-time performance penalty.

551 Here's an example of binding later, at run time:

552 **Java Example of a Variable That's Bound at Run Time**

```
553 titleBar.color = ReadTitleBarColor();
```

554 *ReadTitleBarColor()* is a routine that reads a value while a program is executing,
555 perhaps from the Windows registry.

556 The code is more readable and flexible than it would be if a value were hard-
557 coded. You don't need to change the program to change *titleBar.color*; you
558 simply change the contents of the source that's read by *ReadTitleBarColor()*.
559 This approach is commonly used for interactive applications in which a user can
560 customize the application environment.

561 There is still another variation in binding time, which has to do with when the
562 *ReadTitleBarColor()* routine is called. That routine could be called once at
563 program load time, each time the window is created, or each time the window is
564 drawn—each alternative representing successively later binding times.

565 To summarize, here are the times a variable can be bound to a value in this
566 example (the details could vary somewhat in other cases):

- 567 • Coding time (use of magic numbers)
- 568 • Compile time (use of a named constant)
- 569 • Load time (reading a value from an external source such as the Windows
570 Registry)
- 571 • Object instantiation time (such as reading the value each time a window is
572 created)
- 573 • Just in time (such as reading the value each time the window is drawn)

574

575

576

577

578

579

580

581

582

583

In general, the earlier the binding time, the lower the flexibility and the lower the complexity. For the first two options, using named constants is preferable to using magic numbers for many reasons, so you can get the flexibility that named constants provide just by using good programming practices. Beyond that, the greater the flexibility desired, the higher the complexity of the code needed to support that flexibility, and the more error-prone the code will be. Because successful programming depends on minimizing complexity, a skilled programmer will build in as much flexibility as needed to meet the software’s requirements but will not add flexibility—and related complexity—beyond what’s required.

584

585

10.7 Relationship Between Data Types and Control Structures

586

587

588

589

Data types and control structures relate to each other in well-defined ways that were originally described by the British computer scientist Michael Jackson (Jackson 1975). This section sketches the regular relationship between data and control flow.

590

591

Jackson draws connections between three types of data and corresponding control structures.

592

593


594

595

CROSS-REFERENCE For details on sequences, see Chapter 14, “Organizing Straight-Line Code.”

Sequential data translates to sequential statements in a program

Sequences consist of clusters of data used together in a certain order. If you have five statements in a row that handle five different values, they are sequential statements. If you read an employee’s name, social security number, address, phone number, and age from a file, you’d have sequential statements in your program to read sequential data from the file.



598

599

600

601

F10xx02

Figure 10-2

Sequential data is data that’s handled in a defined order.

602

603

604


605

CROSS-REFERENCE For details on conditionals, see Chapter 15, “Using Conditionals.”

Selective data translates to if and case statements in a program

In general, selective data is a collection in which one of several pieces of data is present at any particular time—one of the elements is selected. The corresponding program statements must do the actual selection, and they consist

of *If-Then-Else* or *Case* statements. If you had an employee payroll program, you might process employees differently depending on whether they were paid hourly or salaried. Again, patterns in the code match patterns in the data.




F10xx03

Figure 10-3

Selective data allows you to use one piece or the other, but not both.

Iterative data translates to for, repeat, and while looping structures in a program

Iterative data is the same type of data repeated several times. Typically, iterative data is stored as records in a file or in arrays. You might have a list of social security numbers that you read from a file. The iterative data would match the iterative code loop used to read the data.



F10xx04

Figure 10-4

Iterative data is repeated.

Your real data can be combinations of the sequential, selective, and iterative types of data. You can combine the simple building blocks to describe more complicated data types.

10.8 Using Each Variable for Exactly One Purpose

KEY POINT

It's possible to use variables for more than one purpose in several subtle ways. You're better off without this kind of subtlety.

Use each variable for one purpose only

It's sometimes tempting to use one variable in two different places for two different activities. Usually, the variable is named inappropriately for one of its uses, or a “temporary” variable is used in both cases (with the usual unhelpful name *x* or *temp*). Here's an example that shows a temporary variable that's used for two purposes:

CODING HORROR

C++ Example of Using One Variable for Two Purposes—Bad Practice

```
// Compute roots of a quadratic equation.
// This code assumes that (b*b-4*a*c) is positive.
temp = Sqrt( b*b - 4*a*c );
root[0] = ( -b + temp ) / ( 2 * a );
root[1] = ( -b - temp ) / ( 2 * a );
...
// swap the roots
temp = root[0];
root[0] = root[1];
root[1] = temp;
```

Question: What is the relationship between *temp* in the first few lines and *temp* in the last few? Answer: The two *temp* have no relationship. Using the same variable in both instances makes it seem as though they're related when they're not. Creating unique variables for each purpose makes your code more readable. Here's an improvement on the example above:

C++ Example of Using Two Variables for Two Purposes—Good Practice

```
// Compute roots of a quadratic equation.
// This code assumes that (b*b-4*a*c) is positive.
discriminant = Sqrt( b*b - 4*a*c );
root[0] = ( -b + discriminant ) / ( 2 * a );
root[1] = ( -b - discriminant ) / ( 2 * a );
...
// swap the roots
oldRoot = root[0];
root[0] = root[1];
root[1] = oldRoot;
```

CROSS-REFERENCE Routine parameters should also be used for one purpose only. For details on using routine parameters, see Section 7.5, “How to Use Routine Parameters.”

663

664

665

666 **CODING HORROR**

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684 **HARD DATA**

685

686

687

688

689

690 **CROSS-REFERENCE** For

691 a checklist that applies to

692 specific types of data rather

693 than general issues, see the

694 checklist in Chapter 12,

695 “Fundamental Data Types.”

696 For issues in naming

697 variables, see the checklist in

698 Chapter 11, “The Power of

Variable Names.”

Avoid variables with hidden meanings

Another way in which a variable can be used for more than one purpose is to have different values for the variable mean different things. For example

- The value in the variable *pageCount* might represent the number of pages printed, unless it equals *-1*, in which case it indicates that an error has occurred.
- The variable *customerId* might represent a customer number, unless its value is greater than *500,000*, in which case you subtract *500,000* to get the number of a delinquent account.
- The variable *bytesWritten* might be the number of bytes written to an output file, unless its value is negative, in which case it indicates the number of the disk drive used for the output.

Avoid variables with these kinds of hidden meanings. The technical name for this kind of abuse is “hybrid coupling” (Page-Jones 1988). The variable is stretched over two jobs, meaning that the variable is the wrong type for one of the jobs. In the *pageCount* example above, *pageCount* normally indicates the number of pages; it’s an integer. When *pageCount* is *-1*, however, it indicates that an error has occurred; the integer is moonlighting as a boolean!

Even if the double use is clear to you, it won’t be to someone else. The extra clarity you’ll achieve by using two variables to hold two kinds of information will amaze you. And no one will begrudge you the extra storage.

Make sure that all declared variables are used

The opposite of using a variable for more than one purpose is not using it at all. A study by Card, Church, and Agresti found that unreferenced variables were correlated with higher fault rates (1986). Get in the habit of checking to be sure that all variables that are declared are used. Some compilers and utilities (such as lint) report unused variables as a warning.

CHECKLIST: General Considerations In Using Data

- Initializing Variables**
- ☐ Does each routine check input parameters for validity?
 - ☐ Does the code declare variables close to where they’re first used?
 - ☐ Does the code initialize variables as they’re declared, if possible?
 - ☐ Does the code initialize variables close to where they’re first used, if it isn’t possible to declare and initialize them at the same time?
 - ☐ Are counters and accumulators initialized properly and, if necessary, reinitialized each time they are used?

- 699 ☐ Are variables reinitialized properly in code that's executed repeatedly?
- 700 ☐ Does the code compile with no warnings from the compiler?
- 701 ☐ If your language uses implicit declarations, have you compensated for the
- 702 problems they cause?

703 Other General Issues in Using Data

- 704 ☐ Do all variables have the smallest scope possible?
 - 705 ☐ Are references to variables as close together as possible—both from each
 - 706 reference to a variable to the next and in total live time?
 - 707 ☐ Do control structures correspond to the data types?
 - 708 ☐ Are all the declared variables being used?
 - 709 ☐ Are all variables bound at appropriate times, that is, striking a conscious
 - 710 balance between the flexibility of late binding and the increased complexity
 - 711 associated with late binding?
 - 712 ☐ Does each variable have one and only one purpose?
 - 713 ☐ Is each variable's meaning explicit, with no hidden meanings?
 - 714
-

715 Key Points

- 716 • Data initialization is prone to errors, so use the initialization techniques
- 717 described in this chapter to avoid the problems caused by unexpected initial
- 718 values.
- 719 • Minimize the scope of each variable. Keep references to it close together.
- 720 Keep it local to a routine or class. Avoid global data.
- 721 • Keep statements that work with the same variables as close together as
- 722 possible.
- 723 • Early binding tends to limit flexibility, but minimize complexity. Late
- 724 binding tends to increase flexibility, but at the price of increased complexity.
- 725 • Use each variable for one and only one purpose.