

26

Code-Tuning Techniques

Contents

- 26.1 Logic
- 26.2 Loops
- 26.3 Data Transformations
- 26.4 Expressions
- 26.5 Routines
- 26.6 Recoding in Assembler
- 26.7 The More Things Change, the More They Stay the Same

Related Topics

- Code-tuning strategies: Chapter 28
- Refactoring: Chapter 24

CODE TUNING HAS BEEN a popular topic during most of the history of computer programming. Consequently, once you’ve decided that you need to improve performance and that you want to do it at the code level, you have a rich set of techniques at your disposal.

This chapter focuses on improving speed and includes a few tips for making code smaller. Performance usually refers to both speed and size, but size reductions tend to come more from redesigning classes and data than from tuning code. Code tuning refers to small-scale changes rather than changes in larger-scale designs.

Few of the techniques in this chapter are so generally applicable that you’ll be able to copy the example code directly into your programs. The main purpose of the discussion here is to illustrate a handful of code tunings that you can adapt to your situation.

The code-tuning changes described in this chapter might seem cosmetically similar to the refactorings described in Chapter 24. But refactorings are changes that improve a program’s internal structure (Fowler 1999). The changes in this chapter might better be called “anti-refactorings.” Far from “improving the

internal structure,” these changes degrade the internal structure in exchange for gains in performance. This is true by definition. If they didn’t degrade the internal structure, we wouldn’t consider them to be optimizations; we would use them by default and consider them to be standard coding practice.

Some books present code tuning techniques as “rules of thumb” or cite research that suggests that a specific tuning will produce the desired effect. As you will soon see, the concept of “rules of thumb” applies poorly to code tuning. The only reliable rule of thumb is to measure the effect of each tuning in your environment. Thus this chapter presents a catalog of “things to try”—many of which won’t work in your environment but some of which will work very well indeed.

26.1 Logic

Much of programming consists of manipulating logic. This section describes how to manipulate logical expressions to your advantage.

Stop Testing When You Know the Answer

Suppose you have a statement like

```
if ( 5 < x ) and ( x < 10 ) then ...
```

Once you’ve determined that x is less than 5, you don’t need to perform the second half of the test.

Some languages provide a form of expression evaluation known as “short-circuit evaluation,” which means that the compiler generates code that automatically stops testing as soon as it knows the answer. Short-circuit evaluation is part of C++’s standard operators and Java’s “conditional” operators.

If your language doesn’t support short-circuit evaluation natively, you have to avoid using *and* and *or*, adding logic instead. With short-circuit evaluation, the code above changes to this:

```
if ( 5 < x ) then
    if ( x < 10 ) then ...
```

The principle of not testing after you know the answer is a good one for many other kinds of cases as well. A search loop is a common case. If you’re scanning an array of input numbers for a negative value and you simply need to know whether a negative value is present, one approach is to check every value, setting a *negativeFound* variable when you find one. Here’s how the search loop would look:

C++ Example of Not Stopping After You Know the Answer

```
negativeInputFound = False;
for ( i = 0; i < iCount; i++ ) {
    if ( input[ i ] < 0 ) {
        negativeInputFound = True;
    }
}
```

A better approach would be to stop scanning as soon as you find a negative value. Here are the approaches you could use to solve the problem:

- Add a *break* statement after the *negativeInputFound = True* line.
- If your language doesn't have *break*, emulate a *break* with a *goto* that goes to the first statement after the loop.
- Change the *for* loop to a *while* loop and check for *negativeInputFound* as well as for incrementing the loop counter past *iCount*.
- Change the *for* loop to a *while* loop, put a sentinel value in the first array element after the last value entry, and simply check for a negative value in the *while* test. After the loop terminates, see whether the position of the first found value is in the array or one past the end. Sentinels are discussed in more detail later in the chapter.

Here are the results of using the *break* keyword in C++ and Java:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	4.27	3.68	14%
Java	4.85	3.46	29%

Note: (1) Times in these tables are given in seconds and are meaningful only for comparisons across rows of each table. Actual times will vary according to the compiler and compiler options used and the environment in which each test is run. (2) Benchmark results are typically made up of several thousand to many million executions of the code fragments to smooth out the sample-to-sample fluctuations in the results. (3) Specific brands and versions of compilers aren't indicated. Performance characteristics vary significantly from brand to brand and version to version. (4) Comparisons among results from different languages aren't always meaningful because compilers for different languages don't always offer comparable code-generation options. (5) The results shown for interpreted languages (PHP and Python) are typically based on less than 1% of the test runs used for the other languages. (6) Some of the "time savings" percentages might not be exactly reproducible from the data in these tables due to rounding of the "straight time" and "code-tuned time" entries.

The impact of this change varies a great deal depending on how many values you have and how often you expect to find a negative value. This test assumed an average of 100 values and assumed that a negative value would be found 50 percent of the time.

Order Tests by Frequency

Arrange tests so that the one that's fastest and most likely to be true is performed first. It should be easy to drop through the normal case, and if there are inefficiencies, they should be in processing the uncommon cases. This principle applies to *case* statements and to chains of *if-then-elses*.

Here's a *Select-Case* statement that responds to keyboard input in a word processor:

Visual Basic Example of a Poorly Ordered Logical Test

```
Select inputCharacter
  Case "+", "="
    ProcessMathSymbol( inputCharacter )
  Case "0" To "9"
    ProcessDigit( inputCharacter )
  Case ",", ".", ":", ";", "!", "?"
    ProcessPunctuation( inputCharacter )
  Case " "
    ProcessSpace( inputCharacter )
  Case "A" To "Z", "a" To "z"
    ProcessAlpha( inputCharacter )
  Case Else
    ProcessError( inputCharacter )
End Select
```

The cases in this *case* statement are ordered in something close to the ASCII sort order. In a *case* statement, however, the effect is often the same as if you had written a big set of *if-then-elses*, so if you get an `<$QS>a<$QS>` as an input character, the program tests whether it's a math symbol, a punctuation mark, a digit, or a space before determining that it's an alphabetic character. If you know the likely frequency of your input characters, you can put the most common cases first. Here's the reordered *case* statement:

Visual Basic Example of a Well-Ordered Logical Test

```
Select inputCharacter
  Case "A" To "Z", "a" To "z"
    ProcessAlpha( inputCharacter )
  Case " "
    ProcessSpace( inputCharacter )
```

```
Case ",", ".:", ":", ";", "!", "?"
    ProcessPunctuation( inputCharacter )
Case "0" To "9"
    ProcessDigit( inputCharacter )
Case "+", "="
    ProcessMathSymbol( inputCharacter )
Case Else
    ProcessError( inputCharacter )
End Select
```

Since the most common case is usually found sooner in the optimized code, the net effect will be the performance of fewer tests. Here are the results of this optimization with a typical mix of characters:

Language	Straight Time	Code-Tuned Time	Time Savings
C#	0.220	0.260	-18%
Java	2.56	2.56	0%
Visual Basic	0.280	0.260	7%

Note: Benchmarked with an input mix of 78 percent alphabetic characters, 17 percent spaces, and 5 percent punctuation symbols.

The Visual Basic results are as expected, but the Java and C# results are not as expected. Apparently that's because of the way *switch-case* statements are structured in C++ and Java—since each value must be enumerated individually rather than in ranges, the C++ and Java code doesn't benefit from the optimization as the Visual Basic code does. This result underscores the importance of not following any optimization advice blindly—specific compiler implementations will significantly affect the results.

You might assume that the code generated by the Visual Basic compiler for a set of *if-then-elses* that perform the same test as the *case* statement would be similar. Here are those results:

Language	Straight Time	Code-Tuned Time	Time Savings
C#	0.630	0.330	48%
Java	0.922	0.460	50%
Visual Basic	1.36	1.00	26%

The results are quite different. For the same number of tests, the VB compiler takes about 5 times as long in the unoptimized case, 4 times in the optimized case. This suggests that the compiler is generating different code for the *case* approach than for the *if-then-else* approach.

166 The improvement with *if-then-elses* is more consistent than it was with the *case*
167 statements, but that’s a mixed blessing. In *C#* and *VB* both versions of the *case*
168 statement approach are faster than both versions of the *if-then-else* approach,
169 whereas in *Java* both versions are slower.

170 This variation in results suggests a third possible optimization, described in the
171 next section.

172 **Compare Performance of Similar Logic Structures**

173 The test described above could be performed using either a *case* statement or *if-*
174 *then-elses*. Depending on the environment, either approach might work better.
175 Here is the data from the preceding two tables reformatted to present the “code-
176 tuned” times comparing *if-then-else* and *case* performance:

Language	case	if-then-else	Time Savings	Performance Ratio
C#	0.260	0.330	-27%	1:1
Java	2.56	0.460	82%	6:1
Visual Basic	0.260	1.00	258%	1:4


177 These results defy any logical explanation. In one of the languages, *case* is
178 dramatically superior to *if-then-else*, and in another, *if-then-else* is dramatically
179 superior to *case*. In the third language, the difference is relatively small. You
180 might think that because *C#* and *Java* share similar syntax for *case* statements,
181 their results would be similar, but in fact their results are opposite each other.

182 This example clearly illustrates the difficulty of performing any sort of “rule of
183 thumb” or “logic” to code tuning—there is simply no reliable substitute for
184 *measuring* results.

185 **Substitute Table Lookups for Complicated**
186 **Expressions**

187 **CROSS-REFERENCE** For
188 details on using table lookups
189 to replace complicated logic,
190 see Chapter 18, “Table-
191 Driven Methods.”

In some circumstances, a table lookup may be quicker than traversing a complicated chain of logic. The point of a complicated chain is usually to categorize something and then to take an action based on its category. As an abstract example, suppose you want to assign a category number to something based on which of Groups *A*, *B*, and *C* it falls into:



G26xx01

Here’s an example of the complicated logic chain that assigns the category numbers:

C++ Example of a Complicated Chain of Logic

```
if ( ( a && !c ) || ( a && b && c ) ) {
    category = 1;
}
else if ( ( b && !a ) || ( a && c && !b ) ) {
    category = 2;
}
else if ( c && !a && !b ) {
    category = 3;
}
else {
    category = 0;
}
```

You can replace this test with a more modifiable and higher-performance lookup table. Here’s how:

C++ Example of Using a Table Lookup to Replace Complicated Logic

```
// define categoryTable
static int categoryTable[ 2 ][ 2 ][ 2 ] = {
    // !b!c !bc b!c bc
    0,  3,  2,  2,  // !a
    1,  2,  1,  1,  // a
};
...

category = categoryTable[ a ][ b ][ c ];
```

Although the definition of the table is hard to read, if it’s well documented it won’t be any harder to read than the code for the complicated chain of logic was. If the definition changes, the table will be much easier to maintain than the earlier logic would have been. Here are the performance results:

192
193
194
195

196
197
198
199
200
201
202
203
204
205
206
207
208
209
210

211
212
213
214
215
216
217
218
219
220
221
222
223
224

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	5.04	3.39	33%	1.5:1
Visual Basic	5.21	2.60	50%	2:1

Use Lazy Evaluation

One of my former roommates was a great procrastinator. He justified his laziness by saying that many of the things people feel rushed to do simply don't need to be done. If he waited long enough, he claimed, the things that weren't important would be procrastinated into oblivion, and he wouldn't waste his time doing them.

Lazy evaluation is based on the principle my roommate used. If a program uses lazy evaluation, it avoids doing any work until the work is needed. Lazy evaluation is similar to just-in-time strategies that do the work closest to when it's needed.

Suppose, for example, that your program contains a table of 5000 values, generates the whole table at startup time, and then uses it as the program executes. If the program uses only a small percentage of the entries in the table, it might make more sense to compute them as they're needed rather than all at once. Once an entry is computed, it can still be stored for future reference ("cached").

26.2 Loops

Because loops are executed many times, the hot spots in a program are often inside loops. The techniques in this section make the loop itself faster.

Unswitching

Switching refers to making a decision inside a loop every time it's executed. If the decision doesn't change while the loop is executing, you can unswitch the loop by making the decision outside the loop. Usually this requires turning the loop inside out, putting loops inside the conditional rather than putting the conditional inside the loop. Here's an example of a loop before unswitching:

CODING HORROR

225
226
227
228
229
230

231
232
233
234

235
236
237
238
239
240

241

242
243
244

245
246
247
248
249

250 **CROSS-REFERENCE** As
251 in the last chapter, this code
252 fragment violates several
253 rules of good programming.
254 Readability and maintenance
255 are usually more important
256 than execution speed or size,
257 but in this chapter the topic is
258 performance, and that implies
259 a trade-off with the other
260 objectives. Like the last
261 chapter, you'll see many
262 examples of coding practices
263 here that aren't recommended
264 in other parts of this book.

```
C++ Example of a Switched Loop
for ( i = 0; i < count; i++ ) {
    if ( sumType == SUMTYPE_NET ) {
        netSum = netSum + amount[ i ];
    }
    else {
        grossSum = grossSum + amount[ i ];
    }
}
```

In this code, the test *if(sumType == SUMTYPE_NET)* is repeated through each iteration even though it'll be the same each time through the loop. You can rewrite the code for a speed gain this way:

```
C++ Example of an Unswitched Loop
if ( sumType == SUMTYPE_NET ) {
    for ( i = 0; i < count; i++ ) {
        netSum = netSum + amount[ i ];
    }
}
else {
    for ( i = 0; i < count; i++ ) {
        grossSum = grossSum + amount[ i ];
    }
}
```

This is good for about a 20 percent time savings:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	2.81	2.27	19%
Java	3.97	3.12	21%
Visual Basic	2.78	2.77	<1%
Python	8.14	5.87	28%

A hazard distinct to this case is that the two loops have to be maintained in parallel. If *count* changes to *clientCount*, you have to remember to change it in both places, which is an annoyance for you and a maintenance headache for anyone else who has to work with the code.

This example also illustrates a key challenge in code tuning—the effect of any specific code tuning is not predictable. The code tuning produced significant improvements in three of the four languages, but not in Visual Basic. To perform this specific optimization in this specific version of VB would produce less maintainable code without any offsetting gain in performance. The general

283 lesson is that you must measure the effect of each specific optimization to be
284 sure of its effect—no exceptions.

285 **Jamming**

286 Jamming, or “fusion,” is the result of combining two loops that operate on the
287 same set of elements. The gain lies in cutting the loop overhead from two loops
288 to one. Here’s a candidate for loop jamming:

289 **Visual Basic Example of Separate Loops That Could Be Jammed**

```
290 For i = 0 to employeeCount - 1  
291     employeeName( i ) = ""  
292 Next  
293 ...  
294 For i = 0 to employeeCount - 1  
295     employeeEarnings( i ) = 0  
296 Next
```

297 When you jam loops, you find code in two loops that you can combine into one.
298 Usually, that means the loop counters have to be the same. In this example, both
299 loops run from 0 to employeeCount - 1, so you can jam them. Here’s how:

300 **CODING HORROR**

Visual Basic Example of a Jammed Loop

```
301 For i = 0 to employeeCount - 1  
302     employeeName( i ) = ""  
303     employeeEarnings( i ) = 0  
304 Next
```

305 Here are the savings:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	3.68	2.65	28%
PHP	3.97	2.42	32%
Visual Basic	3.75	3.56	4%

306 *Note: Benchmarked for the case in which employeeCount equals 100.*

307 As before, the results vary significantly among languages.

308 Loop jamming has two main hazards. First, the indexes for the two parts that
309 have been jammed might change so that they’re no longer compatible. Second,
310 you might not be able to combine the loops easily. Before you combine the
311 loops, make sure they’ll still be in the right order with respect to the rest of the
312 code.

Unrolling

The goal of loop unrolling is to reduce the amount of loop housekeeping. In Chapter 25, a loop was completely unrolled, and 10 lines of code were shown to be faster than 3. In that case, the loop that went from 3 to 10 lines was unrolled so that all 10 array accesses were done individually.

Although completely unrolling a loop is a fast solution and works well when you're dealing with a small number of elements, it's not practical when you have a large number of elements or when you don't know in advance how many elements you'll have. Here's an example of a general loop:

Java Example of a Loop That Can Be Unrolled

```
i = 0;
while ( i < count ) {
    a[ i ] = i;
    i = i + 1;
}
```

To unroll the loop partially, you handle two or more cases in each pass through the loop instead of one. This unrolling hurts readability but doesn't hurt the generality of the loop. Here's the loop unrolled once:

Java Example of a Loop That's Been Unrolled Once

```
i = 0;
while ( i < count - 1 ) {
    a[ i ] = i;
    a[ i + 1 ] = i + 1;
    i = i + 2;
}

if ( i == count ) {
    a[ count - 1 ] = count - 1;
}
```

The technique replaced the original `a[i] = i` line with two lines, and `i` is incremented by 2 rather than by 1. The extra code after the `while` loop is needed when `count` is odd and the loop has one iteration left after the loop terminates.

When five lines of straightforward code expand to nine lines of tricky code, the code becomes harder to read and maintain. Except for the gain in speed, its quality is poor. Part of any design discipline, however, is making necessary trade-offs. So, even though a particular technique generally represents poor coding practice, specific circumstances may make it the best one to use.

Here are the results of unrolling the loop:

331 CODING HORROR

332
333
334
335
336
337
338
339 These lines pick up the case
340 that might fall through the
341 cracks if the loop went by
342 twos instead of by ones.

Language	Straight Time	Code-Tuned Time	Time Savings
C++	1.75	1.15	34%
Java	1.01	0.581	43%
PHP	5.33	4.49	16%
Python	2.51	3.21	-27%

Note: Benchmarked for the case in which count equals 100.

A gain of 16 to 43 percent is respectable, although again you have to watch out for hurting performance, as the Python benchmark shows. The main hazard of loop unrolling is an off-by-one error in the code after the loop that picks up the last case.

What if you unroll the loop even further, going for two or more unrollings? Do you get more benefit? Here's the code for a loop unrolled twice:

Java Example of a Loop That's Been Unrolled Twice

```
i = 0;
while ( i < count - 2 ) {
    a[ i ] = i;
    a[ i + 1 ] = i+1;
    a[ i + 2 ] = i+2;
    i = i + 3;
}
if ( i <= count - 1 ) {
    a[ count - 1 ] = count - 1;
}
if ( i == count - 2 ) {
    a[ count -2 ] = count - 2;
}
```

Here are the results of unrolling the loop the second time:

Language	Straight Time	Single Unrolled Time	Double Unrolled Time	Time Savings
C++	1.75	1.15	1.01	42%
Java	1.01	0.581	0.581	43%
PHP	5.33	4.49	3.70	31%
Python	2.51	3.21	2.79	-12%

Note: Benchmarked for the case in which count equals 100.

The results indicate that further loop unrolling can result in further time savings, but not necessarily so, as the Java measurement shows. The main concern is how

CODING HORROR

376 Byzantine your code becomes. When you look at the code above, you might not
377 think it looks incredibly complicated, but when you realize that it started life a
378 couple of pages ago as a five-line loop, you can appreciate the trade-off between
379 performance and readability.

380

Minimizing the Work Inside Loops

381 One key to writing effective loops is to minimize the work done inside a loop. If
382 you can evaluate a statement or part of a statement outside a loop so that only the
383 result is used inside the loop, do so. It's good programming practice, and, in
384 some cases, it improves readability.

385 Suppose you have a complicated pointer expression inside a hot loop that looks
386 like this:

387

C++ Example of a Complicated Pointer Expression Inside a Loop

388 `for (i = 0; i < rateCount; i++) {`
389 `netRate[i] = baseRate[i] * rates->discounts->factors->net;`
390 `}`

391 In this case, assigning the complicated pointer expression to a well-named
392 variable improves readability and often improves performance.

393

C++ Example of Simplifying a Complicated Pointer Expression

394 `quantityDiscount = rates->discounts->factors->net;`
395 `for (i = 0; i < rateCount; i++) {`
396 `netRate[i] = baseRate[i] * quantityDiscount;`
397 `}`

398 The extra variable, *quantityDiscount*, makes it clear that the *baseRate* array is
399 being multiplied by a quantity-discount factor to compute the net rate. That
400 wasn't at all clear from the original expression in the loop. Putting the
401 complicated pointer expression into a variable outside the loop also saves the
402 pointer from being dereferenced three times for each pass through the loop,
403 resulting in the following savings:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	3.69	2.97	19%
C#	2.27	1.97	13%
Java	4.13	2.35	43%

Note: Benchmarked for the case in which rateCount equals 100.

Except for the Java compiler, the savings aren't anything to crow about, implying that during initial coding you can use whichever technique is more readable without worrying about the speed of the code until later.

Sentinel Values

When you have a loop with a compound test, you can often save time by simplifying the test. If the loop is a search loop, one way to simplify the test is to use a sentinel value, a value that you put just past the end of the search range and that's guaranteed to terminate the search.

The classic example of a compound test that can be improved by use of a sentinel is the search loop that checks both whether it has found the value it is seeking and whether it has run out of values. Here's the code:

C# Example of Compound Tests in a Search Loop

```
found = FALSE;
i = 0;
while ( ( !found ) && ( i < count ) ) {
    if ( item[ i ] == testValue ) {
        found = TRUE;
    }
    else {
        i++;
    }
}

if ( found ) {
    ...
}
```

Here's the compound test.

In this code, each iteration of the loop tests for *!found* and for *i < count*. The purpose of the *!found* test is to determine when the desired element has been found. The purpose of the *i < count* test is to avoid running past the end of the array. Inside the loop, each value of *item[]* is tested individually, so the loop really has three tests for each iteration.

In this kind of search loop, you can combine the three tests so that you test only once per iteration by putting a "sentinel" at the end of the search range to stop the loop. In this case, you can simply assign the value you're looking for to the element just beyond the end of the search range. (Remember to leave space for that element when you declare the array.) You then check each element, and if you don't find the element until you find the one you stuck at the end, you know that the value you're looking for isn't really there. Here's the code:

442

443

444

445 Remember to allow space for

446 the sentinel value at the end

447 of the array.

448

449

450

451

452

453

454

455

456

457

458

C# Example of Using a Sentinel Value to Speed Up a Loop

```
// set sentinel value, preserving the original value
initialValue = item[ count ];
item[ count ] = testValue;

i = 0;
while ( item[ i ] != testValue ) {
    i++;
}

// restore the value displaced by the sentinel
item[ count ] = initialValue;

// check if value was found
if ( i < count ) {
    ...
}
```

When *item* is an array of integers, the savings can be dramatic:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C#	0.771	0.590	23%	1.3:1
Java	1.63	0.912	44%	2:1
Visual Basic	1.34	0.470	65%	3:1

Note: Search is of a 100-element array of integers.

The Visual Basic results are particularly dramatic, but all the results are good. When the kind of array changes, however, the results also change. Here are the results when *item* is an array of single-precision floating-point numbers:

Language	Straight Time	Code-Tuned Time	Time Savings
C#	1.351	1.021	24%
Java	1.923	1.282	33%
Visual Basic	1.752	1.011	42%

Note: Search is of a 100-element array of 4-byte floating-point numbers.

As usual, the results vary significantly.

The sentinel technique can be applied to virtually any situation in which you use a linear search—to linked lists as well as arrays. The only caveats are that you must choose the sentinel value carefully and that you must be careful about how you put the sentinel value into the array or linked list.

Putting the Busiest Loop on the Inside

When you have nested loops, think about which loop you want on the outside and which you want on the inside. Following is an example of a nested loop that can be improved.

Java Example of a Nested Loop That Can Be Improved

```
for ( column = 0; column < 100; column++ ) {  
    for ( row = 0; row < 5; row++ ) {  
        sum = sum + table[ row ][ column ];  
    }  
}
```

The key to improving the loop is that the outer loop executes much more often than the inner loop. Each time the loop executes, it has to initialize the loop index, increment it on each pass through the loop, and check it after each pass. The total number of loop executions is 100 for the outer loop and $100 * 5 = 500$ for the inner loop, for a total of 600 iterations. By merely switching the inner and outer loops, you can change the total number of iterations to 5 for the outer loop and $5 * 100 = 500$ for the inner loop, for a total of 505 iterations. Analytically, you'd expect to save about $(600 - 505) / 600 = 16$ percent by switching the loops. Here's the measured difference in performance:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	4.75	3.19	33%
Java	5.39	3.56	34%
PHP	4.16	3.65	12%
Python	3.48	3.33	4%

The results vary significantly, which shows once again that you have to measure the effect in your particular environment before you can be sure your optimization will help.

Strength Reduction

Reducing strength means replacing an expensive operation such as multiplication with a cheaper operation such as addition. Sometimes you'll have an expression inside a loop that depends on multiplying the loop index by a factor. Addition is usually faster than multiplication, and if you can compute the same number by adding the amount on each iteration of the loop rather than by multiplying, the code will run faster. Here's an example of code that uses multiplication:

499
500
501
502
503
504
505

506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522

523
524
525
526

527
528

529

530
531

Visual Basic Example of Multiplying a Loop Index

```
For i = 0 to saleCount - 1
    commission( i ) = (i + 1) * revenue * baseCommission * discount
Next
```

This code is straightforward but expensive. You can rewrite the loop so that you accumulate multiples rather than computing them each time. This reduces the strength of the operations from multiplication to addition. Here’s the code:

Visual Basic Example of Adding Rather Than Multiplying

```
incrementalCommission = revenue * baseCommission * discount
cumulativeCommission = incrementalCommission
For i = 0 to saleCount - 1
    commission( i ) = cumulativeCommission
    cumulativeCommission = cumulativeCommission + incrementalCommission
Next
```

Multiplication is expensive, and this kind of change is like a manufacturer’s coupon that gives you a discount on the cost of the loop. The original code incremented *i* each time and multiplied it by *revenue * baseCommission * discount*—first by 1, then by 2, then by 3, and so on. The optimized code sets *incrementalCommission* equal to *revenue * baseCommission * discount*. It then adds *incrementalCommission* to *cumulativeCommission* on each pass through the loop. On the first pass, it’s been added once; on the second pass, it’s been added twice; on the third pass, it’s been added three times; and so on. The effect is the same as multiplying *incrementalCommission* by 1, then by 2, then by 3, and so on, but it’s cheaper.

The key is that the original multiplication has to depend on the loop index. In this case, the loop index was the only part of the expression that varied, so the expression could be recoded more economically. Here’s how much the rewrite helped in some test cases:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	4.33	3.80	12%
Visual Basic	3.54	1.80	49%

Note: Benchmark performed with saleCount equals 20. All computed variables are floating point.

26.3 Data Transformations

Changes in data types can be a powerful aid in reducing program size and improving execution speed. Data-structure design is outside the scope of this

532 book, but modest changes in the implementation of a specific data type can also
533 benefit performance. Here are a few ways to tune your data types.

534

Use Integers Rather Than Floating-Point Numbers

535 **CROSS-REFERENCE** For Integer addition and multiplication tend to be faster than floating point.
536 details on using integers and Changing a loop index from a floating point to an integer, for example, can save
537 floating point, see Chapter time. Here’s an example:
12, “Fundamental Data
Types.”

Visual Basic Example of a Loop That Uses a Time-Consuming Floating-Point Loop Index

```
Dim i As Single
For i = 0 to 99
    x( i ) = 0
Next
```

Contrast this with a similar Visual Basic loop that explicitly uses the integer type:

Visual Basic Example of a Loop That Uses a Timesaving Integer Loop Index

```
Dim i As Integer
For i = 0 to 99
    x( i ) = 0
Next
```

How much difference does it make? Here are the results for this Visual Basic code and for similar code in C++ and PHP:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	2.80	0.801	71%	3.5:1
PHP	5.01	4.65	7%	1:1
Visual Basic	6.84	0.280	96%	25:1

554

Use the Fewest Array Dimensions Possible

555 **CROSS-REFERENCE** For Conventional wisdom maintains that multiple dimensions on arrays are
556 details on arrays, see Section expensive. If you can structure your data so that it’s in a one-dimensional array
557 12.8, “Arrays.” rather than a two-dimensional or three-dimensional array, you might be able to
558 save some time.

Suppose you have initialization code like this:

559

560
561
562
563
564
565
566
567
568

Java Example of a Standard, Two-Dimensional Array Initialization

```
for ( row = 0; row < numRows; row++ ) {  
    for ( column = 0; column < numColumns; column++ ) {  
        matrix[ row ][ column ] = 0;  
    }  
}
```

When this code is run with 50 rows and 20 columns, it takes twice as long with my current Java compiler as when the array is restructured so that it's one-dimensional. Here's how the revised code would look:

569
570
571
572
573
574

Java Example of a One-Dimensional Representation of an Array

```
for ( entry = 0; entry < numRows * numColumns; entry++ ) {  
    matrix[ entry ] = 0;  
}
```

Here's a summary of the results, with the addition of comparable results in several other languages:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	8.75	7.82	11%	1:1
C#	3.28	2.99	9%	1:1
Java	7.78	4.14	47%	2:1
PHP	6.24	4.10	34%	1.5:1
Python	3.31	2.23	32%	1.5:1
Visual Basic	9.43	3.22	66%	3:1

Note: Times for Python and PHP aren't directly comparable to times for the other languages because they were run <1% as many iterations as the other languages.

The results of this optimization are excellent in Visual Basic and Java, good in PHP and Python, but mediocre in C++ and C#. Of course the C++ compiler's unoptimized time was easily the best of the group, so you can't be too hard on it.

This wide range of results also show the hazard of following any code-tuning advice blindly. You can never be sure until you try the advice in your specific circumstances.

Minimize Array References

In addition to minimizing accesses to doubly or triply dimensioned arrays, it's often advantageous to minimize array accesses, period. A loop that repeatedly uses one element of an array is a good candidate for the application of this technique. Here's an example of an unnecessary array access:

583
584
585
586
587

588
589
590
591
592
593
594
595
596
597
598

599
600
601
602
603
604
605
606

607
608

609

610
611
612
613

614
615
616
617
618
619

C++ Example of Unnecessarily Referencing an Array Inside a Loop

```
for ( discountType = 0; discountType < typeCount; discountType++ ) {  
    for ( discountLevel = 0; discountLevel < levelCount; discountLevel++ ) {  
        rate[ discountLevel ] = rate[ discountLevel ] * discount[ discountType ];  
    }  
}
```

The reference to *discount[discountType]* doesn't change when *discountLevel* changes in the inner loop. Consequently, you can move it out of the inner loop so that you'll have only one array access per execution of the outer loop rather than one for each execution of the inner loop. The next example shows the revised code.

C++ Example of Moving an Array Reference Outside a Loop

```
for ( discountType = 0; discountType < typeCount; discountType++ ) {  
    thisDiscount = discount[ discountType ];  
    for ( discountLevel = 0; discountLevel < levelCount; discountLevel++ ) {  
        rate[ discountLevel ] = rate[ discountLevel ] * thisDiscount;  
    }  
}
```

Here are the results:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	32.1	34.5	-7%
C#	18.3	17.0	7%
Visual Basic	23.2	18.4	20%

Note: Benchmark times were computed for the case in which typeCount equals 10 and levelCount equals 100.

As usual, the results vary significantly from compiler to compiler.

Use Supplementary Indexes

Using a supplementary index means adding related data that makes accessing a data type more efficient. You can add the related data to the main data type, or you can store it in a parallel structure.

String-Length Index

One example of using a supplementary index can be found in the different string-storage strategies. In C, strings are terminated by a byte that's set to 0. In Visual Basic string format, a length byte hidden at the beginning of each string indicates how long the string is. To determine the length of a string in C, a program has to start at the beginning of the string and count each byte until it

620 finds the byte that's set to 0. To determine the length of a Visual Basic string, the
621 program just looks at the length byte. Visual Basic length byte is an example of
622 augmenting a data type with an index to make certain operations—like
623 computing the length of a string—faster.

624 You can apply the idea of indexing for length to any variable-length data type.
625 It's often more efficient to keep track of the length of the structure rather than
626 computing the length each time you need it.

627 Independent, Parallel Index Structure

628 Sometimes it's more efficient to manipulate an index to a data type than it is to
629 manipulate the data type itself. If the items in the data type are big or hard to
630 move (on disk, perhaps), sorting and searching index references is faster than
631 working with the data directly. If each data item is large, you can create an
632 auxiliary structure that consists of key values and pointers to the detailed
633 information. If the difference in size between the data-structure item and the
634 auxiliary-structure item is great enough, sometimes you can store the key item in
635 memory even when the data item has to be stored externally. All searching and
636 sorting is done in memory, and you have to access the disk only once, when you
637 know the exact location of the item you want.

638 Use Caching

639 Caching means saving a few values in such a way that you can retrieve the most
640 commonly used values more easily than the less commonly used values. If a
641 program randomly reads records from a disk, for example, a routine might use a
642 cache to save the records read most frequently. When the routine receives a
643 request for a record, it checks the cache to see whether it has the record. If it
644 does, the record is returned directly from memory rather than from disk.

645 In addition to caching records on disk, you can apply caching in other areas. In a
646 Microsoft Windows font-proofing program, the performance bottleneck was in
647 retrieving the width of each character as it was displayed. Caching the most
648 recently used character width roughly doubled the display speed.

649 You can cache the results of time-consuming computations too—especially if the
650 parameters to the calculation are simple. Suppose, for example, that you need to
651 compute the length of the hypotenuse of a right triangle, given the lengths of the
652 other two sides. The straightforward implementation of the routine would look
653 like this:

654 Java Example of a Routine That's Conducive to Caching

```
655 double Hypotenuse(  
656     double sideA,
```

657

658

659

660

```
double sideB
) {
    return Math.sqrt( ( sideA * sideA ) + ( sideB * sideB ) );
}
```

661

662

If you know that the same values tend to be requested repeatedly, you can cache values this way:

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

1018

1019

1020

1021

1022

1023

1024

1025

1026

1027

1028

1029

1030

1031

1032

1033

1034

1035

1036

1037

1038

1039

1040

1041

1042

1043

1044

1045

1046

1047

1048

1049

1050

1051

1052

1053

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

1070

1071

1072

1073

1074

1075

1076

1077

1078

1079

1080

1081

1082

1083

1084

1085

1086

1087

1088

1089

1090

1091

1092

1093

1094

1095

1096

1097

1098

1099

1100

1101

1102

1103

1104

1105

1106

1107

1108

1109

1110

1111

1112

1113

1114

1115

1116

1117

1118

1119

1120

1121

1122

1123

1124

1125

1126

1127

1128

1129

1130

1131

1132

1133

1134

1135

1136

1137

1138

1139

1140

1141

1142

1143

1144

1145

1146

1147

1148

1149

1150

1151

1152

1153

1154

1155

1156

1157

1158

1159

1160

1161

1162

1163

1164

1165

1166

1167

1168

1169

1170

1171

1172

1173

1174

1175

1176

1177

1178

1179

1180

1181

1182

1183

1184

1185

1186

1187

1188

1189

1190

1191

1192

1193

1194

1195

1196

1197

1198

1199

1200

1201

1202

1203

1204

1205

1206

1207

1208

1209

1210

1211

1212

1213

1214

1215

1216

1217

1218

1219

1220

1221

1222

1223

1224

1225

1226

1227

1228

1229

1230

1231

1232

1233

1234

1235

1236

1237

1238

1239

1240

1241

1242

1243

1244

1245

1246

1247

1248

1249

1250

1251

1252

1253

1254

1255

1256

1257

1258

1259

1260

1261

1262

1263

1264

1265

1266

1267

1268

1269

1270

1271

1272

1273

1274

1275

1276

1277

1278

1279

1280

1281

1282

1283

1284

1285

1286

1287

1288

1289

1290

1291

1292

1293

1294

1295

1296

1297

1298

1299

1300

1301

1302

1303

1304

1305

1306

1307

1308

1309

1310

1311

1312

1313

1314

1315

1316

1317

1318

1319

1320

1321

1322

1323

1324

1325

1326

1327

1328

1329

1330

1331

1332

1333

1334

1335

1336

1337

1338

1339

1340

1341

1342

1343

1344

1345

1346

1347

1348

1349

1350

1351

1352

1353

1354

1355

1356

1357

1358

1359

1360

1361

1362

1363

1364

1365

1366

1367

1368

1369

1370

1371

1372

1373

1374

1375

1376

1377

1378

1379

1380

1381

1382

1383

1384

1385

1386

1387

1388

1389

1390

1391

1392

1393

1394

1395

1396

1397

1398

1399

1400

1401

1402

1403

1404

1405

1406

1407

1408

1409

1410

1411

1412

1413

1414

1415

1416

1417

1418

1419

1420

1421

1422

1423

1424

1425

1426

1427

1428

1429

1430

1431

1432

1433

1434

1435

1436

1437

1438

1439

1440

1441

1442

1443

1444

1445

1446

1447

1448

1449

1450

1451

1452

1453

1454

1455

1456

1457

1458

1459

1460

1461

1462

1463

1464

1465

1466

1467

1468

1469

1470

1471

1472

1473

1474

1475

1476

1477

1478

1479

1480

1481

1482

1483

1484

1485

1486

1487

1488

1489

1490

1491

1492

1493

1494

1495

1496

1497

1498

1499

1500

1501

1502

1503

1504

1505

1506

1507

1508

1509

1510

1511

1512

1513

1514

1515

1516

1517

1518

1519

1520

1521

1522

1523

1524

1525

1526

1527

1528

1529

1530

1531

1532

1533

1534

1535

1536

1537

1538

1539

1540

1541

1542

1543

1544

1545

1546

1547

1548

1549

1550

1551

1552

1553

1554

1555

1556

1557

1558

1559

1560

1561

1562

1563

1564

1565

1566

1567

1568

1569

1570

1571

1572

1573

1574

1575

1576

1577

1578

1579

1580

1581

1582

1583

1584

1585

1586

1587

1588

1589

1590

1591

1592

1593

1594

1595

1596

1597

1598

1599

1600

1601

1602

1603

1604

1605

1606

1607

1608

1609

1610

1611

1612

1613

1614

1615

1616

1617

1618

1619

1620

1621

1622

1623

1624

1625

1626

1627

1628

1629

1630

1631

1632

1633

1634

1635

1636

1637

1638

1639

1640

1641

1642

1643

1644

1645

1646

1647

1648

1649

1650

1651

1652

1653

1654

1655

1656

1657

1658

1659

1660

1661

1662

1663

1664

1665

1666

1667

1668

1669

1670

1671

1672

1673

1674

1675

1676

1677

1678

1679

1680

1681

1682

1683

1684

1685

1686

1687

1688

1689

1690

1691

1692

1693

1694

1695

1696

1697

1698

1699

1700

1701

1702

1703

1704

1705

1706

1707

1708

1709

1710

1711

1712

1713

1714

1715

1716

1717

1718

1719

1720

1721

1722

1723

1724

1725

1726

1727

1728

1729

1730

1731

1732

1733

1734

1735

1736

1737

1738

1739

1740

1741

1742

1743

1744

1745

1746

1747

1748

1749

1750

1751

1752

1753

1754

1755

1756

1757

1758

1759

1760

1761

1762

1763

1764

1765

1766

1767

1768

1769

1770

1771

1772

1773

1774

1775

1776

1777

1778

1779

1780

1781

1782

1783

1784

1785

1786

1787

1788

1789

1790

1791

1792

1793

1794

1795

1796

1797

1798

1799

1800

1801

1802

1803

1804

1805

1806

1807

1808

1809

1810

1811

1812

1813

1814

1815

1816

1817

1818

1819

1820

1821

1822

1823

1824

1825

1826

1827

1828

1829

1830

1831

1832

1833

1834

1835

1836

1837

1838

1839

1840

1841

1842

1843

1844

1845

1846

1847

1848

1849

1850

1851

1852

1853

1854

1855

1856

1857

1858

1859

1860

1861

1862

1863

1864

1865

1866

1867

1868

1869

1870

1871

1872

1873

1874

1875

1876

1877

1878

1879

1880

1881

1882

1883

1884

1885

1886

1887

1888

1889

1890

1891

1892

1893

1894

1895

1896

1897

1898

1899

1900

1901

1902

1903

1904

1905

1906

1907

1908

1909

1910

1911

1912

1913

1914

1915

1916

1917

1918

1919

1920

1921

1922

1923

1924

1925

1926

1927

1928

1929

1930

1931

1932

1933

1934

1935

1936

1937

1938

1939

1940

1941

1942

1943

1944

1945

1946

1947

1948

1949

1950

1951

1952

1953

1954

1955

1956

1957

1958

1959

1960

1961

1962

1963

1964

1965

1966

1967

1968

1969

1970

1971

1972

1973

1974

1975

1976

1977

1978

1979

1980

1981

1982

1983

1984

1985

1986

1987

1988

1989

1990

1991

1992

1993

1994

1995

1996

1997

1998

1999

2000

2001

2002

2003

2004

2005

2006

2007

2008

2009

2010

2011

2012

2013

2014

2015

2016

2017

2018

2019

2020

2021

2022

2023

2024

2025

2026

2027

2028

2029

2030

2031

2032

2033

2034

2035

2036

2037

2038

2039

2040

2041

2042

2043

2044

2045

2046

2047

2048

204

691 Success also depends on how often the cached information is requested. In some
692 cases, success might also depend on caching done by the hardware. Generally,
693 the more it costs to generate a new element and the more times the same
694 information is requested, the more valuable a cache is. The cheaper it is to access
695 a cached element and save new elements in the cache, the more valuable a cache
696 is. As with other optimization techniques, caching adds complexity and tends to
697 be error prone.

698

26.4 Expressions

699 **CROSS-REFERENCE** For Much of the work in a program is done inside mathematical or logical
700 more information on expressions. Complicated expressions tend to be expensive, so this section looks
701 expressions, see Section 19.1, at ways to make them cheaper.
“Boolean Expressions.”

702

Exploit Algebraic Identities

703 You can use algebraic identities to replace costly operations with cheaper ones.
704 For example, the following expressions are logically equivalent:

705 not a and not B
706 not (a or B)

707 If you choose the second expression instead of the first, you can save a *not*
708 operation.

709 Although the savings from avoiding a single *not* operation are probably
710 inconsequential, the general principle is powerful. Jon Bentley describes a
711 program that tested whether $\text{sqrt}(x) < \text{sqrt}(y)$ (1982). Since $\text{sqrt}(x)$ is less than
712 $\text{sqrt}(y)$ only when x is less than y , you can replace the first test with $x < y$. Given
713 the cost of the $\text{sqrt}()$ routine, you’d expect the savings to be dramatic, and they
714 are. Here are the results:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	7.43	0.010	99.9%	750:1
Visual Basic	4.59	0.220	95%	20:1
Python	4.21	0.401	90%	10:1

715

Use Strength Reduction

716 As mentioned earlier, strength reduction means replacing an expensive operation
717 with a cheaper one. Here are some possible substitutions:

- 718 • Replace multiplication with addition.
 - 719 • Replace exponentiation with multiplication.
 - 720 • Replace trigonometric routines with their trigonometric identities.
 - 721 • Replace *longlong* integers with *longs* or *ints* (but watch for performance
 - 722 issues associated with using native-length vs. non-native-length integers)
 - 723 • Replace floating-point numbers with fixed-point numbers or integers.
 - 724 • Replace double-precision floating points with single-precision numbers.
 - 725 • Replace integer multiplication-by-two and division-by-two with shift
 - 726 operations.
- 727 Here is a detailed example. Suppose you have to evaluate a polynomial. If you're
- 728 rusty on polynomials, they're the things that look like

729 $Ax^2 + Bx + C$

730 The letters *A*, *B*, and *C* are coefficients, and *x* is a variable. General code to

731 evaluate an *n*th-order polynomial looks like this:

732 **Visual Basic Example of Evaluating a Polynomial**

```
733 value = coefficient( 0 )
734 For power = 1 To order
735     value = value + coefficient( power ) * x^power
736 Next
```

737 If you're thinking about strength reduction, you'll look at the exponentiation

738 operator with a jaundiced eye. One solution would be to replace the

739 exponentiation with a multiplication on each pass through the loop, which is

740 analogous to the strength-reduction case a few sections ago in which a

741 multiplication was replaced with an addition. Here's how the reduced-strength

742 polynomial evaluation would look:

743 **Visual Basic Example of a Reduced-Strength Method of Evaluating a**

744 **Polynomial**

```
745 value = coefficient( 0 )
746 powerOfX = x
747 For power = 1 to order
748     value = value + coefficient( power ) * powerOfX
749     powerOfX = powerOfX * x
750 Next
```

751 This produces a noticeable advantage if you're working with second-order

752 polynomials (polynomials in which the highest-power term is squared) or higher-

753 order polynomials.

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
Python	3.24	2.60	20%	1:1
Visual Basic	6.26	0.160	97%	40:1

If you’re serious about strength reduction, you still won’t care for those two floating-point multiplications. The strength-reduction principle suggests that you can further reduce the strength of the operations in the loop by accumulating powers rather than multiplying them each time. Here’s that code:

Visual Basic Example of Further Reducing the Strength Required to Evaluate a Polynomial

```
value = 0
For power = order to 1 Step -1
    value = ( value + coefficient( power ) ) * x
Next
value = value + coefficient( 0 )
```

This method eliminates the extra *powerOfX* variable and replaces the two multiplications in each pass through the loop with one.

Language	Straight Time	First Optimization	Second Optimization	Savings over First Optimization
Python	3.24	2.60	2.53	3%
Visual Basic	6.26	0.16	0.31	-94%

This is a good example of theory not holding up very well to practice. The code with reduced strength seems like it should be faster, but it isn’t. One possibility is that decrementing a loop by *–I* instead of incrementing it by *+I* in Visual Basic hurts performance, but you’d have to measure that hypothesis to be sure.

Initialize at Compile Time

If you’re using a named constant or a magic number in a routine call and it’s the only argument, that’s a clue that you could precompute the number, put it into a constant, and avoid the routine call. The same principle applies to multiplications, divisions, additions, and other operations.

I once needed to compute the base-two logarithm of an integer, truncated to the nearest integer. The system didn’t have a log-base-two routine, so I wrote my own. The quick and easy approach was to use the fact that

$$\log(x)_{\text{base}} = \log(x) / \log(\text{base})$$

Given this identity, I could write a routine like this one:

781 **CROSS-REFERENCE** For
782 details on binding variables
783 to their values, see Section
784 10.6, “Binding Time.”

785
786 This routine was really slow, and since the value of *log*(2) never changed, I
787 replaced *log*(2) with its computed value, 0.69314718. Then the code looked like
this:

788
789 **C++ Example of a Log-Base-Two Routine Based on a System Routine
and a Constant**

```
790 unsigned int Log2( unsigned int x ) {  
791     return (unsigned int) ( log( x ) / LOG2 );  
792 }  
793
```

791 LOG2 is a named constant
792 equal to 0.69314718.

793 Since *log*() tends to be an expensive routine, much more expensive than type
794 conversions or division, you’d expect that cutting the calls to the *log*() function
795 by half would cut the time required for the routine by about half. Here are the
796 measured results:

Language	Straight Time	Code-Tuned Time	Time Savings
C++	9.66	5.97	38%
Java	17.0	12.3	28%
PHP	2.45	1.50	39%

797 In this case, the educated guess about the relative importance of the division and
798 type conversions and the estimate of 50 percent were pretty close. Considering
799 the predictability of the results described in this chapter, the accuracy of my
800 prediction in this case proves only that even a blind squirrel finds a nut
801 occasionally.

802 **Be Wary of System Routines**

803 System routines are expensive and provide accuracy that’s often wasted. Typical
804 system math routines, for example, are designed to put an astronaut on the moon
805 within ± 2 feet of the target. If you don’t need that degree of accuracy, you don’t
806 need to spend the time to compute it either.

807 In the previous example, the *Log2*() routine returned an integer value but used a
808 floating-point *log*() routine to compute it. That was overkill for an integer result,
809 so after my first attempt, I wrote a series of integer tests that were perfectly
810 accurate for calculating an integer *log*₂. Here’s the code:

811 **C++ Example of a Log-Base-Two Routine Based on Integers**

```
812 unsigned int Log2( unsigned int x ) {
```

```
813     if ( x < 2 ) return 0 ;
814     if ( x < 4 ) return 1 ;
815     if ( x < 8 ) return 2 ;
816     if ( x < 16 ) return 3 ;
817     if ( x < 32 ) return 4 ;
818     if ( x < 64 ) return 5 ;
819     if ( x < 128 ) return 6 ;
820     if ( x < 256 ) return 7 ;
821     if ( x < 512 ) return 8 ;
822     if ( x < 1024 ) return 9 ;
823     ...
824     if ( x < 2147483648 ) return 30;
825     return 31 ;
826 }
```

This routine uses integer operations, never converts to floating point, and blows the doors off both floating-point versions. Here are the results:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	9.66	0.662	93%	15:1
Java	17.0	0.882	95%	20:1
PHP	2.45	3.45	-41%	2:3

Most of the so-called “transcendental” functions are designed for the worst case—that is, they convert to double-precision floating point internally even if you give them an integer argument. If you find one in a tight section of code and don’t need that much accuracy, give it your immediate attention.

Another option is to take advantage of the fact that a right-shift operation is the same as dividing by two. The number of times you can divide a number by two and still have a nonzero value is the same as the log₂ of that number. Here’s how code based on that observation looks:

837 **CODING HORROR**

C++ Example of an Alternative Log-Base-Two Routine Based on the Right-Shift Operator

```
839 unsigned int Log2( unsigned int x ) {
840     unsigned int i = 0;
841     while ( ( x = ( x >> 1 ) ) != 0 ) {
842         i++;
843     }
844     return i ;
845 }
```

846

847

848

To non-C++ programmers, this code is particularly hard to read. The complicated expression in the *while* condition is an example of a coding practice you should avoid unless you have a good reason to use it.

849

850

851

This routine takes about 350 percent longer than the longer version above, executing in 2.4 seconds rather than 0.66 seconds. But it's faster than the first approach, and adapts easily to 32-bit, 64-bit, and other environments.

852

853

854

855

KEY POINT This example highlights the value of not stopping after one successful optimization. The first optimization earned a respectable 30-40 percent savings but had nowhere near the impact of the second optimization or third optimizations.

856

857

858

859

860

861

Use the Correct Type of Constants

857

858

859

860

861

Use named constants and literals that are the same type as the variables they're assigned to. When a constant and its related variable are different types, the compiler has to do a type conversion to assign the constant to the variable. A good compiler does the type conversion at compile time so that it doesn't affect -run-time performance.

862

863

864

865

A less advanced compiler or an interpreter generates code for a runtime conversion, so you might be stuck. Here are some differences in performance between the initializations of a floating-point variable *x* and an integer variable *i* in two cases. In the first case, the initializations look like this:

866

867

```
x = 5
i = 3.14
```

868

869

and require type conversions, assuming *x* is a floating point variable and *i* is an integer In the second case, they look like this:

870

871

```
x = 3.14
i = 5
```

872

and don't require type conversions. Here are the results:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
C++	1.11	0.000	100%	not measurable
C#	1.49	1.48	<1%	1:1
Java	1.66	1.11	33%	1.5:1
Visual Basic	0.721	0.000	100%	not measurable
PHP	0.872	0.847	3%	1:1

873

The variation among compilers is once again notable.

Precompute Results

A common low-level design decision is the choice of whether to compute results on the fly or compute them once, save them, and look them up as needed. If the results are used many times, it's often cheaper to compute them once and look them up the rest of the time.

This choice manifests itself in several ways. At the simplest level, you might compute part of an expression outside a loop rather than inside. An example of this appeared earlier in the chapter. At a more complicated level, you might compute a lookup table once when program execution begins, using it every time thereafter, or you might store results in a data file or embed them in a program.

In a space-wars video game, for example, the programmers initially computed gravity coefficients for different distances from the sun. The computation for the gravity coefficients was expensive and affected performance. The program recognized relatively few distinct distances from the sun, however, so the programmers were able to precompute the gravity coefficients and store them in a 10-element array. The array lookup was much faster than the expensive computation.

Suppose you have a routine that computes payment amounts on automobile loans. The code for such a routine would look like this:

Java Example of a Complex Computation That Could Be Precomputed

```
double ComputePayment(  
    long loanAmount,  
    int months,  
    double interestRate  
) {  
    return loanAmount /  
        (  
            1.0 - Math.pow( 1.0 + ( interestRate / 12.0 ), -months ) ) /  
            ( interestRate / 12.0 )  
        );  
}
```

The formula for computing loan payments is complicated and fairly expensive. Putting the information into a table instead of computing it each time would probably be cheaper.

How big would the table be? The widest-ranging variable is *loanAmount*. The variable *interestRate* might range from 5 percent through 20 percent by quarter points, but that's only 61 distinct rates. *months* might range from 12 through 72, but that's only 61 distinct periods. *loanAmount* could conceivably range from

912 \$1000 through \$100,000, which is more entries than you'd generally want to
913 handle in a lookup table.

914 Most of the computation doesn't depend on *loanAmount*, however, so you can
915 put the really ugly part of the computation (the denominator of the larger
916 expression) into a table that's indexed by *interestRate* and *months*. You
917 recompute the *loanAmount* part each time. Here's the revised code:

918 **Java Example of Precomputing a Complex Computation**

```
919 double ComputePayment(  
920     long loanAmount,  
921     int months,  
922     double interestRate  
923 ) {  
924     int interestIndex =  
925         Math.round( ( interestRate - LOWEST_RATE ) * GRANULARITY * 100.00 );  
926     return loanAmount / loanDivisor[ interestIndex ][ months ];  
927 }
```

924 *The new variable*
925 *interestIndex is created to*
926 *provide a subscript into the*
927 *loanDivisor array.*

928 In this code, the hairy calculation has been replaced with the computation of an
929 array index and a single array access. Here are the results of the change:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
Java	2.97	0.251	92%	10:1
Python	3.86	4.63	-20%	1:1

930 Depending on your circumstances, you would need to precompute the
931 *loanDivisor* array at program initialization time or read it from a disk file.
932 Alternatively, you could initialize it to 0, compute each element the first time it's
933 requested, store it, and look it up each time it's requested subsequently. That
934 would be a form of caching, discussed earlier.

935 You don't have to create a table to take advantage of the performance gains you
936 can achieve by precomputing an expression. Code similar to the code in the
937 previous examples raises the possibility of a different kind of precomputation.
938 Suppose you have code that computes payments for many loan amounts, as
939 shown here.

940 **Java Example of a Second Complex Computation That Could Be**
941 **Precomputed**

```
942 double ComputePayments(  
943     int months,  
944     double interestRate  
945 ) {
```

946
947
948
949
950
951
952 *The following code would do*
953 *something with payment here;*
954 *for this example's point, it*
955 *doesn't matter what.*
956
957

```
for ( long loanAmount = MIN_LOAN_AMOUNT; loanAmount < MAX_LOAN_AMOUNT;
    loanAmount++ ) {
    payment = loanAmount / (
        ( 1.0 - Math.pow( 1.0+(interestRate/12.0), - months ) ) /
        ( interestRate/12.0 )
    );
    ...
}
```

Even without precomputing a table, you can precompute the complicated part of the expression outside the loop and use it inside the loop. Here's how it would look:

Java Example of Precomputing the Second Complex Computation

958
959
960
961
962
963
964 *Here's the part that's*
965 *precomputed.*
966
967
968
969
970
971
972
973
974
975

```
double ComputePayments(
    int months,
    double interestRate
) {
    long loanAmount;
    double divisor = ( 1.0 - Math.pow( 1.0+(interestRate/12.0). - months ) ) /
        ( interestRate/12.0 );
    for ( long loanAmount = MIN_LOAN_AMOUNT; loanAmount <= MAX_LOAN_AMOUNT;
        loanAmount++ ) {
        payment = loanAmount / divisor;
        ...
    }
}
```

This is similar to the techniques suggested earlier of putting array references and pointer dereferences outside a loop. The results for Java in this case are comparable to the results of using the precomputed table in the first optimization:

Language	Straight Time	Code-Tuned Time	Time Savings	Performance Ratio
Java	7.43	0.24	97%	30:1
Python	5.00	1.69	66%	3:1

Python improved here, but not in the first optimization attempt. Many times when one optimization does not produce the desired results, a seemingly similar optimization will work as expected.

Optimizing a program by precomputation can take several forms:

- Computing results before the program executes and wiring them into constants that are assigned at compile time

- 982
- 983
- 984
- 985
- 986
- 987
- 988
- 989
- 990
- 991
- Computing results before the program executes and hard-coding them into variables used at run time
 - Computing results before the program executes and putting them into a file that's loaded at run time
 - Computing results once, at program startup, and then referencing them each time they're needed
 - Computing as much as possible before a loop begins, minimizing the work done inside the loop
 - Computing results the first time they're needed and storing them so that you can retrieve them when they're needed again

992

Eliminate Common Subexpressions

993

994

995

996

If you find an expression that's repeated several times, assign it to a variable and refer to the variable rather than recomputing the expression in several places. The loan-calculation example has a common subexpression that you could eliminate. Here's the original code:

997

Java Example of a Common Subexpression

998

999

1000

1001

```
payment = loanAmount / (  
    ( 1.0 - Math.pow( 1.0 + ( interestRate / 12.0 ), -months ) ) /  
    ( interestRate / 12.0 )  
);
```

1002

1003

1004

1005

1006

In this sample, you can assign *interestRate/12.0* to a variable that is then referenced twice rather than computing the expression twice. If you have chosen the variable name well, this optimization can improve the code's readability at the same time that it improves performance. The next example shows the revised code.

1007

Java Example of Eliminating a Common Subexpression

1008

1009

1010

1011

1012

```
monthlyInterest = interestRate / 12.0;  
payment = loanAmount / (  
    ( 1.0 - Math.pow( 1.0 + monthlyInterest, -months ) ) /  
    monthlyInterest  
);
```

1013

The savings in this case don't seem impressive:

Language	Straight Time	Code-Tuned Time	Time Savings
Java	2.94	2.83	4%
Python	3.91	3.94	-1%

It appears that the *Math.pow()* routine is so costly that it overshadows the savings from subexpression elimination. Or possibly the subexpression is already being eliminated by the compiler. If the subexpression were a bigger part of the cost of the whole expression or if the compiler optimizer were less effective, the optimization might have more impact.

26.5 Routines

One of the most powerful tools in code tuning is a good routine decomposition. Small, well-defined routines save space because they take the place of doing jobs separately in multiple places. They make a program easy to optimize because you can refactor code in one routine and thus improve every routine that calls it. Small routines are relatively easy to rewrite in assembler. Long, tortuous routines are hard enough to understand on their own; in assembler they're impossible.

Rewrite Routines In Line

In the early days of computer programming, some machines imposed prohibitive performance penalties for calling a routine. A call to a routine meant that the operating system had to swap out the program, swap in a directory of routines, swap in the particular routine, execute the routine, swap out the routine, and swap the calling routine back in. All this swapping chewed up resources and made the program slow.

Modern computers collect a far smaller toll for calling a routine. Here are the results of putting a string-copy routine in line:

Language	Routine Time	Inline-Code Time	Time Savings
C++	0.471	0.431	8%
Java	13.1	14.4	-10%

In some cases, you might be able to save a few nanoseconds by putting the code from a routine into the program directly where it's needed using a language feature like C++'s *inline* keyword. If you're working in a language that doesn't support *inline* directly but that does have a macro preprocessor, you can use a macro to put the code in, switching it in and out as needed. But modern machines—and "modern" means any machine you're ever likely to work on—impose virtually no penalty for calling a routine. As the example shows, you're as likely to degrade performance by keeping code inline as to optimize it.

26.6 Recoding in Assembler

One longstanding piece of conventional wisdom that shouldn't be left unmentioned is the advice that when you run into a performance bottleneck, you should recode in assembler. Recoding in assembler tends to improve both speed and code size. Here is a typical approach to optimizing with assembler:

1. Write 100 percent of an application in a high-level language.
2. Fully test the application, and verify that it's correct.
3. If performance improvements are needed after that, profile the application to identify hot spots. Since about 5 percent of a program usually accounts for about 50 percent of the running time, you can usually identify small pieces of the program as hot spots.
4. Recode a few small pieces in assembler to improve overall performance.

Whether you follow this well-beaten path depends on how comfortable you are with assembler, how well-suited the problem is to assembler, and on your level of desperation.

I got my first exposure to assembler on the DES encryption program I mentioned in the previous chapter. I had tried every optimization I'd ever heard of, and the program was still twice as slow as the speed goal. Recoding part of the program in assembler was the only remaining option. As an assembler novice, about all I could do was make a straight translation from a high-level language to assembler, but I got a 50 percent improvement even at that rudimentary level.

Suppose you have a routine that converts binary data to uppercase ASCII characters. The next example shows the Delphi code to do it.

Delphi Example of Code That's Better Suited to Assembler

```
procedure HexExpand(  
    var source: ByteArray;  
    var target: WordArray;  
    byteCount: word  
);  
var  
    index: integer;  
    lowerByte: byte;  
    upperByte: byte;  
    targetIndex: integer;  
begin
```

```

1079     targetIndex := 1;
1080     for index := 1 to byteCount do begin
1081         target[ targetIndex ] := ( source[ index ] and $F0 ) shr 4 ) + $41;
1082         target[ targetIndex+1 ] := ( source[ index ] and $0f ) + $41;
1083         targetIndex := targetIndex + 2;
1084     end;
1085 end;

```

Although it's hard to see where the fat is in this code, it contains a lot of bit manipulation, which isn't exactly Delphi's forte. Bit manipulation is assembler's forte, however, so this code is a good candidate for recoding. Here's the assembler code:

Example of a Routine Recoded in Assembler

```

1090
1091 procedure HexExpand(
1092     var source;
1093     var target;
1094     byteCount : Integer
1095 );
1096     label
1097     EXPAND;
1098
1099     asm
1100         MOV     ECX,byteCount      // load number of bytes to expand
1101         MOV     ESI,source         // source offset
1102         MOV     EDI,target        // target offset
1103         XOR     EAX,EAX           // zero out array offset
1104
1105     EXPAND:
1106         MOV     EBX,EAX           // array offset
1107         MOV     DL,[ESI+EBX]      // get source byte
1108         MOV     DH,DL            // copy source byte
1109
1110         AND     DH,$F            // get msbs
1111         ADD     DH,$41           // add 65 to make upper case
1112
1113         SHR     DL,4             // move lsbs into position
1114         AND     DL,$F            // get lsbs
1115         ADD     DL,$41           // add 65 to make upper case
1116
1117         SHL     BX,1             // double offset for target array offset
1118         MOV     [EDI+EBX],DX      // put target word
1119
1120         INC     EAX              // increment array offset
1121         LOOP    EXPAND           // repeat until finished
1122     end;

```

Rewriting in assembler in this case was profitable, resulting in a time savings of 41 percent. It’s logical to assume that code in a language that’s more suited to bit manipulation—C++, for instance—would have less to gain than Delphi code would. Here are the results:

Language	High-Level Time	Assembler Time	Time Savings
C++	4.25	3.02	29%
Delphi	5.18	3.04	41%

The “before” picture in this measurements reflects the two languages’ strengths at bit manipulation. The “after” picture looks virtually identical, and it appears that the assembler code has minimized the initial performance differences between Delphi and C++.

The assembler routine shows that rewriting in assembler doesn’t have to produce a huge, ugly routine. Such routines are often quite modest, as this one is. Sometimes assembler code is almost as compact as its high-level-language equivalent.

A relatively easy and effective strategy for recoding in assembler is to start with a compiler that generates assembler listings as a by-product of compilation. Extract the assembler code for the routine you need to tune, and save it in a separate source file. Using the compiler’s assembler code as a base, hand-optimize the code, checking for correctness and measuring improvements at each step. Some compilers intersperse the high-level-language statements as comments in the assembler code. If yours does, you might keep them in the assembler code as documentation.

CC2E.COM/2672

CHECKLIST: Code-Tuning Techniques

Improve Both Speed and Size

- ☐ Substitute table lookups for complicated logic
- ☐ Jam loops
- ☐ Use integer instead of floating-point variables
- ☐ Initialize data at compile time
- ☐ Use constants of the correct type
- ☐ Precompute results
- ☐ Eliminate common subexpressions
- ☐ Translate key routines to assembler

Improve Speed Only

- ☐ Stop testing when you know the answer
 - ☐ Order tests in *case* statements and *if-then-else* chains by frequency
 - ☐ Compare performance of similar logic structures
 - ☐ Use lazy evaluation
 - ☐ Unswitch loops that contain *if* tests
 - ☐ Unroll loops
 - ☐ Minimize work performed inside loops
 - ☐ Use sentinels in search loops
 - ☐ Put the busiest loop on the inside of nested loops
 - ☐ Reduce the strength of operations performed inside loops
 - ☐ Change multiple-dimension arrays to a single dimension
 - ☐ Minimize array references
 - ☐ Augment data types with indexes
 - ☐ Cache frequently used values
 - ☐ Exploit algebraic identities
 - ☐ Reduce strength in logical and mathematical expressions
 - ☐ Be wary of system routines
 - ☐ Rewrite routines in line
-

26.7 The More Things Change, the More They Stay the Same

You might expect that performance attributes of systems would have changed somewhat in the 10 years since I wrote the first edition of *Code Complete*, and in some ways they have. Computers are dramatically faster and memory is more plentiful. In the first edition, I ran most of the tests in this chapter 10,000 to 50,000 times to get meaningful, measurable results. For this edition I had to run most tests 1 million to 100 million times. When you have to run a test 100 million times to get measurable results, you have to ask whether anyone will ever notice the impact in a real program. Computers have become so powerful that for many common kinds of programs the level of performance optimization discussed in this chapter has become irrelevant.

In other ways, performance issues have hardly changed at all. People writing desktop applications may not need this information, but people writing software

1187 for embedded systems, real-time systems, and other systems with strict speed or
1188 space restrictions can still benefit from this information.

1189 The need to measure the impact of each and every attempt at code tuning has
1190 been a constant since Donald Knuth published his study of Fortran programs in
1191 1971. According to the measurements in this chapter, the effect of any specific
1192 optimization is actually *less predictable* than it was 10 years ago. The effect of
1193 each code tuning is affected by the programming language, compiler, compiler
1194 version, code libraries, library versions, and compiler settings, among other
1195 things.

1196 Code tuning invariably involves tradeoffs among complexity, readability,
1197 simplicity, and maintainability on the one hand and a desire to improve
1198 performance on the other. It introduces a high degree of maintenance overhead
1199 because of all the reprofiling that's required.

1200 I have found that insisting on *measurable improvement* is a good way to resist
1201 the temptation to optimize prematurely and to enforce a bias toward clear,
1202 straightforward code. If an optimization is important enough to haul out the
1203 profiler and measure the optimization's effect, then it's probably important
1204 enough to allow—as long as it works. But if an optimization isn't important
1205 enough to haul out the profiling machinery, then it isn't important enough to
1206 degrade readability, maintainability, and other code characteristics. The impact
1207 of unmeasured code tuning on performance is speculative at best, whereas the
1208 impact on readability is as certain as it is detrimental.

CC2E.COM/2679

1209 Additional Resources

1210 My favorite reference on code tuning is *Writing Efficient Programs* (Bentley,
1211 Englewood Cliffs, N.J.: Prentice Hall, 1982). The book is out of print, but worth
1212 reading if you can find it. It's an expert treatment of code tuning, broadly
1213 considered. Bentley describes techniques that trade time for space and space for
1214 time. He provides several examples of redesigning data types to reduce both
1215 space and time. His approach is a little more anecdotal than the one taken here,
1216 and his anecdotes are interesting. He takes a few routines through several
1217 optimization steps so that you can see the effects of first, second, and third
1218 attempts on a single problem. Bentley strolls through the primary contents of the
1219 book in 135 pages. The book has an unusually high signal-to-noise ratio—it's
1220 one of the rare gems that every practicing programmer should own.

1221 Appendix 4 of Bentley's *Programming Pearls*, 2d Ed. (2000), contains a
1222 summary of the code tuning rules from his earlier book.

- 1223 You can also find a full array of technology-specific optimization books. Several
1224 are listed below, and the web link to the left contains an up-to-date list.
- 1225 CC2E.COM/2686 Booth, Rick. *Inner Loops : A Sourcebook for Fast 32-bit Software Development*,
1226 Boston, Mass.: Addison Wesley, 1997.
- 1227 Gerber, Richard. *Software Optimization Cookbook: High-Performance Recipes*
1228 *for the Intel Architecture*, Intel Press, 2002.
- 1229 Hasan, Jeffrey and Kenneth Tu. *Performance Tuning and Optimizing ASP.NET*
1230 *Applications*, Apress, 2003.
- 1231 Killelea, Patrick. *Web Performance Tuning, 2d Ed*, O'Reilly & Associates, 2002.
- 1232 Larman, Craig and Rhett Guthrie. *Java 2 Performance and Idiom Guide*,
1233 Englewood Cliffs, N.J.: Prentice Hall, 2000.
- 1234 Shirazi, Jack. *Java Performance Tuning*, O'Reilly & Associates, 2000.
- 1235 Wilson, Steve and Jeff Kesselman. *Java Platform Performance: Strategies and*
1236 *Tactics*, Boston, Mass.: Addison Wesley, 2000.

1237 Key Points

- 1238 • Results of optimizations vary widely with different languages, compilers,
1239 and environments. Without measuring each specific optimization, you'll
1240 have no idea whether it will help or hurt your program.
- 1241 • The first optimization is often not the best. Even after you find a good one,
1242 keep looking for one that's better.
- 1243 • Code tuning is a little like nuclear energy. It's a controversial, emotional
1244 topic. Some people think it's so detrimental to reliability and maintainability
1245 that they won't do it at all. Others think that with proper safeguards, it's
1246 beneficial. If you decide to use the techniques in this chapter, apply them
1247 with care.