No.
Date

BT5

```
public interface Moveable {
    void moveUp();
    ——— moveDown();
    ——— moveLeft();
    ——— moveRight();
}

public class MoveablePoint implements Moveable {
    private int x;
    ——— int y;
    ——— int xSpeed;
    ——— int ySpeed;
    public MoveablePoint(int x, int y, int xSpeed, int ySpeed) {
        this.x = x;
        ——— y = y;
        ——— xSpeed = xSpeed;
        ——— ySpeed = ySpeed;
    }
    @Override
    public void moveUp() {
        y += ySpeed;
    }
    @Override
        ~~y =~~
    public void moveDown() {
        y -= ySpeed;
    }
```

futurebook

Scanned with CamScanner

No.

Date

```
    @Override
    public void moveLeft ( ) {
        x -= xSpeed;
    }
    pub
    @Override
    public void moveRight ( ) {
        x += xSpeed;
    }
    @Override
    public String toString ( ) {
        return "Point (" + x + "," + y + ")";
    }
}
public class MoveableCircle implements Moveable {
    private int radius;
    MoveablePoint center;
    public MoveableCircle (MoveablePoint center, int radius) {
        this.center = center;
        this.radius = radius;
    }
    @Override
    public void moveUp ( ) {
        center.moveUp ( );
    }
    @Override
    public void moveDown ( ) {
```

No.
Date

```
        center.moveDown();
    }
    @Override
    public void moveLeft(){
        center.moveLeft();
    }
    @Override
    public void moveRight(){
        center.moveRight();
    }
    @Override
    public String toString(){
        return "Circle[center=" + center + ", radius=" + radius + "]".
    }
}
public class Main {
    public static void main(String[] args){
        MoveablePoint point = new MoveablePoint(0,0,2,5);
                       circle = new MoveableCircle(point,5);
        System.out.println("...");
        circle.moveUp();
        circle.moveRight();
        System.out.println("...");
    }
}
```

futurebook

Scanned with CamScanner