

README

Binoculars

`Binoculars` is a local workflow tool for AI text forensics and humanization. It uses two related `llama.cpp` models - observer and performer - to compute Binoculars-style scores from full logits, then guides you through iterative rewrites of high-risk text spans in the GUI.

If you need to evaluate or revise long-form text without sending documents to a remote detector, this repository provides a practical solution.

- Data and models remain local by default.
- The system computes inspectable signals (`logPPL`, `logXPPL`, `B`) rather than opaque labels.
- Paragraph-level heatmaps show exactly where score pressure originates.
- For any flagged line or selected block, you can generate three rewrite options and rank them by estimated B impact for quick humanization passes.
- Full analysis can be re-run only when you need exact checkpoint scores.
- Optionally, you may use an OpenAI-compatible rewrite backend, with automatic fallback to internal local generation if needed.

Reference paper (also in `background/`): <https://arxiv.org/abs/2401.12070>

Acknowledgment: The Binoculars paper authors - Abhimanyu Hans, Avi Schwarzschild, Valeriia Cherepanova, Hamid Kazemi, Aniruddha Saha, Micah Goldblum, Jonas Geiping, and Tom Goldstein - provided the foundational method for this project.



Screenshot of the GUI

What This Does

Given input text, `binoculars` computes:

- Observer log-perplexity: `logPPL`
- Cross log-perplexity: `logXPPL` (observer distribution scored against performer distribution)
- Binoculars ratio: `B = logPPL / logXPPL`

It can also generate paragraph-level diagnostics and heatmaps.

Why Local / Full Logits

The Binoculars-style cross-entropy term depends on full next-token distributions. In practice, this means:

- `logits_all=True` is required
- Top-k API logprobs are not sufficient for faithful reconstruction
- Observer and performer tokenizer alignment must be exact

The reference paper is included at:

- `background/2401.12070v3.pdf`

Additional local design notes:

- `initial-scoping.md` (local, gitignored)

Theory

Let a tokenized document be:

$$x_1, x_2, \dots, x_T$$

with observer model M_o and performer model M_p .

Observer log-perplexity:

$$\log \text{PPL}_{M_o}(x) = -\frac{1}{T-1} \sum_{t=1}^{T-1} \log p_{M_o}(x_{t+1} \mid x_{\leq t})$$

Cross log-perplexity:

$$\log \text{XPPL}_{M_o, M_p}(x) = -\frac{1}{T-1} \sum_{t=1}^{T-1} \sum_{v \in V} p_{M_o}(v \mid x_{\leq t}) \log p_{M_p}(v \mid x_{\leq t})$$

Binoculars score:

$$B(x) = \frac{\log \text{PPL}_{M_o}(x)}{\log \text{XPPL}_{M_o, M_p}(x)}$$

The current UI/CLI interpretation used by this repository:

- Higher `B` is treated as more human-like
- Lower paragraph `logPPL` is treated as more AI-like for heatmap colouring

Important: This is a scoring signal, not proof of authorship.

Repository Layout

- `binoculars.py`: main CLI and GUI application; `binoculars.sh`: wrapper that activates venv, cleans old instances, and forwards Ctrl-C
- `binocular.sh`: alias wrapper (`exec binoculars.sh`); `config.binoculars.json`: master profile selector (`default` and `profiles`)
- `config.binoculars.llm.json`: optional OpenAI-compatible rewrite backend config for GUI rewrite suggestions; `config.llama31.cuda12gb.fast.json`: fast profile (currently `text.max_tokens=4096`)
- `config.llama31.cuda12gb.long.json`: long profile (currently `text.max_tokens=12288`); `USERGUIDE-GUI.md`: detailed GUI user guide and iterative workflow guidance
- `background/2401.12070v3.pdf`: background paper; `samples/`: sample markdown inputs
- `tests/test_regression_v1_1_x.py`: regression suite; `tests/fixtures/`: fixture docs used by regression tests

Requirements

- Linux or macOS shell
- Python 3.10 or newer
- `numpy`
- `llama-cpp-python`
- Optional: `nltk` (for local WordNet synonym expansion in GUI)
- GGUF models on local disk

Install into the repository venv:

```
venv/bin/pip install numpy llama-cpp-python
```

Optional WordNet setup for richer synonym suggestions:

```
venv/bin/pip install nltk
venv/bin/python - <<'PY'
import nltk
nltk.download("wordnet", quiet=True)
nltk.download("omw-1.4", quiet=True)
PY
```

Model Files

Configs in this repository point to local model paths under `models/`, for example:

- Base observer: Llama 3.1 8B Q5_K_M
- Instruct performer: Llama 3.1 8B Instruct Q5_K_M

You may use different models if tokenizer and vocabulary alignment are preserved.

Configuration

1) Master Profile Config

`config.binoculars.json` selects profile by label:

```
{
  "default": "long",
  "profiles": {
    "fast": "/abs/path/config.llama31.cuda12gb.fast.json",
```

```

    "long": "/abs/path/config.llama31.cuda12gb.long.json"
  }
}

```

`profiles` entries can be either:

- String path (current repository default), or
- Object form:

```

{
  "path": "/abs/path/config.json",
  "max_tokens": 8192
}

```

`max_tokens` in object form (if present) overrides `text.max_tokens` in the concrete profile.

2) Concrete Observer/Performer Profile

Each profile must define:

- `observer`
- `performer`

Optional blocks:

- `text` (`add_bos`, `special_tokens`, `max_tokens`)
- `cache` (`dir`, `dtype`, `keep`)

Notes:

- `n_ctx: 0` means auto (`n_ctx = analyzed token count`)
- `text.max_tokens > 0` truncates input token window
- `cache.dtype` may be `float16` or `float32`

3) Optional Rewrite LLM Config (GUI)

If `config.binoculars.llm.json` is present and enabled, GUI rewrite suggestions can use an external OpenAI-compatible endpoint. If missing or disabled, internal performer-model generation is used. If present but unreachable or invalid at runtime, GUI rewrites automatically fall back to internal generation.

Supported fields include:

- `llm.enabled`; `llm.endpoint_url`
- `llm.request_path` (default `/chat/completions`); `llm.model`
- `llm.api_key` or `llm.api_key_env` (also supports `OPENAI_API_KEY` when enabled); `llm.api_key_header` / `llm.api_key_prefix`
- `llm.timeout_s`; `llm.max_tokens`
- `llm.temperature`; `llm.top_p`
- `llm.context_chars_each_side`; `llm.context_paragraphs_each_side`
- `llm.context_window_max_chars`; `llm.extra_headers`
- `llm.extra_body`

Example:

```

{
  "llm": {
    "enabled": true,
    "endpoint_url": "http://localhost:4141/v1",
    "model": "gpt-4.1",
    "request_path": "/chat/completions",
    "api_key_env": "OPENAI_API_KEY",
    "max_tokens": 220,
    "temperature": 0.78,
    "top_p": 0.95,
    "context_chars_each_side": 1800,
    "context_paragraphs_each_side": 2,
    "context_window_max_chars": 5200
  }
}

```

Execution Model

`binoculars.py` loads models sequentially:

1. Tokenize with observer and performer in `vocab_only=True`
2. Hard-fail if tokenization differs
3. Run observer with full logits
4. Persist observer logits to memmap
5. Unload observer, load performer
6. Compute cross-entropy term from observer distribution versus performer logits
7. Emit metrics and optional diagnostics or heatmap

This approach keeps VRAM usage lower than concurrent dual-model loading.

CLI Usage

Show help:

```
./binoculars.sh --help
```

Basic usage:

```
./binoculars.sh samples/Athens.md
```

JSON output:

```
./binoculars.sh --config long samples/Athens.md --json
```

Heatmap mode:

```
./binoculars.sh --config fast --input samples/Athens.md --heatmap --diagnose-top-k 10
```

Diagnostics:

```
./binoculars.sh --diagnose-paragraphs --diagnose-top-k 10 samples/Athens.md
./binoculars.sh --diagnose-paragraphs --diagnose-print-text samples/Athens.md
```

Run from any directory:

```
cd ~
/home/npepin/Projects/binoculars/binoculars.sh --config long /tmp/doc.md --json
```

Alias wrapper:

```
/home/npepin/Projects/binoculars/binocular.sh --config fast /tmp/doc.md
```

Input Rules

- Provide input as either:
 - Positional `INPUT`, or
 - `--input INPUT`
- If both are provided, the command errors
- If multiple positional paths are given, only the first is used (a warning is emitted)
- If no input is given, stdin (`-`) is used

CLI Options

- `--master-config FILE`: master profile mapping file; `--config PROFILE`: profile label (`fast`, `long`, etc.)
- `--input FILE|-`: explicit input; `--output FILE`: write text output
- `--json`: emit JSON result object; `--diagnose-paragraphs`: rank low-perplexity hotspot paragraphs
- `--diagnose-top-k N`: hotspot count (also used by heatmap selection); `--diagnose-print-text`: print full hotspot text segments

- `--heatmap`: emit console and markdown heatmap output; `--gui FILE`: launch interactive GUI editor/analyzer

`--heatmap` cannot be combined with `--json`.

`--gui` is mutually exclusive with:

- `--input`
- Positional `INPUT`
- `--output`
- `--json`
- `--heatmap`

Heatmap Mode (`--Heatmap`)

When enabled:

- Console output shows:
 - Red and green highlights (ANSI)
 - Simple note markers like `[1]`
 - Line-drawing notes table
 - Wrapped layout (about 85% terminal width)
- File output writes markdown to:
 - `[[HTML_BLOCK_6]]_heatmap.md` in the same directory as the source input
 - Existing heatmap file is backed up first:
 - `[[HTML_BLOCK_7]].YYYYMMDD_HHMMSS.bak` (timestamp format may vary by implementation helper)

Heatmap semantics:

- Red sections: lowest paragraph `logPPL`
- Green sections: highest paragraph `logPPL`
- Note table columns:
 - `Index`; `Label`
 - `% contribution`; `Paragraph`
 - `logPPL`; `delta_vs_doc`
 - `delta_if_removed`; `Transitions`
 - `Chars`; `Tokens`

GUI Mode (`--Gui [[HTML_BLOCK_8]]`)

Launches an editor/analyzer with:

- Window/app name: `Binoculars`
- Left pane: editable source text
- Left gutter:
 - Logical line numbers
 - Red and green contribution bars per line
- Right pane: live markdown preview
- Right-pane footer: real-time synonym panel for clicked words
- Controls:
 - `Analyze`
 - `Save`
 - `Undo` (one level)
 - `Clear Priors`
 - `Quit`
- Status bar:
 - `Binocular score B (high is more human-like): ...`
 - Includes prior score and `Last Line`

For a detailed workflow-oriented guide, see:

- `USERGUIDE-GUI.md`

GUI Behaviour

- **Analyze** :
 - Scores the full current document
 - Preserves cursor and top-view position
 - Updates red and green foreground highlights
 - Updates hover tooltips (`% contribution`, `logPPL`, `delta_if_removed`, `delta_vs_doc`, ranges)
 - Updates status metrics
 - Keeps `Performing analysis on current text...` visible until analysis finishes
 - Edits since last analysis show in yellow
- On advancing to the next **Analyze**, previous highlights or edits are reduced to faint backgrounds, indicating prior states.
- Executing **Clear Priors** clears only these faint backgrounds, leaving other markings intact.
- The **Save** command initiates a write operation:
- `[[HTML_BLOCK_9]]_edited_YYYYMMDDHHMM.md`
- Output is directed to the same directory as the source file.
- During the write process, a modal **Saving...** popup displays the destination filename.

Always-on English spell checking is active:

- Misspelled words are underlined in red.

Synonym suggestions are available:

- Left-click any word in the left pane to request synonyms.
- Lookup actions are debounced to prevent triggering during drag-selection.
- The synonym panel displays up to nine options in three columns, each with a `1..9` button.
- Selecting a synonym replaces the chosen word and marks the change as an edit (yellow).
- The lookup sequence is: local fallback list, then WordNet (if installed), then Datamuse API as a fallback.

Rewrite suggestions can be accessed as follows:

- Right-click a red (**LOW**) paragraph segment to open three rewrite options.; Alternatively, highlight a block (multi-line selection allowed) and right-click to request block rewrites.
- Highlighted-block rewrites round the selection to full lines.; If the selection includes unscored text, only the scored portion is rewritten.
- The popup displays the approximate B impact for each option (exact B requires **Analyze**); Options are sorted by expected B increase, with more human-like choices first.
- Select an option using the mouse or keyboard (`1/2/3`), or **Quit**; The selected rewrite is inserted as an edit (yellow), and prior backgrounds are preserved according to previous line status.
- The B score is not automatically recalculated; the status marks it as stale until the next **Analyze**.

Delete and undo operations are tracked:

- Deleting a selected block with **Delete** or **Backspace** is recorded as a single undoable action.
- **Undo** supports one level of undo for selected-block delete, synonym replacement, red-segment rewrite, and block rewrite.
- Successful undo status is shown briefly, after which metrics return.

Preview selection mirroring is supported:

- Selecting a block in the left pane causes the right preview to mirror the same line range.
- Selected preview lines display LOW, HIGH, or neutral background styles.

Status-bar transient messages:

- Non-analysis events (such as Save, Clear Priors, Delete, or Undo) temporarily replace metrics.
- Most transient messages restore metrics after approximately eight seconds.
- A successful **Undo applied...** restores metrics quickly, in about 1.8 seconds.

Preview Sync and Debug Controls

Environment variables:

- `BINOCULARS_GUI_DEBUG=1`: Starts with the debug overlay enabled; can be toggled in-app with **F9**.
- `BINOCULARS_PREVIEW_VIEW_OFFSET_LINES=-3`: Adjusts vertical view calibration for the right pane, affecting only the preview viewport position (not line mapping).

Wrapper Behaviour (**Binoculars.Sh**)

`binoculars.sh` performs the following:

- Activates the repository virtual environment.
- Runs `binoculars.py`.
- Deactivates the virtual environment on exit.
- Forwards Ctrl-C to the child process.
- Terminates prior running instances by default to free GPU or VRAM resources.

To disable automatic termination if necessary:

```
BINOCULARS_DISABLE_AUTO_KILL=1 ./binoculars.sh ...
```

Output Contract (JSON)

Top-level keys include:

- `input`
- `observer`
- `performer`
- `cross`
- `binoculars`
- `cache`

Optional:

- `diagnostics.low_perplexity_spans` (when `--diagnose-paragraphs` is enabled)

Performance and Tuning Notes

- Main memory usage is driven by full logits (`tokens x vocab`).
- Long contexts are resource-intensive, even if VRAM appears available.
- `text.max_tokens` is the primary limit for runtime and memory safety.
- `n_ctx: 0` is typically optimal (auto-sizes to analyzed tokens).
- Observer and performer components are loaded sequentially.

Current shipped profile token limits:

- `fast`: 4096
- `long`: 12288

Adjust these values in profile JSON files as needed for your hardware.

Troubleshooting

Tokenizer mismatch error:

- Use a model pair from the same family (base and instruct sibling).
- Ensure both configurations reference compatible tokenizer and vocabulary models.

Missing file errors:

- Verify `config.binoculars.json` profile paths.
- Check model paths in the configuration JSON files.

GUI unavailable:

- Confirm that Tkinter is installed in your Python environment.

Unexpected GPU memory contention:

- Close other LLM processes, or rely on the wrapper's auto-kill feature.
- Reduce `text.max_tokens`.
- Lower `n_batch` if necessary.

llama.cpp context warnings:

- Low-signal llama.cpp runtime logs (`INFO`, `WARN`, `DEBUG`, including `llama_context` initialization messages) are suppressed by default for cleaner output.
- To disable log suppression for debugging, set `BINOCULARS_SUPPRESS_LLAMA_CONTEXT_WARNINGS=0`.

Tests

To run the regression suite:

```
./venv/bin/python -m unittest -v tests/test_regression_v1_1_x.py
```

License

PolyForm Noncommercial License 1.0.0. This project is licensed under the **PolyForm Noncommercial License 1.0.0** (see `LICENSE.md`).

Important scope clarification:

- The licence applies to the code, configuration, scripts, and documentation in this repository.
- It does not claim ownership of, or restrict use of, the Binoculars approach described in the associated paper.

Key points:

- Noncommercial use only: use, modification, and redistribution are permitted for noncommercial purposes.
- Commercial use requires explicit authorization. Any paid product or service that incorporates this code must have the author's permission.
- Attribution is mandatory. Redistribution or use of substantial portions of this project must include clear credit and preserve the licence and notice requirements described in `LICENSE.md`.

For commercial applications, contact the author to discuss participation or licensing.

Limitations

- No calibrated classifier thresholds are implemented yet.
- There is no claim of definitive authorship attribution.
- Markdown is processed as plain text; semantic markdown parsing is not performed.
- Long documents may need to be truncated due to full-logit computational cost.

Planned Next Major Feature

The next significant feature will be chunk-aware GUI analysis for large files that cannot be processed in a single pass.

Planned behaviour (pending implementation):

- `Analyze` computes the first analyzable chunk, limited by current token and memory constraints.
- After the first chunk is analyzed, an `Analyze Next` button appears if unscored text remains.
- `Analyze Next` analyzes the next chunk and updates the last covered line.
- `Analyze Next` remains visible until all chunks are processed.
- The status bar `B` should indicate the active chunk, selected by this priority:
 - The chunk containing the currently selected line.
 - The chunk containing the currently selected text block.
 - Otherwise, the chunk with the most lines in the visible window.
- Pressing `Analyze` analyzes the active chunk (not always the first chunk).
- Rewrite suggestions for a red line or highlighted block should compute approximate B-impact for that block within the active chunk context.

Safety / Responsible Use

Treat outputs as probabilistic signals within a broader review process. Do not use this tool as the sole basis for punitive or high-stakes actions.

Appendix: GPTZero vs Binoculars (Public Information)

This appendix summarizes public details about GPTZero and compares them to the Binoculars method implemented here.

1) What Is Known About Gptzero

Public GPTZero materials describe a layered detection system.

- The initial release (January 2023) focused on `perplexity` and `burstiness` as core indicators.
- Current documentation describes a probabilistic, sentence-level and document-level deep-learning detector that does not rely solely on perplexity or burstiness.

- GPTZero states its production system combines multiple components and outputs trinary sentence labels (human, mixed, AI) with confidence and uncertainty handling.

Details not publicly disclosed:

- Exact model architectures.
- Training data composition.
- Post-processing and thresholding methods.
- Adversarial hardening techniques.

Therefore, GPTZero is partially documented, but the full internal mechanisms remain proprietary.

2) How Binoculars Differs

Binoculars is more explicit in its mechanism.

- It is defined by transparent equations over two related language models:
 - observer $\log PPL$
 - observer-vs-performer $\log XPPL$
 - ratio $B = \log PPL / \log XPPL$
- It uses a zero-shot detection approach, requiring no target-model-specific training for the detector.
- The paper reports strong low-FPR performance, detecting over 90% of generated samples at 0.01% FPR in tested scenarios.
- Head-to-head comparisons in the paper show Binoculars outperforming GPTZero in their 2023 evaluation setup.

3) Why Binoculars Can Compete with Gptzero

Available evidence indicates Binoculars can operate in the same competitive tier, with some caveats.

- Published results show strong discrimination at very low false-positive rates, a key deployment factor.
- The mechanism is model-agnostic in the zero-shot sense and can generalize to unseen generators when assumptions hold.
- The approach is inspectable and reproducible (equations and open implementation), aiding calibration and operational trust.

However, caution is warranted.

- “As robust as GPTZero” is context-dependent and should be validated on your domain, document lengths, and attack or perturbation conditions.
- The Binoculars paper notes important limits, such as degraded recall in some low-resource language settings and no guarantee against motivated adversarial evasion.
- Independent benchmarks indicate that many detectors degrade under perturbation, so robustness claims should be treated as empirical and subject to ongoing review.

In practice:

- Binoculars is credibly “same-league” with commercial detectors in several reported scenarios, especially when low-FPR behaviour is required.
- You should run periodic, domain-specific benchmark checks (including perturbed or paraphrased text) before making strong operational claims.

4) Sources

- Binoculars paper (arXiv): <https://arxiv.org/abs/2401.12070>
- Binoculars paper in repo: [background/2401.12070v3.pdf](#)
- GPTZero technology page: <https://gptzero.me/technology>
- GPTZero FAQ (method overview): <https://gptzero.me/faqs/how-does-ai-detection-work>
- GPTZero original launch note (perplexity/burstiness framing): <https://gptzero.me/news/first-release-of-gptzero-for-educators-january-3-2023>
- RAID benchmark (robustness context): <https://arxiv.org/abs/2406.07958>