Tag-Connect no-legs SWD — disposable physical-map fixture

TC2030-CTX-NL external cable: board footprint is a zero-height contact pattern, not a purchased fitted header.
Top PCB map: 1 VTref, 2 SWDIO, 3 nRESET, 4 SWCLK, 5 GND, 6 SWO (optional).



External cable: TC2030-CTX-NL
No purchased part fitted to PCB.
Stock pin1 VCC = probe VTref only.



TI supply-good candidate
RESET2 independent of MCU NRST.
Threshold2.857..2.974V±29mVhystTYP.
Release120..350ms;assert20usTYP ONLY.
Stockland / fullflash / collapse gates OPEN.

Manufacturer Rev B: 6 copper/mask contacts, NO PASTE, 3 unnumbered NPTH alignment holes.
Actual cable contact face is mirrored relative to PCB top. One alignment hole versus paired holes keys orientation.
No tracks/vias in central shaded keepout; no other signal within 0.020 inch (0.508 mm) of any contact.
Stock footprint does not encode those routing rules or full cable mating/access envelope.

All six fixture terminals intentionally unwired: no fake NC flags or source flags.
Main EPS and historical package evidence remain frozen. No real SWD protection circuit is implemented here.

CUSTOM — REVIEW REQUIRED: U1A-U1E TMUX1511PWR review candidate
Construction authorized; bidirectional SPST: SEL HIGH closes S ↔ D; LOW opens. Body color unsupported; green callout alternative.











U1: TI PW14 top-view pin1 upper-left, CCW: no EP / NC / mechanical lead. 14 raw copper/paste/mask pads.
Stock generic land differs from TI example: reserve >=7.70 x5.90mm for worst flash + clearance. Full mechanical / assembly / circuit qualification OPEN.

Sheet: /
File: swd_parts_check.kicad_sch

Title:

Size: B	Date:	**Rev:**
KiCad E.D.A. 10.0.0		Id: 1/1