Exercise: **String Functions**

Day 1, Part D

Use the following code to create a vector of all the files in the answer key folder:

```
> main_dir <- "C:/Users/ngraetz/Documents/repos/r_training_penn/" # CHANGE TO YOUR COPY OF THE TRAIN
> files <- list.files(paste0(main_dir, "exercises/answer_keys/"))</pre>
```

- 1. From the files vector, create a new vector (pdfs) of just the PDF files...
 - a. Using grepl().

```
> pdfs <- files[grepl("pdf", files)]</pre>
```

b. Using grep() with value = F.

```
> pdfs <- files[grep("pdf", files)]</pre>
```

c. Using grep() with value = T.

```
> pdfs <- grep("pdf", files, value = T)</pre>
```

- 2. From the pdfs vector...
 - a. Create a new vector (day1) of just exercises from day 1.

```
> day1 <- grep("exercise_1", pdfs, value = T)</pre>
```

- b. Remove "exercise_" and "_answers.pdf" from the elements of day1. (hint: use gsub())
 - > day1 <- gsub("exercise_", "", day1)</pre>
 - > day1 <- gsub("_answers.pdf", "", day1)</pre>
- c. Replace underscores with spaces in day1.

```
> day1 <- gsub("_", " ", day1)</pre>
```

- d. Remove the lesson number/letter (e.g., "1a") from day1. (hint: use substr())
 - > day1 <- substr(day1, 4, 100)

Bonus

3. Load the Nigeria health metrics data set by running the following:

```
> data <- read.csv(paste0(main_dir, "data/nigeria_healthmap.csv"), stringsAsFactors = F)
```

- a. Keep only the rows where the indicator name includes "immunization coverage".
 - > data <- data[grepl("immunization coverage", data\$indicator),]</pre>
- b. Replace "immunization coverage" with "Coverage" in the indicator variable.
 - > data\$indicator <- gsub("immunization coverage", "Coverage", data\$indicator)</pre>
- c. Remove "(%)" from the indicator variable. (hint: see the fixed argument for gsub)
 - > data\$indicator <- gsub(" (%)", "", data\$indicator, fixed = T)</pre>
- d. The indicator_type variable has an extra space at the end-remove this space. (hint: use gsub() with regular expressions, or try the trimws() function)

```
> data$indicator_type <- gsub(" $", "", data$indicator_type)
> # or
> data$indicator_type <- trimws(data$indicator_type)</pre>
```

e. Using the indicator_type, indicator, location_name, and year variables, create a new variable (full_title) that has values similar to: "Childhood immunizations: BCG Coverage, Nigeria, 2000 (Percent)"