

#31: Paper Discussion

Sankha Narayan Guria

EECS 700: Introduction to Program Synthesis



Regae

[Zhang, Lowmanstone, Wang, Glassman,
UIST'20]

Better UI for a regex synthesizer

Regae: contributions

- Novel way to express intent: semantics augmentation
- Novel way to explain synthesis results to user: data augmentation
- Automata-theoretic algorithms to generate explanatory examples
 - familiar examples with different output, corner cases, distinguishing examples
- Usability confirmed by user study
 - Completion rate: 12/12 vs 4/12; twice more confident; less cognitive load

Regae: limitations

Limited to regexes

Which parts are generalizable and which not?

Marking as general affects completeness

Not tolerant to user mistakes

User study participants might not be representative

Regae: questions

- Behavioral constraints? Structural constraints? Search strategy?
 - IO examples
 - Built-in DSL
 - Top-down enumerative search

Regae: questions

- Does semantic augmentation contribute to behavioral or structural constraints, or something else?
 - Structural because it affects the search space
- What about data augmentation?
 - Directly contributes only to result comprehension
 - Indirectly to behavioral because users can use those examples as input

Regae: questions

- When can we soundly reject the sketch `concat(<num>, e)`?
 - If e.g. `<num>` is marked excluded [that's not what I meant]
 - When there is a positive example that doesn't start with a number
 - More generally, replace `e` with `star(<any>)` and check whether all positives can be parsed!
 - if under not, then replace with an empty-language regex
 - Another idea is define equivalence on regexes, e.g. `optional(star(e))` is equivalent to `star(e)`

Regae: questions

- Why is it important to randomize the order of control vs treatment?

RbSyn

[Guria, Foster, Van Horn, PLDI'21]

Program synthesis from side effects

RbSyn: contributions

- Using side-effects to guide search
- Rule based merging to create if-then-else branches
- Automatic side effect inference from test failures
- Evaluated on programs from real-world benchmarks

RbSyn: limitations

- Cannot synthesize loops/lambdas/etc.
- Effect annotation burden may require domain insight
- Limited to typed subset of Ruby

RbSyn: questions

- Branch merging strategy wrt Synquid and EUSolver?
 - Synquid uses liquid abduction
 - EUSolver uses decision tree learning (information gain heuristic)
 - RbSyn uses rules-based approach as no counterexample possible

RbSyn: questions

- Scaling of branch merging with changing no. of tests (N)
 - $N!$ ways of merges to be checked
 - It is $M!$ if there are only M distinct programs from tests
 - The bottleneck is the number of distinct solutions to individual tests

RbSyn: questions

- Order of search for effect annotations:
 - `User.name`
 - `User`
 - `*`
- Methods to be considered in this order: `name=`, `save`, `delete`

RbSyn: questions

- Why does RbSyn stay sound?
 - Wrong effect inferred: Adds program to the work list, no sound program is eliminated from the work list
 - Wrong method substituted: All correct effect annotated method choices are enumerated