Introduction to Networks and Network Programming

CS 475

A Client-Server Transaction

- **Most network applications are based on the client-server model:**
  - A ***server*** process and one or more ***client*** processes
  - Server manages some ***resource***
  - Server provides ***service*** by manipulating resource for clients
  - Server activated by request from client (vending machine analogy)



Note: clients and servers are processes running on hosts (can be the same or different hosts)

Hardware Organization of a Network Host



3

Computer Networks

- **A *network* is a hierarchical system of boxes and wires organized by geographical proximity**
  - SAN (System Area Network) spans cluster or machine room
    - Switched Ethernet, Quadrics QSW, …
  - LAN (Local Area Network) spans a building or campus
    - Ethernet is most prominent example
  - WAN (Wide Area Network) spans country or world
    - Typically high-speed point-to-point phone lines
- **An *internetwork* (*internet*) is an interconnected set of networks**
  - The Global IP Internet (uppercase "I") is the most famous example of an internet (lowercase "i")
- **Let's see how an internet is built from the ground up**

4

Lowest Level: Ethernet Segment



- **Ethernet segment consists of a collection of *hosts* connected by wires (twisted pairs) to a *hub***
- **Spans room or floor in a building**
- **Operation**
  - Each Ethernet adapter has a unique 48-bit address (MAC address)
    - E.g., 00:16:ea:e3:54:e6
  - Hosts send bits to any other host in chunks called ***frames***
  - Hub slavishly copies each bit from each port to every other port
    - Every host sees every bit
    - Note: Hubs are on their way out. Bridges (switches, routers) became cheap enough to replace them

5

Next Level: Bridged Ethernet Segment



- **Spans building or campus**
- **Bridges cleverly learn which hosts are reachable from which ports and then selectively copy frames from port to port**

6

Conceptual View of LANs

- For simplicity, hubs, bridges, and wires are often shown as a collection of hosts attached to a single wire:

7

Next Level: internets

- Multiple incompatible LANs can be physically connected by specialized computers called *routers*
- The connected networks are called an *internet* (lower case)



LAN 1 and LAN 2 might be completely different, totally incompatible (e.g., Ethernet, Fibre Channel, 802.11, T1-links, DSL, …)*

8

Logical Structure of an internet



- **Ad hoc interconnection of networks**
  - No particular topology
  - Vastly different router & link capacities
- **Send packets from source to destination by hopping through networks**
  - Router forms bridge from one network to another
  - Different packets may take different routes

9

The Notion of an internet Protocol

- **How is it possible to send bits across incompatible LANs and WANs?**
- **Solution: *protocol* software running on each host and router**
  - Protocol is a set of rules that governs how hosts and routers should cooperate when they transfer data from network to network.
  - Smooths out the differences between the different networks

10

What Does an internet Protocol Do?

- **Provides a *naming scheme***
  - An internet protocol defines a uniform format for ***host addresses***
  - Each host (and router) is assigned at least one of these internet addresses that uniquely identifies it
- **Provides a *delivery mechanism***
  - An internet protocol defines a standard transfer unit (***packet***)
  - Packet consists of ***header*** and ***payload***
    - Header: contains info such as packet size, source and destination addresses
    - Payload: contains data bits sent from source host

11

Transferring internet Data Via Encapsulation



PH: Internet packet header
FH: LAN frame header

12

Other Issues

- **We are glossing over a number of important questions:**
  - What if different networks have different maximum frame sizes? (segmentation)
  - How do routers know where to forward frames?
  - How are routers informed when the network topology changes?
  - What if packets get lost?
- **These (and other) questions are addressed by the area of systems known as *computer networking***

13

Global IP Internet (upper case)

- **Most famous example of an internet**
- **Based on the TCP/IP protocol family**
  - IP (Internet Protocol) :
    - Provides *basic naming scheme* and unreliable *delivery capability* of packets (datagrams) from *host-to-host*
  - UDP (Unreliable Datagram Protocol)
    - Uses IP to provide *unreliable* datagram delivery from *process-to-process*
  - TCP (Transmission Control Protocol)
    - Uses IP to provide *reliable* byte streams from *process-to-process* over *connections*
- **Accessed via a mix of Unix file I/O and functions from the *sockets interface***

14

Hardware and Software Organization of an Internet Application



15

A Programmer's View of the Internet

1. Hosts are mapped to a set of 32-bit *IP addresses*

- 129.174.121.120

2. The set of IP addresses is mapped to a set of identifiers called Internet *domain names*

- 129.174.125.153 is mapped to www.cs.gmu.edu

3. A process on one Internet host can communicate with a process on another Internet host over a *connection*

16

Aside: IPv4 and IPv6

- **The original Internet Protocol, with its 32-bit addresses, is known as *Internet Protocol Version 4* (IPv4)**
- **1996: Internet Engineering Task Force (IETF) introduced *Internet Protocol Version 6* (IPv6) with 128-bit addresses**
  - Intended as the successor to IPv4
- **As of 2015, vast majority of Internet traffic still carried by IPv4**
  - Only 4% of users access Google services using IPv6.
- **We will focus on IPv4, but will show you how to write networking code that is protocol-independent.**

17

(1) IP Addresses

- **32-bit IP addresses are stored in an *IP address struct***
  - IP addresses are always stored in memory in *network byte order* (big-endian byte order)
  - True in general for any integer transferred in a packet header from one machine to another.
    - E.g., the port number used to identify an Internet connection.

```
/* Internet address structure */
struct in_addr {
    uint32_t  s_addr; /* network byte order (big-endian) */
};
```

18

Dotted Decimal Notation

- By convention, each byte in a 32-bit IP address is represented by its decimal value and separated by a period
  - IP address: `0x8002C2F2 = 128.2.194.242`
- Use `getaddrinfo` and `getnameinfo` functions (described later) to convert between IP addresses and dotted decimal format.

19

(2) Internet Domain Names



First-level domain names

Second-level domain names

Third-level domain names

20

Domain Naming System (DNS)

- **The Internet maintains a mapping between IP addresses and domain names in a huge worldwide distributed database called *DNS***

- **Conceptually, programmers can view the DNS database as a collection of millions of *host entries.***
  - Each host entry defines the mapping between a set of domain names and IP addresses.
  - In a mathematical sense, a host entry is an equivalence class of domain names and IP addresses.

21

Properties of DNS Mappings

- **Can explore properties of DNS mappings using `nslookup`**
  - Output edited for brevity

- **Each host has a locally defined domain name `localhost` which always maps to the *loopback address* `127.0.0.1`**

```
linux> nslookup localhost
Address: 127.0.0.1
```

- **Use `hostname` to determine real domain name of local host:**

```
linux> hostname
zeus.vse.gmu.edu
```

22

Properties of DNS Mappings (cont)

- Simple case: one-to-one mapping between domain name and IP address:

```
linux> nslookup www.cs.gmu.edu
Address: 129.174.125.153
```

- Multiple domain names mapped to the same IP address:

```
linux> nslookup cs.mit.edu
Address: 18.62.1.6
linux> nslookup eecs.mit.edu
Address: 18.62.1.6
```

23

Properties of DNS Mappings (cont)

- Multiple domain names mapped to multiple IP addresses:

```
linux> nslookup www.twitter.com
Address: 199.16.156.6
Address: 199.16.156.70
Address: 199.16.156.102
Address: 199.16.156.230

linux> nslookup twitter.com
Address: 199.16.156.102
Address: 199.16.156.230
Address: 199.16.156.6
Address: 199.16.156.70
```

- Some valid domain names don't map to any IP address:

```
linux> nslookup ics.cs.cmu.edu
*** Can't find ics.cs.cmu.edu: No answer
```

24

(3) Internet Connections

- **Clients and servers communicate by sending streams of bytes over *connections*. Each connection is:**
  - *Point-to-point*: connects a pair of processes.
  - *Full-duplex*: data can flow in both directions at the same time,
  - *Reliable*: stream of bytes sent by the source is eventually received by the destination in the same order it was sent.

- ***A socket* is an endpoint of a connection**
  - *Socket address* is an `IPaddress:port` pair

- **A *port* is a 16-bit integer that identifies a process:**
  - ***Ephemeral port*: Assigned automatically by client kernel when client makes a connection request.**
  - ***Well-known port:* Associated with some *service* provided by a server (e.g., port 80 is associated with Web servers)**

25

Well-known Ports and Service Names

- **Popular services have permanently assigned *well-known ports* *and* corresponding *well-known service names*:**
  - echo server: 7/echo
  - ssh servers: 22/ssh
  - email server: 25/smtp
  - Web servers: 80/http

- **Mappings between well-known ports and service names is contained in the file `/etc/services` on each Linux machine.**

26

Anatomy of a Connection

- A connection is uniquely identified by the socket addresses of its endpoints (*socket pair*)
  - `(cliaddr:cliport, servaddr:servport)`



51213 is an ephemeral port allocated by the kernel

80 is a well-known port associated with Web servers

27

Using Ports to Identify Services



28

Sockets Interface

- **Set of system-level functions used in conjunction with Unix I/O to build network applications.**
- **Created in the early 80's as part of the original Berkeley distribution of Unix that contained an early version of the Internet protocols.**
- **Available on all modern systems**
  - Unix variants, Windows, OS X, IOS, Android, ARM

29

Sockets

- **What is a socket?**
  - To the kernel, a socket is an endpoint of communication
  - To an application, a socket is a file descriptor that lets the application read/write from/to the network
    - ***Remember:*** All Unix I/O devices, including networks, are modeled as files
- **Clients and servers communicate with each other by reading from and writing to socket descriptors**



- **The main distinction between regular file I/O and socket I/O is how the application "opens" the socket descriptors**

30

Socket Address Structures

- **Generic socket address:**
  - For address arguments to **`connect`**, **`bind`**, and **`accept`**
  - Necessary only because C did not have generic (**`void *`**) pointers when the sockets interface was designed
  - For casting convenience, we adopt the Stevens convention:

    `typedef struct sockaddr SA;`

```
struct sockaddr {
  uint16_t  sa_family;    /* Protocol family */
  char      sa_data[14];  /* Address data.  */
};
```



31

Socket Address Structures

- **Internet-specific socket address:**
  - Must cast (`struct sockaddr_in *`) to (`struct sockaddr *`) for functions that take socket address arguments.

```
struct sockaddr_in  {
  uint16_t        sin_family;  /* Protocol family (always AF_INET) */
  uint16_t        sin_port;    /* Port num in network byte order */
  struct in_addr  sin_addr;    /* IP addr in network byte order */
  unsigned char   sin_zero[8]; /* Pad to sizeof(struct sockaddr) */
};
```



32


Sockets Interface
2. Start client
Client
1. Start server
Server
getaddrinfo
socket
bind
listen
connect
accept
open_clientfd
open_listenfd
Connection request
Client / Server Session
rio_writen
rio_readlineb
3. Exchange data
Await connection request from next client
close
EOF
4. Disconnect client
5. Drop client
33


Sockets Interface
Client
Server
getaddrinfo
socket
bind
listen
connect
accept
open_clientfd
open_listenfd
Connection request
Client / Server Session
rio_writen
rio_readlineb
Await connection request from next client
close
EOF
34

Host and Service Conversion: `getaddrinfo`

- **`getaddrinfo` is the modern way to convert string representations of hostnames, host addresses, ports, and service names to socket address structures.**
  - Replaces obsolete `gethostbyname` and `getservbyname` funcs.
- **Advantages:**
  - Reentrant (can be safely used by threaded programs).
  - Allows us to write portable protocol-independent code
    - Works with both IPv4 and IPv6
- **Disadvantages**
  - Somewhat complex
  - Fortunately, a small number of usage patterns suffice in most cases.

35

Host and Service Conversion: `getaddrinfo`

```
int getaddrinfo(const char *host,            /* Hostname or address */
                const char *service,         /* Port or service name */
                const struct addrinfo *hints,/* Input parameters */
                struct addrinfo **result);   /* Output linked list */

void freeaddrinfo(struct addrinfo *result);  /* Free linked list */

const char *gai_strerror(int errcode);       /* Return error msg */
```

- **Given `host` and `service`, `getaddrinfo` returns `result` that points to a linked list of `addrinfo` structs, each of which points to a corresponding socket address struct, and which contains arguments for the sockets interface functions.**
- **Helper functions:**
  - `freeadderinfo` frees the entire linked list.
  - `gai_strerror` converts error code to an error message.

36

Linked List Returned by `getaddrinfo`



- Clients: walk this list, trying each socket address in turn, until the calls to `socket` and `connect` succeed.
- Servers: walk the list until calls to `socket` and `bind` succeed.

37

`addrinfo` Struct

```
struct addrinfo {
    int              ai_flags;     /* Hints argument flags */
    int              ai_family;    /* First arg to socket function */
    int              ai_socktype;  /* Second arg to socket function */
    int              ai_protocol;  /* Third arg to socket function  */
    char            *ai_canonname; /* Canonical host name */
    size_t           ai_addrlen;   /* Size of ai_addr struct */
    struct sockaddr *ai_addr;      /* Ptr to socket address structure */
    struct addrinfo *ai_next;      /* Ptr to next item in linked list */
};
```

- Each addrinfo struct returned by getaddrinfo contains arguments that can be passed directly to `socket` function.
- Also points to a socket address struct that can be passed directly to `connect` and `bind` functions .

38

Host and Service Conversion: `getnameinfo`

- **`getnameinfo` is the inverse of getaddrinfo, converting a socket address to the corresponding host and service.**
  - Replaces obsolete `gethostbyaddr` and `getservbyport` funcs.
  - Reentrant and protocol independent.

```
int getnameinfo(const SA *sa, socklen_t salen, /* In: socket addr */
                char *host, size_t hostlen,    /* Out: host */
                char *serv, size_t servlen,    /* Out: service */
                int flags);                    /* optional flags */
```

39

Conversion Example

```
#include "csapp.h"

int main(int argc, char **argv)
{
    struct addrinfo *p, *listp, hints;
    char buf[MAXLINE];
    int rc, flags;

    /* Get a list of addrinfo records */
    memset(&hints, 0, sizeof(struct addrinfo));
    hints.ai_family = AF_INET;       /* IPv4 only */
    hints.ai_socktype = SOCK_STREAM; /* Connections only */
    if ((rc = getaddrinfo(argv[1], NULL, &hints, &listp)) != 0) {
        fprintf(stderr, "getaddrinfo error: %s\n", gai_strerror(rc));
        exit(1);
    }
```

hostinfo.c

40

Conversion Example (cont)

```
    /* Walk the list and display each IP address */
    flags = NI_NUMERICHOST; /* Display address instead of name */
    for (p = listp; p; p = p->ai_next) {
        Getnameinfo(p->ai_addr, p->ai_addrlen,
                    buf, MAXLINE, NULL, 0, flags);
        printf("%s\n", buf);
    }

    /* Clean up */
    Freeaddrinfo(listp);

    exit(0);
}
```

hostinfo.c

41

Running hostinfo

```
whaleshark> ./hostinfo localhost
127.0.0.1

whaleshark> ./hostinfo www.cs.gmu.edu
129.174.125.153

whaleshark> ./hostinfo twitter.com
199.16.156.230
199.16.156.38
199.16.156.102
199.16.156.198
```

42

Next time

- Using `getaddrinfo` for host and service conversion
- Writing clients and servers
- Writing Web servers!

43

Additional slides

44

Basic Internet Components

- **Internet backbone:**
  - collection of routers (nationwide or worldwide) connected by high-speed point-to-point networks
- **Internet Exchange Points (IXP):**
  - router that connects multiple backbones (often referred to as peers)
  - Also called Network Access Points (NAP)
- **Regional networks:**
  - smaller backbones that cover smaller geographical areas (e.g., cities or states)
- **Point of presence (POP):**
  - machine that is connected to the Internet
- **Internet Service Providers (ISPs):**
  - provide dial-up or direct access to POPs

45

Internet Connection Hierarchy



46

IP Address Structure

- **IP (V4) Address space divided into classes:**



- **Network ID Written in form w.x.y.z/n**
  - n = number of bits in host address
  - E.g., CMU written as 128.2.0.0/16
    - Class B address
- **Unrouted (private) IP addresses:**

  10.0.0.0/8 172.16.0.0/12 192.168.0.0/16

47

Evolution of Internet

- **Original Idea**
  - Every node on Internet would have unique IP address
    - Everyone would be able to talk directly to everyone
  - No secrecy or authentication
    - Messages visible to routers and hosts on same LAN
    - Possible to forge source field in packet header
- **Shortcomings**
  - There aren't enough IP addresses available
  - Don't want everyone to have access or knowledge of all other hosts
  - Security issues mandate secrecy & authentication

48

Evolution of Internet: Naming

- **Dynamic address assignment**
  - Most hosts don't need to have known address
    - Only those functioning as servers
  - DHCP (Dynamic Host Configuration Protocol)
    - Local ISP assigns address for temporary use

- **Example:**
  - Laptop at CMU (wired connection)
    - IP address 128.2.213.29 (`bryant-tp4.cs.cmu.edu`)
    - Assigned statically
  - Laptop at home
    - IP address 192.168.1.5
    - Only valid within home network

49

Evolution of Internet: Firewalls



- **Firewalls**
  - Hides organizations nodes from rest of Internet
  - Use local IP addresses within organization
  - For external service, provides proxy service
    1. Client request: src=10.2.2.2, dest=216.99.99.99
    2. Firewall forwards: src=176.3.3.3, dest=216.99.99.99
    3. Server responds: src=216.99.99.99, dest=176.3.3.3
    4. Firewall forwards response: src=216.99.99.99, dest=10.2.2.2

50