CAN THO UNIVERSITY

COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY

FACULTY OF SOFTWARE ENGINEERING



GRADUATION THESIS
BACHELOR OF ENGINEERING IN

SOFTWARE ENGINEERING
(HIGH-QUALITY PROGRAM)

RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

Student: Nguyen Thanh Trong

Student ID: B2305615

Class: 2023 – 2027 (K49)

Advisor: Ho Quang Thai, Ph.D.

Can Tho, [MM/YYYY]

CAN THO UNIVERSITY

COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY

FACULTY OF SOFTWARE ENGINEERING



GRADUATION THESIS
BACHELOR OF ENGINEERING IN
SOFTWARE ENGINEERING
(HIGH-QUALITY PROGRAM)

RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

Student:

Nguyen Thanh Trong

Student ID: B2305615

Class: DI2396F1, K49

Advisor:

Ho Quang Thai, Ph.D.

Can Tho, [MM/YYYY]

CAN THO UNIVERSITY
COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY

SOCIALIST REPUBLIC OF VIETNAM
Independence – Freedom – Happiness

THESIS REVISION CONFIRMATION IN ACCORDANCE WITH THE COMMITTEE'S COMMENTS

Thesis Title: RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

Student: Nguyen Thanh Trong Student ID: B2305615

Class Code: DI2396F1

The thesis was presented before the Thesis Examination Committee of the Software Engineering Program.

Members of the Examination Committee:

- [Name], Ph.D.
- [Name], Ph.D.
- [Name], Ph.D.

Reporting date: [Month DD, YYYY]

The thesis has been revised in accordance with the Committee's comments.

Can Tho, ……

Supervisor

Ho Quang Thai, Ph.D.

COMMENTS OF THE ADVISOR

. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .

Can Tho, ……

Advisor

Ho Quang Thai, Ph.D.

ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to my advisor, Dr. Ho Quang Thai, for his guidance throughout this thesis. I also thank the lecturers of the Faculty of Software Engineering, College of Information and Communication Technology, Can Tho University, for the knowledge they gave me, and my family and friends for their support. **[PENDING: review and personalise before submission.]**

Can Tho, ……

Student

Nguyen Thanh Trong

COMMITMENT TO RESULTS

I hereby certify that the graduation thesis titled "RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL" is the result of my own research and has not been submitted for any other degree or qualification.

All references used in the thesis are clearly cited, including the author's name, the title of the work, and the time and place of publication. I accept full responsibility for any unauthorized copying, violations of academic regulations, or instances of academic dishonesty.

Can Tho, ……

Student

Nguyen Thanh Trong

ABSTRACT

A single amino acid substitution can alter the activity of a degron, a sequence element involved in selective protein degradation. This research progress report, dated 6 November 2026, examines substitution effects as changes in the Protein Stability Index (ΔPSI) measured by a peptide reporter assay and the development of a local analysis tool. The computational work reconstructs labels, controls sequence overlap and evaluates models with protein-group-aware folds, inner model selection and group-bootstrap confidence intervals.

The full-PSI development set contains 235 peptides, 122 412 mutation cells and 221 protein groups. Expanding ridge training from WT PSI at most 4 to the full range reduces peptide-macro mean absolute error from 0.43358 to 0.40780 PSI. Frozen ESM2-35M with a convolutional head reaches 0.38435 MAE. A completed local study compares nine frozen pLM checkpoints and 60 matched frozen/LoRA fits. LoRA reaches 0.3637 MAE with restricted training and 0.3650 with full-range training, improving on matched frozen controls by 9.8% and 6.5%. Protein-group intervals support both reductions, while performance by WT-PSI stratum shows a training-coverage trade-off. Scanning-label pre-training helps its tested CNN control; quality weighting does not help ridge. Out-of-fold LoRA probabilities improve Brier score but retain calibration errors.

The local campaign ends with 633 completed jobs and two pending input-dependent extensions. On a locked same-laboratory scanning set, the fixed W5 ridge model reaches positive AUROC 0.8405, but its MAE advantage over predicting zero is unresolved; LoRA has not been evaluated on that set. As of 6 November 2026, a React/FastAPI baseline exists, while persistent projects, batch/protein jobs and experimental comparison remain incomplete. The serving model is unchanged and requires a compatible final refit/export before promotion. The results remain assay development evidence, without independent external, intact-protein or clinical validation.

Keywords: degron, protein stability, mutation effect prediction, ubiquitin–proteasome system, machine learning.

TÓM TẮT

Một phép thay thế amino acid có thể làm thay đổi hoạt tính degron, tín hiệu trình tự liên quan đến phân hủy protein có chọn lọc. Báo cáo tiến độ ngày 06/11/2026 khảo sát dự đoán hiệu ứng đột biến bằng độ thay đổi chỉ số ổn định protein (ΔPSI) trong thí nghiệm reporter peptide và quá trình xây dựng công cụ phân tích local. Quy trình dựng lại nhãn, kiểm soát chồng lặp trình tự và đánh giá theo nhóm protein, với lựa chọn mô hình ở tập trong và khoảng tin cậy bootstrap theo nhóm.

Bộ phát triển toàn dải PSI có 235 peptide, 122 412 ô đột biến và 221 nhóm protein. Mở rộng train ridge từ PSI hoang dã không quá 4 sang toàn dải giảm MAE trung bình theo peptide từ 0.43358 xuống 0.40780 PSI. ESM2-35M đóng băng kết hợp CNN đạt MAE 0.38435. Nghiên cứu local hoàn tất so sánh chín checkpoint pLM đóng băng và 60 lượt fit frozen/LoRA có đối chứng. LoRA đạt MAE 0.3637 khi giới hạn train và 0.3650 khi train toàn dải, giảm tương ứng 9.8% và 6.5% so với frozen cùng điều kiện. Khoảng tin cậy theo nhóm ủng hộ cả hai mức giảm; phân tầng PSI cho thấy đánh đổi về độ bao phủ train. Tiền huấn luyện bằng nhãn scanning giúp CNN trong thiết kế đã thử; trọng số chất lượng không giúp ridge. Xác suất LoRA ngoài fold cải thiện Brier nhưng vẫn còn sai lệch hiệu chuẩn.

Campaign local kết thúc với 633 job hoàn tất và hai mở rộng chờ đầu vào. Trên tập scanning giữ lại cùng phòng thí nghiệm, ridge W5 cố định đạt AUROC dương 0.8405, nhưng lợi thế MAE so với dự đoán 0 chưa rõ; LoRA chưa được đánh giá trên tập này. Đến ngày 06/11/2026, đã có baseline React/FastAPI; lưu dự án, job peptide/protein và đối chiếu thực nghiệm còn dở. Mô hình phục vụ chưa đổi, cần refit và export tương thích trước khi thay thế. Kết quả vẫn là bằng chứng phát triển trong assay, chưa xác nhận độc lập ngoài nguồn, protein nguyên vẹn hay lâm sàng.

Từ khóa: degron, độ bền protein, dự đoán hiệu ứng đột biến, hệ ubiquitin–proteasome, học máy.

RESEARCH PROGRESS STATUS

Evidence cutoff: 6 November 2026. This is a research progress report within the existing thesis document. Its purpose is to explain the problem, the decisions made, the experiments completed and the questions still open. The official project title and Faculty template are retained; unfilled defence, committee and acceptance fields do not represent completed academic procedures.

Verified observations. Public reporter-assay labels, recorded configurations, saved predictions and reproducible calculations support the reported development results. Completion of the local runnable graph means 633 jobs completed, with two extensions awaiting reviewed inputs. It does not establish independent biological validation or acceptance of a final model.

Evidence boundaries. The restricted 91-peptide benchmark, the full-PSI 235-peptide development population and the locked same-laboratory transfer population answer different questions. Their metrics are reported separately. Three seeds sharing an outer partition are repeated fits rather than three independent test cohorts.

Interpretation and hypotheses. An observed error reduction is distinguished from a proposed biological or statistical explanation. Benefits for selecting wet-lab experiments remain potential: no prospective experiment, cost saving or clinical benefit has been measured by this project.

Open work. Independent source validation, LoRA transfer, final serving refit/calibration/export and expanded software acceptance remain open. Missing information is classified explicitly in the accompanying review record instead of being replaced with assumed values.

The introduction states the current research questions. Chapter 2 explains the necessary biological and computational concepts. Section 3.4 reconstructs the research decisions and data versions. Chapter 4 preserves unsuccessful controls alongside the new results and assesses what each question can currently support. The conclusion therefore records provisional findings and the next evidence needed.

TABLE OF CONTENTS

THESIS REVISION CONFIRMATION i

COMMENTS OF THE ADVISOR ii

ACKNOWLEDGEMENTS iii

COMMITMENT TO RESULTS iv

ABSTRACT v

TÓM TẮT vi

RESEARCH PROGRESS STATUS vii

TABLE OF CONTENTS viii

LIST OF FIGURES xiv

LIST OF TABLES xvi

GLOSSARY AND ABBREVIATIONS xx

PART 1. INTRODUCTION 1

1. Problem Statement and Scientific Motivation 1

1.1. From Proteins to Regulated Degradation 1

1.2. Mutation Measurements and Their Limits 1

1.3. The Specific Prediction Problem 2

2. Related Work and the Research Question 2

2.1. What Existing Studies Establish 2

2.2. Research Questions Organising This Progress Report 3

3. Objectives 4

3.1. General Objective 4

3.2. Specific Objectives 4

4. Research Subject and Scope 5

5. Research Process and Technologies 5

6. Contributions Achieved and Still Expected 6
7. Structure and Status of This Report 6

PART 2. CONTENT 7

CHAPTER 1: PROBLEM DESCRIPTION 7
1.1. Detailed Problem Description 7
1.2. Functions of the System 8
1.2.1. Predict the Effect Matrix 8
1.2.2. Rank Substitutions 8
1.2.3. Export Results with Provenance 9
1.2.4. Select a Protein and Tiles 10
1.2.5. Compare with Measured Data 10
1.2.6. View ClinVar and Reference Annotations 11
1.2.7. View Model and Data Provenance 12
1.2.8. Analyse Peptide Batches or a Whole Protein 12
1.2.9. Import Experimental Observations 13
1.2.10. Manage Projects and Analysis History 14
1.3. Non-Functional Requirements 15
1.3.1. Performance Requirements 15
1.3.2. Information Safety Requirements 15
1.3.3. Security Requirements 15
1.3.4. Reliability Requirements 15
1.3.5. Maintainability Requirements 16
1.3.6. Usability and Accessibility Requirements 16
1.4. Implementation and Design Constraints 16
1.4.1. Implementation Constraints 16
1.4.2. Design Constraints 16

CHAPTER 2: THEORETICAL BACKGROUND 17
2.1. Proteins and Their Regulation 17
2.1.1. Amino Acids, Peptides and Protein Structure 17
2.1.2. Stability, Turnover, Degradation and Homeostasis 17
2.1.3. Selective Degradation and Degrons 18

2.1.4. How a Substitution Can Change a Degradation Signal 18
2.2. Experimental Measurements and Mutation Labels 19
2.2.1. GPS Profiling and the Meaning of PSI 19
2.2.2. Scanning, Saturation and the Unit of Observation 19
2.2.3. Constructing and Interpreting the Effect 20
2.2.4. Quality Control, Noise and PSI-Based Selection 20
2.3. Representations and Learning Methods 21
2.3.1. Supervised Regression and Simple Controls 21
2.3.2. Protein Language Models and Embeddings 22
2.3.3. Pointwise, CNN and Multi-Scale CNN Heads 22
2.3.4. Frozen Encoders, Fine-Tuning and LoRA 23
2.3.5. Transfer Learning and Endpoint Compatibility 23
2.4. Evaluation and Reliability 23
2.4.1. Data Splitting, Leakage and Generalisation 23
2.4.2. Losses and Regression Metrics 24
2.4.3. Event Ranking and Probability Calibration 24
2.4.4. Uncertainty, Seeds and Fair Comparisons 25
2.5. Research and Software Toolchains 25

CHAPTER 3: SOLUTION DESIGN AND IMPLEMENTATION 26
3.1. System Overview 26
3.1.1. Product Context 26
3.1.2. Functional Overview 26
3.2. System Architecture 26
3.2.1. Architectural Components 26
3.2.2. Interaction Between Components 27
3.2.3. Design Rationale 27
3.3. Data Design 28
3.3.1. Data Sources and Preprocessing 28
3.3.2. Data Model 28
3.3.3. Data Dictionary 28
3.3.4. Relationships Between Entities 29

3.4. Research Progress and Data Evolution 29
3.4.1. From Peptide Activity to Direct Mutation Labels 29
3.4.2. Why the Study Expanded Training Coverage 31
3.4.3. Why Matched Representation and Head Controls Were Needed 32
3.4.4. What the Current Progress Does and Does Not Establish . . 32
3.5. Method and Model Design 33
3.5.1. Research Campaign and Recovery Design 33
3.5.2. Nested Selection and Prediction Aggregation 33
3.5.3. Frozen Features and Matched Adaptation 35
3.5.4. Uncertainty, Calibration and Transfer Boundaries 37
3.6. Functional Design 37
3.6.1. Batch and Protein Processing 38
3.6.2. Import and Comparison 38
3.6.3. Annotations and Project Screens 38
3.7. Local Execution View 39

CHAPTER 4: TESTING AND EVALUATION 40
4.1. Testing Objectives 40
4.2. Experimental Evaluation 40
4.2.1. Experimental Setup 40
4.2.2. Evaluation Metrics 42
4.2.3. Results 43
4.2.3.1. Direct Learning on the Saturation Matrix 43
4.2.3.2. Published Degformer Checkpoint and Retrained Architecture 45
4.2.3.3. Interaction Designs 45
4.2.3.4. Learning Curve and Relaxing the Degron Threshold 46
4.2.3.5. Number of Clusters or Coverage of the Distribution 49
4.2.3.6. Sensitivity to the Threshold 50
4.2.3.7. Sensitivity to the Clustering Granularity 52
4.2.3.8. Pre-Training on Tile Labels 54
4.2.3.9. Calibration of the Scores and Ranking Utility 56
4.2.3.10. External GPS Labels: Koren et al. Table S4 58

4.2.3.11. Scope Comparison with MetaDegron 59
4.2.3.12. Follow-up on the Restricted Benchmark 60
4.2.3.13. Full-PSI Development Evaluation 61
4.2.3.14. Campaign Completion and Integrity 63
4.2.3.15. Nine-Checkpoint Frozen-Feature Comparison 64
4.2.3.16. Completed Matched Frozen–LoRA Evaluation . . . 65
4.2.3.17. Residual Diagnostics and Difficult Cases 67
4.2.3.18. Probability Calibration and Locked Transfer 69
4.2.3.19. Additional Controls and Practical Consequences . . 71
4.2.3.20. Assessment of the Research Questions 73
4.2.3.21. Remaining Evaluation 75
4.2.4. Discussion 76
4.2.5. Reproducibility of the Reported Results 78
4.3. Software Testing Plan 78
4.3.1. Functions Under Test 78
4.3.2. Approach 78
4.3.3. Criteria for Test Success or Failure 79
4.3.4. Suspension Criteria and Restart Requirements 79
4.3.5. Test Deliverables 79
4.4. Test Management 79
4.4.1. Test Activities 79
4.4.2. Test Environment 79
4.4.3. Resources and Allocation 80
4.4.4. Risks 80
4.5. Test Scenarios and Test Cases 80
4.5.1. Test Scenarios 80
4.5.2. Expanded Local Acceptance Scenarios 80
4.5.3. Test Cases 81
4.6. Test Evaluation 81

PART 3. CONCLUSION 83
1. Provisional Findings at the Progress Cutoff 83
1.1. Knowledge and Skills 83

1.2. Program and Practical Application Potential 84
2. Limitations and Challenges 84
3. Priorities for the Next Research Phase 85

REFERENCES 86

APPENDIX A: INSTALLATION AND USER GUIDE 89
A.1. Installation Requirements 89
A.1.1. Hardware Requirements 89
A.1.2. Software Requirements 89
A.2. Local System Execution 89
A.2.1. Existing Baseline Commands 89
A.2.2. Target Local Workflow 90
A.3. User Guide 90
A.4. Offline Research Campaign Workflow 90

APPENDIX B: SUPPLEMENTARY MATERIALS 92
B.1. Source Code and Data Availability 92
B.2. Additional Tables and Figures 92
B.3. Seed Stability and Inner Selection 96
B.4. Execution Cost and Output Inventory 97

LIST OF FIGURES

Figure 2.1. Original conceptual schematic of a canonical UPS route, informed by [1], [2]. It is not an observed CT553H mechanism; individual signals can require additional conditions, and not all ubiquitination leads to this route. 18
Figure 2.2. Original conceptual diagram of mutation-effect prediction and label construction. No hypothetical PSI values are presented as observations. Measured WT PSI belongs to the label route. 20

Figure 3.1. Planned components of the single local application; arrows denote data interactions. 27
Figure 3.2. Campaign lineage and evidence roles at completion on 6 November 2026. Inheritance preserves compatible work; the combined review does not create independent datasets. 34
Figure 3.3. Group-aware selection and evaluation. The three seed predictions are averaged per cell before computing ensemble metrics. The separate transfer set T evaluates the fixed W5-D recipe. 35

Figure 4.1. Macro AUROC against the mean number of training clusters (nested cluster subsets of 25, 50, 75 and 100% of the outer-training data; the dashed segment is the relaxed-threshold training set). . . 47
Figure 4.2. Gain in macro AUROC over the benchmark training set for each degron threshold, with 95% cluster-bootstrap intervals (horizontal offsets only separate the two models). 51
Figure 4.3. Frozen pLM ridge results under full-range training. Points joined on the same row compare explicit context for one checkpoint; the connectors are not confidence intervals. 65
Figure 4.4. Matched adaptation evidence. (a) Ensemble MAE and individual seed results; (b) paired MAE differences with multiplicity-adjusted group-bootstrap intervals. The seeds share the outer folds and are not independent cohorts. 66

Figure 4.5. Matched per-peptide OOF errors for the three-seed ensembles on W. Each point is one peptide; points below the dashed equality line favour LoRA. Both panels use common scales. The spread is observed heterogeneity, not a confidence interval. 68
Figure 4.6. Probability and transfer limitations. (a) Development OOF positive-event reliability, with the diagonal indicating agreement; (b) locked W5-D transfer MAE by WT PSI. T uses a different population and does not evaluate LoRA. 70

LIST OF TABLES

Table 1.1. Predict the effect matrix 8
Table 1.2. Rank substitutions 9
Table 1.3. Export results with provenance 9
Table 1.4. Select a protein and tiles 10
Table 1.5. Compare with measured data 10
Table 1.6. View ClinVar and reference annotations 11
Table 1.7. View model and data provenance 12
Table 1.8. Analyse peptide batches or a whole protein 13
Table 1.9. Import experimental observations 13
Table 1.10. Manage projects and analysis history 14

Table 3.1. Data roles in research and the first local release 28
Table 3.2. Key workspace fields and invariants 29
Table 3.3. Research progression: the question resolved and the decision it motivated 30

Table 4.1. Fate of the raw saturation peptides under the label filters 41
Table 4.2. Macro AUROC on the 91 peptides of the saturation benchmark. The last column keeps only the cells whose exact sequence is not in the training data of the published Degformer. 44
Table 4.3. Paired AUROC differences between models 44
Table 4.4. Per-seed AUROC of the three main models 44
Table 4.5. Interaction designs against ridge M3. “Criterion met” applies the pre-registered rule above; for the sigmoid gate and the one-seed Degformer architecture the rule is applied descriptively. 46
Table 4.6. Learning curve (P1) and relaxed degron threshold 4.0 (P0). Ranges are over 5 folds and 3 seeds. 47
Table 4.7. Pre-registered verdicts of P1 and P0 48
Table 4.8. Cells of the benchmark peptides and of the 85 peptides added by relaxing the threshold 49
Table 4.9. Gain over the benchmark training set when a fraction of the new clusters is added 49

Table 4.10. Pre-registered verdicts on the new clusters. The reference marginal gain of old-region clusters is 0.0038. 50
Table 4.11. Added data and gains for each degron threshold (cov80, positive cut ΔPSI ≥ 1) 51
Table 4.12. Robustness of the gain at threshold 4.0 (ridge M3) 52
Table 4.13. Gain of the relaxed threshold 4.0 (ridge M3) under different protein partitions. “Groups” are the groups of the 91 benchmark peptides and of all 176 peptides; “Shared” is the number of added peptides that fall in a group of a benchmark peptide; “Excl.” is the mean percentage of the added cells that are removed from training because their group contains a test peptide. 53
Table 4.14. Macro AUROC with and without pre-training on tile labels . . . 55
Table 4.15. Pre-registered comparisons for pre-training. The main configuration is the relaxed threshold 4.0; the threshold 3.0 is reported with the same criteria and was not used to choose the configuration. . . 55
Table 4.16. Probability quality on the outer-test cells (observed fraction of positive cells: 0.131). ECE: expected calibration error over ten equal-mass bins; $\hat{p}$: predicted probability. 56
Table 4.17. Pre-registered comparisons of the Brier score 57
Table 4.18. Ranking utility: the substitutions of each peptide (532 per 28-residue peptide) are ordered by the raw score. A random ranking has enrichment 1. 57
Table 4.19. Gate fixed in advance for merging the labels of Koren et al. (Table S4) into training 58
Table 4.20. Audit of the MetaDegron data and overlap with the data of this thesis 60
Table 4.21. Selected full-PSI development results. MAE is lower-is-better; positive AUROC is higher-is-better. All rows use the same evaluation population and three-seed prediction ensemble. 62
Table 4.22. Paired full-PSI MAE differences; negative values favour the first method. The two ridge range comparisons use 97.5% intervals adjusted for two tests; the remaining intervals are descriptive 95% intervals. All use 5,000 protein-group bootstrap resamples. 63

Table 4.23. Local frozen-feature ridge MAE for all nine checkpoints. "Only" includes the common auxiliary inputs; W5 adds ordered sequence context. All entries use three-seed OOF ensembles. 64
Table 4.24. Matched local ESM2-35M results. MAE uses all 235 peptides; positive AUROC/AP use 184 eligible peptides and negative AUROC uses 110. Higher ranking metrics are better. 65
Table 4.25. Paired local contrasts: LoRA minus its frozen control. Confidence intervals use 5,000 protein-group resamples; 98.75% intervals adjust a post-hoc family of four comparisons. Negative MAE differences and positive AUROC differences favour LoRA. 66
Table 4.26. LoRA peptide-macro MAE by WT-PSI stratum. The final column is the paired D-minus-B difference with a descriptive 95% protein-group interval; n counts peptides. 67
Table 4.27. OOF MAE conditional on the measured effect class ($\Delta = \Delta$PSI). Each metric averages errors within each eligible peptide, then over peptides in that class. Support counts differ from ranking eligibility, which requires at least three cells of each class. 68
Table 4.28. Three largest absolute cell errors for LoRA-B on W, selected after inspection. Positions are within the measured peptide; measured and predicted values are ΔPSI. These illustrate failures and are not clinical or mechanistic case validations. 69
Table 4.29. Out-of-fold three-class probability evaluation. Brier is the unnormalised sum across three classes; lower values are better. The prior uses inner-validation class frequencies. ECE refers only to the positive event and uses ten equal-width bins. 69
Table 4.30. Locked W5-D transfer by WT PSI. n counts peptides and n_+ counts peptides eligible for positive-event AUROC. The zero predictor provides a regression reference. 70
Table 4.31. Research questions, current evidence and boundaries 73
Table 4.32. Planned first-release local acceptance scenarios; no execution result claimed 81
Table 4.33. Executed test cases: agreement of the prototype with the research runner. The tolerance is 10^{-9}. 82

Table B.1. All saved OOF configurations. s is the number of seeds; MAE and event ranking are peptide-macro. Only rows with $s = 3$ are three-seed ensembles. 93
Table B.2. Single-seed and ensemble peptide-macro MAE for the matched local core experiment. 96
Table B.3. Inner-selected epoch counts over 15 outer fits per local core recipe. 96
Table B.4. Local frozen-family recipes chosen by the saved inner-MSE selector. Frequencies across seed/fold pairs are not independent votes for a model family. 96
Table B.5. Recorded durations of completed local job attempts, counting inherited work once. Earlier attempts of paused/resumed jobs may be absent; these are not GPU-active or full elapsed times. 97
Table B.6. Physical output inventory at review time. Weight caches and code snapshots are supporting assets, not evaluation datasets. 98

GLOSSARY AND ABBREVIATIONS

No.	Term / Abbreviation	Definition / Explanation
1	Degron	Sequence element that marks a protein for selective degradation.
2	E3 ligase	Enzyme that recognises substrate proteins and transfers ubiquitin to them.
3	Residue	One amino acid at a specific position of a protein or peptide.
4	Footprint	Map of positions or substitutions that affect degron activity under a given assay.
5	GPS	Global Protein Stability profiling, a fluorescent-reporter assay of protein stability.
6	PSI	Protein Stability Index, a summary of the reporter signal distribution over sorting bins.
7	ΔPSI	PSI of the mutant minus PSI of the wild type.
8	WT	Wild type, the unmutated reference sequence.
9	PAP	Model that predicts degron activity of a whole peptide.
10	AUROC	Area under the receiver operating characteristic curve.
11	MMseqs2	Software for sequence search and clustering.
12	Cov80 / cov50	Protein clusters built with 80% / 50% alignment coverage.
13	pLM	Protein language model pretrained on amino acid sequences.
14	LoRA	Low-rank adaptation of selected pretrained weight matrices.
15	OOF	Out-of-fold predictions made on groups excluded from model fitting.

No.	Term / Abbreviation	Definition / Explanation
16	MAE / MSE	Mean absolute error / mean squared error; regression loss measures.
17	AP	Average precision, a summary of precision–recall ranking.
18	ECE	Expected calibration error, summarised over probability bins.

PART 1. INTRODUCTION

1. Problem Statement and Scientific Motivation

1.1. From Proteins to Regulated Degradation

Proteins carry out catalysis, transport, signalling and structural functions in cells. Their usefulness depends on having the appropriate amount of functional protein in the appropriate place and at the appropriate time. *Protein homeostasis*, or proteostasis, coordinates protein production, folding, localisation and removal; an imbalance can leave insufficient functional protein or allow damaged or unneeded protein to accumulate [3]. Degradation therefore contributes both to quality control and to regulation. The lifetime of a protein is one component of its abundance, alongside its rate of synthesis; abundance and degradation rate are related quantities with different meanings.

The ubiquitin–proteasome system (UPS) provides one route for selective protein removal. A *degron* is a degradation signal whose activity depends on recognition and molecular context. Such signals can involve N-terminal, C-terminal or internal sequence features; they are not a single universal motif [1], [2]. Changes to an amino acid can alter a recognition motif or the accessibility of a signal. An exposed peptide sequence in a reporter and the same sequence buried in a folded protein can consequently behave differently. Proteome-scale peptide measurements indeed identify potent degrons in regions that are buried in the native structure [4].

1.2. Mutation Measurements and Their Limits

Experimental mutagenesis links sequence changes to measured phenotypes. Scanning mutagenesis tests selected replacements along a sequence, whereas saturation mutagenesis samples a broader set of replacements at each position. Early massively parallel sequence–function experiments showed that a few representative replacements can miss important amino-acid-specific behaviour [5]. GPS profiling measures fluorescent fusion reporters in cells [6]; a later application to internal degrons combined peptide screening, mutagenesis and mechanistic follow-up [7]. These approaches make mutation effects observable, but their output is tied to the assay, reporter and cellular condition used.

The practical need is supported by experimental studies rather than by an assumed shortage of computing. For example, VAMP-seq quantified the abundance of 7,801 single-amino-acid variants of PTEN and TPMT, while also documenting proteins for which the assay was unsuitable [8]. Zhang et al. report that a short-peptide assay can miss conformational motifs, some modification-dependent signals and signals whose recognising factors are unavailable in the assayed cells [7]. Thus, extensive measurements still leave gaps in sequence coverage and biological context. A computational model could help rank additional substitutions for follow-up. Whether that ranking saves experimental work must be tested prospectively. CT553H has measured neither a reduction in wet-lab cost nor an improvement in experimental yield.

1.3. The Specific Prediction Problem

This project predicts the change in the Protein Stability Index (PSI) of a peptide reporter after one amino acid substitution:

$$f(s, i, a) \longrightarrow \widehat{\Delta\text{PSI}}, \qquad \Delta\text{PSI} = \text{PSI}_{\text{mutant}} - \text{PSI}_{\text{WT}}, \tag{0.1}$$

where s is the wild-type (WT) peptide sequence, i is the substituted position and a is the new amino acid. In the Zhang assay, higher PSI means greater reporter stability. A positive effect therefore indicates reporter stabilisation and may be consistent with weakening a degradation signal; it does not identify the responsible E3 ligase or establish the mechanism. The task is continuous mutation-effect regression, with event ranking as a secondary analysis. It is distinct from identifying degron-containing peptides, predicting an absolute activity score, estimating folding free energy or measuring the half-life of a natural full-length protein.

2. Related Work and the Research Question

2.1. What Existing Studies Establish

Experimental maps cover internal degrons [7], cytosolic peptides [4] and transcription-factor peptides [9]; the last source is cited here as the inspected 2025 preprint. PAP predicts peptide abundance with a convolutional model and uses mutant–WT score differences to investigate variant abundance effects, including selected experimental validation [4]. MetaDegron predicts E3-targeted degrons

using sequence and other features [10]. DEGRONOPEDIA and DegronMD provide degron prediction and contextual annotation resources [11], [12]. Degformer is an inspected software implementation of transformer-based peptide prediction, cited as a repository rather than as a verified peer-reviewed article [13]. These works demonstrate that computational degron prediction and analysis of mutation effects already exist.

Consequently, combining a protein language model (pLM) with a CNN is not, by itself, an established novel contribution. The narrower question in CT553H is how well continuous substitution effects can be predicted on a specified reporter endpoint when training-label coverage, sequence representation, head architecture and adaptation are compared under common protein-group-aware evaluation. Biological dependencies can otherwise make prediction estimates optimistic [14]. This is a bounded empirical question on the available data, not a claim that prior work has never studied residue effects or controlled sequence similarity.

2.2. Research Questions Organising This Progress Report

The following questions connect the existing protocols and analyses. They organise the present report; they are not presented as an independent preregistration preceding all historical experiments.

1. **RQ1—Training-label coverage:** Does expanding the WT-PSI range used for training improve prediction on a common evaluation population, and which PSI strata benefit or deteriorate?

2. **RQ2—Representation and head:** Do ordered context and pLM representations improve matched baselines, and does CNN or multi-scale CNN mixing add a reproducible advantage over a pointwise control?

3. **RQ3—Transfer learning:** Under which tested conditions does scanning-mutation or peptide-label pre-training improve saturation mutation-effect prediction?

4. **RQ4—Adaptation:** Does LoRA improve over its matched frozen-encoder control across seeds and PSI strata, and what computational cost accompanies the gain? Full fine-tuning requires its own completed evidence and is not inferred from LoRA.

5. **RQ5—Generalisation and reliability:** How stable are predictions across held-out protein groups, where do large errors occur, and how do regression and probability calibration behave on a held-source population?

The remaining literature search on work in Vietnam is *not yet completed*; no claim of national novelty is made. Independent external and biological validation remain open research needs.

3. Objectives

3.1. General Objective

To evaluate methods for predicting reporter-based amino acid substitution effects in degron peptides, with explicit control of sequence relatedness and uncertainty, and to support traceable exploration through a local software tool.

3.2. Specific Objectives

1. Build an auditable pipeline for source provenance, sequence mapping, technical quality control and endpoint-specific mutation labels.

2. Compare ridge, ordered-context, one-hot and pretrained-representation methods under common evaluation conditions; retain historical reference experiments with their original scope.

3. Test coverage, transfer, head architecture and encoder adaptation using matched controls, rather than presuming that greater model complexity improves prediction.

4. Report regression error, event ranking, PSI-stratum behaviour, seed variation and cluster-level uncertainty, with clear distinctions between development and independent validation.

5. Develop a local React/FastAPI tool for peptide and tiled-protein exploration, source annotation, experimental-data comparison, project history and traceable export; verify implementation separately from scientific model validity.

4. Research Subject and Scope

The research subject is the relation between a single amino acid substitution and a measured change in peptide-reporter stability. A *residue* denotes one amino acid at a sequence position; a mutation-effect *footprint* is the map of effects over positions and substitutions, conditional on the assay and any stated effect threshold.

- The main labels come from the human 28-residue peptide study of Zhang et al. [7]. The current full-PSI saturation development population contains 235 peptides in 221 protein groups. Historical restricted populations are reported separately; the enlarged population is not an independent replication of them.
- Sequence, substitution position and amino-acid identity are prediction inputs. Measured WT PSI is used to construct labels and define training arms or analysis strata; it is not an input to the current sequence-only model. Read count, fold and experimental disagreement are likewise kept outside prediction features.
- An $L \times 20$ display organises predicted substitutions. WT self-substitution is a reference entry, not an additional experimentally observed mutation. Missing observations remain missing.
- The first software release targets peptide batches, 28-residue whole-protein tiling, ClinVar/reference annotation, CSV/TSV comparison, persistent local projects and export. These are partly implemented requirements. Scoring tiles across a protein does not establish full-length protein effects; imported measurements do not automatically become training data.
- The software scope is one local application. Public deployment and accounts are outside the current acceptance scope. E3 identification, clinical pathogenicity and therapeutic benefit are not model outputs. No new wet-lab experiments have been performed in this project.

5. Research Process and Technologies

The work proceeds through literature and data audits, hypothesis-driven comparisons, interpretation of negative as well as positive findings, and prototype development. Python, NumPy, pandas, scikit-learn and PyTorch support modelling;

MMseqs2 supports similarity analysis [15]. Git and LaTeX preserve code and report history. The application design uses React/TypeScript, FastAPI and local PostgreSQL with a durable inference worker; SQLite supports isolated baseline development and tests. The implementation status of this design is reported separately in Chapters 3 and 4.

6. Contributions Achieved and Still Expected

As of 6 November 2026, the inspectable contributions are a source-traceable label/QC pipeline, protein-group-aware development evaluation, controlled comparisons of training coverage and representations, and completed local frozen/LoRA out-of-fold analyses. The report also preserves negative transfer and weighting findings, and a held-source W5 check that exposes regression and calibration limits. A restricted-domain baseline and local web/API implementation provide software evidence within their tested scope.

These are progress contributions in data handling, evaluation and empirical understanding. A universally optimal architecture, an independent external advantage, a completed expanded software release and a measured wet-lab benefit remain unestablished. Final model selection and serving promotion require the additional evidence described in the evaluation and future-work sections.

7. Structure and Status of This Report

This is a research progress report built on the existing thesis draft. Chapter 1 specifies the problem and intended software behaviour; Chapter 2 explains the biology, measurements and computational concepts; Chapter 3 links research decisions to data and experimental methods; Chapter 4 reports results, uncertainty and current evidence limits. The concluding part gives provisional findings and next steps. Appendices retain reproducibility and software instructions. Uncompleted administrative, experimental and implementation items are not treated as final thesis results.

PART 2. CONTENT

CHAPTER 1: PROBLEM DESCRIPTION

1.1. Detailed Problem Description

A 28-residue peptide has $28 \times 19 = 532$ possible single-amino-acid substitutions. The proposed software helps a researcher inspect these candidates, choose a shortlist and retain the evidence needed to revisit that choice. Its intended deliverable is a traceable prioritisation workflow. The motivation and experimental limitations are supported in the introduction; this project has not measured a reduction in laboratory cost or an improvement in prospective experimental yield.

The thesis connects two problems. The research pipeline predicts the effect ΔPSI of a substitution from a reference peptide, position and replacement amino acid, using experimental labels and protein-cluster-aware evaluation. The application uses a frozen model to support analysis, annotation and comparison. The model task remains mutation-level prediction; annotation and project management do not change its scientific endpoint.

First-release scope. The software scope confirmed on 29 October 2026 is one local web application using React with TypeScript and FastAPI. It includes single-peptide analysis, peptide batches, whole-protein tiling, ClinVar and approved reference annotations, import of experimental observations for comparison, CSV/JSON export, and persistent projects and analysis history. The browser, API, local worker and database belong to the same local workspace. Public hosting, remote deployment and public sharing are outside acceptance; no separate public and internal editions are required.

The main actor is the researcher operating this local workspace. Account management, multi-user collaboration, wet-lab/sample management, automatic retraining and clinical diagnosis are outside scope. Imported measurements remain project data and are not added automatically to training or benchmark labels. No new biological experiment is required by this thesis.

1.2. Functions of the System

The following use cases describe the target first release, not completed implementation. Baseline single-tile API/frontend code and a CLI already exist; the added project, job and import flows still require implementation and verification. The requirements below define the target behaviour; Chapter 4 specifies the corresponding acceptance scenarios.

1.2.1. Predict the Effect Matrix

Table 1.1. Predict the effect matrix

Use case name: Predict effect matrix	**ID:** UC-01
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: inspect the effect of every single substitution of a peptide.	
Summary description: Enter a 28-residue WT peptide or select a reference tile; obtain 532 scores in a position-by-amino-acid grid with WT cells masked.	
Relationships: Include: validate input and assess domain. Extend: compare observations, view annotations, save analysis.	
Event handling: 1. Enter/select the peptide. 2. Validate syntax, coordinates and domain. 3. Score with a frozen model. 4. Show domain and warnings before the matrix.	
Alternative / exceptional flows: Invalid input: no scores. Known out-of-domain tile: refuse by default; explicit override records a warning. Unknown, unreliable or borderline domain: score only with a prominent limitation label.	
Expected outcome: A transient preview with raw ΔPSI score, calibrated $P(\Delta\text{PSI} \geq 1)$, model identity and domain evidence; explicit save invokes UC-10.	

1.2.2. Rank Substitutions

Table 1.2. Rank substitutions

Use case name: Rank substitutions	**ID:** UC-02
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: choose a shortlist within an experimental budget.	
Summary description: Sort/filter substitutions within each tile and select candidates.	
Relationships: Include: UC-01 or a completed tile of UC-08.	
Event handling: 1. Open ranking. 2. Sort by effect/probability and filter by position or replacement. 3. Select candidates; inspect the top-10% flag.	
Alternative / exceptional flows: No result: request an analysis first. Empty filter: show an explicit empty state.	
Expected outcome: A tile-specific shortlist retaining coordinates and warnings; no implied cross-protein biological ranking.	

1.2.3. Export Results with Provenance

Table 1.3. Export results with provenance

Use case name: Export results	**ID:** UC-03
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: reuse results in an experimental or computational workflow.	
Summary description: Export a single analysis or complete job as CSV/JSON, including selected annotations/comparisons.	
Relationships: Uses: UC-01, UC-05, UC-06, UC-08 and UC-10.	
Event handling: 1. Choose scope and format. 2. Write scores, per-item outcomes, coordinates, model/data versions and warnings.	

Alternative / exceptional flows: Export failure preserves the result for retry. Failed/skipped job items remain in the manifest.
Expected outcome: Complete traceable files, including rows beyond the current page; no public share link.

1.2.4. Select a Protein and Tiles

Table 1.4. Select a protein and tiles

Use case name: Select protein and tiles	**ID:** UC-04
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: locate a known protein region without manually copying coordinates.	
Summary description: Search the loaded human UniProt release; choose a tile or analyse the complete protein through tiling.	
Relationships: Continues to UC-01 or UC-08.	
Event handling: 1. Search accession/gene. 2. Select the reference sequence. 3. Inspect tiles, domain states and coverage. 4. Choose the analysis scope.	
Alternative / exceptional flows: No accession, sequence shorter than 28, non-standard residues or unverified mapping: state the reason and affected coverage.	
Expected outcome: Selected reference release and explicit 1-based peptide/protein coordinates.	

1.2.5. Compare with Measured Data

Table 1.5. Compare with measured data

Use case name: Compare observations	**ID:** UC-05

Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: inspect where prediction agrees or disagrees with measurements.	
Summary description: Choose reference observations or a committed project dataset; align exact WT, position and replacement.	
Relationships: Uses: UC-01/08 and UC-09.	
Event handling: 1. Select dataset and replicate/aggregation. 2. Check mapping, endpoint and units. 3. Display matched values, exclusions and applicable residuals/metrics.	
Alternative / exceptional flows: Missing/unmatched values are not zero. Different assays remain separate without pooled ΔPSI metrics. Insufficient/constant pairs have explicit undefined-metric states.	
Expected outcome: Comparable prediction/observation views with sample counts and provenance; training observations labelled and imports not automatically called independent validation.	

1.2.6. View ClinVar and Reference Annotations

Table 1.6. View ClinVar and reference annotations

Use case name: View annotations	**ID:** UC-06
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher: relate candidate substitutions to published variant and reference evidence.	
Summary description: Show ClinVar missense records, UniProt mapping and approved GPS evidence in release 1.	
Relationships: Extends: UC-01/08; provenance from UC-07.	

Event handling: 1. Enable a layer. 2. Verify accession/release/WT residue. 3. Show classification, review/conflict state, source version, attribution and disclaimer.
Alternative / exceptional flows: Distinguish no match, unmapped custom input, unavailable source and conflicting mapping. Do not guess canonical mappings.
Expected outcome: Traceable annotations separate from effect predictions; annotation absence does not mean benign.

1.2.7. View Model and Data Provenance

Table 1.7. View model and data provenance

Use case name: View model and sources	**ID:** UC-07
Primary actor: Researcher	**Necessity level:** Important **Classification:** Simple
Stakeholders and interests: Researcher and examiner: understand the predicted event, evidence and limitations.	
Summary description: Read frozen model identity, domain, development metrics and source licences/versions.	
Relationships: Supplies evidence to all result/export views.	
Event handling: 1. Open model/data information. 2. Inspect current metadata or the snapshot associated with a saved run.	
Alternative / exceptional flows: Missing historical artefact: report an integrity problem instead of silently substituting a newer source.	
Expected outcome: Explicit distinction between development evidence, imported comparison and independent validation.	

1.2.8. Analyse Peptide Batches or a Whole Protein

Table 1.8. Analyse peptide batches or a whole protein

Use case name: Batch/protein analysis	**ID:** UC-08
Primary actor: Researcher	**Necessity level:** Important **Classification:** Complex
Stakeholders and interests: Researcher: analyse many candidates while retaining item-level failures and context.	
Summary description: Submit bounded peptide records/FASTA or one protein accession/FASTA to a persistent local job.	
Relationships: Uses UC-01/04/10; exports through UC-03.	
Event handling: 1. Choose a project and input mode. 2. Preview validation, tiling and coverage. 3. Confirm local persistence and submit. 4. Track progress and open per-tile results.	
Alternative / exceptional flows: Item failures/refusals preserve successes. Cancellation/restart retain completed results without duplicates. Limits and uncovered residues are explicit.	
Expected outcome: A durable job with reconciled outcome counts, pinned model/source versions and distinct overlapping tile contexts.	

1.2.9. Import Experimental Observations

Table 1.9. Import experimental observations

Use case name: Import observations	**ID:** UC-09
Primary actor: Researcher	**Necessity level:** Important **Classification:** Complex
Stakeholders and interests: Researcher: compare predictions with locally supplied measurements.	
Summary description: Validate CSV/TSV plus assay, units, source, replicate and reference metadata; commit a dataset revision.	
Relationships: Uses UC-10; supplies UC-05.	

Event handling: 1. Upload into a project. 2. Preview row-level errors, duplicates, missingness and mapping. 3. Correct blocking errors and acknowledge warnings. 4. Explicitly commit.
Alternative / exceptional flows: Malformed/nonfinite/WT-conflicting records block commit; conflicting duplicates never overwrite. Other endpoints remain separately labelled.
Expected outcome: An immutable project dataset with file hash and provenance; no update to training data or weights.

1.2.10. Manage Projects and Analysis History

Table 1.10. Manage projects and analysis history

Use case name: Manage projects/history	**ID:** UC-10
Primary actor: Researcher	**Necessity level:** Important **Classification:** Complex
Stakeholders and interests: Researcher: revisit the exact analysis used for an earlier experimental decision.	
Summary description: Create/rename/reopen/delete local projects; save and reopen immutable runs and datasets.	
Relationships: Supports UC-01/03/05/08/09.	
Event handling: 1. Create/select project. 2. Explicitly save a preview or submit/commit work. 3. Reopen history after restart. 4. Rerun as a new entry or confirm deletion after a dependency summary.	
Alternative / exceptional flows: Missing snapshot or failed cleanup is explicit; deletion cannot remove shared reference/model data or other projects.	
Expected outcome: Saved input, configuration, results and provenance retained locally until deletion; no account or public-sharing requirement.	

1.3. Non-Functional Requirements

The detailed identifiers and cases are in the system SRS. The targets below are proposed until measured on the recorded local computer; no external-host performance or availability result is required.

1.3.1. Performance Requirements

Proposed p95 targets are 300 ms for one tile, 200 ms for listing a 1,000-residue protein's tiles and 1.5 s from click to rendered heatmap. Batch/import resource use is measured separately; bounded jobs, pagination and cancellation keep the interface usable. Proposed initial bounds are 100 peptides or one protein of at most 10,000 residues per job, and 10 MiB/100,000 rows per import; these are configurable design defaults, not measured capacities.

1.3.2. Information Safety Requirements

Serve only approved reference data with source versions and required attribution. ClinVar retains its review/conflict information and diagnostic disclaimer. Imported observations stay in a project-specific store with assay/units/replicates and are not automatically pooled into reference or training data.

1.3.3. Security Requirements

Bind application services to loopback and restrict browser origins. Validate all input and uploaded files; never execute their contents or use supplied names as paths. Unsaved previews are transient. Explicit saves, job submissions and import commits persist locally until deletion; no sequences or observations appear in logs, URLs or third-party telemetry. Project history has no automatic 30-day expiry.

1.3.4. Reliability Requirements

Score arrays are deterministic for the same normalised input and frozen configuration. Numerical agreement with the runner must be below 10^{-9} for JSON and 5×10^{-9} for ten-digit CSV. Saved snapshots survive restart; job recovery does not duplicate completed results. Missing data, partial failures and invalid mappings remain visible.

1.3.5. Maintainability Requirements

Version models, source snapshots and schema migrations. Document local API/worker/frontend startup and workspace recovery. Test the clean local workflow rather than cloud installation.

1.3.6. Usability and Accessibility Requirements

Provide keyboard workflows, accessible tables and text/patterns in addition to colour, with WCAG 2.1 AA as the accessibility target. Desktop use is primary; smaller screens use a scrollable matrix/table fallback.

1.4. Implementation and Design Constraints

1.4.1. Implementation Constraints

One student implements the system within the thesis schedule. React with TypeScript and FastAPI are fixed choices; PostgreSQL is local project/reference storage and SQLite supports isolated tests/baseline development. A local worker runs CPU inference. Training and research notebooks remain separate. Docker may package the same local application; public deployment is not a deliverable.

1.4.2. Design Constraints

Whole-protein analysis retains full 28-residue windows at step 23 and reports uncovered positions. It does not establish the behaviour of the intact protein. Every result carries assay/domain evidence; raw ΔPSI, calibrated event probability and clinical annotation are separate quantities. The scope update does not establish clinical validity, an E3 mechanism or completion of research gates.

CHAPTER 2: THEORETICAL BACKGROUND

2.1. Proteins and Their Regulation

2.1.1. Amino Acids, Peptides and Protein Structure

An amino acid is a molecular building block with a side chain that gives it chemical properties such as charge or hydrophobicity. Amino acids linked by peptide bonds form a sequence, conventionally written from the N-terminus to the C-terminus. A *residue* is an amino acid at a particular position in that sequence. A *peptide* denotes a short chain or protein fragment; the experimental input in the main study is a 28-residue peptide. A full protein can contain hundreds of residues, fold into three-dimensional domains, bind partners and undergo chemical modifications. Its linear sequence and spatial structure therefore describe different aspects of the same molecule.

A *wild-type* (WT) sequence is the specified reference for a comparison; a *mutant* differs from it. A missense DNA variant changes an encoded amino acid. Here, a single amino acid substitution is represented directly as (s, i, a), without modelling nucleotide changes, expression or splicing. Insertions, deletions, truncations and combinations of substitutions have different input requirements and are outside the evaluated regression task.

2.1.2. Stability, Turnover, Degradation and Homeostasis

Proteostasis describes the coordinated maintenance of protein amount, conformation and location [3]. *Degradation* is the breakdown of protein molecules. *Turnover* describes their production and removal over time, and *half-life* is a time required for half of an initial population to disappear under a stated model and condition. *Abundance* is the amount present at an observation time; it depends on synthesis as well as removal. None of these quantities is identical to *thermodynamic folding stability*, which describes the energetic preference of folded relative to unfolded states. A mutation can alter one of these properties without changing all of them in the same direction. In particular, the PSI label below is neither a folding free-energy change nor a half-life expressed in hours.

2.1.3. Selective Degradation and Degrons

In a canonical UPS pathway, E1 activates ubiquitin, E2 carries it and an E3 ligase helps determine substrate recognition and ubiquitin transfer. Appropriate ubiquitination can lead to substrate processing by the proteasome. Ubiquitin also has non-degradative roles, so ubiquitination alone is not proof of degradation. Degrons contribute specificity; N- and C-degrons depend on terminal context, while internal degrons occur within a sequence [1], [2]. The UPS is one part of cellular degradation, alongside pathways such as lysosomal degradation.

Degron activity depends on more than the presence of a short word in an amino acid string. A motif may be masked by folding or a binding partner, require a post-translational modification, or be inactive when its recognising machinery is absent. Molecular recognition, access to an appropriate ubiquitination site and proteasomal processing are distinct requirements. The schematic in Figure 2.1 illustrates a possible route rather than a universal mechanism.




Figure 2.1. Original conceptual schematic of a canonical UPS route, informed by [1], [2]. It is not an observed CT553H mechanism; individual signals can require additional conditions, and not all ubiquitination leads to this route.

2.1.4. How a Substitution Can Change a Degradation Signal

A replacement can remove a favourable recognition residue, create a new recognition sequence, alter local chemistry or change how a region is exposed. These are alternative mechanisms, not mechanistic labels supplied by the current model. Degron annotations and experimentally investigated variant effects support the relevance of both sequence and structural context [4], [11], [12]. Conversely, a mutation can alter catalytic activity, localisation or binding without acting through a

degron. A measured reporter effect therefore warrants a statement about that reporter endpoint, followed by a separately labelled biological interpretation.

2.2. Experimental Measurements and Mutation Labels

2.2.1. GPS Profiling and the Meaning of PSI

Global Protein Stability profiling uses a fluorescent fusion and a reference fluorescent signal to compare reporter abundance in cells [6]. In the Zhang implementation, GFP is fused to a peptide and fluorescence relative to DsRed determines six sorting bins. Sequencing associates constructs with their distribution across these bins [7].

For a construct v, let c_{vb} be its read count in bin b, and let C_b be the total count used to normalise that bin in the reconstruction. The inspected processing code uses

$$n_{vb} = c_{vb}\frac{C_1}{C_b}, \qquad \mathrm{PSI}_v = \frac{\sum_{b=1}^{6} b\, n_{vb}}{\sum_{b=1}^{6} n_{vb}}. \tag{2.1}$$

PSI is defined only with sufficient nonzero read support. Its scale is 1–6: lower values correspond to less stable GFP–peptide reporters and higher values to more stable reporters under this assay. The normalisation population and handling of headers matter when reconstructing it from counts. It is a bin-based index, not a direct degradation-rate measurement. GFP maturation, fusion design, expression and cellular condition are part of the observation process. The model does not remove those factors merely by predicting the index accurately.

2.2.2. Scanning, Saturation and the Unit of Observation

Scanning assays test selected replacements along many peptides. Saturation assays seek many or all alternative amino acids at each position, trading breadth across peptides for depth within each peptide. A complete single-substitution design has $19L$ non-self replacements for length L; actual observation is limited by library construction, read coverage and quality control. Systematic sequence–function mapping therefore records both observed effects and missing variants [5].

In this report a *mutation cell* means one entry $(\text{peptide}, i, a)$ in a mutation matrix; it is not one biological cell. Many mutation cells share a peptide, and several peptides can share a source protein or a homologous protein group. They share ref-

erence measurements and sequence context. Consequently, thousands of mutation cells do not provide thousands of independent protein-level replications. Experimental replicates and random-seed training repeats are also different: the former probe measurement variation, while the latter probe variation in the computational procedure.

2.2.3. Constructing and Interpreting the Effect

For each technically eligible mutation, the label is the mutant PSI minus a compatible WT reference. In the inspected saturation processing, each of the two measurement halves has its own WT baseline, obtained as the median of at least ten measured entries encoding the WT amino acid. The final label averages the two within-half differences. Scanning uses the directly measured WT construct for its condition. An unrelated BAG6-WT condition is not substituted for these references.

$$\Delta\mathrm{PSI}_{p,i,a} = \frac{1}{2} \sum_{r \in \{A,B\}} \left(\mathrm{PSI}_{p,i,a,r} - \mathrm{PSI}_{p,\mathrm{WT},r}\right). \tag{2.2}$$

A positive effect means reporter stabilisation; a negative effect means destabilisation. Interpretation as loss or creation of a degron remains conditional on the experimental system. The WT reference is part of label construction, not an experimentally available feature required at prediction time. Figure 2.2 separates this measurement route from the prediction route.




Figure 2.2. Original conceptual diagram of mutation-effect prediction and label construction. No hypothetical PSI values are presented as observations. Measured WT PSI belongs to the label route.

2.2.4. Quality Control, Noise and PSI-Based Selection

Read counts affect precision; low support, invalid coordinates or residues, missing WT references and unreliable replicate support can prevent a label from be-

ing usable. Disagreement between replicates can reflect technical noise or biological condition differences. Replicate averaging reduces some variation but does not establish that errors are independent or remove systematic biases. Abundance assays illustrate the need to retain replicate-level uncertainty and assay applicability limits [8]. The exact filters and their sample-count effects belong to the data methods, rather than to an assumed universal definition of a degron.

WT-PSI thresholds select different populations. Because both mutant and reference PSI lie between 1 and 6, an effect is bounded by $1 - \mathrm{PSI}_{\mathrm{WT}}$ and $6 - \mathrm{PSI}_{\mathrm{WT}}$. A high-PSI WT has less room for large positive changes; the event prevalence and regression target distribution can therefore differ between strata. Expanding the training range changes which examples the model learns from, not just the number of rows. In v3, WT PSI defines training arms and reporting strata; counts support QC, and disagreement is used only in a designated training-weight experiment. WT PSI, counts, groups and fold identifiers are not sequence-model inputs. Test predictions are not clipped using the measured WT PSI.

2.3. Representations and Learning Methods

2.3.1. Supervised Regression and Simple Controls

Supervised regression learns a mapping from inputs to a continuous target using paired observations. A zero-effect predictor provides a necessary reference when many substitutions have small effects. One-hot encoding represents an amino acid by a vector with one nonzero entry among 20 categories; it does not assume a numerical order among amino acids. Peptide composition records counts or fractions and discards order. Ordered local windows preserve which residue occurs at each relative position, allowing a comparison between context and composition.

Ridge regression adds an L_2 penalty to squared-error fitting [16]:

$$\hat{\beta} = \arg\min_{\beta} \sum_{j} (y_j - x_j^{\mathsf{T}}\beta)^2 + \lambda \|\beta\|_2^2. \tag{2.3}$$

The penalty stabilises estimation with correlated features. Ridge is inexpensive and interpretable at the feature level, but its fitted response is linear in the chosen representation. Interactions require explicit features or a nonlinear model. Feature scaling and the penalty must be chosen without using outer-test observations.

2.3.2. Protein Language Models and Embeddings

A pLM learns sequence regularities from protein corpora. ESM-2 uses a transformer to learn contextual residue representations [17], [18]. An *embedding* is a vector representation, not a directly measured biological property. A residue vector can depend on the rest of the input sequence. The current frozen-feature design combines the change in the substituted-site vector and the change in mean sequence vectors, optionally with ordered context. A trained head maps these features to ΔPSI. Dimensionality reduction limits feature size; its parameters must be fitted on training data within each selection split.

Pretraining can provide useful regularities when endpoint labels are limited, but usefulness must be measured against simple controls. Larger embeddings or checkpoints need not improve this endpoint. The labelled-train/test separation also does not certify that sequences or homologs were absent from the original pLM corpus. Sequence pretraining and supervised endpoint-label leakage require separate audits; neither is dismissed by a claim that the encoder is frozen.

2.3.3. Pointwise, CNN and Multi-Scale CNN Heads

A one-dimensional convolution applies a learned filter along sequence positions. A kernel of width k mixes information across k neighbouring positions; applying the same filter at each position shares parameters. The pointwise $k = 1$ head is a control without additional neighbouring-position mixing at that layer. On contextual pLM embeddings, it can still use context already encoded by the pLM. A CNN with a wider kernel tests additional local mixing; parallel kernels of different widths form a multi-scale CNN (mCNN). These are inductive biases, not proof of a biological motif mechanism.

In v3 the tested heads include $k = 1$, $k = 5$ and parallel $k = 3, 5, 7$ branches, with shared centre and sequence-pair/composition inputs where specified. This tests the added role of mixing while keeping important inputs comparable. It does not make all heads identical in parameter count. Additional capacity can fit noise; early stopping, matched folds and paired uncertainty help assess whether the extra complexity has reproducible predictive value. PAP is a related CNN-based peptide-abundance predictor; a mutant–WT PAP difference is a reference score, not automatically a calibrated PSI effect [4].

2.3.4. Frozen Encoders, Fine-Tuning and LoRA

A frozen encoder retains its pretrained weights while the regression head is learned. Full fine-tuning updates the encoder as well. LoRA instead learns a low-rank update, schematically $W' = W + BA$, while holding the base matrix W fixed [19]. This reduces the number of trainable adaptation parameters; it does not guarantee lower total runtime or greater accuracy for this dataset. The implemented comparison adds LoRA to attention query/value projections and learns a head, using a frozen-encoder control with the same data assignments and base revision. Observing changed adapter parameters establishes that adaptation occurred; completed held-out predictions are still required to establish its performance. LoRA evidence cannot stand in for an uncompleted full-fine-tuning experiment.

2.3.5. Transfer Learning and Endpoint Compatibility

Transfer learning uses information learned on a source task or population for a target task. Scanning mutation labels can train a mutation-effect representation with narrower amino-acid coverage; peptide-abundance pre-training supplies a different endpoint and typically a different head. The source must exclude prohibited overlap with target-test groups before training. Source similarity, assay differences and target-label coverage can make transfer helpful or harmful. Negative transfer is an empirical result to retain, not evidence that an implementation was necessarily defective. Binary motif annotations are not converted into continuous ΔPSI labels.

2.4. Evaluation and Reliability

2.4.1. Data Splitting, Leakage and Generalisation

Leakage occurs when information unavailable in the intended prediction setting influences training or selection, yielding misleading evaluation [14]. Randomly splitting mutation cells can put nearly identical mutants and shared WT sequences on both sides. Protein-group-aware splitting keeps related source proteins together; MMseqs2 supports the sequence comparisons [15]. The historical cov80/cov50 definitions and v3 unions are described separately in the methods. A heuristic similarity threshold reduces specified overlap but does not prove complete biological independence, especially for short shared motifs or remote homology.

Nested evaluation chooses hyperparameters, scalers, PCA and stopping epochs

inside outer-training data, then evaluates on held-out outer groups. An out-of-fold (OOF) prediction is made by a fitted model that excluded the corresponding outer group. Overfitting can still occur through repeated human selection on the same development OOF results. A locked recipe evaluated on an untouched source provides different evidence from selecting a winner on development data; a source previously explored in historical work must be described accordingly.

2.4.2. Losses and Regression Metrics

The inspected regressors use squared-error objectives or inner-validation MSE for selection. Selection loss and reporting metric need not coincide. For the main full-PSI endpoint, peptide-macro MAE is

$$\mathrm{MAE}_{\mathrm{macro}} = \frac{1}{P}\sum_{p=1}^{P}\frac{1}{n_p}\sum_{j=1}^{n_p}|y_{pj} - \hat{y}_{pj}|. \tag{2.4}$$

This gives each eligible peptide equal weight, rather than giving a densely observed peptide more influence solely because it has more mutation cells. RMSE increases the influence of large errors; Spearman correlation measures rank association rather than error magnitude. Their aggregation and eligibility rules must be stated before comparing values.

2.4.3. Event Ranking and Probability Calibration

The v3 positive and negative events are $\Delta\mathrm{PSI} \geq 1$ and $\Delta\mathrm{PSI} \leq -1$, respectively. AUROC measures ranking of event versus non-event scores; average precision and top-fraction precision depend additionally on event prevalence. Peptides without sufficient examples of both classes have undefined event-ranking metrics and remain eligible for regression. The old restricted benchmark uses its own eligibility and macro-AUROC rules.

A regression score is not a probability. Calibration learns event probabilities using permitted validation predictions. The Brier score measures squared probability error, whereas expected calibration error (ECE) summarises discrepancies between predicted and observed frequencies within chosen bins. Bin choice and population composition affect ECE. Improved ranking, Brier score and ECE need not occur together, and development calibration does not guarantee calibration after a source shift.

A calibrator must not see the outer-test outcomes it is later evaluated on.

2.4.4. Uncertainty, Seeds and Fair Comparisons

A paired comparison evaluates both methods on the same eligible observations. Bootstrap intervals approximate variation under resampling [20]; here the resampling unit is the protein group, preserving the dependence of its mutation cells. The interval addresses uncertainty under this sampling scheme, not unmeasured assay biases or all future cell types. Seeds measure computational variation and are reported alongside ensemble predictions. The metric of an averaged prediction is not generally equal to the average of seed-specific metrics.

For a difference defined as MAE(method)–MAE(control), a negative value favours the method. A confidence interval crossing zero leaves the direction unresolved at the stated level; it does not prove equivalence. Multiplicity adjustment, when specified, applies to the declared comparison family, not every exploratory contrast. Practical relevance also requires effect size, stratum behaviour and cost. Comparisons across different endpoints, QC versions, folds or runtime campaigns are contextual unless those differences have been reconciled explicitly.

2.5. Research and Software Toolchains

Python, NumPy, pandas, scikit-learn and PyTorch implement the research pipeline. Pinned revisions, configuration, manifests and prediction artifacts support reconstruction. React/TypeScript, FastAPI, local persistence and an inference worker implement the application design. Software test success checks a stated behaviour; it does not supply biological validation, independent model generalisation or proof of wet-lab utility.

CHAPTER 3: SOLUTION DESIGN AND IMPLEMENTATION

This chapter describes the target design confirmed on 29 October 2026. Baseline API/frontend code exists, but the workspace, durable jobs and import extensions below are planned. A design element is not a completed implementation or a passing test. The design follows the requirements in Chapter 1; existing implementation evidence is distinguished from planned work. As of 6 November 2026, the newer workspace UI is a separate interactive review prototype using synthetic fixtures and transient tab state. It has not been integrated with the baseline API or implemented durable projects/jobs. The current research findings are summarised in Section 4.2.3.13; they have not changed the serving model.

3.1. System Overview

3.1.1. Product Context

The research pipeline prepares data, trains and evaluates models offline. One local web application loads a frozen model and reference snapshots; it supports researchers choosing substitutions for follow-up experiments. Runtime input and project observations stay on the local computer.

3.1.2. Functional Overview

The first release covers UC-01 to UC-10 of Chapter 1: prediction, ranking, export, protein/tile lookup, experimental comparison, ClinVar/reference annotations, evidence pages, peptide/protein jobs, experimental import and persistent project history. There is one product configuration with local operation; public hosting and public sharing are excluded.

3.2. System Architecture

3.2.1. Architectural Components

Figure 3.1 shows the target components. All application listeners use loopback; reference downloads and training are preparation activities outside the runtime workflow.

The React client owns input, matrix/ranking interaction and project/job/import screens. FastAPI validates input, applies domain rules, serves reference annotations




Figure 3.1. Planned components of the single local application; arrows denote data interactions.

and stores snapshots. A local worker uses the same inference package for jobs; PostgreSQL stores job state and project-owned records. Generated local file paths hold committed imports and versioned artefacts. Reference ETL never writes user observations into research data.

3.2.2. Interaction Between Components

A single-tile preview is validated and scored without persistence. Explicit Save creates an immutable analysis in a selected project. Batch submission pins model, calibrator, gate and source versions, returns a job ID, then the worker claims items transactionally. The client polls progress and opens per-tile results. Expired worker leases are recovered after restart; completed items are not duplicated. Cancellation and project deletion prevent late writes.

An import first produces a validation preview. Only a valid, explicitly committed dataset becomes available for comparison. A comparison selects a saved analysis and dataset revision, checks assay and mutation alignment, and stores its own result/provenance. Reading history uses saved snapshots, not a new inference call or the latest ClinVar release.

3.2.3. Design Rationale

React supports the interactive matrix, filtered tables and long-running-task states. FastAPI keeps the model computation in Python and provides an explicit REST contract. A local worker separates job execution from interactive requests without

introducing a cloud service. Persistent projects require a database and snapshot lifecycle beyond the baseline transient preview. The trade-offs are local resource limits, file/database consistency and additional recovery/deletion tests. SQLite remains useful for isolated tests, while local PostgreSQL integration is an acceptance task. The OpenAPI contract marks new operations as planned; generating a schema does not implement them.

3.3. Data Design

3.3.1. Data Sources and Preprocessing

Reference snapshots have version/date, checksum and terms of use. Research-only sources and project-imported observations are kept distinct from served reference data (Table 3.1).

Table 3.1. Data roles in research and the first local release

Source	Role and boundary
Zhang Mendeley v2 [21]	Mutation labels and reference observations; training use labelled.
GEO GSE240610 [22]	GPS screen context; preserve estimator and source provenance.
UniProtKB/Swiss-Prot	Pinned human reference sequences, accessions and coordinate/WT checks.
ClinVar	First-release missense annotation; source/review/conflict state, attribution and diagnostic disclaimer.
Project CSV/TSV	User observations for assay-aware comparison only; preserve source, units and replicates.
Voutsinos/PAP [4]	Research baselines and transfer-learning studies; not a replacement for mutation labels.
Larsen [9] and other restricted sources	Research-only consideration subject to rights; not automatically imported into the service.

3.3.2. Data Model

Reference entities are source, protein, tile, measured cell, ClinVar variant and model version. The planned workspace adds project, analysis job, job item, analysis run/cell, imported dataset/observation and comparison. Legacy expiring share tables are not reused as persistent project history.

3.3.3. Data Dictionary

Table 3.2. Key workspace fields and invariants

Entity	Required information
Project	UUID, name, description, creation/update time; one local workspace.
Job and item	Mode/input IDs, pinned configuration, states/counts, item errors, coverage and worker lease; unique completed result per item.
Analysis run/cell	Input and coordinate context; model/gate hashes; scores, rank, warnings, annotation/source snapshot and parent rerun ID.
Dataset/observation	File hash/revision, assay/endpoint/units/source, WT sequence, position, WT/replacement, value/missing reason and replicate.
Comparison	Run/dataset IDs, explicit replicate/aggregation, compatibility decision, alignment counts and metric/result snapshot.

3.3.4. Relationships Between Entities

A project owns jobs, runs and datasets. A job contains input items; each successful tile item produces one immutable run with 532 cells. Dataset observations retain unique mutation/replicate keys. A comparison joins one run and one committed dataset from the same project. Source/model artefacts are versioned independently; changing active reference data must not change an old analysis. Deletion shows dependencies, stops related work and removes owned files/results with retryable cleanup; shared references and weights remain intact. Committed history has no automatic 30-day expiry.

3.4. Research Progress and Data Evolution

The investigation has changed its experimental focus as evidence accumulated. Coverage and stratification address RQ1; representation and head controls address RQ2; source transfer addresses RQ3; matched adaptation addresses RQ4; and grouped evaluation, errors, calibration and transfer boundaries address RQ5. This section reconstructs that reasoning from recorded protocols and results; it does not retrospectively assign preregistered status to exploratory questions. Historical development experiments and the current full-PSI campaign remain distinct. The main milestones are summarised in Table 3.3; Chapter 4 reports their numerical results.

3.4.1. From Peptide Activity to Direct Mutation Labels

The initial data audits established why peptide-level degron scores cannot substitute for mutation effects. A peptide may receive one activity score, whereas

Table 3.3. Research progression: the question resolved and the decision it motivated

Stage	Question and recorded finding	Next decision and boundary
Data audit, 12–15 Oct.	Reconstructed bin-based PSI and distinguished scanning from saturation mutation labels.	Use direct mutation ΔPSI labels and assay-specific WT references; peptide activity is a separate endpoint.
G2 and extensions, 18–19 Oct.	Ridge was a strong saturation baseline; additional nonlinear candidates did not establish an architectural advantage.	Audit training exposure and label availability before adding capacity. The overlapping public checkpoint is unsuitable as clean generalisation evidence.
P0/P1, 22 Oct.	Adding WT-PSI $(3, 4]$ training peptides improved prediction on the original low-PSI test population.	Expand training coverage, while testing whether improvement persists outside the original population. Label scarcity remains an explanation to test.
P3 and scan transfer, 22–23 Oct.	Transfer depended on the source target and learner; peptide-score pretraining did not reliably improve mutation prediction.	Keep source/replicate and training recipe explicit; do not pool endpoints merely because both concern degradation.
R0–R3, 22 Oct.	Reproduction and inference parity passed; cleaned Degformer and frozen ESM–Ridge did not establish superiority; the domain gate required assay-scale mapping.	Preserve a reproducible baseline, add matched head controls, and distinguish domain confidence from effect accuracy.
R6, 23 Oct.	Ordered W5 context improved Ridge; the primary ESM–mCNN contrast was inconclusive. A secondary one-hot mCNN scanning-pretraining contrast was positive.	Separate primary and secondary claims; test representation, head and training range on common full-range folds.
Full-PSI v3, 31 Oct.–6 Nov.	Wide evaluation, pointwise/CNN controls, nine frozen pLM recipes and matched frozen–LoRA evaluation were completed where inputs were available.	Interpret development evidence by stratum and metric; final serving export, external validation and structure inputs remain unfinished.

saturation mutagenesis measures many substitutions at each position. Scanning provides more peptide contexts but only a restricted set of replacement amino acids. Its substitutions are drawn from R, A and S, rather than all 19 alternatives. Consequently, sequence context can be informative in scanning cross-validation while transfer to the saturation substitution distribution remains difficult. This motivated direct training on saturation labels and separate reporting of the two experimental populations.

The WT reference is part of the endpoint definition. Saturation labels subtract the median of valid synonymous observations in each half before averaging the two half-specific effects. Scanning subtracts the measured WT construct of the same replicate. The separate BAG6-WT condition cannot replace either reference. Nor is the approximately 0.9-PSI offset observed between the peptidome screen and intrinsic WT measurements an offset between scanning and saturation mutation labels. These distinctions prevent a change of measurement scale from being mistaken for biological transfer failure.

3.4.2. Why the Study Expanded Training Coverage

G2 evaluated 91 peptides and 47,847 cells at WT PSI at most 3. The P0 experiment retained those outer-test cells and added up to 85 peptides, or 44,490 cells, from WT PSI in $(3, 4]$ to permitted training groups. Ridge macro AUROC increased from 0.8082 to 0.8208, with a paired group-bootstrap 95% interval for the difference of $[0.0061, 0.0190]$. This supports that particular expansion on the original test population. It does not establish performance on the added peptides as test examples.

The associated P1 learning-curve hypothesis was model-dependent. For Ridge, the 100% versus 50% contrast had a 95% interval containing zero and the curve was not monotone; the corresponding neural learner did support a label-quantity effect. Therefore, the earlier interpretation that label scarcity alone explained unsuccessful architectures is too strong. Training distribution, noise, regularisation and representation remain plausible contributors. The full-PSI design subsequently changed both validation and evaluation coverage to measure performance across the full range.

The wide dataset retains 235 technically valid saturation peptides and 122,412 cells. Its 221 groups result from the full-proteome mapping and additional homol-

ogy/sequence unions. Historical counts of 227 legacy groups or 222 full-proteome groups preceded this union procedure; they do not describe extra mutation observations. Likewise, the full-range folds are not the original G2 folds, so an AUROC change between the two populations cannot isolate architectural improvement.

3.4.3. Why Matched Representation and Head Controls Were Needed

R2 added PCA-reduced frozen ESM2-650M features to Ridge and obtained a small, inconclusive gain. R6 then compared sequence representations and convolutional heads. Its primary ESM2-35M mCNN–Ridge difference was $+0.0097$, with a 95% interval of $[-0.0025, 0.0233]$; it did not meet its confirmation criterion. Ordered W5 context did improve Ridge within its adjusted comparison family. Separately, scanning pretraining improved the one-hot mCNN over its scratch control by 0.0147 AUROC, with the adjusted interval $[0.0027, 0.0276]$. That secondary transfer result neither rescues the primary contrast nor establishes an advantage over W5 Ridge.

The ESM mCNN–single-window CNN difference was only 0.0041, with a 95% interval of $[-0.0005, 0.0087]$. The evidence thus motivated a matched pointwise head and broader evaluation rather than a claim that multiple convolutional scales were necessary. Historical Ridge and neural fits also used different final refit policies; the current campaign explicitly refits outer models after inner selection. Recipe, runtime and final fitting policy must accompany any comparison.

3.4.4. What the Current Progress Does and Does Not Establish

The current campaign addresses the new full-range questions using fixed grouped folds, inner selection and explicit training arms. It provides development evidence on frozen representations, convolutional heads and a matched LoRA adaptation. It contains no controlled full-fine-tuning arm. The completed transfer evaluation concerns W5-D alone on a restricted scanning population from the same source laboratory. Calibration, predictive ranking, regression accuracy and biological utility remain different outcomes. Neither completion of the runnable graph nor favourable OOF metrics constitutes final model selection, independent external validation, or a demonstrated reduction in wet-laboratory cost.

3.5. Method and Model Design

Input remains the reference peptide, position and replacement; target is ΔPSI. The existing service baseline is the frozen ridge/Platt model from Section 4.2.3.9. This scope update does not choose a replacement model. Full-PSI CNN, pLM-family and LoRA development evaluation is complete; a compatible final serving refit, calibration and export remain required. Raw effect and calibrated $P(\Delta\text{PSI} \geq 1)$ remain separate fields.

3.5.1. Research Campaign and Recovery Design

The execution unit is a dependency-tracked job with pinned code, data, model revision, protocol and runtime identity. The Kaggle run supplies the reference experiments; the Windows successor expands the pLM family and completes a matched frozen–LoRA comparison. These runs use the same development population, but different software and GPU environments. They are retained as separate estimates.

Figure 3.2 shows how interrupted work is recovered. Completed outputs can be inherited only after compatibility and checksum checks. The tokenizer-repair successor reuses 456 completed jobs from the earlier local campaign; it does not count those jobs twice. Paused training uses committed checkpoints, including optimiser and random-state information. A timer-failure run that produced no scientific OOF predictions is superseded. A final report job denotes completion of the runnable graph; missing reviewed external and structure inputs remain explicit pending states.

3.5.2. Nested Selection and Prediction Aggregation

The evaluation unit is a mutation cell, while splitting and uncertainty respect protein groups. The full-PSI development set W contains 235 peptides, 221 groups and 122,412 cells. Five fixed outer folds are shared across recipes. Seeds 17, 29 and 43 vary the inner group split and stochastic fitting; they do not provide three independent outer test partitions. Arm B permits training examples with WT PSI at most 4; arm D permits the full training range. Inner validation and outer test remain full-range in both arms. The earlier Kaggle arm E balances WT-PSI strata within training.

All preprocessing is fitted on permitted training examples. Hyperparameters, family choices and neural epochs are selected by inner validation MSE. A fresh model




Figure 3.2. Campaign lineage and evidence roles at completion on 6 November 2026. Inheritance preserves compatible work; the combined review does not create independent datasets.

is then fitted on permitted outer training data before predicting the untouched outer test. The nested family selector chooses among 36 frozen-feature recipes separately for each seed/fold; it does not choose the best outer OOF score. Figure 3.3 distinguishes this selection from the locked transfer evaluation.




Figure 3.3. Group-aware selection and evaluation. The three seed predictions are averaged per cell before computing ensemble metrics. The separate transfer set T evaluates the fixed W5-D recipe.

3.5.3. Frozen Features and Matched Adaptation

The family experiment includes ESM2 at 8M, 35M, 150M and 650M parameters, ESM1b-650M, one ESM1v-650M checkpoint, ESM-C-300M, the ProtT5 en-

coder and Ankh-base. For each substitution, the mutant-minus-WT residue embedding at the mutation site is concatenated with its sequence mean. Frozen features are reduced to 64 principal components using training-only transforms and combined with either the common auxiliary features alone or additional ordered W5 context. Ridge regularisation is chosen from $\{0.1, 1, 10, 100, 1000\}$ by inner MSE. The design has $9 \times 2 \times 2 \times 3 \times 5 = 540$ outer fits.

The common sequence-derived inputs contain separate 20-dimensional one-hot blocks for WT and replacement residue and a 20-dimensional peptide-composition vector. Thus a recipe labelled "pLM-only" still includes these 60 inputs. Measured WT PSI is used for labels, training eligibility, balancing and diagnostic strata; it is not supplied as a predictor feature. Read counts, group IDs and fold IDs are likewise excluded from the effect model's feature matrix.

The second experiment holds ESM2-35M, the group folds, auxiliary inputs, head initialisation and training schedule common between frozen and LoRA branches. Both use a 64-unit ReLU head with dropout 0.2. LoRA [19] adds rank-8 adapters with scale $16/8$ to attention query and value projections while retaining frozen pretrained weights. The frozen branch trains the head only. This mutation regressor uses a pointwise/pooled embedding MLP, not a CNN or mCNN. The code also supports full fine-tuning, but the completed campaign schedules only frozen and LoRA branches; no full-fine-tuning performance claim follows from that implementation option. Both branches use AdamW, learning rate 10^{-4}, weight decay 0.01, batch size 8, FP32 computation and gradient clipping at 1. Inner selection permits at most 20 epochs with patience 4, followed by a fresh outer refit for the selected epoch count. The backbone remains in evaluation mode in both branches so that its dropout policy is matched. There are 30 outer fits per branch.

The local environment is Python 3.11.9, PyTorch 2.13.0 with CUDA 13.0, Transformers 5.17.0 and an RTX 5060 Laptop GPU with approximately 8 GiB memory. Model/tokenizer weights are cached and revision-pinned. ProtT5 initially reached a misleading tokenizer fallback requesting `tiktoken`; installing the missing Protobuf dependency restored its intended tokenizer. Ankh uses the original fast tokenizer with residue-level input and an FP32 encoder because FP16 hidden states were non-finite. ProtT5 uses FP16 encoding; stored family features use FP16. These execution choices are recorded parts of the recipes, so this is not a controlled

comparison of pretraining alone.

3.5.4. Uncertainty, Calibration and Transfer Boundaries

MAE is first averaged within a peptide and then across peptides. Positive-event metrics use $\Delta\text{PSI} \geq 1$; negative-event metrics use $\Delta\text{PSI} \leq -1$ and require at least three cells from each class within a peptide. Paired differences are bootstrapped over protein groups with 5,000 resamples. Four matched local contrasts (two arms, MAE and positive AUROC) are additionally reported with conservative post-hoc Bonferroni 98.75% intervals. This adjustment does not turn the development expansion into a preregistered independent confirmation.

Three-class probabilities represent negative, neutral and positive effects. Each outer-fold calibrator is fitted using predictions on its inner validation groups, disjoint from the outer test; probabilities are averaged across seeds. The multiclass Brier score is $\sum_{c=1}^{3}(p_c - y_c)^2$ per cell, without division by the number of classes. Both cell-micro and peptide-macro averages are reported. A null predictor uses inner-validation class frequencies; positive-event ECE uses ten equal-width probability bins. Calibration is evaluated out of fold, separately from final serving-model construction.

For transfer, W5-D is fixed before inspecting T, refitted on all permitted W data, and applied to the locked scanning population with no recorded protein-group overlap with W or scanning development data. T has a different substitution/label distribution and comes from a previously explored source in the same laboratory. It does not provide a new independent external cohort. No LoRA model is selected or evaluated using T in the completed campaign.

Domain integration. The effect model's intrinsic-WT training threshold must not be applied directly to the GPS screen estimator. The R3 research provides a two-tier gate with an intermediate borderline state; integrating its frozen rules and provenance into the baseline remains pending. Every tile has domain evidence; known out-of-domain scoring requires an explicit warned override. Whole-protein mode is a collection of peptide-context predictions, not a validated intact-protein model.

3.6. Functional Design

3.6.1. Batch and Protein Processing

Peptide mode accepts a bounded list or multi-record FASTA of 28-residue inputs. Protein mode accepts one reference accession or one FASTA record. Tile n starts at $(n-1) \cdot 23 + 1$ and ends 27 residues later; only full windows are generated. Report uncovered intervals, invalid windows and domain refusals. Overlapping protein substitutions retain their tile contexts without averaging. Job states are pending, running, completed, partial, failed or cancelled; per-item states and counts explain partial results. Browser tables are paginated; exports include every outcome.

3.6.2. Import and Comparison

CSV/TSV rows contain peptide ID, WT sequence, 1-based position, WT/replacement, observed value and replicate. Optional accession/release/start coordinates are checked together. Metadata identify assay, endpoint, units, source and reference. Duplicate/conflicting mutation-replicate keys, nonfinite values and WT mismatches block commit. Empty observations retain a missing reason.

Comparison requires exact mutation alignment and explicit replicate selection or aggregation. Comparable GPS ΔPSI supports residuals (prediction minus observation), MAE and Spearman with sample counts; insufficient/constant pairs have no reported correlation. Different assay endpoints remain separate without pooled metrics. Imported observations do not automatically constitute independent validation or become training labels.

3.6.3. Annotations and Project Screens

The first release shows ClinVar alongside approved UniProt/GPS context. Show classification, review/conflict state, source release and WT-coordinate agreement; distinguish no match from unavailable/ambiguous mapping. Attribution and diagnostic disclaimer travel with saved/exported annotations. Custom unmapped sequences have explicit annotation-unavailable states. The project workspace exposes history, jobs and datasets; users can reopen snapshots, create reruns as new entries and confirm deletions. New screens and API routes remain pending implementation.

3.7. Local Execution View

One computer hosts the browser, API, worker, PostgreSQL and workspace files. Application listeners bind to loopback; the frontend origin is explicitly allowed. Docker may package the same components, but no remote host, public URL, TLS deployment or separate product edition is required. Appendix A separates baseline startup from the pending first-release workflow.

CHAPTER 4: TESTING AND EVALUATION

4.1. Testing Objectives

To assess reproducibility and detectable overlap between training and test clusters, and to plan verification that the prototype validates input, keeps coordinates and score direction correct, and exports data consistently with the research runner.

This chapter has two parts. Section 4.2 reports the experimental evaluation of the research pipeline; these experiments have been run. Sections 4.3 to 4.6 follow the test-plan outline of the Faculty for the prototype tool. The numerical results retained here come from the recorded CLI verification artefacts. Baseline web/API code and historical local checks also exist, but the first-release extensions confirmed on 29 October 2026 require implementation and new local acceptance evidence; no passing result for those additions is claimed here.

4.2. Experimental Evaluation

This section preserves the initial restricted-PSI experiments and then reports the important follow-up findings and completed campaigns available on 6 November 2026 (Section 4.2.3.13). The original 91-peptide test and the full-PSI evaluation have different populations and primary metrics; their scores must not be read as a single improvement curve. All remain development evidence.

4.2.1. Experimental Setup

Data and labels. The labels come from the saturation-mutagenesis experiment of Zhang et al. [7], [21]. For each peptide, the effect of a substitution is $\Delta\text{PSI} = \text{PSI}_{\text{mutant}} - \text{PSI}_{\text{WT}}$ (Chapter 2). The data set contains two replicate halves of each peptide. The PSI_{WT} reference of a half is the median PSI of the synonymous cells of that half, and at least ten such cells are required. The cell label is the mean ΔPSI of the two halves; a cell is *positive* when $\Delta\text{PSI} \geq 1$. In the initial restricted benchmark, a peptide is accepted only if $\text{PSI}_{\text{WT}} \leq 3.0$. Table 4.1 shows how the 248 raw saturation peptides reduce to the 91 peptides of the benchmark. The single largest cause of loss is the degron threshold, which removes 144 peptides; the technical causes together remove only $10 + 2 + 1 = 13$ peptides. The benchmark set contains 91 peptides in 89 protein clusters and 47 847 cells. The measurement ceiling of this set, computed

as the agreement between its two experimental halves, is 0.9519 AUROC. This is an empirical replicate-agreement reference under this label construction, rather than a mathematical upper bound on prediction.

Table 4.1. Fate of the raw saturation peptides under the label filters

Outcome of the label filters	Peptides
Retained: the benchmark set	91
Removed only by the degron threshold ($PSI_{WT} > 3.0$)	144
Fewer than 10 synonymous cells for the WT reference in a half	10
Sequence mismatch between scan file and UniProt	2
No sequence could be derived	1
Raw saturation peptides	*248*

Splits. Proteins are clustered with MMseqs2 [15] at 30% identity and 80% coverage (cov80). The outer evaluation uses five folds with whole clusters assigned to folds. Inside each outer training set, 20% of the clusters form a validation set for choosing hyper-parameters, so no outer-test label is ever used for tuning. Training is repeated with seeds 17, 29 and 43. The three seeds share the same outer partition and differ only in the inner validation split and in network initialisation, so they are not three independent partitions. The reported score of a model is the AUROC of the average of the three seeds' out-of-fold scores; per-seed results are also kept.

Models.

- **Ridge M3.** Ridge regression [16] on 180 features: one-hot reference and substituted amino acid (40), peptide composition (20) and the ordered ± 3 residue context (120). The penalty is chosen from $\{1, 10, 100, 1000\}$ on the inner validation set.
- **ΔPAP.** The difference of the PAP degron score [4] between mutant and wild type, with the published network frozen (variant `cnn2w1`). It is the reference baseline and uses no training labels.
- **Gated networks.** The same 180 features, with the substitution (pair) and the composition-plus-context inputs projected separately to 32 dimensions; a sig-

moid of the pair projection multiplies the context representation, followed by an MLP ($64 \to 32 \to 1$). Variants add the frozen ΔPAP as a residual or remove the gate. Training uses AdamW (learning rate 2×10^{-3}, weight decay 0.01, batch of about 1,024, at most 60 epochs, patience 8).

- **Degformer.** The published checkpoint (epoch 50) of the transformer [13], scored as $\mathrm{pred}(\mathrm{mutant}) - \mathrm{pred}(\mathrm{WT})$; and the same architecture (d_model 128, 4 layers, 8 heads) retrained from scratch on the training clusters of each fold.

Further interaction designs (FiLM, rank-8 bilinear, ridge with cross-product features) were added as *pre-registered candidates* in Section 4.2.3.3.

Recorded protocols. The acceptance criteria of the overlap check, the interaction designs, the retrained Degformer architecture, the learning-curve and threshold experiments, the re-clustering, the pre-training experiment, the calibration and the audit of the external labels were written to protocol files before execution according to the retained experiment records. These are repository protocol records, not an external registration or independent verification of all planning timestamps. Where a result below is described as met or not met, it refers to its recorded criteria. Observations made after seeing the numbers are labelled as descriptive. The first direct-learning experiment (Table 4.2) has a protocol file but is treated as exploratory.

Environment. The initial experiments described below ran on CPU with Python 3.12.3, NumPy 2.5.3 and PyTorch 2.14.0 (CPU build); each result file records the SHA-256 of its input and of its runner. Large caches and checkpoints are generated again by the runners. The subsequent notebook runs used Kaggle GPUs, and the local expansion uses a separate Windows CUDA runtime (Section 4.2.3.13); checkpoints and feature arrays require separate storage.

4.2.2. Evaluation Metrics

For the initial restricted benchmark, the main metric is the cell-level AUROC (positive: $\Delta\mathrm{PSI} \geq 1$), computed per peptide that has both classes and then averaged over peptides (macro AUROC). Paired differences between two models are computed on the same peptides. The 95% confidence intervals come from 5,000 bootstrap resamples of protein clusters [20]; every peptide of a sampled cluster is kept, so

cells and peptides are not treated as independent. These intervals are conditional on the stored out-of-fold predictions and do not include the variance of retraining. For these initial G2 contrasts, no multiplicity correction is made, so a single interval is a development-stage indication. Later sections identify their own adjusted comparison families, including R6, the two full-PSI range contrasts and the four matched local LoRA contrasts. The full-PSI follow-up instead uses peptide-macro MAE as its primary metric.

Probabilities are assessed with the Brier score (the mean squared difference between the predicted probability and the 0/1 label over the cells), the Brier skill score against a constant forecast of the base rate, $\mathrm{BSS} = 1 - \mathrm{Brier}/\mathrm{Brier}_{\mathrm{const}}$, and the expected calibration error (ECE) over ten equal-mass bins, pooled over the outer-test cells and bootstrapped by cluster in the same way. Ranking utility is the *enrichment at* $k\%$: for each peptide, the substitutions are ordered by predicted score, the precision of the top $k\%$ is divided by the fraction of positive cells of that peptide, and the ratio is averaged over the peptides that have both classes; a random ranking has enrichment 1.

4.2.3. Results

All results below are on a *development benchmark*: the same 91 peptides have been examined in several experiments, and the out-of-fold design is not an independent validation on unseen data.

4.2.3.1. Direct Learning on the Saturation Matrix

Table 4.2 lists the macro AUROC of each model. Ridge M3 reaches 0.8082, above the frozen ΔPAP baseline (0.7693). The paired difference is +0.0389 with a cluster-bootstrap interval [+0.0216, +0.0571] (Table 4.3). The gated network with residual ΔPAP reaches 0.8002 and is below ridge (difference −0.0080, [−0.0152, −0.0006]). Removing the gate (0.7937) or the ΔPAP residual (0.8015) does not change this picture: both variants stay below ridge.

The result of the gate is not stable across seeds (Table 4.4). In seed 29 the gated network is *below* the network without the gate (difference −0.0076, [−0.0152, −0.0005]), whereas it is above in the other two seeds. The ensemble figure should therefore not be read as evidence that the gate helps.

Table 4.2. Macro AUROC on the 91 peptides of the saturation benchmark. The last column keeps only the cells whose exact sequence is not in the training data of the published Degformer.

Model	All cells	Cells without exact-sequence overlap
ΔPAP, frozen (reference)	0.7693	0.7531
Ridge regression on M3 features	0.8082	0.8040
Gated network + residual ΔPAP	0.8002	0.7956
Network without gate, with ΔPAP	0.7937	0.7892
Gated network without ΔPAP	0.8015	0.7940
Degformer, published checkpoint (overlaps its training data)	0.9248	0.9227

Table 4.3. Paired AUROC differences between models

Paired comparison (same peptides)	Difference in AUROC [95% cluster-bootstrap CI]
Ridge − ΔPAP	+0.0389 [+0.0216, +0.0571]
Gated + ΔPAP − ΔPAP	+0.0309 [+0.0125, +0.0501]
Gated + ΔPAP − ridge	−0.0080 [−0.0152, −0.0006]
Gated + ΔPAP − no gate	+0.0065 [+0.0027, +0.0102]
Gated + ΔPAP − gated without ΔPAP	−0.0013 [−0.0048, +0.0023]

Table 4.4. Per-seed AUROC of the three main models

Seed	Ridge	Gated +ΔPAP	No gate	Gated − no gate [95% CI]
17	0.8062	0.7895	0.7806	+0.0089 [+0.0038, +0.0145]
29	0.8068	0.7762	0.7838	−0.0076 [−0.0152, −0.0005]
43	0.8081	0.7881	0.7816	+0.0064 [+0.0013, +0.0113]

4.2.3.2. Published Degformer Checkpoint and Retrained Architecture

The published Degformer checkpoint scores 0.9248, but this is not a held-out result: 42 163 of the 47 847 mutant cells (88.12%) have an exact sequence in its training file, and the wild type of all 91 peptides is in it as well. A natural suspicion is that this exact overlap alone explains the high score. Restricting the evaluation to the 5 684 cells without overlap leaves the score essentially unchanged (0.9227, Table 4.2), so exact cell overlap does not explain the gap. The remaining leak is at the level of the peptide: the model has seen most of the matrix of every peptide, and removing a few dozen cells does not create an unseen peptide. The comparison of the published checkpoint with the models of this thesis is therefore not a fair test of generalisation, and no claim is made about it.

A fair comparison of the architecture requires the same label budget and the same cluster-wise split. Retrained under these conditions (one seed, hyper-parameters as published by its authors, target the absolute PSI), the Degformer architecture reaches 0.7500, below ridge (difference −0.0582, [−0.0734, −0.0426]) and below ΔPAP (Table 4.5). This lower score is not necessarily a property of the architecture itself: it may reflect the small number of training clusters (see Section 4.2.3.4).

4.2.3.3. Interaction Designs

Three interaction designs were fixed before running: FiLM, a rank-8 bilinear form and ridge with 2,400 cross-product features. A candidate was to be called a useful architectural component only if the following held at the same time: (a) its paired difference to ridge is positive in all three seeds, (b) the confidence interval of the ensemble difference excludes zero, and (c) the same holds against ΔPAP. None of the candidates met the criterion (Table 4.5). The best of them, FiLM, is −0.0054 ([−0.0136, +0.0028]) relative to ridge and is below ridge in every seed. The sigmoid gate of the first experiment gives the same direction, and the retrained Degformer architecture is far lower. All candidates are above the frozen ΔPAP, but so is plain ridge.

This result does not show that interaction between the substituted amino acid and its context is absent. The tested designs do not improve on ridge under this label budget and selection procedure. Increased estimation variance is one possible

Table 4.5. Interaction designs against ridge M3. "Criterion met" applies the pre-registered rule above; for the sigmoid gate and the one-seed Degformer architecture the rule is applied descriptively.

Candidate	AUROC	Candidate − ridge [95% CI]	Per-seed difference	Criterion met
Sigmoid gate +ΔPAP (G2 runner)	0.8002	−0.0080 [−0.0152, −0.0006]	−0.0168, −0.0306, −0.0200	No
FiLM (pair-generated scale and shift)	0.8028	−0.0054 [−0.0136, +0.0028]	−0.0104, −0.0162, −0.0091	No
Rank-8 bilinear	0.7933	−0.0149 [−0.0227, −0.0072]	−0.0212, −0.0275, −0.0335	No
Ridge with 2,400 cross-product features	0.7924	−0.0158 [−0.0227, −0.0086]	deterministic	No
Degformer architecture, retrained (one seed)	0.7500	−0.0582 [−0.0734, −0.0426]	one seed only	No

explanation, but was not isolated experimentally. Model capacity, optimisation and representation remain alternative explanations (Section 4.2.3.4).

4.2.3.4. Learning Curve and Relaxing the Degron Threshold

Two questions were put together and their criteria fixed before running. **P1:** does the AUROC still rise with the number of training clusters? **P0:** can the 85 peptides removed by the degron threshold be used as extra *training* labels if the threshold is relaxed from 3.0 to 4.0? The design keeps the outer-test cells exactly equal to those of the 91 benchmark peptides, so every number is comparable with 0.8082; the added peptides enter only the outer-training sets, and those that fall in a test cluster are removed from the training of that fold (531 cells in fold 0 and 532 cells in fold 3, none in the other folds). The partition of the five folds was checked to be identical to the earlier experiment; at the 100% level, the two models reproduce the earlier scores of 0.8082 and 0.8015 exactly. Two models of different capacity were fixed in advance: ridge M3 and the gated network without ΔPAP.

P1. Table 4.6 and Figure 4.1 show the curves. Under the fixed rule the learning curve of ridge does not support the hypothesis of label shortage (Table 4.7). From 100% to 50% of the clusters the difference is only +0.0038 ([−0.0009, +0.0087]) and the sequence of means is not monotone. This must not be read as evidence that the




Figure 4.1. Macro AUROC against the mean number of training clusters (nested cluster subsets of 25, 50, 75 and 100% of the outer-training data; the dashed segment is the relaxed-threshold training set).

Table 4.6. Learning curve (P1) and relaxed degron threshold 4.0 (P0). Ranges are over 5 folds and 3 seeds.

Training level	Train clusters	Train cells	Ridge M3	Gated, no ΔPAP
25%	18	9 068–10 314	0.7776	0.7529
50%	35–36	18 635–19 877	0.8044	0.7859
75%	52–54	28 145–29 048	0.8088	0.7949
100%	70–72	38 233–38 290	0.8082	0.8015
100% + relaxed threshold	153–155	82 191–82 780	0.8208	0.8154

data limit has been reached: the design does not measure a ceiling. The gated network behaves differently: it gains +0.0156 ([+0.0060, +0.0256]), the curve is monotone, and the criterion is met. The two curves suggest diminishing measured returns for ridge within the tested original distribution, while the network is still rising at about 70 clusters. The gap between ridge and the network narrows with data but is not closed (ridge is still higher by 0.0054 at the relaxed-threshold level); the result does not rehabilitate any of the rejected designs, and it must not be extrapolated to "more data will make the architecture win". One of the predictions written before the run, that P1 would probably be supported, was therefore not borne out for ridge.

P0. Adding 85 peptides (44 490 cells, 83 clusters not in the benchmark) lifts ridge from 0.8082 to 0.8208, a gain of +0.0126 ([+0.0061, +0.0190]), positive in each seed (+0.0142, +0.0142, +0.0128). The gated network gains +0.0139 ([+0.0059, +0.0218]). Both meet the pre-registered criteria. The protocol had also predicted, before the run, that P0 would probably fail, because peptides with a high PSI_{WT} are already stable and might have almost no positive cells. The measurement contradicts this prediction (Table 4.8): the share of positive cells falls only from 13.1% to 11.4%, and the 95th percentile of ΔPSI in the added peptides is 1.51, against 1.70 in the benchmark peptides. The threshold of 3.0 therefore appears more conservative than the mutation-effect task requires, even if it is the right threshold for the source assay's different operational question of whether a peptide is a degron. These data do not establish 3.0 as a universal biological boundary.

Table 4.7. Pre-registered verdicts of P1 and P0

Model	Question	ΔAUROC [95% CI]	Pre-registered criteria	Verdict
Ridge M3	P1: 100% — 50%	+0.0038 [−0.0009, +0.0087]	CI> 0: no; monotone: no	insufficient evidence for label shortage
	P0: relaxed — 100%	+0.0126 [+0.0061, +0.0190]	CI> 0: yes; all seeds > 0: yes	accepted
Gated, no ΔPAP	P1: 100% — 50%	+0.0156 [+0.0060, +0.0256]	CI> 0: yes; monotone: yes	supported
	P0: relaxed — 100%	+0.0139 [+0.0059, +0.0218]	CI> 0: yes; all seeds > 0: yes	accepted

Table 4.8. Cells of the benchmark peptides and of the 85 peptides added by relaxing the threshold

Statistic	Benchmark set (91 peptides)	Added set (85 peptides)
Median PSI_{WT}	2.593	3.346
Fraction of positive cells ($\Delta PSI \geq 1$)	0.1310	0.1140
Median ΔPSI	0.125	0.083
95th percentile of ΔPSI	1.697	1.507

4.2.3.5. Number of Clusters or Coverage of the Distribution

The two curves of the previous section seem to contradict each other: ridge is flat between 35 and 71 clusters, yet it rises when 83 more clusters are added. One reading is that the two steps add different things: the first thickens the existing region of PSI_{WT}, the second widens it. The previous experiment cannot separate the two, because it changes the number of clusters and the region together. A second experiment, with its criteria fixed before running, keeps the whole original training set and adds a nested fraction of the new clusters (Table 4.9). The main criterion compares the gain at +50% of the new clusters (about 42 clusters) with the marginal gain of 36 old-region clusters measured before, 0.0038.

Table 4.9. Gain over the benchmark training set when a fraction of the new clusters is added

New clusters added	Mean added	Ridge	Gain	Gated	Gain
none (benchmark)	0	0.8082	—	0.8015	—
+25%	21	0.8143	+0.0061	0.8090	+0.0075
+50%	42	0.8196	+0.0114	0.8118	+0.0103
+75%	64	0.8204	+0.0122	0.8168	+0.0153
+100%	85	0.8208	+0.0126	0.8154	+0.0139

For ridge the gain at +50% is +0.0114 ([+0.0063, +0.0166]), whose interval lies entirely above 0.0038: the main criterion supports coverage of the distribution. For the network the interval contains 0.0038, so the new clusters are useful but not shown to be better than old ones (Table 4.10). The secondary criterion, the shape of the curve, gives the opposite answer: the gain at +25% is 48.4% of the total for ridge and 54.4% for the network, below the threshold of 60% fixed for “early saturation”, so the fixed

rule says “proportional to the number of clusters”. Because the two fixed criteria disagree, the question is *not decided*. As a descriptive remark only, the successive increments of ridge are +0.0061, +0.0053, +0.0007, +0.0005, so roughly 90% of the total gain is already reached at +50%, and the threshold of 60% at +25% was a poor operational choice. This remark does not overturn the verdict.

Table 4.10. Pre-registered verdicts on the new clusters. The reference marginal gain of old-region clusters is 0.0038.

Model	B(50%) − B(0) [95% CI]	Share of total gain at +25%	Primary criterion	Shape criterion
Ridge M3	+0.0114 [+0.0063, +0.0166]	48.4%	supports wider coverage of the distribution	proportional to cluster count
Gated, no ΔPAP	+0.0103 [+0.0033, +0.0172]	54.4%	valuable, but not shown to exceed old-region clusters	proportional to cluster count

What can be stated is limited: clusters from the region $3.0 < \mathrm{PSI}_{\mathrm{WT}} \leq 4.0$ have a marginal value at least equal to that of old-region clusters, and for ridge the evidence suggests it is higher. It cannot be said that the gain is *only* due to wider coverage, because the 83 new clusters differ from the old ones both in region and in protein.

4.2.3.6. Sensitivity to the Threshold

The four thresholds 3.5, 4.0, 4.5 and 5.0 were run in one pass and are all reported (Table 4.11, Figure 4.2). The main configuration of this historical restricted-domain study stays at 4.0, a value fixed before this grid was seen and chosen then only because it roughly doubles the number of peptides; it is not re-chosen from the grid. The later full-PSI task uses a different evaluation population. Every threshold is better than the benchmark training set (all intervals above zero). The ridge gain is highest at 4.0 (+0.0126) and lower at 4.5 (+0.0101) and 5.0 (+0.0093); under the fixed rule (a drop of more than 0.002) this is labelled “decline after 4.0”. That label describes the shape of the point estimates: the intervals overlap widely, and no interval was computed for the difference between 4.0 and 4.5. The gated network is nearly flat from 3.5 to 5.0, so the decline is a property of ridge. It also depends on

how a positive cell is defined: with the positive cut at $\Delta\text{PSI} \geq 1.5$ the maximum for ridge moves to 5.0 (+0.0098) and there is no decline. The share of positive cells in the added peptides falls steadily with the threshold (Table 4.11), which is consistent with peptides that are not degrons starting to dilute the training set (an interpretation, not tested separately).

Table 4.11. Added data and gains for each degron threshold (cov80, positive cut $\Delta\text{PSI} \geq 1$)

Thr.	Peptides	Cells	New clusters	Pos. rate	Ridge AUROC	Ridge Δ [95% CI]	Gated Δ
3.5	+50	26 234	48	0.1197	0.8185	+0.0103 [+0.0043, +0.0164]	+0.0115
4.0	+85	44 490	83	0.1140	0.8208	+0.0126 [+0.0061, +0.0190]	+0.0139
4.5	+106	55 362	102	0.1028	0.8183	+0.0101 [+0.0028, +0.0172]	+0.0125
5.0	+121	63 009	117	0.0918	0.8175	+0.0093 [+0.0016, +0.0169]	+0.0133




Figure 4.2. Gain in macro AUROC over the benchmark training set for each degron threshold, with 95% cluster-bootstrap intervals (horizontal offsets only separate the two models).

The gain at 4.0 survives three definitions of a positive cell and a different assignment of folds (Table 4.12); all four intervals are above zero. The last row must be read with care. The clustering at 50% coverage was meant to test sensitivity to the coarseness of clustering, but on this peptide set cov50 and cov80 produce the same

number of clusters (89) and, as found after the run, the same grouping of peptides; only the representative labels differ, which changes how clusters are assigned to the five folds (the benchmark score becomes 0.8116 instead of 0.8082). That row therefore tests a re-assignment of folds, not coarser clustering; clustering granularity is tested with genuinely different partitions in Section 4.2.3.7.

Table 4.12. Robustness of the gain at threshold 4.0 (ridge M3)

Condition (threshold 4.0)	Ridge Δ vs. base [95% CI]	CI > 0
cov80, ΔPSI ≥ 0.5	+0.0110 [+0.0051, +0.0169]	yes
cov80, ΔPSI ≥ 1.0 (main)	+0.0126 [+0.0061, +0.0190]	yes
cov80, ΔPSI ≥ 1.5	+0.0094 [+0.0037, +0.0149]	yes
cov50 fold assignment, ΔPSI ≥ 1.0	+0.0096 [+0.0032, +0.0159]	yes

4.2.3.7. Sensitivity to the Clustering Granularity

Because cov50 does not change the partition on this peptide set, a grid of seven partitions of the 176 peptides (the 91 benchmark peptides and the 85 added ones) was fixed before running: grouping by UniProt accession (no clustering), the reference MMseqs2 setting (30% identity, 80% coverage) and five looser MMseqs2 settings. The P0 comparison (ridge M3, relaxed threshold 4.0 against the benchmark training set, same cluster bootstrap) was repeated with the folds rebuilt from each partition. The reference level reproduces the earlier scores (0.8082 and 0.8208) and the five folds of the earlier experiment. The criterion fixed in advance: the gain is "robust to granularity" if every partition that differs from the reference and is still informative (fewer than half of the added cells are lost because they share a group with a test peptide) has a bootstrap interval of the gain above zero and a positive gain in all three seeds.

The seven levels give only 4 distinct partitions (Table 4.13): lowering the identity from 0.2 to 0.1 at coverage 0.5, and from 0.1 to 0.0 at coverage 0.3, changes no group, and 30% identity with coverage 0.5 reproduces the reference grouping (only the group labels, and hence the fold assignment, differ; the gain there is +0.0096 [+0.0032, +0.0159], the same value as the cov50 row of Table 4.12). Three partitions differ from the reference and are informative: grouping by accession (+0.0166, [+0.0099, +0.0240]), 20% identity with coverage 0.5 (+0.0134, [+0.0074, +0.0199])

Table 4.13. Gain of the relaxed threshold 4.0 (ridge M3) under different protein partitions. “Groups” are the groups of the 91 benchmark peptides and of all 176 peptides; “Shared” is the number of added peptides that fall in a group of a benchmark peptide; “Excl.” is the mean percentage of the added cells that are removed from training because their group contains a test peptide.

Partition (MMseqs2)	Groups base/all	Shared	Excl. %	AUROC base → relaxed	Gain [95% CI]	Seeds > 0
Accession (no clustering)	91/176	0	0.0	0.8036 → 0.8202	+0.0166 [+0.0099, +0.0240]	yes
id 0.3, cov 0.8 (reference)	89/172	2	0.5	0.8082 → 0.8208	+0.0126 [+0.0061, +0.0190]	yes
id 0.3, cov 0.5 grouping as reference; folds assigned differently	89/172	2	0.5	0.8116 → 0.8212	+0.0096 [+0.0032, +0.0159]	yes
id 0.2, cov 0.5	87/163	6	1.4	0.8051 → 0.8185	+0.0134 [+0.0074, +0.0199]	yes
id 0.1, cov 0.5 identical to the row above	87/163	6	1.4	0.8051 → 0.8185	+0.0134 [+0.0074, +0.0199]	yes
id 0.1, cov 0.3	71/133	22	5.2	0.8096 → 0.8209	+0.0113 [+0.0037, +0.0184]	yes
id 0.0, cov 0.3 identical to the row above	71/133	22	5.2	0.8096 → 0.8209	+0.0113 [+0.0037, +0.0184]	yes

and 10% identity with coverage 0.3 (+0.0113, [+0.0037, +0.0184]). All intervals are above zero and the gain is positive in all three seeds, so under the fixed rule the gain is *robust to granularity*. The point estimates are not monotone in the coarseness (the largest is for grouping by accession), the intervals overlap, and no test of their differences was planned; the absolute benchmark score also moves with the partition (0.8082 for the reference and 0.8116 for the same grouping with other folds), so absolute values must not be compared across rows.

The test is weaker than its name suggests. The coarsest partition still has 71 groups for the 91 benchmark peptides; in it, 22 added peptides share a group with a benchmark peptide and on average 5.2% of the added cells are removed from training, and one of the five test folds consists of a single group. Whether the gain would survive a still coarser split, for example by protein family, is not known.

4.2.3.8. Pre-Training on Tile Labels

The experiment of Voutsinos et al. [4] provides a degradation score for 212 616 tiles of 30 residues, without substitutions. The question was whether initialising the gated network (without ΔPAP) from a model pre-trained to predict these scores lets it learn ΔPSI better under the same label budget. The design was fixed in advance. Pre-training treats each tile as 30 wild-type rows (the substituted-residue input is zero), predicts the tile as the mean over positions and regresses the sign-reversed, standardised degron score. Two branches then share the same architecture, the learning-rate grid (2×10^{-3} or 5×10^{-4}, chosen on the inner validation set) and the inner validation split, and differ only in whether the network starts from the pre-trained state (*pre*) or from random initialisation (*rand*). To prevent leakage, in each outer fold every gene that has a tile similar to a protein of an outer-test cluster (MMseqs2 at 30% identity with an alignment of at least 50 residues, a shared 12-mer, or the same gene name) is removed entirely from the pre-training data *before* any learning; this removed 318, 34, 176, 99, 44 genes in the five folds. The gate on the reproduction of earlier scores was passed (ridge 0.8082 and 0.8208; the gated network within 6.0e-05 of the earlier values). Two comparisons were fixed, both with the rule "bootstrap interval above zero and a positive difference in every seed": (A) *pre* against *rand*, and (B) *pre* against ridge M3.

The result is negative (Tables 4.14 and 4.15). In the main configuration the pre-

Table 4.14. Macro AUROC with and without pre-training on tile labels

Training configuration	Ridge M3	Network, random init.	Network, pre-trained
Relaxed threshold 4.0 (main)	0.8208	0.8175	0.8098
Threshold 3.0 (secondary)	0.8082	0.8009	0.7726

Table 4.15. Pre-registered comparisons for pre-training. The main configuration is the relaxed threshold 4.0; the threshold 3.0 is reported with the same criteria and was not used to choose the configuration.

Thr.	Comparison	Difference [95% CI]	Per-seed difference	Met
4.0 (main)	A: pre-trained − random init.	−0.0077 [−0.0163, +0.0006]	−0.0180, −0.0259, −0.0121	no
	B: pre-trained − ridge M3	−0.0110 [−0.0197, −0.0024]	−0.0234, −0.0330, −0.0263	no
3.0 (secondary)	A: pre-trained − random init.	−0.0283 [−0.0426, −0.0149]	−0.0295, −0.0345, −0.0427	no
	B: pre-trained − ridge M3	−0.0356 [−0.0509, −0.0215]	−0.0458, −0.0550, −0.0637	no

trained network reaches 0.8098, against 0.8175 for random initialisation: difference A is −0.0077 [−0.0163, +0.0006], an interval that contains zero, so pre-training cannot be distinguished from random initialisation; difference B is −0.0110 [−0.0197, −0.0024], so the pre-trained network is below ridge. At threshold 3.0 both differences are clearly negative (A: −0.0283 [−0.0426, −0.0149]; B: −0.0356 [−0.0509, −0.0215]). The difference is negative in all three seeds in every comparison. By the mapping fixed in advance, the conclusion is “insufficient evidence for a benefit of pre-training”. The pre-training task itself was learned (Pearson correlation 0.864 between prediction and score on held-out genes, range 0.857–0.868 over the fifteen runs), so learning this source endpoint does not by itself establish useful transfer to ΔPSI. This result rejects only this design, in which the pre-training sees wild-type sequences only and the whole network is then fine-tuned; designs that pre-train with substitutions, freeze part of this tile-label encoder or train both tasks jointly were not tried. The later frozen-ESM and LoRA experiments use different pretrained representations and are reported separately.

4.2.3.9. Calibration of the Scores and Ranking Utility

The score of ridge M3 is a predicted ΔPSI, not a probability. To report the probability that a substitution is positive ($\Delta\text{PSI} \geq 1$) the model trained at the relaxed threshold 4.0 was kept fixed and evaluated on the same 47 847 outer-test cells (91 peptides, 89 clusters). Calibrators were fitted only on out-of-fold scores of the outer-training pool: the pool was split again into five inner folds by cluster, the ridge model was refitted on four of them, and the scores of the fifth were kept; the outer-test cells never entered a calibrator. Three conversions were fixed in advance: the *raw* score clipped to $[0, 1]$, Platt scaling (a logistic regression on the score) and isotonic regression, with a constant forecast of the base rate of the training pool as a reference for skill. The criteria were also fixed in advance: a conversion is *calibrated* if the bootstrap interval of $\text{Brier}(\text{raw}) - \text{Brier}(c)$ is above zero and the difference is positive in every seed; it has *skill over the base rate* if the interval of $\text{Brier}(\text{constant}) - \text{Brier}(c)$ is above zero; Platt is used in the prototype unless isotonic regression is better with an interval above zero; and the ranking is *enriching* if the interval of the enrichment at 10% is above 1. The raw scores of the three seeds reproduce the earlier AUROC values (gate passed).

Table 4.16. Probability quality on the outer-test cells (observed fraction of positive cells: 0.131). ECE: expected calibration error over ten equal-mass bins; $\hat{p}$: predicted probability.

Score to probability	Brier	95% CI	Skill vs. base rate	ECE	Mean $\hat{p}$
Raw score, clipped to $[0, 1]$	0.1272	[0.1186, 0.1360]	−0.116	0.1437	0.2617
Platt (logistic) scaling	0.0925	[0.0809, 0.1046]	+0.188	0.0163	0.1146
Isotonic regression	0.0925	[0.0810, 0.1045]	+0.188	0.0164	0.1145
Constant (base rate of the training pool)	0.1139	[0.1011, 0.1276]	—	0.0154	0.1219

Platt scaling meets the criterion (Tables 4.16 and 4.17): the Brier score falls from 0.1272 to 0.0925, a difference of +0.0346 [+0.0266, +0.0425], positive in each seed (+0.0346, +0.0347, +0.0347); isotonic regression is practically identical (Platt − isotonic: +0.00002, [−0.0002, +0.0002]), so Platt scaling, with two parameters, is used. The skill over the base rate is +0.188, with the interval of +0.0214 [+0.0175,

Table 4.17. Pre-registered comparisons of the Brier score

Comparison (positive favours the second term)	Difference [95% CI]	Per-seed difference
Brier(raw) − Brier(Platt)	+0.0346 [+0.0266, +0.0425]	+0.0346, +0.0347, +0.0347
Brier(raw) − Brier(isotonic)	+0.0346 [+0.0267, +0.0424]	+0.0345, +0.0347, +0.0347
Brier(constant) − Brier(Platt)	+0.0214 [+0.0175, +0.0253]	+0.0212, +0.0215, +0.0215
Brier(Platt) − Brier(isotonic)	+0.0000 [−0.0002, +0.0002]	—

+0.0253] above zero. The first criterion is a low bar: the raw score read as a probability is *worse* than a constant forecast (skill −0.116; mean value 0.262 against 0.131 observed; recalibration slope 0.35), because it is a regression output. The more informative statement is the skill of about +0.188. The ECE alone does not separate the methods here, since the constant forecast has an ECE (Table 4.16) close to that of Platt scaling.

Local calibration is not perfect. The Platt probabilities are lower than the observed frequency in every bin: the mean is 0.115 against 0.131, and in the highest bin the mean prediction is 0.434 against an observed 0.495 (interval 0.449–0.538). A likely cause is a shift of domain introduced by the relaxed threshold: the calibrator is fitted on a pool that includes the added peptides, in which the fraction of positive cells is lower than in the benchmark peptides (Table 4.8). A sensitivity analysis that was not used for the verdict, fitting the calibrator only on benchmark-domain cells, gives a Brier score of 0.0921, an ECE of 0.0044 and a mean probability of 0.131. For ordering substitutions the shift is irrelevant (the transform is monotone); for absolute probabilities it must be kept in mind.

Table 4.18. Ranking utility: the substitutions of each peptide (532 per 28-residue peptide) are ordered by the raw score. A random ranking has enrichment 1.

Top fraction	Cells	Precision	Recall	Enrichment	95% CI
5%	27	0.551	0.241	4.75	[4.23, 5.28]
10%	54	0.466	0.407	4.02	[3.70, 4.35]
20%	107	0.371	0.611	3.04	[2.86, 3.21]

For prioritising substitutions (Table 4.18), choosing the top 10% of each peptide (about 54 substitutions) gives a precision of 0.47 and a recall of 0.41, an enrichment of 4.02 ([3.70, 4.35]); the criterion is met. The only reference is a random ranking: it is not known how much better the model is than a simple rule, for example one based on the hydrophobicity of the substituted residue. Moreover, the final model is fitted on all of the pool whereas the calibrator is learned from scores of models fitted on four fifths of it (a known limitation of cross-fitting), and all of this is still a development benchmark. The word "calibrated" here means that the Brier score is better than that of the raw score with an interval above zero; it does not mean perfect calibration.

4.2.3.10. External GPS Labels: Koren et al. Table S4

The saturation-mutagenesis tables of Koren et al. [2] use the same endpoint (PSI) and were audited as a possible source of additional training labels. The supplementary tables were downloaded manually, because the automatic download is blocked by the host. The article is not in the open-access subset of the repository, so the tables are used internally only and are not redistributed here. The gate fixed in advance required all of four conditions (Table 4.19).

Table 4.19. Gate fixed in advance for merging the labels of Koren et al. (Table S4) into training

Criterion	Pre-registered threshold	Observed	Met
G1: new clusters at cov80	≥ 20	5 (6 of 13 sequences mapped)	No
R1: PSI recomputed from bin counts	$\lvert\Delta\rvert \leq$ 1e-06 in $\geq$ 99% of rows	1827 of 1827 rows (max. 5.0e-12)	Yes
R2: internal wild-type reference	≥ 8 synonymous cells in ≥ 7 substrates	9 of 9 substrates	Yes
R3: direction of ΔPSI (last Gly of Clone#8)	median $\geq +0.5$, $\geq 90\%$ positive	median +1.04, 100% positive ($n = 19$)	Yes
Gate (G1 and R1 and R2 and R3)			**No**

The data themselves are sound: PSI is reproduced from the bin counts in all rows, an internal wild-type reference can be built for all substrates, and the direction of the effect of the last glycine agrees with the biology. The gate nevertheless fails on

the number of new clusters. Table S4 holds 1 739 substitution cells for 9 substrates; the peptides are 23-residue C-terminal sequences with a stop codon in which only the last ten positions are mutated, a library different from the 28-residue internal peptides of the main labels; PSI is computed from 3 bins and not 6, so ΔPSI values from the two sources cannot simply be added; only 3.0% of the cells have $\Delta\text{PSI} \geq 1$ (against 13.1% in the benchmark), and the effects sit in the last one to three positions. Only 6 of the 13 sequences could be mapped to Swiss-Prot, and one of them overlaps with the training peptides, which leaves 5 new clusters, against the 20 required. As a diagnostic, not part of the gate, the agreement between Tables S3 and S4 on the 12 cells they share is low (Spearman 0.10), so S3 is not used as a label source.

By the consequence fixed in advance, these labels are *not* merged into training, and the planned merging of external labels (P4) and the repeated learning curve on the enlarged set (P5) were therefore not run. The table remains a possible external test set for a C-terminal degron class; this was not done in the thesis and no number is reported for it.

4.2.3.11. Scope Comparison with MetaDegron

MetaDegron [10] was audited as a possible competitor and label source. Its labels are binary motif-level annotations of curated degrons, not ΔPSI; the audit therefore compares scope and data, not predictive scores on the GPS matrix, because MetaDegron-D could not be run on GPS peptides (Table 4.20). Among the main findings, the curated positive set has only 227 human rows, and almost no region of it coincides with the GPS peptides used here (2 scanning peptides, 1 saturation peptide and 0 from the CRISPR screens). Only 1 E3 motif group keeps at least five samples after the strictest filter, so “21 E3 ligases” is a list of motif-compatible assignments, not 21 independently labelled classes. The reported MetaDegron-X AUC of 0.9670 was recomputed from the stored trees, but only on the authors’ prepared tables, and 8 of the 20 positive test coordinates are in the property table of the fitting data; it is not an independent result and not a GPS result. A simple composition logistic baseline on the same positives, split by protein cluster at cov80, gives AUROC between 0.728 and 0.731 (core composition) and between 0.737 and 0.747 (29-residue context), on a reconstructed population and not on the authors’ own training set. The audit therefore suggests positioning MetaDegron as a complementary tool for motif and E3 informa-

tion rather than a head-to-head competitor on residue-level effect prediction; binary motif labels are not converted into ΔPSI.

Table 4.20. Audit of the MetaDegron data and overlap with the data of this thesis

Audit item	Value
Curated positive rows / distinct accessions	302 / 240
Rows with species suffix HUMAN	227
Rows in the property table used by MetaDegron-X	212
E3 motif groups with ≥ 5 samples: before filtering / after the strictest filter (human only, no regional or cluster overlap)	13 / 1
Same-region overlap with GPS scanning peptides (2 624 peptides)	2
Same-region overlap with saturation peptides (248 mapped)	1
Same-region overlap with CRISPR-screen peptides (31 peptides)	0
MetaDegron-X AUC recomputed from the stored trees on the authors' prepared tables (not a GPS result)	0.9670
Positive test coordinates also present in the property table of the fitting data	8 / 20

4.2.3.12. Follow-up on the Restricted Benchmark

Notebook replication reproduced the ridge and prototype-consistency results on Kaggle. A separate Degformer run that excluded training rows touching the outer-test protein clusters completed all three seeds and five folds. Its ensemble AUROC was 0.8068, compared with 0.8208 for the extended-training ridge. This is distinct from the earlier one-seed, saturation-only retraining: the clean-cluster comparison has now been performed, without establishing a transformer advantage.

The frozen ESM2-650M/PCA ridge comparison reached 0.8230, but its paired interval against ridge included zero. In the subsequent representation and context study, ridge with an ordered ± 5 context reached 0.8286, with an adjusted interval of [+0.0021, +0.0139] for the AUROC gain over ± 3. Frozen ESM2-35M with a multi-window CNN reached 0.8305, but the primary comparison with ridge had interval [−0.0025, +0.0233] and did not meet its confirmation criterion. These findings motivated the matched pointwise/CNN control in the full-PSI study.

The same restricted-benchmark study also found a gain from scanning-label fine-tuning of the one-hot mCNN over its own no-scanning control: AUROC difference $+0.01466$, adjusted interval $[0.00272, 0.02759]$. This is a distinct positive transfer control, not evidence that the primary ESM2-mCNN comparison met its cri-

terion. It must also be distinguished from the unsuccessful tile-label pre-training of Section 4.2.3.8.

4.2.3.13. Full-PSI Development Evaluation

Population and protocol. The full-PSI follow-up retains 235 saturation peptides, 122 412 mutation cells and 221 protein groups after technical quality control, without removing peptides by their WT stability. The supporting scanning bundle contains 224 470 cells. The label remains the replicate-mean ΔPSI from the Zhang reporter assay [7], [21]; these are reprocessed public measurements, not new wet-lab data. Groups combine whole-proteome cov80 clusters, additional bidirectional cov50 similarity hits and exact-sequence unions. This is heuristic homology control, not a proof of biological independence. Scanning data are partitioned by group before fitting into development, held-source and saturation-overlap subsets; overlapping scanning groups do not supply transfer-training labels.

Five outer folds and seeds 17, 29 and 43 share the evaluation cells. Training is either restricted to $\mathrm{PSI}_{\mathrm{WT}} \leq 4$, uses the full range, or uses the full range balanced first by WT-PSI stratum and then by peptide. Inner validation covers the full range in all three arms; therefore the restricted arm is not entirely unexposed to high-PSI labels during model selection. Scaling, PCA and hyperparameter selection remain inside the applicable training split. This protocol was designed after earlier results were known and is an extension for development, not an independent preregistration. It defines a new evaluation population rather than expanding the old 91-peptide test.

Models and metrics. Ridge with ordered ± 5 context remains the reference. Frozen ESM2 representations [17] are compared through pointwise, single-window and multi-window convolutional heads. For the matched ESM comparison, the crop, auxiliary inputs and projection are held common; the pointwise head does not mix positions, whereas the CNN does. This isolates positional mixing more closely than comparing different pLM pooling schemes. It does not make the parameter counts equal. Neural epochs are chosen by inner MSE before refitting on the permitted outer-training data.

The primary measure is mean absolute error in PSI units, calculated within each peptide and then averaged across all 235 peptides. Positive-event AUROC uses $\Delta\mathrm{PSI} \geq 1$ and requires at least three cells in each class; only 184 peptides qual-

ify. High-PSI peptides can still inform regression when a positive event is physically unavailable. Each table entry averages the three seed predictions per cell before calculating metrics; it is not an average of seed-level metric values.

Table 4.21. Selected full-PSI development results. MAE is lower-is-better; positive AUROC is higher-is-better. All rows use the same evaluation population and three-seed prediction ensemble.

Configuration	Macro MAE	Positive AUROC
Ridge W5, train $PSI_{WT} \leq 4$	0.43358	0.83118
Ridge W5, full range	0.40780	0.83193
Ridge W5, balanced full range	0.40361	0.82752
One-hot CNN, full range	0.39361	0.82913
Frozen ESM2-35M + pointwise, full range	0.38969	0.83753
Frozen ESM2-35M + CNN, full range	0.38435	0.84882
Frozen ESM2-35M + multi-window CNN, balanced	0.38385	0.84700
One-hot CNN, scanning pre-training, full range	0.38723	0.84249

What the results establish. Full-range training reduces W5 ridge MAE from 0.43358 to 0.40780 (5.94%), with the largest gains in the high-WT-PSI strata. Balancing lowers MAE further to 0.40361, but does not preserve positive-event ranking as well; it is not a uniform improvement. The adjusted intervals in Table 4.22 support a reduction in MAE, but their upper endpoints do not establish the prespecified minimum reduction of 0.02 PSI throughout the intervals.

Frozen ESM2-35M with a CNN reaches MAE 0.38435. Relative to the matched pointwise head, the difference is −0.00534 with descriptive interval [−0.0102, −0.0009]. The balanced multi-window CNN has the lowest selected MAE, 0.38385, but its advantage over the full-range single-window CNN is only 0.00051 PSI. The ranking alone does not establish an architecture winner. Choosing the top 5% of predicted positive substitutions within eligible peptides gives macro precision 58.24% for the ESM CNN; this is a ranking utility measure, not a calibrated probability or whole-dataset accuracy.

Scanning pre-training improves the one-hot CNN from 0.39361 to 0.38723 MAE under this design. Quality weighting worsens ridge relative to its unweighted control (Table 4.22). These results concern mutation-label scanning transfer and a specific weighting recipe. They do not overturn the negative result for Voutsinos tile-

Table 4.22. Paired full-PSI MAE differences; negative values favour the first method. The two ridge range comparisons use 97.5% intervals adjusted for two tests; the remaining intervals are descriptive 95% intervals. All use 5,000 protein-group bootstrap resamples.

Paired comparison	ΔMAE	Cluster-bootstrap CI
Ridge full range minus restricted	−0.02577	[−0.0338, −0.0183]
Ridge balanced minus restricted	−0.02996	[−0.0417, −0.0188]
ESM CNN minus ESM pointwise, full range	−0.00534	[−0.0102, −0.0009]
Scanning-pretrained CNN minus scratch	−0.00639	[−0.0099, −0.0030]
Quality-weighted ridge minus unweighted	+0.00401	[+0.0030, +0.0052]

label pre-training, which uses a different source endpoint and encoder.

4.2.3.14. Campaign Completion and Integrity

The completed snapshot on 6 November contains 633 complete jobs out of 635 planned units. The two remaining states await reviewed external-source and structure inputs; they are not failed training jobs. All nine pLM preflights and feature extractions, 540 ridge fits, 30 frozen-head fits, 30 LoRA fits, OOF collection, core calibration, locked W5-D transfer and reporting have completed. ProtT5 and Ankh now have results in every planned family cell.

The read-only review verifies sizes and SHA-256 hashes for 4,278 local artifact references (5.77 GB) and 2,986 completed Kaggle artifacts (3.07 GB), with no recorded mismatch. It also checks the 76 pinned analysis sources: 75 match the current bytes and one exactly reproduces its Windows-pinned hash after line-ending reconstruction. It confirms that the inherited source state remains unchanged. Fit metadata declares adapter changes in all 30 completed LoRA fits; the present review does not reload model tensors. Inventory counts distinguish physical caches/checkpoints from scientific observations (Appendix B). Hash agreement establishes artifact identity; it does not independently verify biological labels.

There are 41 local OOF recipes and 47 Kaggle recipes, listed completely in Table B.1. Each local recipe contains 367,236 rows: three predictions for each of the same 122,412 cells. Cell keys, labels, groups and outer folds agree with the pinned bundle; predictions are finite and there are no duplicate seed/cell keys. The current review independently recalculates MAE for all 41 local recipes, full metrics for the four matched core recipes, core probability Brier scores and locked-transfer metrics

from saved predictions. It also verifies all 32 files in the pinned dataset manifest and the 15 seed-specific inner split-role sets. The Kaggle metrics remain the recorded analysis, with its artifact identities rechecked. The 88 rows are correlated development estimates, including controls and learning-curve variants, not 88 independently trained model families or validation cohorts. The interrupted Kaggle tuning control has only one seed and is explicitly marked in the appendix.

4.2.3.15. Nine-Checkpoint Frozen-Feature Comparison

Table 4.23 reports the full local family grid in MAE. The four columns share the same evaluation population; B/D change permitted training coverage, while W5 changes explicit ordered context. These are frozen-feature ridge models, distinct from the matched neural-head experiment below. Figure 4.3 shows that model size does not give a monotonic improvement. In arm D, additional W5 context lowers point MAE for only three of nine checkpoints: ESM-C, ProtT5 and Ankh. No simultaneous family-wide significance claim is made from these ranks.

Table 4.23. Local frozen-feature ridge MAE for all nine checkpoints. "Only" includes the common auxiliary inputs; W5 adds ordered sequence context. All entries use three-seed OOF ensembles.

Checkpoint	B only	B + W5	D only	D + W5
ESM2-8M	0.4150	0.4288	0.3995	0.4018
ESM2-35M	0.4157	0.4280	0.4007	0.4022
ESM2-150M	0.4183	0.4296	0.4031	0.4041
ESM2-650M	0.4204	0.4319	0.4056	0.4071
ESM1b-650M	0.4203	0.4295	0.4054	0.4069
ESM1v-650M	0.4179	0.4289	0.4032	0.4050
ESM-C-300M	0.4203	0.4294	0.4046	0.4038
ProtT5	0.4211	0.4301	0.4056	0.4055
Ankh-base	0.4188	0.4279	0.4048	0.4035

Nested selection among the 36 candidates reaches MAE 0.3945 and positive AUROC 0.8409. Its 15 saved seed/fold choices exactly match the minimum saved inner MSE. ESM2-8M is selected five times and Ankh three times; several other checkpoints are selected once or twice (Table B.4). This evaluates a selection procedure, rather than retrospectively reporting the best outer-OOF family score. Its exploratory MAE difference from the Kaggle W5-D reference is -0.01335, with descriptive group-bootstrap interval $[-0.01719, -0.00967]$. The cross-runtime com-




Figure 4.3. Frozen pLM ridge results under full-range training. Points joined on the same row compare explicit context for one checkpoint; the connectors are not confidence intervals.

parison does not isolate the causal contribution of pretraining or model size.

4.2.3.16. Completed Matched Frozen–LoRA Evaluation

The same-runtime controls now permit a complete adaptation comparison (Table 4.24). LoRA-B reaches MAE 0.3637 and positive AUROC 0.8550; LoRA-D reaches 0.3650 and 0.8536, respectively. Relative to their own frozen controls, the MAE reductions are 9.8% and 6.5%. All four matched contrasts retain the favourable direction throughout the adjusted intervals in Table 4.25. This supports adapting this backbone under the specified development protocol; it does not establish that LoRA will improve every pLM, assay or final deployed model.

Table 4.24. Matched local ESM2-35M results. MAE uses all 235 peptides; positive AUROC/AP use 184 eligible peptides and negative AUROC uses 110. Higher ranking metrics are better.

Recipe	MAE	AUROC+	AP+	AUROC−
Frozen-B	0.4034	0.8263	0.4554	0.7541
Frozen-D	0.3904	0.8246	0.4544	0.7667
LoRA-B	0.3637	0.8550	0.5517	0.7921
LoRA-D	0.3650	0.8536	0.5474	0.8028

Table 4.25. Paired local contrasts: LoRA minus its frozen control. Confidence intervals use 5,000 protein-group resamples; 98.75% intervals adjust a post-hoc family of four comparisons. Negative MAE differences and positive AUROC differences favour LoRA.

Comparison / metric	Δ	95% CI	98.75% CI
LoRA B − frozen / MAE	-0.0397	[-0.0470, -0.0324]	[-0.0490, -0.0306]
LoRA B − frozen / AUROC+	0.0288	[0.0209, 0.0366]	[0.0188, 0.0389]
LoRA D − frozen / MAE	-0.0254	[-0.0318, -0.0191]	[-0.0339, -0.0175]
LoRA D − frozen / AUROC+	0.0289	[0.0212, 0.0363]	[0.0192, 0.0387]




Figure 4.4. Matched adaptation evidence. (a) Ensemble MAE and individual seed results; (b) paired MAE differences with multiplicity-adjusted group-bootstrap intervals. The seeds share the outer folds and are not independent cohorts.

Seed-level MAE differs materially from the ensemble (Table B.2). For LoRA-B, single-seed MAEs are about 0.378–0.379, while averaging their predictions gives 0.3637. Consequently, the ensemble result cannot be assigned to a single checkpoint. All seeds improve on their matched frozen controls, but shared outer folds prevent treating the seed results as independent replications. Selected epochs are short: frozen B/D have median 1, LoRA-B median 3 and LoRA-D median 2 (Table B.3). They are chosen by inner validation, not by outer performance.

Arm choice remains a trade-off. LoRA-D minus LoRA-B MAE is $+0.00133$, with descriptive 95% interval $[-0.00295, 0.00554]$. The near tie does not establish that restricted training is generally preferable. Table 4.26 shows that D improves the

PSI > 5 stratum while B is better at PSI ≤ 3. The highest stratum has no eligible positive-event AUROC peptides, because its event range is constrained; it still contributes to regression. Stratum intervals are exploratory.

Table 4.26. LoRA peptide-macro MAE by WT-PSI stratum. The final column is the paired D-minus-B difference with a descriptive 95% protein-group interval; n counts peptides.

WT PSI	n	LoRA-B	LoRA-D	$D - B$ (95% CI)
≤ 3	91	0.3884	0.4002	0.0118 [0.0043, 0.0194]
$(3, 4]$	85	0.3812	0.3815	0.0003 [-0.0056, 0.0064]
$(4, 5]$	36	0.3092	0.3033	-0.0059 [-0.0138, 0.0027]
> 5	23	0.2863	0.2613	-0.0250 [-0.0439, -0.0056]

LoRA-B also has lower MAE than the Kaggle frozen-ESM CNN-D by 0.02069 PSI, with descriptive interval $[-0.02659, -0.01489]$. This is useful for prioritising candidates, but head architecture, runtime and adaptation all differ. The matched local contrasts provide the more specific evidence for adapter training. Kaggle and local ESM2-35M ridge controls are numerically close but are kept separate, rather than relabelled as additional independent seeds.

4.2.3.17. Residual Diagnostics and Difficult Cases

A new calculation directly from the saved OOF predictions examines where the matched adaptation helps and fails. These are post-hoc descriptive diagnostics on W, not new independent tests or subgroup significance claims. Figure 4.5 retains every peptide, including 51 that worsen with LoRA-B and 71 with LoRA-D. The corresponding counts with lower MAE are 184 and 164. After averaging peptide differences within a protein group, B improves 176 groups and worsens 45; D improves 155 and worsens 66. Group counts describe a different weighting from peptide-macro MAE.

Removing each protein group in turn leaves the peptide-macro LoRA-minus-frozen MAE difference negative: ranges are [-0.0404, -0.0389] for B and [-0.0261, -0.0247] for D. This rules out a reversal driven by removal of any one recorded group; it does not establish robustness to simultaneous removal of several related groups or to unobserved biological dependence. LoRA-B fold MAEs range from 0.3384 to 0.3862 and LoRA-D from 0.3431 to 0.3882, so a global average should not be interpreted as




Figure 4.5. Matched per-peptide OOF errors for the three-seed ensembles on W. Each point is one peptide; points below the dashed equality line favour LoRA. Both panels use common scales. The spread is observed heterogeneity, not a confidence interval.

uniform performance. The worst LoRA-B peptide, CCDC17 tile 9, has MAE 0.9035 versus 0.8486 for frozen-B. It remains a failure case despite the average gain.

Table 4.27. OOF MAE conditional on the measured effect class ($\Delta = \Delta$PSI). Each metric averages errors within each eligible peptide, then over peptides in that class. Support counts differ from ranking eligibility, which requires at least three cells of each class.

Effect	Cells	Pep./grp.	Fr.-B	LoRA-B	Fr.-D	LoRA-D	Zero
$-1 < \Delta < 1$	108,782	235/221	0.3270	0.2879	0.3045	0.2843	0.3031
$\Delta \geq 1$	12,053	198/190	0.8187	0.7997	0.8972	0.8479	1.4155
$\Delta \leq -1$	1,577	151/144	1.2407	1.0385	1.1394	0.9510	1.2320

Table 4.27 shows substantially greater errors for large effects than for neutral cells. For $|\Delta\text{PSI}| \geq 1$, LoRA-B and D have MAE 0.8970 and 0.9084, respectively, versus 1.4127 for zero, over 13,630 cells, 232 peptides and 218 groups. The positive class has 12,053 cells; the negative class has only 1,577. LoRA-B's cell-micro signed residual ($\widehat{\Delta} - \Delta$) is -0.9504 for positive cells and $+1.0449$ for negative cells. The direction is consistent with underestimating effect magnitude, but does not isolate a biological mechanism or distinguish model shrinkage from measurement noise. These signed residuals have different weighting from the peptide-macro absolute errors in

the table.

Table 4.28. Three largest absolute cell errors for LoRA-B on W, selected after inspection. Positions are within the measured peptide; measured and predicted values are ΔPSI. These illustrate failures and are not clinical or mechanistic case validations.

Peptide	Fold	Position	Change	Measured	Predicted
P32881_IFNA8_5	2	17	Y→F	3.2866	-0.1573
P13942_COL11A2_20	1	18	R→I	3.1698	-0.2479
P32881_IFNA8_5	2	17	Y→M	3.0830	-0.2058

The difficult cases in Table 4.28 include sign reversals for strongly stabilising measured substitutions. Post-hoc tables by mutant amino acid and by WT–replacement pair are retained in the accompanying audit with support counts. Their uneven support and shared protein contexts prevent interpreting a high subgroup error as a causal residue-specific mechanism.

4.2.3.18. Probability Calibration and Locked Transfer

Table 4.29 distinguishes probabilistic quality from ranking. Both LoRA arms lower multiclass Brier score relative to their frozen controls and the inner-prior baseline. The peptide-macro LoRA-minus-frozen Brier differences are -0.01572 for B and -0.01349 for D, with descriptive 95% group intervals $[-0.01986, -0.01152]$ and $[-0.01736, -0.00970]$. However, positive-event ECE increases. Reliability curves in Figure 4.6 show overconfidence in high-probability bins, which contain fewer cells. A lower Brier score does not establish uniformly better calibration. The model cards currently mark these as CV-only calibrators and leave the final serving-model identifier list empty; model-specific lineage and final refitting remain necessary before inference integration.

Table 4.29. Out-of-fold three-class probability evaluation. Brier is the unnormalised sum across three classes; lower values are better. The prior uses inner-validation class frequencies. ECE refers only to the positive event and uses ten equal-width bins.

Recipe	Brier micro	Brier macro	Prior micro	ECE+
Frozen-B	0.1789	0.1787	0.2006	0.0129
Frozen-D	0.1795	0.1794	0.2006	0.0114
LoRA-B	0.1631	0.1630	0.2006	0.0163
LoRA-D	0.1659	0.1659	0.2006	0.0165

The locked transfer set contains 39,234 R/A/S substitutions across 1,410 peptides and 730 protein groups, with no recorded group overlap with W or scanning development data. Only the fixed W5-D recipe is evaluated. It obtains MAE 0.3991, compared with 0.4024 for predicting zero. The paired difference is -0.0033 with 95% interval [-0.0092, 0.0028], so the average regression advantage is not resolved. Positive AUROC is 0.8405 on 338 eligible peptides and AP is 0.6011; negative AUROC is only 0.5176 on 85 eligible peptides. Regression, positive ranking and negative ranking therefore have different transfer behaviour.

Table 4.30. Locked W5-D transfer by WT PSI. n counts peptides and n_+ counts peptides eligible for positive-event AUROC. The zero predictor provides a regression reference.

WT PSI	n	W5-D MAE	Zero MAE	n_+
≤ 3	524	0.3819	0.4319	231
$(3, 4]$	323	0.3918	0.4158	89
$(4, 5]$	306	0.3998	0.3843	18
> 5	257	0.4428	0.3470	0




Figure 4.6. Probability and transfer limitations. (a) Development OOF positive-event reliability, with the diagonal indicating agreement; (b) locked W5-D transfer MAE by WT PSI. T uses a different population and does not evaluate LoRA.

The transfer failure is concentrated in high-WT-PSI peptides: above 5, W5-D MAE is 0.4428 versus 0.3470 for zero (Table 4.30). Across T, the observed positive-

cell rate is 0.0512, below mean predicted probability 0.0895. Although the three-class Brier score of 0.1291 beats the development-prior baseline of 0.1348, positive probabilities shift upward relative to the observed rate. T contains only R, A and S replacements (25,479, 9,278 and 4,477 cells), uses replicate-1 labels and comes from a previously explored same-laboratory source. These results do not demonstrate independent external validity, clinical utility or transfer of the LoRA gain.

4.2.3.19. Additional Controls and Practical Consequences

The complete Kaggle record also contains composition, unordered-context, substitution-only, learning-curve, quality-weighting and scanning-label controls (Table B.1). The substitution-only ridge encodes WT and replacement identity as separate one-hot blocks; despite its saved "pair" name, it does not add interaction terms or W5 positions. In arm D it reaches MAE 0.4017 and AUROC 0.8092, compared with ordered W5 at 0.4078 and 0.8319. Composition gives 0.4075/0.8109 and unordered context 0.4060/0.8258. Thus explicit ordering improves positive ranking in these controls without minimising MAE. W3-B similarly has slightly lower MAE than W5-B (0.4331 versus 0.4336), while W5-B has higher positive AUROC (0.8312 versus 0.8280). Context benefit depends on the outcome being optimised.

Training-coverage controls A/B/C/D give W5 MAEs 0.4711, 0.4336, 0.4177 and 0.4078 as the training threshold increases from 3 to 4 to 5 to the full range. These are full-range evaluations, so their values cannot be compared directly with the old restricted benchmark. Scanning augmentation of ridge gives MAE 0.4047 using replicate 1 and 0.4048 using the replicate mean, versus 0.4078 without the extra source. The matched scanning CNNs likewise reach about 0.3872/0.3873. The observed point differences do not establish an advantage from averaging replicate labels.

For W5-D, mean single-seed MAE decreases from 0.4413 at one-quarter training data to 0.4189 at one-half, 0.4107 at three-quarters and 0.4078 at full size. Ensemble MAEs are 0.4154, 0.4113, 0.4083 and 0.4078. The large ensemble gain at small fractions must not be misread as a learning curve of one fitted model. Fractional training subsets vary by seed, so their ensemble can have seen a union larger than the stated fraction. The frozen ESM CNN-D improves MAE for 156 of 235 peptides, grouped into 150 of 221 protein groups, relative to W5-D; the advantage is not universal.

The scanning pre-training comparison also examines the 20 substitution-pair types present in scanning and the other 360 types. Improvements are observed outside the 20 scanned pair types, but the subsets remain part of the same development population. This is evidence about the tested representation and label-transfer procedure, not a newly independent transfer cohort. These controls and the negative weighting result remain in the full appendix rather than being removed from the record after a stronger model appears.

Recorded completed-attempt durations total about 14.1 hours for frozen tuning and 36.0 hours for LoRA tuning, versus about 1.4 hours for the 540 ridge fits (Table B.5). Paused/resumed jobs may omit earlier attempt time, so these totals are not exact GPU-active time or the wall-clock duration of the campaign. They still identify adaptation as the main recorded computational cost. The transfer inference timer is for prediction only and does not include fitting, feature preparation, downloads or service startup.

The executable research graph is finished. The next research tasks are reviewed external/structure inputs, independent transfer checks and a compatible final serving refit, calibrator, lineage card and export. The application tasks remain separate. A report marked complete is neither release acceptance nor automatic promotion of the lowest development MAE.

Domain and software integration. The earlier domain-gate study completed both tiers: OOF AUROC was 0.9111 using screen PSI and 0.8154 using sequence-derived features. This estimates membership of the restricted baseline's training domain, not per-mutation prediction accuracy. Raw screen PSI and intrinsic WT PSI are different estimators, so applying the intrinsic threshold directly to screen PSI is invalid. The baseline service still requires the delivered gate adapter and its borderline state. A future full-PSI serving model would need its own domain and calibration policy.

The local React/FastAPI baseline, reference ETL and recorded baseline tests exist. The newer workspace interface is an interactive design prototype with synthetic scores and tab-memory state; it does not establish backend inference or durable storage. Projects/history, peptide and protein jobs, experimental import/comparison and local PostgreSQL acceptance remain open. The serving model remains the calibrated restricted-PSI ridge baseline; none of the new research scores constitutes automatic

model promotion or completion of the research and software gates.

4.2.3.20. Assessment of the Research Questions

Table 4.31 connects the questions in the introduction to the completed experiments. It separates measured changes from explanations and identifies the evidence needed before a stronger claim. The questions organise the current progress report; they do not imply that the entire historical sequence was planned before its first experiment.

Table 4.31. Research questions, current evidence and boundaries

RQ	What is supported	What remains open
RQ1	Expanding training coverage helps ridge under both the restricted-test follow-up and the full-PSI protocol. Full-PSI gains concentrate at high WT PSI.	Added protein groups and wider label coverage change together. Full-range training is not uniformly preferable for LoRA; an independent population is needed to assess this trade-off.
RQ2	Ordered W5 improves restricted-benchmark ranking. Matched frozen-ESM CNN improves full-PSI MAE over its pointwise control.	CNN/mCNN point ranks do not establish a universal architecture winner. Feature recipes, model sizes and runtimes are not fully matched across families.
RQ3	Scanning mutation-label pre-training helps its tested one-hot CNN. Historical tile-score pre-training does not improve the tested gated model.	These interventions change source labels, representation and architecture. Their results cannot identify one universal transfer mechanism or establish transfer to an independent assay.

RQ	What is supported	What remains open
RQ4	Matched LoRA reduces OOF MAE in both B and D with adjusted paired intervals supporting the reductions. All three seeds improve over their matched controls.	LoRA has greater recorded computation cost. Full fine-tuning is not evaluated in this campaign; cost-normalised benefit, deployment latency and independent replication remain unmeasured.
RQ5	Group-aware OOF evaluation, seed/fold diagnostics and calibration quantify development behaviour. Locked W5-D transfer has useful positive ranking but unresolved mean MAE gain.	High-PSI transfer and probability shift persist. No LoRA result on T, prospective wet-lab utility, intact-protein validation or independent external confirmation is available.

Contribution assessment. The verified contributions are a traceable label/QC and grouped-evaluation workflow, compatible baseline and adaptation comparisons, retained unsuccessful controls, and an explicit account of uncertainty and transfer limits. These are methodological and empirical contributions within the studied reporter assay. They are not evidence that combining a pLM with convolution or adapters is itself a new architecture. The software contribution is a working baseline and an expanded design; implementation and acceptance of the expanded workflows remain separate milestones.

Next experiments and decision criteria. The highest scientific priority is a new validation design with a compatible endpoint, audited protein/sequence overlap and an explicit source history. Freeze the candidate recipe and analysis plan before inspecting its outcome; do not reuse the inspected T set to select among candidates. Report peptide/group-macro regression, positive and negative ranking, large-effect residuals, WT-PSI strata and probability reliability together. A favourable ranking score alone is insufficient to claim accurate effect sizes or calibrated probabilities.

Further capacity or transfer experiments should specify matched controls and computational budgets. Final serving refit and export should preserve the chosen ensemble and calibration policy, or re-evaluate them when changed. These are proposed steps; no new training or validation experiment was executed to update this report.

4.2.3.21. Remaining Evaluation

The following parts of the plan have no results in this version of the thesis; no number is given for them.

- **Merging external GPS labels and repeating the learning curve on the enlarged set.** Not run: the only audited source (Table 4.19) did not pass its gate. Other candidate sources (for example Timms et al., Shimshon et al., Bekturova et al. and a recent preprint on disease mutations that disrupt degrons) have not been audited, and their terms of use have not been read.

- **Independent validation.** Development OOF and locked same-laboratory transfer are available. Testing on labels that did not take part in any design decision, including the C-terminal data of Table 4.19, has not been done. The completed held-source route is locked to the prespecified W5 full-range recipe; it is not a test for selecting among all new pLMs. The source was explored historically, so it is not a wholly untouched external assay.

- **Final serving artefacts and further transfer.** The matched local LoRA comparison, CV calibration and locked W5 transfer are complete. CNN, LoRA and family candidates still require a model-specific final refit, calibration lineage and export before serving. LoRA transfer beyond development remains untested. Alternative tile-label pre-training or joint-training designs remain separate untested questions.

- **Comparison of the ranking with simple rules.** Only a random ranking was used as reference (Section 4.2.3.9).

- **Separating the region of PSI_{WT} from the protein.** It needs pairs of peptides of the same protein on both sides of the threshold, which the present data may not contain (Section 4.2.3.5).

- **Expanded local software acceptance and tests with users.** Baseline web/API code exists, but project/history, batch/protein and import/comparison extensions and their acceptance remain pending (Section 4.3); historical checks do not verify this expanded scope.

4.2.4. Discussion

What the initial measurements support. (i) A ridge regression on 180 features is a strong baseline for the substitution effect: it is above the frozen ΔPAP baseline with an interval that excludes zero, and none of the five larger designs tried (the sigmoid-gated networks, FiLM, the bilinear form, the cross-product ridge and the retrained transformer architecture) beat it under the fixed criteria. (ii) Training labels from peptides just above the degron threshold improve the out-of-fold AUROC on the original test cells, and this gain is not caused by an obvious collapse of the label. (iii) The gain is not simply proportional to the number of clusters, but the data do not yet separate wider coverage from more clusters. (iv) The gain from the relaxed threshold does not depend on how proteins are grouped: it is above zero under every informative partition tried, including grouping by accession. (v) The score of ridge M3 can be turned into a probability with a Platt transform that is better than the raw score and than the base rate, and the top 10% of the substitutions of a peptide contains about four times more positive cells than a random choice.

What the follow-up adds. The subsequent studies establish a wider-context ridge improvement on the original test and useful frozen-ESM positional mixing on the new full-PSI task. They do not turn the earlier inconclusive architecture tests into positive confirmations. Full-range training, matched representation/head controls and negative transfer/weighting results are the main new contributions (Section 4.2.3.13).

What remains unsupported. The thesis does not claim a novel architecture or an independently validated architecture winner. The initial interaction gate changes sign between seeds. The published Degformer checkpoint is not held out; the later three-seed clean-cluster retraining is a distinct comparison and did not establish an advantage over ridge. The thesis does not claim that more labels make a larger model win; the gated network is still rising, but it is below ridge at every level that was run. It

does not claim that pre-training on tile labels helps: the one design tried was not better than random initialisation and was below ridge. It does not claim that the external labels of Koren et al. can be merged: they did not pass the gate. It makes no claim of external validation of the probabilities or of the ranking.

Threats to validity.

- The benchmark is a development benchmark on a data set that has been examined several times; the out-of-fold numbers are not an external validation. The original AUROC and the full-PSI MAE describe different populations and cannot be combined into a single progress score.
- The three seeds share one outer partition, and the confidence intervals are conditional on the stored predictions. Most comparisons are exploratory; adjusted families are identified explicitly. There is no global correction covering the entire sequence of development studies.
- The threshold of 4.0 was fixed before the sensitivity grid, but only after the benchmark and a first look at the number of peptides it adds; the near coincidence with the maximum of the grid is not evidence that the way it was chosen was sound.
- The principal saturation evaluation labels come from the Zhang reporter assay. Scanning and saturation are distinct libraries from the same laboratory; tile-label pre-training uses a separate source endpoint. Transfer to a new independent assay remains untested.
- The added peptides pass through the same label pipeline and so inherit its assumptions (the PSI_{WT} reference from synonymous cells, the average of two halves).
- The coarsest partition tested still has 71 groups for 91 peptides, so robustness to a split by protein family is untested; the absolute scores change with the partition.
- The Platt calibrator is fitted on a pool that includes the added peptides, and its probabilities are about 13% too low for the benchmark peptides; the criterion

"better than the raw score" is a low bar, because the raw score is worse than the base rate.

- The pre-training result concerns one design and one encoder; the ranking is compared only with a random ranking.

4.2.5. Reproducibility of the Reported Results

Tables, figures and numerical summaries are generated from the recorded experimental outputs using consistent filtering, aggregation and rounding rules. The experimental setup specifies the data, protein-cluster partitions, seeds and evaluation metrics; each result is interpreted with the controls and limitations of its experiment. The underlying records retain the configurations and input identities needed for computational reproduction. These internal records support traceability, while the thesis presents the scientific methods, results and their interpretation.

4.3. Software Testing Plan

4.3.1. Functions Under Test

The target covers UC-01 to UC-10 of Chapter 1. Functions include scoring, ranking and export; protein selection and ClinVar annotations; model and reference evidence; batch and protein jobs; experimental import and comparison; and persistent projects and history. The recorded CLI verification below covers numerical consistency for the original scoring and export path only. Baseline web/API code and historical test records exist, but these tests have not been rerun here and do not verify the new workflows. The expanded local acceptance scenarios are specified later in this chapter.

4.3.2. Approach

The prototype is a thin layer over a research model, so the main risk is that it computes something different from what was evaluated in Section 4.2. The approach is therefore *back-to-back testing*: the prototype path is compared with the training and evaluation path of the research runner on the 92 337 cells of the 176 peptides. The 180 features are rebuilt in the prototype by an independent implementation (16 620 660 values are compared), so the comparison is not a code path checked against itself.

Baseline input-validation tests exist in the application source. Their historical results are not new execution evidence in this chapter. New domain, job, import, annotation and history cases below remain pending implementation and execution.

4.3.3. Criteria for Test Success or Failure

A check passes when the largest absolute difference between the two paths is below 10^{-9}. The check of the exported file is asserted at 5×10^{-9} in the code, because values are written with ten significant digits; the measured differences are below 10^{-9} for it as well. A test fails when any difference exceeds its limit. For the new workflows, a functional case also requires the specified item states, aligned counts, warnings and durable/deleted records. A skipped or pending case is not a pass; compatible-metric fixtures need independently calculated answers.

4.3.4. Suspension Criteria and Restart Requirements

The verification script stops at the first failed assertion and runs no later check. The command-line tool refuses to run if the model file is missing. Restart: rebuild the frozen model artefact and run the verification procedure again from the beginning.

4.3.5. Test Deliverables

The verification procedure, its machine-readable execution report, the calibration results and Table 4.33 of this chapter form the recorded numerical-consistency evidence. The pending local acceptance work additionally requires dated functional, recovery and resource-use reports.

4.4. Test Management

4.4.1. Test Activities

Executed: building the model and the caches, running the verification script (11 checks). Not executed for the expanded first-release scope: local integration, job/import/history tests, resource measurement and user evaluation. Historical baseline web/API checks are a separate record.

4.4.2. Test Environment

Linux under WSL2 on one development computer, CPU only; Python 3.12.3 and NumPy 2.5.3. The verification needs about 1.2 GB of memory. The model file

and the caches are generated by the scripts and are not stored in the repository.

4.4.3. Resources and Allocation

One tester, the author of the thesis, who is also the developer; there is no independent tester.

4.4.4. Risks

- Back-to-back tests show agreement with the research code, not that the science is right: an error shared by both paths (for example in the definition of the label) would not be found.
- The probabilities are about 13% too low for peptides of the original benchmark domain (Section 4.2.3.9); ranking is not affected.
- The historical CLI has only a printed domain warning. The baseline web gate still needs R3 integration; whole-protein processing must not hide unknown, borderline or out-of-domain tiles.
- User imports can mix endpoints or mis-map residues; validation and separate assay comparisons are required. Persistent jobs/history add crash recovery and file-cleanup risks.
- The model was evaluated only on a development benchmark; no result in this chapter supports a claim of external validity.

4.5. Test Scenarios and Test Cases

4.5.1. Test Scenarios

S1: score a tile given as a sequence. S2: score a tile of a protein given by its UniProt accession. S3: export the scores as CSV and read them back. S4: reject invalid input; the retained CLI verification report does not cover this scenario.

4.5.2. Expanded Local Acceptance Scenarios

Table 4.32 defines the additional scenarios. All are pending; test IDs map to the system SRS and test plan. No public-host deployment is required.

Table 4.32. Planned first-release local acceptance scenarios; no execution result claimed

Case group	Expected evidence
DOM-01, ANN-01	Correct gate estimator/borderline handling; ClinVar and reference mapping, source states and attribution.
BATCH-01 to 06	Bounds, single-tile equivalence, coverage/overlapping contexts, partial failures, cancellation, restart without duplicates and complete exports.
IMP-01 to 04	CSV/TSV validation/commit, WT/replicate alignment, missing/conflicting data and hand-checked assay-compatible metrics.
HIST-01 to 03	Explicit local persistence, immutable reopen/rerun after source changes, confirmed dependency/file deletion.
NF-07, DEP-01/02	Recorded local resource use, clean local installation and restart of the same instance.

4.5.3. Test Cases

Table 4.33 lists the executed cases, which cover S1 to S3 through the comparison of the scores computed by the prototype with those of the research path. The cases of S4 (length different from 28, a character outside the 20 amino acids, an unknown accession, a tile beyond the end of the protein, a tile with a non-standard residue, a missing model file) are specified by the CLI checks; application source contains baseline tests, but no new execution report is added for them here. Expanded first-release cases are specified in Table 4.32.

4.6. Test Evaluation

All 11 executed cases passed; the largest absolute difference is 4.4e-10 (Table 4.33). The prototype therefore reproduces the research model on 92 337 cells, including the scores of the outer-test folds of all fifteen (seed, fold) pairs. This establishes consistency only. It does not show that the predictions are correct (Section 4.2 addresses that, on a development benchmark), and it says nothing about input validation, the interface, the response time (the target of Chapter 1 has not been measured) or usability **[PENDING]**.

The first-release software acceptance remains pending. Existing CLI measurements cannot verify project persistence, experimental-data comparison, ClinVar mapping states, whole-protein coverage or job recovery. Local acceptance must report these cases and the actual computer/resource conditions; public deployment, Internet

Table 4.33. Executed test cases: agreement of the prototype with the research runner. The tolerance is 10^{-9}.

Test case (back-to-back consistency check)	Max. abs. difference	Passed
TC-01: Labels: label pipeline vs. cached labels	0.0e+00	Yes
TC-02: Features: independent featuriser in the prototype vs. cached matrix	1.1e-16	Yes
TC-03: Raw score: prototype vs. trained ridge model	4.4e-16	Yes
TC-04: Platt probability: prototype vs. scikit-learn	3.3e-16	Yes
TC-05: Isotonic probability: prototype vs. scikit-learn	1.7e-13	Yes
TC-06: UniProt accession $\rightarrow$ tile $\rightarrow$ score: vs. training path	0.0e+00	Yes
TC-07: UniProt accession $\rightarrow$ tile $\rightarrow$ probability: vs. training path	0.0e+00	Yes
TC-08: Exported CSV, raw score: vs. in-memory prediction	4.4e-10	Yes
TC-09: Exported CSV, probability: vs. in-memory prediction	4.8e-11	Yes
TC-10: Features of the 91 benchmark peptides: prototype vs. cache	1.1e-16	Yes
TC-11: Outer-test scores of all 15 (seed, fold) pairs: prototype path vs. runner	4.4e-16	Yes

availability and hosted performance are outside the required scope.

PART 3. CONCLUSION

1. Provisional Findings at the Progress Cutoff

1.1. Knowledge and Skills

The work has produced a traceable computational workflow from experimental read counts to mutation labels, protein-group splits and model comparisons. The initial restricted-PSI studies established ridge as a strong baseline and showed that extending training-label coverage can help even when a learning curve within the original distribution is nearly flat. Negative findings on interaction designs and tile-label pre-training were retained rather than replaced by unsupported architecture claims.

The full-PSI extension evaluates 235 peptides in 221 protein groups. Full-range W5 ridge training reduces macro MAE from 0.43358 to 0.40780 PSI. Matched frozen-ESM controls provide development evidence for positional mixing: the CNN reaches 0.38435, compared with 0.38969 for pointwise prediction. Scanning-label pre-training helps its one-hot CNN control, whereas quality weighting does not help ridge. These are conclusions about specified populations and training recipes, not a universal model ranking.

The completed local expansion adds all nine planned pLM checkpoints, 540 frozen-feature ridge fits and 60 matched ESM2-35M frozen/LoRA fits. LoRA reduces MAE from 0.4034 to 0.3637 in arm B and from 0.3904 to 0.3650 in arm D; the adjusted paired intervals support both improvements. Larger frozen encoders do not consistently improve performance, and the nested family selector reaches 0.3945 MAE. B and D remain close overall while differing across WT-PSI strata. These results support a specified adaptation recipe and a comparison procedure rather than a universal family ranking.

Out-of-fold three-class calibration is complete for the four matched core recipes. LoRA improves Brier score, but positive-event ECE and high-probability reliability still expose errors. The locked W5-D transfer evaluation is also complete: positive AUROC is 0.8405, whereas the MAE difference from predicting zero is -0.0033 with interval [-0.0092, 0.0028]. The contrast between ranking and regression limits the transfer claim.

1.2. Program and Practical Application Potential

The calibrated restricted-domain ridge baseline has an inference path numerically consistent with the research runner. A local React/FastAPI implementation supplies single-peptide results, reference lookup, annotations and traceable exports. Its intended use is to shortlist substitutions for experimental follow-up, with visible model, source and domain evidence. The newer workspace UI demonstrates the intended interactions with synthetic fixtures; it is not an integrated persistent application. Projects/history, durable peptide/protein jobs, experimental import/comparison, PostgreSQL integration and their local acceptance remain unfinished as of 6 November 2026. The serving model has not been replaced by a development leaderboard result.

2. Limitations and Challenges

Predictive evidence comes from public reporter-assay sources that have informed several design decisions, including a locked transfer subset from a previously explored source. Protein-group splitting reduces detectable overlap but does not establish complete biological independence; thousands of mutation cells do not create thousands of independent peptides. The original 91-peptide evaluation and the full-PSI task have different populations and metrics. Most follow-up comparisons are exploratory, and the seeds share an outer partition.

The executable local graph is complete; reviewed external-source and structure inputs remain pending. The locked transfer set covers R/A/S substitutions with replicate-1 labels in the same laboratory. High-WT-PSI regression and positive-probability shift show that favourable development ranking does not establish robust transfer. LoRA has not been evaluated on T. Runtime, precision and feature choices also differ across model families. CV calibrators are not final serving artifacts; model-specific final refit, lineage cards and export remain unfinished. Earlier baseline calibration and its domain gate cannot be assumed valid for a new serving model. The gate is not yet integrated correctly into the baseline application. No new wet-lab validation, E3-specific recognition, intact-protein prediction or clinical inference has been established.

3. Priorities for the Next Research Phase

Preserve the completed OOF record, paired uncertainty and unsuccessful controls. Investigate the high-PSI transfer errors and probability shift with an explicitly designed new evaluation, rather than using the already inspected T set to choose among pLMs. New external and structure extensions require reviewed inputs and overlap/rights audits. Any model selected for inference needs an architecture-specific final refit, calibration, domain policy, model card and export; the benefit of the three-seed ensemble must be retained or re-evaluated if the serving configuration changes.

Complete the agreed local software workflows and check numerical consistency, correct domain handling, coordinate/assay alignment, saved-work recovery and measured resource use. Update the remaining installation and acceptance material from executed evidence. Further data sources or biological tests require endpoint, homology and source-rights audits before any broader claim.

REFERENCES

[1] A. Varshavsky, "N-degron and C-degron pathways of protein degradation," *Proceedings of the National Academy of Sciences*, vol. 116, no. 2, pp. 358–366, 2019. DOI: 10.1073/pnas.1816596116.

[2] I. Koren *et al.*, "The eukaryotic proteome is shaped by E3 ubiquitin ligases targeting C-terminal degrons," *Cell*, vol. 173, no. 7, 1622–1635.e14, 2018. DOI: 10.1016/j.cell.2018.04.028.

[3] W. E. Balch, R. I. Morimoto, A. Dillin, and J. W. Kelly, "Adapting proteostasis for disease intervention," *Science*, vol. 319, no. 5865, pp. 916–919, 2008. DOI: 10.1126/science.1141448.

[4] V. Voutsinos *et al.*, "A near-complete map of human cytosolic degrons and their relevance for disease," *Science Advances*, vol. 12, no. 6, eadz3483, 2026. DOI: 10.1126/sciadv.adz3483.

[5] D. M. Fowler, C. L. Araya, S. J. Fleishman, *et al.*, "High-resolution mapping of protein sequence-function relationships," *Nature Methods*, vol. 7, no. 9, pp. 741–746, 2010. DOI: 10.1038/nmeth.1492.

[6] H.-C. S. Yen, Q. Xu, D. M. Chou, Z. Zhao, and S. J. Elledge, "Global protein stability profiling in mammalian cells," *Science*, vol. 322, no. 5903, pp. 918–923, 2008. DOI: 10.1126/science.1160489.

[7] Z. Zhang *et al.*, "Elucidation of E3 ubiquitin ligase specificity through proteome-wide internal degron mapping," *Molecular Cell*, vol. 83, no. 18, 3377–3392.e6, 2023. DOI: 10.1016/j.molcel.2023.08.022.

[8] K. A. Matreyek, L. M. Starita, *et al.*, "Multiplex assessment of protein variant abundance by massively parallel sequencing," *Nature Genetics*, vol. 50, no. 6, pp. 874–882, 2018. DOI: 10.1038/s41588-018-0122-z.

[9] F. B. Larsen *et al.*, "Comprehensive degron mapping in human transcription factors," *bioRxiv*, 2025, Preprint, version 1; cited version inspected. DOI: 10.1101/2025.05.16.654404.

[10] M. Zheng *et al.*, "MetaDegron: multimodal feature-integrated protein language model for predicting E3 ligase targeted degrons," *Briefings in Bioinformatics*, vol. 25, no. 6, bbae519, 2024. DOI: 10.1093/bib/bbae519.

[11] N. A. Szulc, F. Stefaniak, M. Piechota, *et al.*, "DEGRONOPEDIA: A web server for proteome-wide inspection of degrons," *Nucleic Acids Research*, vol. 52, no. W1, W221–W232, 2024. DOI: 10.1093/nar/gkae238.

[12] H. Xu, R. Hu, and Z. Zhao, "DegronMD: Leveraging evolutionary and structural features for deciphering protein-targeted degradation, mutations, and drug response to degrons," *Molecular Biology and Evolution*, vol. 40, no. 12, msad253, 2023. DOI: 10.1093/molbev/msad253.

[13] Alpine2048, *Degformer: Transformer model for internal and C-terminal degron prediction*, GitHub repository, commit 49ee52459967, Repository snapshot inspected 6 November 2026; publication year not established. [Online]. Available: https://github.com/Alpine2048/Degformer.

[14] J. Bernett, D. B. Blumenthal, D. G. Grimm, *et al.*, "Guiding questions to avoid data leakage in biological machine learning applications," *Nature Methods*, vol. 21, no. 8, pp. 1444–1453, 2024. DOI: 10.1038/s41592-024-02362-y.

[15] M. Steinegger and J. Söding, "MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets," *Nature Biotechnology*, vol. 35, no. 11, pp. 1026–1028, 2017. DOI: 10.1038/nbt.3988.

[16] A. E. Hoerl and R. W. Kennard, "Ridge regression: biased estimation for nonorthogonal problems," *Technometrics*, vol. 12, no. 1, pp. 55–67, 1970. DOI: 10.1080/00401706.1970.10488634.

[17] Z. Lin *et al.*, "Evolutionary-scale prediction of atomic-level protein structure with a language model," *Science*, vol. 379, no. 6637, pp. 1123–1130, 2023. DOI: 10.1126/science.ade2574.

[18] A. Vaswani *et al.*, "Attention is all you need," in *Advances in Neural Information Processing Systems 30*, 2017. [Online]. Available: https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

[19] E. J. Hu, Y. Shen, P. Wallis, *et al.*, "LoRA: Low-rank adaptation of large language models," in *International Conference on Learning Representations*, 2022. [Online]. Available: https://openreview.net/forum?id=nZeVKeeFYf9.

[20] B. Efron, "Bootstrap methods: another look at the jackknife," *The Annals of Statistics*, vol. 7, no. 1, pp. 1–26, 1979. DOI: 10.1214/aos/1176344552.

[21] Z. Zhang *et al.*, *Data accompanying the proteome-wide internal degron mapping study*, Mendeley Data, version 2, 2023. DOI: 10.17632/32h94v2yv2.2.

[22] NCBI, *GEO Series GSE240610*, Gene Expression Omnibus. [Online]. Available: https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE240610.

APPENDIX A: INSTALLATION AND USER GUIDE

A.1. Installation Requirements

A.1.1. Hardware Requirements

CPU inference runs on one local computer. Record actual OS, CPU, RAM and free disk in the local test report; batch/import/project storage requirements remain to be measured. A GPU is not required by the runtime application. Offline research training has separate requirements.

A.1.2. Software Requirements

The baseline uses a Python virtual environment and pinned backend dependencies, Node/npm with the frontend lockfile, and locally prepared reference data/model weights. The target adds local PostgreSQL and a job worker. Exact versions are recorded by the implementation's requirements/lockfiles; PostgreSQL/job integration is still pending. The research runner additionally uses its own packages and MMseqs2; these are not all required for serving predictions.

A.2. Local System Execution

There is one local web application. Public hosting, VPS, domain and TLS deployment are outside the required workflow. All application listeners must be bound to loopback.

A.2.1. Existing Baseline Commands

From the repository root, create/install the baseline backend environment with `make-Csystem/appvenv`, then run `make-Csystem/appdev-api`. The API listens on `http://127.0.0.1:8000`. On first run this command prepares a SQLite development database from the local research checkout; it does not start the planned PostgreSQL workspace or durable worker. The existing development ETL's default ClinVar subset must be recorded when interpreting annotations.

In a second terminal enter `system/app/frontend`, run `npmci`, then `npmrun dev----host127.0.0.1`. Open `http://127.0.0.1:5173`. Use the real backend; mock mode contains synthetic scores. These commands are read from the baseline guides and were not executed as application acceptance in this document-update task.

A.2.2. Target Local Workflow

[PENDING: implemented migrations and startup commands for the local PostgreSQL workspace, worker and new screens.] The final guide must reproduce reference preparation, local startup, a saved project, a peptide/protein job, a committed observation dataset, comparison/export, shutdown and reopening on the same machine. Copy database and workspace files together for recovery. Docker may package these same components; it is not a separate public/internal edition.

A.3. User Guide

The target sequence is: create/open a project; choose single peptide, peptide batch or whole protein; review syntax/domain/coverage; submit and inspect per-tile results; view ClinVar/reference evidence; import CSV/TSV with assay/units/replicates and fix validation errors; explicitly commit; compare compatible observations; export scores and provenance; reopen history. Unsaved single-tile previews are transient; saved work persists until deletion. Deletion presents dependencies and requires confirmation. **[PENDING: screenshots and an executed local walkthrough after implementation.]**

A.4. Offline Research Campaign Workflow

The research supervisor is separate from the application's API and job worker. It uses the pinned full-PSI data bundle, pretrained-weight caches and a CUDA environment. From PowerShell at the repository root, `./status-local.cmd` inspects the campaign. To execute or resume permitted work, `./run-local.cmd--hours2` starts a visible session. Request a safe pause using `./pause-local.cmd` or Ctrl+C in that session. Training commits recovery checkpoints approximately every 120 seconds; an abrupt window close can lose work since the last commit. These are operational commands, not commands executed during this thesis-update review.

The graph first checks the runtime/data identity and imported reference outputs, then verifies tokenizer alignment and extracts frozen features for each cached checkpoint. It runs the family ridge grid and matched frozen/LoRA tuning, collects OOF predictions, fits CV calibrators, evaluates the locked W5-D transfer recipe and writes the final report. Complete jobs are skipped when resuming the same compatible campaign; previous source output must remain available for inherited artifacts.

Changing code, data, protocol or relevant runtime properties can create a new identity and must not be bypassed by editing a manifest or copying arbitrary checkpoints.

On 6 November the runnable graph has 633 completed jobs and two pending input-dependent extensions. A session that reports zero executed jobs and then ends has no eligible compute left; restarting it alone does not provide the missing reviewed external or structure inputs. No further training is needed to reproduce the present analysis from the saved artifacts. Cached model/data work can be read offline; acquiring new sources or absent model/dependency files is a preparation step that may require connectivity.

For evidence regeneration, enter the research campaign directory and run `python analyze_local_output.py`. This reads saved OOF artifacts, verifies provenance and recomputes analysis without loading trained checkpoint objects. From the repository root, `python research/output_review_2026_11_06/audit.py` rechecks selected source hashes and exports the full evidence inventory. The report-asset generator then rebuilds tables and scientific figures from the exported JSON. Regeneration is an analysis task; it does not promote a candidate into the application.

APPENDIX B: SUPPLEMENTARY MATERIALS

B.1. Source Code and Data Availability

[PENDING: repository link and release; data are redistributed only where the terms of use allow.]

B.2. Additional Tables and Figures

The following tables preserve the complete campaign record, including controls that do not improve the selected metrics. All W rows share the same 235 peptides, 221 groups and 122,412 cells. Each three-seed row averages predictions per cell before calculating metrics. The two Kaggle frozen-head tuning controls have only seed 17; their scores are not directly equivalent to three-seed ensembles.

Training arms A, B and C restrict WT PSI to at most 3, 4 and 5, respectively; D uses the full range and E balances the full range by stratum and peptide. Validation/test remain full-range. In the family grid, “only” means pLM features with the common auxiliary features, and “context” additionally includes ordered W5 features. Pointwise, CNN and multi-window CNN entries use frozen ESM2 features on Kaggle; the local “frozen” and “LoRA” entries use the matched neural head described in Section 3.5.3. “Rep1” and “mean12” identify scanning-label pre-training targets. Nested-family rows evaluate inner selection, not a retrospective outer-score winner.

For ridge controls, “pair” encodes WT/replacement identity in separate 20-category blocks; it is not an interaction model and has no positional context, despite the saved W5 suffix. “Composition” adds whole-peptide amino acid frequencies, “unordered” adds local frequencies, and “ordered” adds position-specific context. “Sat-quality” changes training weights using replicate disagreement. “Scan-rep1” and “scan-mean12” add source-weighted scanning examples to ridge training with an explicit source indicator; the CNN-transfer rows instead use scanning pre-training. These are distinct interventions and should not be pooled into one transfer claim.

Table B.1. All saved OOF configurations. s is the number of seeds; MAE and event ranking are peptide-macro. Only rows with $s = 3$ are three-seed ensembles.

Origin	Recipe	s	MAE	AUC+	AP+	AUC−
Kaggle	cnn-transfer-rep1-D	3	0.3872	0.8425	0.5024	0.7132
Kaggle	cnn-transfer-mean12-D	3	0.3873	0.8391	0.4985	0.7185
Kaggle	cnn-transfer-scratch-D	3	0.3936	0.8291	0.4597	0.7098
Kaggle	composition-w5-B	3	0.4342	0.8111	0.4040	0.7456
Kaggle	composition-w5-D	3	0.4075	0.8109	0.4047	0.7506
Kaggle	ESM2-35M-cnn-B	3	0.3880	0.8506	0.5097	0.7484
Kaggle	ESM2-35M-cnn-D	3	0.3844	0.8488	0.5095	0.7550
Kaggle	ESM2-35M-cnn-E	3	0.3856	0.8474	0.5066	0.7540
Kaggle	ESM2-35M-context-B	3	0.4281	0.8432	0.4924	0.7095
Kaggle	ESM2-35M-context-D	3	0.4023	0.8445	0.4954	0.7301
Kaggle	ESM2-35M-frozen-B	1	0.4071	0.8233	0.4484	0.7512
Kaggle	ESM2-35M-frozen-D	1	0.3919	0.8221	0.4486	0.7657
Kaggle	ESM2-35M-mcnn-B	3	0.3855	0.8499	0.5036	0.7469
Kaggle	ESM2-35M-mcnn-D	3	0.3850	0.8463	0.5042	0.7570
Kaggle	ESM2-35M-mcnn-E	3	0.3838	0.8470	0.5064	0.7591
Kaggle	ESM2-35M-only-B	3	0.4158	0.8109	0.4291	0.7827
Kaggle	ESM2-35M-only-D	3	0.4008	0.8131	0.4340	0.7868
Kaggle	ESM2-35M-pointwise-B	3	0.4004	0.8375	0.4656	0.7440
Kaggle	ESM2-35M-pointwise-D	3	0.3897	0.8375	0.4739	0.7515
Kaggle	ESM2-35M-pointwise-E	3	0.3886	0.8357	0.4712	0.7557
Kaggle	Nested family	3	0.3975	0.8367	0.4788	0.7578
Kaggle	onehot-cnn-B	3	0.3997	0.8304	0.4575	0.7030
Kaggle	onehot-cnn-D	3	0.3936	0.8291	0.4597	0.7098
Kaggle	onehot-cnn-E	3	0.3947	0.8267	0.4564	0.7166
Kaggle	onehot-mcnn-B	3	0.3985	0.8267	0.4516	0.7046
Kaggle	onehot-mcnn-D	3	0.3935	0.8293	0.4588	0.7199
Kaggle	onehot-mcnn-E	3	0.3921	0.8289	0.4592	0.7200
Kaggle	onehot-pointwise-B	3	0.4059	0.8245	0.4299	0.7129
Kaggle	onehot-pointwise-D	3	0.3955	0.8269	0.4424	0.7264
Kaggle	onehot-pointwise-E	3	0.3920	0.8235	0.4426	0.7338

Continued on next page

Origin	Recipe	s	MAE	AUC+	AP+	AUC−
Kaggle	ordered-w3-B	3	0.4331	0.8280	0.4511	0.6927
Kaggle	ordered-w5-A	3	0.4711	0.8192	0.4436	0.6602
Kaggle	ordered-w5-B	3	0.4336	0.8312	0.4632	0.6745
Kaggle	ordered-w5-C	3	0.4177	0.8314	0.4606	0.6875
Kaggle	ordered-w5-D	3	0.4078	0.8319	0.4614	0.6931
Kaggle	ordered-w5-D-fraction0.25	3	0.4154	0.8231	0.4468	0.6925
Kaggle	ordered-w5-D-fraction0.5	3	0.4113	0.8280	0.4525	0.6975
Kaggle	ordered-w5-D-fraction0.75	3	0.4083	0.8297	0.4555	0.6983
Kaggle	ordered-w5-E	3	0.4036	0.8275	0.4499	0.7109
Kaggle	pair-w5-B	3	0.4149	0.8093	0.4024	0.7458
Kaggle	pair-w5-D	3	0.4017	0.8092	0.4040	0.7499
Kaggle	sat-only-D	3	0.4078	0.8319	0.4614	0.6931
Kaggle	sat-quality-D	3	0.4118	0.8307	0.4579	0.6918
Kaggle	scan-mean12-D	3	0.4048	0.8334	0.4643	0.6963
Kaggle	scan-rep1-D	3	0.4047	0.8334	0.4643	0.6964
Kaggle	unordered-w5-B	3	0.4316	0.8260	0.4414	0.7096
Kaggle	unordered-w5-D	3	0.4060	0.8258	0.4399	0.7199
Local	Ankh-base-context-B	3	0.4279	0.8426	0.4949	0.7097
Local	Ankh-base-context-D	3	0.4035	0.8440	0.4988	0.7310
Local	Ankh-base-only-B	3	0.4188	0.8075	0.4350	0.7822
Local	Ankh-base-only-D	3	0.4048	0.8088	0.4396	0.7882
Local	ESM1b-650M-context-B	3	0.4295	0.8359	0.4773	0.6814
Local	ESM1b-650M-context-D	3	0.4069	0.8360	0.4752	0.7032
Local	ESM1b-650M-only-B	3	0.4203	0.8016	0.4005	0.7431
Local	ESM1b-650M-only-D	3	0.4054	0.8024	0.4088	0.7547
Local	ESM1v-650M-context-B	3	0.4289	0.8384	0.4838	0.7009
Local	ESM1v-650M-context-D	3	0.4050	0.8378	0.4814	0.7187
Local	ESM1v-650M-only-B	3	0.4179	0.8022	0.4153	0.7677
Local	ESM1v-650M-only-D	3	0.4032	0.8027	0.4194	0.7725
Local	ESM2-150M-context-B	3	0.4296	0.8381	0.4894	0.7024
Local	ESM2-150M-context-D	3	0.4041	0.8390	0.4856	0.7199
Local	ESM2-150M-only-B	3	0.4183	0.8029	0.4229	0.7677
Local	ESM2-150M-only-D	3	0.4031	0.8034	0.4258	0.7729

Continued on next page

Origin	Recipe	s	MAE	AUC+	AP+	AUC−
Local	ESM2-35M-context-B	3	0.4280	0.8432	0.4921	0.7097
Local	ESM2-35M-context-D	3	0.4022	0.8445	0.4954	0.7302
Local	ESM2-35M-frozen-B	3	0.4034	0.8263	0.4554	0.7541
Local	ESM2-35M-frozen-D	3	0.3904	0.8246	0.4544	0.7667
Local	ESM2-35M-lora-B	3	0.3637	0.8550	0.5517	0.7921
Local	ESM2-35M-lora-D	3	0.3650	0.8536	0.5474	0.8028
Local	ESM2-35M-only-B	3	0.4157	0.8109	0.4290	0.7829
Local	ESM2-35M-only-D	3	0.4007	0.8131	0.4340	0.7870
Local	ESM2-650M-context-B	3	0.4319	0.8392	0.4832	0.6923
Local	ESM2-650M-context-D	3	0.4071	0.8394	0.4796	0.7139
Local	ESM2-650M-only-B	3	0.4204	0.8033	0.4105	0.7663
Local	ESM2-650M-only-D	3	0.4056	0.8022	0.4093	0.7707
Local	ESM2-8M-context-B	3	0.4288	0.8419	0.4943	0.7052
Local	ESM2-8M-context-D	3	0.4018	0.8433	0.4948	0.7215
Local	ESM2-8M-only-B	3	0.4150	0.8107	0.4398	0.7799
Local	ESM2-8M-only-D	3	0.3995	0.8128	0.4375	0.7839
Local	ESM-C-300M-context-B	3	0.4294	0.8379	0.4806	0.6937
Local	ESM-C-300M-context-D	3	0.4038	0.8391	0.4820	0.7201
Local	ESM-C-300M-only-B	3	0.4203	0.8001	0.4038	0.7643
Local	ESM-C-300M-only-D	3	0.4046	0.8011	0.4062	0.7750
Local	Nested family	3	0.3945	0.8409	0.4877	0.7530
Local	ProtT5-context-B	3	0.4301	0.8414	0.4874	0.7011
Local	ProtT5-context-D	3	0.4055	0.8425	0.4900	0.7244
Local	ProtT5-only-B	3	0.4211	0.8036	0.4143	0.7647
Local	ProtT5-only-D	3	0.4056	0.8049	0.4223	0.7740

B.3. Seed Stability and Inner Selection

Table B.2. Single-seed and ensemble peptide-macro MAE for the matched local core experiment.

Recipe	Seed 17	Seed 29	Seed 43	Ensemble
Frozen-B	0.4073	0.4031	0.4059	0.4034
Frozen-D	0.3920	0.3918	0.3938	0.3904
LoRA-B	0.3794	0.3786	0.3779	0.3637
LoRA-D	0.3794	0.3778	0.3788	0.3650

Table B.3. Inner-selected epoch counts over 15 outer fits per local core recipe.

Recipe	Folds	Minimum	Median	Maximum
frozen-B	15	1	1	3
frozen-D	15	1	1	3
lora-B	15	1	3	7
lora-D	15	1	2	4

Table B.4. Local frozen-family recipes chosen by the saved inner-MSE selector. Frequencies across seed/fold pairs are not independent votes for a model family.

Selected recipe	Outer fits (of 15)
ESM2-8M-context-D	3
Ankh-base-context-D	2
ESM2-35M-context-D	2
ESM2-8M-only-D	2
Ankh-base-only-D	1
ESM1b-650M-context-D	1
ESM1v-650M-only-D	1
ESM2-150M-only-D	1
ESM2-35M-only-D	1
ESM-C-300M-context-B	1

B.4. Execution Cost and Output Inventory

Table B.5. Recorded durations of completed local job attempts, counting inherited work once. Earlier attempts of paused/resumed jobs may be absent; these are not GPU-active or full elapsed times.

Job category	Jobs	Recorded h	Median min
other	15	3.07	0.19
probe	9	0.01	0.09
extract	9	0.96	5.35
ridge	540	1.42	0.16
tune-frozen	30	14.07	27.16
tune-lora	30	36.01	73.30

The cache contains pinned weights and executable source snapshots as well as metrics, OOF arrays, features, fitted models and recovery checkpoints. Physical file counts in Table B.6 can include duplicate content, partial files and superseded attempts. They must not be added to the checksum-verified artifact totals as though they were separate scientific observations. The transport archive contains the same expanded namespace and file sizes as the output tree; it packages Kaggle and local campaigns together with cached weights. It is an additional physical copy, not another experimental run. The archive review verifies small-member CRCs but does not recheck every large compressed payload. Zero-filled JSON metadata in the reviewed expanded copy were recovered from the transport backup, using saved artifact hashes or exact agreement with state records before a fresh integrity check. The historical timer-failure local run contributes no scientific OOF results. The interrupted local source remains required because the successor references its inherited artifacts.

Table B.6. Physical output inventory at review time. Weight caches and code snapshots are supporting assets, not evaluation datasets.

Output role	Physical files	GiB
Pinned executable snapshot	30	0.000
Superseded timer-failure run	18	0.000
Earlier local source campaign	2959	3.541
Completed local successor	2754	2.131
Nine-checkpoint local weight cache	63	14.110
Kaggle reference campaign	2990	2.859
Reference ESM2-35M weight cache	8	0.127
Top-level cache/session metadata	5	0.000
Duplicate transport archive	1	17.542