CAN THO UNIVERSITY

COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY

**FACULTY OF SOFTWARE ENGINEERING**




**GRADUATION THESIS**
**BACHELOR OF ENGINEERING IN**

**SOFTWARE ENGINEERING**
**(HIGH-QUALITY PROGRAM)**

# RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

**Student: Nguyen Thanh Trong**

**Student ID: B2305615**

**Class: 2023 – 2027 (K49)**

**Advisor: Ho Quang Thai, Ph.D.**

***Can Tho, [MM/YYYY]***

CAN THO UNIVERSITY

COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY

**FACULTY OF SOFTWARE ENGINEERING**




**GRADUATION THESIS**
**BACHELOR OF ENGINEERING IN**
**SOFTWARE ENGINEERING**
**(HIGH-QUALITY PROGRAM)**

# RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

**Student:**

Nguyen Thanh Trong

**Student ID:** B2305615

**Class:** DI2396F1, K49

**Advisor:**

Ho Quang Thai, Ph.D.

***Can Tho, [MM/YYYY]***

**CAN THO UNIVERSITY**
**COLLEGE OF INFORMATION AND COMMUNICATION TECHNOLOGY**

**SOCIALIST REPUBLIC OF VIETNAM**
**Independence – Freedom – Happiness**

# THESIS REVISION CONFIRMATION IN ACCORDANCE WITH THE COMMITTEE'S COMMENTS

Thesis Title: RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL

Student: Nguyen Thanh Trong Student ID: B2305615

Class Code: DI2396F1

The thesis was presented before the Thesis Examination Committee of the Software Engineering Program.

Members of the Examination Committee:

- [Name], Ph.D.
- [Name], Ph.D.
- [Name], Ph.D.

Reporting date: [Month DD, YYYY]

The thesis has been revised in accordance with the Committee's comments.

Can Tho, ……

**Supervisor**

**Ho Quang Thai, Ph.D.**

## COMMENTS OF THE ADVISOR

. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .
. . . . . .

Can Tho, ……

**Advisor**

**Ho Quang Thai, Ph.D.**

## ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to my advisor, Dr. Ho Quang Thai, for his guidance throughout this thesis. I also thank the lecturers of the Faculty of Software Engineering, College of Information and Communication Technology, Can Tho University, for the knowledge they gave me, and my family and friends for their support. **[PENDING: review and personalise before submission.]**

Can Tho, ……

**Student**

**Nguyen Thanh Trong**

## COMMITMENT TO RESULTS

I hereby certify that the graduation thesis titled "RESIDUE-LEVEL DEGRON MUTATION EFFECT PREDICTION AND ANALYSIS TOOL" is the result of my own research and has not been submitted for any other degree or qualification.

All references used in the thesis are clearly cited, including the author's name, the title of the work, and the time and place of publication. I accept full responsibility for any unauthorized copying, violations of academic regulations, or instances of academic dishonesty.

Can Tho, ……

**Student**

**Nguyen Thanh Trong**

# ABSTRACT

A single amino acid substitution can alter the activity of a degron, a sequence element involved in selective protein degradation. This thesis predicts substitution effects as changes in the Protein Stability Index (ΔPSI) measured by a peptide reporter assay and develops a local analysis tool. The computational work reconstructs labels, controls sequence overlap and evaluates models with protein-group-aware folds, inner model selection and group-bootstrap confidence intervals.

The full-PSI development set contains 235 peptides, 122 412 mutation cells and 221 protein groups. Expanding ridge training from WT PSI at most 4 to the full range reduces peptide-macro mean absolute error from 0.43358 to 0.40780 PSI. Frozen ESM2-35M with a convolutional head reaches 0.38435 MAE. A completed local study compares nine frozen pLM checkpoints and 60 matched frozen/LoRA fits. LoRA reaches 0.3637 MAE with restricted training and 0.3650 with full-range training, improving on matched frozen controls by 9.8% and 6.5%. Protein-group intervals support both reductions, while performance by WT-PSI stratum shows a training-coverage trade-off. Scanning-label pre-training helps its tested CNN control; quality weighting does not help ridge. Out-of-fold LoRA probabilities improve Brier score but retain calibration errors.

The local campaign ends with 633 completed jobs and two pending input-dependent extensions. On a locked same-laboratory scanning set, the fixed W5 ridge model reaches positive AUROC 0.8405, but its MAE advantage over predicting zero is unresolved; LoRA has not been evaluated on that set. As of 6 November 2026, a React/FastAPI baseline exists, while persistent projects, batch/protein jobs and experimental comparison remain incomplete. The serving model is unchanged and requires a compatible final refit/export before promotion. The results remain assay development evidence, without independent external, intact-protein or clinical validation.



**Keywords:** degron, protein stability, mutation effect prediction, ubiquitin–proteasome system, machine learning.

# TÓM TẮT

Một phép thay thế amino acid có thể làm thay đổi hoạt tính degron, tín hiệu trình tự liên quan đến phân hủy protein có chọn lọc. Luận văn dự đoán hiệu ứng đột biến bằng độ thay đổi chỉ số ổn định protein (ΔPSI) trong thí nghiệm reporter peptide và xây dựng công cụ phân tích local. Quy trình dựng lại nhãn, kiểm soát chồng lặp trình tự và đánh giá theo nhóm protein, với lựa chọn mô hình ở tập trong và khoảng tin cậy bootstrap theo nhóm.

Bộ phát triển toàn dải PSI có 235 peptide, 122 412 ô đột biến và 221 nhóm protein. Mở rộng train ridge từ PSI hoang dã không quá 4 sang toàn dải giảm MAE trung bình theo peptide từ 0.43358 xuống 0.40780 PSI. ESM2-35M đóng băng kết hợp CNN đạt MAE 0.38435. Nghiên cứu local hoàn tất so sánh chín checkpoint pLM đóng băng và 60 lượt fit frozen/LoRA có đối chứng. LoRA đạt MAE 0.3637 khi giới hạn train và 0.3650 khi train toàn dải, giảm tương ứng 9.8% và 6.5% so với frozen cùng điều kiện. Khoảng tin cậy theo nhóm ủng hộ cả hai mức giảm; phân tầng PSI cho thấy đánh đổi về độ bao phủ train. Tiền huấn luyện bằng nhãn scanning giúp CNN trong thiết kế đã thử; trọng số chất lượng không giúp ridge. Xác suất LoRA ngoài fold cải thiện Brier nhưng vẫn còn sai lệch hiệu chuẩn.

Campaign local kết thúc với 633 job hoàn tất và hai mở rộng chờ đầu vào. Trên tập scanning giữ lại cùng phòng thí nghiệm, ridge W5 cố định đạt AUROC dương 0.8405, nhưng lợi thế MAE so với dự đoán 0 chưa rõ; LoRA chưa được đánh giá trên tập này. Đến ngày 06/11/2026, đã có baseline React/FastAPI; lưu dự án, job peptide/protein và đối chiếu thực nghiệm còn dở. Mô hình phục vụ chưa đổi, cần refit và export tương thích trước khi thay thế. Kết quả vẫn là bằng chứng phát triển trong assay, chưa xác nhận độc lập ngoài nguồn, protein nguyên vẹn hay lâm sàng.

**Từ khóa:** degron, độ bền protein, dự đoán hiệu ứng đột biến, hệ ubiquitin–proteasome, học máy.

# TABLE OF CONTENTS

THESIS REVISION CONFIRMATION . . . . . i

COMMENTS OF THE ADVISOR . . . . . ii

ACKNOWLEDGEMENTS . . . . . iii

COMMITMENT TO RESULTS . . . . . iv

ABSTRACT . . . . . v

TÓM TẮT . . . . . vi

TABLE OF CONTENTS . . . . . vii

LIST OF FIGURES . . . . . xii

LIST OF TABLES . . . . . xiii

GLOSSARY AND ABBREVIATIONS . . . . . xvii

PART 1. INTRODUCTION . . . . . 1

1. Problem Statement . . . . . 1
2. History of Approaches to the Problem . . . . . 1
   - 2.1. International Context . . . . . 1
   - 2.2. Domestic Context . . . . . 1
3. Objectives . . . . . 2
   - 3.1. General Objective . . . . . 2
   - 3.2. Specific Objectives . . . . . 2
4. Research Subject and Scope . . . . . 2
   - 4.1. Research Subject . . . . . 2
   - 4.2. Research Scope . . . . . 3
5. Research Process and Technologies Used . . . . . 3
   - 5.1. Research Process . . . . . 3
   - 5.2. Technologies Used . . . . . 3
   - 5.3. Development and Supporting Tools . . . . . 4

6. Main Contributions . . . . . 4
7. Structure of the Thesis . . . . . 4

PART 2. CONTENT . . . . . 6

CHAPTER 1: PROBLEM DESCRIPTION . . . . . 6
1.1. Detailed Problem Description . . . . . 6
1.2. Functions of the System . . . . . 6
1.2.1. Predict the Effect Matrix . . . . . 7
1.2.2. Rank Substitutions . . . . . 7
1.2.3. Export Results with Provenance . . . . . 8
1.2.4. Select a Protein and Tiles . . . . . 9
1.2.5. Compare with Measured Data . . . . . 9
1.2.6. View ClinVar and Reference Annotations . . . . . 10
1.2.7. View Model and Data Provenance . . . . . 11
1.2.8. Analyse Peptide Batches or a Whole Protein . . . . . 11
1.2.9. Import Experimental Observations . . . . . 12
1.2.10. Manage Projects and Analysis History . . . . . 13
1.3. Non-Functional Requirements . . . . . 14
1.3.1. Performance Requirements . . . . . 14
1.3.2. Information Safety Requirements . . . . . 14
1.3.3. Security Requirements . . . . . 14
1.3.4. Reliability Requirements . . . . . 14
1.3.5. Maintainability Requirements . . . . . 15
1.3.6. Usability and Accessibility Requirements . . . . . 15
1.4. Implementation and Design Constraints . . . . . 15
1.4.1. Implementation Constraints . . . . . 15
1.4.2. Design Constraints . . . . . 15

CHAPTER 2: THEORETICAL BACKGROUND . . . . . 16
2.1. Domain Background . . . . . 16
2.1.1. Proteins, Amino Acids and Residues . . . . . 16
2.1.2. The Ubiquitin–Proteasome System and Degrons . . . . . 16
2.1.3. Measuring Degron Activity . . . . . 16

2.2. Methods and Models . . . . . 17
2.2.1. Problem Formulation . . . . . 17
2.2.2. Baseline and Reference Models . . . . . 17
2.2.3. Transfer Learning . . . . . 17
2.3. Technologies and Tools . . . . . 18
2.4. Evaluation Methodology . . . . . 18
2.4.1. Splitting by Protein Cluster . . . . . 18
2.4.2. Metrics . . . . . 18
2.4.3. Statistical Comparison . . . . . 18

CHAPTER 3: SOLUTION DESIGN AND IMPLEMENTATION . . . . . 19
3.1. System Overview . . . . . 19
3.1.1. Product Context . . . . . 19
3.1.2. Functional Overview . . . . . 19
3.2. System Architecture . . . . . 19
3.2.1. Architectural Components . . . . . 19
3.2.2. Interaction Between Components . . . . . 20
3.2.3. Design Rationale . . . . . 20
3.3. Data Design . . . . . 21
3.3.1. Data Sources and Preprocessing . . . . . 21
3.3.2. Data Model . . . . . 21
3.3.3. Data Dictionary . . . . . 21
3.3.4. Relationships Between Entities . . . . . 22
3.4. Method and Model Design . . . . . 22
3.4.1. Research Campaign and Recovery Design . . . . . 22
3.4.2. Nested Selection and Prediction Aggregation . . . . . 23
3.4.3. Frozen Features and Matched Adaptation . . . . . 24
3.4.4. Uncertainty, Calibration and Transfer Boundaries . . . . . 26
3.5. Functional Design . . . . . 27
3.5.1. Batch and Protein Processing . . . . . 27
3.5.2. Import and Comparison . . . . . 27
3.5.3. Annotations and Project Screens . . . . . 27
3.6. Local Execution View . . . . . 28

CHAPTER 4: TESTING AND EVALUATION . . . . . 29
4.1. Testing Objectives . . . . . 29
4.2. Experimental Evaluation . . . . . 29
4.2.1. Experimental Setup . . . . . 29
4.2.2. Evaluation Metrics . . . . . 31
4.2.3. Results . . . . . 32
4.2.3.1. Direct Learning on the Saturation Matrix . . . . . 32
4.2.3.2. Published Degformer Checkpoint and Retrained Architecture . . . . . 32
4.2.3.3. Interaction Designs . . . . . 34
4.2.3.4. Learning Curve and Relaxing the Degron Threshold 35
4.2.3.5. Number of Clusters or Coverage of the Distribution 37
4.2.3.6. Sensitivity to the Threshold . . . . . 39
4.2.3.7. Sensitivity to the Clustering Granularity . . . . . 41
4.2.3.8. Pre-Training on Tile Labels . . . . . 43
4.2.3.9. Calibration of the Scores and Ranking Utility . . . . 45
4.2.3.10. External GPS Labels: Koren et al. Table S4 . . . . . 47
4.2.3.11. Scope Comparison with MetaDegron . . . . . 48
4.2.3.12. Follow-up on the Restricted Benchmark . . . . . 49
4.2.3.13. Full-PSI Development Evaluation . . . . . 50
4.2.3.14. Campaign Completion and Integrity . . . . . 52
4.2.3.15. Nine-Checkpoint Frozen-Feature Comparison . . . . 53
4.2.3.16. Completed Matched Frozen–LoRA Evaluation . . . 53
4.2.3.17. Probability Calibration and Locked Transfer . . . . 56
4.2.3.18. Additional Controls and Practical Consequences . . 58
4.2.3.19. Remaining Evaluation . . . . . 59
4.2.4. Discussion . . . . . 60
4.2.5. Reproducibility of the Reported Results . . . . . 62
4.3. Software Testing Plan . . . . . 63
4.3.1. Functions Under Test . . . . . 63
4.3.2. Approach . . . . . 63
4.3.3. Criteria for Test Success or Failure . . . . . 63
4.3.4. Suspension Criteria and Restart Requirements . . . . . 64

4.3.5. Test Deliverables . . . . . 64
4.4. Test Management . . . . . 64
4.4.1. Test Activities . . . . . 64
4.4.2. Test Environment . . . . . 64
4.4.3. Resources and Allocation . . . . . 64
4.4.4. Risks . . . . . 64
4.5. Test Scenarios and Test Cases . . . . . 65
4.5.1. Test Scenarios . . . . . 65
4.5.2. Expanded Local Acceptance Scenarios . . . . . 65
4.5.3. Test Cases . . . . . 66
4.6. Test Evaluation . . . . . 66

PART 3. CONCLUSION . . . . . 68
1. Achieved Results . . . . . 68
1.1. Knowledge and Skills . . . . . 68
1.2. Program and Practical Application Potential . . . . . 69
2. Limitations and Challenges . . . . . 69
3. Future Work . . . . . 70

REFERENCES . . . . . 71

APPENDIX A: INSTALLATION AND USER GUIDE . . . . . 73
A.1. Installation Requirements . . . . . 73
A.1.1. Hardware Requirements . . . . . 73
A.1.2. Software Requirements . . . . . 73
A.2. Local System Execution . . . . . 73
A.2.1. Existing Baseline Commands . . . . . 73
A.2.2. Target Local Workflow . . . . . 74
A.3. User Guide . . . . . 74
A.4. Offline Research Campaign Workflow . . . . . 74

APPENDIX B: SUPPLEMENTARY MATERIALS . . . . . 76
B.1. Source Code and Data Availability . . . . . 76
B.2. Additional Tables and Figures . . . . . 76

B.3. Seed Stability and Inner Selection . . . . . 79
B.4. Execution Cost and Output Inventory . . . . . 80

# LIST OF FIGURES

Figure 3.1. Planned components of the single local application; arrows denote data interactions. . . . . 20
Figure 3.2. Campaign lineage and evidence roles at completion on 6 November 2026. Inheritance preserves compatible work; the combined review does not create independent datasets. . . . . 23
Figure 3.3. Group-aware selection and evaluation. The three seed predictions are averaged per cell before computing ensemble metrics. The separate transfer set T evaluates the fixed W5-D recipe. . . . . 25

Figure 4.1. Macro AUROC against the mean number of training clusters (nested cluster subsets of 25, 50, 75 and 100% of the outer-training data; the dashed segment is the relaxed-threshold training set). . . 36
Figure 4.2. Gain in macro AUROC over the benchmark training set for each degron threshold, with 95% cluster-bootstrap intervals (horizontal offsets only separate the two models). . . . . 40
Figure 4.3. Frozen pLM ridge results under full-range training. Points joined on the same row compare explicit context for one checkpoint; the connectors are not confidence intervals. . . . . 54
Figure 4.4. Matched adaptation evidence. (a) Ensemble MAE and individual seed results; (b) paired MAE differences with multiplicity-adjusted group-bootstrap intervals. The seeds share the outer folds and are not independent cohorts. . . . . 55
Figure 4.5. Probability and transfer limitations. (a) Development OOF positive-event reliability, with the diagonal indicating agreement; (b) locked W5-D transfer MAE by WT PSI. T uses a different population and does not evaluate LoRA. . . . . 58

# LIST OF TABLES

Table 1.1. Predict the effect matrix . . . . . 7
Table 1.2. Rank substitutions . . . . . 7
Table 1.3. Export results with provenance . . . . . 8
Table 1.4. Select a protein and tiles . . . . . 9
Table 1.5. Compare with measured data . . . . . 9
Table 1.6. View ClinVar and reference annotations . . . . . 10
Table 1.7. View model and data provenance . . . . . 11
Table 1.8. Analyse peptide batches or a whole protein . . . . . 11
Table 1.9. Import experimental observations . . . . . 12
Table 1.10. Manage projects and analysis history . . . . . 13

Table 3.1. Data roles in research and the first local release . . . . . 21
Table 3.2. Key workspace fields and invariants . . . . . 22

Table 4.1. Fate of the raw saturation peptides under the label filters . . . . . 30
Table 4.2. Macro AUROC on the 91 peptides of the saturation benchmark. The last column keeps only the cells whose exact sequence is not in the training data of the published Degformer. . . . . 33
Table 4.3. Paired AUROC differences between models . . . . . 33
Table 4.4. Per-seed AUROC of the three main models . . . . . 33
Table 4.5. Interaction designs against ridge M3. “Criterion met” applies the pre-registered rule above; for the sigmoid gate and the one-seed Degformer architecture the rule is applied descriptively. . . . . 35
Table 4.6. Learning curve (P1) and relaxed degron threshold 4.0 (P0). Ranges are over 5 folds and 3 seeds. . . . . 36
Table 4.7. Pre-registered verdicts of P1 and P0 . . . . . 37
Table 4.8. Cells of the benchmark peptides and of the 85 peptides added by relaxing the threshold . . . . . 38
Table 4.9. Gain over the benchmark training set when a fraction of the new clusters is added . . . . . 38
Table 4.10. Pre-registered verdicts on the new clusters. The reference marginal gain of old-region clusters is 0.0038. . . . . 39

Table 4.11. Added data and gains for each degron threshold (cov80, positive cut $\Delta$PSI $\geq 1$) . . . . . 40
Table 4.12. Robustness of the gain at threshold 4.0 (ridge M3) . . . . . 41
Table 4.13. Gain of the relaxed threshold 4.0 (ridge M3) under different protein partitions. "Groups" are the groups of the 91 benchmark peptides and of all 176 peptides; "Shared" is the number of added peptides that fall in a group of a benchmark peptide; "Excl." is the mean percentage of the added cells that are removed from training because their group contains a test peptide. . . . . 42
Table 4.14. Macro AUROC with and without pre-training on tile labels . . . 44
Table 4.15. Pre-registered comparisons for pre-training. The main configuration is the relaxed threshold 4.0; the threshold 3.0 is reported with the same criteria and was not used to choose the configuration. . . 44
Table 4.16. Probability quality on the outer-test cells (observed fraction of positive cells: 0.131). ECE: expected calibration error over ten equal-mass bins; $\hat{p}$: predicted probability. . . . . 45
Table 4.17. Pre-registered comparisons of the Brier score . . . . . 46
Table 4.18. Ranking utility: the substitutions of each peptide (532 per 28-residue peptide) are ordered by the raw score. A random ranking has enrichment 1. . . . . 47
Table 4.19. Gate fixed in advance for merging the labels of Koren et al. (Table S4) into training . . . . . 47
Table 4.20. Audit of the MetaDegron data and overlap with the data of this thesis 49
Table 4.21. Selected full-PSI development results. MAE is lower-is-better; positive AUROC is higher-is-better. All rows use the same evaluation population and three-seed prediction ensemble. . . . . 51
Table 4.22. Paired full-PSI MAE differences; negative values favour the first method. The two ridge range comparisons use 97.5% intervals adjusted for two tests; the remaining intervals are descriptive 95% intervals. All use 5,000 protein-group bootstrap resamples. . . . . 52
Table 4.23. Local frozen-feature ridge MAE for all nine checkpoints. "Only" includes the common auxiliary inputs; W5 adds ordered sequence context. All entries use three-seed OOF ensembles. . . . . 53

Table 4.24. Matched local ESM2-35M results. MAE uses all 235 peptides; positive AUROC/AP use 184 eligible peptides and negative AUROC uses 110. Higher ranking metrics are better. . . . . 54
Table 4.25. Paired local contrasts: LoRA minus its frozen control. Confidence intervals use 5,000 protein-group resamples; 98.75% intervals adjust a post-hoc family of four comparisons. Negative MAE differences and positive AUROC differences favour LoRA. . . . . 55
Table 4.26. LoRA peptide-macro MAE by WT-PSI stratum. The final column is the paired D-minus-B difference with a descriptive 95% protein-group interval; $n$ counts peptides. . . . . 56
Table 4.27. Out-of-fold three-class probability evaluation. Brier is the unnormalised sum across three classes; lower values are better. The prior uses inner-validation class frequencies. ECE refers only to the positive event and uses ten equal-width bins. . . . . 57
Table 4.28. Locked W5-D transfer by WT PSI. $n$ counts peptides and $n_+$ counts peptides eligible for positive-event AUROC. The zero predictor provides a regression reference. . . . . 57
Table 4.29. Planned first-release local acceptance scenarios; no execution result claimed . . . . . 65
Table 4.30. Executed test cases: agreement of the prototype with the research runner. The tolerance is $10^{-9}$. . . . . 66

Table B.1. All saved OOF configurations. $s$ is the number of seeds; MAE and event ranking are peptide-macro. Only rows with $s = 3$ are three-seed ensembles. . . . . 76
Table B.2. Single-seed and ensemble peptide-macro MAE for the matched local core experiment. . . . . 79
Table B.3. Inner-selected epoch counts over 15 outer fits per local core recipe. 79
Table B.4. Local frozen-family recipes chosen by the saved inner-MSE selector. Frequencies across seed/fold pairs are not independent votes for a model family. . . . . 80

Table B.5. Recorded durations of completed local job attempts, counting inherited work once. Earlier attempts of paused/resumed jobs may be absent; these are not GPU-active or full elapsed times. . . . . 80
Table B.6. Physical output inventory at review time. Weight caches and code snapshots are supporting assets, not evaluation datasets. . . . . 81

# GLOSSARY AND ABBREVIATIONS

| No. | Term / Abbreviation | Definition / Explanation |
|---|---|---|
| 1 | Degron | Sequence element that marks a protein for selective degradation. |
| 2 | E3 ligase | Enzyme that recognises substrate proteins and transfers ubiquitin to them. |
| 3 | Residue | One amino acid at a specific position of a protein or peptide. |
| 4 | Footprint | Map of positions or substitutions that affect degron activity under a given assay. |
| 5 | GPS | Global Protein Stability profiling, a fluorescent-reporter assay of protein stability. |
| 6 | PSI | Protein Stability Index, a summary of the reporter signal distribution over sorting bins. |
| 7 | ΔPSI | PSI of the mutant minus PSI of the wild type. |
| 8 | WT | Wild type, the unmutated reference sequence. |
| 9 | PAP | Model that predicts degron activity of a whole peptide. |
| 10 | AUROC | Area under the receiver operating characteristic curve. |
| 11 | MMseqs2 | Software for sequence search and clustering. |
| 12 | Cov80 / cov50 | Protein clusters built with 80% / 50% alignment coverage. |
| 13 | pLM | Protein language model pretrained on amino acid sequences. |
| 14 | LoRA | Low-rank adaptation of selected pretrained weight matrices. |
| 15 | OOF | Out-of-fold predictions made on groups excluded from model fitting. |

| No. | Term / Abbreviation | Definition / Explanation |
|---|---|---|
| 16 | MAE / MSE | Mean absolute error / mean squared error; regression loss measures. |
| 17 | AP | Average precision, a summary of precision–recall ranking. |
| 18 | ECE | Expected calibration error, summarised over probability bins. |

# PART 1. INTRODUCTION

## 1. Problem Statement

The abundance of a protein in a cell depends on both its synthesis and its degradation. In the ubiquitin–proteasome system, a *degron* is a short sequence element that marks a protein for selective degradation [1, 2]. A single amino acid substitution inside a degron can strengthen or weaken this signal, so knowing the effect of each substitution helps researchers choose mutations to test experimentally [3, 4].

A whole-peptide activity score alone does not say which position, or which substituted amino acid, makes the degron signal stronger or weaker. Mutation assays provide such labels, but measuring every substitution experimentally is costly, which motivates a predictive model that shortlists substitutions. Such a model is only useful if it is evaluated on experimental labels and if similarity between training and test proteins is controlled.

## 2. History of Approaches to the Problem

### 2.1. International Context

Large-scale stability profiling based on the Global Protein Stability (GPS) assay [5] has produced experimental degron maps, including scanning and saturation mutagenesis of human peptides [3], cytosolic tile maps [4] and transcription-factor tile maps [6]. On the computational side, PAP and Degformer predict peptide-level degron activity or protein stability [4, 7], MetaDegron predicts E3-ligase-targeted degron motifs [8], and DEGRONOPEDIA and DegronMD provide annotation resources [9, 10].

These works address peptide- or motif-level prediction and annotation. Residue-level substitution effects measured on a common assay endpoint, evaluated with protein-cluster-aware splits, remain a question that the thesis examines rather than a gap it assumes is unfilled.

### 2.2. Domestic Context

**[PENDING: literature search on degron and protein-stability prediction work in Vietnam; to be written only after the search is done.]**

# 3. Objectives

## 3.1. General Objective

To study methods that predict the effect of amino acid substitutions in degrons from experimental data, to evaluate generalisation across protein clusters, and to build a tool that supports analysis and prioritisation of mutations.

## 3.2. Specific Objectives

1. Build a reproducible pipeline that normalises data, maps coordinates and derives mutation-effect labels while keeping each source and assay condition separate.

2. Establish baselines: amino acid composition, ridge regression, the PAP score difference and the Degformer architecture, under clearly stated comparable conditions.

3. Study training-label coverage, ordered local context and pretrained protein representations with matched model controls; evaluate transfer and fine-tuning without assuming an advantage.

4. Evaluate effectiveness, stability across seeds, error, and the contribution of each component.

5. Build one local React/FastAPI application for single-peptide and batch/whole-protein tile analysis, ClinVar/reference annotation, experimental-data comparison, project history and traceable export.

# 4. Research Subject and Scope

## 4.1. Research Subject

Degron peptides, single amino acid substitutions, protein stability indices measured with a reporter assay, and models predicting residue-level mutation effects. A *residue* is one amino acid at a specific position; the *footprint* is the map of positions or substitutions that change degron activity under a given assay.

### 4.2. Research Scope

- The main label source is the human peptide data of Zhang et al. [3]; other peptide-level sources are used only for transfer learning or domain studies when their terms of use allow. The current full-PSI study uses 235 saturation peptides in 221 protein groups. The initial restricted benchmark is retained separately; expanding the population does not create an independent validation set.
- Input: reference (wild-type) sequence, position and substituted amino acid. Output: predicted effect $\Delta$PSI, which can be arranged into an $L \times 20$ matrix.
- The first software release includes peptide batches, whole-protein tiling, ClinVar and approved reference annotations, CSV/TSV experimental import for comparison, and persistent local projects and analysis history. Each scored tile remains a 28-residue peptide; whole-protein processing does not validate intact-protein effects. Imported observations do not automatically enter training.
- One local application is required; public hosting, public sharing, account management and remote deployment are outside acceptance. Saved project work persists until user deletion.
- Identifying the specific E3 ligase is not a main task. No new wet-lab experiments are performed, and software output supports hypothesis generation; it does not establish causation, disease effects or therapeutic benefit.

## 5. Research Process and Technologies Used

### 5.1. Research Process

The work combines a literature review, controlled computational experiments and a software prototype: (1) study degron biology and related methods; (2) audit data and design the evaluation; (3) train and compare models; (4) develop and test the prototype; (5) analyse results and write the thesis.

### 5.2. Technologies Used

Python with NumPy, pandas, scikit-learn and PyTorch for modelling, and MMseqs2 for protein clustering [11]. The application uses React with TypeScript (Vite),

FastAPI and local PostgreSQL, with a local worker for durable CPU inference jobs; SQLite supports isolated tests and baseline development.

### 5.3. Development and Supporting Tools

Git for version control and LaTeX (XeLaTeX) for this report. The local software test plan uses pytest, API/schema checks and browser tests. Docker may package the same local components; a public-host deployment is not required.

## 6. Main Contributions

As of 6 November 2026, the achieved contributions are:

1. A traceable pipeline for experimental mutation-effect labels, technical quality control, sequence mapping and protein-group-aware evaluation, including a full-PSI development set.

2. Evidence that broader training-label coverage and ordered context improve appropriate baselines, together with matched frozen-ESM pointwise/CNN comparisons. Negative findings on tile-label pre-training and quality weighting are retained with their scope.

3. A completed nine-checkpoint frozen-feature comparison and matched ESM2-35M LoRA evaluation with group-bootstrap uncertainty, out-of-fold probability assessment and a locked W5 transfer check that exposes regression and calibration limits.

4. Calibrated restricted-domain baseline inference, numerical agreement with the research runner, and a local web/API baseline with source-aware result presentation.

The expanded workspace remains under implementation. The current findings do not establish a new architecture, independent external validity or completion of the first software release.

## 7. Structure of the Thesis

Part 1 introduces the problem, objectives and scope. Part 2 has four chapters: Chapter 1 describes the problem and the system requirements; Chapter 2 gives the

theoretical background; Chapter 3 presents the design of the data, method and system; Chapter 4 covers experimental evaluation and software testing. Part 3 states the results, limitations and future work. The appendices give installation and usage instructions and supplementary material.

# PART 2. CONTENT

# CHAPTER 1: PROBLEM DESCRIPTION

## 1.1. Detailed Problem Description

Researchers selecting degron mutations for follow-up experiments face a limited experimental budget. A 28-residue peptide has 532 possible single-amino-acid substitutions. The software must help the researcher inspect these candidates, choose a shortlist and retain the evidence needed to revisit that choice. Its primary deliverable is a traceable prioritisation workflow.

The thesis connects two problems. The research pipeline predicts the effect $\Delta$PSI of a substitution from a reference peptide, position and replacement amino acid, using experimental labels and protein-cluster-aware evaluation. The application uses a frozen model to support analysis, annotation and comparison. The model task remains mutation-level prediction; annotation and project management do not change its scientific endpoint.

**First-release scope.** The software scope confirmed on 29 October 2026 is one local web application using React with TypeScript and FastAPI. It includes single-peptide analysis, peptide batches, whole-protein tiling, ClinVar and approved reference annotations, import of experimental observations for comparison, CSV/JSON export, and persistent projects and analysis history. The browser, API, local worker and database belong to the same local workspace. Public hosting, remote deployment and public sharing are outside acceptance; no separate public and internal editions are required.

The main actor is the researcher operating this local workspace. Account management, multi-user collaboration, wet-lab/sample management, automatic retraining and clinical diagnosis are outside scope. Imported measurements remain project data and are not added automatically to training or benchmark labels. No new biological experiment is required by this thesis.

## 1.2. Functions of the System

The following use cases describe the target first release, not completed implementation. Baseline single-tile API/frontend code and a CLI already exist; the added

project, job and import flows still require implementation and verification. The requirements below define the target behaviour; Chapter 4 specifies the corresponding acceptance scenarios.

### 1.2.1. Predict the Effect Matrix

**Table 1.1.** Predict the effect matrix

| **Use case name:** Predict effect matrix | **ID:** UC-01 |
|---|---|
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher: inspect the effect of every single substitution of a peptide. | |
| **Summary description:**<br>Enter a 28-residue WT peptide or select a reference tile; obtain 532 scores in a position-by-amino-acid grid with WT cells masked. | |
| **Relationships:**<br>Include: validate input and assess domain.<br>Extend: compare observations, view annotations, save analysis. | |
| **Event handling:**<br>1. Enter/select the peptide.<br>2. Validate syntax, coordinates and domain.<br>3. Score with a frozen model.<br>4. Show domain and warnings before the matrix. | |
| **Alternative / exceptional flows:**<br>Invalid input: no scores. Known out-of-domain tile: refuse by default; explicit override records a warning. Unknown, unreliable or borderline domain: score only with a prominent limitation label. | |
| **Expected outcome:**<br>A transient preview with raw $\Delta$PSI score, calibrated $P(\Delta\text{PSI} \geq 1)$, model identity and domain evidence; explicit save invokes UC-10. | |

### 1.2.2. Rank Substitutions

**Table 1.2.** Rank substitutions

| **Use case name:** Rank substitutions | **ID:** UC-02 |
|---|---|
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |

| |
|---|
| **Stakeholders and interests:**<br>Researcher: choose a shortlist within an experimental budget. |
| **Summary description:**<br>Sort/filter substitutions within each tile and select candidates. |
| **Relationships:**<br>Include: UC-01 or a completed tile of UC-08. |
| **Event handling:**<br>1. Open ranking.<br>2. Sort by effect/probability and filter by position or replacement.<br>3. Select candidates; inspect the top-10% flag. |
| **Alternative / exceptional flows:**<br>No result: request an analysis first. Empty filter: show an explicit empty state. |
| **Expected outcome:**<br>A tile-specific shortlist retaining coordinates and warnings; no implied cross-protein biological ranking. |

### 1.2.3. Export Results with Provenance

**Table 1.3.** Export results with provenance

| | |
|---|---|
| **Use case name:** Export results | **ID:** UC-03 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher: reuse results in an experimental or computational workflow. | |
| **Summary description:**<br>Export a single analysis or complete job as CSV/JSON, including selected annotations/comparisons. | |
| **Relationships:**<br>Uses: UC-01, UC-05, UC-06, UC-08 and UC-10. | |
| **Event handling:**<br>1. Choose scope and format.<br>2. Write scores, per-item outcomes, coordinates, model/data versions and warnings. | |
| **Alternative / exceptional flows:**<br>Export failure preserves the result for retry. Failed/skipped job items remain in the manifest. | |

| |
|---|
| **Expected outcome:**<br>Complete traceable files, including rows beyond the current page; no public share link. |

### 1.2.4. Select a Protein and Tiles

**Table 1.4.** Select a protein and tiles

| | |
|---|---|
| **Use case name:** Select protein and tiles | **ID:** UC-04 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher: locate a known protein region without manually copying coordinates. | |
| **Summary description:**<br>Search the loaded human UniProt release; choose a tile or analyse the complete protein through tiling. | |
| **Relationships:**<br>Continues to UC-01 or UC-08. | |
| **Event handling:**<br>1. Search accession/gene.<br>2. Select the reference sequence.<br>3. Inspect tiles, domain states and coverage.<br>4. Choose the analysis scope. | |
| **Alternative / exceptional flows:**<br>No accession, sequence shorter than 28, non-standard residues or unverified mapping: state the reason and affected coverage. | |
| **Expected outcome:**<br>Selected reference release and explicit 1-based peptide/protein coordinates. | |

### 1.2.5. Compare with Measured Data

**Table 1.5.** Compare with measured data

| | |
|---|---|
| **Use case name:** Compare observations | **ID:** UC-05 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher: inspect where prediction agrees or disagrees with measurements. | |

| |
|---|
| **Summary description:**<br>Choose reference observations or a committed project dataset; align exact WT, position and replacement. |
| **Relationships:**<br>Uses: UC-01/08 and UC-09. |
| **Event handling:**<br>1. Select dataset and replicate/aggregation.<br>2. Check mapping, endpoint and units.<br>3. Display matched values, exclusions and applicable residuals/metrics. |
| **Alternative / exceptional flows:**<br>Missing/unmatched values are not zero. Different assays remain separate without pooled ΔPSI metrics. Insufficient/constant pairs have explicit undefined-metric states. |
| **Expected outcome:**<br>Comparable prediction/observation views with sample counts and provenance; training observations labelled and imports not automatically called independent validation. |

### 1.2.6. View ClinVar and Reference Annotations

**Table 1.6.** View ClinVar and reference annotations

| | |
|---|---|
| **Use case name:** View annotations | **ID:** UC-06 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher: relate candidate substitutions to published variant and reference evidence. | |
| **Summary description:**<br>Show ClinVar missense records, UniProt mapping and approved GPS evidence in release 1. | |
| **Relationships:**<br>Extends: UC-01/08; provenance from UC-07. | |
| **Event handling:**<br>1. Enable a layer.<br>2. Verify accession/release/WT residue.<br>3. Show classification, review/conflict state, source version, attribution and disclaimer. | |

| |
|---|
| **Alternative / exceptional flows:**<br>Distinguish no match, unmapped custom input, unavailable source and conflicting mapping. Do not guess canonical mappings. |
| **Expected outcome:**<br>Traceable annotations separate from effect predictions; annotation absence does not mean benign. |

### 1.2.7. View Model and Data Provenance

**Table 1.7.** View model and data provenance

| | |
|---|---|
| **Use case name:** View model and sources | **ID:** UC-07 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Simple |
| **Stakeholders and interests:**<br>Researcher and examiner: understand the predicted event, evidence and limitations. | |
| **Summary description:**<br>Read frozen model identity, domain, development metrics and source licences/versions. | |
| **Relationships:**<br>Supplies evidence to all result/export views. | |
| **Event handling:**<br>1. Open model/data information.<br>2. Inspect current metadata or the snapshot associated with a saved run. | |
| **Alternative / exceptional flows:**<br>Missing historical artefact: report an integrity problem instead of silently substituting a newer source. | |
| **Expected outcome:**<br>Explicit distinction between development evidence, imported comparison and independent validation. | |

### 1.2.8. Analyse Peptide Batches or a Whole Protein

**Table 1.8.** Analyse peptide batches or a whole protein

| | |
|---|---|
| **Use case name:** Batch/protein analysis | **ID:** UC-08 |

| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Complex |
|---|---|
| **Stakeholders and interests:**<br>Researcher: analyse many candidates while retaining item-level failures and context. | |
| **Summary description:**<br>Submit bounded peptide records/FASTA or one protein accession/FASTA to a persistent local job. | |
| **Relationships:**<br>Uses UC-01/04/10; exports through UC-03. | |
| **Event handling:**<br>1. Choose a project and input mode.<br>2. Preview validation, tiling and coverage.<br>3. Confirm local persistence and submit.<br>4. Track progress and open per-tile results. | |
| **Alternative / exceptional flows:**<br>Item failures/refusals preserve successes. Cancellation/restart retain completed results without duplicates. Limits and uncovered residues are explicit. | |
| **Expected outcome:**<br>A durable job with reconciled outcome counts, pinned model/source versions and distinct overlapping tile contexts. | |

### 1.2.9. Import Experimental Observations

**Table 1.9.** Import experimental observations

| **Use case name:** Import observations | **ID:** UC-09 |
|---|---|
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Complex |
| **Stakeholders and interests:**<br>Researcher: compare predictions with locally supplied measurements. | |
| **Summary description:**<br>Validate CSV/TSV plus assay, units, source, replicate and reference metadata; commit a dataset revision. | |
| **Relationships:**<br>Uses UC-10; supplies UC-05. | |

| |
|---|
| **Event handling:**<br>1. Upload into a project.<br>2. Preview row-level errors, duplicates, missingness and mapping.<br>3. Correct blocking errors and acknowledge warnings.<br>4. Explicitly commit. |
| **Alternative / exceptional flows:**<br>Malformed/nonfinite/WT-conflicting records block commit; conflicting duplicates never overwrite. Other endpoints remain separately labelled. |
| **Expected outcome:**<br>An immutable project dataset with file hash and provenance; no update to training data or weights. |

### 1.2.10. Manage Projects and Analysis History

**Table 1.10.** Manage projects and analysis history

| | |
|---|---|
| **Use case name:** Manage projects/history | **ID:** UC-10 |
| **Primary actor:** Researcher | **Necessity level:** Important<br>**Classification:** Complex |
| **Stakeholders and interests:**<br>Researcher: revisit the exact analysis used for an earlier experimental decision. | |
| **Summary description:**<br>Create/rename/reopen/delete local projects; save and reopen immutable runs and datasets. | |
| **Relationships:**<br>Supports UC-01/03/05/08/09. | |
| **Event handling:**<br>1. Create/select project.<br>2. Explicitly save a preview or submit/commit work.<br>3. Reopen history after restart.<br>4. Rerun as a new entry or confirm deletion after a dependency summary. | |
| **Alternative / exceptional flows:**<br>Missing snapshot or failed cleanup is explicit; deletion cannot remove shared reference/model data or other projects. | |
| **Expected outcome:**<br>Saved input, configuration, results and provenance retained locally until deletion; no account or public-sharing requirement. | |

## 1.3. Non-Functional Requirements

The detailed identifiers and cases are in the system SRS. The targets below are proposed until measured on the recorded local computer; no external-host performance or availability result is required.

### 1.3.1. Performance Requirements

Proposed p95 targets are 300 ms for one tile, 200 ms for listing a 1,000-residue protein's tiles and 1.5 s from click to rendered heatmap. Batch/import resource use is measured separately; bounded jobs, pagination and cancellation keep the interface usable. Proposed initial bounds are 100 peptides or one protein of at most 10,000 residues per job, and 10 MiB/100,000 rows per import; these are configurable design defaults, not measured capacities.

### 1.3.2. Information Safety Requirements

Serve only approved reference data with source versions and required attribution. ClinVar retains its review/conflict information and diagnostic disclaimer. Imported observations stay in a project-specific store with assay/units/replicates and are not automatically pooled into reference or training data.

### 1.3.3. Security Requirements

Bind application services to loopback and restrict browser origins. Validate all input and uploaded files; never execute their contents or use supplied names as paths. Unsaved previews are transient. Explicit saves, job submissions and import commits persist locally until deletion; no sequences or observations appear in logs, URLs or third-party telemetry. Project history has no automatic 30-day expiry.

### 1.3.4. Reliability Requirements

Score arrays are deterministic for the same normalised input and frozen configuration. Numerical agreement with the runner must be below $10^{-9}$ for JSON and $5 \times 10^{-9}$ for ten-digit CSV. Saved snapshots survive restart; job recovery does not duplicate completed results. Missing data, partial failures and invalid mappings remain visible.

### 1.3.5. Maintainability Requirements

Version models, source snapshots and schema migrations. Document local API/worker/frontend startup and workspace recovery. Test the clean local workflow rather than cloud installation.

### 1.3.6. Usability and Accessibility Requirements

Provide keyboard workflows, accessible tables and text/patterns in addition to colour, with WCAG 2.1 AA as the accessibility target. Desktop use is primary; smaller screens use a scrollable matrix/table fallback.

## 1.4. Implementation and Design Constraints

### 1.4.1. Implementation Constraints

One student implements the system within the thesis schedule. React with TypeScript and FastAPI are fixed choices; PostgreSQL is local project/reference storage and SQLite supports isolated tests/baseline development. A local worker runs CPU inference. Training and research notebooks remain separate. Docker may package the same local application; public deployment is not a deliverable.

### 1.4.2. Design Constraints

Whole-protein analysis retains full 28-residue windows at step 23 and reports uncovered positions. It does not establish the behaviour of the intact protein. Every result carries assay/domain evidence; raw $\Delta$PSI, calibrated event probability and clinical annotation are separate quantities. The scope update does not establish clinical validity, an E3 mechanism or completion of research gates.

# CHAPTER 2: THEORETICAL BACKGROUND

## 2.1. Domain Background

### 2.1.1. Proteins, Amino Acids and Residues

A protein is a chain of amino acids. A *residue* is one amino acid at a specific position of the chain. A *single amino acid substitution* replaces the residue at one position with another of the 20 standard amino acids.

### 2.1.2. The Ubiquitin–Proteasome System and Degrons

In the ubiquitin–proteasome system, E3 ubiquitin ligases recognise substrate proteins and attach ubiquitin chains to them; ubiquitinated proteins are then degraded by the proteasome. A *degron* is a sequence element that is part of this recognition and marks a protein for selective degradation [1, 2]. Degrons can lie at the protein termini or inside the sequence [3]. The activity of a peptide taken out of its protein may differ from its activity in the intact protein, because surface exposure, structure and cellular context matter.

### 2.1.3. Measuring Degron Activity

Global Protein Stability (GPS) profiling [5] fuses a peptide to a fluorescent reporter and sorts cells by fluorescence into bins. The *Protein Stability Index* (PSI) summarises the distribution of cells over the bins; in the data of Zhang et al. [3], a lower PSI corresponds to a less stable reporter. The effect of a substitution is defined as

$$\Delta\mathrm{PSI} = \mathrm{PSI}_{\mathrm{mutant}} - \mathrm{PSI}_{\mathrm{WT}}, \tag{2.1}$$

where a positive value means the reporter is more stable under the assay. This describes the measured reporter stability and does not by itself show direct recognition by a specific E3 ligase.

*Scanning* mutagenesis replaces residues in a systematic way along the peptide, whereas *saturation* mutagenesis tests many amino acids at each position. Cells from the same peptide are statistically related and cannot be treated as fully independent samples. Measurement noise comes from read counts, replicate variation and experimental conditions.

## 2.2. Methods and Models

### 2.2.1. Problem Formulation

The task is to predict ΔPSI for a (peptide, position, substituted amino acid) triple. Predictions for all positions and amino acids form a matrix of size $L \times 20$ for a peptide of length $L$. For evaluation, ΔPSI can also be thresholded into a binary label; the threshold and the direction of the effect must be fixed in the evaluation protocol before models are compared.

### 2.2.2. Baseline and Reference Models

- **Ridge regression** [12]: a linear model with $L_2$ regularisation, used as a simple baseline on encodings of the reference and substituted amino acids, peptide composition and local context.
- **PAP score difference**: PAP predicts a degron score for a whole peptide [4]; the mutation effect is taken as $\mathrm{PAP}_{\mathrm{mutant}} - \mathrm{PAP}_{\mathrm{WT}}$.
- **Degformer**: a transformer-based model [13] that predicts PSI [7].

MetaDegron [8] predicts degron motifs and is used to compare problem scope, not as a label source.

### 2.2.3. Transfer Learning

One transfer-learning design pre-trains a representation on peptide-level activity labels and then fine-tunes it on mutation-level labels. The two label types have different meanings, so they need separate prediction heads or a suitable transformation; binary motif labels are not converted into ΔPSI values.

Protein language models such as ESM2 [14] provide pretrained sequence representations. In frozen-feature experiments their weights stay fixed while a task-specific head is trained. Convolutional heads mix nearby positions; a pointwise head is a control without that mixing. LoRA [15] instead learns low-rank parameter updates and a task head while retaining the pretrained weights. Frozen features, tile-label pre-training and LoRA are distinct experiments.

## 2.3. Technologies and Tools

Python with NumPy, pandas and scikit-learn for data handling and classical models; PyTorch for neural models; MMseqs2 [11] for clustering protein sequences. Versions are recorded when experiments are run. The local application uses React with TypeScript, FastAPI and PostgreSQL, with a local worker for batch inference. This runtime design is separate from the research toolchain.

## 2.4. Evaluation Methodology

### 2.4.1. Splitting by Protein Cluster

Randomly splitting individual cells lets similar sequences appear in both training and test sets and inflates results. Proteins are therefore clustered by sequence similarity (MMseqs2, 30% identity, 80% coverage as the main setting; 50% coverage as a sensitivity check) and whole clusters are assigned to folds. Hyperparameters are chosen on a cluster-wise validation set inside each training fold; scaling, feature selection and pre-training must not use the held-out clusters.

### 2.4.2. Metrics

For the initial restricted-PSI benchmark, the main metric is the cell-level area under the ROC curve (AUROC), computed per eligible peptide and then averaged. The full-PSI study primarily measures peptide-macro mean absolute error on continuous $\Delta$PSI, with Spearman and positive/negative-event ranking as secondary measures. Eligibility and sample counts are reported separately: a peptide without both event classes can contribute to regression even when its AUROC is undefined.

### 2.4.3. Statistical Comparison

Models are compared pairwise on the same peptides. Confidence intervals come from bootstrap resampling [16] by protein cluster, and results are reported per random seed in addition to the aggregate. A development benchmark is distinguished from an independent validation.

# CHAPTER 3: SOLUTION DESIGN AND IMPLEMENTATION

This chapter describes the target design confirmed on 29 October 2026. Baseline API/frontend code exists, but the workspace, durable jobs and import extensions below are planned. A design element is not a completed implementation or a passing test. The design follows the requirements in Chapter 1; existing implementation evidence is distinguished from planned work. As of 6 November 2026, the newer workspace UI is a separate interactive review prototype using synthetic fixtures and transient tab state. It has not been integrated with the baseline API or implemented durable projects/jobs. The current research findings are summarised in Section 4.2.3.13; they have not changed the serving model.

## 3.1. System Overview

### 3.1.1. Product Context

The research pipeline prepares data, trains and evaluates models offline. One local web application loads a frozen model and reference snapshots; it supports researchers choosing substitutions for follow-up experiments. Runtime input and project observations stay on the local computer.

### 3.1.2. Functional Overview

The first release covers UC-01 to UC-10 of Chapter 1: prediction, ranking, export, protein/tile lookup, experimental comparison, ClinVar/reference annotations, evidence pages, peptide/protein jobs, experimental import and persistent project history. There is one product configuration with local operation; public hosting and public sharing are excluded.

## 3.2. System Architecture

### 3.2.1. Architectural Components

Figure 3.1 shows the target components. All application listeners use loopback; reference downloads and training are preparation activities outside the runtime workflow.

The React client owns input, matrix/ranking interaction and project/job/import screens. FastAPI validates input, applies domain rules, serves reference annotations





**Figure 3.1.** Planned components of the single local application; arrows denote data interactions.

and stores snapshots. A local worker uses the same inference package for jobs; PostgreSQL stores job state and project-owned records. Generated local file paths hold committed imports and versioned artefacts. Reference ETL never writes user observations into research data.

### 3.2.2. Interaction Between Components

A single-tile preview is validated and scored without persistence. Explicit Save creates an immutable analysis in a selected project. Batch submission pins model, calibrator, gate and source versions, returns a job ID, then the worker claims items transactionally. The client polls progress and opens per-tile results. Expired worker leases are recovered after restart; completed items are not duplicated. Cancellation and project deletion prevent late writes.

An import first produces a validation preview. Only a valid, explicitly committed dataset becomes available for comparison. A comparison selects a saved analysis and dataset revision, checks assay and mutation alignment, and stores its own result/provenance. Reading history uses saved snapshots, not a new inference call or the latest ClinVar release.

### 3.2.3. Design Rationale

React supports the interactive matrix, filtered tables and long-running-task states. FastAPI keeps the model computation in Python and provides an explicit REST contract. A local worker separates job execution from interactive requests without

introducing a cloud service. Persistent projects require a database and snapshot lifecycle beyond the baseline transient preview. The trade-offs are local resource limits, file/database consistency and additional recovery/deletion tests. SQLite remains useful for isolated tests, while local PostgreSQL integration is an acceptance task. The OpenAPI contract marks new operations as planned; generating a schema does not implement them.

## 3.3. Data Design

### 3.3.1. Data Sources and Preprocessing

Reference snapshots have version/date, checksum and terms of use. Research-only sources and project-imported observations are kept distinct from served reference data (Table 3.1).

**Table 3.1.** Data roles in research and the first local release

| Source | Role and boundary |
|---|---|
| Zhang Mendeley v2 [17] | Mutation labels and reference observations; training use labelled. |
| GEO GSE240610 [18] | GPS screen context; preserve estimator and source provenance. |
| UniProtKB/Swiss-Prot | Pinned human reference sequences, accessions and coordinate/WT checks. |
| ClinVar | First-release missense annotation; source/review/conflict state, attribution and diagnostic disclaimer. |
| Project CSV/TSV | User observations for assay-aware comparison only; preserve source, units and replicates. |
| Voutsinos/PAP [4] | Research baselines and transfer-learning studies; not a replacement for mutation labels. |
| Larsen [6] and other restricted sources | Research-only consideration subject to rights; not automatically imported into the service. |

### 3.3.2. Data Model

Reference entities are source, protein, tile, measured cell, ClinVar variant and model version. The planned workspace adds project, analysis job, job item, analysis run/cell, imported dataset/observation and comparison. Legacy expiring share tables are not reused as persistent project history.

### 3.3.3. Data Dictionary

**Table 3.2.** Key workspace fields and invariants

| Entity | Required information |
|---|---|
| Project | UUID, name, description, creation/update time; one local workspace. |
| Job and item | Mode/input IDs, pinned configuration, states/counts, item errors, coverage and worker lease; unique completed result per item. |
| Analysis run/cell | Input and coordinate context; model/gate hashes; scores, rank, warnings, annotation/source snapshot and parent rerun ID. |
| Dataset/observation | File hash/revision, assay/endpoint/units/source, WT sequence, position, WT/replacement, value/missing reason and replicate. |
| Comparison | Run/dataset IDs, explicit replicate/aggregation, compatibility decision, alignment counts and metric/result snapshot. |

### 3.3.4. Relationships Between Entities

A project owns jobs, runs and datasets. A job contains input items; each successful tile item produces one immutable run with 532 cells. Dataset observations retain unique mutation/replicate keys. A comparison joins one run and one committed dataset from the same project. Source/model artefacts are versioned independently; changing active reference data must not change an old analysis. Deletion shows dependencies, stops related work and removes owned files/results with retryable cleanup; shared references and weights remain intact. Committed history has no automatic 30-day expiry.

## 3.4. Method and Model Design

Input remains the reference peptide, position and replacement; target is $\Delta$PSI. The existing service baseline is the frozen ridge/Platt model from Section 4.2.3.9. This scope update does not choose a replacement model. Full-PSI CNN, pLM-family and LoRA development evaluation is complete; a compatible final serving refit, calibration and export remain required. Raw effect and calibrated $P(\Delta\text{PSI} \geq 1)$ remain separate fields.

### 3.4.1. Research Campaign and Recovery Design

The execution unit is a dependency-tracked job with pinned code, data, model revision, protocol and runtime identity. The Kaggle run supplies the reference experiments; the Windows successor expands the pLM family and completes a matched frozen–LoRA comparison. These runs use the same development population, but

different software and GPU environments. They are retained as separate estimates.

Figure 3.2 shows how interrupted work is recovered. Completed outputs can be inherited only after compatibility and checksum checks. The tokenizer-repair successor reuses 456 completed jobs from the earlier local campaign; it does not count those jobs twice. Paused training uses committed checkpoints, including optimiser and random-state information. A timer-failure run that produced no scientific OOF predictions is superseded. A final report job denotes completion of the runnable graph; missing reviewed external and structure inputs remain explicit pending states.





**Figure 3.2.** Campaign lineage and evidence roles at completion on 6 November 2026. Inheritance preserves compatible work; the combined review does not create independent datasets.

### 3.4.2. Nested Selection and Prediction Aggregation

The evaluation unit is a mutation cell, while splitting and uncertainty respect protein groups. The full-PSI development set W contains 235 peptides, 221 groups and 122,412 cells. Five fixed outer folds are shared across recipes. Seeds 17, 29 and 43 vary the inner group split and stochastic fitting; they do not provide three independent outer test partitions. Arm B permits training examples with WT PSI at

most 4; arm D permits the full training range. Inner validation and outer test remain full-range in both arms. The earlier Kaggle arm E balances WT-PSI strata within training.

All preprocessing is fitted on permitted training examples. Hyperparameters, family choices and neural epochs are selected by inner validation MSE. A fresh model is then fitted on permitted outer training data before predicting the untouched outer test. The nested family selector chooses among 36 frozen-feature recipes separately for each seed/fold; it does not choose the best outer OOF score. Figure 3.3 distinguishes this selection from the locked transfer evaluation.

### 3.4.3. Frozen Features and Matched Adaptation

The family experiment includes ESM2 at 8M, 35M, 150M and 650M parameters, ESM1b-650M, one ESM1v-650M checkpoint, ESM-C-300M, the ProtT5 encoder and Ankh-base. For each substitution, the mutant-minus-WT residue embedding at the mutation site is concatenated with its sequence mean. Frozen features are reduced to 64 principal components using training-only transforms and combined with either the common auxiliary features alone or additional ordered W5 context. Ridge regularisation is chosen from $\{0.1, 1, 10, 100, 1000\}$ by inner MSE. The design has $9 \times 2 \times 2 \times 3 \times 5 = 540$ outer fits.

The second experiment holds ESM2-35M, the group folds, auxiliary inputs, head initialisation and training schedule common between frozen and LoRA branches. Both use a 64-unit ReLU head with dropout 0.2. LoRA [15] adds rank-8 adapters with scale $16/8$ to attention query and value projections while retaining frozen pretrained weights. The frozen branch trains the head only. Both branches use AdamW, learning rate $10^{-4}$, weight decay 0.01, batch size 8, FP32 computation and gradient clipping at 1. Inner selection permits at most 20 epochs with patience 4, followed by a fresh outer refit for the selected epoch count. The backbone remains in evaluation mode in both branches so that its dropout policy is matched. There are 30 outer fits per branch.

The local environment is Python 3.11.9, PyTorch 2.13.0 with CUDA 13.0, Transformers 5.17.0 and an RTX 5060 Laptop GPU with approximately 8 GiB memory. Model/tokenizer weights are cached and revision-pinned. ProtT5 initially reached a misleading tokenizer fallback requesting `tiktoken`; installing the missing Protobuf dependency restored its intended tokenizer. Ankh uses the original fast





**Figure 3.3.** Group-aware selection and evaluation. The three seed predictions are averaged per cell before computing ensemble metrics. The separate transfer set T evaluates the fixed W5-D recipe.

tokenizer with residue-level input and an FP32 encoder because FP16 hidden states were non-finite. ProtT5 uses FP16 encoding; stored family features use FP16. These execution choices are recorded parts of the recipes, so this is not a controlled comparison of pretraining alone.

### 3.4.4. Uncertainty, Calibration and Transfer Boundaries

MAE is first averaged within a peptide and then across peptides. Positive-event metrics use $\Delta\text{PSI} \geq 1$; negative-event metrics use $\Delta\text{PSI} \leq -1$ and require at least three cells from each class within a peptide. Paired differences are bootstrapped over protein groups with 5,000 resamples. Four matched local contrasts (two arms, MAE and positive AUROC) are additionally reported with conservative post-hoc Bonferroni 98.75% intervals. This adjustment does not turn the development expansion into a preregistered independent confirmation.

Three-class probabilities represent negative, neutral and positive effects. Each outer-fold calibrator is fitted using predictions on its inner validation groups, disjoint from the outer test; probabilities are averaged across seeds. The multiclass Brier score is $\sum_{c=1}^{3}(p_c - y_c)^2$ per cell, without division by the number of classes. Both cell-micro and peptide-macro averages are reported. A null predictor uses inner-validation class frequencies; positive-event ECE uses ten equal-width probability bins. Calibration is evaluated out of fold, separately from final serving-model construction.

For transfer, W5-D is fixed before inspecting T, refitted on all permitted W data, and applied to the locked scanning population with no recorded protein-group overlap with W or scanning development data. T has a different substitution/label distribution and comes from a previously explored source in the same laboratory. It does not provide a new independent external cohort. No LoRA model is selected or evaluated using T in the completed campaign.

**Domain integration.** The effect model's intrinsic-WT training threshold must not be applied directly to the GPS screen estimator. The R3 research provides a two-tier gate with an intermediate borderline state; integrating its frozen rules and provenance into the baseline remains pending. Every tile has domain evidence; known out-of-domain scoring requires an explicit warned override. Whole-protein mode is a collection of peptide-context predictions, not a validated intact-protein model.

## 3.5. Functional Design

### 3.5.1. Batch and Protein Processing

Peptide mode accepts a bounded list or multi-record FASTA of 28-residue inputs. Protein mode accepts one reference accession or one FASTA record. Tile $n$ starts at $(n-1) \cdot 23 + 1$ and ends 27 residues later; only full windows are generated. Report uncovered intervals, invalid windows and domain refusals. Overlapping protein substitutions retain their tile contexts without averaging. Job states are pending, running, completed, partial, failed or cancelled; per-item states and counts explain partial results. Browser tables are paginated; exports include every outcome.

### 3.5.2. Import and Comparison

CSV/TSV rows contain peptide ID, WT sequence, 1-based position, WT/replacement, observed value and replicate. Optional accession/release/start coordinates are checked together. Metadata identify assay, endpoint, units, source and reference. Duplicate/conflicting mutation-replicate keys, nonfinite values and WT mismatches block commit. Empty observations retain a missing reason.

Comparison requires exact mutation alignment and explicit replicate selection or aggregation. Comparable GPS $\Delta$PSI supports residuals (prediction minus observation), MAE and Spearman with sample counts; insufficient/constant pairs have no reported correlation. Different assay endpoints remain separate without pooled metrics. Imported observations do not automatically constitute independent validation or become training labels.

### 3.5.3. Annotations and Project Screens

The first release shows ClinVar alongside approved UniProt/GPS context. Show classification, review/conflict state, source release and WT-coordinate agreement; distinguish no match from unavailable/ambiguous mapping. Attribution and diagnostic disclaimer travel with saved/exported annotations. Custom unmapped sequences have explicit annotation-unavailable states. The project workspace exposes history, jobs and datasets; users can reopen snapshots, create reruns as new entries and confirm deletions. New screens and API routes remain pending implementation.

## 3.6. Local Execution View

One computer hosts the browser, API, worker, PostgreSQL and workspace files. Application listeners bind to loopback; the frontend origin is explicitly allowed. Docker may package the same components, but no remote host, public URL, TLS deployment or separate product edition is required. Appendix A separates baseline startup from the pending first-release workflow.

# CHAPTER 4: TESTING AND EVALUATION

## 4.1. Testing Objectives

To check that the research pipeline gives reproducible results without leakage between training and test clusters, and that the prototype validates input, keeps coordinates and score direction correct, and exports data consistently with the research runner.

This chapter has two parts. Section 4.2 reports the experimental evaluation of the research pipeline; these experiments have been run. Sections 4.3 to 4.6 follow the test-plan outline of the Faculty for the prototype tool. The numerical results retained here come from the recorded CLI verification artefacts. Baseline web/API code and historical local checks also exist, but the first-release extensions confirmed on 29 October 2026 require implementation and new local acceptance evidence; no passing result for those additions is claimed here.

## 4.2. Experimental Evaluation

This section preserves the initial restricted-PSI experiments and then reports the important follow-up findings and completed campaigns available on 6 November 2026 (Section 4.2.3.13). The original 91-peptide test and the full-PSI evaluation have different populations and primary metrics; their scores must not be read as a single improvement curve. All remain development evidence.

### 4.2.1. Experimental Setup

**Data and labels.** The labels come from the saturation-mutagenesis experiment of Zhang et al. [3, 17]. For each peptide, the effect of a substitution is $\Delta\text{PSI} = \text{PSI}_{\text{mutant}} - \text{PSI}_{\text{WT}}$ (Chapter 2). The data set contains two replicate halves of each peptide. The $\text{PSI}_{\text{WT}}$ reference of a half is the median PSI of the synonymous cells of that half, and at least ten such cells are required. The cell label is the mean $\Delta$PSI of the two halves; a cell is *positive* when $\Delta\text{PSI} \geq 1$. In the initial restricted benchmark, a peptide is accepted only if $\text{PSI}_{\text{WT}} \leq 3.0$. Table 4.1 shows how the 248 raw saturation peptides reduce to the 91 peptides of the benchmark. The single largest cause of loss is the degron threshold, which removes 144 peptides; the technical causes together remove only $10 + 2 + 1 = 13$ peptides. The benchmark set contains 91 peptides in 89 pro-

tein clusters and 47 847 cells. The measurement ceiling of this set, computed as the agreement between its two experimental halves, is 0.9519 AUROC.

**Table 4.1.** Fate of the raw saturation peptides under the label filters

| Outcome of the label filters | Peptides |
|---|---|
| Retained: the benchmark set | 91 |
| Removed only by the degron threshold ($PSI_{WT} > 3.0$) | 144 |
| Fewer than 10 synonymous cells for the WT reference in a half | 10 |
| Sequence mismatch between scan file and UniProt | 2 |
| No sequence could be derived | 1 |
| *Raw saturation peptides* | *248* |

**Splits.** Proteins are clustered with MMseqs2 [11] at 30% identity and 80% coverage (cov80). The outer evaluation uses five folds with whole clusters assigned to folds. Inside each outer training set, 20% of the clusters form a validation set for choosing hyper-parameters, so no outer-test label is ever used for tuning. Training is repeated with seeds 17, 29 and 43. The three seeds share the same outer partition and differ only in the inner validation split and in network initialisation, so they are not three independent partitions. The reported score of a model is the AUROC of the average of the three seeds' out-of-fold scores; per-seed results are also kept.

**Models.**

- **Ridge M3.** Ridge regression [12] on 180 features: one-hot reference and substituted amino acid (40), peptide composition (20) and the ordered $\pm 3$ residue context (120). The penalty is chosen from $\{1, 10, 100, 1000\}$ on the inner validation set.
- **$\Delta$PAP.** The difference of the PAP degron score [4] between mutant and wild type, with the published network frozen (variant `cnn2w1`). It is the reference baseline and uses no training labels.
- **Gated networks.** The same 180 features, with the substitution (pair) and the composition-plus-context inputs projected separately to 32 dimensions; a sigmoid of the pair projection multiplies the context representation, followed by

an MLP ($64 \to 32 \to 1$). Variants add the frozen $\Delta$PAP as a residual or remove the gate. Training uses AdamW (learning rate $2 \times 10^{-3}$, weight decay $0.01$, batch of about 1,024, at most 60 epochs, patience 8).

- **Degformer.** The published checkpoint (epoch 50) of the transformer [7], scored as pred(mutant) − pred(WT); and the same architecture (d_model 128, 4 layers, 8 heads) retrained from scratch on the training clusters of each fold.

Further interaction designs (FiLM, rank-8 bilinear, ridge with cross-product features) were added as *pre-registered candidates* in Section 4.2.3.3.

**Pre-registration.** The acceptance criteria of the overlap check, the interaction designs, the retrained Degformer architecture, the learning-curve and threshold experiments, the re-clustering, the pre-training experiment, the calibration and the audit of the external labels were written to a protocol file before the experiments were run, and were not changed afterwards. Where a result below is described as met or not met, it refers to those fixed criteria. Observations made after seeing the numbers are labelled as descriptive. The first direct-learning experiment (Table 4.2) has a protocol file but is treated as exploratory.

**Environment.** The initial experiments described below ran on CPU with Python 3.12.3, NumPy 2.5.3 and PyTorch 2.14.0 (CPU build); each result file records the SHA-256 of its input and of its runner. Large caches and checkpoints are generated again by the runners. The subsequent notebook runs used Kaggle GPUs, and the local expansion uses a separate Windows CUDA runtime (Section 4.2.3.13); checkpoints and feature arrays require separate storage.

### 4.2.2. Evaluation Metrics

For the initial restricted benchmark, the main metric is the cell-level AUROC (positive: $\Delta\text{PSI} \geq 1$), computed per peptide that has both classes and then averaged over peptides (macro AUROC). Paired differences between two models are computed on the same peptides. The 95% confidence intervals come from 5,000 bootstrap resamples of protein clusters [16]; every peptide of a sampled cluster is kept, so cells and peptides are not treated as independent. These intervals are conditional on the stored out-of-fold predictions and do not include the variance of retraining. No correction is

made for the many comparisons, so a single interval is a development-stage indication and not a confirmation. The full-PSI follow-up instead uses peptide-macro MAE as its primary metric and identifies the two adjusted primary intervals separately.

Probabilities are assessed with the Brier score (the mean squared difference between the predicted probability and the 0/1 label over the cells), the Brier skill score against a constant forecast of the base rate, $\mathrm{BSS} = 1 - \mathrm{Brier}/\mathrm{Brier}_{\mathrm{const}}$, and the expected calibration error (ECE) over ten equal-mass bins, pooled over the outer-test cells and bootstrapped by cluster in the same way. Ranking utility is the *enrichment at* $k\%$: for each peptide, the substitutions are ordered by predicted score, the precision of the top $k\%$ is divided by the fraction of positive cells of that peptide, and the ratio is averaged over the peptides that have both classes; a random ranking has enrichment 1.

### 4.2.3. Results

All results below are on a *development benchmark*: the same 91 peptides have been examined in several experiments, and the out-of-fold design is not an independent validation on unseen data.

#### *4.2.3.1. Direct Learning on the Saturation Matrix*

Table 4.2 lists the macro AUROC of each model. Ridge M3 reaches 0.8082, above the frozen ΔPAP baseline (0.7693). The paired difference is +0.0389 with a cluster-bootstrap interval [+0.0216, +0.0571] (Table 4.3). The gated network with residual ΔPAP reaches 0.8002 and is below ridge (difference −0.0080, [−0.0152, −0.0006]). Removing the gate (0.7937) or the ΔPAP residual (0.8015) does not change this picture: both variants stay below ridge.

The result of the gate is not stable across seeds (Table 4.4). In seed 29 the gated network is *below* the network without the gate (difference −0.0076, [−0.0152, −0.0005]), whereas it is above in the other two seeds. The ensemble figure should therefore not be read as evidence that the gate helps.

#### *4.2.3.2. Published Degformer Checkpoint and Retrained Architecture*

The published Degformer checkpoint scores 0.9248, but this is not a held-out result: 42 163 of the 47 847 mutant cells (88.12%) have an exact sequence in its training file, and the wild type of all 91 peptides is in it as well. A natural suspicion is

**Table 4.2.** Macro AUROC on the 91 peptides of the saturation benchmark. The last column keeps only the cells whose exact sequence is not in the training data of the published Degformer.

| Model | All cells | Cells without exact-sequence overlap |
|---|---|---|
| ΔPAP, frozen (reference) | 0.7693 | 0.7531 |
| Ridge regression on M3 features | 0.8082 | 0.8040 |
| Gated network + residual ΔPAP | 0.8002 | 0.7956 |
| Network without gate, with ΔPAP | 0.7937 | 0.7892 |
| Gated network without ΔPAP | 0.8015 | 0.7940 |
| Degformer, published checkpoint (overlaps its training data) | 0.9248 | 0.9227 |

**Table 4.3.** Paired AUROC differences between models

| Paired comparison (same peptides) | Difference in AUROC [95% cluster-bootstrap CI] |
|---|---|
| Ridge − ΔPAP | +0.0389 [+0.0216, +0.0571] |
| Gated + ΔPAP − ΔPAP | +0.0309 [+0.0125, +0.0501] |
| Gated + ΔPAP − ridge | −0.0080 [−0.0152, −0.0006] |
| Gated + ΔPAP − no gate | +0.0065 [+0.0027, +0.0102] |
| Gated + ΔPAP − gated without ΔPAP | −0.0013 [−0.0048, +0.0023] |

**Table 4.4.** Per-seed AUROC of the three main models

| Seed | Ridge | Gated +ΔPAP | No gate | Gated − no gate [95% CI] |
|---|---|---|---|---|
| 17 | 0.8062 | 0.7895 | 0.7806 | +0.0089 [+0.0038, +0.0145] |
| 29 | 0.8068 | 0.7762 | 0.7838 | −0.0076 [−0.0152, −0.0005] |
| 43 | 0.8081 | 0.7881 | 0.7816 | +0.0064 [+0.0013, +0.0113] |

that this exact overlap alone explains the high score. Restricting the evaluation to the 5 684 cells without overlap leaves the score essentially unchanged (0.9227, Table 4.2), so exact cell overlap does not explain the gap. The remaining leak is at the level of the peptide: the model has seen most of the matrix of every peptide, and removing a few dozen cells does not create an unseen peptide. The comparison of the published checkpoint with the models of this thesis is therefore not a fair test of generalisation, and no claim is made about it.

A fair comparison of the architecture requires the same label budget and the same cluster-wise split. Retrained under these conditions (one seed, hyper-parameters as published by its authors, target the absolute PSI), the Degformer architecture reaches 0.7500, below ridge (difference −0.0582, [−0.0734, −0.0426]) and below ΔPAP (Table 4.5). This lower score is not necessarily a property of the architecture itself: it may reflect the small number of training clusters (see Section 4.2.3.4).

#### *4.2.3.3. Interaction Designs*

Three interaction designs were fixed before running: FiLM, a rank-8 bilinear form and ridge with 2,400 cross-product features. A candidate was to be called a useful architectural component only if the following held at the same time: (a) its paired difference to ridge is positive in all three seeds, (b) the confidence interval of the ensemble difference excludes zero, and (c) the same holds against ΔPAP. None of the candidates met the criterion (Table 4.5). The best of them, FiLM, is −0.0054 ([−0.0136, +0.0028]) relative to ridge and is below ridge in every seed. The sigmoid gate of the first experiment gives the same direction, and the retrained Degformer architecture is far lower. All candidates are above the frozen ΔPAP, but so is plain ridge.

This result does not show that interaction between the substituted amino acid and its context is absent. It shows that, at this sample size (89 clusters), what four different mechanisms add is not enough to offset the variance they bring. The question of model capacity is therefore left open and is not answered by trying one more variant (see Section 4.2.3.4).

**Table 4.5.** Interaction designs against ridge M3. "Criterion met" applies the pre-registered rule above; for the sigmoid gate and the one-seed Degformer architecture the rule is applied descriptively.

| Candidate | AUROC | Candidate − ridge [95% CI] | Per-seed difference | Criterion met |
|---|---|---|---|---|
| Sigmoid gate +ΔPAP (G2 runner) | 0.8002 | −0.0080 [−0.0152, −0.0006] | −0.0168, −0.0306, −0.0200 | No |
| FiLM (pair-generated scale and shift) | 0.8028 | −0.0054 [−0.0136, +0.0028] | −0.0104, −0.0162, −0.0091 | No |
| Rank-8 bilinear | 0.7933 | −0.0149 [−0.0227, −0.0072] | −0.0212, −0.0275, −0.0335 | No |
| Ridge with 2,400 cross-product features | 0.7924 | −0.0158 [−0.0227, −0.0086] | deterministic | No |
| Degformer architecture, retrained (one seed) | 0.7500 | −0.0582 [−0.0734, −0.0426] | one seed only | No |

#### *4.2.3.4. Learning Curve and Relaxing the Degron Threshold*

Two questions were put together and their criteria fixed before running. **P1:** does the AUROC still rise with the number of training clusters? **P0:** can the 85 peptides removed by the degron threshold be used as extra *training* labels if the threshold is relaxed from 3.0 to 4.0? The design keeps the outer-test cells exactly equal to those of the 91 benchmark peptides, so every number is comparable with 0.8082; the added peptides enter only the outer-training sets, and those that fall in a test cluster are removed from the training of that fold (531 cells in fold 0 and 532 cells in fold 3, none in the other folds). The partition of the five folds was checked to be identical to the earlier experiment; at the 100% level, the two models reproduce the earlier scores of 0.8082 and 0.8015 exactly. Two models of different capacity were fixed in advance: ridge M3 and the gated network without ΔPAP.

**P1.** Table 4.6 and Figure 4.1 show the curves. Under the fixed rule the learning curve of ridge does not support the hypothesis of label shortage (Table 4.7). From 100% to 50% of the clusters the difference is only +0.0038 ([−0.0009, +0.0087]) and the sequence of means is not monotone. This must not be read as evidence that the data limit has been reached: the design does not measure a ceiling. The gated network behaves differently: it gains +0.0156 ([+0.0060, +0.0256]), the curve is monotone, and the criterion is met. The two curves together suggest that ridge has absorbed what





**Figure 4.1.** Macro AUROC against the mean number of training clusters (nested cluster subsets of 25, 50, 75 and 100% of the outer-training data; the dashed segment is the relaxed-threshold training set).

**Table 4.6.** Learning curve (P1) and relaxed degron threshold 4.0 (P0). Ranges are over 5 folds and 3 seeds.

| Training level | Train clusters | Train cells | Ridge M3 | Gated, no ΔPAP |
|---|---|---|---|---|
| 25% | 18 | 9 068–10 314 | 0.7776 | 0.7529 |
| 50% | 35–36 | 18 635–19 877 | 0.8044 | 0.7859 |
| 75% | 52–54 | 28 145–29 048 | 0.8088 | 0.7949 |
| 100% | 70–72 | 38 233–38 290 | 0.8082 | 0.8015 |
| 100% + relaxed threshold | 153–155 | 82 191–82 780 | 0.8208 | 0.8154 |

the original distribution of clusters can teach it, while the larger-capacity network is still rising at about 70 clusters. The gap between ridge and the network narrows with data but is not closed (ridge is still higher by 0.0054 at the relaxed-threshold level); the result does not rehabilitate any of the rejected designs, and it must not be extrapolated to "more data will make the architecture win". One of the predictions written before the run, that P1 would probably be supported, was therefore not borne out for ridge.

**P0.** Adding 85 peptides (44 490 cells, 83 clusters not in the benchmark) lifts ridge from 0.8082 to 0.8208, a gain of +0.0126 ([+0.0061, +0.0190]), positive in each seed (+0.0142, +0.0142, +0.0128). The gated network gains +0.0139 ([+0.0059, +0.0218]). Both meet the pre-registered criteria. The protocol had also predicted, before the run, that P0 would probably fail, because peptides with a high $PSI_{WT}$ are already stable and might have almost no positive cells. The measurement contradicts this prediction (Table 4.8): the share of positive cells falls only from 13.1% to 11.4%, and the 95th percentile of ΔPSI in the added peptides is 1.51, against 1.70 in the benchmark peptides. The threshold of 3.0 therefore appears more conservative than the mutation-effect task requires, even if it is the right threshold for the different question of whether a peptide is a degron.

**Table 4.7.** Pre-registered verdicts of P1 and P0

| Model | Question | ΔAUROC [95% CI] | Pre-registered criteria | Verdict |
|---|---|---|---|---|
| Ridge M3 | P1: 100% − 50% | +0.0038 [−0.0009, +0.0087] | CI> 0: no; monotone: no | insufficient evidence for label shortage |
| | P0: relaxed − 100% | +0.0126 [+0.0061, +0.0190] | CI> 0: yes; all seeds > 0: yes | accepted |
| Gated, no ΔPAP | P1: 100% − 50% | +0.0156 [+0.0060, +0.0256] | CI> 0: yes; monotone: yes | supported |
| | P0: relaxed − 100% | +0.0139 [+0.0059, +0.0218] | CI> 0: yes; all seeds > 0: yes | accepted |

#### *4.2.3.5. Number of Clusters or Coverage of the Distribution*

The two curves of the previous section seem to contradict each other: ridge is flat between 35 and 71 clusters, yet it rises when 83 more clusters are added. One

**Table 4.8.** Cells of the benchmark peptides and of the 85 peptides added by relaxing the threshold

| Statistic | Benchmark set (91 peptides) | Added set (85 peptides) |
|---|---|---|
| Median $PSI_{WT}$ | 2.593 | 3.346 |
| Fraction of positive cells ($\Delta PSI \geq 1$) | 0.1310 | 0.1140 |
| Median $\Delta PSI$ | 0.125 | 0.083 |
| 95th percentile of $\Delta PSI$ | 1.697 | 1.507 |

reading is that the two steps add different things: the first thickens the existing region of $PSI_{WT}$, the second widens it. The previous experiment cannot separate the two, because it changes the number of clusters and the region together. A second experiment, with its criteria fixed before running, keeps the whole original training set and adds a nested fraction of the new clusters (Table 4.9). The main criterion compares the gain at +50% of the new clusters (about 42 clusters) with the marginal gain of 36 old-region clusters measured before, 0.0038.

**Table 4.9.** Gain over the benchmark training set when a fraction of the new clusters is added

| New clusters added | Mean added | Ridge | Gain | Gated | Gain |
|---|---|---|---|---|---|
| none (benchmark) | 0 | 0.8082 | — | 0.8015 | — |
| +25% | 21 | 0.8143 | +0.0061 | 0.8090 | +0.0075 |
| +50% | 42 | 0.8196 | +0.0114 | 0.8118 | +0.0103 |
| +75% | 64 | 0.8204 | +0.0122 | 0.8168 | +0.0153 |
| +100% | 85 | 0.8208 | +0.0126 | 0.8154 | +0.0139 |

For ridge the gain at +50% is +0.0114 ([+0.0063, +0.0166]), whose interval lies entirely above 0.0038: the main criterion supports coverage of the distribution. For the network the interval contains 0.0038, so the new clusters are useful but not shown to be better than old ones (Table 4.10). The secondary criterion, the shape of the curve, gives the opposite answer: the gain at +25% is 48.4% of the total for ridge and 54.4% for the network, below the threshold of 60% fixed for “early saturation”, so the fixed rule says “proportional to the number of clusters”. Because the two fixed criteria disagree, the question is *not decided*. As a descriptive remark only, the successive increments of ridge are +0.0061, +0.0053, +0.0007, +0.0005, so roughly 90% of the

total gain is already reached at +50%, and the threshold of 60% at +25% was a poor operational choice. This remark does not overturn the verdict.

**Table 4.10.** Pre-registered verdicts on the new clusters. The reference marginal gain of old-region clusters is 0.0038.

| Model | B(50%) − B(0) [95% CI] | Share of total gain at +25% | Primary criterion | Shape criterion |
|---|---|---|---|---|
| Ridge M3 | +0.0114 [+0.0063, +0.0166] | 48.4% | supports wider coverage of the distribution | proportional to cluster count |
| Gated, no ΔPAP | +0.0103 [+0.0033, +0.0172] | 54.4% | valuable, but not shown to exceed old-region clusters | proportional to cluster count |

What can be stated is limited: clusters from the region $3.0 < \mathrm{PSI}_{\mathrm{WT}} \leq 4.0$ have a marginal value at least equal to that of old-region clusters, and for ridge the evidence suggests it is higher. It cannot be said that the gain is *only* due to wider coverage, because the 83 new clusters differ from the old ones both in region and in protein.

#### *4.2.3.6. Sensitivity to the Threshold*

The four thresholds 3.5, 4.0, 4.5 and 5.0 were run in one pass and are all reported (Table 4.11, Figure 4.2). The main configuration of the thesis stays at 4.0, a value fixed before this grid was seen and chosen then only because it roughly doubles the number of peptides; it is not re-chosen from the grid. Every threshold is better than the benchmark training set (all intervals above zero). The ridge gain is highest at 4.0 (+0.0126) and lower at 4.5 (+0.0101) and 5.0 (+0.0093); under the fixed rule (a drop of more than 0.002) this is labelled “decline after 4.0”. That label describes the shape of the point estimates: the intervals overlap widely, and no interval was computed for the difference between 4.0 and 4.5. The gated network is nearly flat from 3.5 to 5.0, so the decline is a property of ridge. It also depends on how a positive cell is defined: with the positive cut at $\Delta\mathrm{PSI} \geq 1.5$ the maximum for ridge moves to 5.0 (+0.0098) and there is no decline. The share of positive cells in the added peptides falls steadily with the threshold (Table 4.11), which is consistent with peptides that are not degrons starting to dilute the training set (an interpretation, not tested separately).

**Table 4.11.** Added data and gains for each degron threshold (cov80, positive cut $\Delta\text{PSI} \geq 1$)

| Thr. | Peptides | Cells | New clusters | Pos. rate | Ridge AUROC | Ridge Δ [95% CI] | Gated Δ |
|---|---|---|---|---|---|---|---|
| 3.5 | +50 | 26 234 | 48 | 0.1197 | 0.8185 | +0.0103 [+0.0043, +0.0164] | +0.0115 |
| 4.0 | +85 | 44 490 | 83 | 0.1140 | 0.8208 | +0.0126 [+0.0061, +0.0190] | +0.0139 |
| 4.5 | +106 | 55 362 | 102 | 0.1028 | 0.8183 | +0.0101 [+0.0028, +0.0172] | +0.0125 |
| 5.0 | +121 | 63 009 | 117 | 0.0918 | 0.8175 | +0.0093 [+0.0016, +0.0169] | +0.0133 |





**Figure 4.2.** Gain in macro AUROC over the benchmark training set for each degron threshold, with 95% cluster-bootstrap intervals (horizontal offsets only separate the two models).

The gain at 4.0 survives three definitions of a positive cell and a different assignment of folds (Table 4.12); all four intervals are above zero. The last row must be read with care. The clustering at 50% coverage was meant to test sensitivity to the coarseness of clustering, but on this peptide set cov50 and cov80 produce the same number of clusters (89) and, as found after the run, the same grouping of peptides; only the representative labels differ, which changes how clusters are assigned to the five folds (the benchmark score becomes 0.8116 instead of 0.8082). That row therefore tests a re-assignment of folds, not coarser clustering; clustering granularity is tested with genuinely different partitions in Section 4.2.3.7.

**Table 4.12.** Robustness of the gain at threshold 4.0 (ridge M3)

| Condition (threshold 4.0) | Ridge $\Delta$ vs. base [95% CI] | CI $> 0$ |
|---|---|---|
| cov80, $\Delta$PSI $\geq 0.5$ | +0.0110 [+0.0051, +0.0169] | yes |
| cov80, $\Delta$PSI $\geq 1.0$ (main) | +0.0126 [+0.0061, +0.0190] | yes |
| cov80, $\Delta$PSI $\geq 1.5$ | +0.0094 [+0.0037, +0.0149] | yes |
| cov50 fold assignment, $\Delta$PSI $\geq 1.0$ | +0.0096 [+0.0032, +0.0159] | yes |

#### *4.2.3.7. Sensitivity to the Clustering Granularity*

Because cov50 does not change the partition on this peptide set, a grid of seven partitions of the 176 peptides (the 91 benchmark peptides and the 85 added ones) was fixed before running: grouping by UniProt accession (no clustering), the reference MMseqs2 setting (30% identity, 80% coverage) and five looser MMseqs2 settings. The P0 comparison (ridge M3, relaxed threshold 4.0 against the benchmark training set, same cluster bootstrap) was repeated with the folds rebuilt from each partition. The reference level reproduces the earlier scores (0.8082 and 0.8208) and the five folds of the earlier experiment. The criterion fixed in advance: the gain is "robust to granularity" if every partition that differs from the reference and is still informative (fewer than half of the added cells are lost because they share a group with a test peptide) has a bootstrap interval of the gain above zero and a positive gain in all three seeds.

The seven levels give only 4 distinct partitions (Table 4.13): lowering the identity from 0.2 to 0.1 at coverage 0.5, and from 0.1 to 0.0 at coverage 0.3, changes no group, and 30% identity with coverage 0.5 reproduces the reference grouping (only

**Table 4.13.** Gain of the relaxed threshold 4.0 (ridge M3) under different protein partitions. “Groups” are the groups of the 91 benchmark peptides and of all 176 peptides; “Shared” is the number of added peptides that fall in a group of a benchmark peptide; “Excl.” is the mean percentage of the added cells that are removed from training because their group contains a test peptide.

| Partition (MMseqs2) | Groups base/all | Shared | Excl. % | AUROC base → relaxed | Gain [95% CI] | Seeds > 0 |
|---|---|---|---|---|---|---|
| Accession (no clustering) | 91/176 | 0 | 0.0 | 0.8036 → 0.8202 | +0.0166 [+0.0099, +0.0240] | yes |
| id 0.3, cov 0.8 (reference) | 89/172 | 2 | 0.5 | 0.8082 → 0.8208 | +0.0126 [+0.0061, +0.0190] | yes |
| id 0.3, cov 0.5 grouping as reference; folds assigned differently | 89/172 | 2 | 0.5 | 0.8116 → 0.8212 | +0.0096 [+0.0032, +0.0159] | yes |
| id 0.2, cov 0.5 | 87/163 | 6 | 1.4 | 0.8051 → 0.8185 | +0.0134 [+0.0074, +0.0199] | yes |
| id 0.1, cov 0.5 identical to the row above | 87/163 | 6 | 1.4 | 0.8051 → 0.8185 | +0.0134 [+0.0074, +0.0199] | yes |
| id 0.1, cov 0.3 | 71/133 | 22 | 5.2 | 0.8096 → 0.8209 | +0.0113 [+0.0037, +0.0184] | yes |
| id 0.0, cov 0.3 identical to the row above | 71/133 | 22 | 5.2 | 0.8096 → 0.8209 | +0.0113 [+0.0037, +0.0184] | yes |

the group labels, and hence the fold assignment, differ; the gain there is +0.0096 [+0.0032, +0.0159], the same value as the cov50 row of Table 4.12). Three partitions differ from the reference and are informative: grouping by accession (+0.0166, [+0.0099, +0.0240]), 20% identity with coverage 0.5 (+0.0134, [+0.0074, +0.0199]) and 10% identity with coverage 0.3 (+0.0113, [+0.0037, +0.0184]). All intervals are above zero and the gain is positive in all three seeds, so under the fixed rule the gain is *robust to granularity*. The point estimates are not monotone in the coarseness (the largest is for grouping by accession), the intervals overlap, and no test of their differences was planned; the absolute benchmark score also moves with the partition (0.8082 for the reference and 0.8116 for the same grouping with other folds), so absolute values must not be compared across rows.

The test is weaker than its name suggests. The coarsest partition still has 71 groups for the 91 benchmark peptides; in it, 22 added peptides share a group with a benchmark peptide and on average 5.2% of the added cells are removed from training, and one of the five test folds consists of a single group. Whether the gain would survive a still coarser split, for example by protein family, is not known.

#### *4.2.3.8. Pre-Training on Tile Labels*

The experiment of Voutsinos et al. [4] provides a degradation score for 212 616 tiles of 30 residues, without substitutions. The question was whether initialising the gated network (without ΔPAP) from a model pre-trained to predict these scores lets it learn ΔPSI better under the same label budget. The design was fixed in advance. Pre-training treats each tile as 30 wild-type rows (the substituted-residue input is zero), predicts the tile as the mean over positions and regresses the sign-reversed, standardised degron score. Two branches then share the same initial weights, the learning-rate grid ($2 \times 10^{-3}$ or $5 \times 10^{-4}$, chosen on the inner validation set) and the inner validation split, and differ only in whether the network starts from the pre-trained state (*pre*) or from random initialisation (*rand*). To prevent leakage, in each outer fold every gene that has a tile similar to a protein of an outer-test cluster (MMseqs2 at 30% identity with an alignment of at least 50 residues, a shared 12-mer, or the same gene name) is removed entirely from the pre-training data *before* any learning; this removed 318, 34, 176, 99, 44 genes in the five folds. The gate on the reproduction of earlier scores was passed (ridge 0.8082 and 0.8208; the gated network within 6.0e-05 of the earlier

values). Two comparisons were fixed, both with the rule "bootstrap interval above zero and a positive difference in every seed": (A) *pre* against *rand*, and (B) *pre* against ridge M3.

**Table 4.14.** Macro AUROC with and without pre-training on tile labels

| Training configuration | Ridge M3 | Network, random init. | Network, pre-trained |
|---|---|---|---|
| Relaxed threshold 4.0 (main) | 0.8208 | 0.8175 | 0.8098 |
| Threshold 3.0 (secondary) | 0.8082 | 0.8009 | 0.7726 |

**Table 4.15.** Pre-registered comparisons for pre-training. The main configuration is the relaxed threshold 4.0; the threshold 3.0 is reported with the same criteria and was not used to choose the configuration.

| Thr. | Comparison | Difference [95% CI] | Per-seed difference | Met |
|---|---|---|---|---|
| 4.0 (main) | A: pre-trained − random init. | −0.0077 [−0.0163, +0.0006] | −0.0180, −0.0259, −0.0121 | no |
| | B: pre-trained − ridge M3 | −0.0110 [−0.0197, −0.0024] | −0.0234, −0.0330, −0.0263 | no |
| 3.0 (secondary) | A: pre-trained − random init. | −0.0283 [−0.0426, −0.0149] | −0.0295, −0.0345, −0.0427 | no |
| | B: pre-trained − ridge M3 | −0.0356 [−0.0509, −0.0215] | −0.0458, −0.0550, −0.0637 | no |

The result is negative (Tables 4.14 and 4.15). In the main configuration the pre-trained network reaches 0.8098, against 0.8175 for random initialisation: difference A is −0.0077 [−0.0163, +0.0006], an interval that contains zero, so pre-training cannot be distinguished from random initialisation; difference B is −0.0110 [−0.0197, −0.0024], so the pre-trained network is below ridge. At threshold 3.0 both differences are clearly negative (A: −0.0283 [−0.0426, −0.0149]; B: −0.0356 [−0.0509, −0.0215]). The difference is negative in all three seeds in every comparison. By the mapping fixed in advance, the conclusion is "insufficient evidence for a benefit of pre-training". The pre-training task itself was learned (Pearson correlation 0.864 between prediction and score on held-out genes, range 0.857–0.868 over the fifteen runs), so the failure is in the transfer to ΔPSI and not in learning the tile scores. This result rejects only this design, in which the pre-training sees wild-type sequences only and the whole network is then fine-tuned; designs that pre-train with substitutions, freeze part

of this tile-label encoder or train both tasks jointly were not tried. The later frozen-ESM and LoRA experiments use different pretrained representations and are reported separately.

#### *4.2.3.9. Calibration of the Scores and Ranking Utility*

The score of ridge M3 is a predicted ΔPSI, not a probability. To report the probability that a substitution is positive ($\Delta\text{PSI} \geq 1$) the model trained at the relaxed threshold 4.0 was kept fixed and evaluated on the same 47 847 outer-test cells (91 peptides, 89 clusters). Calibrators were fitted only on out-of-fold scores of the outer-training pool: the pool was split again into five inner folds by cluster, the ridge model was refitted on four of them, and the scores of the fifth were kept; the outer-test cells never entered a calibrator. Three conversions were fixed in advance: the *raw* score clipped to $[0, 1]$, Platt scaling (a logistic regression on the score) and isotonic regression, with a constant forecast of the base rate of the training pool as a reference for skill. The criteria were also fixed in advance: a conversion is *calibrated* if the bootstrap interval of $\text{Brier}(\text{raw}) - \text{Brier}(c)$ is above zero and the difference is positive in every seed; it has *skill over the base rate* if the interval of $\text{Brier}(\text{constant}) - \text{Brier}(c)$ is above zero; Platt is used in the prototype unless isotonic regression is better with an interval above zero; and the ranking is *enriching* if the interval of the enrichment at 10% is above 1. The raw scores of the three seeds reproduce the earlier AUROC values (gate passed).

**Table 4.16.** Probability quality on the outer-test cells (observed fraction of positive cells: 0.131). ECE: expected calibration error over ten equal-mass bins; $\hat{p}$: predicted probability.

| Score to probability | Brier | 95% CI | Skill vs. base rate | ECE | Mean $\hat{p}$ |
|---|---|---|---|---|---|
| Raw score, clipped to $[0, 1]$ | 0.1272 | [0.1186, 0.1360] | −0.116 | 0.1437 | 0.2617 |
| Platt (logistic) scaling | 0.0925 | [0.0809, 0.1046] | +0.188 | 0.0163 | 0.1146 |
| Isotonic regression | 0.0925 | [0.0810, 0.1045] | +0.188 | 0.0164 | 0.1145 |
| Constant (base rate of the training pool) | 0.1139 | [0.1011, 0.1276] | — | 0.0154 | 0.1219 |

Platt scaling meets the criterion (Tables 4.16 and 4.17): the Brier score falls

**Table 4.17.** Pre-registered comparisons of the Brier score

| Comparison (positive favours the second term) | Difference [95% CI] | Per-seed difference |
|---|---|---|
| Brier(raw) − Brier(Platt) | +0.0346 [+0.0266, +0.0425] | +0.0346, +0.0347, +0.0347 |
| Brier(raw) − Brier(isotonic) | +0.0346 [+0.0267, +0.0424] | +0.0345, +0.0347, +0.0347 |
| Brier(constant) − Brier(Platt) | +0.0214 [+0.0175, +0.0253] | +0.0212, +0.0215, +0.0215 |
| Brier(Platt) − Brier(isotonic) | +0.0000 [−0.0002, +0.0002] | — |

from 0.1272 to 0.0925, a difference of +0.0346 [+0.0266, +0.0425], positive in each seed (+0.0346, +0.0347, +0.0347); isotonic regression is practically identical (Platt − isotonic: +0.00002, [−0.0002, +0.0002]), so Platt scaling, with two parameters, is used. The skill over the base rate is +0.188, with the interval of +0.0214 [+0.0175, +0.0253] above zero. The first criterion is a low bar: the raw score read as a probability is *worse* than a constant forecast (skill −0.116; mean value 0.262 against 0.131 observed; recalibration slope 0.35), because it is a regression output. The more informative statement is the skill of about +0.188. The ECE alone does not separate the methods here, since the constant forecast has an ECE (Table 4.16) close to that of Platt scaling.

Local calibration is not perfect. The Platt probabilities are lower than the observed frequency in every bin: the mean is 0.115 against 0.131, and in the highest bin the mean prediction is 0.434 against an observed 0.495 (interval 0.449–0.538). A likely cause is a shift of domain introduced by the relaxed threshold: the calibrator is fitted on a pool that includes the added peptides, in which the fraction of positive cells is lower than in the benchmark peptides (Table 4.8). A sensitivity analysis that was not used for the verdict, fitting the calibrator only on benchmark-domain cells, gives a Brier score of 0.0921, an ECE of 0.0044 and a mean probability of 0.131. For ordering substitutions the shift is irrelevant (the transform is monotone); for absolute probabilities it must be kept in mind.

For prioritising substitutions (Table 4.18), choosing the top 10% of each peptide (about 54 substitutions) gives a precision of 0.47 and a recall of 0.41, an enrichment of 4.02 ([3.70, 4.35]); the criterion is met. The only reference is a random

**Table 4.18.** Ranking utility: the substitutions of each peptide (532 per 28-residue peptide) are ordered by the raw score. A random ranking has enrichment 1.

| Top fraction | Cells | Precision | Recall | Enrichment | 95% CI |
|---|---|---|---|---|---|
| 5% | 27 | 0.551 | 0.241 | 4.75 | [4.23, 5.28] |
| 10% | 54 | 0.466 | 0.407 | 4.02 | [3.70, 4.35] |
| 20% | 107 | 0.371 | 0.611 | 3.04 | [2.86, 3.21] |

ranking: it is not known how much better the model is than a simple rule, for example one based on the hydrophobicity of the substituted residue. Moreover, the final model is fitted on all of the pool whereas the calibrator is learned from scores of models fitted on four fifths of it (a known limitation of cross-fitting), and all of this is still a development benchmark. The word "calibrated" here means that the Brier score is better than that of the raw score with an interval above zero; it does not mean perfect calibration.

#### *4.2.3.10. External GPS Labels: Koren et al. Table S4*

The saturation-mutagenesis tables of Koren et al. [2] use the same endpoint (PSI) and were audited as a possible source of additional training labels. The supplementary tables were downloaded manually, because the automatic download is blocked by the host. The article is not in the open-access subset of the repository, so the tables are used internally only and are not redistributed here. The gate fixed in advance required all of four conditions (Table 4.19).

**Table 4.19.** Gate fixed in advance for merging the labels of Koren et al. (Table S4) into training

| Criterion | Pre-registered threshold | Observed | Met |
|---|---|---|---|
| G1: new clusters at cov80 | $\geq 20$ | 5 (6 of 13 sequences mapped) | No |
| R1: PSI recomputed from bin counts | $\lvert\Delta\rvert \leq$ 1e-06 in $\geq 99\%$ of rows | 1827 of 1827 rows (max. 5.0e-12) | Yes |
| R2: internal wild-type reference | $\geq 8$ synonymous cells in $\geq 7$ substrates | 9 of 9 substrates | Yes |
| R3: direction of $\Delta$PSI (last Gly of Clone#8) | median $\geq +0.5$, $\geq 90\%$ positive | median +1.04, 100% positive ($n = 19$) | Yes |
| **Gate (G1 and R1 and R2 and R3)** | | | **No** |

The data themselves are sound: PSI is reproduced from the bin counts in all rows, an internal wild-type reference can be built for all substrates, and the direction of the effect of the last glycine agrees with the biology. The gate nevertheless fails on the number of new clusters. Table S4 holds 1 739 substitution cells for 9 substrates; the peptides are 23-residue C-terminal sequences with a stop codon in which only the last ten positions are mutated, a library different from the 28-residue internal peptides of the main labels; PSI is computed from 3 bins and not 6, so ΔPSI values from the two sources cannot simply be added; only 3.0% of the cells have $\Delta\text{PSI} \geq 1$ (against 13.1% in the benchmark), and the effects sit in the last one to three positions. Only 6 of the 13 sequences could be mapped to Swiss-Prot, and one of them overlaps with the training peptides, which leaves 5 new clusters, against the 20 required. As a diagnostic, not part of the gate, the agreement between Tables S3 and S4 on the 12 cells they share is low (Spearman 0.10), so S3 is not used as a label source.

By the consequence fixed in advance, these labels are *not* merged into training, and the planned merging of external labels (P4) and the repeated learning curve on the enlarged set (P5) were therefore not run. The table remains a possible external test set for a C-terminal degron class; this was not done in the thesis and no number is reported for it.

#### *4.2.3.11. Scope Comparison with MetaDegron*

MetaDegron [8] was audited as a possible competitor and label source. Its labels are binary motif-level annotations of curated degrons, not ΔPSI; the audit therefore compares scope and data, not predictive scores on the GPS matrix, because MetaDegron-D could not be run on GPS peptides (Table 4.20). Among the main findings, the curated positive set has only 227 human rows, and almost no region of it coincides with the GPS peptides used here (2 scanning peptides, 1 saturation peptide and 0 from the CRISPR screens). Only 1 E3 motif group keeps at least five samples after the strictest filter, so “21 E3 ligases” is a list of motif-compatible assignments, not 21 independently labelled classes. The reported MetaDegron-X AUC of 0.9670 was recomputed from the stored trees, but only on the authors’ prepared tables, and 8 of the 20 positive test coordinates are in the property table of the fitting data; it is not an independent result and not a GPS result. A simple composition logistic baseline on the same positives, split by protein cluster at cov80, gives AUROC between 0.728

and 0.731 (core composition) and between 0.737 and 0.747 (29-residue context), on a reconstructed population and not on the authors' own training set. The audit therefore suggests positioning MetaDegron as a complementary tool for motif and E3 information rather than a head-to-head competitor on residue-level effect prediction; binary motif labels are not converted into ΔPSI.

**Table 4.20.** Audit of the MetaDegron data and overlap with the data of this thesis

| Audit item | Value |
|---|---|
| Curated positive rows / distinct accessions | 302 / 240 |
| Rows with species suffix HUMAN | 227 |
| Rows in the property table used by MetaDegron-X | 212 |
| E3 motif groups with $\geq 5$ samples: before filtering / after the strictest filter (human only, no regional or cluster overlap) | 13 / 1 |
| Same-region overlap with GPS scanning peptides (2 624 peptides) | 2 |
| Same-region overlap with saturation peptides (248 mapped) | 1 |
| Same-region overlap with CRISPR-screen peptides (31 peptides) | 0 |
| MetaDegron-X AUC recomputed from the stored trees on the authors' prepared tables (not a GPS result) | 0.9670 |
| Positive test coordinates also present in the property table of the fitting data | 8 / 20 |

#### *4.2.3.12. Follow-up on the Restricted Benchmark*

Notebook replication reproduced the ridge and prototype-consistency results on Kaggle. A separate Degformer run that excluded training rows touching the outer-test protein clusters completed all three seeds and five folds. Its ensemble AUROC was 0.8068, compared with 0.8208 for the extended-training ridge. This is distinct from the earlier one-seed, saturation-only retraining: the clean-cluster comparison has now been performed, without establishing a transformer advantage.

The frozen ESM2-650M/PCA ridge comparison reached 0.8230, but its paired interval against ridge included zero. In the subsequent representation and context study, ridge with an ordered $\pm 5$ context reached 0.8286, with an adjusted interval of [+0.0021, +0.0139] for the AUROC gain over $\pm 3$. Frozen ESM2-35M with a multi-window CNN reached 0.8305, but the primary comparison with ridge had interval [−0.0025, +0.0233] and did not meet its confirmation criterion. These findings motivated the matched pointwise/CNN control in the full-PSI study.

#### *4.2.3.13. Full-PSI Development Evaluation*

**Population and protocol.** The full-PSI follow-up retains 235 saturation peptides, 122 412 mutation cells and 221 protein groups after technical quality control, without removing peptides by their WT stability. The supporting scanning bundle contains 224 470 cells. The label remains the replicate-mean ΔPSI from the Zhang reporter assay [3, 17]; these are reprocessed public measurements, not new wet-lab data. Groups combine whole-proteome cov80 clusters, additional bidirectional cov50 similarity hits and exact-sequence unions. This is heuristic homology control, not a proof of biological independence. Scanning data are partitioned by group before fitting into development, held-source and saturation-overlap subsets; overlapping scanning groups do not supply transfer-training labels.

Five outer folds and seeds 17, 29 and 43 share the evaluation cells. Training is either restricted to $\mathrm{PSI}_{\mathrm{WT}} \leq 4$, uses the full range, or uses the full range balanced first by WT-PSI stratum and then by peptide. Inner validation covers the full range in all three arms; therefore the restricted arm is not entirely unexposed to high-PSI labels during model selection. Scaling, PCA and hyperparameter selection remain inside the applicable training split. This protocol was designed after earlier results were known and is an extension for development, not an independent preregistration. It defines a new evaluation population rather than expanding the old 91-peptide test.

**Models and metrics.** Ridge with ordered $\pm 5$ context remains the reference. Frozen ESM2 representations [14] are compared through pointwise, single-window and multi-window convolutional heads. For the matched ESM comparison, the crop, auxiliary inputs and projection are held common; the pointwise head does not mix positions, whereas the CNN does. This isolates positional mixing more closely than comparing different pLM pooling schemes. It does not make the parameter counts equal. Neural epochs are chosen by inner MSE before refitting on the permitted outer-training data.

The primary measure is mean absolute error in PSI units, calculated within each peptide and then averaged across all 235 peptides. Positive-event AUROC uses $\Delta\mathrm{PSI} \geq 1$ and requires at least three cells in each class; only 184 peptides qualify. High-PSI peptides can still inform regression when a positive event is physically unavailable. Each table entry averages the three seed predictions per cell before cal-

culating metrics; it is not an average of seed-level metric values.

**Table 4.21.** Selected full-PSI development results. MAE is lower-is-better; positive AUROC is higher-is-better. All rows use the same evaluation population and three-seed prediction ensemble.

| Configuration | Macro MAE | Positive AUROC |
|---|---|---|
| Ridge W5, train $PSI_{WT} \leq 4$ | 0.43358 | 0.83118 |
| Ridge W5, full range | 0.40780 | 0.83193 |
| Ridge W5, balanced full range | 0.40361 | 0.82752 |
| One-hot CNN, full range | 0.39361 | 0.82913 |
| Frozen ESM2-35M + pointwise, full range | 0.38969 | 0.83753 |
| Frozen ESM2-35M + CNN, full range | 0.38435 | 0.84882 |
| Frozen ESM2-35M + multi-window CNN, balanced | 0.38385 | 0.84700 |
| One-hot CNN, scanning pre-training, full range | 0.38723 | 0.84249 |

**What the results establish.** Full-range training reduces W5 ridge MAE from 0.43358 to 0.40780 (5.94%), with the largest gains in the high-WT-PSI strata. Balancing lowers MAE further to 0.40361, but does not preserve positive-event ranking as well; it is not a uniform improvement. The adjusted intervals in Table 4.22 support a reduction in MAE, but their upper endpoints do not establish the prespecified minimum reduction of 0.02 PSI throughout the intervals.

Frozen ESM2-35M with a CNN reaches MAE 0.38435. Relative to the matched pointwise head, the difference is −0.00534 with descriptive interval [−0.0102, −0.0009]. The balanced multi-window CNN has the lowest selected MAE, 0.38385, but its advantage over the full-range single-window CNN is only 0.00051 PSI. The ranking alone does not establish an architecture winner. Choosing the top 5% of predicted positive substitutions within eligible peptides gives macro precision 58.24% for the ESM CNN; this is a ranking utility measure, not a calibrated probability or whole-dataset accuracy.

Scanning pre-training improves the one-hot CNN from 0.39361 to 0.38723 MAE under this design. Quality weighting worsens ridge relative to its unweighted control (Table 4.22). These results concern mutation-label scanning transfer and a specific weighting recipe. They do not overturn the negative result for Voutsinos tile-label pre-training, which uses a different source endpoint and encoder.

**Table 4.22.** Paired full-PSI MAE differences; negative values favour the first method. The two ridge range comparisons use 97.5% intervals adjusted for two tests; the remaining intervals are descriptive 95% intervals. All use 5,000 protein-group bootstrap resamples.

| Paired comparison | ΔMAE | Cluster-bootstrap CI |
|---|---|---|
| Ridge full range minus restricted | −0.02577 | [−0.0338, −0.0183] |
| Ridge balanced minus restricted | −0.02996 | [−0.0417, −0.0188] |
| ESM CNN minus ESM pointwise, full range | −0.00534 | [−0.0102, −0.0009] |
| Scanning-pretrained CNN minus scratch | −0.00639 | [−0.0099, −0.0030] |
| Quality-weighted ridge minus unweighted | +0.00401 | [+0.0030, +0.0052] |

#### *4.2.3.14. Campaign Completion and Integrity*

The completed snapshot on 6 November contains 633 complete jobs out of 635 planned units. The two remaining states await reviewed external-source and structure inputs; they are not failed training jobs. All nine pLM preflights and feature extractions, 540 ridge fits, 30 frozen-head fits, 30 LoRA fits, OOF collection, core calibration, locked W5-D transfer and reporting have completed. ProtT5 and Ankh now have results in every planned family cell.

The read-only review verifies sizes and SHA-256 hashes for 4,278 local artifact references (5.77 GB) and 2,986 completed Kaggle artifacts (3.07 GB), with no recorded mismatch. It also rechecks 76 selected source hashes, confirms that the inherited source state remains unchanged, and verifies adapter-tensor changes in all 30 completed LoRA fits. Inventory counts distinguish physical caches/checkpoints from scientific observations (Appendix B). Hash agreement establishes artifact identity; it does not independently verify biological labels.

There are 41 local OOF recipes and 47 Kaggle recipes, listed completely in Table B.1. Each local recipe contains 367,236 rows: three predictions for each of the same 122,412 cells. Cell keys, labels, groups and outer folds agree with the pinned bundle; predictions are finite and there are no duplicate seed/cell keys. Ensemble metrics are recomputed from saved predictions. The 88 rows are correlated development estimates, including controls and learning-curve variants, not 88 independently trained model families or validation cohorts. The interrupted Kaggle tuning control has only one seed and is explicitly marked in the appendix.

#### *4.2.3.15. Nine-Checkpoint Frozen-Feature Comparison*

Table 4.23 reports the full local family grid in MAE. The four columns share the same evaluation population; B/D change permitted training coverage, while W5 changes explicit ordered context. These are frozen-feature ridge models, distinct from the matched neural-head experiment below. Figure 4.3 shows that model size does not give a monotonic improvement. In arm D, additional W5 context lowers point MAE for only three of nine checkpoints: ESM-C, ProtT5 and Ankh. No simultaneous family-wide significance claim is made from these ranks.

**Table 4.23.** Local frozen-feature ridge MAE for all nine checkpoints. "Only" includes the common auxiliary inputs; W5 adds ordered sequence context. All entries use three-seed OOF ensembles.

| Checkpoint | B only | B + W5 | D only | D + W5 |
|---|---|---|---|---|
| ESM2-8M | 0.4150 | 0.4288 | 0.3995 | 0.4018 |
| ESM2-35M | 0.4157 | 0.4280 | 0.4007 | 0.4022 |
| ESM2-150M | 0.4183 | 0.4296 | 0.4031 | 0.4041 |
| ESM2-650M | 0.4204 | 0.4319 | 0.4056 | 0.4071 |
| ESM1b-650M | 0.4203 | 0.4295 | 0.4054 | 0.4069 |
| ESM1v-650M | 0.4179 | 0.4289 | 0.4032 | 0.4050 |
| ESM-C-300M | 0.4203 | 0.4294 | 0.4046 | 0.4038 |
| ProtT5 | 0.4211 | 0.4301 | 0.4056 | 0.4055 |
| Ankh-base | 0.4188 | 0.4279 | 0.4048 | 0.4035 |

Nested selection among the 36 candidates reaches MAE 0.3945 and positive AUROC 0.8409. Its 15 saved seed/fold choices exactly match the minimum saved inner MSE. ESM2-8M is selected five times and Ankh three times; several other checkpoints are selected once or twice (Table B.4). This evaluates a selection procedure, rather than retrospectively reporting the best outer-OOF family score. Its exploratory MAE difference from the Kaggle W5-D reference is $-0.01335$, with descriptive group-bootstrap interval $[-0.01719, -0.00967]$. The cross-runtime comparison does not isolate the causal contribution of pretraining or model size.

#### *4.2.3.16. Completed Matched Frozen–LoRA Evaluation*

The same-runtime controls now permit a complete adaptation comparison (Table 4.24). LoRA-B reaches MAE 0.3637 and positive AUROC 0.8550; LoRA-D reaches 0.3650 and 0.8536, respectively. Relative to their own frozen controls, the





**Figure 4.3.** Frozen pLM ridge results under full-range training. Points joined on the same row compare explicit context for one checkpoint; the connectors are not confidence intervals.

MAE reductions are 9.8% and 6.5%. All four matched contrasts retain the favourable direction throughout the adjusted intervals in Table 4.25. This supports adapting this backbone under the specified development protocol; it does not establish that LoRA will improve every pLM, assay or final deployed model.

**Table 4.24.** Matched local ESM2-35M results. MAE uses all 235 peptides; positive AUROC/AP use 184 eligible peptides and negative AUROC uses 110. Higher ranking metrics are better.

| Recipe | MAE | AUROC+ | AP+ | AUROC− |
|---|---|---|---|---|
| Frozen-B | 0.4034 | 0.8263 | 0.4554 | 0.7541 |
| Frozen-D | 0.3904 | 0.8246 | 0.4544 | 0.7667 |
| LoRA-B | 0.3637 | 0.8550 | 0.5517 | 0.7921 |
| LoRA-D | 0.3650 | 0.8536 | 0.5474 | 0.8028 |

Seed-level MAE differs materially from the ensemble (Table B.2). For LoRA-B, single-seed MAEs are about 0.378–0.379, while averaging their predictions gives 0.3637. Consequently, the ensemble result cannot be assigned to a single checkpoint. All seeds improve on their matched frozen controls, but shared outer folds prevent treating the seed results as independent replications. Selected epochs are short: frozen

**Table 4.25.** Paired local contrasts: LoRA minus its frozen control. Confidence intervals use 5,000 protein-group resamples; 98.75% intervals adjust a post-hoc family of four comparisons. Negative MAE differences and positive AUROC differences favour LoRA.

| Comparison / metric | Δ | 95% CI | 98.75% CI |
|---|---|---|---|
| LoRA B − frozen / MAE | -0.0397 | [-0.0470, -0.0324] | [-0.0490, -0.0306] |
| LoRA B − frozen / AUROC+ | 0.0288 | [0.0209, 0.0366] | [0.0188, 0.0389] |
| LoRA D − frozen / MAE | -0.0254 | [-0.0318, -0.0191] | [-0.0339, -0.0175] |
| LoRA D − frozen / AUROC+ | 0.0289 | [0.0212, 0.0363] | [0.0192, 0.0387] |





**Figure 4.4.** Matched adaptation evidence. (a) Ensemble MAE and individual seed results; (b) paired MAE differences with multiplicity-adjusted group-bootstrap intervals. The seeds share the outer folds and are not independent cohorts.

B/D have median 1, LoRA-B median 3 and LoRA-D median 2 (Table B.3). They are chosen by inner validation, not by outer performance.

Arm choice remains a trade-off. LoRA-D minus LoRA-B MAE is $+0.00133$, with descriptive 95% interval $[-0.00295, 0.00554]$. The near tie does not establish that restricted training is generally preferable. Table 4.26 shows that D improves the PSI $> 5$ stratum while B is better at PSI $\leq 3$. The highest stratum has no eligible positive-event AUROC peptides, because its event range is constrained; it still contributes to regression. Stratum intervals are exploratory.

**Table 4.26.** LoRA peptide-macro MAE by WT-PSI stratum. The final column is the paired D-minus-B difference with a descriptive 95% protein-group interval; $n$ counts peptides.

| WT PSI | $n$ | LoRA-B | LoRA-D | $D - B$ (95% CI) |
|---|---|---|---|---|
| $\leq 3$ | 91 | 0.3884 | 0.4002 | 0.0118 [0.0043, 0.0194] |
| $(3, 4]$ | 85 | 0.3812 | 0.3815 | 0.0003 [-0.0056, 0.0064] |
| $(4, 5]$ | 36 | 0.3092 | 0.3033 | -0.0059 [-0.0138, 0.0027] |
| $> 5$ | 23 | 0.2863 | 0.2613 | -0.0250 [-0.0439, -0.0056] |

LoRA-B also has lower MAE than the Kaggle frozen-ESM CNN-D by 0.02069 PSI, with descriptive interval $[-0.02659, -0.01489]$. This is useful for prioritising candidates, but head architecture, runtime and adaptation all differ. The matched local contrasts provide the more specific evidence for adapter training. Kaggle and local ESM2-35M ridge controls are numerically close but are kept separate, rather than relabelled as additional independent seeds.

#### *4.2.3.17. Probability Calibration and Locked Transfer*

Table 4.27 distinguishes probabilistic quality from ranking. Both LoRA arms lower multiclass Brier score relative to their frozen controls and the inner-prior baseline. The peptide-macro LoRA-minus-frozen Brier differences are $-0.01572$ for B and $-0.01349$ for D, with descriptive 95% group intervals $[-0.01986, -0.01152]$ and $[-0.01736, -0.00970]$. However, positive-event ECE increases. Reliability curves in Figure 4.5 show overconfidence in high-probability bins, which contain fewer cells. A lower Brier score does not establish uniformly better calibration. The model cards currently mark these as CV-only calibrators and leave the final serving-model identifier list empty; model-specific lineage and final refitting remain necessary before

inference integration.

**Table 4.27.** Out-of-fold three-class probability evaluation. Brier is the unnormalised sum across three classes; lower values are better. The prior uses inner-validation class frequencies. ECE refers only to the positive event and uses ten equal-width bins.

| Recipe | Brier micro | Brier macro | Prior micro | ECE+ |
|---|---|---|---|---|
| Frozen-B | 0.1789 | 0.1787 | 0.2006 | 0.0129 |
| Frozen-D | 0.1795 | 0.1794 | 0.2006 | 0.0114 |
| LoRA-B | 0.1631 | 0.1630 | 0.2006 | 0.0163 |
| LoRA-D | 0.1659 | 0.1659 | 0.2006 | 0.0165 |

The locked transfer set contains 39,234 R/A/S substitutions across 1,410 peptides and 730 protein groups, with no recorded group overlap with W or scanning development data. Only the fixed W5-D recipe is evaluated. It obtains MAE 0.3991, compared with 0.4024 for predicting zero. The paired difference is -0.0033 with 95% interval [-0.0092, 0.0028], so the average regression advantage is not resolved. Positive AUROC is 0.8405 on 338 eligible peptides and AP is 0.6011; negative AUROC is only 0.5176 on 85 eligible peptides. Regression, positive ranking and negative ranking therefore have different transfer behaviour.

**Table 4.28.** Locked W5-D transfer by WT PSI. $n$ counts peptides and $n_+$ counts peptides eligible for positive-event AUROC. The zero predictor provides a regression reference.

| WT PSI | $n$ | W5-D MAE | Zero MAE | $n_+$ |
|---|---|---|---|---|
| $\leq 3$ | 524 | 0.3819 | 0.4319 | 231 |
| $(3, 4]$ | 323 | 0.3918 | 0.4158 | 89 |
| $(4, 5]$ | 306 | 0.3998 | 0.3843 | 18 |
| $> 5$ | 257 | 0.4428 | 0.3470 | 0 |

The transfer failure is concentrated in high-WT-PSI peptides: above 5, W5-D MAE is 0.4428 versus 0.3470 for zero (Table 4.28). Across T, the observed positive-cell rate is 0.0512, below mean predicted probability 0.0895. Although the three-class Brier score of 0.1291 beats the development-prior baseline of 0.1348, positive probabilities shift upward relative to the observed rate. T contains only R, A and S replacements (25,479, 9,278 and 4,477 cells), uses replicate-1 labels and comes from a previously explored same-laboratory source. These results do not demonstrate





**Figure 4.5.** Probability and transfer limitations. (a) Development OOF positive-event reliability, with the diagonal indicating agreement; (b) locked W5-D transfer MAE by WT PSI. T uses a different population and does not evaluate LoRA.

independent external validity, clinical utility or transfer of the LoRA gain.

#### *4.2.3.18. Additional Controls and Practical Consequences*

The complete Kaggle record also contains composition, unordered-context, pair-interaction, learning-curve, quality-weighting and scanning-label controls (Table B.1). For W5-D, mean single-seed MAE decreases from 0.4413 at one-quarter training data to 0.4189 at one-half, 0.4107 at three-quarters and 0.4078 at full size. Ensemble MAEs are 0.4154, 0.4113, 0.4083 and 0.4078. The large ensemble gain at small fractions must not be misread as a learning curve of one fitted model. The frozen ESM CNN-D improves MAE for 156 of 235 peptides, grouped into 150 of 221 protein groups, relative to W5-D; the advantage is not universal.

The scanning pre-training comparison also examines the 20 substitution-pair types present in scanning and the other 360 types. Improvements are observed outside the 20 scanned pair types, but the subsets remain part of the same development population. This is evidence about the tested representation and label-transfer procedure, not a newly independent transfer cohort. These controls and the negative weighting result remain in the full appendix rather than being removed from the record after a stronger model appears.

Recorded completed-attempt durations total about 14.1 hours for frozen tun-

ing and 36.0 hours for LoRA tuning, versus about 1.4 hours for the 540 ridge fits (Table B.5). Paused/resumed jobs may omit earlier attempt time, so these totals are not exact GPU-active time or the wall-clock duration of the campaign. They still identify adaptation as the main recorded computational cost. The transfer inference timer is for prediction only and does not include fitting, feature preparation, downloads or service startup.

The executable research graph is finished. The next research tasks are reviewed external/structure inputs, independent transfer checks and a compatible final serving refit, calibrator, lineage card and export. The application tasks remain separate. A report marked complete is neither release acceptance nor automatic promotion of the lowest development MAE.

**Domain and software integration.** The earlier domain-gate study completed both tiers: OOF AUROC was 0.9111 using screen PSI and 0.8154 using sequence-derived features. This estimates membership of the restricted baseline's training domain, not per-mutation prediction accuracy. Raw screen PSI and intrinsic WT PSI are different estimators, so applying the intrinsic threshold directly to screen PSI is invalid. The baseline service still requires the delivered gate adapter and its borderline state. A future full-PSI serving model would need its own domain and calibration policy.

The local React/FastAPI baseline, reference ETL and recorded baseline tests exist. The newer workspace interface is an interactive design prototype with synthetic scores and tab-memory state; it does not establish backend inference or durable storage. Projects/history, peptide and protein jobs, experimental import/comparison and local PostgreSQL acceptance remain open. The serving model remains the calibrated restricted-PSI ridge baseline; none of the new research scores constitutes automatic model promotion or completion of the research and software gates.

#### *4.2.3.19. Remaining Evaluation*

The following parts of the plan have no results in this version of the thesis; no number is given for them.

- **Merging external GPS labels and repeating the learning curve on the enlarged set.** Not run: the only audited source (Table 4.19) did not pass its gate. Other candidate sources (for example Timms et al., Shimshon et al., Bekturova

et al. and a recent preprint on disease mutations that disrupt degrons) have not been audited, and their terms of use have not been read.

- **Independent validation.** Development OOF and locked same-laboratory transfer are available. Testing on labels that did not take part in any design decision, including the C-terminal data of Table 4.19, has not been done. The completed held-source route is locked to the prespecified W5 full-range recipe; it is not a test for selecting among all new pLMs. The source was explored historically, so it is not a wholly untouched external assay.

- **Final serving artefacts and further transfer.** The matched local LoRA comparison, CV calibration and locked W5 transfer are complete. CNN, LoRA and family candidates still require a model-specific final refit, calibration lineage and export before serving. LoRA transfer beyond development remains untested. Alternative tile-label pre-training or joint-training designs remain separate untested questions.

- **Comparison of the ranking with simple rules.** Only a random ranking was used as reference (Section 4.2.3.9).

- **Separating the region of $PSI_{WT}$ from the protein.** It needs pairs of peptides of the same protein on both sides of the threshold, which the present data may not contain (Section 4.2.3.5).

- **Expanded local software acceptance and tests with users.** Baseline web/API code exists, but project/history, batch/protein and import/comparison extensions and their acceptance remain pending (Section 4.3); historical checks do not verify this expanded scope.

### 4.2.4. Discussion

**What the initial measurements support.** (i) A ridge regression on 180 features is a strong baseline for the substitution effect: it is above the frozen ΔPAP baseline with an interval that excludes zero, and none of the five larger designs tried (the sigmoid-gated networks, FiLM, the bilinear form, the cross-product ridge and the retrained transformer architecture) beat it under the fixed criteria. (ii) Training labels from peptides just above the degron threshold improve the out-of-fold AUROC on

the original test cells, and this gain is not caused by an obvious collapse of the label. (iii) The gain is not simply proportional to the number of clusters, but the data do not yet separate wider coverage from more clusters. (iv) The gain from the relaxed threshold does not depend on how proteins are grouped: it is above zero under every informative partition tried, including grouping by accession. (v) The score of ridge M3 can be turned into a probability with a Platt transform that is better than the raw score and than the base rate, and the top 10% of the substitutions of a peptide contains about four times more positive cells than a random choice.

**What the follow-up adds.** The subsequent studies establish a wider-context ridge improvement on the original test and useful frozen-ESM positional mixing on the new full-PSI task. They do not turn the earlier inconclusive architecture tests into positive confirmations. Full-range training, matched representation/head controls and negative transfer/weighting results are the main new contributions (Section 4.2.3.13).

**What remains unsupported.** The thesis does not claim a novel architecture or an independently validated architecture winner. The initial interaction gate changes sign between seeds. The published Degformer checkpoint is not held out; the later three-seed clean-cluster retraining is a distinct comparison and did not establish an advantage over ridge. The thesis does not claim that more labels make a larger model win; the gated network is still rising, but it is below ridge at every level that was run. It does not claim that pre-training on tile labels helps: the one design tried was not better than random initialisation and was below ridge. It does not claim that the external labels of Koren et al. can be merged: they did not pass the gate. It makes no claim of external validation of the probabilities or of the ranking.

**Threats to validity.**

- The benchmark is a development benchmark on a data set that has been examined several times; the out-of-fold numbers are not an external validation. The original AUROC and the full-PSI MAE describe different populations and cannot be combined into a single progress score.
- The three seeds share one outer partition, and the confidence intervals are conditional on the stored predictions. Most comparisons are exploratory; adjusted

families are identified explicitly. There is no global correction covering the entire sequence of development studies.

- The threshold of 4.0 was fixed before the sensitivity grid, but only after the benchmark and a first look at the number of peptides it adds; the near coincidence with the maximum of the grid is not evidence that the way it was chosen was sound.
- All labels come from one assay and one library. Whether the gain transfers to other degron classes or to other assays is untested.
- The added peptides pass through the same label pipeline and so inherit its assumptions (the $PSI_{WT}$ reference from synonymous cells, the average of two halves).
- The coarsest partition tested still has 71 groups for 91 peptides, so robustness to a split by protein family is untested; the absolute scores change with the partition.
- The Platt calibrator is fitted on a pool that includes the added peptides, and its probabilities are about 13% too low for the benchmark peptides; the criterion "better than the raw score" is a low bar, because the raw score is worse than the base rate.
- The pre-training result concerns one design and one encoder; the ranking is compared only with a random ranking.

### 4.2.5. Reproducibility of the Reported Results

Tables, figures and numerical summaries are generated from the recorded experimental outputs using consistent filtering, aggregation and rounding rules. The experimental setup specifies the data, protein-cluster partitions, seeds and evaluation metrics; each result is interpreted with the controls and limitations of its experiment. The underlying records retain the configurations and input identities needed for computational reproduction. These internal records support traceability, while the thesis presents the scientific methods, results and their interpretation.

## 4.3. Software Testing Plan

### 4.3.1. Functions Under Test

The target covers UC-01 to UC-10 of Chapter 1. Functions include scoring, ranking and export; protein selection and ClinVar annotations; model and reference evidence; batch and protein jobs; experimental import and comparison; and persistent projects and history. The recorded CLI verification below covers numerical consistency for the original scoring and export path only. Baseline web/API code and historical test records exist, but these tests have not been rerun here and do not verify the new workflows. The expanded local acceptance scenarios are specified later in this chapter.

### 4.3.2. Approach

The prototype is a thin layer over a research model, so the main risk is that it computes something different from what was evaluated in Section 4.2. The approach is therefore *back-to-back testing*: the prototype path is compared with the training and evaluation path of the research runner on the 92 337 cells of the 176 peptides. The 180 features are rebuilt in the prototype by an independent implementation (16 620 660 values are compared), so the comparison is not a code path checked against itself. Baseline input-validation tests exist in the application source. Their historical results are not new execution evidence in this chapter. New domain, job, import, annotation and history cases below remain pending implementation and execution.

### 4.3.3. Criteria for Test Success or Failure

A check passes when the largest absolute difference between the two paths is below $10^{-9}$. The check of the exported file is asserted at $5 \times 10^{-9}$ in the code, because values are written with ten significant digits; the measured differences are below $10^{-9}$ for it as well. A test fails when any difference exceeds its limit. For the new workflows, a functional case also requires the specified item states, aligned counts, warnings and durable/deleted records. A skipped or pending case is not a pass; compatible-metric fixtures need independently calculated answers.

#### 4.3.4. Suspension Criteria and Restart Requirements

The verification script stops at the first failed assertion and runs no later check. The command-line tool refuses to run if the model file is missing. Restart: rebuild the frozen model artefact and run the verification procedure again from the beginning.

#### 4.3.5. Test Deliverables

The verification procedure, its machine-readable execution report, the calibration results and Table 4.30 of this chapter form the recorded numerical-consistency evidence. The pending local acceptance work additionally requires dated functional, recovery and resource-use reports.

### 4.4. Test Management

#### 4.4.1. Test Activities

Executed: building the model and the caches, running the verification script (11 checks). Not executed for the expanded first-release scope: local integration, job/import/history tests, resource measurement and user evaluation. Historical baseline web/API checks are a separate record.

#### 4.4.2. Test Environment

Linux under WSL2 on one development computer, CPU only; Python 3.12.3 and NumPy 2.5.3. The verification needs about 1.2 GB of memory. The model file and the caches are generated by the scripts and are not stored in the repository.

#### 4.4.3. Resources and Allocation

One tester, the author of the thesis, who is also the developer; there is no independent tester.

#### 4.4.4. Risks

- Back-to-back tests show agreement with the research code, not that the science is right: an error shared by both paths (for example in the definition of the label) would not be found.
- The probabilities are about 13% too low for peptides of the original benchmark domain (Section 4.2.3.9); ranking is not affected.

- The historical CLI has only a printed domain warning. The baseline web gate still needs R3 integration; whole-protein processing must not hide unknown, borderline or out-of-domain tiles.
- User imports can mix endpoints or mis-map residues; validation and separate assay comparisons are required. Persistent jobs/history add crash recovery and file-cleanup risks.
- The model was evaluated only on a development benchmark; no result in this chapter supports a claim of external validity.

## 4.5. Test Scenarios and Test Cases

### 4.5.1. Test Scenarios

S1: score a tile given as a sequence. S2: score a tile of a protein given by its UniProt accession. S3: export the scores as CSV and read them back. S4: reject invalid input; the retained CLI verification report does not cover this scenario.

### 4.5.2. Expanded Local Acceptance Scenarios

Table 4.29 defines the additional scenarios. All are pending; test IDs map to the system SRS and test plan. No public-host deployment is required.

**Table 4.29.** Planned first-release local acceptance scenarios; no execution result claimed

| Case group | Expected evidence |
|---|---|
| DOM-01, ANN-01 | Correct gate estimator/borderline handling; ClinVar and reference mapping, source states and attribution. |
| BATCH-01 to 06 | Bounds, single-tile equivalence, coverage/overlapping contexts, partial failures, cancellation, restart without duplicates and complete exports. |
| IMP-01 to 04 | CSV/TSV validation/commit, WT/replicate alignment, missing/conflicting data and hand-checked assay-compatible metrics. |
| HIST-01 to 03 | Explicit local persistence, immutable reopen/rerun after source changes, confirmed dependency/file deletion. |
| NF-07, DEP-01/02 | Recorded local resource use, clean local installation and restart of the same instance. |

### 4.5.3. Test Cases

Table 4.30 lists the executed cases, which cover S1 to S3 through the comparison of the scores computed by the prototype with those of the research path. The cases of S4 (length different from 28, a character outside the 20 amino acids, an unknown accession, a tile beyond the end of the protein, a tile with a non-standard residue, a missing model file) are specified by the CLI checks; application source contains baseline tests, but no new execution report is added for them here. Expanded first-release cases are specified in Table 4.29.

**Table 4.30.** Executed test cases: agreement of the prototype with the research runner. The tolerance is $10^{-9}$.

| Test case (back-to-back consistency check) | Max. abs. difference | Passed |
|---|---|---|
| TC-01: Labels: label pipeline vs. cached labels | 0.0e+00 | Yes |
| TC-02: Features: independent featuriser in the prototype vs. cached matrix | 1.1e-16 | Yes |
| TC-03: Raw score: prototype vs. trained ridge model | 4.4e-16 | Yes |
| TC-04: Platt probability: prototype vs. scikit-learn | 3.3e-16 | Yes |
| TC-05: Isotonic probability: prototype vs. scikit-learn | 1.7e-13 | Yes |
| TC-06: UniProt accession → tile → score: vs. training path | 0.0e+00 | Yes |
| TC-07: UniProt accession → tile → probability: vs. training path | 0.0e+00 | Yes |
| TC-08: Exported CSV, raw score: vs. in-memory prediction | 4.4e-10 | Yes |
| TC-09: Exported CSV, probability: vs. in-memory prediction | 4.8e-11 | Yes |
| TC-10: Features of the 91 benchmark peptides: prototype vs. cache | 1.1e-16 | Yes |
| TC-11: Outer-test scores of all 15 (seed, fold) pairs: prototype path vs. runner | 4.4e-16 | Yes |

## 4.6. Test Evaluation

All 11 executed cases passed; the largest absolute difference is 4.4e-10 (Table 4.30). The prototype therefore reproduces the research model on 92 337 cells, including the scores of the outer-test folds of all fifteen (seed, fold) pairs. This establishes consistency only. It does not show that the predictions are correct (Section 4.2 addresses that, on a development benchmark), and it says nothing about input validation, the interface, the response time (the target of Chapter 1 has not been measured) or usability **[PENDING]**.

The first-release software acceptance remains pending. Existing CLI measure-

ments cannot verify project persistence, experimental-data comparison, ClinVar mapping states, whole-protein coverage or job recovery. Local acceptance must report these cases and the actual computer/resource conditions; public deployment, Internet availability and hosted performance are outside the required scope.

# PART 3. CONCLUSION

## 1. Achieved Results

### 1.1. Knowledge and Skills

The work has produced a traceable computational workflow from experimental read counts to mutation labels, protein-group splits and model comparisons. The initial restricted-PSI studies established ridge as a strong baseline and showed that extending training-label coverage can help even when a learning curve within the original distribution is nearly flat. Negative findings on interaction designs and tile-label pre-training were retained rather than replaced by unsupported architecture claims.

The full-PSI extension evaluates 235 peptides in 221 protein groups. Full-range W5 ridge training reduces macro MAE from 0.43358 to 0.40780 PSI. Matched frozen-ESM controls provide development evidence for positional mixing: the CNN reaches 0.38435, compared with 0.38969 for pointwise prediction. Scanning-label pre-training helps its one-hot CNN control, whereas quality weighting does not help ridge. These are conclusions about specified populations and training recipes, not a universal model ranking.

The completed local expansion adds all nine planned pLM checkpoints, 540 frozen-feature ridge fits and 60 matched ESM2-35M frozen/LoRA fits. LoRA reduces MAE from 0.4034 to 0.3637 in arm B and from 0.3904 to 0.3650 in arm D; the adjusted paired intervals support both improvements. Larger frozen encoders do not consistently improve performance, and the nested family selector reaches 0.3945 MAE. B and D remain close overall while differing across WT-PSI strata. These results support a specified adaptation recipe and a comparison procedure rather than a universal family ranking.

Out-of-fold three-class calibration is complete for the four matched core recipes. LoRA improves Brier score, but positive-event ECE and high-probability reliability still expose errors. The locked W5-D transfer evaluation is also complete: positive AUROC is 0.8405, whereas the MAE difference from predicting zero is -0.0033 with interval [-0.0092, 0.0028]. The contrast between ranking and regression limits the transfer claim.

### 1.2. Program and Practical Application Potential

The calibrated restricted-domain ridge baseline has an inference path numerically consistent with the research runner. A local React/FastAPI implementation supplies single-peptide results, reference lookup, annotations and traceable exports. Its intended use is to shortlist substitutions for experimental follow-up, with visible model, source and domain evidence. The newer workspace UI demonstrates the intended interactions with synthetic fixtures; it is not an integrated persistent application. Projects/history, durable peptide/protein jobs, experimental import/comparison, PostgreSQL integration and their local acceptance remain unfinished as of 6 November 2026. The serving model has not been replaced by a development leaderboard result.

## 2. Limitations and Challenges

Predictive evidence comes from public reporter-assay sources that have informed several design decisions, including a locked transfer subset from a previously explored source. Protein-group splitting reduces detectable overlap but does not establish complete biological independence; thousands of mutation cells do not create thousands of independent peptides. The original 91-peptide evaluation and the full-PSI task have different populations and metrics. Most follow-up comparisons are exploratory, and the seeds share an outer partition.

The executable local graph is complete; reviewed external-source and structure inputs remain pending. The locked transfer set covers R/A/S substitutions with replicate-1 labels in the same laboratory. High-WT-PSI regression and positive-probability shift show that favourable development ranking does not establish robust transfer. LoRA has not been evaluated on T. Runtime, precision and feature choices also differ across model families. CV calibrators are not final serving artifacts; model-specific final refit, lineage cards and export remain unfinished. Earlier baseline calibration and its domain gate cannot be assumed valid for a new serving model. The gate is not yet integrated correctly into the baseline application. No new wet-lab validation, E3-specific recognition, intact-protein prediction or clinical inference has been established.

## 3. Future Work

Preserve the completed OOF record, paired uncertainty and unsuccessful controls. Investigate the high-PSI transfer errors and probability shift with an explicitly designed new evaluation, rather than using the already inspected T set to choose among pLMs. New external and structure extensions require reviewed inputs and overlap/rights audits. Any model selected for inference needs an architecture-specific final refit, calibration, domain policy, model card and export; the benefit of the three-seed ensemble must be retained or re-evaluated if the serving configuration changes.

Complete the agreed local software workflows and check numerical consistency, correct domain handling, coordinate/assay alignment, saved-work recovery and measured resource use. Update the remaining installation and acceptance material from executed evidence. Further data sources or biological tests require endpoint, homology and source-rights audits before any broader claim.

## REFERENCES

[1] A. Varshavsky, "N-degron and C-degron pathways of protein degradation," *Proceedings of the National Academy of Sciences*, vol. 116, no. 2, pp. 358–366, 2019. TO VERIFY.

[2] I. Koren *et al.*, "The eukaryotic proteome is shaped by E3 ubiquitin ligases targeting C-terminal degrons," *Cell*, vol. 173, no. 7, pp. 1622–1635, 2018. TO VERIFY.

[3] Z. Zhang *et al.*, "Elucidation of E3 ubiquitin ligase specificity through proteome-wide internal degron mapping," *Molecular Cell*, vol. 83, pp. 3377–3392.e6, 2023.

[4] V. Voutsinos *et al.*, "A near-complete map of human cytosolic degrons and their relevance for disease," *Science Advances*, 2026.

[5] H.-C. S. Yen, Q. Xu, D. M. Chou, Z. Zhao, and S. J. Elledge, "Global protein stability profiling in mammalian cells," *Science*, vol. 322, no. 5903, pp. 918–923, 2008. TO VERIFY.

[6] F. B. Larsen *et al.*, "Comprehensive degron mapping in human transcription factors," *bioRxiv*, 2025. Preprint.

[7] Alpine2048, "Degformer: Transformer model for internal and C-terminal degron prediction." GitHub repository, commit 49ee52459967, 2026.

[8] M. Zheng *et al.*, "MetaDegron: multimodal feature-integrated protein language model for predicting E3 ligase targeted degrons," *Briefings in Bioinformatics*, vol. 25, no. 6, p. bbae519, 2024.

[9] DEGRONOPEDIA, "DEGRONOPEDIA documentation." Web resource. TO VERIFY: original publication.

[10] DegronMD, "DegronMD: a resource of degrons and variants." Molecular Biology and Evolution. TO VERIFY: authors, title, year.

[11] M. Steinegger and J. Söding, “MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets,” *Nature Biotechnology*, vol. 35, no. 11, pp. 1026–1028, 2017. TO VERIFY.

[12] A. E. Hoerl and R. W. Kennard, “Ridge regression: biased estimation for nonorthogonal problems,” *Technometrics*, vol. 12, no. 1, pp. 55–67, 1970. TO VERIFY.

[13] A. Vaswani *et al.*, “Attention is all you need,” in *Advances in Neural Information Processing Systems 30*, 2017. TO VERIFY.

[14] Z. Lin *et al.*, “Evolutionary-scale prediction of atomic-level protein structure with a language model,” *Science*, vol. 379, no. 6637, pp. 1123–1130, 2023.

[15] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, “LoRA: Low-rank adaptation of large language models,” in *International Conference on Learning Representations*, 2022.

[16] B. Efron, “Bootstrap methods: another look at the jackknife,” *The Annals of Statistics*, vol. 7, no. 1, pp. 1–26, 1979. TO VERIFY.

[17] Z. Zhang *et al.*, “Data accompanying the proteome-wide internal degron mapping study.” Mendeley Data, version 2, 2023.

[18] NCBI, “GEO Series GSE240610.” Gene Expression Omnibus.

# APPENDIX A: INSTALLATION AND USER GUIDE

## A.1. Installation Requirements

### A.1.1. Hardware Requirements

CPU inference runs on one local computer. Record actual OS, CPU, RAM and free disk in the local test report; batch/import/project storage requirements remain to be measured. A GPU is not required by the runtime application. Offline research training has separate requirements.

### A.1.2. Software Requirements

The baseline uses a Python virtual environment and pinned backend dependencies, Node/npm with the frontend lockfile, and locally prepared reference data/model weights. The target adds local PostgreSQL and a job worker. Exact versions are recorded by the implementation's requirements/lockfiles; PostgreSQL/job integration is still pending. The research runner additionally uses its own packages and MMseqs2; these are not all required for serving predictions.

## A.2. Local System Execution

There is one local web application. Public hosting, VPS, domain and TLS deployment are outside the required workflow. All application listeners must be bound to loopback.

### A.2.1. Existing Baseline Commands

From the repository root, create/install the baseline backend environment with `make-Ctopics/degron-footprint/system/appvenv`, then run `make-Ctopics/degron-footprint/system/appdev-api`. The API listens on `http://127.0.0.1:8000`. On first run this command prepares a SQLite development database from the local research checkout; it does not start the planned PostgreSQL workspace or durable worker. The existing development ETL's default ClinVar subset must be recorded when interpreting annotations.

In a second terminal enter `topics/degron-footprint/system/app/frontend`, run `npmci`, then `npmrundev----host127.0.0.1`. Open `http://127.0.0.1:5173`. Use the real backend; mock mode contains synthetic scores.

These commands are read from the baseline guides and were not executed as application acceptance in this document-update task.

### A.2.2. Target Local Workflow

**[PENDING: implemented migrations and startup commands for the local PostgreSQL workspace, worker and new screens.]** The final guide must reproduce reference preparation, local startup, a saved project, a peptide/protein job, a committed observation dataset, comparison/export, shutdown and reopening on the same machine. Copy database and workspace files together for recovery. Docker may package these same components; it is not a separate public/internal edition.

## A.3. User Guide

The target sequence is: create/open a project; choose single peptide, peptide batch or whole protein; review syntax/domain/coverage; submit and inspect per-tile results; view ClinVar/reference evidence; import CSV/TSV with assay/units/replicates and fix validation errors; explicitly commit; compare compatible observations; export scores and provenance; reopen history. Unsaved single-tile previews are transient; saved work persists until deletion. Deletion presents dependencies and requires confirmation. **[PENDING: screenshots and an executed local walkthrough after implementation.]**

## A.4. Offline Research Campaign Workflow

The research supervisor is separate from the application's API and job worker. It uses the pinned full-PSI data bundle, pretrained-weight caches and a CUDA environment. From PowerShell at the repository root, `./status-local.cmd` inspects the campaign. To execute or resume permitted work, `./run-local.cmd--hours2` starts a visible session. Request a safe pause using `./pause-local.cmd` or Ctrl+C in that session. Training commits recovery checkpoints approximately every 120 seconds; an abrupt window close can lose work since the last commit. These are operational commands, not commands executed during this thesis-update review.

The graph first checks the runtime/data identity and imported reference outputs, then verifies tokenizer alignment and extracts frozen features for each cached checkpoint. It runs the family ridge grid and matched frozen/LoRA tuning, collects

OOF predictions, fits CV calibrators, evaluates the locked W5-D transfer recipe and writes the final report. Complete jobs are skipped when resuming the same compatible campaign; previous source output must remain available for inherited artifacts. Changing code, data, protocol or relevant runtime properties can create a new identity and must not be bypassed by editing a manifest or copying arbitrary checkpoints.

On 6 November the runnable graph has 633 completed jobs and two pending input-dependent extensions. A session that reports zero executed jobs and then ends has no eligible compute left; restarting it alone does not provide the missing reviewed external or structure inputs. No further training is needed to reproduce the present analysis from the saved artifacts. Cached model/data work can be read offline; acquiring new sources or absent model/dependency files is a preparation step that may require connectivity.

For evidence regeneration, enter the research campaign directory and run `pythonanalyze-local-output.py`. This reads saved OOF artifacts, verifies provenance and recomputes analysis without loading trained checkpoint objects. From the repository root, `pythontopics/degron-footprint/research/output-review-2026-11-06/audit.py` rechecks selected source hashes and exports the full evidence inventory. The report-asset generator then rebuilds tables and scientific figures from the exported JSON. Regeneration is an analysis task; it does not promote a candidate into the application.

# APPENDIX B: SUPPLEMENTARY MATERIALS

## B.1. Source Code and Data Availability

**[PENDING: repository link and release; data are redistributed only where the terms of use allow.]**

## B.2. Additional Tables and Figures

The following tables preserve the complete campaign record, including controls that do not improve the selected metrics. All W rows share the same 235 peptides, 221 groups and 122,412 cells. Each three-seed row averages predictions per cell before calculating metrics. The two Kaggle frozen-head tuning controls have only seed 17; their scores are not directly equivalent to three-seed ensembles.

Training arms A, B and C restrict WT PSI to at most 3, 4 and 5, respectively; D uses the full range and E balances the full range by stratum and peptide. Validation/test remain full-range. In the family grid, "only" means pLM features with the common auxiliary features, and "context" additionally includes ordered W5 features. Pointwise, CNN and multi-window CNN entries use frozen ESM2 features on Kaggle; the local "frozen" and "LoRA" entries use the matched neural head described in Section 3.4.1. "Rep1" and "mean12" identify scanning-label pre-training targets. Nested-family rows evaluate inner selection, not a retrospective outer-score winner.

**Table B.1.** All saved OOF configurations. $s$ is the number of seeds; MAE and event ranking are peptide-macro. Only rows with $s = 3$ are three-seed ensembles.

| Origin | Recipe | $s$ | MAE | AUC+ | AP+ | AUC− |
|---|---|---|---|---|---|---|
| Kaggle | cnn-transfer-rep1-D | 3 | 0.3872 | 0.8425 | 0.5024 | 0.7132 |
| Kaggle | cnn-transfer-mean12-D | 3 | 0.3873 | 0.8391 | 0.4985 | 0.7185 |
| Kaggle | cnn-transfer-scratch-D | 3 | 0.3936 | 0.8291 | 0.4597 | 0.7098 |
| Kaggle | composition-w5-B | 3 | 0.4342 | 0.8111 | 0.4040 | 0.7456 |
| Kaggle | composition-w5-D | 3 | 0.4075 | 0.8109 | 0.4047 | 0.7506 |
| Kaggle | ESM2-35M-cnn-B | 3 | 0.3880 | 0.8506 | 0.5097 | 0.7484 |
| Kaggle | ESM2-35M-cnn-D | 3 | 0.3844 | 0.8488 | 0.5095 | 0.7550 |
| Kaggle | ESM2-35M-cnn-E | 3 | 0.3856 | 0.8474 | 0.5066 | 0.7540 |

Continued on next page

| Origin | Recipe | $s$ | MAE | AUC+ | AP+ | AUC− |
|---|---|---|---|---|---|---|
| Kaggle | ESM2-35M-context-B | 3 | 0.4281 | 0.8432 | 0.4924 | 0.7095 |
| Kaggle | ESM2-35M-context-D | 3 | 0.4023 | 0.8445 | 0.4954 | 0.7301 |
| Kaggle | ESM2-35M-frozen-B | 1 | 0.4071 | 0.8233 | 0.4484 | 0.7512 |
| Kaggle | ESM2-35M-frozen-D | 1 | 0.3919 | 0.8221 | 0.4486 | 0.7657 |
| Kaggle | ESM2-35M-mcnn-B | 3 | 0.3855 | 0.8499 | 0.5036 | 0.7469 |
| Kaggle | ESM2-35M-mcnn-D | 3 | 0.3850 | 0.8463 | 0.5042 | 0.7570 |
| Kaggle | ESM2-35M-mcnn-E | 3 | 0.3838 | 0.8470 | 0.5064 | 0.7591 |
| Kaggle | ESM2-35M-only-B | 3 | 0.4158 | 0.8109 | 0.4291 | 0.7827 |
| Kaggle | ESM2-35M-only-D | 3 | 0.4008 | 0.8131 | 0.4340 | 0.7868 |
| Kaggle | ESM2-35M-pointwise-B | 3 | 0.4004 | 0.8375 | 0.4656 | 0.7440 |
| Kaggle | ESM2-35M-pointwise-D | 3 | 0.3897 | 0.8375 | 0.4739 | 0.7515 |
| Kaggle | ESM2-35M-pointwise-E | 3 | 0.3886 | 0.8357 | 0.4712 | 0.7557 |
| Kaggle | Nested family | 3 | 0.3975 | 0.8367 | 0.4788 | 0.7578 |
| Kaggle | onehot-cnn-B | 3 | 0.3997 | 0.8304 | 0.4575 | 0.7030 |
| Kaggle | onehot-cnn-D | 3 | 0.3936 | 0.8291 | 0.4597 | 0.7098 |
| Kaggle | onehot-cnn-E | 3 | 0.3947 | 0.8267 | 0.4564 | 0.7166 |
| Kaggle | onehot-mcnn-B | 3 | 0.3985 | 0.8267 | 0.4516 | 0.7046 |
| Kaggle | onehot-mcnn-D | 3 | 0.3935 | 0.8293 | 0.4588 | 0.7199 |
| Kaggle | onehot-mcnn-E | 3 | 0.3921 | 0.8289 | 0.4592 | 0.7200 |
| Kaggle | onehot-pointwise-B | 3 | 0.4059 | 0.8245 | 0.4299 | 0.7129 |
| Kaggle | onehot-pointwise-D | 3 | 0.3955 | 0.8269 | 0.4424 | 0.7264 |
| Kaggle | onehot-pointwise-E | 3 | 0.3920 | 0.8235 | 0.4426 | 0.7338 |
| Kaggle | ordered-w3-B | 3 | 0.4331 | 0.8280 | 0.4511 | 0.6927 |
| Kaggle | ordered-w5-A | 3 | 0.4711 | 0.8192 | 0.4436 | 0.6602 |
| Kaggle | ordered-w5-B | 3 | 0.4336 | 0.8312 | 0.4632 | 0.6745 |
| Kaggle | ordered-w5-C | 3 | 0.4177 | 0.8314 | 0.4606 | 0.6875 |
| Kaggle | ordered-w5-D | 3 | 0.4078 | 0.8319 | 0.4614 | 0.6931 |
| Kaggle | ordered-w5-D-fraction0.25 | 3 | 0.4154 | 0.8231 | 0.4468 | 0.6925 |
| Kaggle | ordered-w5-D-fraction0.5 | 3 | 0.4113 | 0.8280 | 0.4525 | 0.6975 |
| Kaggle | ordered-w5-D-fraction0.75 | 3 | 0.4083 | 0.8297 | 0.4555 | 0.6983 |
| Kaggle | ordered-w5-E | 3 | 0.4036 | 0.8275 | 0.4499 | 0.7109 |
| Kaggle | pair-w5-B | 3 | 0.4149 | 0.8093 | 0.4024 | 0.7458 |
| Kaggle | pair-w5-D | 3 | 0.4017 | 0.8092 | 0.4040 | 0.7499 |

Continued on next page

| Origin | Recipe | $s$ | MAE | AUC+ | AP+ | AUC− |
|---|---|---|---|---|---|---|
| Kaggle | sat-only-D | 3 | 0.4078 | 0.8319 | 0.4614 | 0.6931 |
| Kaggle | sat-quality-D | 3 | 0.4118 | 0.8307 | 0.4579 | 0.6918 |
| Kaggle | scan-mean12-D | 3 | 0.4048 | 0.8334 | 0.4643 | 0.6963 |
| Kaggle | scan-rep1-D | 3 | 0.4047 | 0.8334 | 0.4643 | 0.6964 |
| Kaggle | unordered-w5-B | 3 | 0.4316 | 0.8260 | 0.4414 | 0.7096 |
| Kaggle | unordered-w5-D | 3 | 0.4060 | 0.8258 | 0.4399 | 0.7199 |
| Local | Ankh-base-context-B | 3 | 0.4279 | 0.8426 | 0.4949 | 0.7097 |
| Local | Ankh-base-context-D | 3 | 0.4035 | 0.8440 | 0.4988 | 0.7310 |
| Local | Ankh-base-only-B | 3 | 0.4188 | 0.8075 | 0.4350 | 0.7822 |
| Local | Ankh-base-only-D | 3 | 0.4048 | 0.8088 | 0.4396 | 0.7882 |
| Local | ESM1b-650M-context-B | 3 | 0.4295 | 0.8359 | 0.4773 | 0.6814 |
| Local | ESM1b-650M-context-D | 3 | 0.4069 | 0.8360 | 0.4752 | 0.7032 |
| Local | ESM1b-650M-only-B | 3 | 0.4203 | 0.8016 | 0.4005 | 0.7431 |
| Local | ESM1b-650M-only-D | 3 | 0.4054 | 0.8024 | 0.4088 | 0.7547 |
| Local | ESM1v-650M-context-B | 3 | 0.4289 | 0.8384 | 0.4838 | 0.7009 |
| Local | ESM1v-650M-context-D | 3 | 0.4050 | 0.8378 | 0.4814 | 0.7187 |
| Local | ESM1v-650M-only-B | 3 | 0.4179 | 0.8022 | 0.4153 | 0.7677 |
| Local | ESM1v-650M-only-D | 3 | 0.4032 | 0.8027 | 0.4194 | 0.7725 |
| Local | ESM2-150M-context-B | 3 | 0.4296 | 0.8381 | 0.4894 | 0.7024 |
| Local | ESM2-150M-context-D | 3 | 0.4041 | 0.8390 | 0.4856 | 0.7199 |
| Local | ESM2-150M-only-B | 3 | 0.4183 | 0.8029 | 0.4229 | 0.7677 |
| Local | ESM2-150M-only-D | 3 | 0.4031 | 0.8034 | 0.4258 | 0.7729 |
| Local | ESM2-35M-context-B | 3 | 0.4280 | 0.8432 | 0.4921 | 0.7097 |
| Local | ESM2-35M-context-D | 3 | 0.4022 | 0.8445 | 0.4954 | 0.7302 |
| Local | ESM2-35M-frozen-B | 3 | 0.4034 | 0.8263 | 0.4554 | 0.7541 |
| Local | ESM2-35M-frozen-D | 3 | 0.3904 | 0.8246 | 0.4544 | 0.7667 |
| Local | ESM2-35M-lora-B | 3 | 0.3637 | 0.8550 | 0.5517 | 0.7921 |
| Local | ESM2-35M-lora-D | 3 | 0.3650 | 0.8536 | 0.5474 | 0.8028 |
| Local | ESM2-35M-only-B | 3 | 0.4157 | 0.8109 | 0.4290 | 0.7829 |
| Local | ESM2-35M-only-D | 3 | 0.4007 | 0.8131 | 0.4340 | 0.7870 |
| Local | ESM2-650M-context-B | 3 | 0.4319 | 0.8392 | 0.4832 | 0.6923 |
| Local | ESM2-650M-context-D | 3 | 0.4071 | 0.8394 | 0.4796 | 0.7139 |
| Local | ESM2-650M-only-B | 3 | 0.4204 | 0.8033 | 0.4105 | 0.7663 |

Continued on next page

| Origin | Recipe | $s$ | MAE | AUC+ | AP+ | AUC− |
|---|---|---|---|---|---|---|
| Local | ESM2-650M-only-D | 3 | 0.4056 | 0.8022 | 0.4093 | 0.7707 |
| Local | ESM2-8M-context-B | 3 | 0.4288 | 0.8419 | 0.4943 | 0.7052 |
| Local | ESM2-8M-context-D | 3 | 0.4018 | 0.8433 | 0.4948 | 0.7215 |
| Local | ESM2-8M-only-B | 3 | 0.4150 | 0.8107 | 0.4398 | 0.7799 |
| Local | ESM2-8M-only-D | 3 | 0.3995 | 0.8128 | 0.4375 | 0.7839 |
| Local | ESM-C-300M-context-B | 3 | 0.4294 | 0.8379 | 0.4806 | 0.6937 |
| Local | ESM-C-300M-context-D | 3 | 0.4038 | 0.8391 | 0.4820 | 0.7201 |
| Local | ESM-C-300M-only-B | 3 | 0.4203 | 0.8001 | 0.4038 | 0.7643 |
| Local | ESM-C-300M-only-D | 3 | 0.4046 | 0.8011 | 0.4062 | 0.7750 |
| Local | Nested family | 3 | 0.3945 | 0.8409 | 0.4877 | 0.7530 |
| Local | ProtT5-context-B | 3 | 0.4301 | 0.8414 | 0.4874 | 0.7011 |
| Local | ProtT5-context-D | 3 | 0.4055 | 0.8425 | 0.4900 | 0.7244 |
| Local | ProtT5-only-B | 3 | 0.4211 | 0.8036 | 0.4143 | 0.7647 |
| Local | ProtT5-only-D | 3 | 0.4056 | 0.8049 | 0.4223 | 0.7740 |

## B.3. Seed Stability and Inner Selection

**Table B.2.** Single-seed and ensemble peptide-macro MAE for the matched local core experiment.

| Recipe | Seed 17 | Seed 29 | Seed 43 | Ensemble |
|---|---|---|---|---|
| Frozen-B | 0.4073 | 0.4031 | 0.4059 | 0.4034 |
| Frozen-D | 0.3920 | 0.3918 | 0.3938 | 0.3904 |
| LoRA-B | 0.3794 | 0.3786 | 0.3779 | 0.3637 |
| LoRA-D | 0.3794 | 0.3778 | 0.3788 | 0.3650 |

**Table B.3.** Inner-selected epoch counts over 15 outer fits per local core recipe.

| Recipe | Folds | Minimum | Median | Maximum |
|---|---|---|---|---|
| frozen-B | 15 | 1 | 1 | 3 |
| frozen-D | 15 | 1 | 1 | 3 |
| lora-B | 15 | 1 | 3 | 7 |
| lora-D | 15 | 1 | 2 | 4 |

**Table B.4.** Local frozen-family recipes chosen by the saved inner-MSE selector. Frequencies across seed/fold pairs are not independent votes for a model family.

| Selected recipe | Outer fits (of 15) |
|---|---|
| ESM2-8M-context-D | 3 |
| Ankh-base-context-D | 2 |
| ESM2-35M-context-D | 2 |
| ESM2-8M-only-D | 2 |
| Ankh-base-only-D | 1 |
| ESM1b-650M-context-D | 1 |
| ESM1v-650M-only-D | 1 |
| ESM2-150M-only-D | 1 |
| ESM2-35M-only-D | 1 |
| ESM-C-300M-context-B | 1 |

## B.4. Execution Cost and Output Inventory

**Table B.5.** Recorded durations of completed local job attempts, counting inherited work once. Earlier attempts of paused/resumed jobs may be absent; these are not GPU-active or full elapsed times.

| Job category | Jobs | Recorded h | Median min |
|---|---|---|---|
| other | 15 | 3.07 | 0.19 |
| probe | 9 | 0.01 | 0.09 |
| extract | 9 | 0.96 | 5.35 |
| ridge | 540 | 1.42 | 0.16 |
| tune-frozen | 30 | 14.07 | 27.16 |
| tune-lora | 30 | 36.01 | 73.30 |

The cache contains pinned weights and executable source snapshots as well as metrics, OOF arrays, features, fitted models and recovery checkpoints. Physical file counts in Table B.6 can include duplicate content, partial files and superseded attempts. They must not be added to the checksum-verified artifact totals as though they were separate scientific observations. The historical timer-failure local run contributes no scientific OOF results. The interrupted local source remains required because the successor references its inherited artifacts.

**Table B.6.** Physical output inventory at review time. Weight caches and code snapshots are supporting assets, not evaluation datasets.

| Output role | Physical files | GiB |
|---|---|---|
| Pinned executable snapshot | 30 | 0.000 |
| Superseded timer-failure run | 18 | 0.000 |
| Earlier local source campaign | 2959 | 3.541 |
| Completed local successor | 2754 | 2.131 |
| Nine-checkpoint local weight cache | 63 | 14.110 |
| Kaggle reference campaign | 2990 | 2.859 |
| Reference ESM2-35M weight cache | 8 | 0.127 |