| | **S0** ⟨AD,DD⟩ Multi-instance reference | **S1** ⟨AI,DD⟩ Database server per tenant | **S2** ⟨AI,DS⟩ Database per tenant | **S3** ⟨AI,DB⟩ Schema per tenant | **S4** ⟨AI,DC⟩ Shared schema |
|---|---|---|---|---|---|
| Client and edge | dedicated | shared | shared | shared | shared |
| Identity and access | dedicated | shared | shared | shared | shared |
| Presentation | dedicated | shared | shared | shared | shared |
| Application logic (axis A) | dedicated | shared | shared | shared | shared |
| **Relational data (axis D)** | server per tenant | server per tenant | database per tenant, shared server | schema per tenant, shared database | shared tables, tenant_id column |
| Object storage | dedicated | shared | shared | shared | shared |
| Cache and queue | dedicated | shared | shared | shared | shared |
| Runtime platform | shared nodes | shared nodes | shared nodes | shared nodes | shared nodes |
| Control plane | shared, global | shared, global | shared, global | shared, global | shared, global |
| **Tenant boundary at the data layer** | separate instance stack | separate server process | own database and credentials | own schema and database role | tenant_id and row-level policy |
| **Placement in the application** | outside scope | outside scope | SILO_DATABASE | SCHEMA_PER_TENANT | POOL |
| **Role in this study** | reference only | reference, optional run | candidate | candidate | candidate |

**S5 Bridge:** a tenant-level policy that selects S2, S3 or S4 for each tenant (AWS: a hybrid of silo and pool)

Blue = shared by several tenants, orange = dedicated to one tenant, intermediate colours = partly shared. Within S1 to S4 every layer except the data layer is identical, so that measured differences can be attributed to the data layer. Placements are the application's names for S2 to S4.