Stress-Testing Product-Gated Clustering and Bounded Priority Ranking for Flood-Rescue Reports: A Synthetic Study

Thanh-Trong Nguyen · Ngoc-Anh Le · Nhu-Quynh Nguyen · Tuong-Hung Cao
Hung-Thinh Ngo · Xuan-Phuong Chau · Lan Phuong Phan · Thanh-Khoa Nguyen

Can Tho University

ISDS 2026 | Paper 6444

Presentation overview

From noisy reports to measured scheduling consequences

01 **Problem and research questions**
Why consolidation errors matter

02 **Methods and observable pipeline**
Graph, clustering and bounded priority

03 **Experimental design and metrics**
Two separate suites; run-level evaluation


04 **Results for RQ1–RQ3**
Clustering → ranking → dispatch

05 **Contributions and conclusions**
What is proved, observed and still open

Many reports do not mean many incidents

Schematic flood scenarios: repeated reports, nearby incidents and false destinations


Repeated reports



Many reports,
one physical incident

Risk: repeated trips


Nearby incidents



Close in space,
different incidents

Risk: a missed incident

False reports



Several reports,
no genuine incident

Risk: a false destination

Related approaches and the study gap

Three research strands meet at the report-to-dispatch boundary

Social sensing

Event detection and crisis-information extraction

[6–8]

Report consolidation

Graph community detection and density-based clustering

[1]; Paper 6444 §1

Humanitarian dispatch

Competing need, efficiency and equity objectives

[5]

GAP EXAMINED IN THIS STUDY

How do predicted splits, merges and false destinations propagate through ranking into a scheduler that cannot consult incident truth?

Research questions: do safeguards improve dispatch?

Three stage-specific questions guide the methods, data and evaluation


A safeguard at one stage does not establish benefit at the next.

RQ1	Clustering	Does the tuned Product pipeline improve clustering over Additive?
RQ2	Ranking	Does duplicate-aware priority align with independent simulated benefit?
RQ3	Dispatch	How do predicted splits, merges and noise affect dispatch outcomes?

Observable pipeline: reports to a fixed schedule

Algorithm inputs and evaluator-only truth stay separate

ALGORITHM · OBSERVABLE INPUTS ONLY



Two experimental suites for separate stage tests

Generator 3.0: geographically anchored, semi-synthetic · Candidate 4.1: fully synthetic

Generator 3.0

80 runs · 16 incidents/run
26,288 reports

→ **Required evaluator truth**

Incident linkage +
controlled graph stresses

→ **RQ1**

Clustering

RQ1 geographic anchors: Copernicus EMSR848 · OpenStreetMap · WorldPop 2025

Candidate 4.1

80 datasets · 16 incidents each
30,229 reports

→ **Required evaluator truth**

Independent benefit,
deadlines, service + harm

→ **RQ2 / RQ3**

Ranking / dispatch

Separate samples: complementary stage tests, not one common-sample validation chain.

Why test Product? Geography gates the whole affinity

A plausible mechanism to test; a geographic edge bound alone does not ensure better clusters

PRODUCT

$$w_{ij}^{\times} = a_i a_j G_{ij}(\beta T_{ij} + \gamma C_{ij})$$

ADDITIVE

$$w_{ij}^{+} = a_i a_j(\alpha G_{ij} + \beta T_{ij} + \gamma C_{ij})$$

G Geographic proximity
T Temporal proximity
C Context similarity
a Location/time admission

alpha, beta, gamma: nonnegative weights

ILLUSTRATIVE PAIR · SAME TIME AND CONTEXT, FAR APART




Report A Report B

G = .02; T = C = .90; a = 1; all weights = 1

Product .036 **Additive 1.820**

Bounded priority limits copies, not dishonest claims

Duplicate handling and information verification are different tasks



Repeated payload

→

Evidence families

Exact / near-copy grouping
Family maxima

→

Bounded score

Confidence, clipping
and saturation

$$0 \le P_k \le \mu, \qquad 1 \le \mu \le 2$$

Exact-copy invariance

Requires fixed families and score inputs.

Inflated headcounts remain unverified

Clipping caps influence; it does not verify a claim.

Evaluation protocol and information boundaries

Select on calibration; hold configurations fixed for the test audit

Generator 3.0 / RQ1



Candidate 4.1 / RQ2–RQ3



RQ2: oracle incident grouping

Isolate ranking from upstream clustering errors.

RQ3: predicted clusters

Average resource conditions within each seed: 40 pairs.

Three primary evaluation metrics

Separate endpoints for clustering, ranking and simulated dispatch

ARI

HIGHER IS BETTER

Partition agreement, corrected for chance.

1 = identical; ≈ 0 = chance; negative values are possible.

NDCG@5

HIGHER IS BETTER

Top-five ranking by independent simulated benefit.

Position-discounted and normalized; 1 = the ideal ordering.

Simulated harm


LOWER IS BETTER

Synthetic lateness and service costs, in model units.

This is not observed injury, lives lost or monetary damage.

RQ1: no Product composition advantage is established

Held-out Generator-3.0 test split · 40 paired runs



Additive Louvain

0.9191

Product Louvain

0.9072

Paired Holm p = .2560


16.49%

Product false destinations

RQ1: fivefold copies expose a major failure case

Static 40-run result plus one-run illustration · separate fixed batch stresses

ONE-RUN ILLUSTRATION



Mean paired change in ARI

40 held-out runs · negative = degradation

	GPS 100 m	GPS 300 m	Time 15 min	Time 60 min	Copies 2×	Copies 5×
Product Louvain	-0.012	-0.126	-0.035	-0.163	+0.024	-0.611
Additive Louvain	-0.022	-0.156	-0.038	-0.154	+0.015	-0.622
MD Additive	-0.019	-0.098	-0.044	-0.190	+0.021	-0.606
Product Leiden	-0.012	-0.125	-0.031	-0.156	+0.015	-0.620
Geo-time DBSCAN	-0.030	-0.127	-0.012	-0.055	+0.000	+0.000


5× copies · Product ΔARI

−0.6108

95% CI [−.6318, −.5881]

RQ2: exact-copy stability has a narrow scope

Oracle incident groups and fixed score inputs



Exact copies


2× / 5× / 10×:
zero revised score drift.

Coordinated attack

High-confidence payloads
still distort priority.

RQ2: alignment with simulated benefit remains weak

Even oracle grouping does not establish a general ranking advantage



Revised NDCG@5


0.6669

Random comparator

0.6763

RQ3: safeguards do not ensure better dispatch

Product partition · three resource conditions · 40 test seeds



Three contributions, with explicit evidence limits

Mathematical guarantees, simulated findings and unresolved validation are different claims

CONTRIBUTION	MATHEMATICALLY PROVED	OBSERVED IN SIMULATION	NOT YET ESTABLISHED
1 Product graph	Conditional retained-edge localization	No composition advantage established	Cluster compactness or transfer advantage
2 Family-wise priority	Copy invariance with fixed families / inputs	Zero copy drift; weak benefit alignment	Claim authenticity or true headcounts
3 Downstream audit	No dispatch-policy guarantee	Paired audit exposes adverse outcomes	Expert priorities or field effectiveness

Conclusion and future work

Local safeguards require separate validation at each downstream stage

Stage safeguards do not establish better dispatch.

Clustering	Conditional edge bound; no established Product composition advantage.
Ranking	Fixed-family/input copy invariance; weak benefit alignment.
Dispatch	Safeguards do not ensure better simulated outcomes.

Future work

1 Real-report linkage

2 Expert + source checks

3 Transfer + missingness

4 Joint ranking / dispatch

References (1 of 2)

Methods and evaluation

[1] Blondel, V.D., et al. (2008). Fast unfolding of communities in large networks. J. Stat. Mech., P10008. doi:10.1088/1742-5468/2008/10/P10008
https://doi.org/10.1088/1742-5468/2008/10/P10008

[2] Tomasi, C., & Manduchi, R. (1998). Bilateral filtering for gray and color images. ICCV, 839–846. doi:10.1109/ICCV.1998.710815
https://doi.org/10.1109/ICCV.1998.710815

[3] Hubert, L., & Arabie, P. (1985). Comparing partitions. J. Classification, 2, 193–218. doi:10.1007/BF01908075

https://doi.org/10.1007/BF01908075

[4] Järvelin, K., & Kekäläinen, J. (2002). Cumulated gain-based evaluation of IR techniques. ACM TOIS, 20(4), 422–446. doi:10.1145/582415.582418
https://doi.org/10.1145/582415.582418

[5] Gralla, E., Goentzel, J., & Fine, C. (2014). Assessing trade-offs among multiple objectives for humanitarian aid delivery using expert preferences. POM, 23(6), 978–989. doi:10.1111/poms.12110
https://doi.org/10.1111/poms.12110

[6] Sakaki, T., Okazaki, M., & Matsuo, Y. (2010). Earthquake shakes Twitter users: real-time event detection by social sensors. WWW, 851–860. doi:10.1145/1772690.1772777
https://doi.org/10.1145/1772690.1772777

References (2 of 2)

Data and application context

[7] Alam, F., Ofli, F., & Imran, M. (2018). CrisisMMD: Multimodal Twitter datasets from natural disasters. ICWSM, 12(1), 465–473. doi:10.1609/icwsm.v12i1.14983
https://doi.org/10.1609/icwsm.v12i1.14983

[8] Rahnemoonfar, M., et al. (2021). FloodNet: A high resolution aerial imagery dataset for post flood scene understanding. IEEE Access, 9, 89644–89654. doi:10.1109/ACCESS.2021.3090981
https://doi.org/10.1109/ACCESS.2021.3090981

[9] Copernicus EMS (2025). EMSR848: Flood in Central Viet Nam. mapping.emergency.copernicus.eu/activations/EMSR848/
https://mapping.emergency.copernicus.eu/activations/EMSR848/

[10] OpenStreetMap contributors. OpenStreetMap geographic reference data. ODbL. openstreetmap.org/copyright; Vietnam extract: download.geofabrik.de/asia/vietnam.html
https://www.openstreetmap.org/copyright

[11] WorldPop (2025). Viet Nam constrained population counts, R2024B v1, approximately100m. doi:10.5258/SOTON/WP00803; hub.worldpop.org/geodata/summary?id=56514
https://doi.org/10.5258/SOTON/WP00803

[12] Nguyen, T.-T., et al. (2026). Research artifact for stress-testing flood-rescue report clustering and ranking. GitHub Release v1.0.1.
https://github.com/ngthtrong/nckh2/releases/tag/v1.0.1



THANK YOU

Questions and discussion

Clustering safeguards, ranking stability and dispatch benefit require separate evaluation.

Paper 6444 · Can Tho University


Research artifact [12]: github.com/ngthtrong/nckh2/releases/tag/v1.0.1

Funded by Can Tho University · THS2026-68

Louvain: local moves and graph aggregation


Schematic weighted network · modularity is an objective, not incident-label accuracy

1 Weighted graph




Start with one community for each report node.

2 Local moves



Move nodes when modularity increases.

3 Aggregate



Between-group weight

Communities become weighted super-nodes.

Repeat on the smaller graph until no further modularity gain is obtained.