

****CKA Lab Part 3 - Application Lifecycle Management****

****Lab 1 - Perform rolling updates on a deployment****

Apply the following yaml file <https://raw.githubusercontent.com/David-VTUK/CKAExampleYaml/master/nginx-svc-and-deployment.yaml>

Update this deployment to leverage the nginx container version 1.7.11. Ensure that --record=true has been used.

****Lab 2 - Change the update strategy for a deployment****

Using the YAML file from Lab 1, amend it so that:

- Strategy is “Rolling Update”
- Max Surge is “1”
- Max Unavailable is “1”

****Lab 3 - Perform a rollback on a deployment****

Rollback the changes that were implemented from Lab 1.

****Lab 4 - Scale a deployment****

Scale the deployment from the first lab exercise to leverage 6 pods.

****Lab 5 - Create and run a Job****

Spec and execute a job that:

- Leverages the “perl” image
- Calculates pi to 2000 places

Note, use the command command: ["perl", "-Mbignum=bpi", "-wle", "print bpi(2000)"] in the pod manifest

The command above will output to stdout on the container, therefore inspect the output

****Lab 6 - Create and use a Config Map****

Create two texts files in /tmp/

db_h.txt with the contents “database_host”

db_p.txt with the contents “database_port”

Create a configmap called “db-connection” from the above two files.

Create a nginx pod which leverages these values as environment variables “db_h” and “db_p”

****Lab 7 - Create and use Secrets****

Create a secret called “db-credentials” directly from the CLI with the following key:value pair.

db-username : dbuser

db-password : dbpassword

Create a pod to leverage these as environment variables.

****Lab 8 - Configure a pod with specific environment variables****

Create a pod that has two environment variables configured:

Variable1 = somevalue

Variable2 = someothervalue