FG-01 Accounts — runnable source (PA3 Part E)

Performed: Nguyễn Bảo Minh Triết (24125047), Nguyễn Hồng Tấn Tài (24125078); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

This folder holds everything needed to run functional group FG-01 (accounts and profiles, UC-01-01 to UC-01-08) end to end: the React frontend, the Spring Boot API and a PostgreSQL database. It is a copy of `web/` and `api/authify/` from the repository on 2026-11-14. The earlier clickable UI prototype for every use case (Part D) is shown as screenshots in `../screenshots/`.

Demo video: https://youtu.be/6K9P5xVkhNo

Contents

Performed: Nguyễn Bảo Minh Triết (24125047); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

Path	What it is
`web/`	Vite + React + TypeScript frontend, with Playwright tests
`api/authify/`	Java Spring Boot API (Maven wrapper included)
`docker-compose.yml`	PostgreSQL 16 only
`.env.example`	Every setting the three parts need

Requirements

Performed: Nguyễn Bảo Minh Triết (24125047); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

Docker, JDK 17 or newer, Node.js 20 or newer. Run every command from this folder unless a step says otherwise.

Run

Performed: Nguyễn Bảo Minh Triết (24125047); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

1. Settings: copy `.env.example` to `.env`. Vite reads `VITE_API_BASE_URL` from it.
2. Database:

   ```
   docker compose up -d db
   ```

3. API, in a second terminal (PowerShell):

   ```
   cd api/authify
   $env:DATABASE_URL="jdbc:postgresql://localhost:5432/debatespeak"
   $env:DATABASE_USERNAME="debatespeak"
   $env:DATABASE_PASSWORD="debatespeak_dev_password"
   $env:APP_JWT_SECRET="<any random string of 32 or more characters>"
   .\mvnw spring-boot:run
   ```

On macOS or Linux use `export NAME=value` and `./mvnw spring-boot:run`. If `java -version` is below 17, point `JAVA_HOME` at a JDK 17+ first. The API listens on port 8000; `http://localhost:8000/api/v1/health` returns `{"status":"ok"}`.

4. Frontend, in a third terminal:

   ```
   cd web
   npm ci
   npm run dev
   ```

   Open `http://localhost:5173`. Use `localhost`, which the API allows. If Vite picks another port, restart the API with `FRONTEND_URL` set to that origin.

The API creates its tables on first start and seeds two accounts: a learner, `learner@example.com`, and an admin, `admin@debatespeak.org`. Their passwords are in `api/authify/src/main/java/org/debatespeak/authify/service/AuthService.java`.

What to try

Performed: Nguyễn Bảo Minh Triết (24125047); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

Use case	Steps
UC-01-01, 02	Create account, then sign in
UC-01-02	Reload the page: you stay signed in
UC-01-03	Account → edit profile → Save; reload to see it kept
UC-01-06	Account → Active sessions; sign in from a second browser and sign it out
UC-01-04	Sign out
UC-01-07	Account → Delete account (password and confirmation)
UC-01-08	Sign in as the admin → Account → Manage accounts → suspend, then reactivate

UC-01-05 (password recovery and email verification) is implemented in the API but switched off in the UI until real email delivery is set up with `SPRING_MAIL_USERNAME` and `SPRING_MAIL_PASSWORD`.

Checks

Performed: Nguyễn Bảo Minh Triết (24125047); Review: Nguyễn Hồng Tấn Tài (24125078), 2026-11-14; Edited: Nguyễn Bảo Minh Triết (24125047), 2026-11-14

From `web/`: `npm run build`, `npm run lint`, `npx playwright install chromium`, `npm run test:e2e` (96 tests; they mock the API). The end-to-end run against the real API on 2026-11-14 is recorded in the repository's `specs/002-fg01-accounts/tasks.md`.