

# How to use [(ngModel)] on div's contenteditable in angular2?



I am trying to use ngModel to two way bind div's contenteditable input content as follows:

39

```
<div id="replyinput" class="btn-input" [(ngModel)]="replyContent"
contenteditable="true" data-text="type..." style="outline: none;" ></div>
```



but it is not working and an error occurs:



16

```
EXCEPTION: No value accessor for '' in [ddd in PostContent@64:141]
app.bundle.js:33898 ORIGINAL EXCEPTION: No value accessor for ''
```



edited Aug 22 '17 at 4:10



danday74

21.5k

17

108

143

asked Feb 13 '16 at 9:11



Kim Wong

633

3

11

18

## 6 Answers



NgModel expects the bound element to have a value property, which div s don't have. That's why you get the No value accessor error.

75

You can set up your own equivalent property and event databinding using the textContent property (instead of value ) and the input event:



```
import {Component} from 'angular2/core';
@Component({
  selector: 'my-app',
```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



```
title = 'Angular 2 RC.4';  
model = 'some text';  
constructor() { console.clear(); }  
}
```

[Plunker](#)

I don't know if the `input` event is supported on all browsers for `contenteditable`. You could always bind to some keyboard event instead.

edited Jul 5 '16 at 15:00

answered Feb 13 '16 at 18:19



[Mark Rajcok](#)

303k 95 444 465

Thank you for your answer. But it is not a two way binding. When the user type something in the input, the "model" var will not change. – [Kim Wong](#) Feb 14 '16 at 12:23

1 @KimWong, the `model` var is definitely changing in the Plunker I provided. That's why I put `{{model}}` in the view/template, so that we can see it change when we edit the div. – [Mark Rajcok](#) Feb 15 '16 at 15:47

4 Regardless of the event used to trigger `model=$event.target.textContent`, this currently doesn't work properly on Firefox and Edge. The cursor is always set at index 0 when typing. You should be aware of this. – [Lys](#) Apr 3 '17 at 14:00

4 guys, anyone know how to sort out so the cursor index to not be set at 0 all the time? – [Chris Tarasovs](#) Jun 4 '17 at 17:35

1 currently this is only useful for typing backwards – [rrafalsz](#) Mar 5 '18 at 19:56

### Updated answer (2017-10-09):

Now I have [ng-contenteditable](#) module. Its compatibility with Angular forms.

Old answer (2017-05-11): In my case, I can simple to do:

```
<div  
  contenteditable="true"
```

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

Google

Facebook

First time, after `ngOnInit()` and get `post` from backend, I set `this.postTitle = post.postTitle` in my component.

edited Oct 9 '17 at 18:10

answered May 11 '17 at 10:09



ktretyak

4,687 5 22 41

Working Plunkr here <http://plnkr.co/edit/j9fDFc>, but relevant code below.

9

Binding to and manually updating `textContent` wasn't working for me, it doesn't handle line breaks (in Chrome, typing after a line break jumps cursor back to the beginning) but I was able to get it work using a `contenteditable` model directive from <https://www.namekdev.net/2016/01/two-way-binding-to-contenteditable-element-in-angular-2/>.

I tweaked it to handle multi-line plain text (with `\n` s, not `<br>` s) by using `white-space: pre-wrap`, and updated it to use `keyup` instead of `blur`. Note that some solutions to this problem use the `input` event which isn't supported on IE or Edge on `contenteditable` elements yet.

Here's the code:

#### Directive:

```
import {Directive, ElementRef, Input, Output, EventEmitter, SimpleChanges} from
'angular2/core';

@Directive({
  selector: '[contenteditableModel]',
  host: {
    '(keyup)': 'onKeyUp()'
  }
})
export class ContenteditableModel {
  @Input('contenteditableModel') model: string;
  @Output('contenteditableModelChange') update = new EventEmitter();

  /**
   * ...
   */
}
```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



```

private lastViewModel: string;

constructor(private elRef: ElementRef) {
}

ngOnChanges(changes: SimpleChanges) {
  if (changes['model'] && changes['model'].currentValue !== this.lastViewModel) {
    this.lastViewModel = this.model;
    this.refreshView();
  }
}

/** This should probably be debounced. */
onKeyUp() {
  var value = this.elRef.nativeElement.innerText;
  this.lastViewModel = value;
  this.update.emit(value);
}

private refreshView() {
  this.elRef.nativeElement.innerText = this.model
}
}

```

## Usage:

```

import {Component} from 'angular2/core'
import {ContenteditableModel} from './contenteditable-model'

@Component({
  selector: 'my-app',
  providers: [],
  directives: [ContenteditableModel],
  styles: [
    `div {
      white-space: pre-wrap;

      /* just for looks: */
      border: 1px solid coral;
      width: 200px;
      min-height: 100px;
    }`
  ]
})

```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 

```

<b>Output:</b>
<div>{{text}}</div>

<b>Input:</b><br>
<button (click)="text='Success!'">Set model to "Success!"</button>
,
})
export class App {
  text: string;

  constructor() {
    this.text = "This works\nwith multiple\n\nlines"
  }
}

```

Only tested in Chrome and FF on Linux so far.

edited Dec 21 '16 at 3:05

answered Dec 21 '16 at 1:45



tobek

2,664 2 19 34

1 Tested on Firefox with Windows as well, under Ionic 2, and your code works there as well. Thanks! – Cel Apr 20 '17 at 8:55

Here's [another version](#), based on @tobek's answer, which also supports html and pasting:

7

```

import {
  Directive, ElementRef, Input, Output, EventEmitter, SimpleChanges, OnChanges,
  HostListener, Sanitizer, SecurityContext
} from '@angular/core';

@Directive({
  selector: '[contenteditableModel]'
})
export class ContenteditableDirective implements OnChanges {
  /** Model */

```

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



```

private elRef: ElementRef,
private sanitizer: Sanitizer
) { }

ngOnChanges(changes: SimpleChanges) {
  if (changes['contenteditableModel']) {
    // On init: if contenteditableModel is empty, read from DOM in case the element
    has content
    if (changes['contenteditableModel'].isFirstChange() && !this.contenteditableModel)
  {
    this.onInput(true);
  }
  this.refreshView();
}

@HostListener('input') // input event would be sufficient, but isn't supported by IE
@HostListener('blur') // additional fallback
@HostListener('keyup') onInput(trim = false) {
  let value = this.elRef.nativeElement[this.getProperty()];
  if (trim) {
    value = value.replace(/^[\\n\\s]+/, '');
    value = value.replace(/[\\n\\s]+$/, '');
  }
  this.contenteditableModelChange.emit(value);
}

@HostListener('paste') onPaste() {
  this.onInput();
  if (!this.contenteditableHtml) {
    // For text-only contenteditable, remove pasted HTML.
    // 1 tick wait is required for DOM update
    setTimeout(() => {
      if (this.elRef.nativeElement.innerHTML !== this.elRef.nativeElement.innerText) {
        this.elRef.nativeElement.innerHTML = this.elRef.nativeElement.innerText;
      }
    });
  }
}

private refreshView() {
  const newContent = this.sanitize(this.contenteditableModel);
  // Only refresh if content changed to avoid cursor loss

```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 

```
private getProperty(): string {  
    return this.contenteditableHtml ? 'innerHTML' : 'innerText';  
}  
  
private sanitize(content: string): string {  
    return this.contenteditableHtml ? this.sanitizer.sanitize(SecurityContext.HTML,  
content) : content;  
}  
}
```

answered Jun 28 '17 at 12:45



Rene Hamburger

1,186 8 8

Thanks, but to avoid **ExpressionChangedAfterItHasBeenCheckedError** please use asynchronous `EventEmitter` in output `@Output()` `contenteditableModelChange?= new EventEmitter(true);` [reference](#) to article. Maybe you can update your code. – Atiris Sep 22 '17 at 7:56 ✎

This should be the accepted answer. Excellent. – Charles Robertson Apr 21 at 12:14

I've fiddled around with this solutions and will use the following solution in my project now:

4

```
<div #topicTitle contenteditable="true" [textContent]="model"  
(input)="model=topicTitle.innerText"></div>
```

I prefer using the template reference variable to the "\$event" stuff.

Related link: <https://angular.io/guide/user-input#get-user-input-from-a-template-reference-variable>

answered Nov 6 '17 at 21:03



Flo

53 6

I used this solution on an editable TD as well. `{{model}}` as suggested by some other solutions gave me issues while typing. It would dynamically update

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google





1



Here is a simple solution if what you are binding to is a string, no events necessary. Just put a text box input inside the table cell and bind to that. Then format your text box to transparent

HTML:

```
<tr *ngFor="let x of tableList">
  <td>
    <input type="text" [(ngModel)]="x.value" [ngModelOptions]="{standalone: true}">
  </td>
</tr>
```

answered Jun 8 '18 at 19:19



Isaac

23 3

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

