

# How to use \*ngIf else?

Asked 2 years, 5 months ago Active 16 days ago Viewed 565k times



I'm using Angular and I want to use `*ngIf else` (available since version 4) in this example:

519



99

```
<div *ngIf="isValid">
  content here ...
</div>
```

```
<div *ngIf="!isValid">
  other content here...
</div>
```

How can I achieve the same behavior with `ngIf else` ?



if-statement

angular-template

edited Oct 8 '18 at 21:15



Alexander Abakumov

5,689 5 50 79

asked Mar 24 '17 at 18:18



kawli norman

2,598 2 6 6

Check here for Angular 8 explained with Example NgIf, NgIf Else and NgIf Then Else [freakyjolly.com/...](https://freakyjolly.com/) – Code Spy Aug 7 at 15:02

## 14 Answers



**Angular 4 and 5:**

840



using `else` :

```
<div *ngIf="isValid;else other_content">
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
<ng-template #other_content>other content here...</ng-template>
```

you can also use then else :

```
<div *ngIf="isValid;then content else other_content">here is ignored</div>
<ng-template #content>content here...</ng-template>
<ng-template #other_content>other content here...</ng-template>
```

or then alone :

```
<div *ngIf="isValid;then content"></div>
<ng-template #content>content here...</ng-template>
```

**Demo :**

[Plunker](#)

**Details:**

`<ng-template>` : is Angular's own implementation of the `<template>` tag which is according to [MDN](#) :

The HTML `<template>` element is a mechanism for holding client-side content that is not to be rendered when a page is loaded but may subsequently be instantiated during runtime using JavaScript.

edited Jun 25 '18 at 6:55



Iswar

948 4 23 49

answered Mar 24 '17 at 18:20



Bougarfaoui El houcine

17.2k 4 29 29

- 
- 8 I hoped there was a way just to use `<ng-template>` without another tag like `div`, but oddly it is not... I know the `<div>` gets removed as you use it, but it's kinda weird as implementation I think. – [andreas](#) Mar 30 '17 at 20:03 ✎
- 
- 13 @andreas You can use `<ng-container>` for the if-clause – [Martin Schneider](#) Jun 17 '17 at 11:08
- 
- 2 Note: you can use `ng-container` for the container containing `*ngIf`, but not for the template – [Simon\\_Weaver](#) Jan 18 '18 at 1:32 ✎
- 
- @Simon\_Weaver I figured it out the hard way. But why? why didn't they allow `*ngIf` to work on `ng-template` ? – [Eran Medan](#) Mar 15 '18 at 6:02 ✎
- 

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



149



In Angular 4.x.x You can use [ngIf](#) in four way to achieve simple if else procedure:

#### 1. Just Use If

```
<div *ngIf="isValid">
  If isValid is true
</div>
```

#### 2. Using If with Else (Please notice to **templateName**)

```
<div *ngIf="isValid; else templateName">
  If isValid is true
</div>

<ng-template #templateName>
  If isValid is false
</ng-template>
```

#### 3. Using If with Then (Please notice to **templateName**)

```
<div *ngIf="isValid; then templateName">
  Here is never showing
</div>

<ng-template #templateName>
  If isValid is true
</ng-template>
```

#### 4. Using If with Then and Else

```
<div *ngIf="isValid; then thenTemplateName else elseTemplateName">
  Here is never showing
</div>

<ng-template #thenTemplateName>
  If isValid is true
</ng-template>

<ng-template #elseTemplateName>
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

Tip: **ngIf** evaluates the **expression** and then renders the **then** or **else** template in its place when expression is truthy or falsy respectively. Typically the:

- **then** template is the inline template of **ngIf** unless bound to a different value.
- **else** template is blank unless it is bound.

edited Jul 17 '18 at 17:34



[John Henckel](#)

4,099 1 35 50

answered Oct 19 '17 at 15:18

[user2577907](#)

It seems like the compiler does not accept `...; else ...`. Probably the `;` should be removed. – [slartidan](#) Feb 27 '18 at 15:55

5 in angular-6, I tested with `...; else ...` and it worked – [WasiF](#) Sep 7 '18 at 14:32

To work with observable, this is what I usually do to display if the observable array consists of data.

14

```
<div *ngIf="(observable$ | async) as listOfObject else emptyList">
  <div >
    ....
  </div>
</div>
<ng-template #emptyList>
  <div >
    ...
  </div>
</ng-template>
```

answered Sep 29 '17 at 9:03



[Ah Hiang](#)

313 3 11

"bindEmail" it will check email is available or not. if email is exist than Logout will show otherwise Login will show

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
<ng-template #login><li><a routerLink="/login">Login</a></li></ng-template>
```

edited Jul 23 '17 at 13:17

answered Jul 23 '17 at 13:13



Prashant Shrivastava

144 1 7

2 This doesn't work. If it were correct, then it still wouldn't add any value because the accepted answer shows already how to do it. – [Günter Zöchbauer](#) Jul 23 '17 at 13:18

In Angular 4.0 `if...else` syntax is quite similar to conditional operators in Java.

4

In Java you use to `"condition?stmt1:stmt2"` .

In Angular 4.0 you use `*ngIf="condition;then stmt1 else stmt2"` .

edited Jun 2 '17 at 19:25

answered Apr 11 '17 at 3:51



msanford

7,415 7 47 68



Amit Gaikwad

180 1 9

1 looks like Oracle case when expression.. :- ) – [Peter](#) Jun 30 '17 at 8:09

4 You're referring to the [ternary operator which exists in most C-based languages](#) but this is closer to [Kotlin's if expressions](#). – [mythz](#) Jun 30 '17 at 11:05

ngif expression resulting value won't just be the boolean true or false

4

if the expression is just a object, it still evaluate it as truthiness.

if the object is undefined, or non-exist, then ngif will evaluate it as falseness.

common use is if an object loaded, exist, then display the content of this object, otherwise display "loading.....".

```
<div *ngIf="!object">
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
<div *ngIf="object">
  <!-- the content of this object -->

  object.info, object.id, object.name ... etc.
</div>
```

another example:

```
things = {
  car: 'Honda',
  shoes: 'Nike',
  shirt: 'Tom Ford',
  watch: 'Timex'
};

<div *ngIf="things.car; else noCar">
  Nice car!
</div>

<ng-template #noCar>
  Call a Uber.
</ng-template>

<!-- Nice car ! -->
```

another example:

```
<div *ngIf="things.car; let car">
  Nice {{ car }}!
</div>
<!-- Nice Honda! -->
```

[ngif template](#)

[ngif angular 4](#)

answered Jan 11 '18 at 18:00



[hoogw](#)

**1,875** 19 18

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

4

## Syntax for ngIf/Else

```
<div *ngIf="condition; else elseBlock">Truthy condition</div>  
<ng-template #elseBlock>Falsy condition</ng-template>
```

```
<div *ngIf="person">{{person.name}}</div>
```

The final output

```
<template [ngIf]="person">  
  
  <div>{{person.name}}</div>  
  
</template>
```

## Using NgIf / Else/ Then explicit syntax

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.



```
<div *ngIf="condition; then thenBlock else elseBlock"> ... </div>  
<ng-template #thenBlock>Then template</ng-template>  
<ng-template #elseBlock>Else template</ng-template>
```

```
<ng-container  
  *ngIf="isLoggedIn; then loggedIn; else loggedOut">  
</ng-container>  
  
<ng-template #loggedIn>  
  <div>  
    Welcome back, friend.  
  </div>  
</ng-template>  
<ng-template #loggedOut>  
  <div>  
    Please friend, login.  
  </div>  
</ng-template>
```

## Observables with NgIf and Async Pipe

[For more details](#)

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

```
<div *ngIf="(user$ | async) as user; else loading">
  <user-profile
    [user]="user">
  </user-profile>
  <user-messages
    [user]="user">
  </user-messages>
</div>

<ng-template #loading>
  Loading stuff...
</ng-template>
```

answered Oct 11 '18 at 8:10

[Lyes CHIOUKH](#)

2,638 6 22 46

There are two possibilities to use if condition on HTML tag or templates:

2

1. \*ngIf directive from CommonModule, on HTML tag;
2. if-else

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
<!-- Case 1 -->
<div *ngIf="condition">
  |   if the condition is true will show the content
</div>

<!-- Case 2 -->
<ng-container *ngIf="expression; else elseTemplate">
  |   content on true expression
</ng-container>
<ng-template #elseTemplate>
  |   content on false expression
</ng-template>
```

answered Nov 13 '18 at 16:30

[Rzv Razvan](#)

1,003 1 6 11

ng-template

2

```
<ng-template [ngIf]="condition1" [ngIfElse]="template2">
  ...
</ng-template>
```

```
<ng-template #template2>
  ...
</ng-template>
```


answered May 18 at 9:03

[Aniket](#)

254 1 12

## For Angular 8

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



```
export class AppComponent {  
  isDone = true;  
}
```

## 1) \*ngIf

```
<div *ngIf="isDone">  
  It's Done!  
</div>  
  
<!-- Negation operator-->  
<div *ngIf="!isDone">  
  It's Not Done!  
</div>
```

## 2) \*ngIf and Else

```
<ng-container *ngIf="isDone; else elseNotDone">  
  It's Done!  
</ng-container>  
  
<ng-template #elseNotDone>  
  It's Not Done!  
</ng-template>
```

## 3) \*ngIf, Then and Else

```
<ng-container *ngIf="isDone; then iAmDone; else iAmNotDone">  
</ng-container>  
  
<ng-template #iAmDone>  
  It's Done!  
</ng-template>  
  
<ng-template #iAmNotDone>  
  It's Not Done!  
</ng-template>
```

[edited Aug 20 at 5:13](#)[answered Aug 7 at 15:08](#)

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



You can also use Javascript short ternary conditional operator ? in angular like this:

1

```
{{doThis() ? 'foo' : 'bar'}}
```



or

```
<div [ngClass]="doThis() ? 'foo' : 'bar'">
```

answered May 13 at 7:58



[Sebastian Viereck](#)

**2,775** 27 34



0

```
<div *ngIf="this.model.SerialNumber != '';then ConnectedContent else  
DisconnectedContent" class="data-font"> </div>
```



```
<ng-template #ConnectedContent class="data-font">Connected</ng-template>  
<ng-template #DisconnectedContent class="data-font">Disconnected</ng-template>
```

answered Apr 17 '18 at 15:44



[Amir Twito](#)

**961** 1 17 18



## In Angular 4, 5 and 6

0

We can simply create a *template reference variable* <sup>[2]</sup> and link that to the else condition inside an \*ngIf directive



The possible *Syntaxes* <sup>[1]</sup> are:

```
<!-- Only If condition -->
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
<!-- If and else conditions -->
<div *ngIf="condition; else elseBlock">...</div>
<!-- or -->
<ng-template #elseBlock>...</ng-template>

<!-- If-then-else -->
<div *ngIf="condition; then thenBlock else elseBlock"></div>
<ng-template #thenBlock>...</ng-template>
<ng-template #elseBlock>...</ng-template>

<!-- If and else conditions (storing condition value locally) -->
<div *ngIf="condition as value; else elseBlock">{{value}}</div>
<ng-template #elseBlock>...</ng-template>
```

**DEMO:** <https://stackblitz.com/edit/angular-feumnt?embed=1&file=src/app/app.component.html>

#### Sources:

1. <https://angular.io/api/common/NgIf#syntax>
2. <https://angular.io/guide/template-syntax#template-reference-variables--var->

answered Aug 8 '18 at 20:24



**Kalpesh Panchal**

**598** 5 16



0



I know this has been a while, but want to add it if it helps. The way I went about with is to have two flags in the component and two ngIfs for the corresponding two flags.

It was simple and worked well with material as ng-template and material were not working well together.

answered Sep 20 '18 at 7:29



**user1707141**

**813** 3 19 37

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

Thank you for your interest in this question. Because it has attracted low-quality or spam answers that had to be removed, posting an answer now requires 10 [reputation](#) on this site (the [association bonus does not count](#)).

Would you like to answer one of these [unanswered questions](#) instead?