## Promise.all behavior with RxJS Observables?

Asked 3 years, 6 months ago Active 4 months ago Viewed 34k times



In Angular 1.x I would sometimes need to make multiple http requests and do something with all the responses. I would throw all the promises in an array and call Promise.all(promises).then(function (results) {...}).

67

Angular 2 best practices seem to point towards the use of RxJS's <code>Observable</code> as a replacement to promises in <code>http</code> requests. If I have two or more different Observables created from http requests, is their an equivalent to <code>Promise.all()</code>?





10



asked Feb 24 '16 at 16:44

Corey Ogburn

12.4k 20 92 157

## 4 Answers



The more straightforward alternative for emulating Promise.all is to use the forkJoin operator (it starts all observables in parallel and join their last elements):

66

documentation



• related link: Cf. RxJS: concat three promises, distinguish results



A bit out of scope, but in case it helps, on the subject of chaining promises, you can use a simple flatMap: Cf. RxJS Promise Composition (passing data)





By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

Please help, forkJoin doesn't work when observables passed as parameter don't emit values. I have void Observables and still want to use forkJoin functionality but it is not working – Goga Koreli Nov 16 '18 at 12:39



forkJoin works fine too, but I'd prefer <u>combineLatest</u> since you don't need to worry about it taking the last value of observables. This way, you can just get updated whenever any of them emit a new value too (e.g. you fetch on an interval or something).

12



answered Feb 25 '16 at 4:54



kakigoori

**1,030** 9 2

- 1 This doesn't meet my current needs but I will definitely be using that soon. Corey Ogburn Feb 25 '16 at 5:34
- 2 That doesn't achieve the same behavior as Promise.all(), but it's similar to Promise.any() Purrell Sep 8 '16 at 20:26

if i have 2 calls one return promise and another return observable can i user forkjoin? or promise.all()? or no one, i have to let the 2 functions return same type either promises or observable? – Joe Sleiman Jun 12 '17 at 7:40

@JoeSleiman a bit late, but you can pick your side: Observable.fromPromise() together with Observable.zip(), or Obserable.toPromise() with Promise.all() – Arnaud P Jul 28 '17 at 15:59



On <u>reactivex.io</u> forkJoin actually points to <u>Zip</u>, which did the job for me:

11

let subscription = Observable.zip(obs1, obs2, ...).subscribe(...);



answered Jul 28 '17 at 16:11



Arnaud P

**337** 2 37 4



6

## Update May 2019 using RxJs v6

Found the other answers useful, and wished to offer an example for the answer offered by Arnaud about zip usage.

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

```
import { zip } from "rxjs";
const the weather = new Promise(resolve => {
 setTimeout(() => {
   resolve({ temp: 29, conditions: "Sunny with Clouds" });
 }, 2000);
});
const the tweets = new Promise(resolve => {
 setTimeout(() => {
   resolve(["I like cake", "BBQ is good too!"]);
 }, 500);
});
// Using RxJs
let source$ = zip(the_weather, the_tweets);
source$.subscribe(([weatherInfo, tweetInfo]) =>
 console.log(weatherInfo, tweetInfo)
);
// Using ES6 Promises
Promise.all([the weather, the tweets]).then(responses => {
 const [weatherInfo, tweetInfo] = responses;
 console.log(weatherInfo, tweetInfo);
});
```

The output from both are the same. Running the above gives:

```
{ temp: 29, conditions: 'Sunny with Clouds' } [ 'I like cake', 'BBQ is good too!' ] { temp: 29, conditions: 'Sunny with Clouds' } [ 'I like cake', 'BBQ is good too!' ]
```

answered May 5 at 14:52



By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.