

Pass a JavaScript function as parameter

Asked 6 years, 11 months ago Active 1 year, 7 months ago Viewed 583k times



How do I pass a function as a parameter without the function executing in the "parent" function or using `eval()` ? (Since I've read that it's insecure.)

608

I have this:



```
addContact(entityId, refreshContactList());
```



160

It works, but the problem is that `refreshContactList` fires when the function is called, rather than when it's used in the function.

I could get around it using `eval()` , but it's not the best practice, according to what I've read. How can I pass a function as a parameter in JavaScript?

javascript

function

parameters

edited Jun 1 '15 at 23:38



Nic Hartley

4,783 7 39 58

asked Nov 8 '12 at 9:34



imperium2335

8,513 32 94 162

@llyaskarim your link does no longer work – [smartmeta](#) Feb 17 at 13:07

@smartmeta the site is closed. – [Ilyas karim](#) Feb 17 at 15:04

13 Answers



You just need to remove the parenthesis:

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



This then passes the function without executing it first.



Here is an example:

```
function addContact(id, refreshCallback) {
    refreshCallback();
    // You can also pass arguments if you need to
    // refreshCallback(id);
}

function refreshContactList() {
    alert('Hello World');
}

addContact(1, refreshContactList);
```

edited Nov 8 '12 at 9:43

answered Nov 8 '12 at 9:34



Fenton

169k 48 304 332

-
- 6 @stevefenton, consider updating your answer with h2oooooooo comment, it'd be very useful. – [Morgan Wilde](#) Nov 8 '12 at 9:37
-
- 4 Based on the question, the callback doesn't accept parameters, which is why I have left them out of the example. I'll add a comment about it. – [Fenton](#) Nov 8 '12 at 9:42
-
- 4 @Veverke It would look like this... addContact(1, function(id) { console.log(id); }); – [Fenton](#) Nov 24 '14 at 10:46
-
- 4 @Steve Fenton: after reading your reply I asked myself why did I ask... :-)) – [Veverke](#) Nov 25 '14 at 15:52
-
- 1 The class syntax in ECMAScript wouldn't have an = sign... class myFuncs { rather than class myFuncs = { . You'd also need to be running in an environment that supported the class syntax (not all browsers support it yet). If you are still struggling, it might be better suited to a whole new question as your problem isn't about passing functions - it is general ES syntax. – [Fenton](#) Jun 21 '16 at 21:08
-



If you want to pass a function, just reference it by name without the parentheses:

290

```
function foo(x) {
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
func("Hello World!");  
}  
  
//alerts "Hello World!"  
bar(foo);
```

But sometimes you might want to pass a function *with arguments included*, but not have it called until the callback is invoked. To do this, when calling it, just wrap it in an anonymous function, like this:

```
function foo(x) {  
    alert(x);  
}  
function bar(func) {  
    func();  
}  
  
//alerts "Hello World!" (from within bar AFTER being passed)  
bar(function(){ foo("Hello World!") });
```

If you prefer, you could also use the [apply](#) function and have a third parameter that is an array of the arguments, like such:

```
function eat(food1, food2)  
{  
    alert("I like to eat " + food1 + " and " + food2 );  
}  
function myFunc(callback, args)  
{  
    //do stuff  
    //...  
    //execute callback when finished  
    callback.apply(this, args);  
}  
  
//alerts "I like to eat pickles and peanut butter"  
myFunc(eat, ["pickles", "peanut butter"]);
```

edited Nov 7 '14 at 1:23

answered Jun 6 '14 at 23:11



dallin

4,737

1

22

33

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

that makes JavaScript so powerful and so great to code in. – [TheHansinator](#) Dec 9 '15 at 22:16

@Compynerd255 I agree, this and the ability to quickly create object literals are my two favorite aspects of Javascript. I always miss object literals in languages that don't have them. – [dallin](#) Dec 10 '15 at 22:34

3 I am so thankful to Javascript for providing this feature and to you @dallin to letting me know that it exists. – [Dipendu Paul](#) Apr 7 '16 at 11:28

5 Definitely this must be the accepted answer. – [andreszs](#) Apr 10 '17 at 14:58

Example 1:

51

```
funct("z", function (x) { return x; });
```

```
function funct(a, foo){  
    foo(a) // this will return a  
}
```

Example 2:

```
function foodemo(value){  
    return 'hello '+value;  
}
```

```
function funct(a, foo){  
    alert(foo(a));  
}
```

```
//call funct  
funct('world!', foodemo); //=> 'hello world!'
```

[look at this](#)

edited May 23 '17 at 12:02



Community ♦

1 1

answered Nov 8 '12 at 9:38



[Gadde](#)

1,307 13 34

34



```
function ToBeCalled(){
    alert("I was called");
}

function iNeedParameter( paramFunc) {
    //it is a good idea to check if the parameter is actually not null
    //and that it is a function
    if (paramFunc && (typeof paramFunc == "function")) {
        paramFunc();
    }
}

//this calls iNeedParameter and sends the other function to it
iNeedParameter(ToBeCalled);
```

The idea behind this is that a function is quite similar to a variable. Instead of writing

```
function ToBeCalled() { /* something */ }
```

you might as well write

```
var ToBeCalledVariable = function () { /* something */ }
```

There are minor differences between the two, but anyway - both of them are valid ways to define a function. Now, if you define a function and explicitly assign it to a variable, it seems quite logical, that you can pass it as parameter to another function, and you don't need brackets:

```
anotherFunction(ToBeCalledVariable);
```

edited Sep 18 '13 at 23:44



Colonel Panic

1,476 2 17 31

answered Nov 8 '12 at 9:37



naivists

27.5k 5 48 79

2 Just typeof paramFunc == "function" is enough, cause if it isn't callable, then you can ignore it. – Jimmy Knoot Mar 10 '15 at 14:26

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

15 In addition to Steve Fenton's answer, you can also pass functions directly.

```
function addContact(entity, refreshFn) {  
    refreshFn();  
}  
  
function callAddContact() {  
    addContact("entity", function() { DoThis(); });  
}
```

answered Nov 8 '12 at 9:39



[series0ne](#)

18.2k

28

113

207

I chopped all my hair off with that issue. I couldn't make the examples above working, so I ended like :

```
7 function foo(blabla){  
    var func = new Function(blabla);  
    func();  
}  
  
// to call it, I just pass the js function I wanted as a string in the new one...  
foo("alert('test')");
```

And that's working like a charm ... for what I needed at least. Hope it might help some.

answered Apr 15 '16 at 9:31



[Fenix Aoras](#)

136

2

7

5 Upvote for the starting sentence xD – [GedankenNebel](#) Jul 31 '17 at 10:44

I suggest to put the parameters in an array, and then split them up using the `.apply()` function. So now we can easily pass a function with lots of parameters and execute it in a simple way.

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
}

function refreshContactList(int, int, string) {
    alert(int + int);
    console.log(string);
}

addContact([1,2,"str"], refreshContactList); //parameters should be putted in an array
```

answered Sep 26 '15 at 17:44



Naramsim

3,436 4 21 35

▲ You can also use `eval()` to do the same thing.

5

```
//A function to call
function needToBeCalled(p1, p2)
{
    alert(p1+"="+p2);
}

//A function where needToBeCalled passed as an argument with necessary params
//Here params is comma separated string
function callAnotherFunction(aFunction, params)
{
    eval(aFunction + "("+params+")");
}

//A function Call
callAnotherFunction("needToBeCalled", "10,20");
```

That's it. I was also looking for this solution and tried solutions provided in other answers but finally got it work from above example.

answered Jan 23 '14 at 11:29



NullPointer

2,016 3 26 51

2



```
function a(first,second)
{
  return (second)(first);
}

a('Hello',function(e){alert(e+ ' world!');}); //=> Hello world
```

edited Jan 15 '14 at 16:21

answered Jan 15 '14 at 16:14



cochon

21 2



In fact, seems like a bit complicated, is not.

2



get method as a parameter:

```
function JS_method(_callBack) {
    _callBack("called");
}
```

You can give as a parameter method:

```
JS_method(function (d) {
    //Finally this will work.
    alert(d)
});
```

edited Oct 21 '14 at 7:42

answered Oct 14 '14 at 9:45



Hakkı Eser

259 2 11

1 Please, explain your answer. – [MillaresRoo](#) Oct 14 '14 at 10:16

Sorry. I've corrected – [Hakkı Eser](#) Oct 21 '14 at 7:45

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



The other answers do an excellent job describing what's going on, but one important "gotcha" is to make sure that whatever you pass through is indeed a reference to a function.

2



For instance, if you pass through a string instead of a function you'll get an error:

```
function function1(my_function_parameter){
    my_function_parameter();
}

function function2(){
    alert('Hello world');
}

function1(function2); //This will work

function1("function2"); //This breaks!
```

See [JsFiddle](#)

answered Mar 23 '15 at 20:54



Victor

416 4 17



Some time when you need to deal with event handler so need to pass event too as an argument , most of the modern library like react, angular might need this.

0



I need to override OnSubmit function(function from third party library) with some custom validation on reactjs and I passed the function and event both like below

ORIGINALLY

```
<button className="img-submit" type="button" onClick=
{onSubmit}>Upload Image</button>
```

MADE A NEW FUNCTION `upload` and called passed `onSubmit` and event as arguments

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
upload(event,fn){
  //custom codes are done here
  fn(event);
}
```

edited Feb 20 '18 at 23:56

answered Feb 20 '18 at 23:50



sumit

9,269

9

38

84

▲ You can use a JSON as well to store and send JS functions.

-2

▼ Check the following:

```
var myJSON =
{
  "myFunc1" : function (){
    alert("a");
  },
  "myFunc2" : function (functionParameter){
    functionParameter();
  }
}
```

```
function main(){
  myJSON.myFunc2(myJSON.myFunc1);
}
```

This will print 'a'.

The following has the same effect with the above:

```
var myFunc1 = function (){
  alert('a');
}

var myFunc2 = function (functionParameter){
  functionParameter();
}
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

```
    myFunc2(myFunc1);  
}
```

Which is also has the same effect with the following:

```
function myFunc1(){  
    alert('a');  
}  
  
function myFunc2 (functionParameter){  
    functionParameter();  
}  
  
function main(){  
    myFunc2(myFunc1);  
}
```

And a object paradigm using Class as object prototype:

```
function Class(){  
    this.myFunc1 = function(msg){  
        alert(msg);  
    }  
  
    this.myFunc2 = function(callbackParameter){  
        callbackParameter('message');  
    }  
}  
  
function main(){  
    var myClass = new Class();  
    myClass.myFunc2(myClass.myFunc1);  
}
```

edited May 9 '13 at 8:18

answered May 8 '13 at 16:18



[gazgas](#)

168 1 6

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).