

# Using constants as indices for Javascript Associative Arrays

Asked 8 years, 11 months ago   Active 1 year, 1 month ago   Viewed 10k times

- ▲
- 19
- ▼
- I'm looking to create an associative array in JS, but use constants defined as part of the class as indices.
- The reason I want this is so that users of the class can use the constants (which define events) to trigger actions.

Some code to illustrate:

★

3

```
STATE_NORMAL = 0;
STATE_NEW_TASK_ADDED = 0;
this.curr_state = STATE_NEW_TASK_ADDED;

this.state_machine = {
  /* Prototype:
  STATE_NAME: {
    EVENT_NAME: {
      "next_state": new_state_name,
      "action": func
    }
  }
  */

  STATE_NEW_TASK_ADDED : { // I'd like this to be a constant
    this.EVENT_NEW_TASK_ADDED_AJAX : {
      "next_state": STATE_NEW_TASK_ADDED,
      "action" : function() {console.log("new task added");},
    }
  }
}

// Public data members.
// These define the various events that can happen.
this.EVENT_NEW_TASK_ADDED_AJAX = 0;
this.EVENT_NEW_TASK_ADDED_AJAX = 1;
```

I'm having trouble getting this to work. I'm not too great with JS, but it looks like no matter what I do, the array gets defined with strings and not constants. Is there any way to force the array to use the constants?

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

javascript

constants

associative-array

asked Nov 7 '10 at 9:44



Edan Maor

6,290

14

56

83

## 2 Answers



37



The problem here, actually, is that you can't use a value for the key part when you're defining an object **literally**.

That is to say, this uses the constant values as expected:

```
var CONSTANT_A = 0, CONSTANT_B = 1;
var state_machine = {};
state_machine[CONSTANT_A] = "A";
state_machine[CONSTANT_B] = "B";
console.log(state_machine[0]); // => A
console.log(state_machine[1]); // => B
```

[Run code snippet](#)[Expand snippet](#)

But this won't work as expected, instead using the string `CONSTANT_A` as key:

```
var CONSTANT_A = 0, CONSTANT_B = 1;
var state_machine = {
  CONSTANT_A: "A",
  CONSTANT_B: "B",
};
console.log(state_machine[0]); // => undefined
console.log(state_machine["CONSTANT_A"]); // => A
console.log(state_machine.CONSTANT_A); // => A
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

JavaScript has a shorthand to define object literals where you can omit the double-quotes around keys. Expressions can't be used, so `CONSTANT_A` won't be evaluated.

See also @Kristian's answer below re: ES6/modern JS, essentially making what you want possible.

edited Aug 14 '18 at 5:35

answered Nov 7 '10 at 9:54



Ashe

14.9k

4

42

68

In ES6 you can use computed values for object keys.

33

```
var CONSTANT_A = 0, CONSTANT_B = 1
var state_machine = {
  [CONSTANT_A]: function () {
    return 'a'
  },
  [CONSTANT_B]: function () {
    return 'b'
  }
};

console.log(state_machine)
```

Run code snippet

[Expand snippet](#)

This does not work in IE 11 nor in safari browsers: [https://kangax.github.io/compat-table/es6/#test-object\\_literal\\_extensions\\_computed\\_properties](https://kangax.github.io/compat-table/es6/#test-object_literal_extensions_computed_properties)

edited Jun 19 '16 at 11:14

answered Mar 1 '16 at 14:20



Kristian

663

1

8

15

Thanks! You saved me a lot of time. – Mihir Jun 19 '16 at 8:40

Ah. ES6 is so great – Félix Gañon-Grenier Sep 30 '16 at 15:28

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).