Technologies ▼		
deferences & Guides ▼		
eedback ▼		
guyendoanhien ▼		
<b>Q</b> Search		

# Document.querySelector()

The Document method **querySelector()** returns the first Element within the document that matches the specified selector, or group of selectors. If no matches are found, null is returned.

**Note**: The matching is done using depth-first pre-order traversal of the document's nodes starting with the first element in the document's markup and iterating through sequential

MDN Survey

Help us understand the top 10 needs of Web developers and designers.



element = document.querySelector(selectors);







#### selectors

A DOMString containing one or more selectors to match. This string must be a valid CSS selector string; if it isn't, a SYNTAX\_ERR exception is thrown. See Locating DOM elements using selectors for more about selectors and how to manage them.

Note: Characters that are not part of standard CSS syntax must be escaped using a backslash character. Since JavaScript also uses backslash escaping, be especially careful when writing string literals using these characters. See Escaping special characters for more information.

#### Return value &



An HTMLE1ement object representing the first element in the document that matches the specified set of CSS selectors, or null is returned if there are no matches.

If you need a list of all elements matching the specified selectors, you should use querySelectorAll() instead

### MDN Survey



×

Help us understand the top 10 needs of Web developers and designers.



### Usage notes 🔗

If the specified selector matches an ID that is incorrectly used more than once in the document, the first element with that ID is returned.

CSS pseudo-elements will never return any elements, as specified in the Selectors API.

#### Escaping special characters •

To match against an ID or selectors that do not follow standard CSS syntax (by using a colon or space inappropriately, for example), you must escape the character with a backslash ("\"). As the backslash is also an escape character in JavaScript, if you are entering a literal string, you must escape it *twice* (once for the JavaScript string, and another time for querySelector()):

#### MDN Survey

Help us understand the top 10 needs of Web developers and designers.



```
document.querySelector('#foo\\:bar'); // Ma
14
                                                     he second div
    </script>
```

### Examples &

Finding the first element matching a class •



In this example, the first element in the document with the class "myclass" is returned:

```
var el = document.querySelector(".myclass");
```

A more complex selector •



Selectors can also be really powerful, as demonstrated in the following example. Here, the first <input> element with the name "login" (<input name="login"/>) located inside a <div> whose class is "user-panel main" (<div class="user-panel main">) in the document is returned:

### MDN Survey







## Specifications $\mathcal{S}$

Specification	Status	Comment
DOM The definition of 'document.querySelector()' in that specification.	LS Living Standard	

## Browser compatibility $\mathcal{S}$

Update compatibility data on GitHub

querySelector

Chrome 1

Edge 12

Firefox 3.5

MDN Survey

Help us understand the top 10 needs of Web developers and designers.

Take the survey



×

Opera Android	10.1	
Safari iOS	3.2	
Samsung Internet Android	?	

Flag as incorrect

	Full support
***	• • •

	Compatibility unknowr
--	-----------------------

### See also 🔗

- Locating DOM elements using selectors
- Element.querySelector()
- Document.querySelectorAll()

### MDN Survey

Help us understand the top 10 needs of Web developers and designers.

