

[articles](#) [quick answers](#) [discussions](#) [features](#) [community](#) [help](#)

Search for articles, questions, tips

[Articles](#) » [Languages](#) » [C#](#) » [General](#)

# Aggregate Root Pattern in C#

**Shivprasad koirala**13 Nov 2015 [CPOL](#)Rate this:  4.88 (12 votes)

Aggregate root pattern in C#

Aggregate root are cluster / group of objects that are treated as a single unit of data.

I am sure lots of developers are already using this pattern unknowingly, via this short note I would like to inform you formally what you are doing.



Let us try to understand the above definition with an example. Consider the below “**Customer**” class which has the capability to add multiple “**Address**” objects to it. In order to achieve the same, we have exposed an **address** collection from the **customer** class to represent the 1 to many relationships.

```
class Customer
{
    public string CustomerName { get; set; }
    public DateTime DateofBirth { get; set; }

    public List<Address> Addresses { get; set; }
}

class Address
{
    public string Address1 { get; set; }
    public string Type { get; set; }
}
```

The above class structure works perfectly well. You can create object of **customer** and add multiple **addresses** object to it.

```
Customer cust = new Customer();
cust.CustomerName = "Shiv koirala";
cust.DateofBirth = Convert.ToDateTime("12/03/1977");

Address Address1 = new Address();
Address1.Address1 = "India";
Address1.Type = "Home";
cust.Addresses.Add(Address1);

Address Address2 = new Address();
Address2.Address1 = "Nepal";
Address2.Type = "Home";
cust.Addresses.Add(Address2);
```

Now let's say we want to implement the following validations:

"Customer can only have one address of Home type".

At this moment, the address collection is a NAKED LIST COLLECTION which is exposed directly to the client. In other words, there are no validations and restrictions on the "Add" method of the list. So you can add whatever and how much ever **address** objects as you wish.

```
cust.Addresses.Add(Address2);
```

So how to address this problem in a clean and logical way. If you think logically, "**Customer**" is composed of **Addressescollection**, so **Customer** is like a main root. So rather than allowing DIRECT NAKED ACCESS to **Addresses** list, how about accessing the address list from the **customer** class. In other words, centralizing access to **address** objects from the **customer** class.

So below are three steps which I have implemented to put a centralize **address** validation.

**Step 1:** I have made the **address** list **private**. So no direct access to the collection is possible.

**Step 2:** Created a **"Add"** method in the **"Customer"** class for adding the **"Address"** object. In this **add** method, we have put the validation that only one **"Home"** type address can be added.

**Step 3:** Clients who want to enumerate through the **address** collection for them we have exposed **"IEnumerable"** interface.

Hide Shrink ▲ Copy Code

```
class Customer
{
    // Code removed for clarity
    private List<Address> _Addresses; // Step 1 :- Make List private

    public void Add(Address obj) // Step 2 :- Address objects added via customer
    {
        int Count=0;
        foreach (Address t in _Addresses)
        {
            if (t.Type == "Home")
            {
                Count++;
                if (Count > 1)
                {
                    throw new Exception("Only one home address is allowed");
                }
            }
        }
        _Addresses.Add(obj);
    }

    public IEnumerable<Address> Addresses // Step 3 :- To browse use enumerator
    {
        get { return _Addresses; }
    }
}
```

If you analyze the above solution closely, the **customer** is now the root and the **address** object is manipulated and retrieved via the **customer** class.

Why did we do this? Because **"Customer"** and **"Address"** object is one logical data unit. To maintain integrity of **address** validation, we need to go via the **"Customer"** class. In the same way loading of data, updation, deletion, etc. should all happen via the **"Customer"** class so that we have proper data integrity maintained.

So when we say load **customer** from database, all the respective **address** objects should also get loaded.

So when a group of objects which form one logical unit should have centralized root via which the manipulation of the contained object should happen. This kind of arrangement is terms as "Aggregate Root".

The best way to Learn Design pattern is by doing a project. So if are interested, you can start from the below youtube video which demonstrates Design pattern by doing a project.

## License

This article, along with any associated source code and files, is licensed under [The Code Project Open License \(CPOL\)](#)

## Share

## About the Author



**Shivprasad  
koirala**



Architect <https://www.questpond.com>  
India 🇮🇳

Do not forget to watch my Learn step by step video series.

[Learn MVC 5 step by step in 16 hours](#)

[Learn MVC Core step by step](#)

[Learn Angular tutorials step by step for beginners](#)

[Learn Azure Step by Step](#)

[Learn Data Science Step by Step](#)

[Step by Step Mathematics for Data Science](#)

[Learn MSBI in 32 hours](#)

[Learn Power BI Mobile Step by Step](#)

[Learn SQL Server in 16 hours ser...](#)

[show more](#)

## Comments and Discussions

You must [Sign In](#) to use this message board.



Spacing

Relaxed ▼

Layout

Normal ▼

Per page

25 ▼

[Update](#)

[First](#) [Prev](#) [Next](#)

<b>I think this way is much better</b>	<b>Charles Schneider Pereira</b>	<b>16-Nov-15 23:13</b>
<b>If you want to avoid people accessing your private list, one way is that you can copy it out every time when asked</b>	<b>Song Tiansheng</b>	<b>16-Nov-15 14:39</b>
Re: If you want to avoid people accessing your private list, one way is that you can copy it out every time when asked	<b>Shivprasad koirala</b>	16-Nov-15 14:47
Re: If you want to avoid people accessing your private list, one way is that you can copy it out every time when asked	Song Tiansheng	16-Nov-15 15:11
<b>[My vote of 2] Some changes...</b>	<b>Jono Stewart</b>	<b>15-Nov-15 21:24</b>
<b>Good material, but the example could use</b>	<b>AFell2</b>	<b>13-Nov-15 12:31</b>
<b>i may be wrong</b>	<b>lucwuyts</b>	<b>13-Nov-15 10:55</b>

Last Visit: 27-Aug-19 20:26    Last Update: 27-Aug-19 20:26

[Refresh](#)

1

8/28/2019

Aggregate Root Pattern in C# - CodeProject

 General  News  Suggestion  Question  Bug  Answer  Joke  Praise  Rant  Admin

Use Ctrl+Left/Right to switch messages, Ctrl+Up/Down to switch threads, Ctrl+Shift+Left/Right to switch pages.

[Permalink](#)

[Advertise](#)

[Privacy](#)

[Cookies](#)

[Terms of Use](#)

Layout: [fixed](#) | [fluid](#)

Article Copyright 2015 by **Shivprasad koirala**  
Everything else Copyright © [CodeProject](#), 1999-2019

Web02 2.8.190824.1