

How to concatenate text from multiple rows into a single text string in SQL server?



1709



Consider a database table holding names, with three rows:

Peter
Paul
Mary



535

Is there an easy way to turn this into a single string of Peter, Paul, Mary ?

sql



sql-server

csv

string-concatenation

group-concat

edited Feb 19 '18 at 20:41



Steve Chambers

22.7k 11 102 146

asked Oct 11 '08 at 23:49



JohnnyM

11.3k 10 30 35

22 For answers specific to SQL Server, try [this question](#). – Matt Hamilton Oct 12 '08 at 0:03

15 For MySQL, check out [Group_Concat](#) from [this answer](#) – Pykler May 6 '11 at 19:48

24 I wish the next version of SQL Server would offer a new feature to solve multi-row string concatenation elegantly without the silliness of FOR XML PATH. – Pete Alvin Oct 2 '14 at 11:47

3 Not SQL, but if this is a once-only thing, you can paste the list into this in-browser tool [convert.town/column-to-comma-separated-list](#) – Stack Man May 27 '15 at 7:56

1 In Oracle you can use the LISTAGG(COLUMN_NAME) from 11g r2 before that there is an unsupported function called WM_CONCAT(COLUMN_NAME) which does the same. – Richard Jul 6 '17 at 6:32

45 Answers

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



If you are on SQL Server 2017 or Azure, see [Mathieu Renda answer](#).

1261 I had a similar issue when I was trying to join two tables with one-to-many relationships. In SQL 2005 I found that `XML PATH` method can handle the concatenation of the rows very easily.

If there is a table called `STUDENTS`

SubjectID	StudentName
1	Mary
1	John
1	Sam
2	Alaina
2	Edward

Result I expected was:

SubjectID	StudentName
1	Mary, John, Sam
2	Alaina, Edward

I used the following T-SQL :

```
SELECT Main.SubjectID,
       LEFT(Main.Students, Len(Main.Students)-1) AS "Students"
FROM
(
    SELECT DISTINCT ST2.SubjectID,
                   (
                       SELECT ST1.StudentName + ',' AS [text()]
                       FROM dbo.Students ST1
                       WHERE ST1.SubjectID = ST2.SubjectID
                       ORDER BY ST1.SubjectID
                       FOR XML PATH ('')
                   ) [Students]
    FROM dbo.Students ST2
) Main
```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 

```

SELECT DISTINCT ST2.SubjectID,
SUBSTRING(
(
SELECT ', ' + ST1.StudentName AS [text()]
FROM dbo.Students ST1
WHERE ST1.SubjectID = ST2.SubjectID
ORDER BY ST1.SubjectID
FOR XML PATH ('')
), 2, 1000) [Students]
FROM dbo.Students ST2

```

edited Aug 2 '18 at 11:20



StefanJCollier
1,080 11 20

answered Feb 13 '09 at 11:53

Ritesh

- 11 Great solution. The following may be helpful if you need to handle special characters like those in HTML: [Rob Farley: Handling special characters with FOR XML PATH\(''\).](#) – user140628 Apr 17 '13 at 12:35
- 8 Apparently this doesn't work if the names contain XML characters such as < or & . See @BenHinman's comment. – Sam Aug 13 '13 at 1:26
- 22 NB: This method is reliant on undocumented behavior of FOR XML PATH ('') . That means it should not be considered reliable as any patch or update could alter how this functions. It's basically relying on a deprecated feature. – Bacon Bits Nov 13 '14 at 18:54
- 24 @Whelkahlism The bottom line is that FOR XML is intended to generate XML, not concatenate arbitrary strings. That's why it escapes & , < and > to XML entity codes (& ; , & lt; , & gt;). I assume it also will escape " and ' to & quot; and & apos; in attributes as well. It's *not* GROUP_CONCAT() , string_agg() , array_agg() , listagg() , etc. even if you can kind of make it do that. We *should* be spending our time demanding Microsoft implement a proper function. – Bacon Bits Mar 23 '15 at 14:15 ✎
- 11 Good news: [MS SQL Server will be adding string_agg in v.Next.](#) and all of this can go away. – Jason C Apr 6 '17 at 0:32 ✎



952



This answer may return [unexpected results](#) For consistent results, use one of the FOR XML PATH methods detailed in other answers.

Use COALESCE :

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Just some explanation (since this answer seems to get relatively regular views):

- Coalesce is really just a helpful cheat that accomplishes two things:

1) No need to initialize `@Names` with an empty string value.

2) No need to strip off an extra separator at the end.

- The solution above will give incorrect results if a row has a *NULL* Name value (if there is a *NULL*, the *NULL* will make `@Names` *NULL* after that row, and the next row will start over as an empty string again. Easily fixed with one of two solutions:

```
DECLARE @Names VARCHAR(8000)
SELECT @Names = COALESCE(@Names + ', ', '' ) + Name
FROM People
WHERE Name IS NOT NULL
```

or:

```
DECLARE @Names VARCHAR(8000)
SELECT @Names = COALESCE(@Names + ', ', '' ) +
    ISNULL(Name, 'N/A')
FROM People
```

Depending on what behavior you want (the first option just filters *NULL*s out, the second option keeps them in the list with a marker message [replace 'N/A' with whatever is appropriate for you]).

edited Apr 30 at 12:02



Martin Smith

356k 60 596 709

answered Oct 12 '08 at 0:18



Chris Shaffer

28.7k 4 41 60

67 To be clear, coalesce has nothing to do with creating the list, it just makes sure that *NULL* values are not included. – Graeme Perrow Feb 13 '09 at 12:02

16 @Graeme Perrow It doesn't exclude *NULL* values (a *WHERE* is required for that -- this will *lose results* if one of the input values is *NULL*), and it *is required in this approach* because: *NULL* + non-*NULL* -> *NULL* and non-*NULL* + *NULL* -> *NULL*; also `@Name` is *NULL* by default and, in fact, that property is used as an implicit control here to determine if a ' ' should be added or not. user166200 Aug 15 '10 at 18:57

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



offered by @Ritesh – [R. Schreurs](#) Aug 2 '13 at 8:10

- 10 This is not a reliable method of concatenation. It is unsupported and should not be used (per Microsoft, e.g. support.microsoft.com/en-us/kb/287515, connect.microsoft.com/SQLServer/Feedback/Details/704389). It can change without warning. Use the XML PATH technique discussed in stackoverflow.com/questions/5031204/... I wrote more here: marc.durbin.net/2015/07/... – [Marc Durbin](#) Jul 15 '15 at 0:23

One method not yet shown via the `XML data()` command in MS SQL Server is:

336

Assume table called NameList with one column called FName,

```
SELECT FName + ', ' AS 'data()'
FROM NameList
FOR XML PATH('')
```

returns:

```
"Peter, Paul, Mary, "
```

Only the extra comma must be dealt with.

Edit: As adopted from @NReilingh's comment, you can use the following method to remove the trailing comma. Assuming the same table and column names:

```
STUFF(REPLACE((SELECT '#!' + LTRIM(RTRIM(FName)) AS 'data()' FROM NameList
FOR XML PATH('')), '#!',', ', 1, 2, '') as Brands
```

edited Apr 25 '16 at 15:28



[user1477388](#)

13.6k 21 102 206

answered Apr 5 '11 at 21:19



[jens frandsen](#)

3,369 1 10 2

- 13 holy s**t thats amazing! When executed on its own, as in your example the result is formatted as a hyperlink, that when clicked (in SSMS) opens a new window containing the data, but when used as part of a larger query it just appears as a string. Is it a string? or is it xml that i need to treat differently in

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



'14 at 22:40

- 6 @Baodad That appears to be part of the deal. You can workaround by replacing on an added token character. For example, this does a perfect comma-delimited list for any length: `SELECT STUFF(REPLACE((SELECT '#!' + city AS 'data()' FROM #cityzip FOR XML PATH ('')), ' #!', ', '), 1, 2, '')` – [NReilingh](#) Feb 29 '16 at 18:12
- 1 Wow, actually in my testing using `data()` and a replace is WAY more performant than not. Super weird. – [NReilingh](#) Feb 29 '16 at 18:33



SQL Server 2017+ and SQL Azure: STRING_AGG

293



Starting with the next version of SQL Server, we can finally concatenate across rows without having to resort to any variable or XML witchery.

+150

[STRING_AGG \(Transact-SQL\)](#)

Without grouping

```
SELECT STRING_AGG(Name, ', ') AS Departments
FROM HumanResources.Department;
```

With grouping :

```
SELECT GroupName, STRING_AGG(Name, ', ') AS Departments
FROM HumanResources.Department
GROUP BY GroupName;
```

With grouping and sub-sorting

```
SELECT GroupName, STRING_AGG(Name, ', ') WITHIN GROUP (ORDER BY Name ASC) AS Departments
FROM HumanResources.Department
GROUP BY GroupName;
```

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



- 2 This works with SQL Azure. Great answer! – [user2721607](#) Oct 11 '17 at 20:27
- 2 This also worked for me in Azure SQL. Brilliant! – [Kevin Stone](#) Jan 4 '18 at 20:31

In [SQL Server 2005](#)

270

```
SELECT Stuff(
    (SELECT N', ' + Name FROM Names FOR XML PATH(''), TYPE)
    .value('text()[1]', 'nvarchar(max)'),1,2,N'')
```

In SQL Server 2016

you can use the [FOR JSON syntax](#)

i.e.

```
SELECT per.ID,
Emails = JSON_VALUE(
    REPLACE(
        (SELECT _ = em.Email FROM Email em WHERE em.Person = per.ID FOR JSON PATH)
        , '{', '{ "_": "', ' ', '$[0]_ '
    )
FROM Person per
```

And the result will become

```
Id  Emails
1   abc@gmail.com
2   NULL
3   def@gmail.com, xyz@gmail.com
```

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 

And in SQL Server 2017, Azure SQL Database

You can use the new [STRING_AGG function](#)

edited Jul 23 '18 at 16:55

community wiki
9 revs, 7 users 70%
Steven Chong

-
- 3 Good use of the STUFF function to nix the leading two characters. – [David](#) Aug 11 '11 at 23:12
-
- 3 I like this solution best, because I can easily use it in a select list by appending 'as <label>'. I am not sure how to do this with the solution of @Ritesh. – [R. Schreurs](#) Aug 2 '13 at 8:27
-
- 12 This is better than the accepted answer because this option also handles un-escaping XML reserved characters such as < , > , & , etc. which FOR XML PATH(' ') will automatically escape. – [BateTech](#) Apr 7 '14 at 21:35
-
- This is an awesome response as it resolved the issue and provides the best ways of doing things in different versions of SQL now I wish I could use 2017/Azure – [Chris Ward](#) May 21 '18 at 14:27
-

In MySQL there is a function, [GROUP_CONCAT\(\)](#), which allows you to concatenate the values from multiple rows. Example:

111

```
SELECT 1 AS a, GROUP_CONCAT(name ORDER BY name ASC SEPARATOR ', ') AS people
FROM users
WHERE id IN (1,2,3)
GROUP BY a
```

edited Feb 26 '12 at 18:37



[Peter Mortensen](#)

14.1k 19 88 114

answered Oct 12 '08 at 0:10



[Darryl Hein](#)

70.6k 83 191 245

-
- 2 Used to love this one, have not seen a alternative to this function with any other Db yet! – [Binoj Antony](#) Jun 18 '09 at 6:05
-
- 1 This totally solved my problem. I was trying to pull all the payment dates for a given charge on an account, this solved it perfectly. Thanks! – [Maximus](#) Aug 20 '10 at 15:17

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



@DarrylHein for my needs i used the separator as above. But this cuts me some chars at the very end of the output. This is very strange and seems to be a bug. I dont have a solution, i just workedaround. – [gooleem](#) Dec 6 '16 at 9:28



Use **COALESCE** - [Learn more from here](#)

54

For an example:



102

103

104

Then write below code in sql server,

```
Declare @Numbers AS Nvarchar(MAX) -- It must not be MAX if you have few numbers
SELECT @Numbers = COALESCE(@Numbers + ', ', '') + Number
FROM   TableName where Number IS NOT NULL

SELECT @Numbers
```

Output would be:

102,103,104

edited Sep 22 '17 at 23:27



Graham

4,008 14 42 63

answered Apr 5 '16 at 7:08



pedram

5,161 6 42 67

- 2 This is really the best solution IMO as it avoids the encoding issues that FOR XML presents. I used `Declare @Numbers AS Nvarchar(MAX)` and it worked fine. Can you explain why you recommend not using it please? – [EvilDr](#) Aug 3 '16 at 15:01

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

Postgres arrays are awesome. Example:

47

Create some test data:

```
postgres=# \c test
You are now connected to database "test" as user "hgimenez".
test=# create table names (name text);
CREATE TABLE
test=# insert into names (name) values ('Peter'), ('Paul'), ('Mary');
INSERT 0 3
test=# select * from names;
 name
-----
 Peter
  Paul
  Mary
(3 rows)
```

Aggregate them in an array:

```
test=# select array_agg(name) from names;
 array_agg
-----
 {Peter,Paul,Mary}
(1 row)
```

Convert the array to a comma delimited string:

```
test=# select array_to_string(array_agg(name), ', ') from names;
 array_to_string
-----
 Peter, Paul, Mary
(1 row)
```

DONE

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 



1 1



11.9k 3 32 40

If you need more than one column, for example their employee id in brackets use the concat operator: `select array_to_string(array_agg(name || '(' || id || ')') -- Richard Fox Feb 27 '15 at 11:50`

Not applicable to [sql-server](#), only to [mysql](#) – GoldBishop May 4 '17 at 15:03

Oracle 11g Release 2 supports the LISTAGG function. Documentation [here](#).

45

COLUMN employees FORMAT A50

SELECT deptno, LISTAGG(ename, ',') **WITHIN GROUP (ORDER BY** ename) **AS** employees
FROM emp
GROUP BY deptno;

DEPTNO EMPLOYEES

```
-----
10 CLARK,KING,MILLER
20 ADAMS,FORD,JONES,SCOTT,SMITH
30 ALLEN,BLAKE,JAMES,MARTIN,TURNER,WARD
```

3 rows selected.

Warning

Be careful implementing this function if there is possibility of the resulting string going over 4000 characters. It will throw an exception. If that's the case then you need to either handle the exception or roll your own function that prevents the joined string from going over 4000 characters.

edited Mar 14 '13 at 14:30

answered Mar 8 '12 at 16:29



Alex

7,313 7 58 75

1 For older versions of Oracle, um, concept is perfect. Its use is explained in the link gift by Alex. Thanks Alex! [tccanelli](#) Jul 20 '15 at 12:04

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

In SQL Server 2005 and later, use the query below to concatenate the rows.

33

```

DECLARE @t table
(
    Id int,
    Name varchar(10)
)
INSERT INTO @t
SELECT 1, 'a' UNION ALL
SELECT 1, 'b' UNION ALL
SELECT 2, 'c' UNION ALL
SELECT 2, 'd'

SELECT ID,
stuff(
(
    SELECT ', ' + [Name] FROM @t WHERE Id = t.Id FOR XML PATH('')
),1,1, '')
FROM (SELECT DISTINCT ID FROM @t ) t

```

edited Oct 20 '14 at 8:49



George
Garchagudashvili

5,400 12 34 50

answered Jul 6 '11 at 12:46



Yogesh Bhadauriya

1,155 8 10

2 I believe this fails when the values contain XML symbols such as < or & . – Sam Aug 13 '13 at 1:36

I don't have access to a SQL Server at home, so I'm guess at the syntax here, but it's more or less:

26

```

DECLARE @names VARCHAR(500)

SELECT @names = @names + ' ' + Name
FROM Names

```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



unnecessary one) – [Marc Gravell](#) ♦ Oct 12 '08 at 9:10

3 the only problem with this approach (which i use all the time) is that you can't embed it – [ekkis](#) Nov 23 '12 at 22:22

To get rid of the leading space change the query to `SELECT @names = @names + CASE WHEN LEN(@names)=0 THEN '' ELSE ' ' END + Name FROM Names` – [Tian van Heerden](#) Mar 4 '16 at 9:15 ✎

Also, you have to check that Name is not null, you can do it by doing: `SELECT @names = @names + ISNULL(' ' + Name, '')` – [Vita1ij](#) Mar 18 '16 at 10:49

You need to create a variable that will hold your final result and select into it, like so.

25 Easiest Solution

```
DECLARE @char VARCHAR(MAX);
```

```
SELECT @char = COALESCE(@char + ', ' + [column], [column])
FROM [table];
```

```
PRINT @char;
```

answered Nov 15 '16 at 21:07



[Tigerjz32](#)

2,684 3 18 31

24 A recursive CTE solution was suggested, but no code provided. The code below is an example of a recursive CTE -- note that although the results match the question, the data doesn't *quite* match the given description, as I assume that you really want to be doing this on groups of rows, not all rows in the table. Changing it to match all rows in the table is left as an exercise for the reader.

```
;with basetable as
(
  SELECT id, CAST(name as varchar(max))name,
         ROW NUMBER() OVER(Partition By id order by seq) rw,
```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



```

    )g(id, name, seq)
),
rCTE as (
    SELECT recs, id, name, rw from basetable where rw=1
    UNION ALL
    SELECT b.recs, r.ID, r.name + ', ' + b.name name, r.rw+1
    FROM basetable b
        inner join rCTE r
    on b.id = r.id and b.rw = r.rw+1
)
SELECT name FROM rCTE
WHERE recs = rw and ID=4

```

answered Aug 9 '12 at 21:06

[jmoreno](#)

11.1k 2 39 70

For the flabbergasted: this query inserts 12 rows (a 3 columns) into a temporary basetable, then creates a recursive Common Table Expression (rCTE) and then flattens the name column into a comma-separated string for 4 groups of id s. At first glance, I think this is more work than what most other solutions for SQL Server do. – [knb](#) Jul 24 '17 at 13:34

- 1 @knb: not sure if that is praise,condemnation,or just surprise. The base table is because I like my examples to actually work, it doesn't really have anything to do with the question. – [jmoreno](#) Jul 25 '17 at 2:20

Starting with PostgreSQL 9.0 this is quite simple:

23

```

select string_agg(name, ',')
from names;

```

In versions before 9.0 array_agg() can be used as shown by hgmnz

edited Oct 20 '14 at 10:42

answered Nov 16 '12 at 23:15

[a_horse_with_no_name](#)

316k 48 482 588

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



[a_horse_with_no_name](#) May 17 '13 at 12:11

21



In SQL Server vNext this will be built in with the STRING_AGG function, read more about it here: <https://msdn.microsoft.com/en-us/library/mt790580.aspx>

edited Jan 10 '17 at 15:42

answered Nov 21 '16 at 11:27

[Henrik Fransas](#)**905** 9 13

17



Using XML helped me in getting rows separated with commas. For the extra comma we can use the replace function of SQL Server. Instead of adding a comma, use of the AS 'data()' will concatenate the rows with spaces, which later can be replaced with commas as the syntax written below.

```
REPLACE(  
    (select FName AS 'data()' from NameList for xml path(''))  
    , ' ', ', ')
```

edited Feb 26 '12 at 18:42

answered Apr 7 '11 at 11:16

[Peter Mortensen](#)**14.1k** 19 88 114[Diwakar](#)**179** 1 2

2 This is the best answer here in my opinon. The use of declare variable is no good when you need to join in another table, and this is nice and short. Good work. – [David Roussel](#) Jun 2 '11 at 16:22

7 that's not working good if FName data has spaces already, for example "My Name" – [binball](#) Jun 8 '11 at 15:16

Really it is working for me on ms-sql 2016 Select REPLACE((select Name AS 'data()' from Brand Where Id IN (1,2,3,4) for xml path('')) , ' ', ', ') as allBrands – [Rejwanul Reja](#) Apr 28 '17 at 10:13

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



An empty list will result in NULL value. Usually you will insert the list into a table column or program variable: adjust the 255 max length to your need.

(Diwakar and Jens Frandsen provided good answers, but need improvement.)

edited Feb 26 '12 at 20:03



Peter Mortensen

14.1k 19 88 114

answered Feb 3 '12 at 10:39



Daniel Reis

10.1k 5 36 66

There is a space before the comma when using this :(– [slayernoah](#) Nov 18 '15 at 18:23 ✎

1 Just replace ', ' with ', ' if you don't want the extra space. – [Daniel Reis](#) Nov 18 '15 at 23:17

SELECT STUFF((**SELECT** ', ' + name **FROM** [table] **FOR XML** PATH('')), 1, 2, '')

12

Here's a sample:

```
DECLARE @t TABLE (name VARCHAR(10))
INSERT INTO @t VALUES ('Peter'), ('Paul'), ('Mary')
SELECT STUFF((SELECT ', ' + name FROM @t FOR XML PATH('')), 1, 2, '')
--Peter, Paul, Mary
```

edited Feb 28 '18 at 16:04

answered Jan 25 '18 at 4:55



Max Szczurek

3,440 2 14 25

Thanks so much for giving the smallest possible solution, along with a working example! I had no idea why the top-voted answer works, nor how to replicate it. – [jpaugh](#) Mar 19 '18 at 14:21 ✎

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



▼ This puts the stray comma at the beginning.

However, if you need other columns, or to CSV a child table you need to wrap this in a scalar user defined field (UDF).

You can use XML path as a correlated subquery in the SELECT clause too (but I'd have to wait until I go back to work because Google doesn't do work stuff at home :-)

edited Feb 26 '12 at 18:39



Peter Mortensen

14.1k 19 88 114

answered Oct 13 '08 at 17:24



gbn

352k 60 495 586

▲ With the other answers, the person reading the answer must be aware of a specific domain table such as vehicle or student. The table must be created and populated with data to test a solution.

9

▼ Below is an example that uses SQL Server "Information_Schema.Columns" table. By using this solution, no tables need to be created or data added. This example creates a comma separated list of column names for all tables in the database.

```
SELECT
    Table_Name
    ,STUFF((
        SELECT ',' + Column_Name
        FROM INFORMATION_SCHEMA.Columns Columns
        WHERE Tables.Table_Name = Columns.Table_Name
        ORDER BY Column_Name
        FOR XML PATH ('')), 1, 1, ''
    )Columns
FROM INFORMATION_SCHEMA.Columns Tables
GROUP BY TABLE_NAME
```

answered May 4 '16 at 19:31



Mike Barlow - BarDev

7,285 15 54 77

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

```
SELECT question_id,
       LISTAGG(element_id, ',') WITHIN GROUP (ORDER BY element_id)
FROM YOUR_TABLE;
GROUP BY question_id
```

as @user762952 pointed out, and according to Oracle's documentation <http://www.oracle-base.com/articles/misc/string-aggregation-techniques.php>, the WM_CONCAT() function is also an option. It seems stable, but Oracle explicitly recommends against using it for any application SQL, so use at your own risk.

Other than that, you will have to write your own function; the Oracle document above has a guide on how to do that.

edited May 23 '17 at 11:47



Community ♦

1 1

answered May 13 '13 at 16:02



ZeroK

370 3 7

I really liked elegancy of [Dana's answer](#). Just wanted to make it complete.

7

```
DECLARE @names VARCHAR(MAX)
SET @names = ''

SELECT @names = @names + ', ' + Name FROM Names

-- Deleting last two symbols (', ')
SET @sSql = LEFT(@sSql, LEN(@sSql) - 1)
```

edited May 23 '17 at 11:55

community wiki
3 revs, 2 users 92%
Oleg Sakharov

If you are deleting the last two symbols ', ', then you need to add ', ' after Name ('SELECT \@names = \@names + Name + ', ' FROM Names'). That way the last two chars will always be ', '. – Justin T Dec 18 '15 at 11:04 ✎

In my case I needed to get rid of the *leading* comma so change the query to `SELECT @names = @names + CASE WHEN LEN(@names)=0 THEN '' ELSE ', '`

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



6

```
DECLARE @names VARCHAR(500)
SELECT @names = CONCAT(@names, ' ', name)
FROM Names
select @names
```

answered Feb 12 '15 at 12:01



Rapunzo

625 4 18 40

It would be nice to know *why* CONCAT works. A link to MSDN would be nice. – [DaveBoltman](#) Sep 20 '16 at 8:15

6

This answer will require some privilege in server to work.

[Assemblies](#) are a good option for you. There are a lot of sites that explain how to create it. The one I think is very well explained is this [one](#)

If you want, I have already created the assembly, and it is possible to download the DLL [here](#).

Once you have downloaded it, you will need to run the following script in your SQL Server:

```
CREATE Assembly concat_assembly
  AUTHORIZATION dbo
  FROM '<PATH TO Concat.dll IN SERVER>'
  WITH PERMISSION_SET = SAFE;
GO

CREATE AGGREGATE dbo.concat (
    @Value NVARCHAR(MAX)
    , @Delimiter NVARCHAR(4000)

) RETURNS NVARCHAR(MAX)
EXTERNAL Name concat_assembly.[Concat.Concat];
GO
```

Join **Stack Overflow** to learn, share knowledge, and build your career.

[Email Sign Up](#)

OR SIGN IN WITH



Google



Observe that the path to assembly may be accessible to server. Since you have successfully done all the steps, you can use the function like:

```
SELECT dbo.Concat(field1, ',')
FROM Table1
```

Hope it helps!!!

answered May 8 '15 at 1:39



Nizam

3,398 3 33 53

I usually use select like this to concatenate strings in SQL Server:

5

```
with lines as
(
    select
        row_number() over(order by id) id, -- id is a line id
        line -- line of text.
    from
        source -- line source
),
result_lines as
(
    select
        id,
        cast(line as nvarchar(max)) line
    from
        lines
    where
        id = 1
    union all
    select
        l.id,
        cast(r.line + N', ' + l.line as nvarchar(max))
    from
```

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



```
select top 1
  line
from
  result_lines
order by
  id desc
```

edited Jul 6 '11 at 7:06

answered Jul 6 '11 at 6:58



Vladimir Nesterovsky

422 5 11

If you want to deal with nulls you can do it by adding a where clause or add another COALESCE around the first one.

5

```
DECLARE @Names VARCHAR(8000)
SELECT @Names = COALESCE(COALESCE(@Names + ', ', '') + Name, @Names) FROM People
```

answered Jul 27 '11 at 20:05



Pramod

59 1 3

MySQL complete Example:

5

We have Users which can have many Data's and we want to have an output, where we can see all users Datas in a list:

Result:

id	rowList
0	6, 9
1	1,2,3,4,5,7,8,1

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

```
CREATE TABLE `Data` (  
  `id` int(11) NOT NULL,  
  `user_id` int(11) NOT NULL  
) ENGINE=InnoDB AUTO_INCREMENT=11 DEFAULT CHARSET=latin1;
```

```
INSERT INTO `Data` (`id`, `user_id`) VALUES  
(1, 1),  
(2, 1),  
(3, 1),  
(4, 1),  
(5, 1),  
(6, 0),  
(7, 1),  
(8, 1),  
(9, 0),  
(10, 1);
```

```
CREATE TABLE `User` (  
  `id` int(11) NOT NULL  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

```
INSERT INTO `User` (`id`) VALUES  
(0),  
(1);
```

Query:

```
SELECT User.id, GROUP_CONCAT(Data.id ORDER BY Data.id) AS rowList FROM User LEFT JOIN  
Data ON User.id = Data.user_id GROUP BY User.id
```

answered Jul 22 '15 at 7:51



[user1767754](#)

10.9k 5 78 90

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google





14.1k

19

88

114



49

1

This can be useful too

```
4 create table #test (id int,name varchar(10))
--use separate inserts on older versions of SQL Server
insert into #test values (1,'Peter'), (1,'Paul'), (1,'Mary'), (2,'Alex'), (3,'Jack')
```

```
DECLARE @t VARCHAR(255)
SELECT @t = ISNULL(@t + ', ' + name, name) FROM #test WHERE id = 1
select @t
drop table #test
```

returns

Peter,Paul,Mary

answered Oct 25 '13 at 8:14



endo64

1,615

17

24

- 5 Unfortunately this behavior seems not to be officially supported. [MSDN](#) says: "If a variable is referenced in a select list, it should be assigned a scalar value or the SELECT statement should only return one row." And there are people who observed problems: sqlmag.com/sql-server/multi-row-variable-assignment-and-order – [blueing](#) Dec 5 '13 at 9:11

This method applies to Teradata Aster database only as it utilizes its NPATh function.

3

Again, we have table Students

SubjectID	StudentName
-----------	-------------

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google



Then with NPATH it is just single SELECT:

```
SELECT * FROM npath(  
  ON Students  
  PARTITION BY SubjectID  
  ORDER BY StudentName  
  MODE(nonoverlapping)  
  PATTERN('A*')  
  SYMBOLS(  
    'true' as A  
  )  
  RESULT(  
    FIRST(SubjectID of A) as SubjectID,  
    ACCUMULATE(StudentName of A) as StudentName  
  )  
);
```

Result:

SubjectID	StudentName
1	[John, Mary, Sam]
2	[Alaina, Edward]

answered Nov 15 '13 at 20:26



topchef

13.7k 7 50 92

1 2 next

protected by [Community](#) ♦ Aug 2 '11 at 14:32

Thank you for your interest in this question. Because it has attracted low-quality or spam answers that had to be removed, posting an answer now requires 10 [reputation](#) on this site (the [association bonus](#) does not count).

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Google

Facebook

Join **Stack Overflow** to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH

 Google

Facebook 