# SQL Query Multiple Columns Using Distinct on One Column Only

Ask Question



I am trying to write a SQL query that selects multiple columns from a table with the distinct operator on one column only.



21

The table is simple. The columns are:



I am trying to select all the tblFruit\_FruitType with their corresponding tblFruit ID.

I have tried:

```
Select Distinct(tblFruit_FruitType), tblFruit_ID FROM tblFruit
```

-Returns all results, not just distinct

Select tblFruit\_FruitType, tblFruit\_ID FROM tblFruit Group By tblFruit\_FruitType

-Errors with Column tblFruit\_ID is invalid in the select list because it is not contained in either an aggregate function or the GROUP BY clause.

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Facebook

I also checked out these similar posts and could not get anything to work :(

mySQL select one column DISTINCT, with corresponding other columns

## SQL Server Distinct Union for one column

Hopefully this is enough information for an answer.

Thank you for your time!

EDIT (Sample Data and Desired Results)

tblFruit_ID,	<pre>tblFruit_FruitType,</pre>	tblFruit_FruitName
int	NVarChar	Text
1	Citrus	Orange
2	Citrus	Lime
3	Citrus	Lemon
4	Seed	Cherry
5	Seed	Banana

### Results:









asked Aug 13 '12 at 15:12

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH



Facebook

Home

**PUBLIC** 

## Stack Overflow

Tags

Users

Jobs



## 4 Answers



select \* from tblFruit where
tblFruit\_ID in (Select max(tblFruit\_ID) FROM tblFruit grou

29

answered Aug 13 '12 at 15:26



valex

**22.1k** 6 35 55



This query returns the correct rows with the results. Please see the below answer for more explanation of what is happening! — Steve Aug 13 '12 at 15:39

The below answer also works to produce the desired results.

– Steve Aug 15 '12 at 15:02

Thanks! It helped a lot – MaxG Oct 18 '17 at 12:19



You must use an aggregate function on the columns against which you are not grouping. In this example, I arbitrarily picked the Min function. You are combining the rows with the same <code>FruitType</code> value. If I have two rows with the same <code>FruitType</code> value but different <code>Fruit\_Id</code> values for example, what should the system do?



Select Min(tblFruit\_id) As tblFruit\_id

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up

OR SIGN IN WITH





#### edited Aug 13 '12 at 20:47

answered Aug 13 '12 at 15:16



**Thomas** 

**56.9k** 8 80 126

Nice. Thank you a ton. This worked perfectly and I actually understand what everything does now. I wish I could vote up more then once. - Steve Aug 13 '12 at 15:30

Note: In this query Min(tblFruit id) and Min(tblFruit FruitName) can be from different rows (different Fruits) – valex Aug 13 '12 at 15:30 🧪

You are correct. The query gives the same desired results but does return values from other rows. - Steve Aug 13 '12 at 15:37

@valexhome - Sorry, I see what you are suggesting. Yes, that is true however nothing other than the Id and Type are designed in the output so it will make no difference. - Thomas Aug 13 '12 at 20:50

Yes. I wish I could mark both as correct answers because they both give the exact same desired results. - Steve Aug 15 '12 at 15:01



I needed to do the same and had to query a query to get the result

0

I set my first query up to bring in all IDs from the table and 

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up or sign in with



Faceboo

Save this as Q04 1-0 this returned 1229 results (there are 63 unique records to query - soime with multiple LOTs)

```
SELECT DISTINCT ID
FROM q04_1;
```

Saved that as q04 2

I then wrote another query which brought in the required information linked to the ID

```
SELECT q04 2.ID, tMAIN.Customer, tMAIN.Category
FROM q04 2 INNER JOIN tMAIN ON q04 2.ID = tMAIN.ID;
```

Worked a treat and got me exactly what I needed - 63 unique records returned with customer and category details.

This is how I worked around it as I couldn't get the Group By working at all - although I am rather "wet behind the ears" weith SQL (so please be gentle and constructive with feedback)

answered Nov 3 '17 at 14:39



Marcus Black



select \* from (select



ROW NUMBER() OVER(PARTITION BY tblFruit FruitType ORDER BY

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up or sign in with



Faceboo

edited Feb 12 at 11:18



**Anastasios Selmanis 2,139** 3 18 36

answered Feb 12 at 10:05



Muhammed salem 1

Please add some explanation to that code, such that others can learn from it - Nico Haase Feb 12 at 11:43

Join Stack Overflow to learn, share knowledge, and build your career.

Email Sign Up or sign in with



Facebook