



DBA Fire

SQL Server, MySQL and WordPress Specialist

[DATABASE](#) / [SQL QUICK TIPS](#) / [T-SQL](#) / [TRAINING RESOURCES](#)

Newid() vs Newsequentialid() – Performance Of, Differences Between and Examples

Posted on [July 3, 2015](#) by [Rob StGeorge](#) / [2 Comments](#)

This article helps to explain the key differences between Newid() and Newsequentialid(). (crucial info if you are sitting the 70-461 SQL exam)

Quick Answer

[NEWID\(\)](#) generates the GUID in random order vs [NEWSEQUENTIALID\(\)](#) which generates the GUID in sequential order.

Key Facts


- Newsequentialid() creates a GUID greater than the previous one, *since windows was started*. If windows has been restarted the GUID may begin at a lower range (still unique however).
- For best performance of inserts use newsequentialid().
- NEWSEQUENTIALID is able to completely fill data and index pages.
- Newid() you can use in a select, newsequentialid() you cant
- If you are worried about, or have a need for privacy don't use sequential GUIDs
- NEWID() is [RFC4122](#) compliant.

Newid() vs Newsequentialid() T-SQL Example

```
1  USE dbafire_db;
2  GO
3  ----Create Test Table for with default columns values
4  CREATE TABLE GUID_Example
5  (
6  SeqCol uniqueidentifier DEFAULT NewSequentialID()
7  ,IDCol uniqueidentifier DEFAULT NEWID(),)
8  ----Inserting five default values in table
9  INSERT INTO GUID_Example DEFAULT
10 VALUES
11 INSERT INTO GUID_Example DEFAULT
12 VALUES
13 INSERT INTO GUID_Example DEFAULT
14 VALUES
15 INSERT INTO GUID_Example DEFAULT
16 VALUES
17 -----
18 SELECT *
19 FROM GUID_Example
20
21 ----Clean up database
22
23 DROP TABLE GUID_Example
```

Result Output

Note how easy it would have been to guess the sequentialid value (blue box).



	SeqCol	IDCol
1	C3D76021-2F21-E511-88B2-5427B6585B14	F306FBC8-8B6B-43BA-8ED7-3D63E8E801BC
2	C4D76021-2F21-E511-88B2-5427B6585B14	5C5C2A8A-42CE-4B1A-8DB8-ADBEE58564D7
3	C5D76021-2F21-E511-88B2-5427B6585B14	DE0DAF2A-3BAC-4468-87D8-15E634FA9B67
4	C6D76021-2F21-E511-88B2-5427B6585B14	D20B705E-FF45-4D1A-ACFA-A240D8CF3DA6

In this article we have shown you what the differences are between the two GUID functions.

Is there anything you think we should add, or that you have experienced with either Newid() or Newsequentialid()?

Share this:

Share 0

SHARE



Tweet

Post

Save

 Email

 70-461, guides, newid(), newsequentialid()



Rob StGeorge



Senior SQL Server Database Administrator residing in Auckland, NZ [View all posts by Rob StGeorge →](#)

YOU MIGHT ALSO LIKE

SQL Server Update Statistics - Quick Tips
& Examples
May 4, 2015

sp_executesql Stored Procedure
Examples, Output and Return Values
May 21, 2015

Synonyms SQL Server - Exam Tips
March 15, 2015

2 Comments



Bd Ac

November 17, 2016 at 8:47 pm

trying to figure out the best unique id mechanism to use for distributed databases which are also performant. any information on that would be greatly appreciated. thanks.

Pingback: [Differences Between Newid\(\) vs Newsequentialid\(\) – Priyanka The Fairy](#)

This site uses Akismet to reduce spam. [Learn how your comment data is processed.](#)

© 2019 DBA Fire

Powered by WordPress | Theme: Graphy by Themegraphy