

How can I drop all indexes in a SQL database with one command?



18



5

So, how can I drop all indexes in a SQL database with one command? I have this command that will get me all the 20 or so drop statements, but how can I run all of those drop statements from this "result set"?

```
select * from vw_drop_idnex;
```

Another variation that gives me the same list is:

```
SELECT 'DROP INDEX ' + ix.Name + ' ON ' + OBJECT_NAME(ID) AS QUERYLIST
FROM sysindexes ix
WHERE ix.Name IS NOT null and ix.Name like '%pre_%'
```

I tried to do "exec(select cmd from vw_drop_idnex)" and it didn't work. I am looking for something that works like a for loop and runs the queries one by one.

With Rob Farleys help, final draft of the script is:

```
declare @ltr nvarchar(1024);
SELECT @ltr = ( select 'alter table '+o.name+' drop constraint '+i.name+';'
from sys.indexes i join sys.objects o on i.object_id=o.object_id
where o.type<>'S' and is_primary_key=1
FOR xml path('') );
exec sp_executesql @ltr;

declare @qry nvarchar(1024);
select @qry = (select 'drop index '+o.name+'.'+i.name+';'
from sys.indexes i join sys.objects o on i.object_id=o.object_id
where o.type<>'S' and is_primary_key<>1 and index_id>0
for xml path(''));
exec sp_executesql @qry
```

sql sql-server tsq

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.



I think it's interesting that you added " AS QUERYLIST", when actually the answer you need shouldn't use that - as FOR XML PATH("") will concatenate strings in unnamed columns better (ie, without tags). – [Rob Farley](#) Aug 28 '09 at 0:23

Cool - you've got it sorted. I was basing my stuff on your sysindexes query, since most people don't have a copy of your 'vw_drop_idnex'. – [Rob Farley](#) Aug 29 '09 at 2:16

5 Answers



You're very close.

25



```
declare @qry nvarchar(max);
select @qry =
(SELECT 'DROP INDEX ' + ix.name + ' ON ' + OBJECT_NAME(ID) + '; '
FROM sysindexes ix
WHERE ix.Name IS NOT null and ix.Name like '%prefix_%'
for xml path(''));
exec sp_executesql @qry
```

answered Aug 28 '09 at 0:21



thanks a lot! i knew about that method but i was hoping for something that didnt require declaring a variable. i can make it work though. – [djangofan](#) Aug 28 '09 at 0:24

Also worth mentioning... you should probably consider the quotename function around your names, in case they have spaces in them. – [Rob Farley](#) Aug 28 '09 at 0:24

wow, that XML thing is cool. ;-) – [djangofan](#) Aug 28 '09 at 0:32

its not quite working. i get a message that says: Msg 102, Level 15, State 1, Line 1 Incorrect syntax near '<'. – [djangofan](#) Aug 28 '09 at 0:34

4 Given this is ~3 years later, i used this and fixed it by changing the select like to read: SELECT 'DROP INDEX [' + ix.name + '] ON ' +

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

this worked for me we skip sys indexes and for constraints

6

```

declare @qry nvarchar(max);
select @qry = (

    select 'IF EXISTS(SELECT * FROM sys.indexes WHERE name='''+ i.name +'' AND
object_id = OBJECT_ID(''+s.name+'').[''+o.name+'']))      drop index [''+i.name+''] ON
[''+s.name+''].[''+o.name+'']; '
    from sys.indexes i
        inner join sys.objects o on i.object_id=o.object_id
        inner join sys.schemas s on o.schema_id = s.schema_id
    where o.type<>'S' and is_primary_key<>1 and index_id>0
    and s.name!='sys' and s.name!='sys' and is_unique_constraint=0
for xml path('');

exec sp_executesql @qry

```

edited Apr 5 at 0:23



Graymatter

5,560 2 22 43

answered Dec 31 '15 at 9:25



Anatoli Klammer

1,161 1 9 16

None of the answers quite suited my needs.

0

I needed one that will also drop indexes that backup unique or primary constraints (except if these can't be dropped as they back up a foreign key)

```

DECLARE @SqlScript NVARCHAR(MAX);

SELECT @SqlScript =
(
SELECT
'
BEGIN TRY
'+ CASE WHEN 1 IN (i.is_primary_key, i.is_unique_constraint) THEN
'
ALTER TABLE [' + QUOTENAME(OBJECT_SCHEMA_NAME(i.object_id)) + '].[' + QUOTENAME(i.name) + ']'

```

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.

```

'
DROP INDEX ' + QUOTENAME(i.name) + ' ON ' + QUOTENAME(OBJECT_SCHEMA_NAME(i.object_id))
+ '.' + QUOTENAME(t.name)
END+

END TRY
BEGIN CATCH
RAISERROR('Could not drop %s on table %s', 0,1, ' + QUOTENAME(i.name, '') + ', ' +
QUOTENAME(t.name, '') + ')
END CATCH
'

FROM sys.indexes i
JOIN sys.tables t ON i.object_id = t.object_id
WHERE i.type_desc IN ('CLUSTERED', 'NONCLUSTERED' )
ORDER BY t.object_id, i.index_id DESC
FOR XML PATH(''), TYPE
).value('.', 'NVARCHAR(MAX)');

--Return script that will be run
SELECT @SqlScript AS [processing-instruction(x)]
FOR XML PATH('');

EXEC (@SqlScript);

```

answered Jan 13 '18 at 19:12



Martin Smith

358k 61 603 712

Minor improvements to the accepted answer that I had to make in my own case, mostly to account for schemas:

1

```

declare @qry nvarchar(4000);
select @qry = (select 'drop index ['+s.name+'].['+o.name+'].['+i.name+'];'
from sys.indexes i join sys.objects o on i.object_id=o.object_id join sys.schemas s on
o.schema_id=s.schema_id
where o.type<>'S' and is_primary_key<>1 and index_id>0 and s.name<>'sys'
for xml path(''));
exec sp_executesql @qry

```

Also: In my case it couldn't run in one go because the script becomes longer than 4000 characters. The only way I could think of to deal with that was to put a "top 20" on the inner select and execute it multiple times

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.



John

3,331

2

31

66

To get round the character count limitation, use `nvarchar(max)` as the datatype for `@qry` if you are on SQL 2005 or later. – [Ed Harper](#) Nov 3 '12 at 18:22

@EdHarper I tried that and it told me that type could be used as a variable. I'm on 2008R2 (Express). – [John](#) Nov 3 '12 at 23:35

From: [Stephen Hill's Bloggie](#)

5

```

DECLARE @indexName VARCHAR(128)
DECLARE @tableName VARCHAR(128)

DECLARE [indexes] CURSOR FOR

    SELECT          [sysindexes].[name] AS [Index],
                   [sysobjects].[name] AS [Table]

    FROM            [sysindexes]

    INNER JOIN      [sysobjects]
    ON              [sysindexes].[id] = [sysobjects].[id]

    WHERE          [sysindexes].[name] IS NOT NULL
    AND            [sysobjects].[type] = 'U'
    --AND          [sysindexes].[indid] > 1

OPEN [indexes]

FETCH NEXT FROM [indexes] INTO @indexName, @tableName

WHILE @@FETCH_STATUS = 0
BEGIN
    --PRINT 'DROP INDEX [' + @indexName + '] ON [' + @tableName + ']'
    Exec ('DROP INDEX [' + @indexName + '] ON [' + @tableName + ']')

    FETCH NEXT FROM [indexes] INTO @indexName, @tableName
END

CLOSE          [indexes]
DEALLOCATE     [indexes]

```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

answered Sep 1 '11 at 19:10

[Tawani](#)**6,313** 19 72 101

Excellent! It even includes a commented out print line for testing :) – [Wouter](#) Nov 15 '16 at 16:53

This will fail if there is one constraint on the table since those can only be dropoped using `DROP CONSTRAINT` , not `DROP INDEX` – [tigrou](#) Jan 4 '18 at 10:34

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).