

[articles](#) [Q&A](#) [forums](#) [stuff](#) [lounge](#) [?](#)

Search for articles, questions, tips

[Ask a Question](#)[All](#) [Unanswered](#) [FAQ](#)

How to pass query string to user Control

See more: [Javascript](#) [Ajax](#)Rate this: 

Hi,

I sm trying to develop a user control.

In which ,i am using AjaxModalPopextender.

I want to show list of values in that User Control.

But I want to use this control for most of the forms so i am creating a dynmaic user control.

So can anybody suggest how to pass parameters to user control by using querystring or in any other way.

Thanks in advance

Posted 6-Jun-12 0:09am[Abhijit Parab](#)[Add a Solution](#)

1 solution

Solution 1

Rate this:   

The best way to pass data to a user control would be to have public properties. For example:

[Hide](#) [Copy Code](#)

```
public partial class PopupControl : System.Web.UI.UserControl
{
```

```
public string DisplayValues { get; set; }  
}
```

So, now when you are using this control, you can do something like:

[Hide](#) [Copy Code](#)

```
<uc:popupcontrol runat="server" id="popup1" displayvalues="some values" xmlns:uc="#"unknown" />
```

Similarly, if you are dynamically creating these controls (as you say in your question):

[Hide](#) [Copy Code](#)

```
PopupControl popup = LoadControl(src);  
popup.DisplayValues = "some values";
```

This article pretty much explains this in detail - [Dynamic Loading of ASP.NET User Controls](#)[^]

Of course any query string can also be accessed in a user control just like in a aspx page, but the cleaner way of doing this is with user control properties.

Hope this helps!

Posted 6-Jun-12 19:33pm **Updated** 6-Jun-12 19:37pm v2
[Karthik. A](#)

[Permalink](#)

Comments

[Rahul Rajat Singh](#) 7-Jun-12 2:22am

Very good answer. +5 for that.

[Abhijit Parab](#) 7-Jun-12 2:55am

Thanks for this solution.

I am using now user control properties.

But now i want to access those properties in Javascript

U have any idea, how to access those propeties in Javascript?

Thanks in advance

Karthik. A 7-Jun-12 11:58am

You build the html from the properties you pass right? You will have to use them. For example, say are passing 3 values to the user control and you display it as <div>value 1</div> <div>value 2</div> <div>value 3</div>, attach some class to it like <div class="values">value 1</div> <div class="values">value 2</div> <div class="values">value 3</div>. Then using jquery you can get the values as \$('values') - which will be an array of 3 values. If you post the content of your .ascx file, I can help, looking at the html generated.

Add your solution here

Preview

...

Existing Members

Sign in to your account

Your Email

Password

[Forgot your password?](#)

...or Join us

Download, Vote, Comment, Publish.

Your Email

Optional Password

☒ I have read and agree to the [Terms of Service](#) and [Privacy Policy](#)

☒ Please subscribe me to the CodeProject newsletters

Submit your solution!

When answering a question please:

1. Read the question carefully.
2. Understand that English isn't everyone's first language so be lenient of bad spelling and grammar.
3. If a question is poorly phrased then either ask for clarification, ignore it, or **edit the question** and fix the problem. Insults are not welcome.
4. Don't tell someone to read the manual. Chances are they have and don't get it. Provide an answer or move on to the next question.

Let's work to help developers, not make them feel stupid.

This content, along with any associated source code and files, is licensed under [The Code Project Open License \(CPOl\)](#)

[Advertise](#) | [Privacy](#) | [Cookies](#) | [Terms of Service](#)
Web03 | 2.8.181222.1 | Last Updated 7 Jun 2012

Layout: [fixed](#) | [fluid](#)

Copyright © [CodeProject](#), 1999-2018
All Rights Reserved.

CodeProject, 503-250 Ferrand Drive Toronto Ontario, M3C 3G8 Canada +1 416-849-8900 x 100