

UNIX & LINUX

How can I get the current working directory? [duplicate]

Asked 4 years, 8 months ago Active 2 years, 3 months ago Viewed 608k times



179



36

This question already has an answer here:

[How can I assign the output of a command to a shell variable?](#) 2 answers

I want to have a script that takes the current working directory to a variable. The section that needs the directory is like this `dir = pwd`. It just prints `pwd` how do I get the current working directory into a variable?

bash

shell

scripting

directory

edited Jun 19 '17 at 16:37



terdon ♦

145k

39

299

479

asked Mar 4 '15 at 17:35



Interesting...

1,920

3

13

18

marked as duplicate by [Mikel](#), [Anthon](#), [garethTheRed](#), [Michael Homer](#), [peterph](#) Mar 4 '15 at 22:38

This question has been asked before and already has an answer. If those answers do not fully address your question, please [ask a new question](#).

2 Related: [Getting the source directory of a Bash script from within](#) – [kenorb](#) Jul 19 '17 at 18:37

This is not a duplicate of the question for which it is currently marked as one. The two questions should be compared, at least, based on their titles (as well as their answers). That the *answer* to this question is already covered by another is, or should be, irrelevant. – [Kenny Evitt](#) Mar 2 at 21:49

@KennyEvitt actually, one of the main reasons we close is precisely because an answer has been given elsewhere. And, in fact, the main question here is actually how to assign the output of a command to a variable, which is covered by the dupe. I have also given the answer to this specific case, so all bases are covered. There would be no benefit in opening this again. – [terdon](#) ♦ Mar 2 at 23:52

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

be re-opened, not to allow further activity, but to *not* imply that this question is 'bad'. – [Kenny Evitt](#) Mar 3 at 17:53

- 1 @KennyEvitt closing as a duplicate in no way implies that the question is bad! This question will remain here, answered, for ever. If you really want to know how to get the current working directory, you will find your answer here. If you just want to know how to save the output of a command in a variable, you will also find the answer here by following the link to the dupe. In any case, this isn't really something I should do alone, if you feel strongly that it should be reopened, please open a discussion on [Unix & Linux Meta](#) where such things should be resolved. – [terdon](#) ♦ Mar 3 at 18:36

5 Answers



There's no need to do that, it's already *in* a variable:

272

```
$ echo $PWD  
/home/terdon
```



The `PWD` variable is [defined by POSIX](#) and will work on all POSIX-compliant shells:

PWD

Set by the shell and by the `cd` utility. In the shell the value shall be initialized from the environment as follows. If a value for `PWD` is passed to the shell in the environment when it is executed, the value is an absolute pathname of the current working directory that is no longer than `{PATH_MAX}` bytes including the terminating null byte, and the value does not contain any components that are dot or dot-dot, then the shell shall set `PWD` to the value from the environment. Otherwise, if a value for `PWD` is passed to the shell in the environment when it is executed, the value is an absolute pathname of the current working directory, and the value does not contain any components that are dot or dot-dot, then it is unspecified whether the shell sets `PWD` to the value from the environment or sets `PWD` to the pathname that would be output by `pwd -P`. Otherwise, the `sh` utility sets `PWD` to the pathname that would be output by `pwd -P`. In cases where `PWD` is set to the value from the environment, the value can contain components that refer to files of type symbolic link. In cases where `PWD` is set to the pathname that would be output by `pwd -P`, if there is insufficient permission on the current working directory, or on any parent of that directory, to determine what that pathname would be, the value of `PWD` is unspecified. Assignments to this variable may be ignored. If an application sets or unsets the value of `PWD`, the behaviors of the `cd` and `pwd` utilities are unspecified.

For the more general answer, the way to save the output of a command in a variable is to enclose the command in `$()` or `` `` (backticks).

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

or

```
var=`command`
```

Of the two, the `$()` is preferred since it is easier to build complex commands like `command0 $(command1 $(command2 $(command3)))` .

edited Jun 2 '17 at 14:04

answered Mar 4 '15 at 17:52



terdon ♦

145k

39

299

479

```
dir=$(pwd)
```

26

This is more portable and preferred over the backticks method.

Using `$()` allow you to nest the commands

eg : `mech_pwd=$(pwd; echo in $(hostname))`

edited Mar 4 '15 at 18:07

answered Mar 4 '15 at 17:51



Govind Kailas

681

1

5

14

6 Actually, if anything, the backticks are more portable since they predate the `$()` format. There might conceivably still be some machines running shells that don't support the newer `$()` notation. While both are defined by POSIX, the `$()` is preferred today because it is a cleaner syntax and can be nested (`$(command1 $(command2))`) in a far simpler way than the backticks. – **terdon** ♦ Mar 4 '15 at 18:55

You can either use the environment variable `$PWD` , or write something like:

9

```
dir=`pwd`
```

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).



4

You need to use command substitution to save output of `pwd` command to a variable. Command substitution can use backticks or dollar characters. Like this:



```
$ mkdir "/tmp/new dir"
$ cd "/tmp/new dir"
$ CWD="$(pwd)"
$ echo $CWD
/tmp/new dir
$ cd ~
$ echo $CWD
/tmp/new dir
$ pwd
/home/ja
```

answered Mar 4 '15 at 17:43



Arkadiusz Drabczyk

10.3k 3 23 38



0

The value of the current working directory can be different. If you used symbolic links to get the the current directory, `pwd` will give different results than `/usr/bin/pwd`. Since you are using bash, I would use:



```
dir=$(/usr/bin/pwd)
```

or as per comment:

```
dir=$(pwd -P)
```

as I don't like back quotes since they can't nest.

edited Jul 19 '17 at 18:37



kenorb

answered Mar 4 '15 at 19:41



Robert Jacobs

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).

11/13/2019

bash - How can I get the current working directory? - Unix & Linux Stack Exchange

dir=\$(pwd -P) also works. — [Robert Jacobs](#) Mar 4 '15 at 19:43

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and our [Terms of Service](#).