

[npm Enterprise](#)[Products](#)[Solutions](#)[Resources](#)[Docs](#)[Support](#)[Join](#)[Log In](#)

Search

Get private packages and team management tools with npm Orgs. [Learn more »](#)

yarn-install

1.0.0 • [Public](#) • Published a year ago

[Readme](#)[3 Dependencies](#)[38 Dependents](#)[11 Versions](#)

install

```
> npm i yarn-install
```

⬇ weekly downloads

37,695



version

1.0.0

license

MIT

open issues

2

pull requests

0

homepage

github.com

repository

 **github**

last publish

a year ago

collaborators



Test with RunKit

Report a vulnerability

yarn-install

npm v1.0.0

downloads 163k/month

build passing

If command `yarn` exists it uses Yarn to install, otherwise fallbacks to npm.

Install

```
$ npm install --save yarn-install
```

Usage

```
const install = require('yarn-install')

const result = install({
  deps: ['webpack', 'mocha']
})
//=> result, returned by child_process.spawnSync
```

CLI

```
yarn global add yarn-install
```

then you will have `yarn-install` & `yarn-remove` commands

```
yarn-install pokemon --dev
```

```
yarn-install yo --global
```

```
yarn-remove xo
```

don't forget that `yarn-install` with dependencies is always `--save` by default.

```
yarn-install help
```

```
yarn-remove help
```

API

install([options])

options

deps

Type: array

An array of dependencies to install, you can omit it to install dependencies in `package.json`. If `dependencies` is present, it defaults to `--save` mode.

```
install({  
  deps: ['ava', 'koa']  
})
```

cwd

Type: string

The directory to run the command.

registry

Type: string

Specific a custom npm registry to use.

dev

Type: boolean

Use `--dev` for Yarn and `--save-dev` for npm.

global

Type: boolean

Install globally, stands for `npm --global` or `yarn global`.

remove

Type: boolean

Default: undefined

The reversed behavior to `install`, ie. `yarn remove` and `npm uninstall`

production

Type: boolean

Default: undefined

Only install dependencies in `package.json`.

respectNpm5

Type: boolean

Default: undefined

Use npm if it's `>= npm5`.

install.getPm([options])

Get the package manager that will be used to install.

options

respectNpm5

// Given you have yarn & npm 4 installed

```
const pm = install.getPm()
```

//=> yarn

// Given you have yarn & npm 5 installed

```
const pm = install.getPm()
```

//=> yarn

// Given you have yarn & npm 5 installed

```
const pm = install.getPm({ respectNpm5: true })
```

//=> npm

Contributing

1. Fork it!
2. Create your feature branch: `git checkout -b my-new-feature`
3. Commit your changes: `git commit -am 'Add some feature'`
4. Push to the branch: `git push origin my-new-feature`
5. Submit a pull request :D

License

MIT © EGOIST

Keywords

yarn install



HELP

[Documentation](#)

[Resources](#)

[Support / Contact Us](#)

[Registry Status](#)

[Report Issues](#)

[npm Community Site](#)

[Security](#)

ABOUT NPM

[About npm, Inc](#)

[JavaScriptSurvey.com](#)

[Events](#)

[Jobs](#)

[Press](#)

[npm Weekly](#)

[Blog](#)

[Twitter](#)

[GitHub](#)

TERMS & POLICIES

Terms of Use

Code of Conduct

Package Name Disputes

Privacy Policy

Reporting Abuse

Other policies