

Wi-Fi SECURITY ANALYSIS REPORT

Report ID: 2BCC814B | Date: 18 24 2026, 11:24

SSID: P410 5G

BSSID: 38:F6:CF:E2:68:9A

Security: Low-Medium Risk (WPA3 Transition Mode) (MFP Protected)

Signal: -79.00 dBm

Channel: channel 40 (5GHz)

SECURITY SCORE

85

out of 100

✓ Positive Security Features

- WPA3 Support: Enhanced security for modern devices.
- Strong AES/CCMP encryption: The current industry standard for data privacy.
- MFP Capable: Supports management frame protection for compatible clients.
- 5GHz Band: Higher bandwidth and lower interference than 2.4GHz.

■ Identified Risks & Mitigations

RISK: WPA3 Transition Mode: Maintains compatibility with older WPA2 devices.

Action: If all your devices support WPA3, switch the router to 'WPA3-SAE Only' mode to prevent Downgrade Attacks.

RISK: Personal PSK: Vulnerable to offline dictionary/brute-force attacks.

Action: Use a complex password (12+ characters, mixed cases, numbers, symbols) and change it periodically.

Technical Metadata Extraction

Below is the raw frame information captured during the scan:

AP Channel Report

channel(s): 50

operating class: 129

BSS Load

available admission capacity: 31250 [*32us]

channel utilisation: 0/255

station count: 3

Country

Code: CN

Environment: Indoor/Outdoor

constraints

- Channels [50 - 50] @ 27 dBm

DS Parameter set: channel 40

ERP: Barker_Preamble_Mode

Extended capabilities

flags

- BSS Transition
- Operating Mode Notification
- Max Number Of MSDUs In A-MSDU is unlimited

HE Operation

BSS Color: 0

Basic HE-MCS NSS Set

1 streams: MCS 0-7

2 streams: not supported

3 streams: not supported

4 streams: not supported

5 streams: not supported

6 streams: not supported

7 streams: not supported

8 streams: not supported

info: 0xffffc

HE Operation Parameters

Default PE Duration: 4

TXOP Duration RTS Threshold: 1023

info: (0x003ff4)

flags

- BSS Color Disabled

HE capabilities

1 streams

• MCS 0-11

• MCS 0-11

• MCS 0-11

• MCS 0-11

2 streams

• MCS 0-11

• MCS 0-11

• MCS 0-11

• MCS 0-11

3 streams

- not supported
- not supported
- not supported
- not supported

4 streams

- not supported
- not supported
- not supported
- not supported

5 streams

- not supported
- not supported
- not supported
- not supported

6 streams

- not supported
- not supported
- not supported
- not supported

7 streams

- not supported
- not supported
- not supported
- not supported

8 streams

- not supported
- not supported
- not supported
- not supported

HE MAC Capabilities (0x00011a081044)

Maximum A-MPDU Length Exponent: 3

flags

- +HTC HE Supported
- BSR
- OM Control
- BQR
- A-MSDU in A-MPDU
- OM Control UL MU Data Disable RX

HE PHY Capabilities

(0x0c20ce926f12afd0000c00):

Beamformee STS <= 80MHz: 3

Beamformee STS > 80MHz: 3

DCM Max Constellation: 2

DCM Max Constellation Rx: 2

Max NC: 2

Sounding Dimensions <= 80MHz: 2

Sounding Dimensions > 80MHz: 2

flags

- HE40/HE80/5GHz
- HE160/5GHz
- LDPC Coding in Payload

- NDP with 4x HE-LTF and 3.2us GI
- STBC Tx <= 80MHz
- STBC Rx <= 80MHz
- Full Bandwidth UL MU-MIMO
- Partial Bandwidth UL MU-MIMO
- SU Beamformer
- SU Beamformee
- MU Beamformer
- Codebook Size SU Feedback
- Codebook Size MU Feedback
- Triggered SU Beamforming Feedback
- Triggered MU Beamforming Feedback
- Partial Bandwidth Extended Range
- PPE Threshold Present
- STBC Tx > 80MHz
- STBC Rx > 80MHz
- TX 1024-QAM
- RX 1024-QAM

flags

- HE RX MCS and NSS set <= 80 MHz
- HE TX MCS and NSS set <= 80 MHz
- HE RX MCS and NSS set 160 MHz
- HE TX MCS and NSS set 160 MHz
- PPE Threshold 0x79 0x1c 0xc7 0x71 0x1c 0xc7 0x71

HT capabilities

Capabilities

Max AMSDU length: 7935 bytes

flags

- RX LDPC
- HT20/HT40
- SM Power Save disabled
- RX HT20 SGI
- RX HT40 SGI
- TX STBC
- RX STBC 1-stream
- No DSSS/CCK HT40

info: 0x9ef

HT RX MCS rate indexes supported: 0-15

Maximum RX AMPDU length 65535 bytes (exponent: 0x003)

Minimum RX AMPDU time spacing: 2 usec (0x04)

flags

- HT TX MCS rate indexes are undefined

HT operation

HT protection: 20 MHz

L-SIG TXOP Prot: 0

OBSS non-GF present: 0

PCO active: 0

PCO phase: 0

RIFS: 0

STA channel width: any

STBC beacon: 0

dual CTS protection: 0

dual beacon: 0
non-GF present: 1
primary channel: 40
secondary channel offset: below
Information elements from Probe Response frame
Power constraint: 0 dB
RM enabled capabilities
Capabilities
flags
• Neighbor Report
• AP Channel Report
info: 0x02 0x00 0x01 0x00 0x00
Measurement Pilot Capability: 0
Nonoperating Channel Max Measurement Duration: 0
RSN
Authentication suites: PSK SAE
Capabilities: 1-PTKSA-RC 1-GTKSA-RC MFP-capable (0x0080)
Group cipher: CCMP
Group mgmt cipher suite: AES-128-CMAC
Pairwise ciphers: CCMP
Version: 1
flags
• 0 PMKIDs
SSID: P410 5G
Supported rates: 6.0* 9.0 12.0* 18.0 24.0* 36.0 48.0 54.0
TSF: 579672509802 usec (6d, 17:01:12)
Transmit Power Envelope
VHT capabilities
VHT Capabilities (0x33ca79f6)
Max MPDU length: 11454
Supported Channel Width: 160 MHz
flags
• RX LDPC
• short GI (80 MHz)
• short GI (160/80+80 MHz)
• TX STBC
• SU Beamformer
• SU Beamformee
• MU Beamformer
• +HTC-VHT
• RX antenna pattern consistency
• TX antenna pattern consistency
VHT RX MCS set
1 streams: MCS 0-9
2 streams: MCS 0-9
3 streams: not supported
4 streams: not supported
5 streams: not supported
6 streams: not supported
7 streams: not supported
8 streams: not supported
VHT RX highest supported: 1560 Mbps

VHT TX MCS set

- 1 streams:** MCS 0-9
- 2 streams:** MCS 0-9
- 3 streams:** not supported
- 4 streams:** not supported
- 5 streams:** not supported
- 6 streams:** not supported
- 7 streams:** not supported
- 8 streams:** not supported

VHT TX highest supported: 1560 Mbps

VHT extended NSS: supported

VHT operation

VHT basic MCS set: 0xfffc

center freq segment 1: 42

center freq segment 2: 50

channel width: 1 (80 MHz)

WMM

BE: CW 3-1023, AIFSN 3

BK: CW 15-1023, AIFSN 7

VI: CW 7-15, AIFSN 2, TXOP 3008 usec

VO: CW 3-7, AIFSN 2, TXOP 1504 usec

flags

- u-APSD

info: Parameter version 1

beacon interval: 100 TUs

capability: ESS Privacy ShortPreamble APSD RadioMeasure (0x1831)

freq: 5200.0

last seen

- 15864.218s [boottime]
- 2222 ms ago

signal: -79.00 dBm