

Wi-Fi SECURITY ANALYSIS REPORT

Report ID: C94EF159 | Date: 26 28 2026, 18:28

SSID: P419 5G

BSSID: CC:71:90:D6:04:49

Security: High Risk (Mixed WPA1/WPA2 AES)

Signal: -40.00 dBm

Channel: channel 36 (5GHz)

SECURITY SCORE

35

out of 100

✓ Positive Security Features

- Strong AES/CCMP encryption: The current industry standard for data privacy.
- 5GHz Band: Higher bandwidth and lower interference than 2.4GHz.

■ Identified Risks & Mitigations

RISK: Legacy Mixed Mode: Supports outdated WPA1 protocols.

Action: Update router configuration to 'WPA2-AES Only'. Supporting WPA1 makes your network vulnerable to older exploits.

RISK: Personal PSK: Vulnerable to offline dictionary/brute-force attacks.

Action: Use a complex password (12+ characters, mixed cases, numbers, symbols) and change it periodically.

RISK: Missing MFP: Vulnerable to de-authentication (disconnection) attacks.

Action: Enable 'Management Frame Protection' (802.11w) in security settings to prevent attackers from forcibly disconnecting your devices.

Technical Metadata Extraction

Below is the raw frame information captured during the scan:

Country

Code: US

Environment: Indoor/Outdoor

constraints

- Channels [36 - 64] @ 30 dBm
- Channels [100 - 144] @ 30 dBm
- Channels [149 - 165] @ 30 dBm

DS Parameter set: channel 36

Extended capabilities

flags

- BSS Transition
- Max Number Of MSDUs In A-MSDU is unlimited

HT capabilities

Capabilities

Max AMSDU length: 3839 bytes

flags

- RX LDPC
- HT20/HT40
- SM Power Save disabled
- RX HT20 SGI
- TX STBC
- RX STBC 1-stream
- No DSSS/CCK HT40

info: 0x1af

HT RX MCS rate indexes supported: 0-15

Maximum RX AMPDU length 65535 bytes (exponent: 0x003)

Minimum RX AMPDU time spacing: 4 usec (0x05)

flags

- HT TX MCS rate indexes are undefined

HT operation

HT protection: 20 MHz

L-SIG TXOP Prot: 0

OBSS non-GF present: 0

PCO active: 0

PCO phase: 0

RIFS: 0

STA channel width: any

STBC beacon: 0

dual CTS protection: 0

dual beacon: 0

non-GF present: 1

primary channel: 36

secondary channel offset: above

Information elements from Probe Response frame

Power constraint: 3 dB

RM enabled capabilities

Capabilities

flags

- Neighbor Report
- AP Channel Report

info: 0x02 0x00 0x01 0x00 0x00

Measurement Pilot Capability: 0

Nonoperating Channel Max Measurement Duration: 0

RSN

Authentication suites: PSK

Capabilities: 1-PTKSA-RC 1-GTKSA-RC (0x0000)

Group cipher: CCMP

Pairwise ciphers: CCMP

Version: 1

SSID: P419 5G

Supported rates: 6.0* 9.0 12.0* 18.0 24.0* 36.0 48.0 54.0

TPC report: TX power: 63 dBm

TSF: 6139090993904 usec (71d, 01:18:10)

Transmit Power Envelope

Local Maximum Transmit Power For 20 MHz: 15 dBm

Local Maximum Transmit Power For 40 MHz: 15 dBm

Local Maximum Transmit Power For 80 MHz: 15 dBm

VHT capabilities

VHT Capabilities (0x33c00031)

Max MPDU length: 7991

Supported Channel Width: neither 160 nor 80+80
flags

- RX LDPC
- short GI (80 MHz)
- +HTC-VHT
- RX antenna pattern consistency
- TX antenna pattern consistency

VHT RX MCS set

- 1 streams: MCS 0-9
- 2 streams: MCS 0-9
- 3 streams: not supported
- 4 streams: not supported
- 5 streams: not supported
- 6 streams: not supported
- 7 streams: not supported
- 8 streams: not supported

VHT RX highest supported: 780 Mbps

VHT TX MCS set

- 1 streams: MCS 0-9
- 2 streams: MCS 0-9
- 3 streams: not supported
- 4 streams: not supported
- 5 streams: not supported
- 6 streams: not supported
- 7 streams: not supported
- 8 streams: not supported

VHT TX highest supported: 780 Mbps

VHT extended NSS: not supported

VHT operation

VHT basic MCS set: 0xffffa

center freq segment 1: 42
center freq segment 2: 0
channel width: 1 (80 MHz)

WMM

BE: CW 15-1023, AIFSN 3
BK: CW 15-1023, AIFSN 7
VI: CW 7-15, AIFSN 2, TXOP 3008 usec
VO: CW 3-7, AIFSN 2, TXOP 1504 usec
info: Parameter version 1

WPA

Authentication suites: PSK
Group cipher: CCMP
Pairwise ciphers: CCMP
Version: 1

beacon interval: 100 TUs

capability: ESS Privacy RadioMeasure (0x1011)

freq: 5180.0

last seen

- 2612.029s [boottime]
- 2687 ms ago

signal: -40.00 dBm