

Wi-Fi SECURITY ANALYSIS REPORT

Report ID: 9181E5F8 | Date: 26 03 2026, 19:03

SSID: P419
BSSID: CC:71:90:D6:04:48
Security: High Risk (Mixed WPA1/WPA2 AES)
Signal: -40.00 dBm
Channel: channel 6 (2.4GHz)

SECURITY SCORE

35
out of 100

✓ Positive Security Features

- Strong AES/CCMP encryption: The current industry standard for data privacy.

■ Identified Risks & Mitigations

RISK: Legacy Mixed Mode: Supports outdated WPA1 protocols.

Action: Update router configuration to 'WPA2-AES Only'. Supporting WPA1 makes your network vulnerable to older exploits.

RISK: Personal PSK: Vulnerable to offline dictionary/brute-force attacks.

Action: Use a complex password (12+ characters, mixed cases, numbers, symbols) and change it periodically.

RISK: Missing MFP: Vulnerable to de-authentication (disconnection) attacks.

Action: Enable 'Management Frame Protection' (802.11w) in security settings to prevent attackers from forcibly disconnecting your devices.

Technical Metadata Extraction

Below is the raw frame information captured during the scan:

Country

Code: US

Environment: Indoor/Outdoor

constraints

- Channels [1 - 11] @ 30 dBm

DS Parameter set: channel 6

ERP: Barker_Preamble_Mode

Extended capabilities

flags

- HT Information Exchange Supported
- BSS Transition

Extended supported rates: 6.0 12.0 24.0 48.0

HT capabilities

Capabilities

Max AMSDU length: 3839 bytes

flags

- RX LDPC
- HT20
- SM Power Save disabled
- RX HT20 SGI
- TX STBC
- RX STBC 1-stream
- No DSSS/CCK HT40

info: 0x1ad

HT RX MCS rate indexes supported: 0-15

Maximum RX AMPDU length 65535 bytes (exponent: 0x003)

Minimum RX AMPDU time spacing: 4 usec (0x05)

flags

- HT TX MCS rate indexes are undefined

HT operation

HT protection: no

L-SIG TXOP Prot: 0

OBSS non-GF present: 0

PCO active: 0

PCO phase: 0

RIFS: 0

STA channel width: 20 MHz

STBC beacon: 0

dual CTS protection: 0

dual beacon: 0

non-GF present: 1

primary channel: 6

secondary channel offset: no secondary

Information elements from Probe Response frame

RSN

Authentication suites: PSK

Capabilities: 1-PTKSA-RC 1-GTKSA-RC (0x0000)

Group cipher: CCMP

Pairwise ciphers: CCMP

Version: 1

SSID: P419

Supported rates: 1.0* 2.0* 5.5* 11.0* 9.0 18.0 36.0 54.0

TSF: 6141247476028 usec (71d, 01:54:07)

WMM

BE: CW 15-1023, AIFSN 3

BK: CW 15-1023, AIFSN 7

VI: CW 7-15, AIFSN 2, TXOP 3008 usec

VO: CW 3-7, AIFSN 2, TXOP 1504 usec

info: Parameter version 1

WPA

Authentication suites: PSK

Group cipher: CCMP

Pairwise ciphers: CCMP

Version: 1

beacon interval: 100 TUs

capability: ESS Privacy ShortSlotTime (0x0411)

freq: 2437.0

last seen

- 4768.593s [boottime]
- 2380 ms ago

signal: -40.00 dBm