

Wi-Fi SECURITY ANALYSIS REPORT

Report ID: 0692D478 | Date: 28 17 2026, 09:17

SSID: VKU_Student
BSSID: EC:FC:C6:24:16:D1
Security: Medium Risk (WPA2-PSK AES)
Signal: -45.00 dBm
Channel: channel 116 (5GHz)

SECURITY SCORE

65
out of 100

✓ Positive Security Features

- Strong AES/CCMP encryption: The current industry standard for data privacy.
- 5GHz Band: Higher bandwidth and lower interference than 2.4GHz.

■ Identified Risks & Mitigations

RISK: Personal PSK: Vulnerable to offline dictionary/brute-force attacks.

Action: Use a complex password (12+ characters, mixed cases, numbers, symbols) and change it periodically.

RISK: Missing MFP: Vulnerable to de-authentication (disconnection) attacks.

Action: Enable 'Management Frame Protection' (802.11w) in security settings to prevent attackers from forcibly disconnecting your devices.

Technical Metadata Extraction

Below is the raw frame information captured during the scan:

Country

Code: VN

Environment: Indoor/Outdoor

constraints

- Channels [36 - 64] @ 23 dBm
- Channels [100 - 140] @ 30 dBm
- Channels [149 - 165] @ 23 dBm

DS Parameter set: channel 116

Extended capabilities

flags

- Extended Channel Switching
- BSS Transition
- Operating Mode Notification
- TWT Responder Support
- Max Number Of MSDUs In A-MSDU is unlimited

HE Operation

BSS Color: 13

Basic HE-MCS NSS Set

- 1 streams:** MCS 0-7
 - 2 streams:** not supported
 - 3 streams:** not supported
 - 4 streams:** not supported
 - 5 streams:** not supported
 - 6 streams:** not supported
 - 7 streams:** not supported
 - 8 streams:** not supported
- info:** 0xffffc

HE Operation Parameters

- Default PE Duration:** 4
 - TXOP Duration RTS Threshold:** 1023
- info:** (0x003ff4)

HE capabilities

1 streams

- MCS 0-11
- MCS 0-11

2 streams

- MCS 0-11
- MCS 0-11

3 streams

- MCS 0-11
- MCS 0-11

4 streams

- MCS 0-11
- MCS 0-11

5 streams

- not supported
- not supported

6 streams

- not supported
- not supported

7 streams

- not supported
- not supported

8 streams

- not supported
- not supported

HE MAC Capabilities (0x000512081000)

Maximum A-MPDU Length Exponent: 2

flags

- +HTC HE Supported
- TWT Responder
- BSR
- OM Control
- OM Control UL MU Data Disable RX

HE PHY Capabilities

(0x44200ec06f5b8518000c00):

Beamformee STS <= 80MHz: 3

Beamformee STS > 80MHz: 3

Max NC: 3

Sounding Dimensions <= 80MHz: 3

Sounding Dimensions > 80MHz: 3

flags

- HE40/HE80/5GHz
- 242 tone RUs/5GHz
- LDPC Coding in Payload
- NDP with 4x HE-LTF and 3.2us GI
- STBC Tx <= 80MHz
- STBC Rx <= 80MHz
- Rx HE MU PPDU from Non-AP STA
- SU Beamformer
- SU Beamformee
- MU Beamformer
- Ng = 16 SU Feedback
- Codebook Size SU Feedback
- Triggered SU Beamforming Feedback
- PPE Threshold Present
- TX 1024-QAM
- RX 1024-QAM

flags

- HE RX MCS and NSS set <= 80 MHz
- HE TX MCS and NSS set <= 80 MHz
- PPE Threshold 0x3b 0x1c 0xc7 0x71 0x1c 0xc7 0x71 0x1c 0xc7 0x71

HT capabilities

Capabilities

Max AMSDU length: 3839 bytes

flags

- RX LDPC
- HT20/HT40
- SM Power Save disabled
- RX HT20 SGI

- RX HT40 SGI
- TX STBC
- RX STBC 1-stream
- No DSSS/CCK HT40

info: 0x1ef

HT RX MCS rate indexes supported: 0-31

Maximum RX AMPDU length 65535 bytes (exponent: 0x003)

Minimum RX AMPDU time spacing: 4 usec (0x05)

flags

- HT TX MCS rate indexes are undefined

HT operation

HT protection: 20 MHz

L-SIG TXOP Prot: 0

OBSS non-GF present: 1

PCO active: 0

PCO phase: 0

RIFS: 0

STA channel width: any

STBC beacon: 0

dual CTS protection: 0

dual beacon: 0

non-GF present: 1

primary channel: 116

secondary channel offset: above

Information elements from Probe Response frame

Power constraint: 0 dB

RSN

Authentication suites: PSK

Capabilities: 4-PTKSA-RC 4-GTKSA-RC (0x0028)

Group cipher: CCMP

Pairwise ciphers: CCMP

Version: 1

SSID: VKU_Student

Supported rates: 6.0* 9.0 12.0* 18.0 24.0* 36.0 48.0 54.0

TPC report: TX power: 24 dBm

TSF: 44652179572 usec (0d, 12:24:12)

Transmit Power Envelope

Local Maximum Transmit Power For 20 MHz: 30 dBm

Local Maximum Transmit Power For 40 MHz: 30 dBm

Local Maximum Transmit Power For 80 MHz: 30 dBm

VHT capabilities

VHT Capabilities (0x0f8b79b0)

Max MPDU length: 3895

Supported Channel Width: neither 160 nor 80+80

flags

- RX LDPC
- short GI (80 MHz)
- TX STBC
- SU Beamformer
- SU Beamformee
- MU Beamformer

VHT RX MCS set

1 streams: MCS 0-9
2 streams: MCS 0-9
3 streams: MCS 0-9
4 streams: MCS 0-9
5 streams: not supported
6 streams: not supported
7 streams: not supported
8 streams: not supported

VHT RX highest supported: 0 Mbps

VHT TX MCS set

1 streams: MCS 0-9
2 streams: MCS 0-9
3 streams: MCS 0-9
4 streams: MCS 0-9
5 streams: not supported
6 streams: not supported
7 streams: not supported
8 streams: not supported

VHT TX highest supported: 0 Mbps

VHT extended NSS: supported

VHT operation

VHT basic MCS set: 0x0000
center freq segment 1: 122
center freq segment 2: 0
channel width: 1 (80 MHz)

WMM

BE: CW 15-1023, AIFSN 3
BK: CW 15-1023, AIFSN 7
VI: CW 7-15, AIFSN 2, TXOP 3008 usec
VO: CW 3-7, AIFSN 2, TXOP 1504 usec
flags

- u-APSD

info: Parameter version 1

beacon interval: 100 TUs

capability: ESS Privacy (0x0011)

freq: 5580.0

last seen

- 6257.551s [boottime]
- 697 ms ago

signal: -45.00 dBm