

Your grade: **100%**

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

Next item →

1. Which of the following is true about policy-based methods? (**Select all that apply**)

1 / 1 point

☒ Policy-based methods allow smooth improvement in the policy without drastic changes.

✓ **Correct**

Correct. As the policy parameters change the action probabilities change smoothly, but with value-based methods a small change in action-value function can drastically change the action probabilities.

☒ Policy-based methods can learn an optimal policy that is stochastic.

✓ **Correct**

Correct. It can learn a stochastic optimal policy, such as the soft-max in action preferences.

☒ Policy-based methods are useful in problems where the policy is easier to approximate than action-value functions.

✓ **Correct**

Correct. For example in the Mountain Car problem a good policy is easy to represent whereas the value function is complex.

☒ Policy-based methods can be applied to continuous action space domains.

✓ **Correct**

Correct. By parameterizing a policy to represent a probability distribution such as Gaussian, it can be applied to continuous action space domains.

2. Which of the following statements about parameterized policies are true? (**Select all that apply**)

1 / 1 point

☐ The policy must be approximated using linear function approximation.

☒ The probability of selecting any action must be greater than or equal to zero.

✓ **Correct**

Correct! This is one of the conditions for a valid probability distribution.

☐ The function used for representing the policy must be a softmax function.

☒ For each state, the sum of all the action probabilities must equal to one.

✓ **Correct**

Correct! This condition is necessary for the function to be a valid probability distribution.

3. Assume you're given the following preferences $h_1 = 44$, $h_2 = 42$, and $h_3 = 38$, corresponding to three different actions (a_1, a_2, a_3), respectively. Under a softmax policy, what is the probability of choosing a_2 , rounded to three decimal numbers?

1 / 1 point

☐ 0.42

☐ 0.002

☒ 0.119

☐ 0.879

✓ **Correct**

Correct!

4. Which of the following is true about softmax policy? (Select all that apply)

1 / 1 point

☐ It cannot represent an optimal policy that is stochastic, because it reaches a deterministic policy as one action preference dominates

others.

- ☒ It can be parameterized by any function approximator as long as it can output scalar values for each available action, to form a softmax policy.

✔ **Correct**

Correct. It can use any function approximation from deep artificial neural networks to simple linear features.

- ☐ Similar to epsilon-greedy policy, softmax policy cannot approach a deterministic policy.

- ☒ It is used to represent a policy in discrete action spaces.

✔ **Correct**

Correct!

5. What are the differences between using softmax policy over action-values and using softmax policy over action-preferences? (**Select all that apply**)

1 / 1 point

- ☒ When using softmax policy over action-values, even if the optimal policy is deterministic, the policy may never approach a deterministic policy.

✔ **Correct**

Correct. The policy will always select proportional to exponentiated action-values.

- ☐ When using softmax policy over action-values, assuming a tabular representation, the policy will converge to the optimal policy regardless of whether the optimal policy is stochastic or deterministic.

- ☒ When using softmax policy over action-preferences, assuming a tabular representation, the policy will converge to the optimal policy regardless of whether the optimal policy is stochastic or deterministic.

✔ **Correct**

Correct. Action-preferences does not approach specific values like action-values do. They can be driven to produce a stochastic policy or deterministic policy.

6. What is the following objective, and in which task formulation?

1 / 1 point

$$r(\pi) = \sum_s \mu(s) \sum_a \pi(a|s, \theta) \sum_{s', r} p(s', r|s, a) r$$

- ☐ Undiscounted return objective, episodic task
- ☐ Discounted return objective, continuing task
- ☒ Average reward objective, continuing task
- ☐ Average reward objective, episodic task

✔ **Correct**

Correct.

7. The following equation is the outcome of the policy gradient theorem. Which of the following is true about the policy gradient theorem? (Select all that apply)

1 / 1 point

$$\nabla r(\pi) = \sum_s \mu(s) \sum_a \nabla \pi(a|s, \theta) q_\pi(s, a)$$

- ☒ This expression can be converted into the following expectation over π :

$$\mathbb{E}_\pi[\nabla \ln \pi(A|S, \theta) q_\pi(S, A)]$$

✔ **Correct**

Correct. In fact, this expression is normally used to perform stochastic gradient updates.

- ☒ The true action value q_π can be approximated in many ways, for example using TD algorithms.

✔ **Correct**

Correct.

- ☒ We do not need to compute the gradient of the state distribution μ .

✓ Correct
Correct.

- ✓ This expression can be converted into:

$$\mathbb{E}_{\pi}[\sum_a \nabla \pi(a|S, \theta) q_{\pi}(S, a)]$$

In discrete action space, by approximating q_{π} we could also use this gradient to update the policy.

✓ Correct
Correct. The expression contains sum over actions, which can be computed for discrete actions. In the textbook, this is also called the all-actions method.

8. Which of the following statements is true? (Select all that apply)

1 / 1 point

- ✓ Subtracting a baseline in the policy gradient update tends to reduce the variance of the update, which results in faster learning.

✓ Correct
Correct.

- ✓ To update the actor in Actor-Critic, we can use TD error in place of q_{π} in the Policy Gradient Theorem.

✓ Correct
Correct. This is equivalent to using one-step state value and subtracting a current state value baseline.

- ✓ The Actor-Critic algorithm consists of two parts: a parameterized policy — the actor — and a value function — the critic.

✓ Correct
Correct.

- ☐ TD methods do not have a role when estimating the policy directly.

9. We usually want the critic to update at a faster rate than the actor.

1 / 1 point

- ☒ True
☐ False

✓ Correct
Correct!

10. Consider the following state features and parameters θ for three different actions (red, green, and blue):

1 / 1 point

$$\mathbf{X}(s) = \begin{bmatrix} 0.1 \\ 0.3 \\ 0.6 \end{bmatrix} \quad \theta = \begin{bmatrix} 45 \\ 73 \\ 21 \\ 120 \\ 120 \\ -10 \\ -100 \end{bmatrix} \quad \left. \begin{array}{l} \} \\ \} \\ \} \end{array} \right\} \begin{array}{l} a_0 \\ a_1 \end{array}$$

$$\begin{bmatrix} 200 \\ -25 \end{bmatrix} \Bigg\} a_2$$

Compute the action preferences for each of the three different actions using linear function approximation and stacked features for the action preferences.

What is the action preference of a_0 (red)?

- ☐ 33
- ☒ 39
- ☐ 37
- ☐ 35

✓ **Correct**
Correct.

11. Which of the following statements are true about the Actor-Critic algorithm with softmax policies? (**Choose all that apply**)

1 / 1 point

- ☒ Since the policy is written as a function of the current state, it is like having a different softmax distribution for each state.

✓ **Correct**
Correct!

- ☒ The learning rate parameter of the actor and the critic can be different.

✓ **Correct**
Correct! In practice, it is preferable to have a slower learning rate for the actor so that the critic can accurately critique the policy.

- ☐ The actor and the critic share the same set of parameters.
- ☐ The preferences must be approximated using linear function approximation.

12. Which of the following is an advantage of Gaussian policy parameterization over discretizing the action space? (**Select all that apply**)

1 / 1 point

- ☒ Continuous actions also allow learning to generalize over actions.

✓ **Correct**
Correct.

- ☐ Gaussian policies are differentiable, whereas policies over discretized actions are not.

- ☒ Even if the true action set is discrete, but very large, it might be better to treat them as a continuous range.

✓ **Correct**
Correct.

- ☒ There might not be a straightforward way to choose a discrete set of actions.

✓ **Correct**
Correct! Selecting a discrete set of actions that results in good performance is problem dependent. Maybe we need hundreds of actions. Maybe it is state dependent!