# AMAZON BASE BUILDING COMPLIANCE STANDARD

| | |
|---|---|
| **Task Title** | Flammable gas detectors |
| **APM Object** | CT.SAFE.FLAMGASDETECT |
| **APM Description** | Flammable gas detectors |
| **General tasks always required** | Follow safety procedures - e.g. 1MRA, LOTO, PPE, etc.<br>Ensure that all WOs are carried out by qualified, certified staff with appropriate familiarisation and supervision as required<br>Add notes for each observation and create a FWO if necessary to eliminate defects<br>Use appropriate tools, chemicals and industry standard practices (RME policy permitting)<br>Ensure relevant logs, readings and certification is uploaded to APM prior to WO closure. CT evidence must be additionally uploaded to the DMS (WorkDocs in DE)<br>To suggest improvements please raise a SIM or contact document authors<br>Leonardo Vitale (LEOVITAL) Rob Gisby (EWARTGXR) or APM, Benito Sanchez Sanchez de Puerta (BPPUERTA)<br>SIM - Link to SIM template |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Last Update: (Version)** | abr-24 | **Last Update Change Detail:** | PM evidence changed from 3M to 12M. | **Activities may be covered by No-Go restrictions:** | Not Specified | **Special Certification Required:** | **Delivered By:** |
| **Evidenced part or full by PM:** | Yes | **Related BBM PM:** | GAS - FIRE.DET.HYDRO | **Related CT Areas:** | CT.HVAC.GASDET - CT.HVAC.GASAPPLIANCE | | |

## Scope

Any site where flammable gas detectors (e.g. methane gas detectors, hydrogen gas detectors, etc.) are used to provide early warning of high concentrations of potentially explosive or flammable gases.

## Using this document

This document is intended as a guide and may not be exhaustive. Whilst this document is based extensively on professional guidance and subject to periodic review, individual sites must be diligent to ensure they are aware of, and comply to, local and changing regulations.
The format of these standards is intended to improve navigation between maintenance and compliance standards and to allow frequent, minor updates to a single living resource. Please avoid offline or printed versions and check version dates and change log.
In the event of becoming aware of errors or omissions in this document, sites must provide detail, including references to relevant source information to their local planner for escalation - SIM Link above.
This document is considered released as draft.
For Information contact Authors: R Gisby (ewartgxr), Leonardo Vitale (leovital) and Benito Sanchez Sanchez de Puerta (bppuerta)

## Maintenance and Compliance Relationship

Where relevant, associated Base Building PM's are listed on the header . In many cases maintenance contributes to, or fulfils compliance requirement. This may not be exhaustive and is intended to assist users to identify relevant maintenance.
If a BBM Maintenance activity fully meets the compliance requirements below, periodic upload of PM evidence will be required to APM and DMS / Workdays depending on region.

## Key to Abbreviations

The key to the below document is as follows:
**CT** - Amazon compliance / statutory task - not otherwise covered by a BBM Standard PM. Evidence to be provided into APM and DMS upon task closure.
**CT*** - This is a conditional task based or based on findings from previous inspections. If a frequency is not used, a further appropriate frequency needs to be in either the region, or 'ALL'. Local teams must ensure appropriate frequency.
**(CT)** - Compliance task which is likely met or exceeded by a CT task in [ALL] and therefore achieved by proxy BUT local site must satisfy themselves that requirements are fully met.
**PM** - Requirement can demonstrated through appropriate maintenance - Refer to relevant PM Standard
**(PM)** - Maintenance task which is met or exceeded by a PM task in [ALL] and therefore achieved by proxy BUT local site must satisfy themselves that requirements are fully met including regional / manufacturer requirements.
**EVID** - Periodic upload of evidence to DMS, for non-CT task lines. For example, evidence of PM completion, certification, licence etc.
**EVID*** - Conditional requirement to upload evidence at the interval provided
**N A R** - No Additional Requirement

## Required Tasks

| Region | Task Index | Task Frequency | Task Requirements | Qualification of Inspector | Records Required | PM | Weekly | Monthly | 3 Monthly | 6 Monthly | 12 Monthly | 24 Monthly | Additional |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| All | 1 | In accordance with manufacturer's instructions and planned maintenance programme. | Routine maintenance of all flammable gas detectors to ensure correct integrity, including potential damage, loose parts, connections, etc. | Competent person, usually internal | Maintenance logbook | PM | | | | | EVID | | |
| All | 2 | In accordance with manufacturer's instructions and the site risk assessment, but at least monthly. | Routine inspection and testing of all flammable gas detectors. A "bump test" should be performed, which consists of exposing the gas detector to a high concentration of a gas to ensure the sensors respond and the alarms are functioning. | Competent person, best practice to outsource | Inspection records, report or certificate.<br>Risk assessment<br>CE Declaration of Conformity. | | | CT | | | | | |
| All | 3 | In accordance with manufacturer's instructions and the site risk assessment, but at least every 6 months.<br>A calibration should also follow any failed bump test. | Routine calibration of all sensors | Competent person, best practice to outsource | Inspection records, report or certificate.<br>Risk assessment | | | | | CT | | | |

## Related Regional Legislation

| Region | Relevant legislation | Vendor Certification | Statutory requirement |
|---|---|---|---|
| ALL | No region specific legislation specified | N/A | N/A |

| | | | |
|---|---|---|---|
| CZ | Decree No. 246/2001 Coll.<br>Act No. 133/1985 Coll. on Fire Protection.<br><br>ČSN 332570, ČSN 332000, ČSN EN 62305,<br>ČSN 331600.ed.2,<br>Decree No. 50/1978 Coll. | Accredited company<br><br>Review technician | Once a year, unless the manufacturer establishes a shorter<br>Revision of equipment 6 - 36 months depending on the type of environment |
| DE | Betriebssicherheitsverordnung – BetrSichV<br><br>DGUV Information 213-057 - Gaswarneinrichtungen und -geräte für den Explosionsschutz<br><br>DGUV Information 213-056 - Gaswarneinrichtungen und -geräte für toxische Gase/Dämpfe und Sauerstoff | Trained person (unterwiesene Person) for the visual inspection<br><br>OR<br><br>A qualified person (Fachpersonal) for the functional check.<br><br>OR<br><br>Competent person (befähigte Person) for the system check and maintenance record check. | After installation, gas warning devices must be tested for their function by a competent person.<br><br>Visual inspection once a month, a functional inspection at least every 4 months, and a system inspection at least every year.<br><br>For devices with a self-monitoring system, functional inspections can be conducted at least once a year.<br><br>For portable devices the visual inspection must also include a display test, and must be conducted before each shift, or every working day if the device is used over the course of a shift change. |
| ES | RD 919/2006, of July 28, which approves distribution and usage of gas fuel and its Complementary Technical Instructions ICG 01 to 11.<br><br>RD 681/2003, of June 12, which approves the protection of the health and safety of workers exposed to the risks derived from explosive environments in the workplace.<br><br>RD 842/2002, of August 2, which approves the electrotechnical regulation for low voltage and its 52 Complementary Technical Instructions.<br>Technical Instruction ITC-BT-29. | Accredited company (OCA) by ENAC for low-voltage related inspections and authorised company for fuel gas install inspections. | At least every 5 years within official low-voltage inspections<br><br>At least every 5 years within official gas fuel install inspections. |
| FR | Labor Code Article R4227-39 relating to safety equipment<br>Code du travail article R4227-39 relatif aux consignes de sécurité incendie<br>https://www.legifrance.gouv.fr/codes/article_lc/LEGIARTI000024769386<br>Site Authorization Permit can require additional periodic exams<br>APSAD - voluntary standard for insurance | Competent person, best practice to outsource to specialist company. | Routine maintenance of gas detectors.<br>Bump testing to ensure correct operation of detector and alarm in accordance with manufacturer's instructions.<br>Regular calibration of flammable gas detectors in accordance with manufacturer's instructions, but at least 6-monthly. Additionally, following any failed bump test. |
| IT | Legislative Decree 9/04/2008 n.81<br>CEI EN 60079-29-2:2016 (Maintenance)<br>CEI EN 60079-29-1:2017 (Performance requirements and test methods)<br>UNI 11522:2014 (Flammable gas detectors for domestic use-Maintenance) | Competent person. | Bump testing, regular calibration and maintenance of flammable gas detectors in accordance with manufacturer's instructions, but at least every 6 months. |
| PL | Regulation of Minister Of Interior and Administration of June 7, 2010 on fire protection of buildings, other structures and areas (Journal of Laws 2010, number 109, item 719)<br>Regulation of the Minister of Economy of 30 October 2002 on the minimum requirements for occupational health and safety in the use of machines by employees at work (Journal of Laws 2002, number 191, item 1596)<br>Regulation of the Minister of Economy of October 21, 2008 on essential requirements for machines (Dz.U. 2008 nr 199 poz. 1228) | Competent person, best practice to outsource to specialist company. | Routine maintenance of gas detectors.<br>Bump testing to ensure correct operation of detector and alarm in accordance with manufacturer's instructions.<br>Regular calibration of flammable gas detectors in accordance with manufacturer's instructions, but at least once a year. Additionally, following any failed bump test. |
| ROI | S.I. No. 299/2007 - Safety, Health and Welfare at Work (General Application) Regulations 2007 (irishstatutebook.ie)<br>Safety, Health and Welfare at Work Act 2005 (irishstatutebook.ie)<br>BS EN 60079-29-1:2016 – Explosive atmospheres. Gas detectors. Performance requirements of detectors for flammable gases | Competent person, best practice to outsource to specialist company. | Routine maintenance of gas detectors.<br>Bump testing to ensure correct operation of detector and alarm in accordance with manufacturer's instructions. |
| SK | Ordinance No. 140/2018 Coll. on details in the field of installation of gas equipment<br>STN EN 61779 Electrical apparatus for the detection and measurement of flammable gases | Qualified and certified person (producer or dealer of equipment) | Annual inspection of stationary and portable gas detectors. |
| UK | Health and Safety at Work etc. Act 1974 (legislation.gov.uk)<br>Health and Safety at Work (Northern Ireland) Order 1978 (legislation.gov.uk)<br>The Management of Health and Safety at Work Regulations 1999 (legislation.gov.uk)<br>Management of Health and Safety at Work Regulations (Northern Ireland) 2000 (legislation.gov.uk)<br>BS EN 60079-29-1:2016 – Explosive atmospheres. Gas detectors. Performance requirements of detectors for flammable gases | Competent person, best practice to outsource to specialist company. | Routine maintenance of gas detectors.<br>Bump testing to ensure correct operation of detector and alarm in accordance with manufacturer's instructions, but at least monthly.<br>Regular calibration of flammable gas detectors in accordance with manufacturer's instructions, but at least 6-monthly. Additionally, following any failed bump test. |