

San Jose State University
CMPE 202
Summer 2018
T3am Project Report

Professor Paul Nguyen
Professor Gopinath Vinodh

Table of Contents

| | |
|------------------------------------------------------------------------------------|----------|
| General Information | 6 |
| Team Members | 6 |
| Demo URL / Accounts | 6 |
| Front End App | 6 |
| Back End / API App | 6 |
| Code Repository URLs | 7 |
| Back end (back end api / java server) | 7 |
| Set up Documentation | 7 |
| Extra Credit Implementations | 7 |
| Implement a "real" iOS or Android Mobile App calling the REST API | 7 |
| Implement Web "Front-End" Deployed to Heroku for Starbucks Payment Card management | 7 |
| Deploy API to AWS as Docker Containers in Amazon Containers | 7 |
| DockerFile | 7 |
| Sprint Information | 8 |
| Burndown Chart | 9 |
| Team Schedule / Task Allocation | 9 |
| Sprint Standup Journal | 10 |
| 07/21/2018 to 07/27/2018 | 10 |
| 07/20/2018 | 11 |
| 07/19/2018 | 11 |
| 07/17/2018 to 07/18/2018 | 11 |
| 07/16/2018 | 11 |
| 07/15/2018 | 12 |
| 07/14/2018 | 12 |

| | |
|--------------------------------------------|-----------|
| Github Push Contributors Graph | 12 |
| Technologies | 14 |
| Back End | 14 |
| Apache Camel | 14 |
| Maven | 14 |
| Google Guice | 14 |
| JUnit/Python unittest | 14 |
| iBATIS Data Mapping Framework | 14 |
| Front End (webapp) | 14 |
| jQuery, jQuery UI, bootstrap and moment.js | 15 |
| Deployment | 15 |
| App Flow | 15 |
| Sign up flow | 15 |
| Login flow | 16 |
| Dashboard | 16 |
| Cards List | 17 |
| Add New Card | 18 |
| Purchases List | 19 |
| Add New Purchase | 20 |
| Cloud Infrastructure | 21 |
| Back End Deployment | 21 |
| Docker on AWS ECS | 22 |
| Build Docker image | 22 |
| Push to ECS repository | 22 |
| Run from EC2 | 22 |
| Run from ECS Fargate | 23 |
| Front End Heroku deployment | 27 |
| App Setup | 27 |
| Config Vars | 28 |

| | |
|----------------------------|-----------|
| Database Schema | 29 |
| sb_user | 29 |
| Schema | 29 |
| Results | 29 |
| sb_card | 29 |
| Schema | 30 |
| Results | 30 |
| sb_purchase | 30 |
| Schema | 31 |
| Results | 31 |
| API Spec | 32 |
| Sign up (Create User) | 32 |
| Curl Sample | 32 |
| Response | 32 |
| Sign in (Log in) | 32 |
| Curl Sample | 32 |
| Response | 33 |
| Get Cards Reload by UserId | 33 |
| Curl Sample | 33 |
| Response | 33 |
| Reload Card by UserId | 33 |
| Curl Sample | 33 |
| Response | 34 |
| Get Purchases by UserId | 35 |
| Curl Sample | 35 |
| Response | 35 |
| Add Purchase by UserId | 35 |
| Curl Sample | 35 |
| Response | 35 |

| | |
|----------------------------------|-----------|
| Class Design UML Diagrams | 36 |
| State Diagrams | 38 |
| Sign In / Sign Up | 38 |
| Add Card | 38 |
| Add Purchase | 39 |
| Unit Testings | 39 |
| Java Unit Tests | 39 |
| Python End-To-End Tests | 40 |

General Information

Team Members

Our team is called t3am and has the following members:

- Sy Le (006088940)
- Hyunwook Shin (012507417)
- Kevin Lai (008498282)
- Lin Cheng (012484459)

Demo URL / Accounts

Front End App

Front End App can be accessed via

- <http://cmpe202-t3am-starbucks-webapp.herokuapp.com>

Demo Account

email: **syle@gmail.com**

password: **password**

Back End / API App

Back end app can be accessed via

- <http://cmpe202-java-rest-api.herokuapp.com>
- <http://ec2-34-192-241-153.compute-1.amazonaws.com:8202>

Code Repository URLs

Back end (back end api / java server)

<https://github.com/nguyensjsu/su18-202-t3am>

<https://github.com/nguyensjsu/su18-202-t3am/tree/master/web-app>

Set up Documentation

Follow this doc to setup the environment locally.

<https://docs.google.com/document/d/1YKTIsn7VnxUjwjOXPIQigHKz-usWgbWOH0NESBkKrKk/edit?usp=sharing>

Jenkins Server (CI/CD)

<https://ec2-18-222-125-85.us-east-2.compute.amazonaws.com/jenkins>

Extra Credit Implementations

Our team chooses to implement the following things for extra credit

Implement a "real" iOS or Android Mobile App calling the REST API

Implement Web "Front-End" Deployed to Heroku for Starbucks Payment Card management

Refer to the heroku link above for front end app and the front end code

Deploy API to AWS as Docker Containers in Amazon Containers

DockerFile

```
FROM java
EXPOSE 8202
COPY . /opt/t3am
CMD nohup java -cp /opt/t3am/starbucks2-service-1.0.jar RestService &
```

More details about the docker file can be found here in our repo


<https://github.com/nguyensjsu/su18-202-t3am/blob/master/Dockerfile>

Sprint Information

Refer to this link for more information about our doc.

https://docs.google.com/spreadsheets/d/1pfwGlnHH9siD7P3Q7gQIALwi6-xfxB6CuSd0tBX_e3c/edit?usp=sharing

Burndown Chart



Team Schedule / Task Allocation

| Task | Owner | ETA in Hour |
|-----------------------|-------|-------------|
| Initial Planning work | Team | 2 |

| | | |
|--------------------------------------------------------------------------------------------------|------------------|-----|
| Set up RDS and DB tables | Lin Cheng | 8 |
| Set up the pipeline for webapp (AWS Beanstalk) includes the domain and basic hello world api. | Lin Cheng | 2 |
| Set up CI/CD pipeline for the above webapp/noSQL in the github repo... | Hyunwook | 2 |
| Initial code plumbing for the API server | Lin Cheng | 12 |
| Set up Response Header Content Type - Application/JSON | Sy Le | 1 |
| GET /api/v1/signin | Hyunwook | 8 |
| GET /api/v1/signout | Hyunwook | 4 |
| GET /api/v1/signup | Sy Le | 10 |
| GET /api/v1/user_profile return the information related to the user by user_id | Sy Le | 4 |
| GET /api/v1/transactions list all the transactions (card reloads vs purchase history) by user_id | Hyunwook & Kevin | 8 |
| POST /api/v1/reload add a new card to the list | Lin Cheng | 6 |
| POST /api/v1/purchase add a new purchase transaction to the list | Kevin Lai | 8 |
| Add Unit Tests | Hyunwook | 4 |
| Extra Credit Module 1 - Web Front End client side code development | Sy Le | 15 |
| Extra Credit Module 1 - Web Front End deployment on Heroku | Sy Le | 10 |
| MISC - Deploy BE code to Heroku | Sy Le | 16 |
| Docker image and deploy to AWS ECS | Lin Cheng | 10 |
| Do Project Report | TEAM | 40 |
| | | 170 |

Sprint Standup Journal

07/21/2018 to 07/27/2018

- Team mainly works on project report

07/20/2018

- Done Front End and Deployed Front End App and API to Heroku
 - api : <http://cmpe202-java-rest-api.herokuapp.com>
 - webapp : <http://cmpe202-t3am-starbucks-webapp.herokuapp.com>
- Started and work on report

07/19/2018

- Complete last set of flow front end integration
- Start work on the deployment of front end heroku deployment
- Added Validation to API
- Wrap server response in ServerResponse
- Start work on project report
- Successfully run on AWS ECS Fargate

07/17/2018 to 07/18/2018

- Continue working on integrating Web FE in Add Purchase Flow
- Refactored and clean up code to make the Add Purchase API flow to work
- Clean up sql_backup file
- Docker container for the API later
- WIP - Continued Add mode unit tests

07/16/2018

- Completed API to sign in using email and password
- Deployed our API Back End to heroku: <http://cmpe202-java-rest-api.herokuapp.com>
- Continued BE and FE (webapp) integration work: authentication (signin / signup) flow
- Parameterized Database Connection Strings, App Host, App Port into environment for deployment.
- Fixed UserProfile Fetch API to return real data instead of mocks

- WIP - CI/CD pipeline with jenkins
- WIP - Plumbing up unit tests

07/15/2018

- Initial Code complete, Server is now Up and Running
- Created 2 AWS EC instances for prod and dev
 - PROD: ec2-18-209-62-254.compute-1.amazonaws.com
 - DEV: ec2-34-192-241-153.compute-1.amazonaws.com
- Created AWS RDS for data store
- Functional getCards API
- Functional signUp API
- Basic plumbing works for POJO Objects such as Purchase, UserProfile, Card
- Created SQL Backup file for new deployment sql_backup

07/14/2018

- Team meetup, draft out dependencies, task breakdown and initial work


Github Push Contributors Graph

<https://github.com/nguyensjsu/su18-202-t3am/graphs/contributors>

Jun 10, 2018 – Jul 20, 2018

Contributions: Commits ▾


Contributions to master, excluding merge commits



synle

67 commits 2,634 ++ 1,171 --


#1



h7shin

26 commits 1,083 ++ 763 --

#2



Kevin-Lai

10 commits 111 ++ 32 --


#3



xzchenglin

9 commits 1,161 ++ 145 --

#4



Technologies

Back End

Apache Camel

The back end is built using Apache Camel which is used to serve up REST API endpoints.

Maven

The back end project is bundled using maven.

Google Guice

We used Guice to handle dependencies injection, namely `@Inject`

iBATIS Data Mapping Framework

Internally we used iBATIS to map java code to SQL queries

Front End (webapp)

The front end application in this project is a thin layer that handles integration with the back end API described above to handle basic flows of payments, purchases, reloads for drink ordering.

jQuery, jQuery UI, bootstrap and moment.js

The front end is built using Bootstrap, jQuery, jQuery UI to construct the major piece of the UI and moment.js to handle date formatting

Deployment

As for deployment, we used Heroku to deploy. You can find more information below.

Testing and CI/CD

JUnit/Python Unit Test

JUnit library is used to run component-level unit tests in tools and models packages.

Python unittest library stress the end-to-end API testing on a local mock server.

Jenkins

Jenkins job starts a test backend server locally by compiling the source code from GitHub using “make run”. As the Jenkins node does not have access to the git repository, we instead have created a recent copy of the source code (instead of git clone). After starting a service that listens to port 8082, Jenkins runs “make test” to run a series of API testing against the local server. This is ensure that there is no regressions or unexpected failures in our APIs. Once both JUnit and Python (end-to-end API) tests pass, the job will be marked as SUCCESS.

The screenshot displays the Jenkins web interface for a specific build. At the top, the Jenkins logo is on the left, a red square with the number '2' in the center, and a search bar on the right. Below the header, the breadcrumb navigation shows 'Jenkins > API Testing > #122'. On the left sidebar, there are links: 'Back to Project', 'Status', 'Changes', 'Console Output', 'Edit Build Information', 'Delete Build', and 'Previous Build'. The main content area features a large blue sphere icon next to the text 'Build #122 (Jul 20, 2018 11:34:15 PM)'. To the right of this, it says 'Started 10 min ago' and 'Took 2 min 4 sec'. Below the build title, there is a note 'No changes.' and a button 'add description'. At the bottom, it says 'Started by user Admin 202'. The footer of the page indicates 'Page generated: Jul 20, 2018 11:44:25 PM UTC', a link to 'REST API', and 'Jenkins ver. 2.121.1'.

Jenkins

2

search

Admin 202 | log out

Jenkins > API Testing > #122

ENABLE AUTO REFRESH

Back to Project

Status

Changes

Console Output

Edit Build Information

Delete Build

Previous Build

Build #122 (Jul 20, 2018 11:34:15 PM)

Started 10 min ago
Took 2 min 4 sec

add description

No changes.

Started by user Admin 202

Page generated: Jul 20, 2018 11:44:25 PM UTC


REST API

Jenkins ver. 2.121.1

Nginx

Nginx is used to route requests to Jenkins HTTPS server <https://ec2-18-222-125-85.us-east-2.compute.amazonaws.com:8081/login>

App Flow



Sign up flow

New users used this to sign up for new account

Login flow

Existing users log in with their existing account

CMPE202 T3AM Starbucks Store

Sign In

Sign Up

Email address

syle@gmail.com

Password

.....

Sign In

Dashboard

This is where users check their remaining balance as well as some information about their account

CMPE202 T3AM Starbucks Store

User

Reloads History

Purchases History

New Card

New Purchase

Log Out

User ID

958bbc20-cda2-4f57-9fe6-e1ecb6e6e913

Email address

syle@gmail.com

Full Name

Sy Le

Current Balance

\$36.00

Cards List

This is where user look for their previous reloaded gift cards

CMPE202 T3AM Starbucks Store

User

Reloads History

Purchases History

New Card

Refresh

| Number | Code | Balance | Date Added |
|-----------|------|---------|----------------------------|
| 111111111 | 111 | \$10.00 | July 18th 2018, 3:20:57 pm |
| 222222222 | 222 | \$20.00 | July 18th 2018, 3:21:13 pm |
| 333333333 | 333 | \$30.00 | July 19th 2018, 2:41:04 pm |

Add New Card

This is where user add a new gift card

Add New Card

User ID

958bbc20-cda2-4f57-9fe6-e1ecb6e6e913

Email address

syle@gmail.com

Card ID

4444444444

Card Code

444

Card Balance

40

Save

Cancel

Purchases List

This is where users can view their previous purchases

CMPE202 T3AM Starbucks Store

User

Reloads History

Purchases History

New Purchase

Refresh

| Balance | Note | Date Added |
|---------|-------------|----------------------------|
| \$3.00 | Iced Coffee | July 18th 2018, 3:26:33 pm |
| \$3.00 | Iced Coffee | July 18th 2018, 3:26:34 pm |
| \$3.00 | Iced Coffee | July 18th 2018, 3:26:38 pm |
| \$4.00 | Frap | July 18th 2018, 3:29:54 pm |
| \$5.00 | Chai | July 18th 2018, 3:49:18 pm |
| \$6.00 | Thai Tea | July 19th 2018, 2:41:31 pm |

Add New Purchase

This is where the user add a new purchase

Add New Purchase

User ID

958bbc20-cda2-4f57-9fe6-e1ecb6e6e913

Email address

syle@gmail.com

Charge Amount

5

Note

Cold Brew

Save

Cancel

Cloud Infrastructure

Back End Deployment

Docker on AWS ECS

Build Docker image

- Check out code
- Go to source root(su18-202-t3am) and do a “mvn install”

- Run "java -cp starbucks2-service/target/starbucks2-service-1.0.jar RestService"
- Copy starbucks2-service/target/starbucks2-service-1.0.jar and starbucks2-service/target/lib/ to EC2 server's /opt/t3am
- From /opt/t3am, "docker build -t t3am ."

Push to ECS repository

- Login to AWS ECR: "aws ecr get-login --no-include-email"
- Create repository: "aws ecr create-repository --repository-name t3am"
- Tag image: "docker tag t3am 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am"
- Push: "docker push 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am"

```
[root@ip-172-31-3-105 t3am]# docker tag t3am 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am
[root@ip-172-31-3-105 t3am]# docker push 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am
The push refers to a repository [914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am]
a76d79f03ef5: Pushed
35c20f26d188: Layer already exists
c3fe59dd9556: Layer already exists
6ed1a81ba5b6: Layer already exists
a3483ce177ce: Layer already exists
ce6c8756685b: Layer already exists
30339f20ced0: Layer already exists
0eb22bfb707d: Layer already exists
a2ae92ffcd29: Layer already exists
latest: digest: sha256:816288955be83bf80de4d9cb02703024897909d8a1e944ad65cb65c8b3160969 size: 2212
```

Run from EC2

- Login to AWS ECR: "aws ecr get-login --no-include-email"
- Pull: "docker pull 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am"



```
[root@ip-172-31-1-174 ~]# docker pull 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am
Using default tag: latest
latest: Pulling from t3am
e12c678537ae: Already exists
8d9ed335b7db: Already exists
3318dd58ae60: Already exists
624ba6156166: Already exists
c7a02d193df7: Already exists
813b62320378: Already exists
81cf5426393a: Already exists
0a2b7222259b: Already exists
ffff8146f091: Pull complete
Digest: sha256:816288955be83bf80de4d9cb02703024897909d8a1e944ad65cb65c8b3160969
Status: Downloaded newer image for 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am:latest
```

- Tag image: “docker tag 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am t3am”
- Run: “docker run -p 8202:8202 t3am”

```
[root@ip-172-31-1-174 ~]# docker run -p 8202:8202 t3am
log4j:WARN No appenders could be found for logger (org.apache.ibatis.logging.LogFactory).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
INFO [main] - Loaded 222 type converters
INFO [main] - Apache Camel 2.19.3 (CamelContext: camel-1) is starting
INFO [main] - JMX is enabled
INFO [main] - Runtime endpoint registry is in extended mode gathering usage statistics of all incoming and outgoing endpoints
INFO [main] - StreamCaching is not in use. If using streams then its recommended to enable stream caching. See more details at
INFO [main] - Route: route4 started and consuming from: direct://bizoption
INFO [main] - Route: route5 started and consuming from: direct://bizget
INFO [main] - Route: route6 started and consuming from: direct://bizpost
Jul 17, 2018 6:21:27 AM org.restlet.engine.connector.NetServerHelper start
INFO: Starting the internal [HTTP/1.1] server on port 8202
INFO [main] - Route: route1 started and consuming from: http://localhost:8202/api/v1/(path)?restletMethods=OPTIONS
INFO [main] - Route: route2 started and consuming from: http://localhost:8202/api/v1/(path)?restletMethods=GET
INFO [main] - Route: route3 started and consuming from: http://localhost:8202/api/v1/(path)?restletMethods=POST
INFO [main] - Total 6 routes, of which 6 are started.
INFO [main] - Apache Camel 2.19.3 (CamelContext: camel-1) started in 0.925 seconds
```

Run from ECS Fargate

- Define a Fargate Task using the docker image

| Container Name | Image |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
|   t3am-c | 914381644891.dkr.ecr.us-east-1.amazonaws.com/t3am |

Details

Port Mappings

| Host Port | Container Port | Protocol |
|-----------|----------------|----------|
| 8202 | 8202 | tcp |

Healthcheck

Command ping localhost

| Interval | Timeout | Start period | Retries |
|----------|---------|--------------|---------|
| 100 | 3 | 100 | 3 |

- Create a cluster and run the task

Cluster : t3am

Get a detailed view of the resources on your cluster.

Status **ACTIVE**

Registered container instances 0

Pending tasks count 0 Fargate, 0 EC2

Running tasks count 1 Fargate, 0 EC2

Active service count 1 Fargate, 0 EC2

Draining service count 0 Fargate, 0 EC2

Services

Tasks

ECS Instances

Metrics

Scheduled Tasks

Create

Update

Delete

Filter in this page

Launch type

ALL

Service type

ALL



Service Name

Status

Service ty...

Task Defin...




t3am-s

ACTIVE

REPLICA

t3am-t:1

- Get the created instance IP and try visiting

| Network interf... | Subnet ID | VPC ID | Zone | Security groups | Description | Instan... | Status | IPv4 Public IP |
|-------------------|------------------|--------------|------------|-----------------|-------------------|-----------|----------------------------------------------------------------------------------------------|----------------|
| eni-05e60662 | subnet-1ebe6a... | vpc-541c5533 | us-east-1d | t3am-s-1585 | arn:aws:ecs:us... | |  in-use | 34.224.74.171 |

GET ▾

http://34.224.74.171:8202/api/v1/cards|

Authorization

Headers (2)

Body

Pre-request Script

Type

No Auth

Body

Cookies

Headers (8)


Test Results

Pretty

Raw

Preview

JSON ▾



1

[]

Front End Heroku deployment

App Setup

The screenshot shows the Heroku dashboard for the application 'cmpe202-t3am-starbucks-webapp'. The interface includes a top navigation bar with the Heroku logo, a search bar, and a user profile icon. Below the navigation bar, the application name is displayed along with a star icon, an 'Open app' button, and a 'More' dropdown menu. The GitHub repository 'synle/cmpe202-t3am-starbucks-webapp' is linked, with the 'master' branch selected. A horizontal menu contains tabs for Overview, Resources, Deploy, Metrics, Activity, Access, and Settings. The 'Resources' tab is active, showing 'Free Dynos' and an 'Upgrade to Hobby...' button. A notification for 'Web Dyno Autoscaling' is present, with 'Hide' and 'Learn More' buttons. At the bottom, a table lists the application's resources, showing a 'web' dyno running 'node index.js' with a toggle switch, a price of '\$0.00', and an edit icon.

HEROKU

Jump to Favorites, Apps, Pipelines, Spaces...

Personal > cmpe202-t3am-starbucks-webapp


GITHUB synle/cmpe202-t3am-starbucks-webapp master

Overview Resources Deploy Metrics Activity Access Settings



Free Dynos Upgrade to Hobby...

Web Dyno Autoscaling: Available now for Performance web dynos and Private Spaces. Hide Learn More

| | | | | |
|-----|---------------|--------------------------|--------|--|
| web | node index.js | <input type="checkbox"/> | \$0.00 | |
|-----|---------------|--------------------------|--------|--|


 **HEROKU**

Jump to Favorites, Apps, Pipelines, Spaces...



Info


Region

 United States

Stack

heroku-16


Framework

 Node.js

Slug Size

17.3 MiB of 500 MiB

GitHub Repo

 synle/cmpe202-t3am-starbucks-webapp

Heroku Git URL

`https://git.heroku.com/cmpe202-t3am-starbucks-webapp.git`

Config Vars

API_HOST is set in the config file which the front end app is used to communicate with the back end API

Config Vars



Config Vars

Hide Config Vars

Config vars change the way your app behaves. In addition to creating your own, some add-ons come with their own.

API_HOST

https://cmpe202-java



KEY

VALUE

Add

Database Schema

sb_user

This is where we store users' information

Schema

▼ public.sb_user

▼ Columns

☐ user_id

CHARACTER VARYING

☐ email

CHARACTER VARYING

☐ full_name

CHARACTER VARYING

☐ password

CHARACTER VARYING


☐ balance

NUMERIC

☐ date_added

BIGINT

Results



A screenshot of a query results viewer showing three rows of data from the sb_user table. The table has six columns: user_id, email, full_name, password, balance, and date_added. The data is displayed in a table with a light blue header and alternating light blue and white rows. The first row shows a user with email syle@gmail.com, full name Sy Le, password password, balance 0, and date_added 1531952274019. The second row shows a user with email syle1@gmail.com, full name Sy Le, password password, balance 0, and date_added 1531959952188. The third row shows a user with email syle2@gmail.com, full name Sy Le2, password password, balance 0, and date_added 1532036670245. A mouse cursor is visible over the balance column of the third row.

| user_id | email | full_name | password | balance | date_added |
|-------------------|-----------------|-----------|----------|---------|---------------|
| 958bbc20-cda2-... | syle@gmail.com | Sy Le | password | 0 | 1531952274019 |
| feab2bad-d5dd-4.. | syle1@gmail.com | Sy Le | password | 0 | 1531959952188 |
| e4c226eb-2168-... | syle2@gmail.com | Sy Le2 | password | 0 | 1532036670245 |

sb_card

This is where we store previous reloaded card. This has a user_id foreign key that relates records to users

Schema

▼ public.sb_card

▼ Columns

| | |
|------------|-------------------|
| card_id | BIGINT |
| uid | CHARACTER VARYING |
| number | CHARACTER VARYING |
| code | CHARACTER VARYING |
| balance | NUMERIC |
| date_added | BIGINT |

Results

Rows 5

CSV JSON CSV JSON

| card_id | uid | number | code | balance | date_added |
|---------|-------------------|-----------|------|---------|---------------|
| 4 | 958bbc20-cda2-... | 111111111 | 111 | 10 | 1531952457886 |
| 5 | 958bbc20-cda2-... | 222222222 | 222 | 20 | 1531952473593 |
| 6 | feab2bad-d5dd-4.. | 123456789 | 123 | 100 | 0 |
| 7 | 958bbc20-cda2-... | 333333333 | 333 | 30 | 1532036464962 |
| 8 | 958bbc20-cda2-... | 444444444 | 444 | 40 | 1532049960445 |

sb_purchase

This is where we stores previous purchases. This has a user_id foreign key that relates records to users

Schema

public.sb_purchase

Columns

purchase_id

BIGINT

uid

CHARACTER VARYING

balance

NUMERIC

date_added

BIGINT

note

CHARACTER VARYING

Results

Rows 7

CSVJSONCSVJSON

| purchase_id | uid | balance | date_added | note |
|-------------|-------------------|---------|---------------|---------------|
| 1 | 958bbc20-cda2-... | 3 | 1531952793526 | Iced Coffee |
| 2 | 958bbc20-cda2-... | 3 | 1531952794984 | Iced Coffee |
| 3 | 958bbc20-cda2-... | 3 | 1531952798744 | Iced Coffee |
| 4 | 958bbc20-cda2-... | 4 | 1531952994579 | Frap |
| 5 | 958bbc20-cda2-... | 5 | 1531954158600 | Chai |
| 6 | 958bbc20-cda2-... | 6 | 1532036491432 | Thai Tea |
| 7 | feab2bad-d5dd-4.. | 30 | 1532037687755 | Meal Combo #1 |

API Spec

Sign up (Create User)

This API is used for NEW users to sign up for new account.

Curl Sample

```
curl -X POST \  
  http://localhost:8202/api/v1/signup \  
  -H 'accept: application/json' \  
  -d '{  
    "email": "syle1@gmail.com",  
    "full_name": "Sy Le",  
    "password": "password"  
  }'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/UserProfile.java>

Sign in (Log in)

This API is used for EXISTING users to sign in with their old account.

Curl Sample

```
curl -X POST \  
  http://localhost:8202/api/v1/signin \  
  -H 'accept: application/json' \  
  -d '{
```

```
"email": "syle1@gmail.com",  
"password": "password"  
}'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/UserProfile.java>

Get Cards Reload by UserId

This API is used to get a list of cards reloaded by userId

Curl Sample

```
curl -X GET \  
  'http://localhost:8202/api/v1/cards?uid=2c60158e-d432-4b78-a300-360cc6fa7260'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/Card.java>

Reload Card by UserId

This API is used to add/reload a card for a user by UserId

Curl Sample

```
curl 'http://localhost:8080/api/v1/reload' \8081/no-referrer' \  
  -H 'Connection: keep-alive' \  
  -H 'DNT: 1' --data-binary \  
'{"uid":"958bbc20-cda2-4f57-9fe6-e1ecb6e6e913","number":"111111111","code":"111","balance":"10"}'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/Card.java>

Get Purchases by UserId

This API is used to get a list of previous purchases by UserID

Curl Sample

```
curl -X GET \  
  'http://localhost:8202/api/v1/purchases?uid=2c60158e-d432-4b78-a300-360cc6fa7260'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/Purchase.java>

Add Purchase by UserId

This API is used to add a purchase by UserID


Curl Sample


```
curl 'http://localhost:8080/api/v1/purchase' \  
  -H 'Content-Type: application/json; charset=utf-8' \  
  -H 'DNT: 1' --data-binary '{"uid":"958bbc20-cda2-4f57-9fe6-e1ecb6e6e913","balance":"3","note":"Iced Coffee"}'
```

Response

<https://github.com/nguyensjsu/su18-202-t3am/blob/master/starbucks2-domain/src/main/java/model/Purchase.java>


Class Design UML Diagrams






State Diagrams


Sign In / Sign Up



Add Card



Add Purchase



Unit Testings

Java Unit Tests

Helper package JUnit

```
-----  
T E S T S  
-----  
Running helper.JSONHelperTest  
Tests run: 3, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 0.246 sec  
Results :  
Tests run: 3, Failures: 0, Errors: 0, Skipped: 0  
[INFO]
```

Model Package JUnit

```
-----  
T E S T S  
-----  
Results :  
Tests run: 0, Failures: 0, Errors: 0, Skipped: 0
```

Python End-To-End Tests

Workflow:

1. Run “mvn build” to build the JAR
2. Run the JAR, and start the backend server listening to localhost:8202
3. Run python test “api_tests” which send REST API requests to the localhost server
4. Verify that responses and fields match the expected results

```
python -m unittest api_tests  
...  
-----  
Ran 3 tests in 0.249s  
  
OK  
dock2 ~/wses/su18-202-t3am/jenkins/tests$ █
```

Each Jenkins Job runs the python end-to-end tests. A screenshot of a successful run is shown below:


```
python-requests/2.6.0 CPython/2.7.5 Linux/3.10.0-862.3.2.el7.x86_64 -  
.  
-----  
Ran 3 tests in 0.635s  
  
OK  
make[2]: Leaving directory `/var/lib/jenkins/workspace/API Testing/su18-202-  
t3am/jenkins/tests'  
make[1]: Leaving directory `/var/lib/jenkins/workspace/API Testing/su18-202-t3am/jenkins'  
+ set +x  
sed -i "s/value=\"_your_db_password\"/value=\"****\"/g" starbucks2-  
domain/src/main/java/sql-maps-config.xml  
++ ps -ef  
++ grep 'java.*jar'  
++ grep -v grep  
++ grep Rest  
++ awk '{print $2}'  
+ kill -9 3706  
make: *** [run] Killed  
Finished: SUCCESS
```